Authors: Yi Yang ^{a, b}, John E. Dec ^b, Magnus Sjöberg ^b, and Chunsheng, Ji ^b

Affiliation: ^a Department of Mechanical Engineering, University of Melbourne, Parkville, Victoria, 3010, Australia

^b Combustion Research Facility, Sandia National Laboratories, Livermore, California, 94551, USA

Corresponding Author: Yi Yang

Mailing address: Department of Mechanical Engineering, University of Melbourne, Parkville, Victoria, 3010, Australia

Telephone: (+61) 3 8344 8104

Email: yi.yang@unimelb.edu.au

Abstract

Modern spark-ignition (SI) engine technologies have considerably changed in-cylinder conditions under which fuel autoignition and engine knock take place. In this paper, fundamental HCCI engine experiments are proposed as a means for characterizing the impact of these technologies on the knock propensity of different fuels. In particular, the impacts of turbocharging, direct injection (DI), and downspeeding on operation with ethanol and gasoline are investigated to demonstrate this approach. Results reported earlier for ethanol and gasoline on HCCI combustion are revisited with the new perspective of how their autoignition characteristics fit into the anti-knock requirement in modern SI engines. For example, the weak sensitivity to pressure boost demonstrated by ethanol in HCCI autoignition can be used to explain the strong knock resistance of ethanol fuels for turbocharged SI engines. Further, ethanol's high sensitivity to charge temperature makes charge cooling, which can be produced by fuel vaporization via direct injection or by piston expansion via spark-timing retard, very effective for inhibiting knock. On the other hand, gasoline autoignition shows a higher sensitivity to pressure, so only very low pressure boost can be applied before knock occurs. Gasoline also demonstrates low temperature sensitivity, so it is unable to make as effective use of the charge cooling produced by fuel vaporization or spark retard. These arguments comprehensively explain literature results on ethanol's substantially better anti-knock performance over gasoline in modern turbocharged DISI engines. Fundamental HCCI experiments such as these can thus be used as a diagnostic and predictive tool for knock-limited SI engine performance for various fuels. Examples are presented where HCCI experiments are used to identify biofuel compounds with good potential for modern SI-engine applications.

Keywords: Knock propensity, HCCI, turbocharging, DISI, ethanol

Introduction

The increasing use of alternative fuels, including alcohols and those derived from non-conventional oil sources (e.g., oil sands), is considerably changing the fuel chemical composition for spark ignition (SI) engines [1, 2]. Understanding the knock limit of these fuels is essential for engine design and operation. Meanwhile, the in-cylinder conditions under which knock occurs have also changed significantly with the adoption of modern engine technologies. Both of these changes considerably affect anti-knock performance of gasoline fuels in SI engine combustion, since the end-gas autoignition is controlled by chemical kinetics that depend on both in-cylinder thermodynamic conditions and fuel composition.

Conventionally, octane numbers (ON) are used to quantify fuel knock propensity. Standard octane tests are conducted in Cooperative Fuel Research (CFR) engines at naturally aspirated conditions with the fuel supplied by a carburettor. Such conditions are considerably different from those in modern SI engines which often operate outside the conditions used to determine the research and motor octane numbers (RON and MON) [3, 4]. For example, the K-factor in the Octane Index model, $OI = RON - K(RON - MON)$, is 0 in the RON test and 1 in the MON test; however, K is often found to be negative in turbocharged DISI engines¹ and varies significantly with operating conditions [3-5]. Applying octane numbers to modern SI engines therefore requires extrapolating the conventional octane numbers in order to predict the fuel's anti-knock performance. The applicability of such extrapolation is open to question.

Adoption of modern engine technologies, e.g., turbocharging and direct fuel injection, produces higher pressures and lower temperatures inside the cylinder. Through engine downspeeding (for reducing friction losses), more time is allowed for autoignition to occur. These changes have a mixed impact on SI engine knock and induce different responses among fuels in their anti-knock performance. For example, ethanol has higher RON and MON than gasoline and also shows better anti-knock performance compared to gasoline for operation without boost and with port fuel injection. For operation with turbocharging and direct fuel injection, the improvement of anti-knock quality with ethanol becomes markedly greater than that of gasoline [6]. Such differences have been attributed partly to the

¹ Negative K values correspond to higher in-cylinder pressure than in the RON test at comparable cylinder temperatures [20]

larger vaporization cooling effect that ethanol produces from DI fuelling, but more importantly, to the stronger knock resistance of ethanol's autoignition chemistry [6, 7]. However, the role of autoignition chemistry has not been systematically studied across fuels, in particular, data for autoignition experiments in engine environment are lacking.

The objective of this paper is to propose that fundamental HCCI (homogeneous charge compression ignition) engine experiments can be used to characterize autoignition properties of different fuels, and these autoignition properties can then be used to predict fuels relative knock propensity in SI engines adopting modern technologies. In particular, the impacts of three SI engine technologies, turbocharging, direct injection, and downspeeding, on the anti-knock performance of different fuels have been investigated. HCCI experiments for ethanol and gasoline reported in previous publications by the current authors are revisited and used to explain the remarkable anti-knock performance of ethanol reported in the literature [6], which confirms the validity and utility of the proposed method.

Methodology

The concept of using HCCI engine combustion to study SI engine knock is based on the understanding that the two processes are controlled by the same process, namely autoignition. Normal SI engine knock results from the combined effects of turbulent deflagration and piston motion on the rise of the in-cylinder pressure, with an associated temperature rise of the unburned gas, leading to hot autoignition. During the compression, heat transfer from the flame to the end gas, whose autoignition initiates knock, is negligible because the first-autoignited gas pockets are usually located far away from the flame. Therefore, the process undergone by this part of end gas can be approximated by a homogeneous fuel/air mixture being compressed to hot ignition with a piston, essentially the process in an HCCI engine.

Given the differences in HCCI and SI engine operations (as discussed below), the proposed HCCI experiments are not intended to reproduce the exact end-gas autoignition that leads to SI engine knock. Rather, these HCCI experiments are used to quantify various fuels' autoignition sensitivities to changes in engine operating conditions. These

sensitivities, which can be regarded as fuel properties since they are rooted in the fuel autoignition chemistry, are then used to predict or explain the anti-knock quality of these fuels in SI engines for corresponding changes in operating conditions. Therefore, despite the different conditions inside the cylinder, autoignition in the two engines is sufficiently similar so that the impact of engine operating parameters on one process (e.g., HCCI autoignition) can be reasonably extended to understand their impact on the other (e.g., SI knock). It should be noted that by using this method, detailed features of SI engine combustion, such as turbulent flame propagation rates and temperature inhomogeneities in the unburned gas, are not considered explicitly. Rather, their impact on the autoignition process is lumped into other parameters, e.g. in-cylinder pressure and temperature, in the HCCI engine tests. This is similar to the way measurements in an octane test engine are used to predict fuel performance in production engines even though turbulent flame speeds and temperature inhomogeneities are very different between these engines, owing to substantial differences in their design.

Being controlled by chemical kinetics, autoignition depends on the engine operating parameters that affect reaction rates, i.e., temperature, pressure, equivalence ratio, engine speed (affecting available time), etc. It is noted that a major difference exists between HCCI and SI engines in terms of the amount of charge dilution. To prevent knock, HCCI engines usually operate with considerably diluted mixtures, using excess air or EGR. With air dilution, fuel-air equivalence ratios (ϕ) are typically substantially lower (maximum $\phi \sim 0.55$) than in SI engines ($\phi \sim 1.0$), or EGR may be used to substitute the excess air so that ϕ approaches 1.0, but the total dilution is essentially the same as with air dilution (i.e. the same fuel/(air + EGR) mass-ratio). For simplicity, the following discussion is given in terms of air dilution, but an equivalent amount of EGR dilution could also be used. For the method proposed here, a question that needs to be addressed is whether the results obtained at low equivalence ratios (HCCI experiment) are relevant for explaining or predicting knock in stoichiometric SI engines. To investigate this, the CHEMKIN [8] software was used to examine ignition delays of isooctane and ethanol in air in a constant-volume reactor using mechanisms from Lawrence-Livermore National Laboratory [9, 10]. As shown in Fig. 1, ignition delays of both fuels are somewhat shorter at the stoichiometric condition compared to the lean condition. However, comparing the two fuels, the relative trends of ignition delay vs. reciprocal of temperature (τ_{ig} vs. $1/T$) and ignition delay vs. pressure are nearly the same at $\phi = 0.5$ (left plots) and $\phi = 1.0$ (right plots). These modelling results indicate that the relative difference

with changes in operating conditions between different fuels can be validly extended from lean (dilute) HCCI combustion to stoichiometric SI knock.²

Fig. 1

Similar to the computational results in Fig. 1, it can be expected that for a given fuel, autoignition in a lean HCCI experiment would require somewhat higher temperatures and/or pressures than the end-gas autoignition in a stoichiometric SI engine. However, as mentioned above, the objective is to predict trends with changes in operating conditions and the relative performance of different fuels, not to match exact values. By sweeping temperatures and pressures over a wide range in the proposed HCCI experiments, they are used to determine the fuel's autoignition sensitivity to variations in temperature and pressure, rather than to determine autoignition at specific fixed conditions. In other words, the interpretation of the HCCI data is focused on $\Delta\tau$ vs. ΔT , rather than τ vs. T at specific conditions.³

This proposed method offers some unique advantages over the standard engine experiments used for characterizing fuel knock properties. Compared to the standard octane number tests, where RON and MON correspond to only two operation conditions, this method allows investigation of the autoignition propensity over a range of operating conditions typical of those encountered by modern SI engines. This can be accomplished by independently controlling the temperature, pressure, fuel preparation, engine speed etc. of the HCCI test engine. Compared to the knock-limited SI engine experiments, e.g., in [6], this method avoids engine-damaging knock and removes the complexity of turbulent flame propagation, while preserving the reciprocating nature and timescales of engine combustion. Indeed, the HCCI combustion process can be considered as being similar to rapid compression machine

² It is noted that differences between the two fuels are somewhat larger at $\phi = 1.0$ than at 0.5, but this effect is secondary compared to the overall similarity at the two equivalence ratios.

³ It should be noted, however, that actual temperature and pressure conditions for autoignition are in the same range for both engines. For example, during the gasoline intake pressure sweep ($P_{in} = 1.0$ to 1.6 bar), to be reported later in Fig. 2, the cylinder pressure at the autoignition timing (crank angle for 10% burn point, or CA10) varied from 29.9 to 50.6 bar, and the gas temperature varied from 1033 to 1012 K. In comparison, the in-cylinder conditions at the knock onset in the standard RON test for PRF91 (the same RON as the gasoline in the HCCI experiment reported here) are 37.8 bar and 998 K (for unburned gas) [11].

experiments running in a continuous manner under realistic boundary conditions for engines. Compared to the K-factor in the Octane Index model [3,4], which must be determined for specific engines and specific operating conditions, results from the HCCI-engine experiments provide a more general understanding of the autoignition problem and the factors affecting the knock propensity. As an initial study to establish the conceptual link between HCCI and SI combustion, this work is not intended to propose a numerical scale for ranking fuel autoignition reactivity. Such practice has been conducted in [12-14] where correlations for evaluating HCCI performance were proposed using the fuel chemical composition and defined engine operating conditions. These studies, however, largely focused on combustion in HCCI engines and the link to SI engine knock was not explored. The present work thus focuses on bridging these two types of engine combustion and aims to establish a theoretical basis for further development of this method of evaluating fuel performance.

Experiment

Engine setup

The engine used for these HCCI experiments was derived from a Cummins B-series diesel engine which has been converted for single-cylinder HCCI operation. The displacement is 0.98 L/cylinder. The active HCCI cylinder is fitted with a custom piston with an open combustion chamber that gives a geometric compression ratio of 14:1. Air is supplied by a compressor and metered with sonic nozzles to produce the desired intake pressures (P_{in}). A fully premixed charge is used for all cases reported here by using a fuel vaporizer and mixing system upstream of the intake plenum. Electrical heaters are used to maintain the desired intake temperature (T_{in}). The engine speed is 1200 rpm for all cases except for studying the effects of downspeeding. Details of the engine, fuelling system, combustion-chamber geometry, experimental setup, data acquisition, and method for heat release calculations can be found in [15].

Test conditions

The HCCI experiments are designed to provide an understanding of the individual impacts of turbocharging, direct injection, and downspeeding on the knock propensity of neat ethanol and a reference gasoline. To simulate the impacts of these technologies on in-cylinder conditions, three parameters are swept as listed below.

1. intake pressure sweep for the effect of turbocharging;
2. intake temperature sweep for the effect of charge cooling by DI fuelling;
3. engine speed sweep for the effect of downspeeding.

Knock propensity in this study is measured by two types of indicators. (1) Autoignition timing, which is used for cases where one of the above three parameters is swept and the other two parameters are kept constant. More advanced autoignition timing indicates higher knock propensity. (2) Adjustment of one parameter, such as intake temperature, to maintain a constant autoignition timing while another parameter is swept over the range of interest. For these cases, a lower required T_{in} indicates a higher autoignition reactivity and hence, a higher knock propensity for the fuel. Operating conditions for each sweep are reported along with the results below.

The properties of ethanol and gasoline used in the HCCI experiments are listed in Table 1. The gasoline is a reference grade gasoline from Chevron-Phillips with a tightly controlled hydrocarbon composition. Also shown is the baseline gasoline used for ethanol blending in the knock-limited SI engine experiment by Stein et al. [6]. Properties of this gasoline were reported in [16].

Table 1

Most HCCI data reported here have been published in several previous papers by the current authors [15, 17-19]. These previous studies primarily focused on the use of these fuels for HCCI-engine operation and did not discuss their anti-knock properties for SI engine combustion, which is the topic of the present work.

Results and Discussion

Impact of turbocharging (intake pressure sweep)

Turbocharging increases the intake pressure, and the pressures after compression and in the end-gas, which generally enhances the propensity of the fuel to autoignite. However, it is known that different fuels respond to pressure variations in different manners [20]. Figure 2 shows the variation of the bottom dead center temperature

(T_{BDC}) required to maintain a constant crank angle of the 10% burn point (CA10) as P_{in} is increased for both ethanol and gasoline. T_{BDC} is used here essentially as a corrected intake temperature that accounts for heat-transfer during intake and mixing with residuals [21]. No EGR was used except for gasoline at intake pressure of 1.8 bar (23% EGR). For this case, EGR was used due to the intake temperature being reduced to the lowest temperature allowed in these fully premixed experiments, 60°C. In addition, the equivalence ratio for this case was determined using fuel/charge mass ratio as $\phi_m = \frac{(F/C)}{(F/A)_{stoich}}$ [15], which was maintained at 0.38 like the other data points with air dilution.

It can be seen that for both ethanol and gasoline, increasing P_{in} reduces the T_{BDC} requirement, indicating that autoignition is enhanced, i.e., a higher knock propensity. However, for a given increase in P_{in} , e.g., from 1.0 to 1.6 bar, the temperature reduction with ethanol (~20°C) is much smaller than that of gasoline (~35°C). This difference indicates that the propensity for knock increases to a much smaller degree for ethanol than for gasoline. For SI engine applications, this result indicates that ethanol will be much more knock resistant than gasoline when turbocharging is used, and its advantage over gasoline becomes greater as boost pressure increases.

Fig. 2

To better understand the difference in the effect of pressure for ethanol and gasoline, heat release rates prior to the hot ignition have been analysed, as shown in Fig. 3. These data are from the same sweeps as in Fig. 2. In the plots in Fig. 3, the pre-ignition heat release rates have been highly amplified so their magnitude, which is indicative of the fuel autoignition reactivity, can be readily compared. Note that since ϕ is kept constant as P_{in} increases, these heat release rates have been normalized by the total heat release to remove differences due to variations in the total fuel energy supplied.

For ethanol, the normalized pre-ignition heat release rates remain nearly constant over $P_{in} = 1.0 - 1.8$ bar (Fig. 3a), suggesting that the pressure does not enhance the actual autoignition reaction rate of individual ethanol molecules. In other words, for the global reaction rate of ethanol autoignition, $k[Fuel]^m[O_2]^n$, if we assume that m and n are

both ~ 1 [22], the pressure only increases the fuel and oxygen concentration terms and does not increase the rate constant k . Thus, the relatively small T_{BDC} reduction with increased P_{in} , as observed for ethanol in Fig. 2, is possibly a result of only needing to compensate for the higher reactant concentration inside the cylinder, not due to an induction of new reaction pathways. In contrast, the normalized pre-ignition heat release rates of gasoline are significantly promoted by the increased pressure (Fig. 3b), indicating that the reaction rate per gasoline molecule, or the rate constant k , is increased by intake-pressure boost, in addition to the increased fuel and oxygen concentrations. This behaviour is consistent with the increased importance of low- and intermediate-temperature reaction pathways for combinations of higher pressures and lower temperatures for hydrocarbon fuels [23]. With this additional pressure-induced heat-release rate, the temperature required by gasoline for autoignition drops faster than ethanol, as observed in Fig. 2. The changes of pre-ignition heat-release rates with pressure in Fig. 3 well explain the trends of P_{in} vs. T_{BDC} in Fig. 2, and support the argument that turbocharging enhances the knock propensity of gasoline to a much greater extent than it does for ethanol.

Fig. 3

Impact of direct injection (intake temperature sweep)

The benefit of direct injection for knock suppression is generally realized by using early DI fuelling (during the intake stroke), so that vaporization of the DI fuel cools the charge, reducing the overall in-cylinder temperature, and thus inhibiting end-gas autoignition.

Ethanol is known to have a considerably larger charge cooling capacity than conventional hydrocarbon-based fuels, due to its higher heat of vaporization and larger fuel mass for a given equivalence ratio [17, 24]. This increases the potential for knock reduction with ethanol compared to gasoline. However, an important factor that is often ignored is the sensitivity of the fuel's autoignition chemistry to the charge cooling, i.e., dependence of autoignition reaction rates on the charge temperature, which can vary significantly among fuels (as shown below). In other words, charge cooling will strongly inhibit knock only if the fuel's autoignition is sufficiently sensitive to the reduced temperature.

The temperature effect on the knock propensity of gasoline and ethanol is shown in Fig. 4, where the dependence of CA10 on T_{in} is shown for naturally aspirated condition ($P_{in} = 1.0$ bar). Note that for these HCCI data, the fuel has been evaporated in an electrically heated vaporizing chamber and then fully mixed with air before entering the engine. Therefore, fuel vaporization cooling is not a factor here, and the impact of intake temperature on the autoignition reactions, and thus knock propensity, can be isolated. It can be seen from Fig. 4 that for both gasoline and ethanol, reducing the intake temperature slows the autoignition kinetics, thus more time is required to reach hot ignition, which results in later CA10s. The slope of these curves is the key feature here, and it indicates the sensitivity of the fuel's autoignition to changes in temperature. Comparing the two fuels, ethanol shows stronger temperature sensitivity, since for a given T_{in} reduction, ethanol's CA10 is retarded more than that of gasoline. This suggests that for the same amount of charge cooling, the autoignition rate will be slowed more for ethanol, i.e., knock will be less likely to occur with ethanol. Thus, not only does ethanol have stronger vaporization cooling with DI fuelling, but a given amount of cooling has a greater effect on reducing the autoignition rate. The combination of the two effects results in a much greater reduction in the knock propensity than for DI fueling with gasoline. In short, there is more vaporization cooling and that cooling is more effective with ethanol.

Fig. 4

The strong temperature sensitivity of ethanol not only better utilizes the charge cooling produced from DI fuel vaporization, it also makes the charge cooling from piston expansion more effective for inhibiting knock. The latter is particularly important because SI engines commonly use spark-timing retard to shift the combustion farther into the expansion stroke to control knock.

Impact of turbocharging + direct injection

The temperature sensitivity analysis discussed above is for naturally aspirated conditions ($P_{in} = 1.0$ bar). When turbocharging is used, the temperature sensitivity may change, and thus the DI effect on knock propensity could be different.

As seen in Figs. 2 and 3, autoignition of ethanol and gasoline show different dependences on pressure. The pre-ignition heat release rates, an indication of fuel autoignition reactivity, are significantly promoted for gasoline but remain essentially constant for ethanol when pressure increases (Fig. 3). As the reactivity increases at higher pressures, gasoline autoignition tends to become less sensitive to the DI-induced temperature reduction inside the cylinder. This occurs because the lower temperatures increase the amount of heat release from the low- and intermediate-temperature reactions, which counteracts the effect of the temperature reduction [25]. Figure 5 confirms this, showing that the temperature sensitivity of gasoline is considerably reduced at $P_{in} = 2.4$ bar, where a given change in T_{in} produces a much smaller change in CA10 at $P_{in} = 2.4$ bar than at $P_{in} = 1.0$ bar. As a result, the charge cooling produced by fuel vaporization or piston expansion becomes less effective for knock control with gasoline for turbocharged conditions. On the other hand, for ethanol, the autoignition reactivity is hardly affected by pressure, as evident from Fig. 3a. Thus, ethanol's strong sensitivity to temperature (i.e., charge cooling) is largely preserved, as shown in Fig. 5 where a small T_{in} drop produces a large CA10 retard. In summary, the autoignition reactivity of ethanol remains low under boosted conditions, and it can be further reduced by charge cooling (via DI fueling and spark retard), while gasoline autoignition reactivity is enhanced by boost and charge cooling are much less effective at reducing its reactivity. As a result, the difference in the knock propensity of ethanol and gasoline becomes much greater at boosted intake pressures compared to naturally aspirated conditions, as evident from the SI engine experiments discussed below.

Fig. 5

Understanding literature data on knock-limited SI engine performance with turbocharging and DI

The insights gained from the above fundamental HCCI experiments can be applied to understand the anti-knock performance of ethanol/gasoline blends in a modern SI engine, as reported by Stein et al. [6]. Using direct injection and simulated turbocharging (with an air compressor), Stein et al. reported SI engine performance in terms of knock-limited net mean effective pressure (NMEP) for a wide range of fuel blends and intake pressures.

An example of their results comparing the performance of E50 (gasoline:ethanol = 50:50 by volume) and neat gasoline (E0) are shown in Fig. 6. These two fuels are not the same as the ones used in the HCCI experiments: the gasoline is somewhat more reactive (RON = 88, vs. 91 in the HCCI experiments), and the ethanol is blended with the gasoline rather than being neat ethanol. Nevertheless, ethanol should be responsible for the differences observed between E0 and E50. Additionally, Anderson et al. [16] have shown in a companion paper that a blend of 50% ethanol with a RON = 88 gasoline gives more than three-fourths of the RON increase that would occur for switching from this gasoline to neat ethanol, which suggests that its autoignition reactivity should shift by a similar amount. Therefore, the general trends obtained from the HCCI experiments with neat ethanol and the RON = 91 gasoline, regarding the effects of variations in cylinder pressure and temperature on the knock propensities of the fuels, should still be fully applicable to the reasoning in this paper.

Two different fuelling methods were used by Stein et al., early DI and a so-called upstream fuel injection (UFI) in which fuel is injected well upstream of the intake port. The temperature at the intake port is fixed at 52°C for all the tests. Therefore, with UFI, fuel vaporization is completed upstream of the intake port, which is essentially the same as in the HCCI experiments with fully premixed fueling. The engine speed is fixed at 1500 rpm for the data reported here, and a stoichiometric charge is used, except for the data point at the highest load point of E50-DI (where enrichment is used to suppress knock to allow a higher NMEP). The load (NMEP) is determined by intake pressure, as indicated in the inset in Fig. 6. Spark-timing retard is used to retard the 50% burn point (CA50), thereby controlling knock. In all cases, the combustion occurs with knock-limited spark advance.

Fig. 6

Retarding the combustion timing after TDC utilizes the charge cooling from piston expansion to slow the autoignition kinetics and prevent knock. Similar to the case of DI charge cooling, the effectiveness of piston-expansion cooling for knock control depends on the sensitivity of the fuel's autoignition to the temperature drop. The "E0, UFI" case in Fig. 6 shows that for neat gasoline, a large CA50 retard only allows a marginal increase of NMEP, indicating that the expansion cooling is not very effective for controlling knock as the intake pressure is increased with load. This can be

explained by the weaker temperature-sensitivity of gasoline autoignition discussed above (Fig. 4) in combination with its higher pressure sensitivity (Fig. 2). For the same reason, the charge cooling produced by DI fuel vaporization is not very effective for inhibiting knock as can be seen by a comparison of the “E0-UFI” and “E0-DI” data. The NMEP of gasoline therefore appears to be self-constrained due to the strong pressure sensitivity and weak temperature sensitivity of its autoignition.

On the other hand, adding ethanol into gasoline substantially changes the trends. With 50% ethanol, E50 should possess ~50% of the charge-cooling capacity of pure ethanol, and its autoignition reactivity should be approaching that of ethanol, as discussed above for the RON change [16]. For a pre-vaporized fuel/air mixture, comparison of the “E0-UFI” and “E50-UFI” cases shows that the maximum NMEP increases from 7 bar to 27 bar using pressure boost and spark retard with addition of 50% ethanol to the fuel. This large increase in load is possible because of the combined weak pressure sensitivity (see Figs. 2 and 3) and strong temperature sensitivity of ethanol autoignition (see Figs. 4 and 5). The weak pressure sensitivity allows high boost for higher load before the onset of knock, and the strong temperature sensitivity even under boosted conditions makes the autoignition very sensitive to the piston-expansion cooling, so CA50 retard is very effective for controlling knock.

For DI fueling, the load with E0 only increases by about 1 bar NMEP (E0-UFI vs. E0-DI), but for E50, the strong vaporization cooling from ethanol coupled with the high temperature sensitivity (which is not much affected by pressure boost as shown in Fig. 5) greatly improves the anti-knock performance, allowing the maximum load to be increased from 27 to 41 bar.

In summary, the observed DISI engine performance can be well explained by the autoignition characteristics revealed by HCCI experiments. The data in Fig. 6 demonstrate that the weak pressure sensitivity and strong temperature sensitivity of ethanol autoignition provides ideal anti-knock properties that can be exploited in turbocharged DISI engines using spark timing for knock control.

Impact of downspeeding (speed sweep)

Another important engine operating parameter affecting knock is the engine speed, which determines the time available for the end-gas to undergo the autoignition reactions. Lower engine speeds typically produce a higher knock propensity, which represents a challenge for the current trend of engine downspeeding.

Autoignition sensitivity to changes of engine speed is fuel dependent, just as its sensitivity to changes of pressure and temperature discussed above. Figure 7 shows results from HCCI experiments at $P_{in} = 1.0$ bar where the engine speed is plotted against the intake temperature required to maintain a fixed CA50 [17]. For both ethanol and gasoline, the required intake temperature drops as engine speed decreases for speeds < 1200 rpm, indicating higher knock propensity at lower speeds, which is consistent with SI engine observations. Gasoline shows a much steeper T_{in} drop than ethanol at these speeds, primarily because of the onset of low-temperature heat release (LTHR) [17], which substantially reduces the temperature required for autoignition. The T_{in} drop with ethanol is much smaller because no LTHR occurs even at very low speeds. Therefore, the anti-knock performance of ethanol remains high at these low speeds, which is desired for SI engine downspeeding.

Figure 7 also shows some trends that are consistent with the octane numbers of the two fuels. As shown in Table 1, gasoline has RON = 91 and MON = 83, and ethanol has RON = 109 and MON = 90. It is noted that the RON difference between the two fuels is much larger than their MON difference (18 vs. 7). This is consistent with the T_{in} difference between ethanol and gasoline at the speeds where these ONs are measured. At 600 rpm (for RON), the T_{in} difference is much larger than that at 900 rpm (for MON), indicating much larger anti-knock difference at lower speeds than at higher speeds. Similar arguments have been presented in [17]. Note that unlike the RON test where the fuel vaporization cooling and autoignition chemistry both contribute to the anti-knock performance⁴, the HCCI experiments are conducted with pre-vaporized fuel; thus, the T_{in} difference in Fig. 7 essentially reflects the difference in the autoignition reactivity of ethanol and gasoline at 600 rpm.

⁴ The intake port temperature of the RON test is affected by fuel vaporization cooling because a constant temperature is maintained upstream of the carburettor, independently of the fuel being tested.

At the speeds > 1200 rpm, the T_{in} of both fuels become much less sensitive to the engine speed for naturally aspirated operation, because more pumping work is required to induct the charge in a shorter amount of time, which causes a stronger dynamic heating effect [21]. This effect raises the temperature of the charge mixture by an amount that increases with engine speed. Also, higher engine speeds allow less time for heat transfer. As a result of these two effects, less external heating is required, and the required T_{in} actually drops slightly for speeds greater than about 1500 rpm, even though the charge temperature prior to autoignition must continue to increase with engine speed to maintain the same CA50, as indicated by the T_{BDC} curve in Fig. 7. Compared to gasoline, ethanol appears more sensitive to the increase in dynamic heating with speed, since its T_{in} curve shows a greater (though still small) decrease with engine speed than gasoline. This is consistent with the stronger temperature sensitivity of ethanol as observed in Fig. 4.

Compared to gasoline, ethanol is more knock resistant at low engine speeds due to the lack of active low-temperature autoignition chemistry, but could be more knock prone at high speeds due to its high sensitivity to the increase in wall temperature and dynamic heating. This argument is supported by the T_{in} crossover in Fig. 7, which suggests that ethanol could become more knock-prone than gasoline as speed increases in naturally aspirated SI engines. This would be an important anti-knock property and is not revealed directly by RON and MON measurements.

Application to other biofuels

This method of using HCCI experiments to explain fuel anti-knock properties in SI engines can be applied to other fuels. In particular, HCCI experiments could be used to elucidate fundamental autoignition characteristics of next-generation biofuels that are intended for SI engine applications. Figure 8 shows results for two oxygenated fuels, isopentanol [18] and cyclopentanone [15], which are potential components for advanced biofuels. Data for gasoline and ethanol are included as well. The results indicate that for isopentanol, changes in anti-knock properties with operating conditions are similar to gasoline, since its autoignition shows very similar sensitivities to temperature, pressure, and speed. However, isopentanol may be slightly more knock prone than gasoline at all conditions since its T_{in} requirement is about $10 - 15^{\circ}\text{C}$ less. Cyclopentanone, on the other hand, behaves similarly to ethanol, but may

have even better anti-knock properties, as indicated by its stronger temperature sensitivity, weaker pressure sensitivity, and significantly higher T_{in} requirement compared to ethanol at a given speed. These properties suggest that for knock-limited combustion in a turbocharged DISI engine, isopentanol's performance would be generally similar to gasoline, while cyclopentanone could perform even better than ethanol^{5, 6}. Such predictions obtained from fundamental HCCI experiments could be valuable for deciding which new biofuels and biofuel blends are most promising and to be selected for further performance testing in modern SI engines. As such, HCCI tests like these reported here complement well RON and MON measurements for fuel-screening purposes, and provide fundamental understanding of new fuels' autoignition characteristics not easily obtained from typical SI engine testing.

Fig. 8

Conclusions

Fundamental HCCI engine experiments are proposed as means of characterizing the fuel anti-knock properties in modern SI engines where the combustion environment is being substantially changed by the use of advanced engine technologies. Autoignition reactivities, which are directly correlated with knock propensities, are studied as a function of in-cylinder temperatures, pressures, and engine speeds for ethanol and a conventional (ethanol-free) gasoline, in order to understand the impacts from using turbocharging, direct injection and downspeeding. The major conclusions are:

- The impact of turbocharging on knock propensity can be studied by conducting an intake-pressure sweep of HCCI combustion. With fixed combustion timing, the relationship between T_{BDC} and P_{in} indicates the pressure sensitivity of the fuel's autoignition. A lower pressure sensitivity, such as that of ethanol, indicates less enhancement in knock propensity by turbocharging.

⁵ It is noted that the heat of vaporization of cyclopentanone (509 kJ/kg) is significantly lower than that of ethanol (920 kJ/kg). This, plus the lower fuel fraction at a given equivalence ratio for cyclopentanone, would make fuel vaporization produce less charge cooling for cyclopentanone than for ethanol.

⁶ These reported fuel properties are for neat compounds. In practice, these or other new fuels would likely be used as blends with gasoline, which will affect performance characteristics, so tests should also be conducted on the blend mixtures of interest.

- The impact of vaporization cooling from direct injection, and end-gas cooling from spark-timing retard, on the knock propensity can be studied by conducting an intake-temperature sweep in HCCI combustion. With a fixed combustion timing, the relationship between CA10 and T_{in} indicates the temperature sensitivity for the fuel autoignition. A higher temperature sensitivity, e.g., that of ethanol, indicates that charge (or end-gas) cooling resulting from direct injection and/or spark retard, is more effective for reducing the knock propensity.
- The impact of downspeeding on knock propensity can be studied by conducting engine speed sweep of HCCI combustion. With fixed combustion timing, the relationship between T_{in} and RPM indicates the speed sensitivity of fuel autoignition. Lower speed sensitivity, e.g., that of ethanol at < 1200 rpm, indicates a lower knock propensity when the engine speed is reduced to this range.
- All considered, these fundamental HCCI experiments provide a comprehensive understanding of why different fuels respond differently to changes of operating conditions. In particular, they explain why ethanol is superior to gasoline for modern turbocharged DISI engines.
- Based on these HCCI experiments, two candidate biofuels, isopentanol and cyclopentanone were assessed regarding their anti-knock potential in SI engines. Cyclopentanone appears to be an attractive SI fuel that may provide high anti-knock performance that exceeds that of ethanol thanks to its very low pressure sensitivity and high temperature sensitivity.

Overall, this article shows that HCCI experiments can provide valuable insights to help explaining trends in SI-engine knock and for assessing the potential of new fuels. Moreover, fuel anti-knock properties characterized by this method cover a much wider range of operating conditions than the conventional octane numbers, and should be particularly relevant to modern turbocharged SI engines.

Acknowledgments

This work was performed at the Combustion Research Facility, Sandia National Laboratories, Livermore, CA. Support was provided by the U.S. Department of Energy, Office of Vehicle Technologies. Sandia National Laboratories is a multi-program laboratory managed and operated by Sandia Corporation, a wholly owned subsidiary of Lockheed

Martin Corporation, for the U.S. Department of Energy's National Nuclear Security Administration under contract DE-AC04-94AL85000. Yi Yang also thanks the Early Career Research Grant from the University of Melbourne for supporting the writing of this paper.

References

1. N. Berkowitz and J. Speight, *Fuel*, 1975. **54**(3) 138-149.
2. A. McIlroy and G. McRae, Basic Research Needs for Clean and Efficient Combustion of 21st Century Transportation Fuels, Report of the Basic Energy Sciences Workshop, Department of Energy, United States, 2005, 40.
3. G.T. Kalghatgi, SAE Paper No. 2001-01-3584, 2001.
4. G.T. Kalghatgi, SAE Paper No. 2001-01-3585, 2001.
5. V. Mittal and J. Heywood, SAE Paper No. 2008-01-2414, 2008.
6. R.A. Stein, D. Polovina, K. Roth, M. Foster, M. Lynskey, T. Whiting, J.E. Anderson, M.H. Shelby, T.G. Leone, and S. VanderGriend, SAE Paper No. 2012-01-1277, 2012.
7. E. Kasseris and J. Heywood, SAE Paper No. 2012-01-1284, 2012.
8. CHEMKIN-PRO 15131, Reaction Design: San Diego, 2013.
9. H.J. Curran, P. Gaffuri, W.J. Pitz, and C.K. Westbrook, *Combust. Flame*, 2002. **129**(3) 253-280.
10. N.M. Marinov, *Int. J. Chem. Kinet.*, 1999. **31** 183-220.
11. T.M. Foong, K.J. Morganti, M.J. Brear, G.d. Silva, Y. Yang, and F.L. Dryer, to be submitted.
12. V.H. Rapp, W.J. Cannella, J.Y. Chen, and R.W. Dibble, *Combust. Sci. Tech.*, 2013. **185**(5) 735-748.
13. G. Shibata and T. Urushihara, SAE Paper No. 2007-01-0220, 2007.
14. I. Truedsson, W. Cannella, B. Johansson, and M. Tuner, SAE Paper No. 2014-01-2667, 2014.
15. Y. Yang and J.E. Dec, SAE Paper No. 2013-01-2627, 2013.
16. J.E. Anderson, T.G. Leone, M.H. Shelby, T.J. Wallington, J.J. Bizub, M. Foster, M.G. Lynskey, and D. Polovina, SAE Paper No. 2012-01-1274, 2012.
17. M. Sjöberg and J.E. Dec, SAE Paper No. 2010-01-0338, 2010.
18. Y. Yang, J.E. Dec, N. Dronniou, and B.A. Simmons, SAE Paper No. 2010-01-2164, 2010.
19. J. Dec, Y. Yang, C. Ji, and J. Dernet, SAE Paper No. 2015-01-0813, 2015.
20. G.T. Kalghatgi, SAE Paper No. 2005-01-0239, 2005.
21. M. Sjöberg and J.E. Dec, SAE Paper No. 2004-01-1900, 2004.
22. Y. Yang, J.E. Dec, N. Dronniou, M. Sjöberg, and W. Cannella, SAE Paper No. 2011-01-1359, 2011.
23. E.J. Silke, W.J. Pitz, C.K. Westbrook, M. Sjöberg, and J.E. Dec, SAE Paper No. 2008-01-0019, 2008.
24. T. Foong, K. Morganti, M. Brear, G. da Silva, Y. Yang, F.L. Dryer, SAE Paper No. 2013-01-0886, 2013.
25. M. Sjöberg and J.E. Dec, *Proc. Combust. Inst.*, 2007. **31** 2895-2902.

Table 1 Properties of ethanol and gasoline used in HCCI experiments, and baseline gasoline for ethanol blends in SI engine experiment [6].

	Ethanol	Gasoline in HCCI test ^a	Gasoline in SI test ^b
Formula	C ₂ H ₆ O	C _{6.83} H _{13.7}	C _{6.75} H _{13.2}
Molecular Weight, g/mol	46.1	95.2	94.2
Boiling Point, °C	78.3	T ₁₀ = 59 T ₅₀ = 93 T ₉₀ = 145	NA
Density at 20°C, g/cm ³	0.7893	0.7460	0.727
Lower Heating Value (LHV), gas, MJ/kg	27.75	43.47	43.8
A/F stoichiometric (kg/kg)	9.00	14.8	14.6
Heat of Vaporization at 25°C, kJ/kg	920	308 ^c	350
ΔH _{vap, 25°C} for stoichiometric charge, kJ/kg	92.0	20.5	22.4
Research octane number (RON)	109	90.8	88.2
Motor octane number (MON)	90	83.2	81.7
Octane sensitivity (RON-MON)	19	7.6	6.5
Chemical Composition (vol%)			
normal paraffin	-	9.6	21.2
iso paraffin	-	42.7	42.4
naphthene	-	16.2	4.9
olefin	-	4.8	5.8
aromatics	-	26.7	25.7

^a Chevron-Phillips reference gasoline (RD-387)

^b Gasoline properties were reported in a separated study [16].

^c This value is for isooctane since the value for this gasoline is not available.

List of Figure Captions

Fig. 1 Ignition delay of isooctane and ethanol in air, simulated with the homogeneous, constant-volume, closed, adiabatic reactor in CHEMKIN [8]. Mechanisms for isooctane and ethanol are from LLNL [9, 10].

Fig. 2 Pressure sensitivity for the autoignition of gasoline and ethanol, as indicated by the bottom dead center temperature (T_{BDC}) required for maintaining a fixed ignition timing (CA10) with changes of the intake pressure. $\phi = 0.38$, and 1200 rpm. TDC compression is at 360°C. A later CA10 was used for gasoline at $P_{in} = 1.8$ bar (and 1.6 bar for comparison) to avoid excessive engine knocking. These data were first reported in [17] for ethanol and in [15] for gasoline.

Fig. 3 Heat release rates prior to hot ignition at various intake pressures, for ethanol (a) and gasoline (b). Same data set as in Fig. 2. Normalization by the total heat release was applied in order to remove the differences in fuel input energy.

Fig. 4 Temperature sensitivity for the autoignition of ethanol and gasoline, as indicated by the intake temperature as a function of CA10 at $P_{in} = 1$ bar. $\phi = 0.4$ and 1200 rpm. No EGR was used. Data first published in [15].

Fig. 5 Temperature sensitivity at boosted conditions. A T_{in} difference of 25°C between y-axes, same as in Fig. 4, is used to facilitate a comparison.

Fig. 6 Knock-limited SI engine performance - NMEP at knock-limited spark advance for gasoline (RON=88) and E50 (gasoline : ethanol = 50:50 by vol.). DI = direct injection, UFI = upstream (of intake port) fuel injection. Changes in NMEP are produced by varying P_{in} , while maintaining stoichiometric combustion for an engine speed of 1500 rpm. T_{in} is held fixed at 52°C. Reproduced from [6] with permission.

Fig. 7 Engine speed sensitivity for the autoignition of ethanol and gasoline, as indicated by the intake temperature required to maintain a constant combustion timing ($CA_{50} = 372^\circ CA$). $P_{in} = 1.0$ bar, $\phi = 0.38$, no EGR. Data first reported in [17].

Fig. 8 Anti-knock properties of isopentanol [18] and cyclopentanone [15] and their comparison with ethanol and gasoline. (a) temperature sensitivity – isopentanol (b) temperature sensitivity – cyclopentanone (c) pressure sensitivity (d) speed sensitivity. Same conditions as in the respective sweeps discussed above.

FIGURES

Fig. 1 Ignition delay of isooctane and ethanol in air, simulated with the homogeneous, constant-volume, closed, adiabatic reactor in CHEMKIN [8]. Mechanisms for isooctane and ethanol are from LLNL [9, 10].

Fig. 2 Pressure sensitivity for the autoignition of gasoline and ethanol, as indicated by the bottom dead center temperature (T_{BDC}) required for maintaining a fixed ignition timing (CA10) with changes of the intake pressure. $\phi = 0.38$, and 1200 rpm. TDC compression is at 360°CA. A later CA10 was used for gasoline at $P_{in} = 1.8$ bar (and 1.6 bar for comparison) to avoid excessive engine knocking. These data were first reported in [17] for ethanol and in [15] for gasoline.

Fig. 3 Heat release rates prior to hot ignition at various intake pressures, for ethanol (a) and gasoline (b). Same data set as in Fig. 2. Normalization by the total heat release was applied in order to remove the differences in fuel input energy.

Fig. 4 Temperature sensitivity for the autoignition of ethanol and gasoline, as indicated by the intake temperature as a function of CA10 at $P_{in} = 1 \text{ bar}$, $\phi = 0.4$ and 1200 rpm. No EGR was used. Data first published in [15].

Fig. 5 Temperature sensitivity at boosted conditions. A T_{in} difference of 25°C between y-axes, same as in Fig. 4, is used to facilitate a comparison.

Fig. 6 Knock-limited SI engine performance - NMEP at knock-limited spark advance for gasoline (RON=88) and E50 (gasoline : ethanol = 50:50 by vol.). DI = direct injection, UFI = upstream (of intake port) fuel injection. Changes in NMEP are produced by varying P_{in} , while maintaining stoichiometric combustion for an engine speed of 1500 rpm. T_{in} is held fixed at 52°C. Reproduced from [6] with permission.

Fig. 7 Engine speed sensitivity for the autoignition of ethanol and gasoline, as indicated by the intake temperature required to maintain a constant combustion timing ($CA_{50} = 372^\circ CA$). $P_{in} = 1.0$ bar, $\phi = 0.38$, no EGR. Data first reported in [17].

Fig. 8 Anti-knock properties of isopentanol [18] and cyclopentanone [15] and their comparison with ethanol and gasoline. (a) temperature sensitivity – isopentanol (b) temperature sensitivity – cyclopentanone (c) pressure sensitivity (d) speed sensitivity. Same conditions as in the respective sweeps discussed above.