1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36

Brief Research Article

**Improvement of Stability of Polidocanol Foam for Nonsurgical Permanent
Contraception**

**Jian Xin Guo, Lisa Lucchesi, and Kenton Gregory*
Oregon Biomedical Engineering Institute, Wilsonville, OR

Financial Support: This research was supported by a generous grant from the Bill & Melinda Gates Foundation (OPP1060424).

Word Count:
Abstract 213
Introduction 302
Methods 407
Results 431
Discussion 715
Total: 1931

Key Words: tubal occlusion, permanent contraception, female, polidocanol foam, stability, benzalkonium chloride

Running Title: Improvement of stability of polidocanol foam for nonsurgical permanent contraception

*Corresponding Author:
Jian Guo, PhD
Center for Regenerative Medicine
Oregon Health & Science University
Portland, OR 97239
Phone: 503-418-0242; Fax: 503-418-0025; email: guoj@ohsu.edu

37

38 **Abstract**

39 Polidocanol foam, used clinically as a venous sclerosant, has recently been studied as a
40 safe, inexpensive means for permanent contraception. We studied methods to improve
41 foam properties that might improve safety and efficacy of polidocanol foam for intra-
42 uterine application. Delivering a detergent-type sclerosant as a foam rather than a liquid
43 can increase the epithelial disrupting activity of the agent. Increasing foam stability and
44 thus duration of epithelial agent exposure time could increase epithelial effect while
45 allowing reduction in agent concentration and potential toxicity. The stability of foam is
46 mainly related to the surface tension, concentration, type of gas and method of foam
47 production. In this study, we explored mechanical (filters) and chemical (surfactant)
48 strategies to improve stability of polidocanol foam (PF) for use in permanent
49 contraception. Several types of microporous filters adapted to a syringe-based foaming
50 device were explored to evaluate the effect of pore structures of filters on foam formation
51 and characteristics. The results suggest that the pore characteristics of the filter play an
52 important role in forming stable foam. The stability of PF improved with the addition of
53 small amount of benzalkonium chloride (BZK), a cationic surfactant. These findings, if
54 shown to be efficacious in animal models of contraception, could lead to a safe, simple
55 and inexpensive new means of permanent contraception.

56

1. Introduction

Polidocanol is a non-ionic surfactant that is used clinically for venous sclerotherapy. The activity of a surfactant-based sclerosant can be increased by delivering the agent as a foam. The rationale for using foam is to provide the greatest therapeutic effect while using the lowest total dose of the injected agent. A recent report demonstrating fallopian tubal occlusion in macaques following trans-cervical treatment with 5% polidocanol foam (PF) provides the basis for studying foam sclerotherapy as a novel and inexpensive alternative approach to surgical permanent contraception for women [1]. One advantage of adapting polidocanol for this use is that the compound is currently FDA approved (0.5% and 1%) for use in venous sclerotherapy.

To ensure adequate epithelial damage and reliable tubal sclerosis, an optimal foam preparation must have sufficient stability to remain in contact with the target tissue for an adequate treatment interval. Liquid drainage and bubble coarsening, coalescence or rupture adversely affects foam stability during delivery before exposure to the epithelium in the fallopian tubes and lead to incomplete or inadequate treatment. The nonhuman primate studies of PF for permanent contraception have compensated for this problem by using a higher concentration (5%) of PF than is currently approved for human use [1]. Improving the stability of PF may increase polidocanol exposure time and PF delivery to the epithelial cells, and thus allow use of lower concentrations for permanent contraception. A variety of approaches have been evaluated to improve foam stability for venous sclerotherapy; changing the foaming gas, adjusting polidocanol concentration, varying pH or temperature, adding chemicals, and modifying the foaming device [2-6]. We explored two novel approaches to improve polidocanol foam stability: 1) the effect of filter pore structure on foam formation (mechanical), 2) the addition of a

small amount of benzalkonium chloride (BZK) that has surfactant properties to stabilize bubbles (chemical).

2. Materials and methods

Polidocanol (Sigma-Aldrich P9641) and BZK (Sigma-Aldrich 234427) used in this study were both chemical grade. Three types of commercial 5 μm filters were evaluated in this study: polytetrafluoroethylene (PTFE) microporous membrane (Filter #1, Millipore LSWP01300), nylon mesh (Filter #2, Spectrum Laboratories 145814) and polycarbonate track-etched membrane (Filter #3, Millipore TMTP1300). The surface morphology of the three filters was characterized with scanning electron microscope (SEM) (FEI Quanta 200). The filters for SEM characterization were sputter coated with 20Å of Au/Pd metal.

Four separate solutions (3% polidocanol, 5% polidocanol, 0.01% BZK, and 0.1% BZK) were prepared by dissolving polidocanol or BZK in water and mixing overnight. Two polidocanol solutions containing 0.01% BZK and 0.1% BZK were prepared by adding BZK to 3% stock polidocanol solution and mixing overnight. A modified double-syringe technique originally described by Tessari [5] was used for foam preparation. Briefly, 2.4 ml of foaming solution and 9.6 ml of air (1:4 ratio) were mixed in two 12 ml syringes connected via a 3-way stopcock with an inline filter holder by pushing the plungers back and forth 20 times to generate foam. Triplicate experiments were prepared for each type of filter and each concentration of polidocanol solution with and without BZK. Foams generated with 3% polidocanol without filters and without BZK were used as a control.

To estimate the foam bubble size, the freshly made foam was immediately sandwiched between two microscopic slides (3x2 in) with a 30 μm spacer and microscopic images of the bubbles were taken with iPhone 5s camera equipped with a ProScope microscope (Bodelin Technologies, Oregon, USA). The diameter of the

individual bubble was measured with ImageJ software [7] and the mean diameter of the bubbles at the image center (1.5x1.5 mm) was used for foam comparison.

To evaluate foam stability, the foam drainage was measured with a method similar to that used in prior studies of polidocanol and other foams [6, 8]. Briefly, a total of 10 ml of freshly made foam was immediately dispensed into a 15 ml conical bottom graduated glass tube. Foam stability was assessed by measuring the time (in seconds) required for 1 ml of liquid to drain and accumulate from the foam (drainage time). The longer the drainage time the more stable the foam.

All values were expressed as mean $\pm$ standard deviation (n=3). One-way ANOVA analysis with post hoc test was used to evaluate statistical significance; $p < 0.05$ was considered significant for each of the independent experiments.

3. Results

3.1 Effect of membrane filter on polidocanol foam stability and bubble size

The SEM images of the top surfaces of Filter #1, #2 and #3 are shown in Figure 1. The microscopic appearance of the pore structure showed marked differences between filters: Filter #1 pores were irregular and tortuous; Filter #2 had rectangle-like pores; Filter #3 pores were regular and circular.

Figure 2 illustrates the comparison of mean drainage time for 3% PF generated without and with the various filters. Compared to no filter (mean drainage time = 184.67 ± 5.13 s), the use of any filter (Filter #1, #2 or #3) significantly improved foam stability ($p < 0.05$). Further comparison among these three types of filters revealed that PF prepared using Filter #3 had a significantly longer drainage time (227.00 ± 3.46 s) than foam prepared with Filter #1 (210.33 ± 8.02 s, $p < 0.05$) or Filter #2 (215.00 ± 4.36 s, $p < 0.05$) (Figure 2).

Mean bubble diameter for 3% PF generated with and without a filter is shown in Figure 2. Consistent with the results of the foam stability assay, PF generated without a filter resulted in a larger bubble size ($107.06 \pm 6.31 \mu\text{m}$) than filter-generated foam. Although all 3 filters have the same pore size ($5\mu\text{m}$), the mean bubble diameters of PF prepared with the filters differed significantly. Filter #3 produced significantly smaller bubbles ($68.90 \pm 0.56 \mu\text{m}$) than Filter #2 ($74.33 \pm 3.41 \mu\text{m}$, $p < 0.05$), and Filter #2 bubbles were significantly smaller than Filter #1 ($87.63 \pm 6.37 \mu\text{m}$, $p < 0.05$).

3.2 Effect of BZK on stability and bubble size of PF

Our initial observations of foaming behavior of low concentrations of BZK solutions without polidocanol showed that BZK foams were unstable. The drainage time of foam prepared with 0.1% BZK solution without polidocanol was less than 1 minute and the foam prepared with 0.01% BZK solution without polidocanol collapsed immediately after it was formed (data not shown).

However, when BZK was added to 3% polidocanol solution, the resulting combined BZK/PF appeared more uniform and stable. Figure 4 displays the drainage time observed for 3% PF with and without BZK, and for 5% PF without BZK (the current standard) under the same foaming conditions including the same filter (Filter #3). The addition of 0.1% BZK to 3% PF significantly increased the drainage time ($336 \pm 9.54\text{s}$) compared to 3% ($227.00 \pm 3.46\text{s}$, $p < 0.05$) or 5% ($274.67 \pm 0.57\text{s}$, $p < 0.05$) PF without BZK. Interestingly, a decrease of the BZK concentration from 0.1% to 0.01% did not result in a significant change in drainage time ($336 \pm 9.54\text{s}$ vs $321.67 \pm 13.58\text{s}$, $p = 0.18$) for 3% PF.

4. Discussion

A safe, simple and inexpensive approach to nonsurgical permanent contraception would improve family planning options for women who desire no further pregnancies. Although 1% polidocanol foam is FDA-approved for use as an agent for venous sclerotherapy, higher concentrations have been required to achieve sclerosis of the fallopian tubes in a nonhuman primate model [1]. Improvement of foam stability and lifetime could increase the exposure time and PF delivery to the epithelium during treatment and result in greater damage to the epithelium and underlying stromal tissue, leading to more reliable tubal occlusion. Strategies that optimize foam stability may make it possible to use of lower concentrations of polidocanol for nonsurgical permanent contraception. Although both 1% and 3% PF have been evaluated for venous sclerotherapy, no clinical benefit is seen with the higher concentration [9]. There is no clinical data on the safety of 5% PF, so strategies that could improve the effectiveness of lower concentrations of polidocanol for use in permanent contraception should improve safety and acceptability of the approach. Our results demonstrate that a 5 μ m filter improves the quality (stability and bubble size) of 3% polidocanol foam, and that the combination of a 5 μ m filter and 0.01% BZK resulted in foam quality superior to that 5% PF.

Use of a 5 μ m filter hub to generate foam with another detergent based surfactant, sodium tetradecyl sulfate (STS) has previously been reported [10]. The novel finding in our study is that filter pore structure also influences foam performance. The circular pores (Filter #3) produced more stable foam than the other shapes tested. One possible explanation for this effect is that the regularity of pore shape (circular) produces bubbles of a highly regular shape during the initial generation and that these may be more stable than those produced by filters with irregular shaped openings. Further investigation of other types of filters with different pore characteristics is in progress.

BZK is a cationic surfactant with antimicrobial and antiviral activity. It has a long history of FDA allowance for a broad spectrum of medical uses and approved in topical treatments such as eye drop, wound, and vaginal treatments. Clinical safety for internal use has not been fully evaluated. The critical micelle concentration (CMC) of BZK is around 0.02% [11]. The CMC of a surfactant is the minimum concentration required for the solution to form micelles or foam in the presence of a gas. The improvement of PF stability by BZK at a concentration below its CMC suggests that BZK is acting as a foam stabilizer rather than a foaming agent. This improvement occurs with a small addition of BZK; no further change in bubble size was observed when the concentration of BZK added to 3% polidocanol was increased from 0.01% to 0.1% (Figure 5). Mixed surfactant systems have been reported to exhibit improve foam stability, when compared to their individual components [12, 13]. In particular, mixtures at a molecular ratio of 1:3 or 3:1 lead to an interfacial phenomenon that results in more favorable hexagonal molecular arrangement (packing) that improve stability [14]. However, the molecular ratio of BZK to polidocanol used in the present study was much lower (<1:150). The observed stabilization of polidocanol foam with this small amount of BZK may be in part due to a synergic effect, similar to that observed for a mixture of non-ionic and cationic surfactants [14], although the mechanism is not fully understood.

Anatomically, major differences exist between veins and fallopian tubes with respect to the morphology and physiology. Unlike the endothelium of veins, the fallopian tube has a tortuous lumen with two types of epithelial cells (ciliated and secretory) filled with tubal fluid (secretions). The complexity of fallopian tube presents new challenges for the application of foam sclerotherapy. Currently, there is incomplete understanding of how PF interacts differently with this epithelium compared to endothelium, particularly in the presence of the tubular fluid instead of the blood. However, given the fact that the clinical

evidence from the phlebology literature supports the superiority of foam over liquid polidocanol for larger veins, it makes sense to use foam for the purpose of nonsurgical permanent contraception [16]. The preliminary results from this study suggest that it may be possible to use low cost physical and chemical approaches to increase the stability and activity of PF.

5. Conclusion

Preliminary results showed that the adaption of an inline filter in the syringe-based foaming device or the addition of small amount of BZK improved the stability of polidocanol foam. The findings in this study provide a potential opportunity to reduce the concentration and dose of polidocanol required to produce tubal occlusion. The confirmation of these effects needs to be done in nonhuman primate models.

References

- [1] J.T. Jensen, C. Hanna, S. Yao, E. Micks, A. Edelman, L. Holden, Ov.D. Slayden, Blockade of tubal patency following transcervical administration of polidocanol foam: initial studies in rhesus macaques, *Contraception* 2014;89:540-49.
- [2] J.D. Peterson, M.P. Goldman, An Investigation into the influence of various gases and concentration of sclerosants on foam stability, *Dermatol Surg.* 2011;37:12-18
- [3] B. Van Deurzen, R.P. Geulen, S.S. Tellings, C. Van Der Geld, T. Nijsten, Polidocanol concentration and time affect the properties of foam used for sclerotherapy, *Dermatol Surg.*, 2011;37:1448-55.

[4] G.C. Valenzuela, K. Wong, D.E. Connor, M. Behnia, K. Parsi, Foam Sclerosant are more stable at lower temperature, *Eur. J. Vasc. Endovasc. Surg.*, 2013;46:593-99.

[5] A. Cavezzi, L. Tessari, Foam sclerotherapy techniques: different gases and methods of preparation, catheter versus direct injection. *Phlebology*, 2009;24:247–51.

[6] R Rial, L S Hervas, G. Monux, A. Galindo, A. Martin, M. Hernando, I. Martinez, A Hernando, F. J. Serrano, Polidocanol foam stability in terms of its association with glycerin, *Phlebology*, 2013;29:304-309

[7] W.S. Rasband, ImageJ, U. S. National Institutes of Health, Bethesda, Maryland, USA, <http://imagej.nih.gov/ij/>, 1997-2014

[8] R petkova, S. Tcholkova, N.D. Denkov, Role of polymer-surfactant interactions in foams: Effects of pH and surfactant head group for cationic polyvinylamine and anionic surfactants, *Colloids Surf. A: Physicochem. Eng. Aspects*, 2013;438:174-185

[9] B. Van Deurzen, R.P Ceulen, S.S. Tellings, C VDG Geld, T. Nijsten, Polidocanol concentration and time affect the properties of foam used for sclerotherapy. *Dermatol Surg.* 2011;37:1448-55.

[10] A.R. Shirazi, M. Goldman, The use of a 5- μ m filter hub increases foam stability when using the double-syringe technique, *Dermatol Surg.* 2008;34:91–92.

[11] T. Deutsche, U. Porkert, R. Reiter, T. Keck, H. Riechelmann, In vitro genotoxicity and cytotoxicity of benzalkonium chloride, *Toxicol In Vitro*, 2006;20:1472-77.

[12] P.M. Holland, D.N. Rubingh, Mixed Surfactant Systems, ACS Symposium Series No. 501, Washington, DC, 1992.

[13] J.F. Scamehorn, Phenomena in Mixed Surfactant Systems, ACS Symposium Series No. 311, Washington, DC, 1986.

[14] D.O. Shah, Significance of the 1:3 molecular ratio in mixed surfactant systems, J. Colloid Interface Sci, 1971;37:744-52

[15] A. Bera, K. Ojha, A. Mandal, Synergistic Effect of Mixed Surfactant Systems on Foam Behavior and Surface Tension, J. Surfact. Deterg. 2013;16:621–30.

[16] C. Hamel-Desnos, P. Desnos, J.C. Wollmann, P. Ouvry, S. Mako, F.A. Allaert. Evaluation of the efficacy of polidocanol in the form of foam compared with liquid form in sclerotherapy of the greater saphenous vein: initial results. Dermatol. Surg. 2003;29:1170-5;

Figure captions:

Figure 1. SEM images of the top surface of (a) Filter #1, (b) Filter #2, and (c) Filter #3

Figure 2. The time required for 1 ml of liquid to drain and accumulate from 10 ml of PF (3% polidocanol) generated with three types of filters with different pore characteristics: tortuous (Filter 1), rectangle-like (Filter 2) and circular (Filter 3). Results are mean $\pm$ STD (n=3), *p<0.05.

280

281 Figure 3. Bubble diameter of PF (3% povidocanol) generated with three types of filters
282 with different pore characteristics: tortuous (Filter 1), rectangle-like (Filter 2) and circular
283 (Filter 3). Results are mean $\pm$ STD (n=3), *p<0.05.

284

285 Figure 4. The time required for 1 ml of liquid to drain from 10 ml of PF prepared with 3%
286 povidocanol without and with BZK, and 5% povidocanol without BZK. All PF were
287 generated with Filter #3. Results are mean $\pm$ STD (n=3), *p<0.05.

288

289 Figure 5. Bubble diameter of PF prepared with 3% povidocanol without and with BZK,
290 and 5% povidocanol without BZK. All PF were generated with Filter #3. Results are mean
291 $\pm$ STD (n=3). There is no significant difference in bubble diameter between these PF.

292

Brief Research Article

Improvement of Stability of Polidocanol Foam for Nonsurgical Permanent
Contraception

**Jian Xin. Guo, Lisa Lucchesi, and Kenton Gregory*

Oregon Biomedical Engineering Institute, Wilsonville, OR

Figures and captions:

Figure 1. SEM images of the top surface of (a) Filter #1, (b) Filter #2, and (c) Filter #3

Figure 2. The time required for 1 ml of liquid to drain and accumulate from 10 ml of PF (3% polidocanol) generated with three types of filters with different pore characteristics: tortuous (Filter 1), rectangle-like (Filter 2) and circular (Filter 3). Results are mean $\pm$ STD (n=3), *p<0.05.

Figure 3. Bubble diameter of PF (3% povidone-iodine) generated with three types of filters with different pore characteristics: tortuous (Filter 1), rectangle-like (Filter 2) and circular (Filter 3). Results are mean $\pm$ STD (n=3), *p<0.05.

Figure 4. The time required for 1 ml of liquid to drain from 10 ml of PF prepared with 3% povidone-iodine without and with BZK, and 5% povidone-iodine without BZK. All PF were generated with Filter #3. Results are mean $\pm$ STD (n=3), *p<0.05.

Figure 5. Bubble diameter of PF prepared with 3% polidocanol without and with BZK, and 5% polidocanol without BZK. All PF were generated with Filter #3. Results are mean $\pm$ STD (n=3). There is no significant difference in bubble diameter between these PF.