**Characterization of diffuse pollutions from forested watersheds in Japan during
storm events - its association with rainfall and watershed features**

Zhao Zhang¹, Takehiko Fukushima^{1*}, Yuichi Onda¹, Shigeru Mizugaki^{1,2}, Takashi
Gomi^{2,3}, Ken'ichirou Kosugi⁴, Shinya Hiramatsu⁵, Hikaru Kitahara⁵, Koichiro Kuraji⁶,
Tomomi Terajima⁷, and Kazuo Matsushige⁸

¹ Graduate School of Life and Environmental Science, University of Tsukuba, Tsukuba, 305-
8572, Japan

² Japan Science and Technology Agency

³ Disaster Prevention Research Institute, Kyoto University, Kyoto, 611-0011, Japan

⁴ Graduate School of Agriculture, Kyoto University, Kyoto, 606-8502, Japan

⁵ Faculty of Agriculture, Shinshu University, Nagano, 399-4598, Japan

⁶ Graduate School of Agricultural and Life Science, The University of Tokyo, Tokyo, 489-
0031, Japan

⁷ Faculty of Science, Chiba University, Chiba, 263-8522, Japan

⁸ National Institute for Environmental Studies, Tsukuba, 886-0387, Japan

Corresponding Author:

Name: Takehiko Fukushima

Address: Division of Integrative Environment Science, Graduate School of Life and
Environmental Science, University of Tsukuba, Tsukuba 305-8572, Japan

Tel & Fax: 029-853-4210

Email: fukushima@arsia.geo.tsukuba.ac.jp

Abstract

Forest areas have been identified as important sources of nonpoint pollution in Japan. The managers must estimate stormwater quality and quantities from forested watersheds to develop effective management strategies. Therefore, stormwater runoff loads and concentrations of 10 constituents (total suspended solids, dissolved organic carbon, PO₄-P, dissolved total phosphorus, total phosphorus, NH₄-N, NO₂-N, NO₃-N, dissolved total nitrogen, and total nitrogen) for 72 events across five regions (Aichi, Kochi, Mie, Nagano, and Tokyo) were characterised. Most loads were significantly and positively correlated with stormwater variables (total event rainfall, event duration, and rainfall intensity), but most discharge-weighted event concentrations (DWECS) showed negative correlations with rainfall intensity. Mean water quality concentration during baseflow was correlated significantly with storm concentrations ($r = 0.41-0.77$). Although all pollutant load equations showed high coefficients of determination ($R^2 = 0.55-0.80$), no models predicted well pollutant concentrations, except those for the three N constituents ($R^2 = 0.59-0.67$). Linear regressions to estimate stormwater concentrations and loads were greatly improved by regional grouping. The lower prediction capability of the concentration models for Mie, compared with the other four regions, indicated that other watershed or storm characteristics should be included in the prediction models. Significant differences among regions were found more frequently in concentrations than in loads for all constituents. Since baseflow conditions implied available pollutant sources for stormwater, the similar spatial characteristics of pollutant concentrations between baseflow and stormflow conditions were an important control for stormwater quality.

Keywords: Forested watershed; Stormwater; Pollutant loads; Discharge-weighted event concentration; Runoff volume

1. Introduction

Forest areas have been identified as important sources of nonpoint pollution in Japan (Kunimatsu and Kira, 1986; Umemoto et al., 2001), with 65% land cover area, steep mountain landscape, and frequent storms (Oguchi et al., 2001). Unlikely other countries, the present problems facing Japanese forest are insufficient forest management with the decline of consumption in domestic wood, even lower than the level of approximately one-third of its peak in 1973. Most of trees were planted for commercial use 40 years ago. Area of forests of over 40 years which need

appropriate care, such as thinning, make up 80% of the total planted forests. There are some forests where surface runoff and soil erosion occur during strong rainfall events due to over-crowding, probably enhancing the nutrient output (Onda et al., 2006; Tsujimura et al., 2006). Owing to impacts on receiving waters and the expense of monitoring the source of nonpoint pollution, predictive models for stormwater loads and concentrations are desirable. Such models can aid forested watershed managers to make loading estimates for unmonitored events.

Numerous studies on diffuse pollution have been conducted worldwide on stormwater in urban and agricultural areas (e.g., Smith et al., 2007; Sonzogni et al., 2005; Brezonik and Stadelmann, 2002). Unfortunately, related studies on forested watersheds are comparatively rare (Zhang et al., 2007; Shinomiya et al., 2004), although some reports have implied a significant contribution of storm events to annual load (Ahearn et al., 2004; McBroom et al., 2006; Edwards et al., 2003). Generally, routine monitoring of pollutant concentrations and loads has been performed at weekly, biweekly, or monthly intervals in forested watersheds (Umemoto et al., 2001; Oyanagi et al., 2002; Shibata et al., 2001). Although many loading estimates have been reported, the reported data are inconsistent and vary considerably. Transient pollution events are responsible for the transport of large quantities of sediment and nutrients, with a few storm events accounting for nearly the entire annual load (McBroom et al., 2006; Edwards et al., 2003).

Pollutant runoff during storm events has been concerns recently in Japan (Matsumoto et al., 2005; Shinomiya et al., 2004; Okudaira et al., 2005; Ohno et al., 2005; Zhang et al., 2007). All of these studies were limited to fewer than 10 events at one or several sites within the same region, and no definitive results were obtained. To remedy this limitation and to investigate the impact of storm events on the

sustainable development of forested watershed, a comprehensive project across five forested regions in Japan, the Field Investigation and Modelling Study on the Effects of the Forest Devastation on Flooding and Environmental Issues, was undertaken.

One subproject focused on stormwater quality from forested watersheds.

Geographic and physical factors—vegetation type, growing situation, soil type, and slope (Detenbeck et al., 2003; Vitousek and Reiners, 1975; Novotny and Olem, 1994)—are important factors determining the generation of diffuse pollution. Climatic factors such as rainfall intensity, event duration, storm frequency, and time since antecedent rainfall event/dry days are also important (Ahearn et al., 2004; Schreiber et al., 2001). Few studies have comprehensively considered all factors, accounting for the relative significance of each factor. Site-specific models have been developed worldwide to predict runoff volumes, loads, and concentrations (Fisher and Katz, 1984; Niehus, 1997; Prych and Ebbert, 1986; Shinomiya et al., 2004), but predictive models applicable across regions are rare. Brezonik and Stadelmann (2002) emphasised that compilation and analysis of stormwater quality and quantity data are necessary steps in developing predictive models to estimate stormwater runoff loads. By analysing a database of urban and suburban runoff data, they found that predictive models based on storm and watershed variables partially explained pollutant loads (R^2 generally < 0.60), but that R^2 values of all concentration models were less than 0.42 (Brezonik and Stadelmann, 2002). In addition, comparisons among stormwater runoff data from different forested watersheds are few (Zhang et al., 2007); however, such studies would help elucidate element cycling and improve nutrient loss estimation, and consequently improve policies for water resource and forest management. The objectives of this study were to (1) statistically characterise storm runoff loads and discharge-weighted event concentrations (DWECS) of 10 constituents in forested

watersheds; (2) determine relationships between runoff volumes/loads/DWECs and storm/watershed characteristics; (3) develop predictive equations relating runoff volumes, loads, and concentrations to easily measured physical, and climatic characteristics; (4) compare our results with the previous studies; and (5) discuss other potential impacts of storm and watershed variables to improve predictive models.

2. Methodology

2.1. Research sites

Forested watersheds are located over a wide range of longitudes ($\sim 6^\circ$) from $133^\circ 08'E$ to $139^\circ 19'E$ in five regions in Japan. Within each region, we selected four to eight streams sharing similar geological conditions. Further information on the sites was given by Zhang (2007). The site characteristics are briefly summarised below.

The Aichi sites are located in the Aichi Research Forest of the University of Tokyo, east of Inuyama in Aichi Prefecture. The watershed is composed mainly of Neogene sediments with undulating topography. The Kochi sites are located in the Tsuzuragawa watershed, which is part of the east tributary of the Shimanto River, southeast of Taishouchou in Kochi Prefecture. The terrain comprises somewhat steep and incised hillsides. Sandstone and pelitic rocks are dominant in these areas. The Mie sites are located in Taikichou, Mie Prefecture, and are characterised by generally steep slopes. The prevalent rock is gneiss, with typical brown forest soil cover. The Nagano sites are located in the Terasawayama Education and Research Forest of Shinshu University in Ina, Nagano Prefecture. The Tanazawagawa, a small tributary of the Tenryu River, discharges from this area. As in Mie, steep slopes are a common feature of this area. The watersheds are underlain by granite. The Tokyo sites are

located in the Joubanzawa watershed, a tributary of the Arakawa River, and near the headwaters of the Narikigawa in Tokyo. Steep, incised hillsides are common in this area. The watershed is underlain by sandstone, pelitic rocks, and chert.

The topological, meteorological, and vegetational information for each sampling site has been presented by Zhang (2007). Monthly mean air temperature and precipitation data collected from 1979 to 2000 in the five regions are presented in Fig. 1 for comparison with data collected during the study period (June 2004-September 2005). Higher precipitation inputs were commonly observed from May to October in all regions except Nagano, and precipitation amounts during the period (percentage of annual total) were 1082 mm (69.2%), 2182 mm (69.9%), 1471 mm (71.1%), 704 mm (48.5%), and 1079 mm (73.2%) for Aichi, Kochi, Mie, Nagano, and Tokyo, respectively. The monthly precipitation was distributed more evenly throughout the year in Nagano than in the other four regions. In addition, the estimated maximum rainfall intensity at 1~1.5 year of recurrence was 15~20 mm h⁻¹ in Nagano, 15~30 mm h⁻¹ in Aichi and Tokyo, 20~35 mm h⁻¹ in Mie, and 30~45 mm h⁻¹ in Kochi. The observed maximum rainfall intensities during the study period showed a little difference from the estimated values given above, with the lowest (18 mm h⁻¹) in Nagano, followed by 23.6, 25.4, 57.4, and 61.2 mm h⁻¹ for Tokyo, Aichi, Kochi, and Mie, respectively.

2.2. Field and laboratory procedures

Streamflow in each watershed has been measured continuously since May 2004 with a Parshall flume or V-notch weir in combination with a water-level recorder (TruTrack WT-HR500 and 1000, Christchurch, New Zealand). In addition, stormflow samples were collected throughout by storm hydrographs using automatic samplers,

which were activated automatically when the water table increased. Discrete samples were usually collected every 0.5 h, sometimes every 1 or 2 h during the falling limb of the hydrograph, or throughout the storm for large watersheds (with area > 30 ha). To well characterise stormwater concentrations and loads and minimise sampling method errors, we eliminated some failed sampling data, such as when no peak flow samples were collected or when samples covered less than 85% of the event duration, since stormwater quality varies greatly throughout a storm in these streams (Zhang et al. 2007). DWEC and total load data were available for total suspended solids (TSS), total phosphorus (TP), total nitrogen (TN), dissolved total phosphorus (DTP), dissolved total nitrogen (DTN), dissolved organic carbon (DOC), NH₄-N, NO₂-N, NO₃-N, and PO₄-P. Detailed information on laboratory measurement has been presented by Zhang (2007).

2.3. Data analysis

Monitored events occurred between June 2004 and September 2005. A total of 72 storm events at 23 sites were chosen for analysis. DWECs of all constituents were expressed in mg l⁻¹; loads in kg event⁻¹; and total runoff in m³ event⁻¹. DWECs were calculated using the following equation:

$$DWEC = \sum_{i=1}^n C_i Q_i / \sum_{i=1}^n Q_i \quad (1)$$

where Q_i is the instantaneous discharge, C_i is the instantaneous concentration, and n is number of stormwater samples. Loads were calculated from the following equation:

$$Load = \sum_{i=1}^n A Q_i (C_{i-1} + C_i) / 2 \quad (2)$$

where AQ_i is the cumulative discharge since the last sample was taken, C_i is the instantaneous concentration, and n is number of stormwater samples. AQ_1 and C_0

were defined as zero since no sample was collected before it. While there are many ways to calculate loads (e.g., Walling and Webb, 1981; Swistock et al., 1997; Kunimatsu and Sudo, 1997; Brezonik and Stadelmann, 2002), we used instantaneous concentration and cumulative discharge, which are generally better for characterising stormwater than other methods, at least for suspended constituents (Bunte and MacDonald, 1998). Average rainfall intensity was defined as the total rainfall divided by the time period of the event. Event duration was defined as the period from the start of automatic sampling to when the water returned to the starting level at the sampler, or to when the next event occurred. Days since the last event was based on the days since at least 35 mm of precipitation occurred. We assumed that mean water quality concentrations during baseflow conditions described the differences between watersheds and represented their respective attributes. MCB at each site during the study period was used to characterise the impact of baseflow on stormwater concentration and load.

2.4. Statistical analysis

XLSTAT 2006 (AddinsoftTM) was used to compute descriptive statistics, generate histograms, and compute the correlation matrices and linear regressions. Since the data were skewed, variables were log transformed before correlations and regressions were calculated. Variables having zero values were expressed as $\log(0.5 \times \text{limit of detection})$. The Kolmogorov-Smirnov test ($\alpha < 0.01$) was used to evaluate the fit of transformed data to a normal distribution.

Correlation matrices were computed between log-transformed stormwater constituents and watershed/climatic variables. Forward stepwise multiple regressions were applied to relate runoff volumes, loads, and DWECs to storm characteristics,

antecedent conditions, watershed area, slope, and sources. DWEC boxes by region group were plotted using OriginPro 7 (OriginLab Corp.). For examining the differences of water quality and quantity, we performed one-way ANOVA among regions. The Tukey multiple comparison and F-test were used to identify significant differences ($P < 0.05$) in loads and DWECs among regions. Regression models were developed to predict runoff volumes, loads, and DWECs using log-transformed data in each region group.

3. Results and discussion

3.1. Characteristics of stormwater runoff

Runoff events were monitored throughout the year; most occurred in summer and autumn. Total event rainfall amounts ranged from 44.2 to 398.4 mm, and maximum rainfall intensity and average intensity ranged from 4.4 to 62.4 mm h⁻¹, and from 2.5 to 41.5 mm h⁻¹, respectively. Duration ranged from 2.5 to 56.7 h, and time to antecedent rainfall event (> 35 mm) ranged from 8 h to 23 days. All precipitation data were log-normally distributed, and the Kolmogorov-Smirnov test indicated that the log transformation improved their fitness to normal distribution. Runoff volumes for all events ranged from <10 to 32 875 m³, and runoff depths ranged from 0.07 to 268 mm. After log transformation, runoff volume was normally distributed. The symmetry of runoff depth was improved, but the data were still skewed.

Loads ranged over from four times, even up to seven orders of magnitude for most constituents (Table 1-A). All data were positively skewed with a long right tail, and log transformations yielded nearly normal distributions for all constituents. Loads expressed in kg ha⁻¹ event⁻¹ (Table 1-B) ranged over four orders of magnitude.

DWECs (Table 1-C) ranged over from 20 times, even up to three orders of magnitude for most constituents. All DWECs were skewed except DTN and TN. Log transformation yielded nearly normal distribution for all DWECs except NO₂-N. Generally, runoff concentrations were higher than concentrations during baseflow (Zhang 2007). However, the mean DWECs in our study were generally lower than those of storm runoff from urban or rural areas in UAS and Korea.

3.2. Relationships between runoff data and explanatory variables

Factors contributing to sources of diffuse pollutants in forested watersheds were identified as a step in developing models to predict runoff volumes, loads, and concentrations. Correlation coefficients were calculated between stormwater variables and climatic/watershed characteristics to determine whether these parameters, based on easily obtainable climatic and watershed information, could be used to develop predictive models. The following explanatory variables were considered. Storm characteristics: total rainfall (mm), duration (h), maximum intensity (mm/h), average intensity (mm/h), and the days since the last event (>35 mm, day). Watershed characteristics: total watershed area (ha), average slope of watershed (°), and baseflow concentration. Although there could be some correlation between average intensity and maximum intensity, we used both for our first statistical and model analyses, since it is difficult to accurately describe rainfall features using only a few parameters owing to the stochasticity of rainfall.

Before comparing explanatory variables with runoff variables, we evaluated correlations among the log-transformed explanatory variables in each group. Storm variables were correlated significantly with each other except for a weak correlation between average and duration ($r = 0.11$). For example, total rainfall was correlated

with duration ($r = 0.67$), maximum intensity ($r = 0.83$), average intensity ($r = 0.65$), and days since the last event ($r = 0.54$). Area was negatively correlated with storm variables except duration ($r = 0.12$). No significant correlations were found between slope and storm variables or watershed characteristics except baseflow concentrations of DOC and P constituents ($r = -0.38, 0.56, 0.49$, and 0.32 for DOC, $\text{PO}_4\text{-P}$, DTP, and TP, respectively). Significant correlations were also found between area and baseflow concentrations of N constituents except $\text{NH}_4\text{-N}$ ($r = -0.59, 0.50, 0.55$, and 0.58 for $\text{NO}_2\text{-N}$, $\text{NO}_3\text{-N}$, DTN, and TN, respectively). No other significant correlations were found between watershed variables.

Runoff volume was correlated significantly with storm characteristics: total rainfall ($r = 0.64$), duration ($r = 0.78$), maximum intensity ($r = 0.51$), average intensity ($r = 0.45$), and days since the last event ($r = 0.78$). These results were expected for the first four variables since each leads to the generation of more runoff. A weak correlation ($r = 0.24$) between runoff volume and area was found, while no correlation with slope was found ($P > 0.60$). The positive correlation between days since the last event and runoff volume, and the lack of correlation between slope and runoff volume, could be considered surprising, since less or more runoff would be expected after a long dry period or from a steeper watershed, respectively. In fact, these relationships are expected considering the characteristics of storms that contribute to Hortonian overland flow in a forested watershed (Miyata et al., 2007) and the minor topographic control of the occurrence of overland flow (Elsenbeer and Vertessy, 2000). Miyata et al. (2007) investigated the impact of soil properties on overland flow occurrence and behaviour on a plot scale in a Japanese cypress forest, and observed that Hortonian flow resulted mainly from water repellency in the surface soil. This result implied that Hortonian flow begins readily when storm rainfall occurs after a long dry period,

leading to more runoff generation. They also observed that runoff ratio decreased during wet periods and gradually increased during dry periods, consistent with our finding of a positive correlation between runoff volume and days since the last event (Miyata et al., 2007). They also found that overland flow from a plot with 40.7° slope was greater than that from a plot of very similar area with 43.3° slope during most rainfall events, implying that the role of slope on stormwater runoff volume can be ignored (Miyata et al., 2007). Elsenbeer and Vertessy (2000) conducted a study in the Amazon rainforest and found that the occurrence of overland flow resulted from high rainfall intensity and frequency showed no obvious topographic control.

We performed statistical analyses on the pollutant loads and storm and watershed variables; only the significant correlations are discussed here (Table 2-A). Most constituents were significantly and positively correlated with at least four storm variables, except total rainfall, duration, and maximum intensity for PO₄-P and NO₃-N. All storm variables showed significant correlations with TSS, DOC, and NH₄-N export (ranging from 0.310 for TSS with average intensity to 0.647 for NH₄-N with maximum intensity). Generally, total rainfall, duration and maximum intensity seemed to be the most important factors determining pollutant loading from forested watersheds.

We also calculated correlations between runoff loads and watershed characteristics (Table 2-A). Significant and positive correlations with area were found in all constituents except NH₄-N, and *r* values ranged from 0.267 (DOC) to 0.432 (NO₃-N). No significant correlation was found between any pollutant load and slope. Two variables, TP and NH₄-N, showed significant correlations with baseflow concentration, a negative correlation for TP (*r* = -0.29) and a positive correlation for NH₄-N (*r* = 0.54).

All DWECs (except TSS, TP, and NO₂-N, which had no correlation with any explanatory variables) were significantly correlated with at least two explanatory variables (Table 2-B). We compared the correlation coefficients for loads with storm characteristics and found two differences: (1) that all significant correlations between storm variables and DWECs were negative except NH₄-H ($r = 0.35$) with maximum intensity; and (2) that rainfall intensity indexes (maximum intensity and average intensity), instead of total rainfall and duration, which were the most important factors in determining pollutant loads, seemed to be the most important factors in determining pollutant concentrations. The negative correlations between pollutant concentrations and rainfall intensity (r ranging from -0.26 between PO₄-P and maximum intensity to -0.52 between DTN and average intensity) and those between pollutant concentrations and total rainfall (from -0.28 for NO₃-N to -0.36 for DTN) suggest that strong events generate more diluted runoff with dissolved constituents. There were no significant correlations between pollutant concentrations and duration, suggesting that different runoff mechanisms control stormwater quality in forests than in urban settings. Brezonik and Stadelmann (2002) found that most pollutant concentrations showed significant ($P < 0.01$) and negative correlations with total rainfall and duration from urban stormwater runoff. Such differences indicate that available pollutant sources for stormwater in urban settings are limited in comparison with those in the forest in our study. The negative correlation between days since the last event and pollutant concentrations does not support the idea that pollutants accumulate during dry periods; this idea has been confirmed in urban settings (Brezonik and Stadelmann, 2002; Shirasuna et al., 2006).

Significant correlations were also common for watershed variables (Table 2-B), particularly for baseflow concentration, which showed significant and positive

correlations with all dissolved constituents except NO₂-N. Two constituents (NH₄-N and DOC) were significantly and negatively correlated with two watershed variables, area ($r = -0.32$) and slope ($r = -0.54$), respectively, and three other N constituents (NO₃-N, DTN, and TN) were significantly and positively correlated with area ($r = 0.41, 0.44, \text{ and } 0.41$, respectively). The negative correlation between area and NH₄-N concentration may be explained by the volatility of NH₄-N causing a dilution effect as water flows downstream. However, we cannot explain the positive correlations between area and NO₃-N, DTN, and TN, because their baseflow concentrations showed significant and positive correlations with area. Similarly, we cannot explain the negative correlation between slope and DOC, because of the significant and negative correlation between baseflow concentration of DOC and slope as discussed above.

3.3. Estimating runoff volume

Runoff volumes were estimated by multiple linear regression using four storm variables and one watershed variable (area) (Table 3-A). Model 1 was based on the complete data set, and model 2 excluded events in the Nagano region, where relatively weak rainfall intensities were observed (maximum intensity < 15 mm/h). The two predictive equations accounted well for runoff volumes ($R^2 = 0.78$ and 0.81 for models 1 and 2, respectively), especially for model 2, which accounted well for runoff volume with mean absolute percentage error (MAPE) less than 18%.

Runoff ratio, calculated as total event runoff divided by total rainfall (both in mm), is a simple and important index for evaluating stormwater and watershed attributes. Runoff ratios in our study spanned a wide range (0.0001-0.979), which is not surprising because different storm events and watershed characteristics were included

in the complete data set. The mean and median were 0.545 and 0.281, respectively.

Both of these values exceeded runoff ratios in urban storms (0.157 and 0.133 for mean and median, respectively) in Minnesota, United States (Brezonik and Stadelmann, 2002), although the minimum runoff ratio in our study was lower than the minimum ratio in the Minnesota study. This finding suggests that the role of forest vegetation in reducing flood quantity, which is generally accepted worldwide (e.g. Cheng et al., 2002; Sun et al., 2002), is limited for extreme storms.

Runoff ratios were insignificantly correlated (around $p < 0.05$) with all explanatory variables. Log-transformed runoff ratios were significantly correlated with three log-transformed storm variables ($r = 0.419, 0.489$, and 0.355 for total rainfall, maximum intensity, and average intensity, respectively), and log-transformed area ($r = -0.289$). These correlations are expected for these storm variables because all three lead to the generation of more runoff. The negative correlation between runoff ratio and area can be reasonably explained by a general nest structure in each region, since an increase in the watershed area may raise the contributing area of subsurface and groundwater flows from the hillslope (Ohte et al., 2001), leading to a smaller runoff ratio from a larger watershed than from a smaller one during storm events.

3.4. Multiple regression estimating loads and DWECs for the whole data set

As discussed above, linear correlations were found between explanatory variables and stormwater loads/concentrations; these correlations reflect many factors contributing to the observed runoff concentrations and loads. Taking all these factors into account, we obtained multiple linear regression models using the complete data set to predict stormwater loads/concentrations (Table 4). The coefficients of determination (R^2) of the load models (ranging from 0.55 for $\text{PO}_4\text{-P}$ to 0.80 for TN)

were higher than those of the respective concentrations (ranging from 0.11 for NO₂-N to 0.67 for TN) for all constituents. The load models ($R^2 > 0.67$ and MAPE < 20%) of six constituents, TSS, DTP, TP, NO₃-N, DTN, and TN, were useful in predicting stormwater variables for future events. Three concentration models (NO₃-N, DTN, and TN), with $R^2 > 0.59$ and MAPE < 20%, were also useful. However, only 55-78% of the variations were explained by the load models (DOC, PO₄-P, NH₄-N, and NO₂-N), and MAPE values ranged from 29% to 109%. Moreover, the concentration models for TSS, DOC, PO₄-P, DTP, TP, NH₄-N and NO₂-N explained only 11-41% of the variation, and MAPE values ranged from 48% to 341%. The average R^2 of our load/concentration models was higher (0.26/0.10) than those of comprehensive urban models for the common constituents (Brezonik and Stadelmann, 2002). We attributed these improvements to our more detailed description of storm characteristics (five variables rather than three). The variables in Minnesota study included total rainfall, duration, days since the last event, and one derived index (average intensity).

3.5. Analysis of loads and DWEC grouping by region

Since regression models using the entire data set had large uncertainties, we modelled the regions one by one. We assumed that sites in the same region would behave similarly owing to their similar climates and geography, and that such separation would yield more accurate models.

We prepared box plots of DWECs (Fig. 2) and a summary of ranges and medians of stormwater yields (Table 5) to characterise region-specific stormwater quality and quantity. In all cases, ranges of the DWECs and loads in each region were considerably less than those obtained using the whole data set (Table 1-B and 1-C). Grouping the sites by region thus provided better modelling results of concentrations and loads. We examined differences in DWECs and loads among regions for 95%

confidence intervals of median values and found significant differences more frequently in DWECs than in loads for all constituents. Significant differences were found for all constituent concentrations when comparing two or more regions, except NO₂-N (data not shown), which did not differ significantly between any two regions. The highest medians of TSS, DOC, and all P constituent (PO₄-P, DTP, and TP) concentrations were found in Nagano, those of TN, DTN, and NO₃-N in Tokyo, and those of NH₄-N in Aichi. However, the lowest medians of TSS, TN, NO₃-N, DTN, and DOC were found in Kochi, those of P constituents in Aichi, and those of NH₄-N in Nagano. These spatial characteristics of constituent concentrations were very similar to those during baseflow (Zhang 2007). These results further confirmed the correlations between DWECs and baseflow concentrations discussed above.

No significant difference in stormwater yield (kg ha⁻¹ event⁻¹) was found between any two regions for most pollutant loads, including DOC, DTP, NO₂-N, PO₄-P, TN, TP, and TSS (Table 5). However, we found that Mie showed significantly lower DTN and NO₃-N loads than Tokyo, and that Aichi showed a significantly higher NH₄-N load than the other four regions.

We computed linear regressions to estimate runoff volumes for respective regions using more than two transformed explanatory variables and considering the sample numbers and the significant correlations between runoff volumes and variables (Table 3-B). Except for Nagano, each regression equation explained 15% more variation than those for models 1 and 2, which used the whole data set. The models for Aichi, Mie, and Tokyo had smaller MAPE values (< 10%) than that of model 2.

As we expected, most pollutant load models for individual regions had better predictive capability (with $R^2 > 0.71$) than the models using the whole data set (Fig. 3-1)), with three exceptions (NH₄-N in Mie and Nagano, and TP in Nagano, all with R^2

< 0.50). All load models explained more than 83% of variation, in particular for Aichi
 (MAPE < 7%). However, data were collected for only five events in this region. All
 load models for Kochi explained more than 88% of variation, and MAPE values of
 most models were lower than 3% except TSS and DOC (18% and 22%, respectively).
 Load models in Tokyo also explained more than 73% of variation, with most MAPE
 values < 10% except DTP, NH₄-N, and NO₂-N (18%, 38%, and 13% of variation,
 respectively). In Mie, all load models explained more than 80% of variation with
 MAPE values < 14% except NH₄-N. In general, load models in Nagano had weaker
 predictive ability than those in the other four regions. We attributed the weak
 predictive capability of the Nagano load models to the influence of other hydrological
 processes (e.g. evapotranspiration), which might be important controlling factors
 since the weakest rainfall intensity occurred in this region. All regression coefficients
 in Aichi and Mie were positive for rainfall amount, while either positive or negative
 terms were found in the other three regions (e.g. negative terms for all constituents in
 Nagano and Tokyo with the exceptions of positive terms for TP and TN in Nagano
 and NH₄-N in Tokyo). The area coefficients were consistently negative for all load
 models in Aichi, while all were positive in Tokyo and Mie, and both negative and
 positive coefficients were found in the other two regions. No coefficients of MCB and
 rainfall intensity were consistently positive or negative for all constituents in all
 regions.

We computed linear regressions to estimate stormwater quality for each group
 using three or more explanatory variables and considering their correlation
 coefficients with concentration and the sample numbers (as with the load
 computations). As we expected, the average R^2 of all models (including NH₄-N and
 NO₂-N models for each group) was improved by 0.32, and the average MAPE value

was decreased by 85% compared with the models using the whole data set (Fig. 3-(2)).

Regression equations in the Aichi group, including TSS, DOC, $\text{NH}_4\text{-N}$, $\text{NO}_3\text{-N}$, DTN, and TN, had the greatest reductions in MAPE values (all <10%) compared with the equations using the complete data. However, data were collected for only five events in this region. As with the load computations, concentration models for TN, DTN, and $\text{NO}_3\text{-N}$ had better predictive capability (all MAPE values < 10% except 18% for $\text{NO}_3\text{-N}$ in Mie) than those for other constituents, followed by TSS. In contrast, in all DWEC models, P constituents and DOC had the poorest predictive capability in each region. In general, DWEC models in Mie had weaker predictive capability (R^2 ranging from 0.32 for TN and DTP to 0.57 for TSS) than the models in the other four regions. These results were expected; given that more events in Mie occurred continuously with the days since the last event less than 1 day, we could not separate the impact of one event from the last one because of the extremely variable watershed characteristics (in contrast, only average concentrations during baseflow were used to describe watershed characteristics). In urban stormwater analysis, concentration models grouped by land use and watershed size also improved on average, explaining 15% more of the variation than the models using the complete data set (Brezonik and Stadelmann, 2002). However, all R^2 values were still lower than 0.50 for most constituents, far lower than our average R^2 (0.70).

3.6. The impacts of runoff volume and pollutant sources available in watersheds on

DWECs—some important implications for further investigation

Since storm variables were the primary factors used in modelling runoff volume, we further investigated the relationships between runoff volume ($\text{m}^3 \text{ ha}^{-1} \text{ event}^{-1}$) and DWECs, as well as those between baseflow concentrations and DWECs (Fig. 4). We

assumed that analysis of the original (not log-transformed) data would reveal important mechanisms controlling stormwater concentrations.

We compared linear relationships between baseflow concentrations and DWECs of three dissolved constituents (DOC, DTP, and DTN). The R^2 values of these relationships were 0.28, 0.47, and 0.63 ($p < 0.05$), respectively. Owing to the design of this study and the randomness of rainfall, we failed to measure each antecedent baseflow concentration for respective events at each site. We believe that the concentration models would be improved by the addition of detailed information about antecedent watershed conditions on forested land, e.g., A_0 depth and main constituent concentrations in the soil water.

We evaluated two kinds of impact of runoff volume ($\text{m}^3 \text{ha}^{-1} \text{event}^{-1}$) on pollutant concentrations (Fig. 4), the dilution effect on dissolved constituents (DOC and DTN), and the concentration effect on TSS (except Nagano). Given more and stronger rainfall causing more runoff generation, these results were consistent with the previous results (Zhang et al. 2007), in which particulate nutrients showed positive relationships with rainfall intensity, in contrast to negative relationships for dissolved nutrients. However, our results were inconsistent with previous one, which ascribe the diluted effect during the latter storm to the depleted nutrients by the events occurring before (Ahearn et al., 2004). Further investigating DTN, we found negative correlations with runoff volume in Kochi and Mie, with positive correlations in Aichi, Nagano, and Tokyo, where weaker storms occurred; the latter two regions were in so-called N saturation states (Zhang 2007). These results implied that concentration models would be improved if the total data set were grouped by rainfall intensity and/or level of N saturation. Owing to the limited sample numbers, we were unable to carry this analysis further, and we mention this possibility for further study.

4. Conclusions

In this study, we analysed stormwater quality and quantity for 72 events in 23 forested watersheds in Japan. Pollutant loads ranged over four orders of magnitude, and the distributions were skewed, with long right tails. Pollutant concentrations (DWECS) ranged over 20 times, or even up to three orders of magnitude, and all distributions were skewed except DTN and TN. All log-transformed loads and concentrations except NO₂-N concentration yielded nearly normal distributions. Stormwater concentrations were higher than those during baseflow conditions.

Runoff volume was correlated significantly with storm characteristics, but was not correlated with slope, suggesting that there is no obvious topographic control of runoff generation. The best regression equation to estimate runoff volume was based on total rainfall amount, event duration, rainfall intensity and watershed area.

All loads were significantly and positively correlated with storm variables. In contrast, all constituent concentrations except TSS and NH₄-N showed negative correlations with rainfall intensity, suggesting that storm events generated more dilute runoff for these constituents. One watershed characteristic, baseflow concentration, showed significant and positive correlations with all dissolved constituents except NO₂-N. In general, total rainfall, duration, rainfall intensity, and area were the most important predictors of event loads. Rainfall intensity and baseflow concentration were the most important predictors for DWEC models.

Six linear regression load equations, for TSS, DTP, TP, NO₃-N, DTN, and TN, were useful for predicting stormwater loads. In contrast, only three concentration models were useful for future prediction. Uncertainty was high for other load and DWEC models when the whole data set was used.

Regression models for runoff volume, loads, and concentrations for five regional groups had better predictive ability in general. Load models in Nagano had weaker predictive capability than those in the other four regions, as did concentration models in Mie. We attributed the weak predictive capability of Nagano load models to the influence of other hydrological processes (e.g. evapotranspiration), which might be important controlling factors since the weakest rainfall intensity occurred in this region. We believe that the Mie results can be explained by our inability to separate the impact of one event from the last because of the extremely variable watershed characteristics.

We examined differences in DWECs and loads among regions and found significant differences more frequently in DWECs than in loads for all constituents. The highest means of TSS, DOC, and all P constituent concentrations were found in Nagano, those of TN, DTN, and $\text{NO}_3\text{-N}$ in Tokyo, and those of $\text{NH}_4\text{-N}$ in Aichi. Since baseflow conditions implied available pollutant sources for stormwater, the similar spatial characteristics between baseflow concentration and DWEC were also an important control for stormwater quality.

Based on these findings, we suggest that the regression equation based on a high-resolution sampling in a specific forested region is the most appropriate to estimate DWEC/load from the watershed outside Japan. If such observation is not available, a selection of the suitable model in our studies based on the similar climate and geology as those in our five regions can provide somewhat base for estimating the DWEC/load for the watershed outside Japan; however, the high uncertainty is expected since environmental factors, such as baseflow concentration, climate, geology, and topography, are usually operated at a regional scale.

Acknowledgements

This study was funded by the Japan Science and Technology Agency, Core Research for Evolutional Science and Technology.

References:

- Ahearn DS, Sheibley RW, Dahlgren RA, Keller KE. Temporal dynamics of stream water chemistry in the last free-flowing river draining the western Sierra Nevada, California. *J Hydrol* 2004; 295: 47-63.
- Brezonik PL, Stadelmann TH. Analysis and predictive models of stormwater runoff volumes, loads, and pollutant concentrations from watersheds in the Twin Cities metropolitan area, Minnesota, USA. *Water Res* 2002; 36: 1743-57.
- Bunte K, MacDonald LH. Scale considerations and the detectability of sedimentary cumulative watershed effects. Report submitted to the U.S. Forest Service and the National Council for Air and Stream Improvement of the Paper Industry Council, Colorado State University, Fort Collins, CO, USA, 1998; 327.
- Cheng JD, Lin LL, Lu HS. Influences of forest on the water flows from headwater watersheds in Taiwan. *Forest Ecol Manag* 2002; 165: 11-28.
- Detenbeck NE, Elonen CM, Taylor DL, Anderson LE, Jichia TM, Batterman SL. Effects of hydrogeomorphic region, catchment storage and mature forest on baseflow and snowmelt stream water quality in second-order Lake Superior Basin tributaries. *Freshwater Biol* 2003; 48: 912-27.
- Edwards PJ, Williard KWJ, Kochenderfer JN. Sampling considerations for establishment of baseline loadings from forested watersheds for TMDL application. *Environ Monit Assess* 2003; 98: 201-23.

Elsenbeer H, Vertessy RA. Stormflow generation and flowpath characteristics in an Amazonian rainforest catchment. Hydrol Process 2000; 14: 2367-81.

Fisher GT, Katz BG. Analysis of urban storm-water runoff characteristics of four basins in the Baltimore metropolitan area, Maryland. U.S. Geological Survey Water Resources Investigation Report 1984; 84-4099.

Kunimatsu T, Kira T. Discharge of nutrients from forest lands and its control. Water Purif Liq Waste Treat 1986; 27: 721-30 (in Japanese).

Kunimatsu T, Sudo M. Measurement and evaluation of nutrient runoff loads from mountainous forested lands. J Japan Soc Water Environ 1997; 20: 810-5 (in Japanese).

Lee JH, Bang KW. Characterization of urban stormwater runoff. Water Res 2000; 34: 1773-1780.

Matsumoto Y, Okudaira K, Nishida K. Analysis of DOC determining processes of spring water based on hydrological data measurements during rain events. Proceedings of 39th Annual Meeting of Japan Society on Water Environment 2005; 10 (in Japanese).

McBroom M, Beasley RS, Chang M, Gowin B, Ice G. Runoff and sediment losses from annual and unusual storm events from the Alto experimental watersheds, Texas: 23 years after silvicultural treatments. <http://www.tucson.ars.ag.gov/icrw/proceedings/McBroom.pdf>, Oct. 2006; 607-13.

Miyata S, Kosugi K, Gomi T, Ueno M, Sidel RC, Onda Y, Mizuyama T. Occurrence of overland flow and its effect on storm discharge at a headwater catchment with water repellent soil. Hydrol Process 2007 (in press).

- 1 Niehus CA. Characterization of stormwater runoff in Sioux Falls, South Dakota,
2
3
4
5
6 2 1995-96. U.S. Geological Survey Water Resources Investigation Report. 1997;
7
8 97-4070.
9
- 10 4 Novotny V, Olem H. Water Quality: Prevention, Identification and Management of
11
12 Diffuse Pollution. Van Nostrand-Reinhold, New York, NY.1994.
13
14
- 15 6 Oguchi T, Saito K, Kadomura H, Grossman M. Fluvial geomorphology and
16
17 paleohydrology in Japan. Geomorphology 2001; 39: 1-9.
18
- 19 8 Ohno A, Nishida K, Haga H, Matsumoto Y. Humic organic matter and other DOC
20
21 constituent in a forested catchment. Proceedings of 39th Annual Meeting of Japan
22
23 Society on Water Environment 2005; 11 (in Japanese).
24
25 10
- 26 Ohte N, Tokuchi N, Shibata H, Tsujimura M, Tanaka T, Mitchell MJ.
27
28 Hydrobiogeochemistry of forest ecosystems in Japan: major themes and research
29
30 issues. Hydrol Process 2001; 15: 1771-89.
31
32
- 33 14 Okudaira K, Nishida K, Matsumoto Y. Distribution and fluctuation of dissolved
34
35 organic nitrogen in a mountainous catchment. Proceedings of 39th Annual Meeting
36
37 of Japan Society on Water Environment 2005; 8 (in Japanese).
38
39 16
- 40 Onda Y, Tsujimura, M, Fujihara J, Ito J. Runoff generation mechanisms in high-relief
41
42 mountainous watersheds with different underlying geology. J Hydrol 2006; 331:
43
44 659-673.
45
46
- 47 20 Oyanagi N, Urakawa R, Haibara K, Toda H. The dynamics of dissolved organic
48
49 nitrogen and dissolved organic carbon in a small watershed of established Japanese
50
51 cedar and cypress plantation. Jpn J Forest Environ 2002; 44: 11-20 (in Japanese).
52
53 22
- 54 Prych EA, Ebbert JC. Quantity and quality of storm runoff from three urban
55
56 catchments in Bellevue, Washington. U.S. Geological Survey Water Resources
57
58 Investigation Report 1986; 86-4192: 1-37.
59
60
61
62
63
64
65

- 1
2
3
4 Schreiber JD, Rebich RA, Cooper CM. Dynamics of diffuse pollution from US
5
6 2 southern watersheds. *Water Res* 2001; 35: 2534-42.
7
8
9 Shibata H, Mitsuhashi H, Miyake Y, Nakano S. Dissolved and particulate carbon
10
11 4 dynamics in a cool-temperate forested basin in northern Japan. *Hydrol Process*
12
13 2001; 15: 1817-28.
14
15 6 Shinomiya Y, Yamada T, Inagaki Y, Torii A. Characteristics of output of NO₃-N load
16
17 during storms in a mountainous headwater catchment of Shimanto river. *J Jpn Soc*
18
19 8 *Water Environ* 2006; 11: 723-9 (in Japanese).
20
21
22 Shirasuna H, Fukushima T, Matsushige K, Imai A, Ozaki N. Runoff and loads of
23
24 10 nutrients and heavy metal from an urbanized area. *Water Sci Technol* 2006; 53:
25
26 203-13.
27
28
29 12 Smith DR, Owens PR, Leytem AB, Warnemuende EA. Nutrient losses from manure
30
31 and fertilizer applications as impacted by time to first runoff event. *Environ Pollut*
32
33 14 2007; 147: 131-7.
34
35
36 Sonzogni WC, Chesters G, Coote DR, Jeffs DN, Konrad JC, Ostry RC, Taylor GD,
37
38 16 Fletcher TD, Wong THF, Breen PF, Duncan HP. Nitrogen composition in urban
39
40 runoff—implications for stormwater management. *Water Res* 2005;39: 1982-9.
41
42
43 18 Sun G, McNulty SG, Amatya DM, Skaggs RW, Swift JLW, Shepard JP, Riekerk H. A
44
45 comparison of the watershed hydrology of coastal forested wetlands and the
46
47 20 mountainous uplands in the Southern US. *J Hydrol* 2002; 263: 92-104.
48
49
50 Swistock BR, Edwards PJ, Wood F, DeWalle DR. Comparison of methods for
51
52 22 calculating solute exports from six forested Appalachian watersheds. *Hydrol*
53
54 *Process* 1997; 11: 655-99.
55
56
57
58
59
60
61
62
63
64
65

Tsujimura M, Onda Y, Harada D. The role of Horton overland flow in rainfall-runoff process in an unchanneled catchment covered by unmanaged Hinoki plantation. J Japan Soc Hydrol Water Resour 2006; 19: 17-24 (in Japanese).

Umemoto S, Komai Y, Inoue T. Runoff characteristics of nutrients in the forest streams in Hyogo Prefecture, Japan. Water Sci Technol 2001; 44: 151-6.

Vitousek PM, Reiners WA. Ecosystem succession and nutrient retention: a hypothesis. Bioscience 1975; 25: 376-81.

Walling DE, Webb BW. The Reliability of Suspended Sediment Load Data, in Erosion and Sediment Transport Measurement. IAHS Publication 1981; 133: 177-194.

Zhang Z, Fukushima T, Onda Y, Gomi T, Fukuyama T, Sidle RC, Kosugi K, Matsushige K. Nutrient runoff from forested watersheds in central Japan during typhoon storms: Implications for understanding runoff mechanisms during storm events. Hydrol Process 2007; 21: 1167-1178.

Zhang, Z. Doctoral Thesis, Graduate School of Life and Environmental Science, University of Tsukuba: Export of Carbon, Nitrogen, and Phosphorus from Forested Watersheds in Japan. 2007; Chapter 2: 12-31.

Table 1

2 Summary of monitored (A) event load data, (B) stormwater yields, and (C) DWECS

	TSS	DOC	PO ₄ -P	DTP	TP	NH ₄ -N	NO ₂ -N	NO ₃ -N	DTN	TN
<i>n</i>	72	72	69	69	67	69	69	69	69	67
(A)										
Min.	12.0	0.50	0	0.006	0.01	0	0	0.004	0.14	0.22
Max.	107.9E+6	380,574	100	271	757	485	160	57,133	58,489	68,140
Med.	11,622	397	0.15	1.83	6.56	2.55	1.22	128	222	294
Mean	1.6E+6	8,645	3.04	11.2	76.2	27.8	8.61	1,800	2,007	2,388
Std.	12.7E+6	45,458	12.6	34.6	177	79.2	23.8	7,274	7,516	8,642
(B)										
Min.	2.63	0.19	0	0.001	0.003	0	0	0.002	0.03	0.05
Max.	3.2E+6	11,463	8.05	23.5	610	162	32.7	1,689	1,853	2,316
Med.	7,565	411	0.12	0.73	2.21	1.56	0.69	64.0	95.3	160
Mean	70,694	838	0.59	2.94	33.8	10.8	2.50	258	323	456
Std.	382,405	1,566	1.28	4.68	90.3	26.8	5.76	382	442	586
(C)										
Min.	1.63	0.48	0	4.1E-05	0.001	0	0	0.002	0.02	0.14
Max.	2237	13.1	0.02	0.04	1.75	0.16	0.03	2.50	2.54	3.32
Med.	24.3	0.97	0.001	0.004	0.01	0.004	0.002	0.27	0.41	0.75
Mean	121	1.41	0.002	0.006	0.10	0.02	0.003	0.56	0.66	1.00
Std.	321	1.75	0.004	0.007	0.30	0.03	0.005	0.62	0.63	0.76
(D) Urban/Storm										
1 (USA)	184	-	0.20	0.20	0.58	-	-	0.53(NO ₂ +NO ₃)	-	3.08
2 (USA)	245	-	-	-	-	-	-	-	-	-
3 (Korea)	583	-	4.15	-	7.93	-	-	1.41	11.4(TKN)	-
4 (Korea)	162	-	1.49	-	3.53	-	-	1.33	4.68	-
5 (Korea)	365	-	1.35	-	5.5	-	-	6.05	1.4(TKN)	-

A unit is in kg event⁻¹, B in kg ha⁻¹ event⁻¹, and C in mg l⁻¹.

(D) is mean DWEC in other previous studies; ‘-’ means no data available.

2 D_1 from Brezonik and Stadelmann (2002), a study on the urban storm runoff in Twin Cities metropolitan area.

4 D_2 from Mcbroom et al. (2006), a study on the storm (Allison) in Alto experimental watersheds, Texas.

6 (D) 3,4, 5 from Lee and Bang (2000), a study on urban storm runoff. D_3 was high-density residence area; D_4 was industry area, and D_5 for undeveloped area.

8

10

12

14

16

18

20

22

24

Table 2

2 Pearson correlation coefficients (r) between (A) storm event loads/(B) DWECs and
 storm/watershed variables

	Storm variables					Watershed variables		
	TRA	DUR	MRI	ARI	LAS	Area	Slope	MCB
(A)								
TSS	0.623	0.497	0.603	0.310	0.376	0.303	0.082	
DOC	0.605	0.569	0.644	0.311	0.438	0.267	0.038	-0.184
PO ₄ -P	0.477	0.518	0.322	0.136	0.158	0.276	0.162	0.066
DTP	0.583	0.617	0.503	0.169	0.319	0.324	0.217	-0.221
TP	0.582	0.545	0.494	0.168	0.304	0.307	0.190	-0.286
NH ₄ -N	0.531	0.369	0.647	0.328	0.385	-0.039	-0.072	0.540
NO ₂ -N	0.512	0.579	0.531	0.260	0.396	0.304	0.191	-0.125
NO ₃ -N	0.397	0.533	0.373	0.016	0.241	0.432	0.113	0.203
DTN	0.475	0.592	0.437	0.070	0.309	0.417	0.055	-0.003
TN	0.556	0.605	0.511	0.166	0.391	0.370	0.088	-0.077
(B)								
TSS	0.166	-0.036	0.049	0.056	-0.087	0.185	-0.108	
DOC	-0.099	-0.131	-0.131	-0.032	-0.162	0.113	-0.538	0.495
PO ₄ -P	-0.048	0.048	-0.259	-0.144	-0.268	0.126	0.075	0.416
DTP	-0.205	-0.037	-0.439	-0.367	-0.363	0.114	0.084	0.485
TP	0.017	-0.005	-0.156	-0.142	-0.181	0.119	0.096	0.216
NH ₄ -N	0.203	0.006	0.346	0.192	0.155	-0.318	-0.243	0.413
NO ₂ -N	-0.151	0.099	-0.111	-0.074	-0.066	0.172	0.072	0.184
NO ₃ -N	-0.274	0.038	-0.347	-0.461	-0.285	0.411	-0.010	0.755
DTN	-0.358	0.020	-0.508	-0.519	-0.339	0.438	-0.205	0.773
TN	-0.181	0.070	-0.408	-0.377	-0.165	0.412	-0.156	0.767

4 Correlations significant at $p < 0.05$ were expressed in bold.

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65

TRA means total rainfall amount; DUR means rainfall duration; MRI means
2 maximum rainfall intensity; ARI means average rainfall intensity; LAS means the
days since the last event; MCB means baseflow concentration.

4

6

8

10

12

14

16

18

20

22

24

Table 3

2 Multiple linear regression equations for estimating runoff volumes (m^3)^a

Model	Constant	TRA	DUR	MRI	ARI	Area	<i>n</i>	<i>R</i> ²	MSE	MAPE
A^b		(cm)	(h)	(cm/h)	(cm/h)	(ha)				%
1	-2.269	-0.117	1.696	1.775	0.247	0.615	72	0.78	0.262	24
2	-1.508	0.609	1.033	1.122	-0.085	0.789	59	0.81	0.204	17
B										
Aichi	2.189	2.297	-1.063			-3.570	5	1.00	0.001	0
Kochi	0.869	4.656	5.554	-9.419		0.476	11	0.90	0.006	17
Mie	-0.490	1.255	0.173		0.227	1.177	31	0.97	0.036	7
Nagano	-2.299	-2.188	2.340	3.233		0.931	13	0.83	0.208	44
Tokyo	-3.392	0.402	1.064	2.809		0.851	12	0.96	0.097	10

^aBoth models have form: $\log(\text{runoff volume}) = \text{Constant} + \sum a_i \log(\text{predictor}$

4 variable);

^bModel 1 was based on the complete data set; model 2 were derived from excluding
6 events in Nagano.

^cRefer to table 2 for the meanings of acronyms.

8

10

12

14

16

Table 4

2 Multiple linear regression equation for estimating (A) loads and (B) concentrations

	Constant	TRA	DUR	MRI	ARI	LAS	Area	MCB	<i>n</i>	<i>R</i> ²	MSE	MAPE
(A)												
TSS	-1.482	1.115	0.228	2.702	-1.004	0.147	1.123		72	0.75	0.43	15
DOC	-2.748	-0.302	1.466	2.474	-0.208	0.122	0.692	0.358	72	0.78	0.27	29
PO ₄ -P	-2.788	1.031	0.799	3.051	-1.229	-0.309	1.010	1.185	66	0.55	1.21	109
DTP	-0.867	0.292	1.100	2.313	-0.914	0.021	0.719	0.613	69	0.73	0.32	17
TP	-1.235	1.079	0.041	3.598	-2.435	0.183	1.016	2.021	67	0.67	0.54	19
NH ₄ -N	0.390	-0.061	0.793	4.361	-2.695	0.300	0.172	1.437	62	0.59	1.22	78
NO ₂ -N	-2.540	-0.777	2.265	2.046	0.455	0.134	0.755	-0.303	65	0.67	0.60	33
NO ₃ -N	-0.374	-0.093	1.784	2.104	-0.465	-0.007	0.800	0.592	69	0.73	0.44	12
DTN	0.661	0.114	1.417	1.932	-0.739	0.115	0.800	0.262	69	0.75	0.33	9
TN	1.291	0.460	1.060	1.812	-0.924	0.273	0.855	0.005	67	0.80	0.26	7
(B)												
TSS	0.560	1.254	-1.234	0.690	-0.912	-0.039	0.492		72	0.24	0.37	48
DOC	-1.191	-0.199	0.003	0.541	-0.113	-0.040	0.075	0.629	72	0.37	0.02	155
PO ₄ -P	-0.453	1.063	-0.720	0.989	-1.068	-0.452	0.400	1.224	66	0.28	1.01	214
DTP	1.240	0.476	-0.384	0.179	-0.826	-0.119	0.076	0.635	69	0.28	0.20	181
TP	0.647	1.183	-1.473	1.680	-2.260	0.024	0.399	2.114	67	0.19	0.53	180
NH ₄ -N	1.541	-0.137	-0.424	2.603	-2.353	0.176	-0.387	1.129	62	0.41	0.88	194
NO ₂ -N	0.284	-0.953	0.731	0.904	0.237	-0.052	0.060	0.718	65	0.11	0.40	341
NO ₃ -N	0.945	-0.206	0.400	0.564	-0.283	-0.195	0.071	0.904	69	0.59	0.21	19
DTN	1.260	-0.075	0.142	0.526	-0.407	-0.092	0.039	0.876	69	0.63	0.09	9
TN	0.734	0.224	-0.160	0.589	-0.555	0.051	0.075	1.141	67	0.67	0.05	6

All equations have forms: $\log(\text{load, kg})/(\text{concentration, mg l}^{-1}) = \text{Constant} + \sum a_i$

4 $\log(\text{predictor variable})$.

Refer to table 2 for the meanings of acronyms.

6

Table 5 Range and median of stormwater yields by region grouping

Region	TSS	DOC	PO ₄ -P	DTP	TP	NH ₄ -N	NO ₂ -N	NO ₃ -N	DTN	TN
Aichi	111-96369	46-2488	0-0.30	0.07-0.67	0.13-1.89	1.34-161	0.05-1.15	0.58-841	4.28-1078	4.37-1175
	(7859)	(1329)	(0.02)	(0.14)	(1.00)	(64)	(0.23)	(10)	(125)	(254)
Kochi	57-71329	10-4777	0.003-8.1	0.06-23.50	0.07-185	0.01-48	0.02-13	3.98-1081	4.53-1374	5.13-1485
	(5227)	(478)	(0.94)	(1.95)	(2.97)	(7.17)	(1.04)	(71.1)	(95.3)	(126)
Mie	614-225980	90-2000	0-2.17	0.14-16.62	0.12-610	0-56	0-33	0.45-838	2.37-1028	25.6-2316
	(15263)	(618)	(0.18)	(1.97)	(3.99)	(4.94)	(1.38)	(105)	(153)	(322)
Nagano	2.6-4933	0.2-16	0-0.09	0.001-0.17	0.003-7.10	0-0.07	0-0.02	0.002-15.5	0.03-17.9	0.05-20.3
	(263)	(2.02)	(0.007)	(0.03)	(0.17)	(0.002)	(0.003)	(2.07)	(2.25)	(4.40)
Tokyo	24-55719	8.5-1028	0-3.87	0.01-8.69	0.10-16	0-2.05	0.03-3.46	12.8-1689	13.5-1853	15.0-1530
	(7405)	(214)	(0.36)	(1.69)	(1.42)	(0.09)	(0.34)	(630)	(641)	(324)

All units are in kg ha⁻¹ event⁻¹

Captions:

2 Fig. 1 Monthly precipitation (columns) and mean air temperature (lines) of the sites
(1979-2000). A means Aichi, K for Kochi, M for Mie, N for Nagano, and T for
Tokyo

Fig. 2 Box plots of DWECs, (mg L^{-1}) in each region

Fig. 3 Comparisons of R^2 (columns) and MAPE (lines) for (1) load models and (2)
concentration models; the symbols have the same means Fig.1

Fig. 4 The relationships between MCBs/runoff volume ($\text{m}^3 \text{ ha}^{-1} \text{ event}^{-1}$) and DWECs

10

12

14

16

18

20

22

24

Fig. 1 Monthly precipitation (columns) and mean air temperature (lines) of the sties
(1979-2000); A means Aichi, K for Kochi, M for Mie, N for Nagano, and T for Tokyo

Fig. 2 Box plots of discharge-weighted event concentrations (mg l^{-1}) in each region

Fig. 3 Comparisons of R^2 (columns) and MAPE (lines) for (1) load models and (2) concentration models, A means Aichi, K for Kochi, M for Mie, N for Nagano, and T for Tokyo

Fig. 4 MCBs vs. DWECs and runoff volume vs. DWECs.