Determination of groundwater recharge mechanism in the deep loessial unsaturated zone by environmental tracers

Zhi Li^{a*}, Xi Chen^a, Wenzhao Liu^a, Bingcheng Si^{a,b*}

^a State Key Laboratory of Soil Erosion and Dryland Farming on the Loess Plateau, College of Natural Resources and Environment, Northwest A&F University, Yangling 712100, China

^b Department of Soil Science, University of Saskatchewan, Saskatoon SK S7N 5A8, Canada

*Corresponding author.

Abstract: Studying the groundwater recharge mechanism in regions with thick unsaturated zone can greatly improve our understanding of hydrological processes since these regions have complex groundwater processes. This study attempted to discuss the groundwater recharge in a region covered by loess over 130 m deep in China's Loess Plateau. The water stable isotope, tritium and chloride in precipitation, groundwater and soil water were determined and used as inputs of mass balance methods. The tracer technique is found to be applicable and effective this region with thick unsaturated zone. The groundwater originates from rapid precipitation infiltration through some fast flow paths. The total recharge is likely to be 107 ± 55 mm yr⁻¹ accounting for $19 \pm 10\%$ of average annual precipitation, while the recharge from preferential flow accounts for $87 \pm 4\%$ of the total recharge. The identified recharge mechanism has important implication to groundwater management and recharge modeling for regions covered by thick loess.

Keywords: recharge mechanism; soil water movement; environmental tracers; mass balance method; Loess Plateau

1. Introduction

Understanding groundwater recharge mechanism can provide fundamental information for water resources management (Gleeson et al., 2016). However, this is difficult for the regions with thick unsaturated zone or large water storage that increases the complexity of hydrological process dynamics (Camacho Suarez et al., 2015). In such cases, selection of appropriate methods is very important. Although the techniques for groundwater recharge estimation can be classified into physical, tracer and numerical modeling approaches (Scanlon et al., 2002), the tracer technique has been the most successful one in estimating recharge, especially in dry regions (Allison et al., 1994; Gee and Hillel, 1988). Therefore, studying recharge mechanism in regions with thick unsaturated zone using tracer techniques can improve our understanding of groundwater processes.

The Loess Plateau of China, located in a subhumid to arid climate zone, is subject to severe water shortage since significant downward trend has been observed in streamflow and water table (Gao et al., 2015; Liang et al., 2015). Under such scenario, it is very important to understand the hydrological processes to effectively manage water resources. However, the groundwater recharge mechanism has been poorly understood due to the thick loessial soil with a depth up to 250 m (Fu, 1989). It is particularly difficult to investigate groundwater processes on the loess tableland since it is covered by loess over 130 m deep and the water table is greater than 30 m below the surface (Li et al., 2017). As gullies deeply cut through the bedrock, tablelands are isolated as islands. The groundwater should only originate from

precipitation since there is no flow from underlying or adjacent aquifers (Yan, 1986). Based on observation of soil moisture and water table, several earlier studies qualitatively concluded that piston flow should contribute little due to the existence of desiccation layers (Li, 1983) while preferential flow might be the dominant recharge mechanism (Wang, 1982; Yan, 1986). However, it is difficult to further quantify the recharge through those conventional methods.

Tracer methods have recently been used for recharge quantification since they can link precipitation with soil water and groundwater, despite the deep vadose zone. For example, Cheng et al. (2014) confirmed that groundwater should be mainly from infiltration of precipitation through rapid flow paths since the isotopic signature of groundwater is similar to precipitation, but different from deep soil water. Although the piston flow in some regions has been quantified by tritium peak and/or chloride mass balance methods in recent years (Gates et al., 2011; Huang and Pang, 2011; Lin and Wei, 2006), little is known about the contributions from preferential flow to total recharge. However, this information is very important for water resource management under the growing pressure of population growth and groundwater depletion.

In this study, we will discuss several questions related to the tracer technique and groundwater recharge in the loess tableland. Is the tracer technique applicable to regions with thick unsaturated zone? Which is the dominant recharge form of groundwater in these regions? How much can groundwater be recharged? This information can be very useful for similar regions with deep depositional environment.

2. Materials and Methods

2.1 Study area

The sampling sites are within the Heihe watershed with an area of 1504 km² (a first order tributary of the Jing River) (Fig.1). The soil is predominantly silt loam with silt contents greater than 50%. According to the observation of six weather stations from 1961 to 2012, the mean annual precipitation is 571 mm with about 55% falling between July and September, and the average annual temperature is 9.4 °C. The land uses includes farmland, forests and grasslands with farmlands occupying more than 50% of the study area, and rainfed farming is the main form of agriculture due to its limited water resources (Li et al., 2010).

[Fig.1 about here](#)

The hydrogeological conditions are quite similar across the study area (Fig.2). Above the mudstone and sandstone beds (N₂ and KZ series), there are three layers of loess cover, i.e. Wucheng Loess (Q1, lower Pleistocene), Lishi Loess (Q2, middle Pleistocene), and Malan Loess (Q3, upper Pleistocene). The Wucheng Loess has a thickness of 22–78 m and is the aquitard due to its low permeability. The Malan Loess is the top soil with a thickness of about 15 m. The depth to water table ranges from 30 to 100 m.

[Fig.2 about here](#)

2.2 Sampling and analytical methods

We collected soil samples from seven sites during 2012–2013 to determine soil water contents, chloride concentrations and isotopic compositions ($\delta^{18}\text{O}$ and $\delta^2\text{H}$).

91 Among the seven sites, three sites (S1 to S3) were farmlands with a long-term rotation
92 of wheat and maize, two sites were grasslands (S4 from natural grassland and S5 from
93 eight-year-old alfalfa) and the remaining two sites were 20-year old apple orchards
94 (S6 and S7), respectively. All the sites are flat and have no irrigation, which excludes
95 additional water inputs. The maximum distance between the upstream sampling site
96 and the downstream site is about 100 km. The large distance allows the effect of
97 possible spatial variations due to soil or climate to be considered.

98 At each site, a hollow-stem auger was used to obtain soil samples at a sampling
99 interval of 0.10 m to a depth of 10 m. Each sample was split into two halves to obtain
100 two sets of samples. For one set, soil water contents were determined by subsampling
101 a composite of two consecutive samples through the oven drying method, thus having
102 a sampling interval of 0.2 m (n=350). For the other set, a composite of every three
103 consecutive samples was made to obtain two subsamples for the determination of
104 chloride concentration and stable isotopes (n=210), respectively. The first subsample
105 was used to determine gravimetric water contents by oven drying method, and then 40
106 g of the dried sample was mixed with 60 ml double deionized water and subsequently
107 agitated for 8 h. Chloride concentration of the supernatant solution was analyzed
108 using ion chromatography (DIONEX ICS-1100, Thermal Fisher Scientific, USA).
109 Chloride concentration of the soil pore water was obtained by dividing chloride
110 concentration of the supernatant solution by the gravimetric soil water content and by
111 multiplying the mass ratio of the solution over the dried soil sample. For the second
112 subsample, soil water was extracted in the laboratory using the vacuum extraction

method (Araguás-Araguás et al., 1995; Stewart, 1972) for stable isotope measurements. Therefore, Cl concentrations and stable isotope fractions had a sampling interval of 0.3 m for each core.

Precipitation samples were collected at two sites respectively located at the upper and lower reach of the Heihe River, which incorporated the impacts of elevation and climate on isotopic compositions. Precipitation samples in 2012 and 2013 were collected by using a rain gauge. All rainfall water directly flowed into a bottle connected with the funnel, and a pingpang ball was put in the funnel to minimize evaporation. Groundwater was sampled twice per month at seven sites (six for spring and one for well) at proximity to the locations where one or more soil cores were taken. The spring samples were collected at springheads. The well was pumped to let it refill with fresh groundwater before sample collection. The runoff at the outlets of about 10 sub-watersheds was sampled after a wet event during August or September (n=50, [Table 1](#)) to determine the chloride concentration. All precipitation, groundwater and runoff samples were stored in 100-ml polyethylene bottles and refrigerated at temperatures of about 4°C before analysis. Stable isotopic compositions of the precipitation (n=123), groundwater (n=96), soil water samples (n=210) were determined using an LGR LIWA V2 isotopic liquid water analyzer with a precision of 0.5‰ for $\delta^2\text{H}$ and 0.1‰ for $\delta^{18}\text{O}$. Two groundwater samples were taken: One from a well (G7 in [Fig.1](#)) and the other from confined aquifer below the bedrock of unsaturated zone around G4 in [Fig.1](#). 600 ml groundwater was sampled for electrolytic enrichment before determination by an ultra-low-level scintillation

counter (Quantulus 1220, PerkinElmer, Singapore).

2.3 Interpreting groundwater recharge mechanism

2.4.1 Chloride mass balance

As chloride is a conservative element, either at the field or catchment scales, the chloride inputs from atmosphere ($P \cdot Cl_{pr}$) are equal to the sum of those in groundwater ($R_{tot} \cdot Cl_{gw}$) and runoff ($Q \cdot Cl_Q$) (Allison and Hughes, 1978; Dyck et al., 2003; Harrington et al., 2002; Song et al., 2006; Wood and Sanford, 1995).

$$P \cdot Cl_{pr} = R_{tot} \cdot Cl_{gw} + Q \cdot Cl_Q \quad (1)$$

where P is the mean annual precipitation (mm), Cl_{pr} is the mean annual chloride concentration in precipitation (mg L^{-1}); R_{tot} and Q are the mean annual total recharge and runoff (mm yr^{-1}), while Cl_{gw} and Cl_Q are the chloride concentration of groundwater and runoff, respectively (mg L^{-1}).

The total groundwater recharge R_{tot} estimated in Equation 1 may comprise different components. Specifically, if Cl_{sw} (chloride concentration in soil pore water below root zone) is similar to Cl_{gw} , piston flow can be assumed as the only recharge mechanism and the recharge rate can be directly estimated by Equation 1 (Allison and Hughes, 1978). However, if Cl_{sm} is much greater than Cl_{gw} , a preferential flow component may exist, and a two-component recharge process should be considered (Sharma and Hughes, 1985; Wood, 1999).

$$R_{tot} \cdot Cl_{gw} = R_d \cdot Cl_{sm} + R_{pf} \cdot Cl_{pf} \quad (2)$$

where R_{tot} , R_d and R_{pf} are the total recharge, recharge by piston flow and preferential flow, respectively (mm yr^{-1}); Cl_{pf} is the chloride concentration in preferential flow.

The contributions of piston and preferential flow to the total recharge can be calculated according to the two-component recharge model as follows:

$$f(R_{pf}) = (Cl_{sm} - Cl_{gw}) / (Cl_{sm} - Cl_{pf}) \quad (3)$$

$$f(R_d) = 1 - f(R_{pf}) \quad (4)$$

where $f(R_d)$ and $f(R_{pf})$ are the fractions of piston and preferential flow in total recharge, respectively.

2.4.2 Estimating precipitation-related variables

The precipitation-related variables in Equation 1 are the mean annual precipitation and chloride concentration in precipitation. The mean annual precipitation can be easily determined from the long-term record of precipitation (over 50 years), and is 571 mm for the period of 1961–2012. The chloride input flux Cl_{pr} is a key parameter, and it should be determined from an accurate long-term record.

So far, the most reliable data with a ‘long-term’ observation are those from the Acid Deposition Monitoring Network in East Asia (EANET). The data from Jiwozi village near Xi’an city, China (33°50’N, 108°48’E), were used to estimate the chloride inputs at the study site. Located in a rural area, the chloride records in precipitation represent the natural state with little perturbation of atmospheric pollution. About 100 km east of the study area, the annual mean precipitation of Jiwozi is about 573 mm, which is similar as that of the study area (571 mm yr⁻¹). Monthly chloride concentrations in precipitation have been recorded from 2001 to 2013. However, the data completeness is 67% and 51% for 2001 and 2002, and the record of 2003 with

complete measurement is greatly deviated from the regressed line of the other years (Fig.3). The data during 2004–2013 were thus used to estimate a volume-weighted average of chloride concentration as $1.0\pm0.4 \text{ mg L}^{-1}$.

Besides wet deposition, chloride inputs can also be derived from dry deposition and dust. However, the observation of dry deposition cannot be obtained. We, therefore, validated the reliability of the Cl flux by inverse calculation from the recharge rate estimated by tritium peak method. Our previous study showed that tritium contents in soil water were the largest at the depth of 7.2 m (Zhang et al., 2017), and the corresponding diffuse recharge was estimated as 25 mm yr^{-1} . As the chloride concentration in soil water is 29.2 mg L^{-1} (Table 2) and the mean annual precipitation is 571 mm yr^{-1} , the chloride content in bulk precipitation (including dry deposition) can be calculated as 1.3 mg L^{-1} . This value falls within the uncertainty interval of $1.0\pm0.4 \text{ mg L}^{-1}$ observed from EANET, which implies that the value of $1.0\pm0.4 \text{ mg L}^{-1}$ can represent the atmospheric chloride inputs of the study area.

Fig.3 about here

2.4.3 Estimating runoff-related variables

The runoff-related variables include runoff amount Q and the chloride concentration in runoff Cl_Q . Q was determined by the observation from runoff plots in Changwu Agro-Ecological experiment station starting from 2004. Seven runoff plots have a slope of 0.5° , width of 5 m and length of 20 m or 50 m, with a maize-wheat-fallow rotation. Annually, no more than nine rainfall events generate runoff and the runoff coefficients are 0.015 ± 0.022 (Gan, 2005; Mao, 2012). Therefore,

the observed runoff coefficient of 0.015 ± 0.022 were used in this study.

The chloride concentration in runoff on tableland has not been monitored in-situ. However, the runoff at the outlets of about ten sub-watersheds of the Heihe watershed have been sampled in August or September during 2012–2013, and their chloride concentration was determined as $6.3 \pm 4.0 \text{ mg L}^{-1}$ ($n=50$) (Chen, 2015). The chloride concentration in runoff is several times of that in precipitation, which has also been observed in some other catchments (Guan et al., 2010; Peck and Hurle, 1973).

2.4.4 Analyzing uncertainties in estimated recharge rates

As the chloride concentration in precipitation and runoff only had short-term observations and there are spatial variations in soil water (Table 1–2), the error propagation analysis was carried out to obtain an uncertainty interval. To estimate the total groundwater recharge by Equation 1, the runoff coefficient (0.015 ± 0.022), the chloride concentration in precipitation ($1.0 \pm 0.4 \text{ mg L}^{-1}$), groundwater ($4.8 \pm 0.9 \text{ mg L}^{-1}$) and runoff ($6.3 \pm 4.0 \text{ mg L}^{-1}$) will be considered (Table 1).

[Table 1 about here](#)

To quantify the contributions of piston and preferential flow to the total groundwater recharge (Equation 3–4), the chloride concentration in soil water ($29.2 \pm 5.6 \text{ mg L}^{-1}$, Table 2), preferential flow and groundwater were considered. It should be noted that the chloride concentration in preferential flow can vary between that in precipitation and that in surface runoff. However, due to the small runoff coefficients of 0.015 ± 0.022 and unlikely exchange of Cl between soil and water in fracture and fissures on the loess plateau, precipitation was used as the only water

sources of preferential flow. Therefore, the chloride concentration in preferential flow (Cl_{pf} in Equation 3) was assumed to be the same as that in precipitation, i.e. 1.0 ± 0.4 mg L⁻¹. According to Equation 3, if the chloride concentrations in preferential flow are higher than what we assumed, the contribution of preferential flow to the total recharge becomes greater. Therefore, the estimated proportion of preferential flow in this study only gives the lower bound.

Given the standard deviation of each component in Equation 2, the uncertainty in estimated groundwater recharge rates can be obtained through a first order perturbation analysis.

$$\Delta R_{tot}^2 = \left(\frac{\partial f}{\partial Cl_{pr}}\right)^2 \Delta Cl_{pr}^2 + \left(\frac{\partial f}{\partial Q}\right)^2 \Delta Q^2 + \left(\frac{\partial f}{\partial Cl_Q}\right)^2 \Delta Cl_Q^2 + \left(\frac{\partial f}{\partial Cl_{gw}}\right)^2 \Delta Cl_{gw}^2 \quad (5)$$

$$\Delta R_{pf}^2 = \left(\frac{\partial f}{\partial Cl_{sm}}\right)^2 \Delta Cl_{sm}^2 + \left(\frac{\partial f}{\partial Cl_{gw}}\right)^2 \Delta Cl_{gw}^2 + \left(\frac{\partial f}{\partial Cl_{pr}}\right)^2 \Delta Cl_{pr}^2 \quad (6)$$

where $\Delta(\cdot)$ represents the standard deviation of a certain variable, $\partial f / \partial(\cdot)$ represents the partial derivative of f with respect to a certain variable.

3. Results

3.1 Critical depth for steady state in soil profiles

We firstly used water content, chloride concentration and isotope data from the 10-m soil profiles to identify the critical depth below which tracer concentration are under steady state, so that we can determine the tracer concentration used for piston flow. Soil water contents within the depth of 0–4 m are highly variable for each of the seven soil cores, which could be a result of varying root water uptake and rainfall infiltration (Fig.4). However, those within the depth of 4–10 m fluctuate around a constant value, indicating reduced seasonal variation of root water uptake and rainfall

infiltration. Therefore, the active soil water layers can be defined as the 0–4 m profiles and their thickness across the region seem to be similar.

[Fig.4 about here](#)

The averaged $\delta^{18}\text{O}$ values of soil water for shallow layers (0–4 m) vary between -12.1‰ and -7.2‰ , while those for deeper layers (>4 m) are less variable (between -10.4‰ and -7.7‰) ([Fig.4](#)). The variations among soil profile could be a reflection of evaporation, rainfall infiltration and piston displacement of water over time. Within the top 2 m, there is still in the zone of influence from evaporation. In the meantime, in the coarse loessial soil, large rainfall events (generally light water) could penetrate to a depth of 4 m, which may result in depleted soil water. Rainfall infiltration could also push old water (enriched water) downward. Therefore, soil water at different depths could have large differences, depending on the source of the water (old water or new rainfall infiltration).

[Table 2 about here](#)

The chloride concentration is variable in shallow layers ([Fig.4](#)), but stabilizes below 6 m. The stabilization depth is greater than that of soil water and isotopic composition since chloride concentration is a long-term average while water contents and $\delta^{18}\text{O}$ are more easily affected by seasonal variations in precipitation inputs and root water uptake (Huang and Gallichand, 2006; Li and Huang, 2008). Therefore, 6 m can be regarded as a critical depth, below which groundwater recharge is in a steady state with a constant rate.

Although water contents, isotopic compositions and chloride concentration

become stable at 4 or 6 m, Zhang et al. (2017) showed that the peak tritium concentration of soil water corresponding the precipitation tritium inputs of 1963 was at the depth of about 8 m. Therefore, 8 m is used as the critical depth to further exclude the potential impacts of land use change and fertilizer application in the past 50 years. The chloride concentration below 8 m is applied to calculate piston flow in the following sections.

3.2 Recharge components

We directly compared the isotopic compositions and chloride concentration within 8–10 m soil profiles with those in groundwater to determine the recharge components. On average, the $\delta^{18}\text{O}$ differences between groundwater and S3, S5–7 are less than 1‰, while the other profiles have relatively higher $\delta^{18}\text{O}$ values than groundwater (Table 1–2). However, t-test ($p=0.05$) shows that the isotopic compositions of groundwater are different from those of soil water within the depth of 8–10 m for all profiles except for S7. Chloride concentration in soil is much greater than that in groundwater and precipitation. Therefore, recharge from piston flow cannot be the only source of groundwater. Further, as precipitation and groundwater have similar chloride concentrations, recharge from preferential flow may account for a great proportion of total recharge. In addition, the tritium concentration in the confined groundwater is not detectable while that in the shallow groundwater is 2.5 TU, which confirms the contribution from precipitation.

We carried out dual isotope comparison between precipitation, soil water (>8 m) and groundwater to further analyze their relationships (Fig.5). Except for a few data

points from S3 and S6 profiles are very close to the Local Meteoric Water Line (LMWL), most data points of soil water fall below LMWL ($\delta^2\text{H}=7.36\delta^{18}\text{O}+3.59$, $R^2=0.94$), implying that they are from precipitation but enriched by evaporation. The groundwater isotopic compositions are very close to LMWL, suggesting that groundwater may originate from quick precipitation inputs. Furthermore, the isotopic compositions of groundwater are similar to those of precipitation in August and September (Fig.5).

[Fig.5 about here](#)

3.3 Groundwater recharge rates

Based on the observation of chloride concentration, precipitation and runoff amount (Table 1), the regional average recharge can be calculated using Equation 1 and the uncertainty interval can be given by Equation 5 (Table 3). Overall, the total recharge rate is $107\pm55 \text{ mm yr}^{-1}$, which accounts for $19\pm10\%$ of the annual precipitation. The great uncertainty in recharge rate mainly comes from the variations in chloride input flux. For example, keeping the other variables unchanged, the annual mean recharge rate is 36 mm yr^{-1} and 154 mm yr^{-1} respectively for the lower bound (0.6 mg L^{-1}) and upper bound (1.4 mg L^{-1}) of chloride input flux.

[Table 3 about here](#)

The contributions of each recharge component to the total recharge were estimated by Equation 3–4 and the uncertainty can be quantified by Equation 6 (Table 3). The contribution of preferential flow to the total recharge is $87\pm4\%$; accordingly, the corresponding contributions of piston flow to the total recharge is $13\pm4\%$. To

validate the results from chloride mass balance, the oxygen isotopes of different water samples were also used as inputs of [Equations 3–4 and 6](#). The isotope-based mean contribution of preferential flow to the total recharge is $86\pm1\%$, which is very similar to that from chloride.

4. Discussion

4.1 Is the mass balance method applicable?

To use the mass balance method, two assumptions related to the steady state in the hydrological system should be validated. The first is related to the steady state between precipitation and groundwater, a prerequisite for [Equation 1](#) and [Equation 7](#) to quantify the recharge rate from precipitation (Leaney et al., 2003; Scanlon et al., 2009). The second is the steady state of chloride concentration in soil water that corresponds only to precipitation input and is free of the impacts from fertilizer application and land use change (Guan et al., 2013; Peck and Hurle, 1973). This forms the basis of [Equation 2](#) to quantify the recharge rate from piston flow in soil.

Here we used the groundwater tritium concentration in our study and the results of a tritium profile from our previous study (Zhang et al., 2017) to verify the two assumptions. The peak tritium contents corresponding to 1963 precipitation were detected at the depth of 8 m, which implies that modern soil water has not reached water table. For the steady state between precipitation and groundwater, the confined groundwater is tritium free whereas the shallow groundwater has a low but detectable tritium concentration (2.5 TU), which implies that the shallow groundwater consists of post-bomb water. Further, the post-bomb water can only be from precipitation since

modern soil water has not reached groundwater (Zhang et al., 2017). The post-bomb groundwater from modern precipitation can be well mixed with the pre-bomb groundwater by the flowpath from the center to the edge of tablelands because of differences in elevation. For the second assumption about steady state of chloride concentration in soil, it can be easily verified by the 8-m depth of peak tritium contents. The 8-m depth suggests that the impacts of fertilizer application and land use change starting in the 1980s on chloride concentration cannot reach 8-m depth; thus, the chloride concentration below 8 m can be considered as steady state.

Subsequently, the chloride concentration below 8 m represents water older than 50 years; thus, it exhibits an age mismatch with that in modern precipitation. To solve this problem, the variability of annual precipitation in the past four centuries on the Loess Plateau was examined. Tan et al. (2014) found that the annual precipitation, controlled by the Asian summer monsoon, fluctuated with time but presented no significant trend over time. As the chloride flux is closely related to the distance from ocean (Hutton, 1976), the long-term average chloride concentration in the precipitation from the Asian summer monsoon would not change. Therefore, the chloride concentration in soil water below 8 m can match that in modern precipitation. Furthermore, the chloride concentration in soil water within the depth of 8–45 m in the study area is $19.2 \pm 7.8 \text{ mg L}^{-1}$ (personal communication with Dr. Lu Yanwei). The small variations in the chloride concentration imply that the chloride inputs are stable during the past decades or even centuries. Thus, the age mismatch in the two components of Equation 2 may not violate the steady state condition.

4.2 Where does groundwater come from?

As the rivers are located in the gullies, with elevations lower than tablelands by several hundred meters, it is unlikely that the groundwater in tablelands is recharged by runoff. Therefore, only two water sources for tableland-groundwater, i.e. precipitation or deep confined water. According to the hydrogeological characteristics, it is highly unlikely that deep confined groundwater flows upward through the thick red clay (22–78 m in thickness, [Fig.2](#)) with low permeability to recharge shallow groundwater, rather than discharging directly to lower gullies (Tan et al., 2016). This conclusion is confirmed by the groundwater tritium contents in our study since groundwater from the confined aquifer is tritium free while the shallow groundwater has detectable tritium content. Further, the water table responded to rainy season with an increase of about 0.3 m in Changwu tableland within our study area (Wang et al., 2010). Therefore, local precipitation is likely the recharge source for groundwater in shallow loess aquifers.

The feasibility of precipitation to recharge groundwater through the deep unsaturated zone is still highly debatable; therefore, it is necessary to determine how precipitation recharges groundwater. Our results show that groundwater is likely to be from episodic recharge during August and September. This conclusion is consistent with the progressive understanding of groundwater recharge in literature. Lin and Wei (2006) found that the soil water below 15-m depth was almost tritium free while the groundwater with a water table of 20–30 m deep has a tritium content of 34.4–43.4 TU, suggesting piston flow was not the only recharge mechanism. Gates et al. (2011)

concluded that drainage through the unsaturated zone contributed little to spring discharge in the Zhifangou Catchment due to the distinct isotopic signatures between spring water and soil pore water. Furthermore, Tan et al. (2016) observed that the groundwater isotopic compositions had a clear response to precipitation in rainy season in Gansu Province, which is very close to our study area.

The groundwater is thus likely from local precipitation by preferential flow, which can be further validated by the tritium content in groundwater. The groundwater from pre-bomb events should be tritium free; however, the results from this study as well as those distributed widely across CLP contradicted with this assumption. Specifically, the tritium contents greater than 10 TU have been detected in the other regions (Huang et al., 2014; Lin and Wei, 2006; Liu et al., 2009; Ma et al., 2006; Su et al., 2009; Tan et al., 2016). In this study, the tritium contents of groundwater are very low though preferential flow dominates groundwater recharge. This controversial issue can be interpreted by the sharp comparison between the small recharge and huge water storage in the thick aquifer. Assuming groundwater as a well-mixed reservoir (Le Gal La Salle et al., 2001), the long-term averaged renewal rate is 0.2% per year based on the tritium data. Therefore, the percentages of modern groundwater from the past 50 years should be about 10%, and the large groundwater storage dilutes the tritium concentration. Furthermore, the high concentration of precipitation tritium around 1963 has gone through radioactive decay that substantially reduces the tritium contents from bomb water and the tritium contents in modern precipitation are low.

The identified recharge mechanism is similar as regions covered by loess in other countries. For example, the ~8 m depth tritium and nitrate profiles across two loess hillslopes exhibit multiple peaks in Pullman in southeastern Washington State, USA, which indicates that piston flow is not the sole flow process, and further simulation indicated that deeper peaks resulted from preferential vertical and/or lateral flow (O'Brien et al., 1996).

4.3 How much is groundwater recharged?

The estimated total recharge rate falls within the ranges from literature for the Loess Plateau (9–100 mm yr⁻¹, 2–22% of average annual precipitation, [Table 4](#)). However, the recharge rates from the earlier work are mostly in form of piston flow, while those in this study are the sum of piston and preferential flow.

[Table 4 about here](#)

The estimated piston flow in this study is about 14 mm yr⁻¹, accounting for 2% of mean annual precipitation (calculated from [Table 3](#)) and 13±4% of the total recharge. These values are smaller than most of the earlier work using tracer method (9–100 mm yr⁻¹, [Table 4](#)); however, they are very close to those based on numerical models. For example, Huang and Gallichand (2006) estimated the deep percolation for farmland and apple orchard as 9.3–18.3 mm accounting for 2–3% of mean annual precipitation, and Zhang et al. (2007) simulated the deep percolation for farmland as 17 mm accounting for 3% of mean annual precipitation. This may be because the two modeling studies only considered piston flow and the similar values imply that the estimated recharge for piston flow in this study is reliable.

The above differences may be due to the following two reasons: First, the chloride concentration in precipitation used by earlier work is greater than this study (1.0 mg L⁻¹), such as 1.7 mg L⁻¹ or 1.4 mg L⁻¹, which are also estimated from EANET without excluding the incomplete observation (missing values). Annual estimates of volume-weighted Cl concentration from incomplete observation could be biased considering the strong variability in the monthly Cl concentrations in the precipitation. It is prudent to exclude, in the calculation of mean annual Cl concentration, those years with more than 10% missing values.

Second, after comparing the chloride and isotope in precipitation, soil water and groundwater, preferential flow was taken into account and the two-component mass balance method was used. However, most of earlier studies did not incorporate groundwater as a variable in the mass balance equation, and directly calculated the recharge based on methods for piston flow. The techniques only based on unsaturated-zone data provide estimates of potential recharge, whereas those based on groundwater data generally provide estimates of actual recharge (Scanlon et al., 2002). Therefore, by incorporation of groundwater, the results of this study likely reflect the actual values.

4.4 What is the implication to groundwater recharge monitoring and modeling?

This study has important implication for groundwater recharge modeling in the region. A vadose zone deeper than 30 m is very common on the Loess Plateau and in many parts of the world. As a result, there is a huge volume of available water storage in the vadose zone. Normally, we assume all the water participates in transport, and

transit time (or residence time) can be calculated as the time it takes to replace all the water in the vadose zone. By measuring soil water contents within the vadose zone, we could estimate soil water storage in the zone. Given the deep drainage rate, we can calculate the residence time or transit time of water and chemicals within the zone. As demonstrated by Edmunds and Smedley (2000), the transit time can be as long as hundreds to thousands of years. However, if the available storage is probably bypassed through active preferential flow system, the calculated transit time would be erroneous, substantially underestimating water renewal and surface-applied chemical arrival time at the ground water. This would also invalidate the conventional methodology for monitoring and modeling the hydrologic system. New paradigms of monitoring and modeling the hydrologic system may be required in the thick vadose zone.

Though the recharge in this thick unsaturated zone is mainly from preferential flow, the pathway and the trigger are poorly understood. Most groundwater recharge models assume that recharge is predominately piston flow in arid and semi-arid zones. Performing well for regions where piston flow dominates, those models may fail for preferential flow-dominated recharge regions. Some models do take preferential flow into consideration; however, their treatment of the preferential flow is largely empirical, making it difficult to extrapolate the model results in space and time. Therefore, the key issue for a model is to quantify the piston flow under all land use and to determine the threshold for precipitation to generate preferential flow. For the latter, when and how does water flow through macropores should be fully understood

to parameterize the model (Beven and Germann, 2013; Nimmo, 2012).

5. Conclusion

Environmental tracer methods including stable isotopes and chloride balance methods were used to interpret the relationships among precipitation, soil water and groundwater in the tableland of China's Loess Plateau. The isotopic compositions of groundwater were different from those of deep soil water but were similar to those of precipitation; meanwhile, the chloride concentration in soil pore water was much greater than that in groundwater and precipitation. In addition, the groundwater has detectable tritium concentration. Therefore, groundwater was very likely from the rapid input of precipitation through preferential flow. Quantitatively, the estimated total recharge is likely to be $107 \pm 55 \text{ mm yr}^{-1}$ accounting for about $19 \pm 10\%$ of average annual precipitation, among which preferential flow accounted for $87 \pm 4\%$ of the total recharge. The assumption of steady state between precipitation and groundwater or the steady state of soil water at depth are valid, and the isotope or chloride mass balance methods are thus applicable to the study region, which provides new tool for groundwater recharge estimation in regions with depositional environment. The identified main recharge form and quantified recharge rate on the Loess Plateau with deep vadose zone provide useful information for groundwater management and recharge modeling.

Conflict of interest

The authors declare that they have no conflict interest.

Acknowledgements

This study is jointly funded by the National Science Foundation of China

(51179161&41371233), Special-Funds of Scientific Research Programs of State Key Laboratory of Soil Erosion and Dryland Farming on the Loess Plateau (A314021403-C2 & K318009902-1423), Chinese Universities Scientific Fund (2452015105) and equipment grant for the “Thousand Talent Plan” from the Northwest A&F University. The constructive suggestions from the three reviewers are greatly appreciated.

References:

- Allison G, Hughes M. The use of environmental chloride and tritium to estimate total recharge to an unconfined aquifer. *Australian Journal of Soil Research* 1978; 16: 181-195.
- Allison GB, Gee GW, Tyler SW. Vadose-Zone Techniques for Estimating Groundwater Recharge in Arid and Semiarid Regions. *Soil Science Society of America Journal* 1994; 58: 6-14.
- Araguás-Araguás L, Rozanski K, Gonfiantini R, Louvat D. Isotope effects accompanying vacuum extraction of soil water for stable isotope analyses. *Journal of Hydrology* 1995; 168: 159-171.
- Beven K, Germann P. Macropores and water flow in soils revisited. *Water Resources Research* 2013; 49: 3071-3092.
- Camacho Suarez VV, Saraiva Okello AML, Wenninger JW, Uhlenbrook S. Understanding runoff processes in a semi-arid environment through isotope and hydrochemical hydrograph separations. *Hydrol. Earth Syst. Sci.* 2015; 19: 4183-4199.
- Chen X. Study on Water Circulation Mechanism for The Tableland-Gully Region of Loess Plateau by Using Environmental Tracers. Master. Northwest A&F University, Yangling, 2015, pp. 56.
- Cheng LP, Liu WZ, Li Z, Chen J. Study of soil water movement and groundwater recharge for the loess tableland using environmental tracers. *Transactions of the ASABE* 2014; 57: 23-30.
- Dyck MF, Kachanoski RG, de Jong E. Long-term Movement of a Chloride Tracer under Transient, Semi-Arid Conditions. *Soil Science Society of America Journal* 2003; 67: 471-477.
- Edmunds WM, Smedley PL. Residence time indicators in groundwater: the East Midlands Triassic sandstone aquifer. *Applied Geochemistry* 2000; 15: 737-752.
- Fu B. Soil erosion and its control in the loess plateau of China. *Soil Use and Management* 1989; 5: 76-82.
- Gan Z. The process and characteristic of water balance of farmland on the tableland of the Loess Plateau. Soil Science. Master. Institute of Soil and Water Conservation, Chinese Academy of Science, Yangling, 2005, pp. 66.
- Gao Z, Zhang L, Cheng L, Zhang X, Cowan T, Cai W, et al. Groundwater storage trends in the Loess Plateau of China estimated from streamflow records. *Journal of Hydrology* 2015; 530: 281-290.
- Gates JB, Scanlon BR, Mu XM, Zhang L. Impacts of soil conservation on groundwater recharge in the semi-arid Loess Plateau, China. *Hydrogeology Journal* 2011; 19: 865-875.
- Gee GW, Hillel D. Groundwater recharge in arid regions: Review and critique of estimation methods. *Hydrological Processes* 1988; 2: 255-266.
- Gleeson T, Befus KM, Jasechko S, Luijendijk E, Cardenas MB. The global volume and distribution of modern groundwater. *Nature Geosci* 2016; 9: 161-167.
- Guan H, Hutson J, Ding Z, Love A, Simmons CT, Deng Z. Principal component analysis of watershed hydrochemical response to forest clearance and its usefulness for chloride mass balance applications. *Water Resources Research* 2013; 49: 4362-4378.

529 Guan H, Love AJ, Simmons CT, Hutson J, Ding Z. Catchment conceptualisation for examining
 530 applicability of chloride mass balance method in an area with historical forest clearance. *Hydrol.*
 531 *Earth Syst. Sci.* 2010; 14: 1233-1245.
 532 Harrington GA, Cook PG, Herczeg AL. Spatial and Temporal Variability of Ground Water Recharge in
 533 Central Australia: A Tracer Approach. *Ground Water* 2002; 40: 518-527.
 534 Huang MB, Gallichand J. Use of the SHAW model to assess soil water recovery after apple trees in the
 535 gully region of the Loess Plateau, China. *Agricultural Water Management* 2006; 85: 67-76.
 536 Huang T, Pang Z. Estimating groundwater recharge following land-use change using chloride mass
 537 balance of soil profiles: a case study at Guyuan and Xifeng in the Loess Plateau of China.
 538 *Hydrogeology Journal* 2011; 19: 177-186.
 539 Huang X, Liu Q, Xue Z, Liu J. The characteristics of groundwater isotopes in upper reach plain of
 540 Qingshui River, Ningxia. *Journal of Arid Land Resources and Environment* 2014; 28: 143-148.
 541 Hutton JT. Chloride in rainwater in relation to distance from ocean. *Search* 1976; 7: 207-208.
 542 Le Gal La Salle C, Marlin C, Leduc C, Taupin JD, Massault M, Favreau G. Renewal rate estimation of
 543 groundwater based on radioactive tracers (^3H , ^{14}C) in an unconfined aquifer in a semi-arid area,
 544 Iullemeden Basin, Niger. *Journal of Hydrology* 2001; 254: 145-156.
 545 Leaney FW, Herczeg AL, Walker GR. Salinization of a Fresh Palaeo-Ground Water Resource by
 546 Enhanced Recharge. *Ground Water* 2003; 41: 84-92.
 547 Lei XY. Characteristics of loess pore distribution in north Shaanxi and east Gansu. *Chinese Science*
 548 *Bulletin* 1985; 30: 656-661.
 549 Lei XY. Pore type and collapsibility of loess in China. *Science China (Series B)* 1987: 1309-1318.
 550 Li Y, Huang M. Pasture yield and soil water depletion of continuous growing alfalfa in the Loess Plateau
 551 of China. *Agriculture, Ecosystems & Environment* 2008; 124: 24-32.
 552 Li YF. The relationship between permeability and porosity in loess of China. Beijing: Geological
 553 publishing house, 1994.
 554 Li YS. The properties of water cycle in soil and their effect on water cycle for land in the loess region.
 555 *Acta Ecologica Sinica* 1983; 3: 91-101.
 556 Li Z, Lin X, Coles AE, Chen X. Catchment-scale surface water-groundwater connectivity on China's
 557 Loess Plateau. *CATENA* 2017; 152: 268-276.
 558 Li Z, Liu W, Zhang X, Zheng F. Assessing and regulating the impacts of climate change on water
 559 resources in the Heihe watershed on the Loess Plateau of China. *Science China Earth Sciences*
 560 2010; 53: 710-720.
 561 Liang W, Bai D, Wang F, Fu B, Yan J, Wang S, et al. Quantifying the impacts of climate change and
 562 ecological restoration on streamflow changes based on a Budyko hydrological model in China's
 563 Loess Plateau. *Water Resources Research* 2015; 51: 6500-6519.
 564 Lin R, Wei K. Tritium profiles of pore water in the Chinese loess unsaturated zone: Implications for
 565 estimation of groundwater recharge. *Journal of Hydrology* 2006; 328: 192-199.
 566 Liu X, Liu B, Yang S. Driving Force of Sediment Production and Potential of Sediment Reduction in the
 567 Gullied Rolling Loess Area. *Yellow River* 2014; 36: 1-3.
 568 Liu X, Zhou B, Wei Y. Analysis on groundwater based on environmental isotopes in the Longdong Basin.
 569 *Arid Zone Research* 2009; 26: 804-810.
 570 Ma Z, Niu G, Liu F, Hou G, Dang X, Su Y. Isotope evidence of strong runoff zone of karst groundwater in
 571 eastern Weibei, Shaanxi, China, and its renewability evaluation. *Geological Bulletin of China*
 572 2006; 25: 756-761.

573 Mao T. Process of runoff-sediment in Wangdong Watershed on tableland of the Loess Plateau. Soil
574 Science. Master. Northwest A&F University, Yangling, 2012, pp. 74.

575 Nimmo JR. Preferential flow occurs in unsaturated conditions. *Hydrological Processes* 2012; 26:
576 786-789.

577 O'Brien R, Keller CK, Smith JL. Multiple Tracers of Shallow Ground-Water Flow and Recharge in Hilly
578 Loess. *Ground Water* 1996; 34: 675-682.

579 Peck AJ, Hurle DH. Chloride balance of some farmed and forested catchments in southwestern Australia.
580 *Water Resources Research* 1973; 9: 648-657.

581 Scanlon BR, Healy RW, Cook PG. Choosing appropriate techniques for quantifying groundwater
582 recharge. *Hydrogeology Journal* 2002; 10: 18-39.

583 Scanlon BR, Stonestrom DA, Reedy RC, Leaney FW, Gates J, Cresswell RG. Inventories and
584 mobilization of unsaturated zone sulfate, fluoride, and chloride related to land use change in
585 semiarid regions, southwestern United States and Australia. *Water Resources Research* 2009;
586 45: W00A18.

587 Sharma ML, Hughes MW. Groundwater recharge estimation using chloride, deuterium and oxygen-18
588 profiles in the deep coastal sands of Western Australia. *Journal of Hydrology* 1985; 81: 93-109.

589 Song X, Liu X, Xia J, Yu J, Tang C. A study of interaction between surface water and groundwater using
590 environmental isotope in Huaisha River basin. *Science in China Series D: Earth Sciences* 2006;
591 49: 1299-1310.

592 Stewart GL. Clay-Water Interaction, the Behavior of ^3H and ^2H in Adsorbed Water, and the Isotope
593 Effect. *Soil Sci. Soc. Am. J.* 1972; 36: 421-426.

594 Su X, Wan Y, Dong W, Hou G. Hydraulic relationship between Malianhe river and groundwater:
595 Hydrogeochemical and isotopic evidences. *Journal of Jilin University (Earth Science Edition)*
596 2009; 39: 1087-1094.

597 Tan H, Wen X, Rao W, Bradd J, Huang J. Temporal variation of stable isotopes in a
598 precipitation-groundwater system: implications for determining the mechanism of groundwater
599 recharge in high mountain-hills of the Loess Plateau, China. *Hydrological Processes* 2016; 30:
600 1491-1505.

601 Tan L, An Z, Huh C, Cai Y, Shen C, Shiao L, et al. Cyclic precipitation variation on the western Loess
602 Plateau of China during the past four centuries. *Scientific Reports* 2014; 4: 6381.

603 Wang DQ. The characteristics of groundwater recharge on the Luochuan tableland.
604 *Hydrogeology&Engineering Geology* 1982: 1-8.

605 Wang R, Liu W, Zhao X. Dynamic characteristics of groundwater level on Changwu tableland.
606 *Agricultural Research in the Aird Areas* 2010; 28: 48-52.

607 Wood WW. Use and misuse of the chloride-mass balance method in estimating ground water recharge.
608 *Ground Water* 1999; 37: 2-3.

609 Wood WW, Sanford WE. Chemical and Isotopic Methods for Quantifying Ground-Water Recharge in a
610 Regional, Semiarid Environment. *Ground Water* 1995; 33: 458-468.

611 Yan TB. Discussion on the renewal period of groundwater on the Loess Tableland.
612 *Hydrogeology&Engineering Geology* 1986: 42-44.

613 Zhang S, Simelton E, Lövdahl L, Grip H, Chen D. Simulated long-term effects of different soil
614 management regimes on the water balance in the Loess Plateau, China. *Field Crops Research*
615 2007; 100: 311-319.

616 Zhang ZQ, Evaristo J, Li Z, Si BC, McDonnell JJ. Tritium analysis shows apple trees may be transpiring

Fig.1 Sample sites for precipitation (P), soil (S) and groundwater (G) on the loess tableland within the Heihe watershed

Fig.2 Hydrogeological profiles in the study area

Fig.3 Observed annual precipitation and its volume-weighted chloride concentration in Jiwozi site of EANET (circle means incomplete measurements)

Fig.4 Water contents (left), isotopic compositions (middle) and chloride concentration (right) for soil profiles under different vegetation. The vertical line with error bar is the average values of groundwater.

Fig.5 The dual stable isotopic compositions of precipitation, deep soil water (>8 m) and groundwater sampled during 2012-2013. Numbers in the figure denote the month of a year; circle size denotes the monthly mean precipitation amount.

Table 1. Isotopic compositions and chloride concentration in precipitation, groundwater and runoff

		$\delta^{18}\text{O}$, ‰	$\delta^2\text{H}$, ‰	Cl, mg L ⁻¹	No. of samples
Precipitation	Average-arithmetic	-8.1	-56.3	—	123
	Standard deviation - arithmetic	4.1	31.1	—	
	Average-amount weighted	-10.4	-72.3	1.0 [†]	
	Standard deviation -amount weighted	1.8	13.1	0.4	
Groundwater	Average	-10.2	-71.5	4.8	96
	Standard deviation	0.5	3.9	0.9	
Runoff	Average	-9.2	-67.2	6.3	50
	Standard deviation	0.9	6.6	4.0	

[†]Cl concentration in precipitation, estimated from EANET according to the relationships between annual mean precipitation amount and chloride concentration

Table 2. Water contents, isotopic compositions and chloride concentration in seven soil profiles

Profiles	Land use	Depth, m	Water contents, %		$\delta^{18}\text{O}$, ‰		Cl, mg L ⁻¹	
			0-10 m	8-10 m	0-10 m	8-10 m	0-10 m	8-10 m
S1	Farmland	10	18.3	18.6	-8.4	-7.3	87.7	26.7
S2	Farmland	10	16.4	17.7	-7.5	-8.2	34.9	23.5
S3	Farmland	10	17.2	17.6	-10.7	-10.8	29.3	26.9
S4	Natural grassland	10	20.0	20.0	-10.1	-7.7	25.9	23.4
S5	Alfalfa	10	15.7	15.9	-9.6	-9.4	43.6	31.2
S6	Apple orchard	10	15.5	12.9	-9.5	-9.3	34.1	37.0
S7	Apple orchard	10	14.2	13.8	-8.8	-9.8	286.4	35.8
Average			16.7	16.6	-9.2	-9.0	77.4	29.2
Standard deviation			2.0	2.6	1.1	1.2	94.5	5.6

Table 3. Chloride-based estimation of groundwater recharge

Total recharge rate, mm		Percentage of preferential flow, %		Percentage of piston, %	
Average	Error	Average	Error	Average	Error
107	±55	87	±4	13	±4

Table 4. Estimated groundwater recharge in form of piston flow on the Loess Plateau

No	Location	Methods	Land use	Mean P	Isotope slope			Cl concentration, mg L ⁻¹			Piston recharge		Publication
					P	G	S	P	G	S	mm yr ⁻¹	% (R/P)	
1	Zhifangou Catchment, Shaanxi	CMB&Isotope	Five sites: two farmlands, one tree plantation, one hillslope with introduced shrubs, one natural forest vegetation	500	7.5	6.3	3.5	1.4	—	6.3-25.9	55-90	11-18	Gates, et al. (2011)
2	Hequan, Guyuan	CMB&Isotope	Five sites: two natural grasslands, two farmlands, one alfalfa	450	7.5	—	7.5	1.7	8.5	7.7-89.1	50-100	11-22	Huang and Pang (2013)
3	Wudan, Inner Mongolia	Tritium profiles	No vegetation	360	—	—	—	—	—	—	47	13	Lin and Wei (2006)
4	Pingding, Shanxi	Tritium profiles	No vegetation	550	—	—	—	—	—	—	68	12	Lin and Wei (2006)
5	Xifeng, Gansu	CMB	Winter wheat	523	—	—	—	1.7	—	27.3	33	6	Huang and Pang (2011)
6	Changwu, Shaanxi	Modeling	Apple orchard and wheat	545	—	—	—	—	—	—	9.3-18.3	2-3	Huang and Gallichand (2006)
7	Luochuan, Shaanxi	Modeling	Farmland	568	—	—	—	—	—	—	17	3	Zhang et al. (2007)
8	Heihe watershed, Gansu & Shaanxi	CMB&Isotope	Seven sites: three farmlands, two grasslands and two apple orchards	584	7.4	6.6	5.7	1.0	4.8	22.9-37.8	14	2	This study

P, precipitation; G, groundwater; S, soil water; R, recharge.

Isotope slopes of precipitation in study 1 and 2 are all from Xi'an City.