Singe Image-based Data-driven Indoor Scenes Modeling

Abstract

With a single input indoor image (including sofa, tea table, etc.), a 3D scene can be reconstructed from a single image using an existing model library in three stages: image analysis, model retrieval and relevance feedback. In the image analysis stage, we obtain the object information from the input image using geometric reasoning technology combined with an image segmentation method. In the model retrieval stage, line drawings are extracted from 2D objects and 3D models by using different line rendering methods. We exploit various tokens to represent local features and then organize them together as a star-graph to show a global description. By comparing similarity among the encoded line drawings, models are retrieved from the model library. Also, for a better user experience, we add a relevance feedback stage following the retrieval stage. The Support Vector Machine method is used to conduct the feedback operation. After this stage, the retrieved models are in conformance with the image semantic. The 3D scene is then reconstructed. Experimental results show that, driven by the given model library, indoor scenes modeling from a single image could be achieved automatically and efficiently.

Keywords: data-driven, indoor scenes modeling, single image, image analysis, model retrieval, relevance feedback

1. Introduction

With the development of 3D acquisition and modeling technology, sharable 3D models are rapidly increasing. Repositories like Trimble/Google 3D warehouse[1] and TurboSquid[2] contain millions of digital models. On the basis of previous work, people deform these models to make them conform with new design requirements using the existing digital geometric content reasonably and repeatedly. It not only greatly reduces the rigmarole work, but also largely shortens the period of design and modeling. All of these factors have important value for the development of modeling technologies[3] [4] [5].

Since 3D model reconstruction from a single image has always been a ill-posed problem, it is difficult to directly construct the scene from images. However, many existing libraries contain a large number of useful surface models, from which similar models can be retrieved to reconstruct the virtual scene. From this point of view, we present a new approach for model-driven indoor scene modeling from single image. Since color images contain many geometric cues, in the first image analysis stage, geometric reasoning is combined with the image segmentation method to obtain the main object information from indoor scene images. The extracted object information can be used in the following retrieval stage. In the model retrieval stage, the idea from sketch-based retrieval[6] [7] is borrowed. In our method, since 2D objects and 3D models can all be represented by line drawings, similar models can easily be obtained from the model library by comparing their similarity. In line drawing representation, we propose a novel feature encoding method, which hierarchically combines global and local features together to represent a line drawing. In this way, similar 3D models can be retrieved reasonably. In addition, retrieved models might not be semantically reasonable. We, therefore, amend the retrieval result using relevance feedback for better

results. This stage brings user into the modeling procedure, and makes the reconstructed scene be more similar to the original image semantic.

Contribution. Our main contribution includes the following:

- (1) With the support of existing model libraries, an approach for 3D indoor scenes reconstruction from a single image is presented. This method reconstructs objects from the scene automatically and efficiently.
- (2) We propose a novel feature encoding method for line drawings. In this encoding method, not only local features but also structured global features are represented. It converts the clutter of pixel data into an ordered expression in line with the human visual perception, and the retrieval precision is improved accordingly.

2. Related works

Image-based 3D reconstruction. Image-based modeling is an ideal way for constructing a 3D world in people's mind. Traditional image-based modeling technologies require one to take photos from different viewpoints for one scene and then use technologies such as stereo vision to construct 3D scenes [8] [9]. However, the inconvenience of taking several photos for a scene leads to limitations of these methods. Therefore, methods for single-image-based modeling technology would be more widely accepted, since a single scene image is usually available. In the computer vision field, traditional single-image-based modeling methods construct a 3D scene using cues like lightness [10], texture [11], focal length [12], etc. However, these methods always have strict restrictions for object properties, such as shapes and light reflection in a scene. They are only

available for certain scenes. In subsequent studies, some researchers attempt to add interactions to simplify the reconstruction problem [13] [14] [2]. Many of these methods construct the scene through manually setting vanishing points and geometric invariant for an image. However, they also have limitations in that only certain geometries and basic planes can be constructed. In our method, based on the existing model library, we could reconstruct a more reasonable scene from a single image.

Model-driven 3D shape modeling. In recent years, data-driven modeling based on the model library has become an emerging modeling technology [3] [4] [15] [16], since the number of 3D models on the Internet is rapidly increasing. Many studies have developed modeling technologies for a single object. In these studies, there are three categories according to various input items.

In the first category, people transform models guided by images. Chaudhuri et al. [3] introduce data-driven suggestions for 3D modeling which allows the artist to benefit from customized examples that stimulate creativity. They describe shape and retrieval and shape correspondence techniques for creative prototyping of 3D models. Further research can be found in paper [4], where they introduce assembly-based modeling which is a promising approach to broadening the accessibility of 3D modeling. In assembly-based modeling, new models are assembled from shape components extracted from a database. A probabilistic reasoning approach is introduced to the problem of identification of relevant components to be presented to the user. Given a repository of shapes, they learn a probabilistic graphical model that encodes semantic and geometric relationships among shape components. A similar approach based on the photo is introduced by Xu et al [17]. They introduce an algorithm for 3D object modeling where the user draws creative inspiration from an object captured in a single photograph. They use the photo as the guidance to retrieve the model parts to deform models and finally to reconstruct a model.

Another category of methods starts from sketches. Some researchers have implemented sketch-based model retrieval technologies [7] [6]. With the sketches as input, they retrieve similar models in the model library. However, these kinds of methods pay more attention to the increase of retrieval precision, rather than the modeling itself. Some people use sketches as the guidance to construct 3D models based on the model library. They provide a new direction for single object modeling. Fan et al. [18] present a novel sketch-based modeling system which allows novice users to create 3D custom models by assembling parts based on a database of pre-segmented 3D models. Different from previous systems, their system supports the user with visualized and meaningful shadow guidance under his strokes dynamically to guide the user to convey his design concept easily and quickly. Xie et al. [19] rethink model design as navigating through different possible combinations of part assemblies based on a large collection of pre-segmented 3D models and propose an interactive sketch-to-design system, where the user sketches prominent features of parts to combine.

In the third category, people use collected point cloud data or estimate image depth to help complete the reconstruction.

With cloud data, Shen et al. [20] introduce a technique that allows quick conversion of acquired low-quality data from consumer-level scanning devices to high-quality 3D models with labeled semantic parts and their assembly reasonably close to the underlying geometry. However, only a single object could be reconstructed in this kind of methods.

In addition, apart from sketch-based retrieval technology, other methods have certain limitations on the model library. When objects in different categories have to be modeled, the library has to be built by categories. In the scene reconstruction, since there are several objects in one scene, it's difficult to exploit the above methods. Since the different objects in a scene are not marked, we don't know how to map them to the model categories.

Model-driven 3D scenes modeling. With the development of technology, some people proposed scene modeling approaches based on the model library which are classified into two categories according to different input items.

One category of methods is for sketches. Based on the existing model library, sketch retrieval technology is combined with sketch modeling technology to construct a scene in some approaches. Cases such as various objects in one scene can be handled. However, there are still certain requirement on the order and category for input sketches. Lee et al. [21] introduce a modeling system for parts composition with a sketching interface which needs considerable user interaction. In the paper [22], Shin et al. propose a system that takes simple 2D sketches of models in a scene as input for 3D scene construction. The system then automatically identifies corresponding models in a database and puts them in the appropriate location and posture so that their appearance matches the user's input sketches. However, their system need extensive interaction when drawing sketches and retrieval algorithms also need to be improved. Further research has [23] leveraged more precise retrieval methods, but the limitations are similar.

In the other category of methods, with the help of model library, people use the collected point cloud data to construct a scene. Shao et al. [24] present an interactive approach to the semantic modeling of indoor scenes with a consumer-level RGBD camera. Meanwhile, Nan et al. [25] present an algorithm for recognition and reconstruction of scanned 3D indoor scenes. Chen et al. [26] also present a novel solution to automatic semantic modeling of indoor scenes from a sparse set of low-quality RGB-D images and Contextual relationships learned from the 3D database are used to constrain reconstruction, ensuring semantic compatibility between both object models and parts. In these methods, researchers usually segment the scene image with point cloud data. Each object in the image can then be located and a similar object is easily retrieved in the model library. When every object is fixed, the scene reconstruction is completed accordingly. Although these studies have achieved some success, there are special requirements for the input. In addition, this technology is inconvenient for most people, especially non-professional who users would find it difficult to draw the scene sketch and would be unable to collect point cloud data without professional devices. We note that s-

ingle scene images are relatively easy obtained from the real world, therefore, if the scene reconstruction can be completed from a single image with the help of an existing model library, the method would be more valuable and widely available for common users.

We start with this motivation to carry out research about reconstruction from a single image. Based on this idea, a version of this paper has been published in Graphics Interface 2015 [27]. In that paper, we first analyze the image and separate furniture out from the image background. Then model retrieval is then conducted to get models from the library. The retrieved models are put in the room according to the relative position and finally reconstruction is completed. Compared with the conference version, in this paper, 1) due to the semantic conflict of retrieval, our approach adds relevance feedback to solve this problem; 2) we performed a more comprehensive survey of related work; 3) we conducted more experiments; and 4) more technical details, discussions, and analyses are provided.

3. Overview

The input of our algorithm is an image I taken from a single viewpoint and model library S containing many furniture models. In our method, we would reconstruct the scene in a three-stage process involving image analysis, model retrieval and relevance feedback. Figure 1 shows the overview of our approach.

Image analysis. In this stage, the main goal is to extract objects from image I for the convenience of following retrieval. The corresponding objects are represented as $(O_1, \dots, O_n)$. In this paper, geometric reasoning [28] [29] is used combined with image segmentation technology to complete the analysis task. First, by the geometric reasoning method, camera parameters as well as cuboids of objects in image can be obtained. The scene image is then over-segmented using the mean-shift image segmentation method [30], in which the over-segmented areas are merged to obtain the target objects from the input image with the guidance of the cuboids that we just obtained. Detailed steps are introduced in Section 4.

Model retrieval. Our main task in this stage is to retrieve similar models based on obtained objects to reconstruct a scene. To handle the work, we first exploit the idea of sketch retrieval [7]. Different line rendering methods are used to extract line drawings for image objects and models in the model library S . In order to facilitate the model retrieval, line drawings are then encoded into a special feature representation. Inspired by the image organization method Patch Net [31], we propose a new feature encoding method. In this paper, we use tokens to represent the local feature in a line drawing and then form the tokens into a star-graph for global feature representation. Next, guided by the viewpoint information from the image analysis stage, each object from the input image can be retrieved in the model library with a graph-matching method. Finally, we place the models into the 3D space of the scene to finish the reconstruction. The details are shown in Section 5.

Relevance feedback. According to users' intention, we correct the unsatisfactory results using relevance feedback method to obtain a more reasonable 3D scene. The reconstructed scene should be more similar to the original image. In this stage, the user first labels the top k retrieved results, labelling the satisfied as positive and the unsatisfied as negative. The system then uses a relatively simple SVM method [32] [33] to train the labeled data and ranks the results again. If a user is still unsatisfied with the current results, he could do the labeling again and the system could conduct feedback once more. Finally, user-selected models are put onto the relative position of 3D room. The scene reconstruction is then completed. Details of this stage is referenced in Section 6.

In addition, we present the details of the experiment analysis in Section 7. Section 8 is a summary and forecast.

4. Image Analysis

A single input image may contain several objects and objects that are retrieved one by one in the model retrieval stage. This requires us to know the information about objects in an image. In this section, we will introduce the details about the image analysis. Limitations are discussed in Section 7.3.

4.1. Geometric Reasoning from a Single Image

The most direct way to obtain the object information in an image is to conduct the image segmentation. However, we find that existing segmentation methods have difficulty in handling complex scenes and we want more information about the image such as the viewpoint of the scene. As a result, a simple image segmentation method cannot meet our requirements. Taking this into account, we need more cues for image analysis. We know that there is information about geometric relationship between lines, parallax relationship and contours in an image. With these passive cues, we can easily reason the geometric locations of objects in a scene. These studies of geometric reasoning based on the geometrical characteristics in 3D space, have achieved a series of research results [28] [29] [34] [35]. By using geometric reasoning, we could obtain the object information from an image. In our approach, we use these reasoning methods [28] [29] to analyze the image, obtaining the viewpoint of a scene and the cuboids of the main objects. Scene viewpoints help to select line drawings in the retrieval stage and object cuboids are used to extract objects from image after image segmentation.

For an input image in Figure 2(a), we first extract line segments using Canny edge detector, link edge pixels and fit line segments in Figure 2(b). Vanishing points could be recovered from these line segments. Using a line-sweeping algorithm, we divide these line segments into three groups and form one plane from each line segment group which represents an orientation map (as shown in Figure 2(c)) in the scene area. Different map combinations form a number of cuboids which are possible objects in a scene [28] (as shown in Figure 2(d)). Room hypotheses (as shown in Figure 2(e)) are also generated from line segments in a way similar to the method described in Lee

Figure 1: An overview of our approach. With an input indoor scene image, the output 3D scene is reconstructed with a three-stage process: image analysis, model retrieval and relevance feedback.

et al. [29]. We next examine exhaustive combinations of a room hypothesis with several cuboids to form a series of scene configuration hypotheses. However, not all scene configurations are reasonable. So we check them to reject invalid configurations by spatial reasoning which define volumetric constraints of spatial exclusion between walls and objects or between the objects themselves. By evaluating scene configurations [28], the most reasonable scene configuration hypothesis could be obtained. In our experiment, if an automatic analysis result is unreasonable, we interactively locate one satisfied cuboid and our system then iteratively performs spatial reasoning and scene configuration evaluating the location of other cuboids. Finally we get a satisfied scene configuration and main objects cuboids are shown in Figure 2(f).

4.2. Objects Obtaining

We have just obtained object locations from images in Section 4.1. But it is not enough to guide the following retrieval. In the retrieval stage, we need other information such as object contours. We use the image segmentation method to over-segment an input image. Although the over-segmented results can hardly show the main objects in a scene, with the regulation of cuboids in Section 4.1, we can obtain each main object information by the method of proportionally combining over-segment areas in a cuboid. Figure 3 shows an overview of the process for locating the objects. In our method, we first use mean-shift method [30] to over-segment the image. For the input image in Figure 2(a), we get the over-segmented result that is shown in Figure 3(a). These over-segmented areas are then combined together proportionally into the cuboids with the result that is shown in Figure 3(b). Through these these operations, objects ($O_1, \dots, O_n$) are extracted from the image. Figure 3(c) shows the final segmentation results for this input image. Four objects are extracted to be candidates for following modeling.

5. Model retrieval

After obtaining the main objects ($O_1, \dots, O_n$) from the input image I , we can retrieve similar models in the model library S . For each retrieval operation, one object O_i is handled. In most

Figure 3: Object obtaining process. (a) Over-segmented result for the input image using mean-shift method. (b) Combination result with the constraint of cuboids. (c) Main objects we extract from the image.

cases, when people want to retrieve 3D models from 2D objects, they always compare the similarity between them. Therefore, in the model retrieval stage, our main problems are: 1) How to represent both the 2D objects and 3D models in a consistent form and conduct feature analysis and 2) What matching mechanism can we use to perform the retrieval efficiently. Our methods for solving above two problems will be introduced below.

5.1. Consistent feature representation for 2D objects and 3D models

We use the 2D object information as a query to conduct model retrieval. To get a more reasonable result, we need to represent the features of 2D object and 3D model at the same level. Inspired by the sketch retrieval methods [7], we extract line drawings from image objects O_i and render lines for models in model library in order to represent them in the same way of line drawing. In line rendering for objects, we use coherence line drawing [36](CLD) method for the task. However, since we use different line-rendering methods for 2D objects and 3D models, properties of these two line drawings are apparently different. Taking this into consideration, we treat the 2D object line drawings by operations of resizing, smoothing and eroding to make them have the same characteristic as 3D model line drawings. Figure 4 shows the main objects obtained from Figure 3, line drawings by coherent line drawing method and final line drawings after our procession. As the results indicate, major line feature information for an object can be shown in the line drawing in this way. We then use the suggestive contours [37] (SC) method to render the models into line drawings. Figure 5 gives the line drawing examples for several models in library. We can also see that it represents the model feature details well.

Figure 2: Geometric reasoning process. (a) Input image. (b) Extracted line segments. (c) Three orientation maps in reasoning process. (d) Cube hypotheses. (e) Room hypotheses. (f) Cuboids for main objects in the image.

Figure 4: Line drawings extracted from objects in Figure 3. (a) Input objects. (b) Line drawings by CLD method. (c) Line drawings after processing.

Figure 5: Line drawings of models in library. (a) Input models. (b) Line drawings by SC method.

are introduced as follows. First, we collect all black pixels of the line drawing image. Then, for one certain pixel, we delete pixels around it whose Manhattan distance is less than 17. This procedure is performed iteratively until a series of sparse points is left. With these sparse points as centers, we sample patches from image and finally obtain many 35*35 size patches. We next exploit the Daisy descriptor [42] to calculate each local feature of patches and cluster patches using k-means clustering method. In this paper, we get 150 cluster centers which are known as 150 tokens. Figure 6 shows some tokens of our result.

Figure 6: Examples of tokens learned from line drawings. Each token is a clustering center representing local feature.

With these tokens, we can easily represent an input line drawing image using token replacement method by replacing local patches with the most similar tokens. For details, at each time, we calculate Daisy features of all patches and each patch is centered by one black pixel in the line drawing image. Comparing all patches with the 150 tokens, we get the most similar pair and replace the patch with its token pair. We then delete the replaced patch in original line drawing and iterate until almost all patches are replaced. We proceed token replacement for line drawings in Figure 4 and 5, and the result are shown in Figure 7. We can see that the structure of the line drawings do not change too much after the replacement.

However, those steps merely describe the local feature and lack global descriptions. In order to show the line drawings from an integral and structural perspective, we combine the local and global features together to make a representation. The star-graph [40] is used to organize the discrete tokens. In this way, the whole line drawing can be represented by a global structure. Details about star-graph are as follows. First, we find the center point of an object, from which we draw a line to each token center. By this means, star-graphs are constructed. The simple schematic diagram is shown in Figure 8. We represent each star-graph as $G=(V,E)$, V is the nodes (each token is a node, as color blocks in Figure 8), E is the edges (each edge

Figure 7: Token replacement for line drawings. Original line drawings are at left and token replacement results are at right. (a) Token replacement results for 2D objects. (b) Token replacement results for example models.

is a vector from object center to token center, as lines in Figure 8). For visibility of the star-graph, we gives a part of tokens and same token color represent the same token. We can see that the star-graphs have a good structure to organize the local features.

Figure 8: Star-graph schematic diagrams for line drawings. In each star-graph, color blocks represent tokens, and lines which link graph center with tokens represent distance vectors. (a) Replaced line drawings(left) and their corresponding star-graph(right) for 2D objects. (b) Replaced line drawings(left) and their corresponding star-graph(right) for example models.

With these encoding approach, we can prepare all the models off-line in the model library. For each model in the library, we render the model projection under different viewpoints and then encode it using this approach. Although this task is time consuming, it is off-line work and we don't spend too much time when retrieving. It will significantly improve the efficiency of our retrieval task much.

5.2. Retrieval process

After above feature representation, we begin the retrieval stage. In traditional sketched-based model retrieval or image-based single-object reconstruction [17] [18] [7], there is a limited amount of prior knowledge to use. To get a better retrieval

result, researchers always project the model in many different viewpoints in order to compare different projection features. This method complicates retrieval process and also increases calculation. However, in section 4.1, we mentioned that an image includes many cues, based on which we can reason the geometric information of that image to obtain the scene viewpoints. With the known viewpoint, several viewpoints can be selected from the library and calculation can be simplified greatly when comparing the projection features. Besides, for the following retrieval, since we represent the features into star-graphs, retrieval can be processed by graph-matching approach. Next, we introduce the details of these two works.

5.2.1. Viewpoint selection

In 2D image, the camera position relative to a scene has direct impact on the distributions of vanishing points. Reversely, if we know the vanishing points, it's easy to obtain the camera position. According to geometric reasoning result in sections 4.1, we could estimate three vanishing points by extending three line sets in Figure 2(b). 2D cuboids on the image plane can be seen as the perspective projection of cuboids in 3D space. Under these conditions, we could calculate the scene viewpoint with known vanishing points. Details are introduced as follows.

Figure 9: Schematic drawings for how we obtain the scene viewpoint. (a) Three vanishing points of the image. (b) Schematic drawing for parallel lines projection. (c) Front view of the image in three-point perspective. (d) Side view of the image.

We obtained three vanishing points V_x, V_y, V_z from geometric reasoning result, as Figure 9(a) shows. Figure 9(b) is the schematic drawing for formation of vanishing points. Projection of two parallel lines in 3D space extends with intersection at vanishing point. The line linking the vanishing point and viewpoint is parallel with the original two lines in 3D space. Suppose $QXYZ$ is local object coordinate system and coordinate origin Q has projection point Q' on image projection plane in Figure 9(c). Starting from Q' we draw lines to the three vanishing points V_x, V_y, V_z on image plan, $Q'V_x, Q'V_y, Q'V_z$ can be seen as projection coordinate axes of $QXYZ$. With the vanishing points V_x, V_y, V_z as vertices, we plot a triangle $\Delta V_x V_y V_z$. For each triangle edge, we construct three hemispheres that intersect at one point, which is known as viewpoint of the scene in 3D space. Figure 9(d) shows the side view of the image plan and viewpoint E has orthographic projection E' on the plan. According to Figure 9(b), we know that the line between viewpoint and one vanishing point is parallel with the corresponding coordinate axis, i.e. in Figure 9(d), $EV_z \parallel QZ$ (QZ is the z axis of local object coordinate system). Viewpoint E is at the normal of projection plane through the projection point E' . Distance

472 D from viewpoint E to projection plane could be calculated by
473 formula (1).

$$D^2 = |AE'| \times |E'V_z| = |BE'| \times |E'V_y| = |CE'| \times |E'V_x| \quad (1)$$

474 Next, we move the local object coordinate system $QXYZ$
475 towards projection plane along the projection direction so that
476 Q and Q' are at the same position. Assuming that Q and Q' are
477 the same point which makes no difference on view angles to the
478 scene, for the reason that changing distance between a scene
479 and projection plane merely changes the size of projection on
480 the plane. In Figure 9(d), $\mathbf{n}$ is normal vector of the projection
481 plane and α, β, γ are angles between $\mathbf{n}$ and three coordinate axes
482 x, y, z of $QXYZ$ (We only shows γ angle in the figure). Then we
483 could obtain that,

$$\cos \gamma = \frac{D}{|EV_z|} = D / \text{sqr}t(D^2 + |E'V_z|^2) \quad (2)$$

484 The same procedure may be adapted to obtain the follow-
485 ing.

$$\begin{aligned} \cos \alpha &= \frac{D}{|EV_x|} = D / \text{sqr}t(D^2 + |E'V_x|^2) \\ \cos \beta &= \frac{D}{|EV_y|} = D / \text{sqr}t(D^2 + |E'V_y|^2) \end{aligned} \quad (3)$$

486 Suppose that point E' has the position of $E'(X_{E'}, Y_{E'}, Z_{E'})$
487 relative to the coordinate system $QXYZ$ and i_z is the unit vec-
488 tor on $E'V_z$. We can then obtain from Figure 9(d) that $Z_{E'} =$
489 $|Q'E' \cdot i_z| \cdot \sin \gamma$, where $Q'E' \cdot i_z$ is the projection vector of $Q'E'$
490 in i_z direction. Then,

$$Z_{E'} = |Q'E' \cdot i_z| \cdot \sin \gamma = |Q'E' \cdot i_z| \times \sqrt{1 - \cos^2 \gamma} \quad (4)$$

491 The same procedure may be adapted to obtain the follow-
492 ing,

$$\begin{aligned} X_{E'} &= |Q'E' \cdot i_x| \cdot \sin \alpha = |Q'E' \cdot i_x| \times \sqrt{1 - \cos^2 \alpha} \\ Y_{E'} &= |Q'E' \cdot i_y| \cdot \sin \beta = |Q'E' \cdot i_y| \times \sqrt{1 - \cos^2 \beta} \end{aligned} \quad (5)$$

493 Hence position of the viewpoint E relative to $QXYZ$ is as
494 follows.

$$\begin{aligned} E(X_E, Y_E, Z_E) &= \\ E(X_{E'} - D \times \cos \alpha, Y_{E'} - D \times \cos \beta, Z_{E'} - D \times \cos \gamma) \end{aligned} \quad (6)$$

495 We next transform the position into a tuple $\langle \varphi, \theta \rangle$ under the
496 corresponding sphere coordinate system representing deflection
497 angle of the viewpoint to scene models, φ is the horizontal de-
498 flection angle and θ is vertical deflection angle.

$$\varphi = \arctan \frac{\sqrt{X_E^2 + Y_E^2}}{Z_E} \quad (7)$$

$$\theta = \frac{\pi}{2} - \arctan \frac{Y_E}{X_E}$$

499 After obtaining the scene viewpoint, all the 3D models should
500 be under a similar viewpoint so that they are consistent with the

501 query object. In the following retrieval process, for the permis-
502 sion of error range, we choose projection line drawings within
503 the range of $\langle \varphi + \varepsilon, \theta + \sigma \rangle$, ε, σ is a certain amount of error.
504 That is, in the model library that have been pre-processed, we
505 simply choose projections under feasible viewpoints. We ran-
506 domly select several models in library and Figure 10 gives mod-
507 el projections under similar viewpoints.

Figure 10: Model projections under similar viewpoints. (a) Object from image. (b) Model projections under similar viewpoints with the object.

508 5.2.2. graph-matching-based model retrieval

Figure 11: Star-graph-matching based model retrieval. (a) Retrieval. (b) Star-graph matching. (c) Retrieval result ranked by similarity from top to bottom.

509 After calculating the viewpoint of a scene, we choose model
510 star-graphs from library in a permissible error range. Based on
511 graph matching, model retrieval is conducted shown in Figure
512 11(a). Firstly, we define the involved variables. Suppose q as
513 object line drawing and S_k as one of n selected line drawings in
514 library. Then in Figure 11(b), the corresponding star-graph is
515 $G^q = (V^q, E^q)$ and $G^{S_k} = (V^{S_k}, E^{S_k})$. The similarity between the
516 object q and projection S_k can be calculated with formula (8).

$$P(G^q, G^{S_k}) = \sum_i \max_j P(V_j^{S_k} | V_i^q) P(E_j^{S_k} | E_i^q) \quad (8)$$

517 Where $P(\cdot, \cdot)$ is a normalized distance value that measures
518 the similarity between two star-graphs. We can view it as a
519 probability of similarity. V_i^q and $V_j^{S_k}$ are nodes in graphs, known
520 as tokens. E_i^q and $E_j^{S_k}$ are vectors from graph center to token
521 positions. Using them, we calculate the token feature similarity
522 term using the following formula.

$$P(V_j^{S_k} | V_i^q) = \frac{1}{1 + \exp(-\|V_i^q - V_j^{S_k}\|)} \quad (9)$$

523 The token location similarity term can be obtained by the
524 following formula.

$$P(E_j^{S_k}|E_i^q) = \exp(-(E_j^{S_k} - E_i^q)^T S_L^{-1} (E_j^{S_k} - E_i^q)) \quad (10)$$

Here, S_L is a constant covariance matrix to allow for some deviations in patch locations.

We introduce the details of the star-graph matching in the following. First, for each query token in G^q , we seek for D tokens at the approximate location in G^{S_k} . Here D is much smaller than the number of total tokens. Then, in the D tokens, we select the most similar token with the query token in G^q , using both feature and location similarity term to measure the token similarity probability. Finally, we accumulate similarity probabilities for all query tokens in G^q . The value represents the graph similarity between G^q and G^{S_k} .

For higher retrieval precision, we then select the top M similar graphs from above results to calculate the similarity conversely. That means, for each graph G^{S_k} in the top M , above method is used again to get the $P(G^{S_k}, G^q)$ between all M graphs G^{S_k} and the query graph G^q . We then obtain the final similarity probability P for that query graph in formula (11). The highest score responds to the most similar model in the model library.

$$P = \omega_1 P(G^q, G^{S_k}) + \omega_2 P(G^{S_k}, G^q) \quad (11)$$

Where G^q is the query graph and G^{S_k} is a graph of top M in first retrieval. ω_1, ω_2 are the coefficients. We conduct an experiment and assign 0.5 to both coefficients for higher retrieval precision.

Figure 12: Model retrieval result for the scene objects. (Models in yellow frames indicates user's selection) (a) Input objects. (b) Top 5 retrieval results in our model library.

After above calculation, we can obtain the ranked similarities between image objects and all models in library shown in Figure 11(c). In this paper, we output the top 5 retrieval results for users to select, as is shown in Figure 12 that yellow frames indicate user's selection. We can see that our result has great similarity with input object. Finally, according to the relative locations of each object in the image, we place user-selected models into the 3D scene. In this way, the scene reconstruction is completed. Figure 13 shows our reconstructed 3D indoor scene.

Figure 13: Scene reconstruction result. (a) Input indoor scene image. (b) Final scene reconstruction result.

6. Relevance Feedback

Our approach has received some improvement on feature encoding and similarity matching algorithm. However, our retrieval, like many other content-based multimedia information retrieval methods, there exists semantic gap [43] between human and computer systems. On the one hand, the requirements and understanding of a human are semantic concepts of a high level. Computer systems can only conduct retrieval through model contours and features. This is one requirement where we should map model feature of a low level onto users' intention of a high level. On the other hand, for a certain object in an image, different users have different intentions. The dynamics of the intention decides that retrieval system can hardly find a certain map method for all cases. This map method is a similarity matching method that from model feature to user intention.

Relevance feedback resolves this problem effectively. It uses user intention to improve the quality of retrieval result. However, compared with other machine learning problems, small samples and real-time capability are main challenges for relevance feedback algorithms. The primary problem is small samples that a feedback learning algorithm faces [44] [45] [46]. Limited by interaction, in the feedback procedure, the system can only do training from finite user learning samples with much less than instances in a library and feature dimensions. Therefore, for small sample cases, over-fitting problems are quite common. In these cases, the training procedure can distinguish labeled instances very well, but unable to tell the unlabeled instances effectively. It is therefore hard to guarantee the stability of feedback performance. The other problem is real-time capability. It is the basic requirement for feedback learning. The feedback procedure should be fast enough to satisfy user's interaction.

The Support vector machine has excellent abilities of learning and generalizing. We take advantage of it to conduct our relevance feedback experiment. First, we display our top k retrieved models to users through the user interface. A user can label their satisfied instances as positive and the unsatisfied as negative. These k labeled instances can be viewed as training data. We use our feature encoding method to encode the instances and SVM to train the data, and finally get the classification model. Matlab libsvm toolbox [47] is used in our experiment and the penalty factor is set as $[2^{-8}, 2^8]$. We use the score function between two line-drawings as our user-defined kernel function, which is shown in formula (11). For instances that are not labeled, we view them as test set and rank them using our trained SVM model to return users with a new result as feed-

back. In this case, training data are small because of labelling
only one time, and the classification performance may not be as
good as we expect. So if the user is not pleased, he can do the
feedback once more.

Figure 14: Relevance feedback results for the input image. First line displays the furniture and second line is our first retrieval results. The following lines are the satisfied results after several feedbacks. (a) For the sofa, the user conducts the 3rd feedback and be satisfied with the result. (b) For the tea table, the 2nd feedback result conforms with user’s intention. (c) After the first feedback, result is satisfying and feedback is stopped. In the figure, the red frame represents satisfied positive model, while green one represents negative model.

Figure 14 shows the feedback results about retrieval instances. First, the system retrieves models from the library by star-graph matching method. The results are displayed in the second line. These results are without any prior knowledge, so some of them do not afford users’ requirement. Then, users label the retrieved models as positive or negative (red and green frames indicate positive and negative respectively) in first feedback. Our system train the labeled data and re-rank the models as shown in the third line of figure 14. Green frames shows the number of unsatisfied models. Also, system provides interfaces for more feedback procedure, which embodies user intention better. We don’t show another armchair in figure 14 for the reason that, the first retrieval result is good enough, so relevance feedback is not needed any more. We verify the similarity between feedback result and Ground Truth (figure 18). After several relevance feedback procedures, our result conforms well with Ground Truth, which indicates results reflect users’ intentions well and we also

get better retrieval results through the relevance feedback.

Users can choose any model from feedback results and system combine them together to build new scenes. Figure 15 shows a diversified reconstruction scene result. The results are not only in various forms, but also conform with the image scene very well.

Figure 15: Several scene reconstruction results after relevance feedback. (a) Input indoor scene image. (b) Diversified scene reconstruction results.

7. Experiment and Analysis

In this section, we show our experimental results and analyze them. The limitations of our method are also discussed.

7.1. Result analysis

We implement the algorithm with Windows 8, AMD A8-5500 3.20GHz CPU and 8GB memory. To verify the effectiveness, we tested it with some other indoor scene images. The result is shown in Figure 16. In the image analysis stage, geometric reasoning and object extraction consumes about 20s individually. In model retrieval stage, we established the model library with 200 models, among which are 90 sofas, 50 chairs, 20 tables and 40 tea table models (the details are in the supplementary material). All the models come from 3D Warehouse. Based on the model library, k-means clustering for 150 tokens takes 10 hours, and encoding all the line drawings takes about 20h. After feature encoding, for an input scene image, it takes about 50 seconds in reconstruction step (time determined by the image size). Preprocessing is time-consuming however, so this work could be done in advance. Thus in model retrieval stage, our method constructs the scene much more quickly.

To verify our feature encoding approach, we also conducted common 2D descriptors for comparison. Retrieval results for the extracted objects in Figure 3(c), are provided in Figure 14, using different methods of GALIF [7], Fourier [48], Zernike moments [49] and HOG [50] feature descriptors. Among them, GALIF is one of the best sketch-based retrieval method in recent years and Fourier, Zernike moments and HOG are common 2D shape feature descriptors that Li et al. [51] mentioned. All retrievals are conducted under the viewpoint obtained in our paper.

It can be seen that our retrieval results have more similarity with the input query object. In addition, for retrieval in mixed model library without category labels, more models from our result are semantically in the same category with the query object. This is mainly because traditional feature encoding methods only start from local or global features. Even though there is combinatorial optimization of features, it leads to more uncontrollable results and more dissimilarity for the reason that

Figure 16: Other reconstruction results. (a) Input indoor scene image. (b) Reconstructed 3D scenes (Models are from retrieval). (c) Reconstructed 3D scenes (Models are randomly chosen by users after relevance feedback).

retrieval is not performed on a unified feature. In this paper, we consider the local and global feature in a unified feature system. Models from the same category are more consistent in similarity. The retrieval results are more likely to be in the same category. The feature encoding method that we proposed is readily available in a mixed model library.

We do not have available Ground Truth for comparison experiment, because we built the library according to our own need. As a result, we took the idea of Huang et al. [52] who construct Ground Truth by themselves for better comparison. We completed our Ground Truth in an iterative manner in the following way. In the process, we randomly chose 20 users and asked them to construct their own Ground Truth iteratively one by one. For each object, the first user select from the model library the top 5 similar models, which are modified by the next user until all users agree with the 5 models. We took the 5 models as Ground Truth for the object. Figure 18 gives Ground Truth for objects in Figure 17. We display the models that belong to the Ground Truth, marking them in color frames. A red frame indicates the model is in the Ground Truth while green frame indicates it beyond the Ground Truth. Our result has more red frames, which means that we have more retrieved models belonging to the Ground Truth. It proves that our results are more similar to actual object and corresponded better to characteristics of human vision. We, therefore, conclude that our approach is more precise and relatively more effective.

7.2. Comparison with other methods

Our approach has some similarities with the method of sketch-based 3D reconstruction [23]. Both methods leverage 2D sketches as the input to retrieve models from the library and to

Figure 17: Retrieval results for one scene using different feature descriptors. Red frame indicates the model belongs to the Ground Truth while green frame indicates it beyond the Ground Truth. (Please refer to the supplementary material for clear image)

complete scene reconstruction. However, many differences exist between these two methods. First, the inputs are different. Our inputs are images which are more readily available, while their inputs are sketches drawn by hand which make it hard for non-professional users to draw a scene according to the criteria. Our inputs are simple and more convenient for users. In addition, sketch-based 3D reconstruction method refers to paper [7] to conduct their model retrieval. We present a new method to encode the line-drawings which not only embodies local feature, but also the hierarchical and structured global feature. It converts the clutter of pixel data into an ordered expression in

Figure 18: Ground Truth from iterative method.

line with the human visual perception, and also the retrieval precision is also improved accordingly. We have made some comparisons in section 7.1 and found it better than the sketch-based model retrieval [23]. In addition, sketch-based 3D reconstruction method provide a concept called structure group. It solves the problem of semantic conflict very well. In our paper, we solve this problem by relevance feedback which is easy to realize in the approach.

We also compare our research with the method of interactive images [34]. They also need the cuboid of furniture in their study. However, the first problem is that their method can hardly separate object from the image background automatically. The second issue is that selecting cuboid proxies by hand is inconvenient to operate. In our approach, system can analyze the image automatically and separate furniture from the image background with few interaction. In the terms of research goals, they mainly focus on the movement and change of furniture, while what we want is to realize the reconstruction of a 3D scene which has more realistic significance.

There are some similarities with other research like RGBD-based model reconstruction [24], sketch-based model retrieval [7], etc. However, the comparison shows that the research start point and goals are quite different. We focus on the research about scene reconstruction from a single image and do not need professional depth image devices nor much interaction. The final retrieval precision have achieved development than other sketch-based retrieval method. Therefore, our research about scene reconstruction from a single image provides a more convenient and richer way for reconstructing a 3D scene.

7.3. Limitations

The first limitation is the input images. Normally, for an input image, geometric frame structures are needed in the image analysis stage. We use edge lines of structures to facilitate the calculation of the scene vanishing point. The image analyzing experiment also presents better results for regular geometries than irregular geometries. In terms of object extracting, if there is sharp color contrast between objects and background, little interactions are needed in object extracting, as shown in figure 2. For some images however, colors in adjacent areas are quite similar, so we use obtained cuboids to help in segmenting interactions. These interactions towards pre-segmented areas concentrate on borders of cuboids. We simply assign these border areas as part of one object or not in our experiment. In the

case of covering, our method tolerates small amount of covering, such as cups on tea table or pillows on sofa. For large covering which change the object contours significantly(e.g. chairs in second and fourth row of figure 16), this method provides a poor result. Figure 19 shows some unsatisfied geometric reasoning result. However, through interaction, we can also get objects from the image, and retrieval stage works well. Generally speaking, our image analysis method provide a reliable performance for most indoor scene images.

Figure 19: Some unsatisfied result in geometric reasoning.

Secondly, we do not deform retrieved models. If all the models in the database vary greatly with a query object, it would be difficult to retrieve out a satisfying 3D model. In the future we hope to make the study of deformed method to solve the above problems.

8. Conclusion

In this paper, we present a novel model-driven indoor scenes modeling method based on a single image. With the help of rich model resources on the Internet, we are able to conduct 3D modeling from a single indoor scene image efficiently. The result shows that the method proposed in this paper is simple and efficient. Our method provides a new surface modeling technique from a single image.

In future work, we want to use more reasonable geometric reasoning methods to analysis images better. We also consider adding contour deformation in the retrieval process to get more reasonable 3D models.

References

- [1] Zhang L, Dugas-Phocion G, Samson JS, Seitz SM. Single-view modelling of free-form scenes. *The Journal of Visualization and Computer Animation* 2002;13(4):225–35.
- [2] Chen T, Zhu Z, Shamir A, Hu SM, Cohen-Or D. 3-sweep: extracting editable objects from a single photo. *ACM Transactions on Graphics (TOG)* 2013;32(6):195.
- [3] Chaudhuri S, Koltun V. Data-driven suggestions for creativity support in 3d modeling. In: *ACM Transactions on Graphics (TOG)*; vol. 29. ACM; 2010, p. 183.
- [4] Chaudhuri S, Kalogerakis E, Guibas L, Koltun V. Probabilistic reasoning for assembly-based 3d modeling. In: *ACM Transactions on Graphics (TOG)*; vol. 30. ACM; 2011, p. 35.
- [5] Funkhouser T, Kazhdan M, Shilane P, Min P, Kiefer W, Tal A, et al. Modeling by example. In: *ACM Transactions on Graphics (TOG)*; vol. 23. ACM; 2004, p. 652–63.
- [6] Shao T, Xu W, Yin K, Wang J, Zhou K, Guo B. Discriminative sketch-based 3d model retrieval via robust shape matching. In: *Computer Graphics Forum*; vol. 30. Wiley Online Library; 2011.
- [7] Eitz M, Richter R, Boubekur T, Hildebrand K, Alexa M. Sketch-based shape retrieval. *ACM Trans Graph* 2012;31(4):31.

- [8] Dhond UR, Aggarwal JK. Structure from stereo-a review. *IEEE transactions on systems, man, and cybernetics* 1989;19(6):1489–510.
- [9] Scharstein D, Szeliski R. A taxonomy and evaluation of dense two-frame stereo correspondence algorithms. *International journal of computer vision* 2002;47(1-3):7–42.
- [10] Horn BK. Height and gradient from shading. *International journal of computer vision* 1990;5(1):37–75.
- [11] Super BJ, Bovik AC. Shape from texture using local spectral moments. *Pattern Analysis and Machine Intelligence, IEEE Transactions on* 1995;17(4):333–43.
- [12] Nayar SK, Nakagawa Y. Shape from focus. *Pattern analysis and machine intelligence, IEEE Transactions on* 1994;16(8):824–31.
- [13] Horry Y, Anjyo KI, Arai K. Tour into the picture: using a spidery mesh interface to make animation from a single image. In: *Proceedings of the 24th annual conference on Computer graphics and interactive techniques*. ACM Press/Addison-Wesley Publishing Co.; 1997, p. 225–32.
- [14] Criminisi A, Reid I, Zisserman A. Single view metrology. *International Journal of Computer Vision* 2000;40(2):123–48.
- [15] Kalogerakis E, Chaudhuri S, Koller D, Koltun V. A probabilistic model for component-based shape synthesis. *ACM Transactions on Graphics (TOG)* 2012;31(4):55.
- [16] Xu K, Zhang H, Cohen-Or D, Chen B. Fit and diverse: Set evolution for inspiring 3d shape galleries ????.
- [17] Xu K, Zheng H, Zhang H, Cohen-Or D, Liu L, Xiong Y. Photo-inspired model-driven 3d object modeling. In: *ACM Transactions on Graphics (TOG)*; vol. 30. ACM; 2011, p. 80.
- [18] Fan L, Wang R, Xu L, Deng J, Liu L. Modeling by drawing with shadow guidance. In: *Computer Graphics Forum*; vol. 32. Wiley Online Library; 2013, p. 157–66.
- [19] Xie X, Xu K, Mitra NJ, Cohen-Or D, Gong W, Su Q, et al. Sketch-to-design: Context-based part assembly. In: *Computer Graphics Forum*; vol. 32. Wiley Online Library; 2013, p. 233–45.
- [20] Shen CH, Fu H, Chen K, Hu SM. Structure recovery by part assembly. *ACM Transactions on Graphics (TOG)* 2012;31(6):180.
- [21] Lee J, Funkhouser T. Sketch-based search and composition of 3d models. In: *Proceedings of the fifth eurographics conference on sketch-based interfaces and modeling*. Eurographics Association; 2008, p. 97–104.
- [22] Shin H, Igarashi T. Magic canvas: interactive design of a 3-d scene prototype from freehand sketches. In: *Proceedings of Graphics Interface 2007*. ACM; 2007, p. 63–70.
- [23] Xu K, Chen K, Fu H, Sun WL, Hu SM. Sketch2scene: Sketch-based co-retrieval and co-placement of 3d models. *ACM Transactions on Graphics (TOG)* 2013;32(4):123.
- [24] Shao T, Xu W, Zhou K, Wang J, Li D, Guo B. An interactive approach to semantic modeling of indoor scenes with an rgbd camera. *ACM Transactions on Graphics (TOG)* 2012;31(6):136.
- [25] Nan L, Xie K, Sharf A. A search-classify approach for cluttered indoor scene understanding. *ACM Transactions on Graphics (TOG)* 2012;31(6):137.
- [26] Chen K, Lai YK, Wu YX, Martin R, Hu SM. Automatic semantic modeling of indoor scenes from low-quality rgb-d data using contextual information. *ACM Transactions on Graphics (TOG)* 2014;33(6):208.
- [27] Liu Z, Zhang Y, Wu W, Liu K, Sun Z. Model-driven indoor scenes modeling from a single image. In: *Proceedings of the 41st Graphics Interface Conference*. Canadian Information Processing Society; 2015, p. 25–32.
- [28] Gupta A, Hebert M, Kanade T, Blei DM. Estimating spatial layout of rooms using volumetric reasoning about objects and surfaces. In: *Advances in Neural Information Processing Systems*. 2010, p. 1288–96.
- [29] Lee DC, Hebert M, Kanade T. Geometric reasoning for single image structure recovery. In: *Computer Vision and Pattern Recognition, 2009. CVPR 2009. IEEE Conference on*. IEEE; 2009, p. 2136–43.
- [30] Comaniciu D, Meer P. Mean shift: A robust approach toward feature space analysis. *Pattern Analysis and Machine Intelligence, IEEE Transactions on* 2002;24(5):603–19.
- [31] Hu SM, Zhang FL, Wang M, Martin RR, Wang J. Patchnet: a patch-based image representation for interactive library-driven image editing. *ACM Transactions on Graphics (TOG)* 2013;32(6):196.
- [32] Vapnik V. *The nature of statistical learning theory*. Springer Science & Business Media; 2013.
- [33] Vapnik V, Golowich SE, Smola A. Support vector method for function approximation, regression estimation, and signal processing. In: *Advances in Neural Information Processing Systems 9*. Citeseer; 1996,.
- [34] Zheng Y, Chen X, Cheng MM, Zhou K, Hu SM, Mitra NJ. Interactive images: cuboid proxies for smart image manipulation. *ACM Trans Graph* 2012;31(4):99.
- [35] Xiao J, Russell B, Torralba A. Localizing 3d cuboids in single-view images. In: *Advances in Neural Information Processing Systems*. 2012, p. 746–54.
- [36] Kang H, Lee S, Chui CK. Coherent line drawing. In: *Proceedings of the 5th international symposium on Non-photorealistic animation and rendering*. ACM; 2007, p. 43–50.
- [37] DeCarlo D, Finkelstein A, Rusinkiewicz S, Santella A. Suggestive contours for conveying shape. *ACM Transactions on Graphics (TOG)* 2003;22(3):848–55.
- [38] Csürka G, Dance C, Fan L, Willamowski J, Bray C. Visual categorization with bags of keypoints. In: *Workshop on statistical learning in computer vision, ECCV*; vol. 1. 2004, p. 1–2.
- [39] Lowe DG. Distinctive image features from scale-invariant keypoints. *International journal of computer vision* 2004;60(2):91–110.
- [40] Li Y, Song YZ, Gong S. Sketch recognition by ensemble matching of structured features 2013;.
- [41] Lim JJ, Zitnick CL, Dollár P. Sketch tokens: A learned mid-level representation for contour and object detection. In: *Computer Vision and Pattern Recognition (CVPR)*, 2013 IEEE Conference on. IEEE; 2013, p. 3158–65.
- [42] Winder S, Hua G, Brown M. Picking the best daisy. In: *Computer Vision and Pattern Recognition, 2009. CVPR 2009. IEEE Conference on*. IEEE; 2009, p. 178–85.
- [43] Müller M, Röder T, Clausen M. Efficient content-based retrieval of motion capture data. In: *ACM Transactions on Graphics (TOG)*; vol. 24. ACM; 2005, p. 677–85.
- [44] Inselberg A. The plane with parallel coordinates. *The Visual Computer* 1985;1(2):69–91.
- [45] Shneiderman B. Tree visualization with tree-maps: 2-d space-filling approach. *ACM Transactions on graphics (TOG)* 1992;11(1):92–9.
- [46] Cui Q, Ward MO, Rundensteiner EA, Yang J. Measuring data abstraction quality in multiresolution visualizations. *Visualization and Computer Graphics, IEEE Transactions on* 2006;12(5):709–16.
- [47] Chang CC, Lin CJ. Libsvm: A library for support vector machines. *ACM Transactions on Intelligent Systems and Technology (TIST)* 2011;2(3):27.
- [48] Zhang D, Lu G, et al. A comparative study on shape retrieval using fourier descriptors with different shape signatures. In: *Proc. of international conference on intelligent multimedia and distance education (ICIMADE01)*. 2001, p. 1–9.
- [49] Khotanad A, Hong YH. Invariant image recognition by zernike moments. *Pattern Analysis and Machine Intelligence, IEEE Transactions on* 1990;12(5):489–97.
- [50] Dalal N, Triggs B. Histograms of oriented gradients for human detection. In: *Computer Vision and Pattern Recognition, 2005. CVPR 2005. IEEE Computer Society Conference on*; vol. 1. IEEE; 2005, p. 886–93.
- [51] Li B, Lu Y, Godil A, Schreck T, Bustos B, Ferreira A, et al. A comparison of methods for sketch-based 3d shape retrieval. *Computer Vision and Image Understanding* 2014;119:57–80.
- [52] Huang SS, Shamir A, Shen CH, Zhang H, Sheffer A, Hu SM, et al. Qualitative organization of collections of shapes via quartet analysis. *ACM Transactions on Graphics (TOG)* 2013;32(4):71.