The small-angle performance of a dual-readout fiber calorimeter

A. Cardini^c, M. Cascella^d, S. Choi^m,
D. De Pedis^g, R. Ferrari^h, S. Franchinoⁱ,
G. Gaudio^h, S. Ha^m, J. Hauptman^j,
L. La Rotonda^k, S. Lee^{m,n}, F. Li^j, M. Livan^f,
E. Meoni^l, F. Scuri^b, A. Sill^a, and R. Wigmans^{a, 1}

^a *Texas Tech University, Lubbock (TX), USA*

^b *INFN Sezione di Pisa, Italy*

^c *INFN Sezione di Cagliari, Monserrato (CA), Italy*

^d *Dipartimento di Fisica, Università di Salento, and INFN Sezione di Lecce, Italy*

^f *INFN Sezione di Pavia and Dipartimento di Fisica, Università di Pavia, Italy*

^g *INFN Sezione di Roma, Italy*

^h *INFN Sezione di Pavia, Italy*

ⁱ *CERN, Genève, Switzerland*

^j *Iowa State University, Ames (IA), USA*

^k *Dipartimento di Fisica, Università della Calabria, and INFN Cosenza, Italy*

^l *Tufts University, Medford (MA), USA*

^m *Korea University, Seoul, Korea*

ⁿ *Kyungpook National University, Daegu, Korea*

Abstract

The performance of the RD52 dual-readout calorimeter is measured for very small angles of incidence between the 20 GeV electron beam particles and the direction of the fibers that form the active elements of this calorimeter. The calorimeter response is observed to be independent of the angle of incidence for both the scintillating and the Čerenkov fibers, whereas significant differences are found between the angular dependence of the energy resolution measured with these two types of fibers. The experimental results are on crucial points at variance with the predictions of GEANT4 Monte Carlo simulations.

PACS: 29.40.Ka, 29.40.Mc, 29.40.Vj

Key words: Dual-readout calorimetry, Čerenkov light, optical fibers

¹ Corresponding author. Email wigmans@ttu.edu, fax (+1) 806 742-1182.

1 Introduction

Sampling calorimeters based on large numbers of optical fibers embedded in a metal absorber structure offer some distinct advantages compared to other detectors of high-energy particles. Since the fibers act at the same time as the active medium in which the signals are produced and as a wave guide transporting the signals to the outside world, it is possible to construct hermetic detector structures, which is very important in modern colliding-beam experiments. Also, the very frequent shower sampling allowed by a fiber configuration strongly reduces the effects of sampling fluctuations. Such fluctuations tend to dominate the energy resolution of electromagnetic sampling calorimeters. Several particle physics experiments have taken advantage of these features, *e.g.*, CHORUS [1], KLOE [2], DELPHI [3], WA89 [4], H1 and CMS [5].

In dual-readout calorimeters, two different types of signals are produced by the showering particles. These two types of signals, which represent the total energy deposit by ionization (dE/dx) and the Čerenkov light produced by the relativistic shower products, provide complementary information, which makes it for example possible to determine the electromagnetic fraction of each hadronic shower. The fluctuations in that fraction typically dominate the hadronic energy resolution of calorimeters, and dual-readout calorimeters thus offer the possibility to eliminate the effects of these fluctuations and obtain excellent hadronic performance [6,7].

In the calorimeter discussed in this paper, signals are generated in scintillating fibers, which measure the deposited energy, and in clear plastic fibers, which measure the relativistic shower particles, by means of the Čerenkov light generated by these. A large number of such fibers are embedded in a copper absorber structure. This detector is longitudinally unsegmented, the fibers are oriented in *approximately* the same direction as the particles to be detected. In previous papers, we have focused on the electromagnetic performance of this detector [8] and on its capability to identify the particles developing showers in it [9]. In this paper, we investigate its performance as a function of the angle of incidence of the showering particles. This study was inspired by the results of Monte Carlo simulations, which suggested anomalous effects when electrons or photons enter the calorimeter almost parallel to the optical fibers [10]. These effects derive from the fact that the early component of em showers (*i.e.*, before the shower maximum is reached) is extremely collimated. When an electron enters this calorimeter parallel to the fibers, the signal from the early shower component strongly depends on the impact point, *i.e.*, inside a fiber or in between fibers. This effect leads to a deterioration of the em energy resolution and may also affect the calorimeter response².

In Section 2, the instruments and the experimental setup in which the measurements

² Following the convention introduced in [11], we define the calorimeter *response* in this paper as the average calorimeter signal per unit deposited energy. In this convention, a linear calorimeter thus has a constant response, and a compensating calorimeter has the same response for electrons and hadrons.

were carried out are described, as well as the calibration and data analysis methods that were used. Experimental results are presented in Section 3. In the concluding Section 4, we discuss these results and their implications.

2 Equipment and measurements

2.1 Detectors and beam line

The measurements described in this paper were performed in the H8 beam line of the Super Proton Synchrotron at CERN. For these particular studies, we used a beam of 20 GeV electrons, which were steered into a module of the RD52 fiber calorimeter. A system of auxiliary detectors, described below, was used to select the beam particles that entered the calorimeter in a well defined, small area.

The calorimeter module used for the studies described in this paper consisted of a copper absorber matrix, 2.5 m long ($10 \lambda_{\text{int}}$), with a cross section of $9.2 \times 9.2 \text{ cm}^2$. It was subdivided into four towers ($4.6 \times 4.6 \times 250 \text{ cm}^3$), and each tower contained 1024 plastic optical fibers (diameter 1.0 mm, equal numbers of scintillating and clear plastic fibers)³. Each tower produced two signals, a scintillation signal and a Čerenkov signal, which were detected by separate PMTs⁴. For this reason, this type of detector is also known as a DREAM (Dual-REAdout Method) calorimeter. The fiducial mass of the calorimeter module was $\sim 120 \text{ kg}$, it contained 45% fibers by volume and the sampling fraction for minimum ionizing particles, both for the scintillation and for the Čerenkov sampling structure, was 4.6%. The effective radiation length and Moliere radius were both about 25 mm. Figure 1a shows this module while it was under construction; details of the fiber structure, as well as a front view of the finished product, are shown in Figure 1b, where the scintillating and Čerenkov fibers are indicated by S and $\check{C}$, respectively.

The experimental setup contained also a number of auxiliary detectors, which were intended to determine the identity of individual beam particles, and to measure their trajectory. Figure 1c shows a schematic overview of the beam line, in which the positions of these auxiliary counters are indicated:

- Two small scintillation counters provided the signals that were used to trigger the data acquisition system. These Trigger Counters (T_1, T_2) were 2.5 mm thick, and the area of overlap was $4 \times 4 \text{ cm}^2$. Downstream from these counters, a third scintillation counter (T_H) was installed. The latter had a hole with a radius of 10 mm in it. A (anti-)coincidence between the logic signals from these counters

³ The scintillating fibers were of the type SCSF-78 (polystyrene core), produced by Kuraray. Their numerical aperture was 0.55 and the cladding thickness $20 \mu\text{m}$. The Čerenkov light was generated in PMMA based SK40 fibers, produced by Mitsubishi. Their numerical aperture was 0.50, and the thickness of the cladding $10 \mu\text{m}$.

⁴ Hamamatsu R8900, 10-stage.

Fig. 1. The calorimeter module used for these studies (*a, b*). Schematic overview of the arrangement of the auxiliary detectors that were used to define the beam spot and to identify the individual beam particles (*c*, not to scale). See text for details.

provided the trigger ($T_1 \cdot T_2 \cdot \overline{T_H}$).

- The trajectories of individual beam particles could be reconstructed with the information provided by two small drift chambers (DC1, DC2), which were installed upstream and downstream of the trigger counters. This system made it possible to determine the location of the impact point of the 20 GeV beam particles at the calorimeter surface with a precision of about 2 mm.
- About 80 cm upstream of the calorimeter, a preshower detector (PSD) provided signals that could be used to remove pions and muons contaminating the electron beams. This PSD consisted of a 5 mm thick lead plate, followed by a 5 mm thick plastic scintillator. Electrons started developing showers in this device, while muons and hadrons typically produced a signal characteristic of a minimum ionizing particle (mip) in the scintillator plate.
- Downstream of the calorimeter (DREAM), a tail catcher (TC) also served to identify pions and muons, since the electron showers were typically fully contained in the calorimeter. This tail catcher consisted of a simple $20 \times 20 \text{ cm}^2$ scintillation counter.
- Further downstream of the calorimeter, behind an additional $8\lambda_{\text{int}}$ worth of absorber, a $50 \times 50 \text{ cm}^2$ scintillation counter (μ) served to identify muons that contaminated the particle beam.

The goal of the present studies was to measure the calorimeter performance for very small angles of incidence. For that purpose the table on which the calorimeter was installed was modified such as to allow rotation in the horizontal plane with a precision better than one milliradian⁵.

⁵ We thank Michael Jeckel and Ilias Efthymiopoulos for making these modifications to our equipment.

95 2.2 Data acquisition

96 Low-loss cables with a 15-mm diameter were used to transport the signals from the
97 trigger counters to the counting room. The signal speed in these cables was mea-
98 sured to be $0.78c$. The calorimeter signals, as well as the signals from the auxiliary
99 counters that needed to be digitized (PSD, tail catcher, muon counter) were trans-
100 ported through RG-58 cables with (for timing purposes) appropriate lengths to the
101 counting room.

102 There, the signals to be digitized were fed into charge ADCs. The signals from the
103 wire chambers were fed into TDCs. The time information could be converted into
104 (x, y) coordinates of the point where the beam particle traversed the chamber.

105 The data acquisition system used VME electronics. Two VME crates hosted all
106 the needed readout and control boards. The signals from the calorimeter channels
107 and the auxiliary detectors were integrated and digitized with a sensitivity of 100
108 fC/count, on 12-bit QDC V792 CAEN modules. The timing information of the
109 tracking chambers was recorded with 1 ns resolution in a 16-bit 16-channel CAEN
110 V775N TDC. Our readout scheme optimized the CPU utilization and the data tak-
111 ing efficiency using the bunch structure of the 42-second SPS accelerator cycle,
112 during which period beam particles were provided to our experiment by means of
113 two extractions with a duration of 4.8 seconds each.

114 2.3 Experimental data, calibration and analysis methods

115 The measurements described in this paper were performed in the H8 beam of the
116 CERN Super Proton Synchrotron. Beams enriched in electrons were derived from a
117 secondary beam of positively charged particles, by sending these particles through
118 a 5 mm thick lead radiator. In practice, only the electron component of the sec-
119 ondary beam lost a substantial energy fraction passing through this material, and
120 electrons⁶ of the desired momentum (20 GeV) were selected with properly tuned
121 downstream bending magnets and collimators.

122 The measurements were performed by steering the beams into a region near the
123 geometrical center of the module. Typically, for each run 20 000 events were col-
124 lected. In each run, 10% randomly triggered events provided pedestal information.
125 For each event, the ADC information of all calorimeter towers was recorded, as well
126 as the ADC data from the auxiliary detectors (muon counter, PSD, tail catcher), and
127 the TDC data from the wire chambers.

128 Off-line, the beam chamber information could be used to select events that entered
129 the calorimeter in a small region (typically with a radius < 5 mm) located near

⁶ The selected particles were positively charged anti-electrons (positrons). However, we systematically refer to these particles as *electrons* in this paper.

its geometric center. The information provided by the auxiliary detectors was used to identify each event either as an electron, a muon or a pion. It turned out that the 20 GeV beam consisted predominantly ($> 50\%$) of electrons. However, there was also a substantial contamination by muons and pions. Since the beam profiles of the various types of beam particles differed, the precise fraction of electrons depended on the chosen size of the beam spot: the smaller the beam spot, the purer the electron sample.

The analyses described in Section 3 were performed on purified event samples of electrons. To that end, the following cuts were applied. *Electrons* were identified as particles that produced a signal in the PSD that was larger than ~ 200 ADC counts above pedestal, which corresponds to the combined signals produced by 2 minimum ionizing particles (mips) traversing this detector. Additional requirements were that no signals incompatible with electronic noise were produced in the tail catcher and the muon counter. The effects of these cuts on the scintillation signals from one of the four calorimeter towers is illustrated in Figure 2. In order to further limit the event sample to electrons that deposited (most of) their energy in the calorimeter, the total scintillation signal of the calorimeter was also required to be larger than 15 GeV.

Fig. 2. The scintillation signal distribution in one of the calorimeter towers before (a) and after (b) applying the cuts intended to eliminate the contaminating muons and pions from the 20 GeV particle beam.

The electrons deposited typically $\sim 1\%$ of their energy in the preshower detector. The effects of that on the calorimeter signals were studied in the present analyses. This was possible since all angular scans were performed separately with and without the PSD in the beam line. In the latter case, the event samples inevitably contained some fraction of pions (typically $\sim 10\%$). Inspired by the results of an earlier study [8], we found that this hadron contamination could be effectively reduced by using the ratio of the two types of calorimeter signals, C/S . However, it also turned out that by applying such a cut, a bias was introduced which improved the em energy resolution in the scintillation channel significantly. We come back to this issue in Section 4. For this reason, the C/S calorimeter signal ratio was *not* used in the analyses described in Section 3, and the effects of the PSD on the energy

159 resolution were studied by using the PSD just as a passive absorber, *i.e.*, without
160 making use of the signals it generated. For both data sets, we used exactly the same
161 procedure to purify the electron event samples, and this procedure was exclusively
162 based on the auxiliary detectors, *not* on the calorimeter data.

163 In this paper, we call the angle between the particle trajectory and the fiber direction
164 θ in the vertical plane and ϕ in the horizontal plane. The detailed angular scans of
165 which the results are the topic of this paper were possible because the calorimeter
166 was mounted on a table that could be rotated in the horizontal plane; the azimuth
167 angle ϕ could be varied with a precision and reproducibility of about 1 milliradian.
168 In the vertical plane, a deviation of the angle θ was achieved by tilting the calori-
169 meter module. Angular ϕ scans were carried out for two values of the tilt angle:
170 $\theta = 1^\circ$ and $\theta = 2^\circ$.

171 The calibration of the calorimeter towers was performed by steering the 20 GeV
172 electron beam into the centers of each of the four calorimeter towers. The PSD was
173 installed in the beam line during these measurements, allowing the selection of a
174 pure sample of beam electrons for this purpose. In an analysis described elsewhere
175 [8], we found that the electrons deposited, on average, 85% of their energy in the hit
176 tower, so that the average signal corresponded to an energy deposit of ~ 17 GeV.
177 The calibration of the signals, in terms of GeV per ADC count, was performed
178 in two steps. First, the average signals from the four towers were equalized, in
179 terms of GeVs. Second, an overall multiplication factor was determined from the
180 requirement that the total calorimeter signal, for electrons entering the calorimeter
181 in the central region, parallel to the fibers, equals the beam energy of 20 GeV. This
182 procedure was applied separately for the scintillation and the Čerenkov signals. The
183 calibration was performed at $(\theta = 1^\circ, \phi = 0^\circ)$ with the PSD installed in the beam
184 line. It was repeated several times during the beam tests (which lasted one week)
185 and found to be stable within 1%.

186 When the table on which the detector was installed was rotated, the impact point of
187 the beam particles shifted. For a rotation from $\phi = 0$ to the maximum angle used in
188 these studies ($\phi = 5^\circ$), this shift amounted to 120 mm. For each angle of incidence
189 ϕ , the horizontal displacement was chosen such that the shower maximum was
190 always located in the same area (at a depth of ~ 15 cm) inside the calorimeter.
191 This was done to minimize any systematic effects caused by fiber-to-fiber response
192 differences.

193 2.4 Why 20 GeV electrons?

194 The electromagnetic energy resolution, σ/E , of a calorimeter such as this one typ-
195 ically consists of the following components:

- 196 • A *stochastic* term, which is determined by sampling fluctuations and fluctuations
197 in the number of photoelectrons

- 198 • A noise term, caused by pedestal fluctuations
- 199 • A term resulting from *shower leakage* fluctuations
- 200 • An *energy independent* (or *constant*) term, caused by instrumental effects, such
- 201 as fiber-to-fiber response differences, position dependence of the quantum effi-
- 202 ciency of the PMTs, *etc.*

203 The first three terms depend on the energy of the showering particles. Leakage
 204 fluctuations depend, in addition, also on the type of leakage (lateral, longitudinal,
 205 albedo). Only the contribution of lateral leakage fluctuations to the em energy res-
 206 olution is a consideration for our detector. They depend on the shower energy as
 207 $x\%/\sqrt[4]{E}$ [11], where x is the average leakage percentage ($\sim 4\%$ for small angles of
 208 incidence). The contribution of the stochastic term to the energy resolution scales
 209 with $1/\sqrt{E}$, that of the noise term with $1/E$, while the contribution of the constant
 210 term does not change with the particle energy. As a result, the energy resolution
 211 of the calorimeter is dominated by the noise term at very low energies and by the
 212 constant term at the high end of the energy spectrum.

213 Our studies were inspired by the possible effects of changes in the sampling charac-
 214 teristics of the calorimeter for very small angles of incidence. Therefore, we chose
 215 a particle energy for which the energy resolution is dominated by the contribution
 216 of the stochastic term. This consideration led to the choice of 20 GeV electrons. At
 217 this energy, the contributions of the four terms mentioned above to the relative em
 218 energy resolution were estimated to be 4%, $< 1\%$, 2-3% and $< 1\%$, repectively, for
 219 the scintillation signals, and 5%, $< 1\%$, 1-2% and $< 1\%$, for the Čerenkov signals.
 220 The contribution of energy independent effects was minimized by using a small
 221 beam spot and by steering the beam such that the location of the shower maximum
 222 was independent of the angle of incidence (see section 2.3).

223 Based on measurements with the original DREAM detector [12], we estimate the
 224 average shower containment at 96%, given the effective radial size of 2.1 Moliere
 225 radii. This value is for the angle at which the module was calibrated. At larger
 226 angles, the shower maximum (located at a depth of ~ 15 cm) stays at the same
 227 spot, but the shower containment is probably a bit smaller because of side leakage
 228 from the tail. The containment is better for the Čerenkov signals.

229 In the following, the measured energy resolution, σ/E , has been determined on the
 230 basis of Gaussian fits to the pulse height spectra, over a range spanning ± 2 standard
 231 deviations around the mean value. Examples of such fits are shown in Figures 4 and
 232 14.

233 3 Experimental results

234 3.1 The angular dependence of the calorimeter response

235 Angular scans were performed for two values of the tilt angle: $\theta = 1^\circ$ and 2° . Data
 236 were collected for 20 GeV electrons entering the calorimeter at azimuth angles

237 ϕ ranging from -5° to $+5^\circ$. In order to check possible effects of the upstream
 238 preshower detector, all measurements were carried out with and without the PSD
 239 in place. The impact point of the beam was chosen near the geometric center of the
 240 calorimeter, and events were selected that entered the calorimeter within a circle of
 241 radius 4 mm around that point (Figure 3). In the following, we only show results
 242 for the angular range from -4° to $+3^\circ$.

Fig. 3. Schematic view of the calorimeter, showing the four towers into which it is divided. The beam spot is indicated by the shaded area. The direction of the beam line is indicated for different angles of incidence of the beam particles.

243 It turned out that at larger angles, lateral leakage effects and the fact that different
 244 fibers contributed significantly to the signals started to play a role, and these effects
 245 were not of interest for our present studies⁷.

246 Figure 4 shows typical signal distributions recorded for the Čerenkov signals, with
 247 the preshower detector in (Figure 4a) or out of the beamline (Figure 4b). The figure
 248 illustrates not only the capability of the preshower detector to remove the pion con-
 249 tamination by means of the signal it generates, but also the effects of this upstream
 250 absorber on the calorimeter signals. When this absorber is removed, the calorimeter
 251 signals increase, on average, a little bit (about 2% in this example). In addition, the
 252 calorimeter's energy resolution improves as a result of the absence of *fluctuations*
 253 in the energy fraction lost in the upstream absorber.

254 In Figure 5, the measured calorimeter response is shown as a function of the az-
 255 imuth angle of incidence ϕ . Results are given separately for the scintillation and
 256 the Čerenkov signals, for a tilt angle $\theta = 1^\circ$, with the preshower detector in the
 257 beam line (PSD IN). It turns out that the calorimeter signal varied by less than one
 258 percent for angles of incidence ranging from -4° to $+4^\circ$, both for the scintillation
 259 and the Čerenkov channels. In fact, the distribution of the calorimeter response ob-
 260 tained for the 21 different angles for which it was measured varied only by 0.34%

⁷ Since the beam spot was chosen slightly off-center, leakage effects also affected the results at $\phi = +4^\circ$. The data point ($\theta = 1^\circ, \phi = 3^\circ$, PSD IN) was forgotten in the data taking procedures, and is thus missing in Figures 5,7,8.

Fig. 4. Typical calorimeter signal distributions recorded with the preshower detector in (a) or out (b) of the beam line. These distributions were obtained for the Čerenkov signals, at angles $\phi = -0.2^\circ$ and $\theta = 2^\circ$.

261 and 0.35% for the two types of signals (σ_{rms}). We measured the response variations
 262 also for the other sets of measurements, *i.e.*, with the PSD IN or OUT, and for tilt
 263 angles θ of 1° or 2° . The results are summarized in Table 1.

264 For all these configurations, the response variations were measured to be smaller
 265 than 1%, represented by the shaded area around the average signal shown in Figure
 266 5. No experimental evidence was found for the specific angular response depen-
 267 dence predicted by GEANT4 Monte Carlo simulations[10] in any of these mea-
 268 surement series.

Fig. 5. The average calorimeter signals for 20 GeV electrons in the Čerenkov (a) and the scintillation (b) channels, as a function of the azimuth angle of incidence (ϕ) of the beam particles. The tilt angle θ was 1° , and the PSD was in the beam line. The shaded area represents a variation of $\pm 1\%$ with respect to the average signal.

Table 1

Variation of the calorimeter response to 20 GeV electrons with the azimuth angle of incidence ϕ ranging from -4° to $+4^\circ$ (σ_{rms} expressed as a percentage of the average calorimeter signal).

<i>Signal type</i>	<i>Preshower Detector</i>	<i>Tilt angle θ</i>	<i>Response variation</i>
Čerenkov	IN	1°	0.34%
Scintillation	IN	1°	0.35%
Čerenkov	OUT	1°	0.56%
Scintillation	OUT	1°	0.81%
Čerenkov	IN	2°	0.33%
Scintillation	IN	2°	0.44%
Čerenkov	OUT	2°	0.36%
Scintillation	OUT	2°	0.85%

3.2 The angular dependence of the energy resolution

3.2.1 The difference between the scintillation and Čerenkov signals

The energy resolutions measured for the 20 GeV electrons showering in the calorimeter are shown in Figure 6 as a function of the azimuth angle of incidence ϕ , separately for the scintillation and the Čerenkov signals. The tilt angle θ was 1° and the preshower detector was out of the beam line for these particular results. The figure shows remarkable differences between the two types of signals. Not only is the energy resolution significantly worse for the scintillation signals, for all angles in this range, but the resolution measured for the scintillation signals also depends strongly on the angle of incidence, unlike the resolution measured with the Čerenkov signals.

These results are consistent with earlier observations that the energy resolution at a fixed angle of incidence ($\phi = 1.5^\circ, \theta = 1.0^\circ$) tends to become better for the Čerenkov signals than for the scintillation ones as the energy of the electron beam increases [8]. Since the sampling structure is the same for both types of fibers, and the light yield considerably larger (and event-to-event fluctuations in the number of scintillation photoelectrons thus correspondingly smaller), one would naively expect to measure better energy resolutions for the scintillation signals. The fact that the opposite effect is experimentally observed is a consequence of the extremely collimated nature of the em showers in the early stage of the shower development, before the shower maximum is reached, *i.e.*, in the first 10 cm of this particular calorimeter.

Neighboring fibers of the same type are separated by 2 - 3 mm (edge-to-edge, see Figure 1b) and that distance is of the same order as the shower width in this early

Fig. 6. The energy resolution measured for 20 GeV electrons in the scintillation and the Čerenkov channels, as a function of the azimuth angle of incidence (ϕ) of the beam particles. The tilt angle θ was 1° , and the PSD was out of the beam line.

stage of the shower development. Therefore, the calorimeter signal (from this early shower component) depends crucially on the impact point of the particles, if these enter the calorimeter parallel to the fibers. This dependence is quickly reduced when the particles enter the calorimeter at a small angle with the fibers. For example, at 2° the lateral displacement over a depth of 10 cm already amounts to 3.5 mm, comparable with the fiber-to-fiber distance. As the angle increases, this early collimated shower component is thus sampled more and more in the same way as the rest of the shower. However, at angles where this is not the case, this effect adds an additional component to the em energy resolution. This effect is, in first approximation⁸, energy independent and thus acts as a constant term.

Now, why does this phenomenon only affect the resolution measured with the scintillation signals? The reason is that the collimated early shower component does *not* contribute to the Čerenkov signals, since the Čerenkov light produced by shower particles traveling in the same direction as the fibers falls outside the numerical aperture of the fibers. Another spectacular consequence of this phenomenon is the fact that calorimeters of this type can distinguish event-by-event between the energy loss in the form of ionization and radiation when detecting muons, since the Čerenkov fibers only produce signals for the bremsstrahlung component [13]. For

⁸ The depth of the shower maximum increases with the shower energy, but this is a logarithmic effect. For example, the shower maximum for 10 GeV electrons in copper is located at $\sim 5X_0$, and for 100 GeV at $\sim 8X_0$.

the 20 GeV electrons, the Čerenkov fibers thus only register shower particles that travel at relatively large angles with the shower axis ($20 - 60^\circ$), and such particles are for all practical purposes only found beyond the shower maximum, where the shower is wide compared to the typical distance separating neighboring fibers of the same type. The “constant” term that affects the scintillation resolution is thus practically absent for the Čerenkov signals.

3.2.2 Effects of the PSD and the tilt angle

The results measured for a tilt angle $\theta = 2^\circ$ confirm the above explanation. This is illustrated in Figure 7, where the energy resolution is shown as a function of the azimuth angle ϕ , for the measurements performed at $\theta = 1^\circ$ and at $\theta = 2^\circ$. The deterioration of the energy resolution for small angles ϕ is considerably smaller for the $\theta = 2^\circ$ data, because it is the *total* angle (*i.e.*, a combination of ϕ and θ) that counts in this context. As expected, the energy resolution measured for the Čerenkov signals is not affected by the change of the angle of incidence of the beam particles.

Fig. 7. The energy resolution measured for 20 GeV electrons in the scintillation and the Čerenkov channel, as a function of the azimuth angle of incidence (ϕ) of the beam particles. Results are compared for tilt angles θ of 1° and 2° . These results were obtained with the PSD in the beam line.

However, a careful comparison of the Čerenkov results shown in Figures 6 and 7 does reveal some differences. These are due to the fact that the PSD was in the beam line in one case (Figure 7) and out in the other (Figure 6). We investigated the effects of the PSD absorber on the measured energy resolutions in a systematic way.

330 The results of this analysis are shown in Figure 8. It turns out that opposing effects
 331 are observed for the energy resolution measured with the two types of signals.

Fig. 8. The energy resolution measured for 20 GeV electrons in the scintillation and Čerenkov channels, as a function of the azimuth angle of incidence (ϕ) of the beam particles. Results are compared for data taken with and without the preshower detector in the beam line. The tilt angle θ was 1° in both cases.

332 The energy resolution measured with the Čerenkov signals deteriorates when the
 333 PSD is in the beam line. This is to be expected, since the fluctuations that deter-
 334 mine the energy resolution of the calorimeter are now increased because of the
 335 additional fluctuations in the amount of energy absorbed by this upstream device.
 336 Surprisingly, the energy resolution measured with the scintillation signals exhibits
 337 the opposite effect, it *improves* as a result of installing the $1X_0$ thick absorber up-
 338 stream of the calorimeter. This effect is a consequence of the fact that the absorber
 339 causes the shower to start effectively 80 cm upstream of the calorimeter proper. As
 340 a result, upon entering the calorimeter, the shower is somewhat less radially colli-
 341 mated than when the beam particles enter the calorimeter undisturbed. Therefore,
 342 the impact point dependence of the calorimeter response is somewhat reduced, and
 343 it is this impact point dependence that is responsible for the fact that the scintilla-
 344 tion resolution is so much worse for the scintillation signals than for the Čerenkov
 345 ones, at very small angles of incidence.

346 The effect of the PSD absorber on the measured energy resolution is summarized in
 347 Table 2, for both signals and for both tilt angles used in these experiments. The table
 348 shows that the energy resolution measured with the Čerenkov signals gets worse by
 349 $\sim 7\%$, while the resolution measured with the scintillation signals improves by a

Table 2

The effect of the upstream (PSD) absorber on the energy resolution of the calorimeter for 20 GeV electrons. Shown is the effect averaged over 21 azimuth angles of incidence ϕ , ranging from -4° to $+4^\circ$. The change in the fractional energy resolution (expressed as a percentage of the average calorimeter signal) is positive if the resolution gets worse (*i.e.*, increases) when the PSD is inserted in the beam line. A negative effect indicates that the energy resolution gets better (*i.e.*, decreases) as a result of this operation.

Signal type	Tilt angle θ	Change in fractional energy resolution
Čerenkov	1°	$(+6.0 \pm 0.7)\%$
Scintillation	1°	$(-6.8 \pm 1.3)\%$
Čerenkov	2°	$(+8.3 \pm 0.5)\%$
Scintillation	2°	$(0 \pm 1.3)\%$

350 similar percentage for a tilt angle $\theta = 1^\circ$. When the tilt angle is increased to 2° ,
 351 there is no net change in the scintillation resolution. Since the effective angle of
 352 incidence of the beam particles is now larger, the effects that either deteriorate the
 353 resolution (by means of fluctuations in the energy deposited in the calorimeter) or
 354 improve it (by means of increasing the shower width) apparently cancel each other
 355 in this case.

Fig. 9. The energy resolution measured for 20 GeV electrons in the scintillation and Čerenkov channels, as a function of the azimuth angle of incidence (ϕ) of the beam particles. Results are compared for data taken with and without the preshower detector in the beam line. The tilt angle θ was 2° in both cases.

356 This is illustrated by Figure 9, which shows the energy resolution for the two types

of signals as a function of the azimuth angle of incidence, for data taken with and without the PSD in the beam line, at a tilt angle $\theta = 2^\circ$.

3.3 Combining the two types of signals

The use of two independent signals in dual-readout calorimeters is inspired by the beneficial effects of measuring the em shower component event by event for the hadronic calorimeter performance. For the detection of em showers, initiated by electrons or photons, there is absolutely no compelling reason to consider these signals separately. Both types of fibers sample the em showers independently and, as illustrated by the results shown in Figures 6 and 7, the Čerenkov signals provide an even better energy resolution for small angles of incidence, despite the considerably smaller light yield. There is thus absolutely no reason why one should not use the combination of both signals to measure the properties of the showering electrons or photons. Since the sampling fraction and the sampling frequency are twice as large as for the two individual channels, one should expect the contribution of sampling fluctuations to the energy resolution to be reduced by as much as a factor of $\sqrt{2}$ ⁹. In addition, the much smaller effective fiber-to-fiber distance should reduce the angular dependence of the energy resolution.

Figure 10 shows the energy resolution for the 20 GeV electron showers for the sum of the scintillation and the Čerenkov signals, as a function of the azimuth angle of incidence ϕ . For comparison, the results measured for the two signals separately are shown as well. The results qualitatively confirm the naive expectation formulated above. Using the sum of both signals, the energy resolution is found to be better than for the individual signals, and less dependent on the angle of incidence than the resolution measured with the scintillation signals. This is good news, since it means that the dual-readout fiber calorimeter is not only an excellent hadron calorimeter, but also provides good performance for em showers, even at the very small angles of incidence studied in this paper. In compensating calorimeters such as the ZEUS [16] and SPACAL [17] ones, the em energy resolution was limited by sampling fluctuations, which were relatively large because of the requirement of a small sampling fraction. This requirement does not apply for our calorimeter, where the sampling fluctuations (and thus the em energy resolution) can be made much smaller.

The em energy resolution for each of the two signals is determined by sampling fluctuations and by fluctuations in the number of photoelectrons. Apart from these stochastic fluctuations, there is also an angle dependent constant term which only

⁹ Sampling fluctuations are determined by the number of different shower particles (N) that contribute to the calorimeter signal. If this number doubles, then the statistical precision of this number ($\sqrt{N}/N = 1/\sqrt{N}$), and thus the energy resolution, improve by a factor $\sqrt{2}$. See Reference [11] for more details.

Fig. 10. The energy resolution measured for 20 GeV electrons in the scintillation and the Čerenkov channels and for the sum of both signals, as a function of the azimuth angle of incidence ϕ . The (green) crosses represent Equation 1. The tilt angle θ was 2° and the PSD was out of the beam line.

contributes to the scintillation resolution. Because of the structure of the calorimeter, the sampling fluctuations are the same for both types of signals, and if these were the only contribution to the energy resolution, then one would expect the resolution to be smaller by a factor of $\sqrt{2}$ for the combined signal. If photoelectron statistics would only affect the Čerenkov resolution, and the constant term only the scintillation resolution, one can show that the resolution for the combined signals is equal to

$$\frac{\sigma_{[C+S]/2}}{E} = \frac{\sqrt{(\sigma_C/E)^2 + (\sigma_S/E)^2}}{2} \quad (1)$$

The (green) crosses in Figure 10 represent the result of this calculation. They describe the measured resolution very well for angles $\phi \geq 2^\circ$.

The fact that the energy resolution in the Čerenkov channel is 5% leads immediately to the conclusion that this signal must consist of at least 400 photoelectrons (20 Cpe/GeV). If we include the contributions of sampling fluctuations, which may be estimated at 2.8% (see Section 4), we find a Čerenkov light yield of 30 Cpe/GeV (*i.e.*, 600 photoelectrons for 20 GeV showers). Sampling fluctuations also contribute 2.8% to the energy resolution for the scintillation channel. Therefore, the constant term deriving from the impact point dependence of the response clearly dominates this resolution, for all angles of incidence studied here. However, by combining the Čerenkov and scintillation signals, the value of this constant term drops below 2% for angles of incidence larger than 2 degrees. This is consistent

411 with our previous findings [8].

412 The angular energy resolution measured with the scintillation signals exhibits an
413 asymmetry, in the sense that the resolution is better for positive values of ϕ than for
414 the corresponding negative ones. The same phenomenon is observed for the $\theta =$
415 2^{circ} in Figure 7, where the PSD was installed in the beam line. The asymmetry is
416 much smaller at $\theta = 1^\circ$ (Figures 7, 8). We assume that the mentioned asymmetry
417 is caused by the fact that different fibers contribute to the signals and the fiber-to-
418 fiber response differences are not necessarily the same at relatively large positive
419 and negative angles. The impact point dependence of the response that is the topic
420 of our study should be symmetric with the angle of incidence. However, as the
421 angle increases, the impact point dependence gradually vanishes, while the other
422 mentioned effect increases and gets its chance to affect the results.

423 3.4 Monte Carlo simulations

424 One of the reasons for performing the studies described in this paper¹⁰ was the
425 prediction by Monte Carlo simulations of some very specific effects that would
426 occur for very small angles of incidence [10]. These predictions included:

- 427 (1) A dip in the calorimeter response when the angle of incidence $\theta = \phi$.
- 428 (2) An electron resolution for the sum of the scintillation and Čerenkov signals
429 that is significantly better, by more than a factor of $\sqrt{2}$, than the resolution
430 measured for either of the two types of signals individually.
- 431 (3) An anti-correlation between the signals measured with the scintillating fibers
432 and the signals measured with the Čerenkov fibers.

433 The first effect would be due to the fact that when $\theta = \phi$, the shower axis may
434 penetrate over some depth inside the calorimeter without encountering a single
435 fiber. In Figure 11, the experimentally measured response is shown together with
436 the GEANT4 prediction, as a function of the azimuth angle of incidence ϕ , for a
437 tilt angle $\theta = 1^\circ$. Neither the experimental data nor the Monte Carlo simulations
438 show any evidence for a dip at $\theta = \phi = 1^\circ$. No dip was observed for $\theta = \phi = 2^\circ$
439 either. It should be pointed out that the calculations described in [10] concerned a
440 calorimeter with the same structure as the current one, but with lead as absorber
441 material, instead of copper. Whereas lead and copper have approximately the same
442 Moliere radius, the radiation length in copper is larger than that in lead by about
443 a factor of three. While the showers in these two calorimeters thus have approx-
444 imately the same lateral dimensions, they penetrate much deeper into the copper
445 structure. The probability that the early, collimated shower part is less efficiently
446 sampled for angles of incidence $\theta = \phi$ is thus smaller in copper.

¹⁰ Relevant details about the GEANT4 Monte Carlo simulations performed in the context
of the studies described in this paper can be found in Reference [10].

Fig. 11. Comparison between the measured calorimeter response (a, c) and the GEANT4 prediction (b, d), as a function of the azimuth angle ϕ , for a tilt angle $\theta = 1^\circ$. Results are given separately for the scintillation (a, b) and Čerenkov (c, d) signals, with the PSD out of the beam line. In all four diagrams, the grey areas represent response values that differ less than 1% from the average value.

The calorimeter response does exhibit some dependence on the angle of incidence, but the variations are small, typically less than 1% of the average value (represented by the grey areas in Figure 11). The Monte Carlo simulations describe these variations better in the case of the Čerenkov signals than for the scintillation ones.

The position dependence of the scintillation signal that is the cause of the angular dependence of the scintillation resolution (Figure 6) implies a larger signal when the beam particle enters the calorimeter inside a scintillating fiber than at a position in between two scintillating fibers. Effects 2 and 3 listed above are closely related, since the GEANT4 simulations predict a similar effect for the Čerenkov signals. In other words, when the scintillation signal reaches its maximum value, the Čerenkov signal is at its minimum. This anti-correlation between the two types of signals is visible in the scatter plot shown in Figure 12(b,d). It is also an important factor for the improvement in the energy resolution when both signals are combined (Figure 13).

However, the predicted anti-correlation is *not* confirmed by the measurements. The experimental data shown in Figures 12(a,c) and 13 are clearly at variance with the GEANT4 results. The absence of an anti-correlation between the two experimental signals should not really be a surprise, since the strong angular dependence of the

Fig. 12. Scatter plots of the Čerenkov versus the scintillation signals for 20 GeV electrons in the RD52 copper dual-readout calorimeter. Experimental data (a) are compared with GEANT4 simulations (b). Also shown are the average Čerenkov signals as a function of the average scintillation signal, measured in slices with a width of 0.4 GeV (c, d). The angle of incidence of the beam particles was ($\phi = 1.5^\circ$, $\theta = 1.0^\circ$).

calorimeter resolution observed for the scintillation signals was found to be absent for the Čerenkov signals (Figures 6 - 9). Since this angular dependence is a direct consequence of the impact point dependence of the calorimeter response, there is thus no reason for an anti-correlation between the two signals.

In Figure 13, the measured energy resolutions are compared with those predicted by the GEANT4 simulations. Results are given separately for the scintillation signals (Figure 13a,b), the Čerenkov signals (Figure 13c,d) and the sum of both signals (Figure 13e,f), for a tilt angle $\theta = 1^\circ$. The simulated energy resolution for the scintillation signals also exhibits a substantial dependence on the angle of incidence, but the resolution values are considerably better than the experimental ones. In addition, there is a significant increase in the resolution for $\phi = \theta = 1^\circ$, an effect that was not observed in the experimental data.

Fig. 13. Comparison between the measured energy resolution for 20 GeV electrons of the RD52 calorimeter and the GEANT4 prediction, as a function of the azimuth angle ϕ , for a tilt angle $\theta = 1^\circ$. Results are given separately for the scintillation and Čerenkov signals, and for the sum of both signals. The error bars are statistical only.

477 The energy resolution in the Čerenkov channel also exhibits a maximum value
 478 around $\phi = \theta = 1^\circ$, but the angular dependence is clearly smaller than in the
 479 scintillation case. We also notice that the simulated energy resolution is signifi-
 480 cantly worse than the measured value, for all angles considered here. In addition,
 481 the measured energy resolution is independent of the angle of incidence.

482 The resolutions for the sum of both signals are most similar. The resolution deteri-
 483 orates slightly when the angle of incidence approaches zero degrees, but the effects
 484 are considerably smaller than for the scintillation signal alone. Since the resolution
 485 is overestimated in one case and underestimated in the other, the simulated resolu-
 486 tion for the sum of the signals is in rather good agreement with the experimental
 487 value, ranging from 3-4% in the simulations and 4-5% experimentally.

One may wonder what causes the differences between the experimental and simulated characteristics of the performance of our calorimeter in detecting 20 GeV electron showers. We believe that the intricate calorimeter structure may be an important factor. The calorimeter consists of several different materials (copper, polystyrene, PMMA, air) separated by one millimeter or less, and this represents a very demanding environment for shower simulations. Moreover, the showers are initially extremely collimated, with lateral dimensions that are even small compared to the fiber-to-fiber distance. As a result, the calorimeter (scintillation) signal depends sensitively on the precise impact point of the beam particles. The beam spot is chosen to be $8 \times 8 \text{ mm}^2$. This area contains on average 15 fibers of each type, but depending on its precise location and the angle of incidence it may also be effectively 14 in one case and 16 in another. This may lead to significant effects on the response and energy resolution. Experimentally, we don't have information on the precise structure of the beam spot, at the relevant (sub-)mm level. These factors make a detailed comparison between the experimental and simulated results a challenging proposition.

4 Discussion

4.1 High resolution calorimetry

The results of the studies presented in this paper, combined with the Monte Carlo simulations of the hadronic performance of a full-scale calorimeter of the type tested here [14,15], complete the information needed to come to a total assessment of the experimental performance of the copper based dual-readout fiber calorimeter relative to that of “traditional” compensating calorimeters such as the ones used by the ZEUS experiment [16] and built in the context of the SPACAL project [17]. The latter calorimeters did provide excellent hadronic energy resolution ($\sim 35\%/\sqrt{E}$), but suffered from two drawbacks:

- (1) Because of the use of high- Z absorber material, depleted uranium in the case of ZEUS, lead in the case of SPACAL, the e/mip ratio of these calorimeters was about 0.6 (ZEUS) or 0.7 (SPACAL). This means that the calorimeter response to (em or hadronic) showers was only 60 - 70% as large as that of particles that deposited their entire energy in the form of ionization of the absorber material. This phenomenon adversely affected the resolution for jets, where a significant fraction of the energy is carried by soft hadrons that range out rather than develop showers. The fluctuations in the fraction of the jet energy carried by such particles contribute to the energy resolution and thus make it worse than for single hadrons.
- (2) To achieve compensation, these calorimeters needed to have a very specific sampling fraction for charged particles, such as to achieve the right response to the many neutrons produced in the hadronic shower development. This sampling fraction was small, *e.g.*, 2.4% in the case of SPACAL. As a result, the

528 em energy resolution was not very good in these calorimeters, since that reso-
 529 lution is typically dominated by sampling fluctuations. For 20 GeV electrons,
 530 both SPACAL and ZEUS reported an em energy resolution in excess of 4%.

531 These effects are strongly mitigated in the calorimeter that is the topic of this pa-
 532 per. Even though the calorimeters we have built so far are too small to fully contain
 533 hadron showers, Monte Carlo simulations suggest that hadronic energy resolutions
 534 of $30\%/\sqrt{E}$ should be attainable in a sufficiently large detector [14,15]. Since a
 535 relatively low- Z absorber is used, the effects of fluctuations in the jet fraction car-
 536 ried by non-showering hadrons should be much smaller than in calorimeters based
 537 on high- Z absorber material. The e/mip ratio of copper is 0.85, *i.e.*, much closer
 538 to the ideal value (1.0) than for structures based on uranium as absorber material.

539 Concerning the electromagnetic performance, the RD52 calorimeter offers the ad-
 540 vantage that the sampling fraction is not constrained by the compensation require-
 541 ment. Our data show that, even in the very unfavorable condition when electrons or
 542 photons enter the calorimeter at very small angles of incidence, resolutions better
 543 than those reported by ZEUS and SPACAL are obtained in some cases (*e.g.*, 3.4%
 544 at $\phi = 3^\circ$, Figure 10). At larger angles of incidence, further improvement may be
 545 expected, since the impact point dependence of the scintillation signals vanishes.
 546 According to the standard formula describing the contributions of sampling fluc-
 547 tuations¹¹ to the em energy resolution [11], such fluctuations limit this resolution
 548 to $8.3\%/\sqrt{E}$ in the calorimeter used for the present studies, *i.e.*, $\sim 2.0\%$ for 20
 549 GeV electrons. Fluctuations in the number of Čerenkov photoelectrons increase
 550 this limit to $\sim 2.8\%$.

551 4.2 The tricky effects of C/S cuts

552 The studies performed in the context of this paper taught us one valuable lesson,
 553 worthy of sharing with the readership. As described in Section 2.3, the 20 GeV
 554 particle beam used for our studies contained a substantial fraction of pions and
 555 muons. These particles could be effectively removed from the event samples by
 556 means of the external detectors (preshower detector, tail catcher and muon counter).
 557 However, in measurements without an upstream absorber (*i.e.*, the PSD was out of
 558 the beam line), it turned out to be challenging to completely eliminate the pion
 559 contamination.

560 In a previous study [9], we found that the Čerenkov/scintillation calorimeter signal
 561 ratio was an efficient tool to discriminate between electrons and pions. Therefore,
 562 we tried to clean up our electron event samples by means of a cut on that signal
 563 ratio. Figure 14 shows that this worked quite well. The pion contamination, visible

¹¹ The dependence of the sampling term on the sampling fraction and the sampling frequency is well described by $a_{\text{samp}} = 2.7\% \sqrt{d/f_{\text{samp}}}$, where the fiber diameter d and the sampling fraction for mips f_{samp} are 1 mm and 9.2%, respectively [11].

Fig. 14. Signal distributions for the Čerenkov and scintillation signals with and without a cut on the ratio of these two signals. The angle of incidence of the 20 GeV electrons was ($\phi = 0 \pm 0.5^\circ$, $\theta = 1^\circ$). The preshower detector was out of the beam line. See text for more details.

as a broad bump below 15 GeV, was reduced by a factor of five retaining only events with $C/S > 0.92$, while the contents of the electron peak were about 20% smaller as a result of this cut. However, this figure shows one other amazing effect, namely the improvement in the energy resolution for the electrons, from 8.8% to 7.3% in the scintillation signal. These data concern the measurements at a tilt angle of 1° and an azimuth angle $\phi = 0 \pm 0.5^\circ$, in other words the configuration for which the effects of the impact point dependence of the scintillation energy resolution reaches its maximum (see Figure 8). And the observed improvement as a result of this C/S cut is even larger than that resulting from inserting the PSD absorber in the beam line. What is going on here?

By retaining events with a large C/S signal ratio, one selectively eliminates events with a large scintillation signal. These are predominantly events in which the beam particles entered the calorimeter close to a scintillating fiber. In this procedure, the effect of the impact point dependence on the energy resolution is diminished, and therefore the measured energy resolution improves, especially in the scintillation channel, where this dependence plays a key role.

Additional support for this explanation may be derived from Figure 15, which shows the calorimeter response to 20 GeV electrons as a function of the azimuth

Fig. 15. The average calorimeter signal for 20 GeV electrons in the scintillation (a) and Čerenkov (b) channels, as a function of the azimuth angle of incidence (ϕ) of the beam particles. The tilt angle θ was 1° and the preshower detector was out of the beam line. Only events with a Čerenkov/scintillation signal ratio larger than 0.9 are included. The error bars only include statistical effects.

angle of incidence, ϕ , for events selected with a cut on the C/S calorimeter signal ratio. As was demonstrated experimentally in reference [18] and confirmed by GEANT4 simulations [10], the scintillation response is larger when the electrons enter the calorimeter inside a scintillating fiber rather than in between scintillating fibers, especially at very small angles of incidence. The selective elimination of events, resulting from the C/S cut, increases with the impact point dependence of the S signals and is thus largest for angles at which the particles enter the calorimeter parallel to the fibers. This is what is observed in Figure 15a.

This experience constitutes an example of the importance of one of the fundamental rules of testing calorimeters: If one wants to measure the performance of a calorimeter, one should *only* use external detectors to select events (in this case to eliminate pions from the mix), not the calorimeter signals themselves, since this might lead to biased event samples.

Acknowledgments

We thank CERN for making good particle beams available to our experiments in the H8 beam. This study was carried out with financial support of the United States Department of Energy, under contract DE-FG02-12ER41783, by Italy's Istituto Nazionale di Fisica Nucleare and Ministero dell'Istruzione, dell'Università e della Ricerca, and by the Basic Science Research Program of the National Research Foundation of Korea (NRF), funded by the Ministry of Science, ICT &

602 Future Planning under contract 2015R1C1A1A02036477. In addition, we thank
603 Korea University for the support received by their researchers who contributed to
604 this project.

605 References

- 606 [1] E. Eskut *et al.*, Nucl. Instr. and Meth. **A401** (1997) 7.
- 607 [2] A. Antonelli *et al.*, Nucl. Instr. and Meth. **A354** (1995) 352.
- 608 [3] S.J. Alvsvåg *et al.*, Nucl. Instr. and Meth. **A290** (1990) 320.
- 609 [4] M. Beck *et al.*, Nucl. Instr. and Meth. **A381** (1996) 330.
- 610 [5] G. Bayatian *et al.*, Eur. Phys. J. **C53** (2008) 139.
- 611 [6] R. Wigmans, New Journal of Physics **10** (2008) 025003.
- 612 [7] R. Wigmans, in *Handbook of Particle Detection and Imaging*, eds. C. Grupen and I.
613 Buvat, vol. 1, 497-517, Springer Verlag (2011).
- 614 [8] N. Akchurin *et al.*, Nucl. Instr. and Meth. **A735** (2014) 130.
- 615 [9] N. Akchurin *et al.*, Nucl. Instr. and Meth. **A735** (2014) 120.
- 616 [10] N. Akchurin *et al.*, Nucl. Instr. and Meth. **A762** (2014) 100.
- 617 [11] R. Wigmans, *Calorimetry, Energy Measurement in Particle Physics*, International
618 Series of Monographs on Physics, Vol. 107, Oxford University Press (2000).
- 619 [12] N. Akchurin *et al.*, Nucl. Instr. and Meth. **A548** (2005) 336.
- 620 [13] N. Akchurin *et al.*, Nucl. Instr. and Meth. **A533** (2004) 305.
- 621 [14] R. Wigmans *et al.*, *RD52 Status Report 2015: Dual-Readout Calorimetry for High-*
622 *Quality Energy Measurements*, Internal document CERN-SPSC-2015-015, CERN,
623 Genève, Switzerland.
- 624 [15] R. Wigmans, *New Results from the RD52 Project*, Proc. of the 13th Pisa Meeting on
625 “Frontier Physics for Frontier Detectors”, May 24-30 2015, La Biodola, Elba (Italy),
626 accepted for publication in Nucl. Instr. and Meth.
- 627 [16] G. Drews *et al.*, Nucl. Instr. and Meth. **A290** (1990) 335.
- 628 [17] D. Acosta *et al.*, Nucl. Instr. and Meth. **A308** (1991) 481.
- 629 [18] N. Akchurin *et al.*, Nucl. Instr. and Meth. **A536** (2005) 29.