Title:

Interaction of Cosmic Ray Muons with Spent Nuclear Fuel Dry Casks and Determination of
Lower Detection Limit

Authors:

S. Chatzidakis^{*}, C.K. Choi, L.H. Tsoukalas

Purdue University, School of Nuclear Engineering, West Lafayette, IN 47907

***Contact Info:**

Tel: +1 765-496-6136, Fax: +1 765-494-9570, E-mail: schatzid@purdue.edu

Abstract

The potential non-proliferation monitoring of spent nuclear fuel sealed in dry casks interacting continuously with the naturally generated cosmic ray muons is investigated. Treatments on the muon RMS scattering angle by Moliere, Rossi-Greisen, Highland and, Lynch-Dahl were analyzed and compared with simplified Monte Carlo simulations. The Lynch-Dahl expression has the lowest error and appears to be appropriate when performing conceptual calculations for high-Z, thick targets such as dry casks. The GEANT4 Monte Carlo code was used to simulate dry casks with various fuel loadings and scattering variance estimates for each case were obtained. The scattering variance estimation was shown to be unbiased and using Chebyshev's inequality, it was found that 10^6 muons will provide estimates of the scattering variances that are within 1% of the true value at a 99% confidence level. These estimates were used as reference values to calculate scattering distributions and evaluate the asymptotic behavior for small variations on fuel loading. It is shown that the scattering distributions between a fully loaded dry cask and one with a fuel assembly missing initially overlap significantly but their distance eventually increases with increasing number of muons. One missing fuel assembly can be distinguished from a fully loaded cask with a small overlapping between the distributions which is the case of 100,000 muons. This indicates that the removal of a standard fuel assembly can be identified using muons providing that enough muons are collected. A Bayesian algorithm was developed to classify dry casks and provide a decision rule that minimizes the risk of making an incorrect decision. The algorithm performance was evaluated and the lower detection limit was determined.

Keywords: Muons, monitoring, spent nuclear fuel, dry casks, classification, lower detection limit

1. Introduction

Cosmic ray muons could play an important role in nuclear nonproliferation and monitoring nuclear material, presenting advantages over existing methods. Cosmic ray muons are charged particles generated naturally in the atmosphere from high energy cosmic rays. Cosmic ray muons have approximately 200 times the mass of electron and, impinge upon the earth at an approximate rate of $10,000 \text{ particles m}^{-2} \text{ min}^{-1}$ [1]. Muons have the ability to penetrate high density materials, are freely available, no radiological sources are required and consequently there is a total absence of any artificial radiological dose. A system that monitors the interactions and tracks the path of muons could serve as a unique way to monitor the contents of a sealed and shielded container, where any significant deviations in scattering distribution would imply material diversion. Conventional methods, e.g., X-rays, are limited in that they cannot penetrate dense well-shielded objects [2]. More sophisticated techniques such as penetrating neutrons require the deployment of an expensive accelerator [3]. Relativistic muons, naturally generated in the atmosphere, have sufficient energy to pass completely through sealed dense containers and by monitoring the muon tracks it is possible to deduce the content within [3].

Potential muon monitoring applications could be used to verify international treaty declarations in proving that the diversion of plutonium has not occurred including the removal of spent nuclear fuel from dry casks. Since the early 1950's, approximately 65,000 metric tons of used fuel have been generated, 75% of which are stored in spent fuel pools while the remaining 25% is under dry storage conditions [4]. The postponement of the opening of a permanent repository until 2048 has led to increased used fuel accumulation at reactor sites. As a result, utilities have built dry storage facilities, known as Independent Spent Fuel Storage Installations (ISFSIs). In the next few years, essentially all plants will have reached capacity of their spent fuel pools and ISFSIs will be required. After the spent

nuclear fuel has been placed inside the dry cask, the cask is sealed, not allowing for visual inspection. Monitoring nuclear waste and controlling nuclear material at its source could minimize the risks of nuclear proliferation and reduce potential homeland threats [5].

Cosmic ray muons have been investigated over the years with emphasis in archaeology, volcano imaging and material identification. It is worth noting the pioneering work of E. P. George [6] who measured cosmic ray muon flux attenuation to infer rock depth covering underground tunnels and that of L. Alvarez et al. [7] who searched for hidden chambers within the Egyptian pyramids. Similar methods were used to image volcanoes for determining magma location for use in eruption prediction models. Nagamine [8] used large horizontal muon detectors and on one side of the Mt. Tsukuba and based on muon attenuation principles reconstructed the internal structure of the volcano. Muons are also being investigated to image Mt. Vesuvius [9]. Recent efforts led to development of imaging algorithms for cargo scanning and molten fuel location [10-13]. LANL demonstrated the use of muons and multiple Coulomb scattering to detect high Z materials hidden in a large volume of low Z materials and developed muon detectors suitable for surveillance of cross-border transport containers [14]. Hogan et al. [15] used a large muon detector with resolution of 400 μm (FWHM) for the detection of high Z targets against low Z backgrounds in the order of minutes. It was pointed out that momentum measurement could improve image resolution and a method to indirectly obtain momentum estimates by measuring muon scattering in several layers of materials with known thickness was proposed. Initially, Point-of-Closest-Approach (PoCA), a geometry-based reconstruction algorithm inspired by earlier work on nuclear scattering radiography [16], was developed and used [17]. Schultz later on derived a more detailed algorithm based on statistical reconstruction techniques [13]. The algorithm is based on measured muon scattering and displacement information and the results provided improved reconstruction images. However, later work pointed computation and

memory usage issues that may limit its use [12]. Computational performance was then improved by an updated version of the imaging algorithm based on Expectation-Maximization [18].

In the present treatment, the applicability of muons for monitoring of spent nuclear fuel dry casks is investigated. Purpose is to use muons to differentiate between spent nuclear fuel dry casks with different amounts of fuel loading. The theory of multiple Coulomb scattering is explored to obtain the most representative feature describing the passage of muons through matter. The GEANT4 Monte Carlo code coupled with a “Muon Generator” was used to simulate dry casks with various fuel loadings e.g., fully loaded, half loaded, one row of fuel assemblies missing, one fuel assembly missing and empty, and scattering variance estimates for each case were obtained. Using Chebyshev’s inequality, 10^6 muons will provide scattering variances estimates that are within 1% of the true value at a 99% confidence level. The relative difference when one fuel assembly is missing is in the order of 1% to 5% depending on detector size and dry cask orientation. These estimates were used as reference values to calculate scattering distributions and evaluate the asymptotic behavior for small variations on fuel loading. It is shown that the scattering distributions between a fully loaded dry cask and one with a fuel assembly missing initially overlap significantly but their distance eventually increases with increasing number of muons. At least 100,000 muons are needed to distinguish one missing fuel assembly from a fully loaded cask. A Bayesian monitoring algorithm was developed to classify dry casks and provide a decision rule that minimizes the risk of making an incorrect decision.

A brief description of muon characteristics and available theoretical treatments on multiple scattering of muons are described in Section 2. Section 3 provides details related to dry cask simulations using GEANT4 and statistical analysis of the scattering variance

estimations, respectively. Finally, the developed Bayesian monitoring algorithm along with performance evaluation are presented and discussed in Sections 4 and 5.

2. Cosmic ray muons

Cosmic radiation, originating mainly from outside our solar system constantly bombards the upper layers of the Earth's atmosphere [19]. Measurements showed that cosmic radiation comprises of 98% protons and heavier nuclei and 2% of electrons [9]. Out of the 98% of protons and heavier nuclei, 87% are protons, 12% are helium nuclei and the rest are heavier nuclei. The magnetosphere and the ozone layer of the atmosphere create a protective layer that filters and shields from cosmic radiation. However, a small amount penetrates into the atmosphere where it collides with the molecules of the atmosphere creating extensive showers of secondary particles that eventually reach sea-level. As a result of processes occurring in the atmosphere, the hadronic component, the electromagnetic component and the muonic component represent the spectrum of particles reaching the surface. The secondary particle shower includes protons, neutrons, pions, kaons, gammas, electrons and positrons. Muons are produced from pion or kaon decay. A particle shower is represented schematically in Fig. 1.

Fig. 1. Representation of a cosmic ray shower

Cosmic ray muons passing through matter lose energy from inelastic collisions with electrons and are deflected from nuclei due to multiple Coulomb scattering. This deflection is the sum of all the small random contributions during a muon's path [20]. Different treatments have been published on the multiple scattering of charged particles by atoms. Of these, Moliere's theory, which remains analytical to the end [20], is in good agreement with most of experimental data. Moliere derived the angular scattering distribution starting from Rutherford's single scattering formula using the small angle approximation. The root mean square (RMS) scattering angle of the Gaussian part in Moliere's scattering distribution is given by [21]:

$$\theta_{RMS}^M = \chi_c \sqrt{B} \quad (1)$$

where:

$$B = 1.153 + 2.583 \log(\chi_c / \chi_a)^2 \quad (2)$$

Moliere defined a characteristic angle, χ_c , which was later corrected by Bethe to account for the inelastic scattering off atomic electrons. For a homogeneous target it is given by:

$$\chi_c^2 = \frac{4\pi N_A \rho X Z^2 Z(Z+1)e^4}{Ap^2\beta^2 c} \quad (3)$$

158 where N_A is Avogadro's number, Z and A the atomic and mass number, ρ is the density of
 159 the materials, X material thickness. Moliere used the Thomas-Fermi model to account for the
 160 screening of the Coulomb potential by the atomic electrons and derived an expression for the
 161 screening angle, χ_a :

$$\chi_a^2 = \chi_0^2(R + 3.76\eta^2) \quad (4)$$

162 where $R=1.13$. R is constant for all Z and:

$$\chi_0 = 1.13\alpha(m_e c/p)Z^{1/3} \quad (5)$$

$$\eta = \frac{zZe^2}{\hbar v} \quad (6)$$

163 A considerably simpler expression was introduced by Rossi and Greisen [22] that has been
 164 extensively used due to its simplicity:

$$\theta_{RMS}^{RG} = \frac{21.2 \text{ MeV}}{\beta c p} \sqrt{\frac{X}{X_0}} \quad (7)$$

165 In 1975, Highland [23] suggested a correction term to the Rossi-Greisen formula which
 166 results to the following expression, currently adopted by Particle Data Group [24]:

$$\theta_{RMS}^H = \frac{13.6\sqrt{2} \text{ MeV}}{\beta c p} \sqrt{\frac{X}{X_0}} \left[1 + 0.038 \ln \left(\frac{X}{X_0} \right) \right] \quad (8)$$

167 Lynch and Dahl [25] suggested a form where the $\ln(X/X_0)$ term is replaced by $\ln(ZX/X_0)$:

$$\theta_{RMS}^L = \frac{13.6\sqrt{2} \text{ MeV}}{\beta c p} \sqrt{\frac{X}{X_0}} \left[1 + 0.038 \ln \left(\frac{ZX}{X_0} \right) \right] \quad (9)$$

168 In the above expressions, p is the particle's momentum in MeV/c, c is the speed of light, β is
 169 the ratio of particle's speed to the speed of light, X is the thickness of the traversed medium.
 170 X_0 is the radiation length, a characteristic quantity that describes the passage of muons
 171 through matter. In the present work, radiation length was calculated using [26]:

$$\frac{1}{X_0} = 4\alpha r_e^2 \frac{N_A}{A} \{Z^2 [L_{rad} - f(Z)] + Z L'_{rad}\} \quad (10)$$

where Z , A , r_e , N_A are the atomic number, atomic mass, Bohr radius and Avogadro number, respectively and:

$$L_{rad} = \ln(184.15Z^{-1/3}) \quad (11)$$

$$L'_{rad} = \ln(1194Z^{-2/3}) \quad (12)$$

The function $f(Z)$ is an infinite sum but for elements up to Uranium can be accurately represented by:

$$f(Z) = \alpha^2 [(1 + \alpha^2)^{-1} + 0.20206 - 0.0369\alpha^2 + 0.0083\alpha^4 - 0.002\alpha^6] \quad (13)$$

For compounds, i.e., UO_2 :

$$\frac{1}{X_0} = \sum_i \frac{w_i}{X_i} \quad (14)$$

where w_i and X_i are the weight fraction and radiation length of the i -th element. For multiple layers of materials the combined radiation length was calculated using:

$$\frac{d_0 \rho_0}{X_0} = \sum_j \frac{d_j \rho_j}{X_j} \quad (15)$$

where d_j , ρ_j and X_j are the thickness, density, and radiation length of the j -th layer. Radiation length follows a decreasing trend with increasing material atomic number, and therefore it is expected that the higher the atomic number the larger the scattering angle. This indicates that a partially loaded container would result in a smaller than normal scattering angle than a fully loaded. Radiation length for materials typical to dry casks is shown in Fig. 2.

Fig. 2. Radiation length variation for different materials

3. Dry cask modeling

Commercial dry casks can be classified into two main categories, i) metal canisters shielded in vertical concrete or metal overpack and, ii) metal canisters shielded in concrete modules [27]. Fig. 3 shows basic components of commercial vertical and horizontal dry casks. Gamma shielding is provided by the cask body itself, also known as overpack. The fuel assemblies are stored in the fuel canister consisting internally of welded borated stainless steel plates in an array of square channels. Typically, dry casks provide space for 24-32 PWR or 56-86 BWR assemblies [27]. The radiation lengths for six common dry cask designs have been calculated using equations (10) to (15). The first three belong to the class of casks having a concrete overpack, i.e., VSC-24, HI-STORM, NUHOMS, and the rest are casks with metallic body, i.e., CASTOR, TN, HI-STAR. The dry casks are considered to consist of the cask body and the spent nuclear fuel assemblies. Canister structure and inner basket have been neglected due to their small thickness. The results are shown in Fig. 4. Two reference casks, one that corresponds to casks with concrete overpack and a second one corresponding to casks with metallic body, have been constructed in such a way that would provide similar

radiation length number to the real ones. It appears that dry casks have an overall ratio X/X_0 ranging from 10 when empty up to 180 when fully loaded.

The RMS scattering angle for $0.1 < X/X_0 < 160$ is compared against results obtained from Monte Carlo calculations using GEANT4 to simulate 10^5 muons having energy 3 GeV. A comparison between the expressions given by Moliere, Rossi-Greisen, Highland and Lynch-Dahl is shown in Fig. 5. It appears that for large X/X_0 , the Rossi-Greisen and the Highland expressions are less accurate and have considerable error, 25% and 15%, respectively. Moliere and Lynch-Dahl expressions provide a better representation of the RMS scattering for large atomic numbers and large thicknesses. It is therefore recommended to use the Lynch-Dahl expression when performing calculations for high-Z, thick targets.

Fig. 3. Typical commercial vertical and horizontal dry cask storage configurations [13]

Fig. 4. Ratio X/X_0 for various commercial fully loaded and empty dry casks

Fig. 5. Comparison of scattering angles (RMS)

Measurement of muon scattering angles requires placement of position sensitive muon detectors on two opposite sides of the object to be inspected. Cosmic ray muons pass through the top detector plane and their initial trajectories are recorded. The muons then pass through concrete and UO₂, exiting through another layer of concrete before hitting and interacting with the bottom plane of detectors where their final trajectories are also recorded. The detector measurements are then processed to determine the scattering variance, estimated by:

$$\sigma_{\theta}^2 = \sum_{i=1}^3 (\sigma_{\theta}^2)_i = \frac{1}{2N} \sum_{i=1}^3 \sum_{k=1}^N (\theta_{x_k}^2 + \theta_{y_k}^2)_i \quad (16)$$

where θ_x and θ_y are the projected scattering angles for the i -th layer of material and N is the number of measurements corresponding to each angle. The GEANT4 Monte Carlo simulator [28] was used for tracking muons and their paths through dry casks. Fig. 6 depicts dry cask simulations for 4 GeV muons incident upon a dry cask. One case considers a typical commercial dry cask fully loaded with 24 PWR fuel assemblies while the other one is empty. The dry cask has concrete (density 2.3 g/cm³) walls, 3.658 m high and with inner and outer radius of 0.8635 m and 1.35 m, respectively. The fuel assemblies are rectangular in shape, 214.5x214.5 mm, and comprise of 15x15 UO₂ fuel rods, 3.658 m high and 10.7 mm in diameter. A muon beam is initiated at 45° zenith angle and scattering patterns are visualized. The fully loaded cask has a wider distribution of deflection angles than its counterpart making it feasible to separate these two cases, albeit extreme for visualization purposes, with minimal processing.

The aforementioned simulation was based on monoenergetic - monodirectional muons initiated from a point source at 45° zenith angle. To take into account the energy spectrum and the angular distribution of actual muons, 10⁶ muons having energies 1-60 GeV were simulated using a “Muon Generator” that generates muons following the actual sea level

distribution [29]. The “Muon Generator” was coupled with GEANT4. Typical commercial dry casks [27] with various PWR fuel loadings, i.e., fully loaded, half loaded, one row of fuel assemblies missing, one fuel assembly missing and empty, were simulated using GEANT4 to obtain accurate estimates of the scattering variance. Simulations were performed for three detector sizes having areas $1.2 \times 1.2 \text{ m}^2$ (small) $2.4 \times 2.4 \text{ m}^2$ (medium) and $3.6 \times 3.6 \text{ m}^2$ (large). The detectors are idealized gas chambers 1 cm thick filled with Argon gas at standard temperature and pressure and can record muon position. Muon momentum measurement typically requires expensive magnetic spectrometers and existing muon detectors for security applications do not have this capability. In this analysis, muon momentum was not used. Only the muon component of cosmic rays was simulated and other secondary particles were neglected to speed-up simulations. The muon source covers the detector area and is initiated at distance 20 cm from the first detector plane. Only muons that pass through all detector planes were recorded. For each case, the scattering variance was estimated. This estimate is a function of random variables and therefore is a random variable itself. To calculate the behavior of the scattering variance estimator, the Gamma distribution needs to be introduced:

$$Gamma(\alpha, \beta) = \frac{\beta^\alpha y^{\alpha-1}}{\Gamma(\alpha)} e^{-\beta y}, \alpha, \beta > 0, y \geq 0 \quad (17)$$

The expected value and variance of the Gamma distribution with parameters α, β is given by:

$$E[Y] = \frac{\alpha}{\beta} \quad (18)$$

$$Var[Y] = \frac{\alpha}{\beta^2} \quad (19)$$

Using moment generating functions, the square of a normal random variable follows Gamma distribution with parameters:

$$Y^2 \sim Gamma\left(\frac{1}{2}, \frac{1}{2\sigma^2}\right) \quad (20)$$

The estimator of the scattering variance is a function of the sum of squared random variables:

$$Z = \sum_{i=1}^N Y_i^2 \quad (21)$$

266 The distribution of the random variable Z can be derived using the moment generating
 267 function and can be shown to be distributed according to Gamma distribution with
 268 parameters:

$$Z = \sum_{i=1}^N Y_i^2 \sim \text{Gamma}\left(\frac{N}{2}, \frac{1}{2\sigma^2}\right) \quad (22)$$

269 The expected value and variance of random variable Z are:

$$\mathbb{E}[Z] = N\sigma^2 \quad (23)$$

$$\text{Var}[Z] = 2N\sigma^4 \quad (24)$$

270 The scattering variance estimator is therefore unbiased:

$$\mathbb{E}\left[\frac{1}{N}Z\right] = \mathbb{E}\left[\frac{1}{N}\sum_{i=1}^N Y_i^2\right] = \frac{1}{N}\mathbb{E}\left[\sum_{i=1}^N Y_i^2\right] = \frac{N}{N}\mathbb{E}[Y_i^2] = \sigma^2 \quad (25)$$

271

272 Using Chebyshev's inequality, 10^6 muons will provide scattering variance estimates that are
 273 within 1% of the true value at a 99% confidence level. The results of the scattering variance
 274 estimates for each case are shown in Table I. The estimated scattering variances are
 275 illustrated in Fig. 7 for small ($1.2 \times 1.2 \text{ m}^2$) detectors placed around vertical and horizontal dry
 276 casks. The trend is similar for medium and larger sized detectors. Scattering variance
 277 decreases with decreasing amounts of fuel loading, in agreement with theory. The difference
 278 between a fully loaded dry cask and one with a fuel assembly missing is very small and high
 279 statistics will be required to differentiate between these two cases. In Table II, the relative
 280 difference between a fully loaded dry cask and dry casks with smaller amounts of fuel is
 281 shown. The relative difference when one fuel assembly is missing is in the order of 1% to 5%
 282 depending on detector size and dry cask orientation.

Table I. GEANT4 estimated scattering variances for various fuel loadings and muon detector sizes (10^6 muons)

	Vertical (mrad ²)			Horizontal (mrad ²)		
	Small	Medium	Large	Small	Medium	Large
Fully loaded	4373.164	5048.470	4119.453	2680.254	3853.753	3343.153
FA missing	4315.194	4981.015	4059.512	2545.822	3754.225	3292.644
Row missing	3438.542	4205.093	3475.069	1964.067	3401.041	3101.739
Half loaded	2652.753	3288.292	2792.103	1357.913	3003.923	2878.459
Empty	965.565	1542.145	1493.074	1.044	2101.649	2370.501

Table II. Scattering variance relative difference from fully loaded cask (10^6 muons)

	Vertical			Horizontal		
	Small (%)	Medium (%)	Large (%)	Small (%)	Medium (%)	Large (%)
FA missing	1.32	1.33	1.45	5.01	2.58	1.51
Row missing	21.37	16.7	15.64	26.72	11.74	7.22
Half loaded	39.34	34.86	32.22	49.33	22.05	13.89
Empty	77.9	69.45	63.75	99.9	45.46	29.09

Fig. 6. GEANT4 simulations. Fully loaded (left) and empty (right) dry cask. Detectors are located around the cask (light grey) and yellow points signify interactions with dry cask.

Fig. 7. GEANT4 estimated scattering variance for vertical and horizontal dry casks with different spent nuclear fuel loading.

The amount of muons passing through the detector planes depends on the size, orientation and detector solid angle. The angular distribution can be approximated by [10]:

$$\frac{dN}{d\Omega} = \frac{3}{\pi} \cos^2 \theta \left(\frac{\text{muons}}{\text{min sr cm}^2} \right) \quad (26)$$

312 where θ is the zenith angle. The detector solid angle is:

$$\Omega = \frac{\vec{A} \cdot \vec{n}}{d^2} = \frac{hw \sin \varphi}{d^2} \text{ (sr)} \quad (27)$$

313 where h and w represent the dimensions (width, height) of the detector planes and, d is the
 314 distance from the dry cask centerline to the first detector plane (Fig. 9). The number of muons
 315 passing through a detector is:

$$N = \frac{dN}{d\Omega} \Omega (\vec{A} \cdot \vec{n}) = \frac{dN}{d\Omega} \Omega hw \sin \varphi \left(\frac{\text{muons}}{\text{min}} \right) \quad (28)$$

316 The number of muons passing through a detector as a function of the detector size and zenith
 317 angle is shown in Table III. For example, horizontal detectors located at zenith angle 89° ,
 318 vertically oriented with $\varphi=90^\circ$ and with dimensions $h=w=3.6$ m and $d=1.5$ m would require
 319 approximately 0.3 (~8 hours) and 3 days to gather 10^5 and 10^6 muon measurements,
 320 respectively. A detector located at smaller zenith angles would require less time to gather the
 321 same amount of measurements. Detectors located at zenith angle 45° , vertically oriented with
 322 $\varphi=45^\circ$ and with dimensions $h=w=1.2$ m and $d=1.5$ m would require approximately 45
 323 minutes to gather 10^5 muon measurements. This result does not take into account other
 324 factors that would increase measurement time, for example background radiation field and
 325 detector noise.

326

327

Fig. 8. Detector geometry, zenith angle and detector plane vectors.

Table III. Muons per minute measured for different detector geometries and zenith angles.

Height h (m)	Width w (m)	Distance d (m)	zenith angle θ ($^{\circ}$)	detector angle ϕ ($^{\circ}$)	muons/min
1.2	1.2	1.5	0	90	8800.63
			45	45	2200.15
			89	90	2.68
2.4	2.4	1.5	0	90	140810.10
			45	45	35202.52
			89	90	42.88
3.6	3.6	1.5	0	90	712851.17
			45	45	178212.79
			89	90	217.12

In-house Monte Carlo simulations of muon-dry cask interactions were performed to investigate the asymptotic behavior and the effect of the number of muons (10^4 , 10^5 and 10^6) to differentiate between a fully loaded dry cask and one with a fuel assembly missing. The scattering variance estimates from GEANT4 were used as reference values to compute the

scattering distributions resulting from muons having energies in the range of 1-60 GeV. The simulation was repeated 5,000 times and the obtained scattering variance distributions are shown in Fig. 9. The distributions initially overlap significantly for 10,000 muons but their distance increases with increasing number of muons. For 10,000 muons, the scattering distributions overlap and it is not possible to discriminate between the two cases. When distributions overlap unavoidably misclassifications would occur, i.e., a fully loaded cask may be classified as having fuel assemblies missing (false alarm) or inversely a cask with missing fuel assemblies may be classified as fully loaded (miss). One missing fuel assembly can however be distinguished from a fully loaded cask with a small overlapping between the distributions when more than 100,000 muons are measured. This indicates that the removal of a standard fuel assembly can be identified using muons providing that enough muons are collected. The increasing separation of the distributions reveals that the scattering variance can be used as a feature for discrimination between casks and the development of a classifier for that purpose is possible.

Fig. 9. Scattering variance distributions as a function of the number of muons measured (top: 10^4 muons, middle: 10^5 muons, bottom: 10^6 muons)

4. Bayesian monitoring algorithm

A real-time Bayesian monitoring system was developed to classify dry casks using a decision rule that minimizes the risk of making an incorrect decision. The classifier block diagram is shown in Fig. 10. Input measurements are muon scattering angles. Processing of scattering angles would result in the extraction of an appropriate feature that captures the behavior of the system, in the present case the scattering variance. Training data, either simulated or experimental, are needed to train the classifier and determine the decision boundary. Parameter estimation of the underlying distributions can be achieved using any density estimation statistical method, e.g., maximum likelihood estimation. Testing data are used to complete the design, analyze the performance of the classifier and evaluate false alarm rate, detection rate and effect of prior knowledge. The outcome of the classifier is a decision that will allow classification of a dry cask. The selected decision rule minimizes the risk associated with a decision:

$$R(\delta) = \underset{\delta}{\operatorname{argmin}} \mathbb{E}_{Y\Theta}[C(\delta(Y), \Theta)] \quad (29)$$

where $\mathbf{Y}$ is the accumulated dataset with muon measurements, $C(\delta(\mathbf{Y}), \Theta)$ is the cost of selecting category $\delta(\mathbf{Y})$ when the true decision is Θ . A sealed container either fully or partially loaded represents two distinct categories. Let the two categories represented as H_0 and H_1 . Samples from a fully loaded cask, i.e., category H_0 , follow distribution $f_0(y)$ with zero mean, variance σ_0^2 and prior probability π_0 , $H_0: \mathbf{Y} \sim f_0(y)$. Samples from a partially loaded cask, i.e., category H_1 , follow distribution $f_1(y)$ with zero mean, variance σ_1^2 and prior probability π_1 , $H_1: \mathbf{Y} \sim f_1(y)$. The cost for selecting category H_i when the true category is H_j would be C_{ij} . In this case, the decision rule that minimizes the overall risk is:

$$C_{00}\pi_0(y) + C_{01}\pi_1(y) \lesseqgtr_{H_1}^{H_0} C_{10}\pi_0(y) + C_{11}\pi_1(y) \Rightarrow \quad (30)$$

$$\frac{f_1(y)}{f_0(y)} \lesseqgtr_{H_1}^{H_0} \frac{(C_{10} - C_{00})\pi_0}{(C_{01} - C_{11})\pi_1} \quad (31)$$

385 Setting the ratio of the likelihood functions to $L(y)$ and the right hand side of the inequality to
 386 τ the decision rule can be written in compact form:

$$\mathcal{L}(y) \leq_{H_1}^{H_0} \tau \quad (32)$$

387 This decision rule suggests that in order to minimize the risk, category H_0 must be selected
 388 when the likelihood ratio is smaller than the boundary value τ or category H_1 when the
 389 likelihood ratio is larger than the boundary value τ . Suppose N muon measurements from a
 390 dry cask:

$$\mathbf{Y} = [y_1, y_2, \dots, y_N]^T \quad (33)$$

391 These measurements are independent and identically distributed and the likelihood function
 392 is:

$$f_j(y) = \prod_{i=1}^N f_j(y_i) = \frac{1}{(2\pi\sigma_j^2)^{N/2}} e^{-\frac{1}{2\sigma_j^2} \sum_{i=1}^N y_i^2} \quad (34)$$

393 Using the likelihood ratio test, the following decision rule can be derived:

$$\sum_{i=1}^N y_i^2 \leq_{H_1}^{H_0} \frac{2\sigma_1^2\sigma_0^2 N \ln \frac{\sigma_1}{\sigma_0}}{(\sigma_1^2 - \sigma_0^2)} + \frac{2\sigma_1^2\sigma_0^2 \ln \tau}{(\sigma_1^2 - \sigma_0^2)} \quad (35)$$

394 This rule depends on the number of measurements N , the variances σ_0^2 , σ_1^2 and value τ .
 395 Value τ includes the cost associated with each decision and the priors. Dividing by the
 396 number of measurements N , a decision rule that provides an estimate of the scattering
 397 variance is derived:

$$\frac{1}{N} \sum_{i=1}^N y_i^2 \leq_{H_1}^{H_0} \frac{2\sigma_1^2\sigma_0^2 \ln \frac{\sigma_1}{\sigma_0}}{(\sigma_1^2 - \sigma_0^2)} + \frac{2\sigma_1^2\sigma_0^2 \ln \tau}{N(\sigma_1^2 - \sigma_0^2)} \Rightarrow \quad (36)$$

398 A classifier using the above derived rule is an optimal classifier having a separation boundary
 399 that can be written as the sum of two terms, where the first term depends solely on the
 400 characteristics of the scattering distribution whereas the second term depends on the number
 401 of measurements, the priors and the associated cost for each classification decision.

Asymptotically, as the number of input measurements N approaches infinity the decision rule will depend only on the first term.

Fig. 10. Classifier block diagram

5. Performance evaluation

The performance of the classifier is characterized by the probability of error

$$\mathbb{P}_{error} = \pi_0 \mathbb{P}(H_1|H_0) + \pi_1 \mathbb{P}(H_0|H_1) = \pi_0 \mathbb{P}_F + \pi_1 \mathbb{P}_M \quad (37)$$

where $\mathbb{P}_F = \mathbb{P}(H_1|H_0)$ is the probability of selecting H_1 when the correct is H_0 and $\mathbb{P}_M = \mathbb{P}(H_0|H_1)$ is the probability of selecting H_0 when the correct is H_1 . The performance of the algorithm depends on the prior probabilities, π_0 and π_1 , as well as the probabilities of false alarm $\mathbb{P}_F$ and miss $\mathbb{P}_M$. To evaluate the algorithm performance, the GEANT4 scattering variance estimates

were used as reference values for the parameters of the scattering density distributions, i.e., σ_0 and σ_1 . σ_0 corresponds to a fully loaded dry cask. Muons were repeatedly drawn from this distribution and compared to. 1,000 simulations were used as testing data to calculate the number of misclassifications. The above procedure was repeated 100 times and the resulting probability of error, for two different sets of priors and 10,000 muons is shown in Fig. 11. The results demonstrate that the probability of error decreasing with increasing relative difference. The effect of the priors diminishes as the relative difference increases beyond 10%. A relative difference from a fully loaded dry cask in the order of 10% or more is needed to reduce probability of error to zero when 10,000 muons measured. 10,000, 50,000 and 100,000 muons were simulated and the probability of error was calculated as a function of the relative difference for $\pi_0=0.9$ and $\pi_1=0.1$. The average probability of error is shown in Fig. 12. The relative difference corresponding to zero probability of error decreases with increasing muon measurements. For 100,000 muons the relative difference for zero error probability is 3%. This corresponds to a dry cask with loading which is very close to one fuel assembly missing.

Fig. 11. Probability of error using muons for two different set of priors. Probability of error tends to zero with increasing amount of removed material.

Fig. 12. Average Probability of error using different number of muons and prior probability $\pi_0 = 0.9$.

6. Conclusions

The reliable and safe management of spent nuclear fuel is among the critical tasks to be addressed for the advancement of fission-based nuclear energy. There is a steady increase in the volume of spent nuclear fuel stored on-site (at reactor) as currently there is no permanent disposal option. No alternative disposal path is currently available and storage of spent nuclear fuel in dry cask storage containers is anticipated for the near future. The motivation to develop a capability to monitor stored materials within dry casks stems from the need to investigate whether the stored content agrees with facility declarations to allow proliferation detection and international treaty verification. Cosmic ray muon imaging is a potential next generation technology in non-destructive evaluation and muons can play a central role in monitoring nuclear waste and spent nuclear fuel stored in dense well shielded containers.

The main purpose of this paper is to investigate the applicability of muons for monitoring spent nuclear fuel dry casks. Treatments on the muon RMS scattering angle by Moliere, Rossi-Greisen, Highland and, Lynch-Dahl were analyzed and compared with simplified Monte Carlo simulations. The Lynch-Dahl expression has the lowest error and appears to be appropriate when performing conceptual calculations for high-Z, thick targets such as dry casks. The GEANT4 Monte Carlo code was used to simulate dry casks with various fuel loadings and scattering variance estimates for each case were obtained. The scattering variance estimation was shown to be unbiased and using Chebyshev's inequality, it was found that 10^6 muons will provide estimates of the scattering variances that are within 1% of the true value at a 99% confidence level. These estimates were used as reference values to calculate scattering distributions and evaluate the asymptotic behavior for small variations on fuel loading. It is shown that the scattering distributions between a fully loaded dry cask and one with a fuel assembly missing initially overlap significantly but their distance

eventually increases with increasing number of muons. One missing fuel assembly can be distinguished from a fully loaded cask with a small overlapping between the distributions which is the case of 100,000 muons. This indicates that the removal of a standard fuel assembly can be identified using muons providing that enough muons are collected. The separation of the distributions reveals that the scattering variance can be used as a feature for discrimination between casks and the development of a classifier for that purpose is possible.

A decision rule to classify dry cask which minimizes the risk of making an incorrect decision was derived using Bayesian principles. A classifier using the derived decision rule can be written as the sum of two terms, where the first term depends solely on the characteristics of the scattering distribution whereas the second term depends on the number of measurements, the priors and the associated cost for each classification decision. It was shown that the scattering variance can provide an appropriate feature to determine a decision boundary and allow differentiation of amount equivalent to a spent nuclear fuel assembly. The performance of the proposed monitoring algorithm was evaluated and the lower detection limit for a zero probability error was determined.

Acknowledgments

This research was supported using funding received from the DOE Office of Nuclear Energy's Nuclear Energy University Programs under Contract DE-NE0000695.

References

- [1] O.C. Allkofer. Introduction to cosmic radiation, K. Thiemig, 1975.
- [2] K. N. Borozdin et al., Radiographic imaging with cosmic ray muons, *Nature*, Vol. 422, p. 277, 2003.
- [3] P.M. Jeneson, Large vessel imaging using cosmic ray muons, *Nuclear Instruments and Methods in Physics Research A*, Vol. 525, pp. 346-351, 2004.
- [4] Blue Ribbon Commission on American's Nuclear Future, Report to the Secretary of Energy, 2012.
- [5] C. Jewett et al., Simulation of the use of cosmic rays to image nuclear waste and verify the contents of spent fuel containers, *Proceedings of the Waste Management Conference*, Phoenix, AZ, 2011.
- [6] E. P. George, *Commonwealth Engineer*, 455 (1955).
- [7] L. W. Alvarez, J.A. Anderson, F. Elbedwe, J. Burkhard, A. Fakhry, A. Girgis, A. Goneid, F. Hassan, D. Iverson, G. Lynch, Z. Miligy, A.H. Moussa, Mohammed-Sharkawi, and L. Yazolino, *Science* 167, (1970) 832.
- [8] Nagamine, K., Geo-tomographic Observation of Inner-structure of Volcano with Cosmic-ray Muons, *Journal of Geography* 104(7), pp 998-1007 (1995).
- [9] C.J. Rhodes, Muon tomography: looking inside dangerous places, *Science Progress*, 98(3), 2910299, 2015.
- [10] Borozdin, K., et al., Cosmic Ray Radiography of the Damaged Cores of the Fukushima Reactors. *Physical Review Letters*, 2012. 109(15).
- [11] L. J. Schultz, Cosmic ray muon radiography, Thesis dissertation, Portland State University, 2003.
- [12] S. Riggi et al., Muon tomography imaging algorithms for nuclear threat detection inside large volume containers with the Muon Portal detector, arXiv:1307.0714v1, 2013.

513 [13] L. J. Schultz et al., Statistical reconstruction for cosmic ray muon tomography, IEEE
514 Transactions on Image Processing, Vol. 16, No. 8, pp. 1985-1993, 2007.

515 [14] Green, J.A., et al., Optimizing the Tracking Efficiency for Cosmic Ray Muon
516 Tomography. 2006 IEEE Nuclear Science Symposium Conference Record, Vol 1-6, 2006: p.
517 285-288.

518 [15] Hogan, G.E., et al., Detection of High-Z Objects using Multiple Scattering of Cosmic
519 Ray Muons. AIP Conference Proceedings, 2004. 698(1): p. 755-758.

520 [16] Charpak, G., et al., Applications of 3-D Nuclear Scattering Radiography in Technology
521 and Medicine, Proceedings of the Society of Photo-optical Instrumentation Engineers 312, pp
522 156-163 (1983).

523 [17] Schultz, L.J., et al., Image reconstruction and material Z discrimination via cosmic ray
524 muon radiography. Nuclear Instruments & Methods in Physics Research, Section A
525 (Accelerators, Spectrometers, Detectors and Associated Equipment), 2004. 519(3): p. 687.

526 [18] R.C. Hoch, Advances in cosmic ray muon tomography reconstruction algorithms,
527 Master's thesis, Florida Institute of Technology, 2009

528 [19] M.S.E. Abdel-Monem. Cosmic ray muon spectrum and charge ration, Thesis
529 Dissertation, University of Houston, 1974.

530 [20] Bethe, H. A., Phys. Rev. 89, (1953) 1256.

531 [21] Moliere, G., J. Phys. Sci. 3, (1948) 78.

532 [22] B. Rossi and K. Greisen, Rev. Mod. Phys. 13 (7941) 240;

533 [23] V. L. HIGHLAND, "Some practical remarks on multiple scattering," Nucl. Inst. Meth.,
534 129, 497-199 (1975).

535 [24] K.A. Olive et al. (Particle Data Group), Chin. Phys. C, 38, 090001 (2014).

536 [25] G. R. LYNCH & O. I. DAHL, "Approximations to multiple Coulomb scattering,"
537 Nuclear Instruments and Methods in Physics Research B, 58, 6-10 (1991).

538 [26] Y.S. Tsai, Rev. Mod. Phys. 46, (1974) 815.

539 [27] Industry Spent Fuel Handbook, Electric Power Research Institute, Technical Report
540 1021048, 2010.

541 [28] S. AGOSTINELLI et al., “GEANT4 – A simulation toolkit,” Nuclear Instruments and
542 Methods in Physics Research A, 506, 250–303 (2003).

543 [29] S. CHATZIDAKIS et al., “Developing a cosmic ray muon sampling capability for muon
544 tomography and monitoring applications,” Nuclear Instruments and Methods in Physics
545 Research A, 804, 33-42, (2015).

546

547