Title: Progress in Understanding Sheeting Joints over the Past Two Centuries

Author: Stephen J. Martel, University of Hawaii, Department of Geology and Geophysics

Corresponding author: Stephen J. Martel*, smartel@hawaii.edu, 1-808-856-7797

Affiliation Address: Department of Geology and Geophysics, University of Hawaii, 1680 East-West Road, Honolulu, HI, 96822

Key words (maximum of 6)

Sheeting joints

Fracture mechanics

Topography

Driving stress

Water pressure

Abstract

Sheeting joints share many geometric, textural, and kinematic features with other joints, but differ in that they are (a) discernibly curved, and (b) open near to and subparallel to the topographic surface. Where sheeting joints are geologically young, the surface-parallel compressive stresses are large, typically several MPa or greater. Sheeting joints are best developed beneath domes, ridges, and saddles. They also are reported, albeit rarely, beneath valleys or bowls. A mechanism that accounts for these associations has been sought for more than a century: the commonly subscribed explanation of erosion of overburden, by itself, is inadequate. Principles of fracture mechanics, together with the mechanical effects of a curved topographic surface experiencing a surface-parallel compression, provide a framework that accounts for the cardinal characteristics of sheeting joints. A compressive stress parallel to a convex topographic surface induces a tension perpendicular to the surface at shallow depths. In some cases, this combination alone can overcome the weight of overburden to open sheeting joints. Plausible distributions of water pressure in sheeting joints would help open and drive them beneath valleys, saddles, and bowls. Thermal stresses help sheeting joints develop very near the ground surface. Sheeting joints thus appear to reflect an intricate fracture process primarily involving the shape, slope, and scale of the topography; the regional horizontal stresses; the effect of gravity; and groundwater pressure. Understanding how sheeting joints evolve in three dimensions through time remains an outstanding challenge and would illuminate their effect on landscapes, slope stability, and fluid flow.

1. Introduction

Sheeting joints are discernibly curved fractures that open near the surface of the Earth at shallow depths, form essentially parallel to the topographic surface, and divide large (mountainous) rock masses into thin layers (Whitney, 1865, 1869; Harris, 1888; Gilbert, 1904; Holman, 1976; Faust, 1978). They are visually striking where best developed (Fig. 1) and occur in many places (Branner, 1896; Cadman, 1970, and references therein; Twidale, 1982; Holzhausen, 1989; Hencher and others, 2011). Sheeting joints develop in many kinds of strong rocks, such as granite, gneiss, massive sandstone, mafic intrusive rocks, marble, and basalt (Matthes, 1930; Bain, 1931; Balk, 1937; Jahns, 1943; Holzhausen, 1977, and references therein; Faust, 1978). Owing to their striking form, widespread development, and utility in quarries, sheeting joints have attracted attention for more than two centuries (e.g., Pötzsch, 1803; Dale, 1923).

Interest in sheeting joints continues for many interrelated reasons. Sheeting joints provide an opportunity to understand how rock fractures grow to larger sizes than can be reproduced in laboratory samples (e.g., Griggs, 1936; Brace and Bombolakis, 1963; Cadman, 1970; Peng, 1970; Holzhausen, 1977, 1989). They reflect how topography influences stresses in the Earth (e.g., Jeffreys, 1924; Savage et al., 1985; Savage and Swolfs, 1986; Miller and Dunne, 1996; Molnar, 2004) and occur where stresses cause rock bursts in nearby mines and quarries (e.g., Niles, 1871; Dale, 1923; White, 1946; Twidale and Bourne, 2003). They are renowned for their role in landscape development (Gilbert, 1904; Matthes, 1930; Bradley, 1963), and have the potential to reveal how topography evolves through time (Jahns, 1943; Ziegler et al., 2013). Sheeting joints strongly influence shallow groundwater systems (Fig. 2; also see Dale and Smith, 1907; LeGrand, 1949; Wyrick and Borchers, 1981; Cressler et al., 1983; Trainer, 1988; Cohen,

1993; Borchers, 1996). They play important roles in the breakdown of rock, the development of soils, and erosion (Branner, 1896; Hencher et al., 2011), as well as in mass wasting (e.g., Terzaghi, 1962; Da Costa Nunes et al., 1979; Hermanns and Strecker, 1999; Wieczorek and Snyder, 1999; Chigara, 2000; Hencher et al., 2011). Sheeting joints, owing to their varied potential mechanical and hydrologic impacts, can be important to account for in investigations of potential nuclear waste disposal sites (e.g., Talbot, 1999; Ivars and Hakami, 2005; Fox et al., 2007; Johansson, 2008; Liljedahl et al., 2011; Geier et al., 2012; Joutsen, 2012). They are mechanically related to the growth of hydraulic fractures parallel to the topographic surface (Holzhausen, 1977). Finally, in light of their contribution to spectacular landscapes in places such as Yosemite National Park, California (Glazner and Stock, 2010), Ayers Rock, Australia (Vidal Romani and Twidale, 1999), and Sugarloaf, Brazil (Branner, 1896; Jones, 1973), sheeting joints have captured the attention of many in the general public. In spite of more than two centuries of study, however, a solid comprehensive explanation of how sheeting joints form has been elusive.

Historically, sheeting joints have been referred to by many names. For example, some of the earliest references use stratigraphic terms such as pseudo-stratification (Hitchcock, 1841) and bedding joints (Harris, 1888) to describe sheeting joints in igneous rocks. Even Hutton (1899) described “apparent stratification” in granite at Goatfell in Arran, Scotland, that he subsequently recognized as “cracking” (Fig. 1b). Terms with stratigraphic implications will not be used here because granitic rocks, which commonly develop sheeting joints, are not sedimentary rocks, and because sheeting joints in many sandstones cut across bedding (e.g., Bradley, 1963; Bahat et al., 1995). Another term, flat-lying joint (Balk, 1937), is inappropriate because (1) sheeting joints are characteristically curved, and (2) the term was originally developed to describe fractures

associated with the emplacement of plutons at depth rather than to describe near-surface processes, including those in sedimentary rocks (Fig. 1j). Sheeting joints also have been called sheet structure (Dale, 1923; Jahns, 1943; Holzhausen, 1989), dome structure (Gilbert, 1904), cross-joints (Geikie, 1905), sheet joints (Dale and Smith, 1907), exfoliation (Matthes, 1930), exfoliation planes (Balk, 1937); sheeting (Billings, 1942), exfoliation joints (Harland, 1957), unloading joints (e.g., Ramsay and Huber, 1987), and sheet fractures (Vidal Romaní and Twidale, 1999). The term exfoliation is not used here because it has been used to refer to boulders (e.g., Blackwelder, 1925), and the focus here is solely on the scale of large outcrops and mountain masses. The term sheeting joint is used here for three main reasons: (1) historical continuity; (2) sheeting joints bound sheet-like rock layers, so the term is descriptive; and (3) sheeting joints exhibit the key kinematic qualities of joints (as will be shown).

Our understanding of sheeting joints benefits from studies at scales ranging from that of grains (e.g., Dale, 1923) to the hand sample (e.g., Peng, 1970) to the field (e.g., Holzhausen, 1977; Mitchell, 2010; Ziegler et al., 2014a). Experimental studies with hand-sample sized specimens are particularly valuable for providing insight into the nucleation of fractures. The focus here though is on sheeting joints at the scale of meters to hundreds of meters under natural conditions. Jaeger et al. (2007) emphasized the importance of accounting for features of the proper scale in the introduction of their treatise on rock mechanics: “The mechanical structure of rock presents several different appearances, depending upon the scale and the detail with which it is studied.... On a scale with dimensions ranging from a few meters to hundreds of meters, the structure of some rocks is continuous, but more often it is interrupted by cracks, joints, and bedding plane.... Where these disturbances have significant dimensions, they must be treated as part of the structure or as a boundary.” Paterson and Wong (2005) echo those comments in their

monograph on experimental brittle rock deformation. At the scale of focus here, the surface of the Earth and sheeting joints themselves constitute prominent boundaries that must be taken into consideration. These features motivate a mechanical analysis that explicitly accounts for the dimensions of sheeting joints, using linear elastic fracture mechanics (LEFM), and effects of a curved traction-free surface that bounds a rocks mass.

This article focuses on progress made in understanding the mechanism(s) by which macroscopic sheeting joints develop. It combines both a review of the characteristics of sheeting joints and an analytical section on sheeting joint mechanics, as Pollard and Aydin (1988) did in their appraisal of progress in understanding jointing in general. The treatment first reviews the essential geometric and kinematic characteristics of sheeting joints that a viable mechanical explanation must account for. It draws findings from key publications in the last two centuries and compares them with findings about joints in general. The main hypotheses proposed to explain sheeting joints are then summarized and scrutinized to see whether they indeed account for the essential characteristics of sheeting joints. This material sets the stage for a description of elementary principles of linear elastic fracture mechanics (LEFM) as the basis for a theoretical framework for understanding sheeting joints, which is novel in terms of its context. The manuscript closes by identifying areas for future research that seem especially promising.

2. Characteristics of sheeting joints

2.1 Geometry of individual sheeting joints

Sheeting joints characteristically parallel or nearly parallel the topographic surface in a variety of topographic settings. Exposures of barren bedrock reveal that sheeting joints are most common beneath ridge crests and, especially, domes (Fig. 1a-e; see also Gilbert, 1904; Holman,

1976) but also occur at saddle-shaped surfaces (Fig. 1f), both on ridge crests and at the lips of waterfalls or cascades (Gilbert, 1904). Sheeting joints in barren bedrock are least common beneath valleys or bowls but have been reported there too (Matthes, 1930; Jahns, 1943; Holman, 1976; Vidal Romani and Twidale, 1999; Ziegler et al., 2014). The dip of sheeting joints ranges from horizontal near the summits of domes and in many quarries (Dale, 1923; Jahns, 1943; Holzhausen, 1989) to vertical on cliffs (Fig. 1j; see also Matthes, 1930; Bradley, 1963; Bahat et al., 1995) to overhanging where slopes overhang (Bradley, 1963).

Sheeting joints span a range in dimensions of more than two orders of magnitude. Ziegler et al. (2014) observed sheeting joints from more than 25 locations in the Swiss Alps and concluded that 95% of them had plumose axes with lengths between 2m and 20 m. The largest individual sheeting joints can have dimensions parallel to their surfaces of more than 100 m and perhaps as large as a few hundred meters (Matthes, 1930; Holzhausen, 1977; Bahat et al., 1995). In contrast, Pollard and Aydin (1988) commented that the long dimension of joints in general rarely exceeds 100m. Sheeting joints thus can exceed the typical dimensions of many other joints. In addition, Jahns (1943) depicted the sheeting joints that he studied in New England as increasing in length with increasing depth below the surface (Fig. 3).

Although the curvature of sheeting joints is one of their distinguishing traits, surprisingly few estimates or measurements of their curvature appear in the literature. Two principal curvatures can be used to quantify the local shape at a point on any smooth surface (Gauss, 2005). The principal curvatures are the maximum and minimum curvatures defined by the intersections of the surface with all planes normal to the surface at the point in question, where the directions of the principal curvatures are 90° apart. Holman (1976) reported essentially cylindrical concave sheeting joints at the bottom of a valley in Yosemite National Park, California with a maximum

principal curvature of $0.03\text{--}0.05\text{ m}^{-1}$, and the minimum principal curvature near zero. Collins and Stock (2016) determined a convex (negative) curvature of -0.0086 m^{-1} for a sheeting joint in Yosemite Valley. Mitchell (2010) calculated the two principal curvatures of the topographic surface at a small bell-shaped dome in the park (Fig. 1e) from three-dimensional laser scanning data. The sheeting joints effectively coincide with the topographic surface on most of the dome, so the curvatures of the topographic surface closely approximate those of the sheeting joints. Around the doubly convex top of that dome both principal curvatures generally are negative and between -0.01 m^{-1} and -0.04 m^{-1} . Near the saddle-shaped base of the dome, the most convex (negative) curvature is between 0 m^{-1} and -0.01 m^{-1} , and the most concave (positive) curvature generally is between 0.01 m^{-1} and 0.04 m^{-1} . The most convex (negative) curvature decreases in absolute magnitude from the top of the dome towards its base. Likewise, both Matthes (1930) and Jahns (1943) observed that sheeting joints elsewhere tend to become flatter (less convex) with depth beneath domes.

In their simplest form, the perimeters of sheeting joints are crudely elliptical (Fig. 4) or fan-shaped with a fringe of helicoidal fractures (Holman, 1976; Holzhausen, 1977; Bahat et al., 1995; Zeigler, 2014a). Originally separate sheeting joints can link to form a compound structure with a more complicated perimetric shape (e.g., Bahat et al., 1995; Stock et al., 2012). Sheeting joints thus have perimetric shapes akin to other joints in massive rock (Pollard and Aydin, 1988).

Sheeting joints develop at shallow depths (Gilbert, 1904), usually less than 50 m (Brunner and Scheidegger, 1973). In a few quarries, however, they have been reported at greater depths, such as more than 97 m by Jahns (1943) and more than 100 m by Twidale (1971). These maximum depths typically are small relative to the radii of curvature of 1 km or more for the long-wavelength local topography at several quarries with sheeting joints (e.g., Martel, 2006).

2.2 Sheeting joint patterns

Sheeting joints rarely if ever occur individually. Instead, they characteristically occur in collections that typically exhibit systematic patterns of spacing and overlap.

The spacing between sheeting joints (i.e., the thickness of the intervening sheets of rock) generally increases with depth normal to the ground surface (Fig. 2; see also Holman, 1976). The spacing near the surface can be as small as several millimeters, and the largest spacing observed so far is ~60 m (Matthes, 1930). The data of Jahns (1943) and Holzhausen (1989) from the Fletcher quarry in Massachusetts indicate the gross spacing-to-depth ratio generally is between 0.1 and 0.4. The spacing between sheeting joints thus is generally small relative to their length, width, and radii of curvature. The small ratio of spacing to trace length reflects at least in part to the ability of a sheeting joint to twist into echelon segments that subsequently propagate and overlap (Holzhausen, 1989).

Sheeting joints commonly overlap considerably. For example, in the wall of a quarry along the Tioga Road in Yosemite National Park (Fig. 1g), sheeting joints are spaced ~1 m apart and have traces that overlap by ~50 m, yielding a spacing-to-overlap ratio of 0.02. Ratios such as this prompt rock with convex sheeting joints to be likened to the layers of an onion (Harris, 1888; Gilbert, 1904). Although the spacing between sheeting joints commonly is quite uniform (Fig. 1), some exhibit gentle hook-shaped overlapped ends, (Fig. 5; see also Holzhausen, 1989). Other kinds of joints with small ratios of spacing to overlap commonly are hook-shaped also (Pollard and Aydin, 1988).

2.3 Kinematic relationships

Resolving whether sheeting joints are dominantly opening mode fractures or shear fractures is critical to assessing how they form. Four different kinds of information bear on this issue of

kinematics: the sense of relative displacement, fracture aperture, surface texture, and the nature of fracturing near the perimeter of sheeting joints.

Many sheeting joints have hairline apertures (e.g., Holzhausen, 1989), but much larger apertures are common (Fig. 6). This aperture variation occurs because after or as many sheeting joints open the overlying rock slab arches upward (e.g., Niles, 1871; Matthes, 1930; Collins and Stock, 2016). Ericson and Olvmo (2004) documented one sheeting joint beneath an arched slab in Yosemite National Park with a maximum aperture of ~0.6 m, and several others with apertures greater than 0.1 m. Talbot (1999) observed sheeting joints 14 m below the ground surface with apertures as large as 0.5 m. Apertures that large are rarely observed along other kinds of joints, which tend to have maximum apertures of less than a centimeter (e.g., Segall and Pollard, 1983; Marrett et al., 1999). The large apertures of many sheeting joints are consistent with a dominantly opening mode origin.

Sheeting joints typically exhibit no discernible slip (e.g., Dale, 1923; Jahns, 1943). Slip can be observed across some sheeting joints (e.g., Holzhausen, 1989), but this slip does not mean that they characteristically originate as dominantly shear fractures: (a) small amounts of slip can occur behind the tip of an opening mode fracture (Pollard and Aydin, 1988); (b) detached rock slabs overlying sheeting joints can simply slide downslope after they open (e.g., Glazner and Stock, 2010), and (c) joints can be reactivated as faults (e.g., Segall and Pollard, 1983). These observations indicate that sheeting joints originally open and in some cases subsequently shear, rather than originating as shear fractures of one sense and then characteristically slipping in an opposite sense to yield no net slip.

Sheeting joints commonly display a plumose surface texture consisting of arrest lines (ribs) and hackles (Fig. 4; see also Holman, 1976; Holzhausen, 1989; Bahat et al., 1995; Zeigler et al.,

2014a). The characteristic presence of plumose structure, together with a characteristic lack of slickensides and slickenlines, is consistent with sheeting joints originating as dominantly opening-mode fractures as opposed to shear fractures (Pollard and Aydin, 1988).

The gentle hook-shaped overlapped ends exhibited by some sheeting joints (Fig. 5) are consistent with an opening mode origin (e.g., Pollard and Aydin, 1984). The ends of sheeting joint traces typically lack the oblique “tail cracks” commonly observed near the ends of sheared joints and faults (e.g., Segall and Pollard, 1983).

Sheeting joints share the same essential kinematic and textural characteristics of joints in general, rather than the essential kinematic characteristics of shear fractures. Therefore, sheeting joints originate as opening mode fractures.

2.4 Relative age

Sheeting joints generally show abundant evidence of relative geologic youth, although ascertaining their absolute age has been problematic. They typically cut all other geologic structures in a rock mass, such as foliations, geologic contacts, and other fractures (Balk, 1939; Jahns, 1943). Dale (1923) observed that sheeting joints in many granite quarries in New England also cross aligned grain-scale cracks known as the rift. Not all sheeting joints are the youngest structures, however, and not all sheeting joints essentially parallel the modern surface. Dale (1923) described double sheet structure (two distinct sets of sheeting joints), and Jahns (1943) identified multiple sites where the topography has been substantially modified since the older sheeting joints formed.

In some outcrops, systematic fractures occur that apparently are younger than some sheeting joints. These younger fractures are perpendicular to and terminate against sheeting joints, with

the overall pattern resembling the joints in a masonry wall (Fig. 1i). These perpendicular fractures link sheeting joints mechanically and help weakening the host rock mass.

Direct field evidence as to the relative ages of sheeting joints in a stack is difficult to find because sheeting joints commonly do not intersect each other. Owing to the tendency for sheeting joints to “round off” sharp corners, however, Matthes (1930) inferred that as sheeting joints in a stack became less curved they also became younger. This tendency for sheeting joints to round off corners has been observed in quarries (e.g., White, 1946) and at road cuts (Fig. 1h). The age progression inferred by Matthes (1930) implies that sheeting joints beneath domes would tend to become younger with depth and possibly with distance downslope from the summits of domes.

2.5 Hydrologic characteristics

Sheeting joints can contribute substantially to groundwater flow, in part because of their typical great length, large aperture, and connections to other fractures that result in integrated hydraulic systems (Borchers, 1996). The apertures along sheeting joints can be tens or hundreds of times greater than along other joints, and since the fluid flow rate in fractures tends to vary as the cube of the fracture aperture (e.g., Witherspoon, et al., 1980), some sheeting joints can transmit water much more readily than typical joints. Connections to fractures of other orientations allow sheeting joints to access surface sources of water, even where sheeting joints might not directly intersect the surface.

2.6 Mechanical associations

High in situ compressive stresses parallel to the ground surface have long been associated with sheeting joints (e.g., Niles, 1871; Dale and Smith, 1907; Dale, 1923; White, 1946; Holzhausen, 1989). These stresses are manifest in different ways. One is the buckling of rock

slabs bounded by sheeting joints (Niles, 1871; Dale and Smith, 1907, 1923; Matthes, 1930; Ericson and Olvmo, 2004). The fractures formed during buckling failures typically are perpendicular to the underlying sheeting joint. A second manifestation is that rock slabs taken from quarries with sheeting joints commonly extend after being extracted (e.g., Dale, 1923). Cadman (1970) calculated the uniaxial compressive stresses needed to cause the buckling failures and the measured extensions. The stresses ranged from 1 MPa to 17 MPa and generally exceeded 10 MPa. In addition, the principal horizontal stresses in rock masses with sheeting joints have been evaluated at several places using overcoring measurements (e.g., Table 1). The published stress values typically are much less than half the typical unconfined compressive strengths of ~100 MPa for granites, marbles, and sandstones (e.g., Hatheway and Kiersch, 1989).

Sheeting joints characteristically develop at shallow depths in strong rocks subject to compressive stresses parallel to the topographic surface of several MPa or more (Table 1). In stark contrast, reports of sheeting joints in weak rocks such as shale are conspicuously absent, presumably because weak rocks fail in shear under large differential stresses (e.g., Nygård et al., 2006). Sheeting joints apparently develop only in rocks subject to, and able to withstand, large differential stresses, with large ambient compressive stresses parallel to the topographic surface and a weak ambient compressive stress (or tensile stress) perpendicular to the surface.

3. Prominent hypotheses in the literature

Several hypotheses have been proposed to account for the growth of macroscopic sheeting joints (Dale, 1923; Jahns, 1943). Perhaps the most prominent are: 1) erosion of overburden (Gilbert, 1904); (2) weathering; (3) thermal stresses arising from insolation (Shaler, 1869; Van Hise, 1904); (4) emplacement of plutons (e.g., Whitney, 1865); (5) residual stresses (Price, 1966); (6) buckling failures (Bahat et al., 1999); and (7) axial splitting (e.g., Leith et al.,

2014a,b). Any viable hypotheses must account for the geometric, kinematic, temporal, and mechanical associations described above and be consistent with general physical principles.

3.1 Erosion of overburden

Perhaps the most widely subscribed explanation for sheeting joints is that they form in response to erosion and the associated reduction in vertical compressive stress, as tentatively suggested by Gilbert (1904). This explanation, however, fails to account for some crucial observations. First, if sheeting joints were primarily a response to erosion of overburden, then they would be expected to develop better where more overburden has been moved. Sheeting joints then should be more common in valleys than on adjacent ridges. Instead, in areas with abundant sheeting joints, sheeting joints typically are best developed on ridge crests and generally are scarce or absent at valley bottoms (e.g., Fig. 1f). Second, rocks extracted from quarries and freed from tractions do not spontaneously develop sheeting joints. Third, not all deeply eroded rocks contain sheeting joints (Twidale, 1973). Fourth, uniform erosion on a regional scale would reduce the vertical compressive stress equally at all depths, rather than causing a reduction only near the surface. If a reduction in vertical compressive stress due to uniform erosion were an essential part of the mechanism for the formation of sheeting joints, then sheeting joints should develop at a broad range of depths, not just near the surface. Relief of overburden pressure cannot be the fundamental reason why sheeting joints form, although it could contribute to their development.

3.2 Weathering

If weathering caused sheeting joints, then all sheeting joints should be weathered. Both Dale (1923) and Jahns (1943) observed that mineral grains along sheeting joints in some quarries show no signs of weathering. So even though weathering clearly occurs along sheeting joints, the

evidence indicates the weathering occurs after they form, hence weathering cannot cause the sheeting joints.

3.3 Solar insolation

Thermal stresses arising from temperature changes at the ground surface can contribute to the opening and propagation of sheeting joints very close to the ground surface. For example, Warth (1895) described the use of wood fires to produce sheeting joints about 15 cm below the floors of quarries in India. Collins and Stock (2016) used 3.5 years of measurements to document that diurnal temperature changes correspond to aperture changes of a pre-existing sheeting joint 10 cm behind the north wall of Yosemite Valley. Temperature changes arising from solar insolation, however, do not appear capable of causing sheeting joints to form at depths of several tens of meters. Theoretical calculations of conductive temperature changes arising from periodic heating of the surface show that diurnal temperature changes of 10°C at the surface decay to negligible values at a depth of 2 m in bedrock, consistent with the measurements of Anderson (1998), and would increase surface-parallel stresses there by less than 0.07 MPa. Likewise, annual temperature changes of 10°C at the surface decay to negligible values at a depth of 25 m and would increase surface-parallel stresses there by less than 0.07 MPa (Cadman, 1970; see also Holzhausen, 1989). Those stress changes are miniscule relative to the in situ stresses parallel to the surface where sheeting joints develop, indicating that conductive temperature changes arising from solar insolation are incapable of contributing meaningfully to the formation of sheeting joints below a depth of a couple of meters.

3.4 Solidification of plutons

Solidification of plutons (Whitney, 1865) was rejected by Jahns (1943) as a possible cause of sheeting joints. He observed that sheeting joints in granitic rocks develop only near the surface of

granitic bodies, conform to the topography rather than the plutonic boundaries, are completely independent of foliation or mineralogic layering in the plutons, and transect not only the plutons but also the host country rock. In addition, the presence of sheeting joints in sedimentary rocks rule out solidification of plutons as a general cause for sheeting joints.

3.5 Residual stresses

Residual stresses are stresses that remain within an isothermal body that experiences no external tractions (McClintock and Argon, 1966). In order for a body to remain at equilibrium, any residual tensions must be balanced by residual compressions (Friedman, 1972).

Theoretically, residual stresses could exist at any scale, but in the massive rocks where sheeting joints develop best, the most plausible residual stresses would exist at the grain scale. The net effect is that residual tensile stresses and residual compressive stresses would tend to balance out over distances of several grains in massive rock. Residual stresses at the grain scale thus cannot be invoked to account for the systematic appearance of sheeting joints at scales of tens or hundreds of meters.

3.6 Buckling

Buckling occurs in beams and plates that are thin relative to their in-plane extent. This means a beam or plate of rock, and the sheeting joint(s) that bound it, must exist *before* buckling occurs. Hence, buckling cannot cause sheeting joints, although buckling might assist in the propagation of a pre-existing sheeting joint beneath a slab that buckles.

3.7 Axial splitting

Axial splitting develops in cylindrical hand-sample-sized laboratory samples subjected to large axial compressive stresses and weak (or non existent) radial compressive stresses, with the

resulting fractures approximately paralleling the axis of the sample (Wong, 1982; Horii and Nemat-Nasser, 1985; Diederichs et al., 2004). Axial splitting depends greatly on the details of the loading conditions at the ends of the sample, the shape of the sample, and grain-scale stress concentrations (Peng, 1970; Wong, 1982). Axial splitting could be important in the nucleation of sheeting joints at the scale of several centimeters, but for a few reasons seems unlikely to be able to be scaled up to account for sheeting joints tens or hundreds of meters long. First, stable axial splitting cracks produced during laboratory uniaxial compression tests rarely grow to lengths more than a few times greater than the lengths of the initial flaws (e.g., Horii and Nemat-Nasser, 1985). Second, localized grain-scale stress concentrations appear unlikely to account for sheeting joints tens or hundreds of meters long because clustered alignments of grain-scale tensile stress concentrations over distances of tens or hundreds of meters are unlikely (also see the paragraph above that discusses residual stresses at the grain-scale and section 4.4 below). Third, the formation of the axial cracks in samples of granite and gneiss typically requires the applied most compressive stresses to be at least 50 to 55 MPa, more than one-third to one-half the unconfined compressive strength of the rock (Diederichs et al., 2004; Leith et al., 2014a,b), whereas the greatest compressive stresses at sites with sheeting joints typically are much less (Table 1), generally 10-20% of the unconfined compressive strength of samples of the host rock. Fourth, axial splitting experiments do not produce a regular series of essentially parallel smooth curved cracks with spacings that are small relative to their length; the axial splitting cracks appear distinctly different from sheeting joints. Fifth, the processes that precede axial splitting in rock samples, such as kinking of biotites, crushing of fine particles, and mineral-specific cracking (Wong, 1982) do not have obvious equivalents at the scale of sheeting processes. In spite of these scaling differences, both phenomena require a large difference between the maximum and

minimum principal stresses. For example, Leith et al. (2014a,b) found that axial splitting in samples of granite and gneiss requires the most compressive stress to be at least eleven times greater than the least compressive stress. Although the processes for axial splitting and sheeting joints differ in some key ways, the stresses under which the processes occur are similar in some key ways.

3.8 Conclusions

The mechanisms discussed above do not account fully for sheeting joints and hence are rejected as complete explanations. Some of them contribute to sheeting joints, but none of them account for critical scales involved with sheeting joints: the length and depth scales of the sheeting joints, the scales of the in-situ stresses, and the scales of the topography. These scales are accounted for in the ensuing treatment involving principles of fracture mechanics.

4. Mechanics of sheeting joints

4.1 Overview

Pollard and Aydin (1988) concluded that principles of linear elasticity theory (e.g., Malvern, 1969; Timoshenko and Goodier, 1970) and linear elastic fracture mechanics (LEFM) (Lawn and Wilshaw, 1975) provide a physically appropriate and useful conceptual framework for investigating joints in general. Numerous studies have demonstrated conclusively that linear elasticity theory and LEFM can explain many aspects of joints and other opening mode fractures, such as: (1) the patterns they make at scales ranging from outcrops to regions of many square kilometers (e.g., Pollard and Aydin, 1984; Delaney et al., 1986; Olson and Pollard, 1989; Bergbauer and Martel, 1999); (2) the conditions necessary for them to propagate or to terminate (e.g., Helgeson and Aydin, 1991; Renshaw and Pollard, 1995; Cooke and Underwood, 2001;

Cosgrove and Engelder, 2004); (3) their mechanical interaction (e.g., Pollard and Aydin, 1988); and (4) their spacing and aperture (e.g., Pollard and Segall, 1987; Renshaw and Park, 1997; Gross et al., 1995; Bai and Pollard, 2000a, 2000b; Bai et al., 2000). In spite of the proven value of the LEFM framework for understanding the macroscopic behavior of joints generally, this framework has not been widely adopted in the study of sheeting joints.

According to principles of LEFM, the initiation, propagation, and termination of an opening-mode fracture, such as a sheeting joint, depend on the geometry of the fracture, the geometry of the host body, and the stresses within the body, not the strains (e.g., Lawn and Wilshaw, 1975; Pollard and Segall, 1987). The distinction between stress (which has dimensions of force per unit area) and strain (a dimensionless term that describe changes in size and/or shape, e.g., Malvern, 1969) unfortunately has long been blurred in the study of sheeting joints. For example, the concept that a sheeting joint is an “unloading fracture” (see section 3.1) relies upon the notion that as rocks are exhumed, the compressive stress acting on the exhumed rock surface is relieved and the rock can expand, or strain, normal to the surface. This expansion does not correspond to a tension normal to the surface, however, and according to principles of LEFM does not require fractures to develop parallel to the surface. Furthermore, some of the seminal contributions to the literature on sheeting joints (e.g., Gilbert, 1904; Dale, 1923; and Jahns, 1943) associate sheeting joints with “compressive strain”, yet “compression” refers to a stress, not a strain. In the stress-based fracture mechanics analyses used here, tensile stresses are considered as positive, and compressive stresses (e.g., pressures) as negative. This approach is consistent with conventional fracture mechanics usage (e.g., Lawn and Wilshaw, 1975; Pollard and Segall, 1987).

The ensuing mechanical analyses reflect how the stresses associated with topography, horizontal tectonic loads, gravity, and fluid pressure influence the initiation, propagation, and

termination of sheeting joints. The mechanical treatments are primarily two-dimensional and confined to vertical planes for the sake of clarity and simplicity. In these two-dimensional treatments, no variation in the geometry, material properties or boundary conditions are permitted perpendicular to the planes of interest, and displacements perpendicular to those planes will be zero. One brief but important treatment compares two-dimensional and three-dimensional effects.

4.2 Stresses associated with sheeting joints

4.2.1 Driving stress

The driving stress σ_D is a critical factor in determining whether a joint can open. The driving stress (Fig. 7) is the difference between (a) the ambient most tensile stress (σ_1) before the joint opens and the normal stress σ_c acting on the wall of the joint if it were to open (Pollard and Segall, 1987):

$$\sigma_D = \sigma_1 - \sigma_c . \quad (1)$$

The average driving stress must be positive along a joint for it to open (Pollard and Muller, 1976). Both an ambient tension and an internal pressure within a joint can contribute to a positive driving stress. For a dry open joint, σ_c equals zero, but for a fluid-filled joint σ_c equals the fluid pressure and has a negative sign. Sheeting joints have been generated artificially by pumping pressurized air down boreholes in quarries (Watson, 1910). In nature, water can act as a pressurized fluid. One of the outstanding and vexing mechanical problems regarding sheeting joints is the source of a positive driving stress, especially since the driving stress must account for the weight of the overburden.

The magnitude of the driving stress can be gauged against the differential stress σ_{Diff} ,

$$\sigma_{Diff} = \sigma_1 - \sigma_3, \quad (2)$$

where σ_3 is the most compressive ambient stress (presumably parallel to the joint). Since large compressive stresses (typically several MPa or more) are measured parallel to young sheeting joints, σ_3 characteristically is negative and of large absolute value. For a dry sheeting joint open at shallow depths, σ_1 , σ_c and σ_D would be expected to be small relative to σ_{Diff} . Sheeting joints thus can be expected to typically have low average driving stresses. A quantity related to the driving stress is $\Delta\sigma$, the perturbation of the stress perpendicular to the joint, as evaluated along the joint itself. This stress perturbation is the negative of the driving stress (Fig. 7):

$$\Delta\sigma = -\sigma_D. \quad (3)$$

As a consequence of the low driving stress, the opening of a sheeting joint perturbs the stress field in the adjacent rock only a small amount. This has important consequences for how sheeting joints propagate and interact.

4.2.2 Driving stress gradient at the topographic surface

The gradient in the driving stress at the topographic surface illuminates where sheeting joints might and might not initially open in the shallow subsurface. The driving stress is zero at the topographic surface, so if the driving stress gradient (i.e., the rate of change with depth) is positive at the surface, then the driving stress must become positive at shallow depths (see Fig. 2 of Martel, 2011). The driving stress gradient at a curved, dry, traction-free topographic surface

$|\vec{\nabla}\sigma_D^{dry}|$ has two contributions from curvature-stress products and a contribution from gravity:

$$|\vec{\nabla}\sigma_D^{dry}| = k_1\sigma_{11} + k_2\sigma_{22} - \rho_r g \cos\beta, \quad (4a)$$

where k_1 and k_2 are the most positive and least positive principal curvatures, respectively, at a point on the surface (see Fig. 8, inset); σ_{11} and σ_{22} are the stresses parallel to the surface in the

directions of k_1 and k_2 , respectively (see Fig. 8, inset); ρ_r is the density of the rock; g is gravitational acceleration; and β is the slope of the surface (Martel, 2011). If the contributions from the curvature-stress products are sufficiently positive and overcome the negative contribution from gravity, then a positive net gradient exists, guaranteeing a positive driving stress in the shallow subsurface. The curvature-stress products will be positive if the curvatures are negative (convex) and the stresses are negative (compressive). This condition provides insight into why sheeting joints are favored at domes and ridges subject to a large surface-parallel compression. Conversely, if the curvature terms are positive (concave) and the stress terms are negative (compressive) then the curvature-stress products will be negative, and the driving stress gradient will be negative. This condition similarly provides insight into why sheeting joints are scarce at valleys (singly concave surfaces) and bowls (doubly concave surfaces). At topographic saddles, where k_1 is positive but k_2 is negative, and the surface-parallel stresses are compressive, the driving stress gradient could be either positive or negative, and sheeting joints might or might not open.

By setting the left side of Equation 4a to zero, one can obtain threshold curves for the curvatures and surface-parallel stresses needed for a positive driving stress gradient (i.e., conditions permitting sheeting joints to open). Figure 8 shows threshold curves for the crests of a ridge ($\beta = 0$, $k_1 = 0$, $k_2 = k$) and an axisymmetric dome ($\beta = 0$, $k_1 = k_2 = k$) assuming the surface-parallel stresses are isotropic ($\sigma_{11} = \sigma_{22} = \sigma$) and the rock density is $2.7 \times 10^3 \text{ kg/m}^3$. The threshold curve for the dome is lower than for the ridge because a dome has two positive curvature-stress products in equation (4a), whereas a ridge has only one since $k_1 = 0$. This relationship accounts for why sheeting joints would tend to develop more readily on domes than on ridges. A two-dimensional model would need to use surface-parallel stresses about twice

those in an axisymmetric three-dimensional model to yield similar driving stresses near the topographic surface.

Where the shallow subsurface is saturated, or water fills a conduit from the surface that sheeting joints might extend from, then the expression for the driving stress gradient can be modified to account for the positive contribution of the water pressure. Assuming the water is static, the modified expression is

$$\left| \vec{\nabla} \sigma_D^{sat} \right| = \left| \vec{\nabla} \sigma_D^{dry} \right| + \rho_w g \cos \beta, \quad (4b)$$

where ρ_w is the density of the water. The water pressure contribution to the driving pressure gradient is positive and substantially lowers the threshold curves in Fig. 8, expanding the range of conditions under which sheeting joints could open. The threshold curves would be even lower for inclined slopes ($\beta > 0^\circ$).

4.2.3 The ambient stress field

The ambient stress field in the subsurface can be modeled to help explain patterns of sheeting joints. The ambient stress field is modeled by solving a boundary value problem in elasticity theory that accounts for the shape and traction-free nature of the topographic surface, the effect of gravity, and a regional horizontal stress T . Figures 9 and 10 illustrate stress fields in vertical cross sections for two-dimensional, homogenous, isotropic, isothermal rock masses with cosinusoidal topographic surfaces. The solutions are obtained by the boundary element method (Crouch and Starfield, 1983; Martel, 2000; Slim et al., 2014) where the topographic surface is simulated by a traction-free cosinusoidal crack that extends five wavelengths to either side of the ridge crest. The amplitude A is 3% of the wavelength L . In both figures, the uniform horizontal tectonic stress T is large relative to the vertical stress scale $\rho g A$ associated with gravity. In

Figure 9, $T = -63\rho gA$, but in Figure 10, $T = -84\rho gA$ (i.e., the regional horizontal compressive stress is 33% larger in Figure 10 than in Figure 9).

Figures 9a and 10a show the most tensile stress (σ_1) scaled by $-T$. The heavy contour separates regions where σ_1 is positive and sheeting joints could open from where σ_1 is negative. The contour interval is non-uniform, being ten times finer where σ_1 is positive than where σ_1 is negative. This is done to show more detail where σ_1 is positive. Figures 9a and 10a show tensile maxima of $\sim 0.005|T|$ and $\sim 0.01|T|$, respectively. The tensile maximum is larger and a bit deeper for the larger regional horizontal compression.

The results in Figures 9 and 10 can be scaled to topography of a particular amplitude, provided the A/L ratio stays fixed. For example, if $A = 18$ m, $L = 600$ m, and $\rho = 2.7 \times 10^3$ kg/m³, then $T = -30$ MPa in Figure 9 and $T = -40$ MPa in Figure 10. The scaled tensile stress maxima are at depths below the summits of ~ 28 m and ~ 43 m, respectively. The tensile stress σ_1 reaches a maximum of ~ 0.15 MPa for Figure 9a, but is about three times larger (~ 0.4 MPa) in Figure 10a. As will be shown, a tension of 0.15 MPa might be too small to propagate sheeting joints from grain scale flaws, but a tension of 0.4 MPa might be quite adequate. Magnitudes of regional horizontal compression of 30-40 MPa are roughly twice as large as typical measurements at domes with sheeting joints, but this doubling seems appropriate to use in a two-dimensional model to simulate a dome. Greater values of $-T$ would make sheeting joints even more likely to form.

4.2.4 The effect of water pressure

Water pressure from rainfall or snowmelt contributes to slope failures in fractured rock slopes (e.g., Wieczorek and Jäger, 1996), helps open and drive crevasses down from the surface of glaciers (Weertman, 1971; Smith, 1976; Das et al., 2008), and also would help open and drive

sheeting joints. The pressure from freezing water (ice) would also help open and drive sheeting joints. Many sheeting joints transmit water, and the typical chemistry of groundwater from sheeting joints indicate they must be hydraulically connected to sources of surface water that would lie upslope (e.g., Borchers, 1996). Fractures clearly can transmit water to depth in granite, but they also can in unsaturated porous rocks (Tokunaga and Wan, 1997, 2001). Sheeting joints conceivably could tap water from as high as the crest of a neighboring ridge crest. Under this scenario, artesian pressures could arise in sheeting joints. Although rarely reported, artesian conditions have been documented in sheeting joint systems (LeGrand (1949). Figures 9b and 10b show the scaled driving stress $\sigma_D^{sat}/(-T)$ assuming still water fills a fracture network that extends down from the ridge crest to points in the subsurface. This arrangement generates the maximum possible water pressure and represents one end of a spectrum of possible water pressures. A comparison of Figures 9a and 9b with Figures 10b and 10b, respectively, shows that water pressure would substantially expand and deepen the regions where positive driving stresses could occur in the subsurface to including regions beneath valleys. Using the same scaling as in the previous paragraph, the scaled driving stress maxima are at depths below the summits of ~44 m in Figure 9b and ~66 m in Figure 10b. Thus, the region of positive driving stress would extend to a depth of more than 170 m for Figure 10b. The tensile stress reaches a maximum of ~0.6 MPa for $T = 30$ MPa in Figure 9b, and ~1 MPa for $T = 40$ MPa in Figure 10b. Both levels are likely to be able to nucleate sheeting joints from grain-scale flaws based on the fracture mechanics criteria described in Section 4.3.2. The presence of water thus could play a key role in the formation of sheeting joints by allowing them to open in places where a compressive stress parallel to the topographic surface, by itself, cannot.

4.2.5 *Stress trajectories*

Trajectories perpendicular to the least compressive stress (Figures 9c and 10c) serve as proxies for the orientations of sheeting joints that might form. The contours of zero tensile stress and zero driving stress are superposed to show where sheeting joints might open. For the cases illustrated in Figures 9c and 10c, the assumed levels of regional horizontal compressive stress are entirely adequate to yield sheeting joint orientations like those depicted by Jahns (1943) in Figure 3.

4.3 *Initiation of sheeting joints*

4.3.1 *The initiation process*

Sheeting joints presumably initiate by processes involving grain-scale stress concentrations. For example, axial splitting processes might lead to fractures with in-plane dimensions of several centimeters that could then grow longer by other mechanisms. Alternatively, sheeting joints might nucleate directly from grain-scale flaws (e.g., grain boundaries or grain scale cracks) that experience a sufficiently large driving stress. This process can be addressed within the context of LEFM using stress intensity factors.

4.3.2 *Stress intensity factors*

Stress intensity factors describe the intensity of stresses and the relative displacements of the walls of a fracture near its tipline. They also can be used to assess whether a fracture would nucleate or propagate if the stress intensity factor exceeds a threshold value (Lawn and Wilshaw, 1975). Near a fracture tipline, the relative displacements of the walls (Fig. 11) can be perpendicular to the fracture (mode I), parallel to the fracture and perpendicular to the tipline (mode II), and parallel to the fracture and parallel to the tipline (mode III). Each mode has an associated stress intensity factor. For an isolated two-dimensional planar opening-mode crack of

length $2a$ in an infinite body subject to a uniform driving stress along its length, the stress intensity factors depend on the driving stress (Tada et al., 2000):

$$K_I = \sigma_D \sqrt{\pi a} \quad (5a)$$

$$K_{II} = 0 \quad (5b)$$

$$K_{III} = 0 \quad (5c)$$

Non-zero values of K_{II} or K_{III} can cause a joint to curve or twist into echelon segments as it grows (Pollard and Aydin, 1988). For a joint to propagate in a brittle elastic rock, sufficient energy must exist to fracture the rock and advance the tipline. This condition is met if

$$G_c = \left[(K_I^2 + K_{II}^2)(1 - \nu) + K_{III}^2 \right] / 2\mu, \quad (6)$$

where G_c is a positive threshold value, ν is Poisson's ratio, and μ is the shear modulus of the rock (Pollard and Aydin, 1988). For a crack to propagate, the stress intensity factor(s) must exceed a threshold value. If the driving stress remains constant and positive for a planar crack, then according to Equation 5a, once the crack exceeds a threshold length, it will continue to grow because its length $2a$ increases and hence K_I continues to increase.

An estimate of the driving stress required for propagation can be based on a threshold value for K_I . Laboratory measurements of the critical stress intensity factor K_{Ic} required for runaway fracture growth in granitic rocks generally are between $0.6 \text{ MPa}\cdot\text{m}^{1/2}$ and $2.5 \text{ MPa}\cdot\text{m}^{1/2}$ (Atkinson and Meredith, 1987a). The minimum stress intensity factor required for subcritical (stable) propagation is not known but in some cases is less than 5% of K_{Ic} (Atkinson and Meredith, 1987b) or less than $0.03 \text{ MPa}\cdot\text{m}^{1/2}$. Estimates of the required subcritical stress intensity factor based on geological measurements in the field are as low as $0.04 \text{ MPa}\cdot\text{m}^{1/2}$ (Segall and Pollard, 1983). For a granitic rock with a grain size of 1 cm, a reasonable value of the

initial flaw half –length is 5 mm. Using a subcritical threshold stress intensity factor of $0.03 \text{ MPa}\cdot\text{m}^{1/2}$, a fracture would propagate with a driving stress of 0.2 MPa (2 atmospheres), which is small relative to the differential stress at which sheeting joints occur. For starter flaws larger than a grain, the required driving stress for propagation would be smaller and would allow for sheeting joints to propagate in all the scaled examples previously discussed.

4.4 Propagation of sheeting joints

4.4.1 Stable and unstable propagation

Sheeting joints apparently can propagate in both stable and unstable fashion. Ziegler et al. (2014a) deduced that sheeting joints typically propagate incrementally and subcritically based on the surface textures of the joints. This behavior is consistent with driving stresses being small relative to in situ differential stresses. Dynamic sheeting joint propagation has been documented in quarries (e.g., Holzhausen, 1989). Acoustic signals associated with sheeting joint propagation in natural slopes (e.g., Stock et al., 2012) could arise from either subcritical or critical fracture propagation.

4.4.2 Effect of the sign of the driving stress

Several experimental studies have shown that cracks propagating from the tips of a sheared flaw in a specimen subject to a uniaxial compression grow in the direction of maximum compressive stress and then tend to stop after growing a distance of a few initial flaw lengths (e.g., Brace and Bombolakis, 1963; Hoek and Bieniawski, 1965; Nemat-Naser and Horii, 1982; Horii and Nemat-Naser, 1985). These results indicate that uniaxial compression is not sufficient to account for sheeting joints with dimensions of tens of meters or more, much greater than the dimensions of the grains or crystals in rocks.

Analytical solutions for the stress intensity factor for cracks that grow parallel to a

compressive stress show how sensitive crack growth is to the sign of the driving stress. For example, Figure 12 shows K_I for collinear cracks of length a that radiate from a circular hole of radius R in an infinite plate with a strong remote compressive (negative) stress σ_3 parallel to the cracks, and with a weak remote stress σ_1 perpendicular to the cracks ($\sigma_3 = \sigma_1$). For uniaxial compression ($\sigma_3 < 0$, $\sigma_1 = 0$), if a hole is absent ($a/(a + R) = 1$, or $R = 0$), then $K_I = 0$ no matter how compressive σ_3 is. If a hole does exist, however, then a localized circumferential tension develops around it in response to the remote uniaxial compression. This induced tension helps drive a fracture away from the hole in the direction of the remote compression, as reflected by the rising positive stress intensity factor as a increases. However, the induced circumferential stress eventually becomes weakly compressive away from the hole, and as a result the stress intensity factor drops toward zero, even as the cracks lengthen. The presence of even a very mild compression perpendicular to the cracks ($\sigma_1 < 0$) eventually causes the stress intensity factor to become negative as a increases, indicating that the cracks will stop propagating. Conversely, a weak tensile (positive) stress perpendicular to the crack will maintain a positive value of K_I and promote crack growth; the same effect can be achieved if fluid pressure in the cracks yields a positive driving stress. These results are consistent with the experimental and theoretical findings of Horii and Nemat-Nasser (1985) and reinforce the importance of a positive driving stress to account for the observed dimensions of sheeting joints.

4.4.3 Joint propagation path

Three key consequences emerge from a consideration of sheeting joints with a small driving stress where the ambient differential stress is large. First, the opening of such a joint perturbs the stress field in the adjacent rock only a small amount. Consequently, the path that a sheeting joint would propagate along can be predicted well based on the stress field *before* the joint opens, with

the joint propagating essentially perpendicular to the local most tensile stress as evaluated before the sheeting joint opens. The stress trajectories in Figures 9 and 10 are nearly parallel to the topographic surface at shallow depths but become nearly horizontal and flatter at greater depth. This change accounts for the observed changes in curvature of sheeting joints with depth. Second, a large compressive stress parallel to a sheeting joint will tend to inhibit the ability of a sheeting joint to deviate away from the stress trajectories (Cotterell and Rice, 1980). Third, joints with a small driving stress tend to interact little, have nearly parallel traces, and exhibit small ratios of spacing to overlap (e.g., Olson and Pollard, 1989).

4.4.4 Mechanical interaction

The mechanical interactions of sheeting joints with the topographic surface and with other sheeting joints affect the patterns that sheeting joints make. The interaction with the topographic surface is more important owing to its greater extent and because the relatively small driving stresses of sheeting joints retards their interaction. As a result, the overall patterns of sheeting joints are determined by interactions with the topography, whereas the interaction among sheeting joints would affect details of those patterns.

The interaction between a sheeting joint and the topographic surface will tend to be negligible until the sheeting joint length becomes about equal to its depth (Fig. 13). The upper wall of the sheeting joint then will be displaced upward markedly more than the lower wall is displaced downward, and a tangential relative displacement will occur across the tip of the sheeting joint (Pollard and Holzhausen, 1979; Stock et al., 2012; Zhang et al., 2002). This condition increases both the mode I and mode II stress intensity factors and promotes further propagation of the sheeting joint. The increase in the mode II stress intensity factors also will tend to cause a sheeting joint to grow towards the surface (see Holzhausen (1989) and Stock et

al. (2012) for examples of this), although that tendency is substantially retarded by the large compressive stress parallel to the surface (Cotterell and Rice, 1980).

The shapes of natural topographic surfaces will also affect interactions with sheeting joints. Natural topographic surfaces reflect a broad spectrum of wavelengths of different amplitudes, with the amplitude typically decaying as the wavelength decreases (e.g., Sayles and Thomas, 1978; Perron et al., 2008). The ambient stress field depends on this spectrum. For a given wavelength, the maximum length of a sheeting joint would be about half a wavelength, the distance between the inflection points bounding the convex segments of a wavelength. The depth to which the topographic stress perturbations extend also depends on the wavelength and is probably no more than half a wavelength below the mean elevation, at least for topographic amplitudes that are small relative to the topographic wavelength (i.e., $A/L < 0.04$) (Martel, 2016). As a result, longer sheeting joints would likely develop at depth (Fig. 14), and shorter ones will be concentrated near the surface (Fig. 15). Furthermore, the stress perturbation caused by the opening of a joint tends to cause the spacing between joints to scale with joint length (Pollard and Aydin, 1988). The increase in joint length with depth thus would tend to yield a wider joint spacing with depth. The typical topographic spectrum thus favors an increase in sheeting joint spacing with depth. In addition, convexities of small amplitude and small wavelength can occur in valleys, and this geometry can account for some sheeting joints in valleys.

Joints interact mechanically with one another because when a joint opens it perturbs the stress field in the surrounding rock (Pollard and Aydin, 1988). As closely-spaced, non-coplanar joints grow towards one another, their tips tend to first diverge, but then as the tips overlap they tend to propagate towards the neighboring joint and then terminate: this propagation behavior produces a hook-shaped pattern between slightly overlapped joints. For the case of sheeting

joints, however, the stress perturbations will be mild because the driving stresses are small, allowing sheeting joints to develop large overlaps relative to their spacing, with very mild hook shapes (see Fig. 5). The large differential stress will also retard the tendency of sheeting joints to develop pronounced hooks (Fig. 16).

4.5 Joint arrest

A variety of processes could cause sheeting joints to terminate. Joints with a small driving stress would tend to propagate only a relatively short distance into a region where the ambient stress acting across the path of a joint is compressive. In the absence of fluid pressure, sheeting joints would tend to terminate near a transition from convex to concave topography. The processes governing the growth and arrest of sheeting joints could be particularly sensitive to hydraulic conditions (e.g., Zhang and Jeffrey, 2014). For example, a sheeting joint could be arrested and subsequently close where it encountered a feature that drained water from the sheeting joint. A sheeting joint could also terminate against a geologic structure with low shear strength (e.g., Helgeson and Aydin, 1991). Observations show, however, that many subhorizontal sheeting joints cross steep geologic structures, presumably because a high compressive stress parallel to a sheeting joint tends to lock the walls of the steep structure and lessen its ability to stop the sheeting joint. Mechanical interaction with other sheeting joints could also cause a sheeting joint to terminate (Pollard and Aydin, 1988), but this effect would be mitigated owing to the small driving stresses of sheeting joints. Variations in the in situ stress field arising from the shape of the topography, and changes in the hydraulics of a fractured rock mass, seem to be the most likely factors to lead to the arrest of sheeting joints.

5. Conclusions and Recommendations

Sheeting joints are dominantly opening mode fractures that occur near, and nearly parallel to, the topographic surface. They characteristically are curved and have small ratios of spacing to overlap. As the depth beneath the surface increases, the spacing, length, and radii of curvature appear to increase. Sheeting joints are more typically found beneath surfaces that are convex in at least one direction (domes, ridges, and saddles) than surfaces that are not. They form where the compressive stress perpendicular to the joints due to the weight of overburden is small (usually less than 1 MPa) and the ambient compressive stress parallel to them is large (usually several MPa or more). The principal radii of curvature of the topographic surface and the amplitude of the topography vary with the spectrum of the topographic wavelength and are key length scales affecting the mechanics of sheeting joint growth.

In spite of considerable effort, a complete explanation for sheeting joints that is physically viable and consistent with observations and data has been lacking. Fracture mechanics principles considered in the context of a curved, traction-free surface subject to a surface-parallel compression provide a physically viable way to account for all the salient characteristics of sheeting joints. In this fracture mechanics perspective, the shape of the topography, the magnitude of the surface-parallel compression, and water pressure play a critical role in the nucleation, propagation, and termination of sheeting joints. The recognition that groundwater can help drive sheeting joints relates them to two other kinds of fractures: (1) intrusions parallel to the surface (e.g., Pollard and Holzhausen, 1979); and (2) shallow horizontal hydraulic fractures (Zhang et al., 2002). Jahns (1943) noted that sheeting joints are absent in intensely fractured rock. Presumably this absence reflects the inability of intensely fractured rock to sustain large differential stresses near the ground surface. However, pre-existing fractures that conduct water

from the surface to depth could be important in the formation of deep sheeting joints. Pre-existing fractures thus could hinder or enhance the formation of sheeting joints.

Field and laboratory research dedicated to sheeting joints could test the mechanism proposed here. Measurements of the water pressure, topographic surface shape, and in situ stresses would be most illuminating where sheeting joints are growing and could be monitored using acoustic transducers. Hydraulic fracturing experiments could be conducted where sheeting joints were on the verge of growing. Reproducible measurements of the three in-situ principal stresses prior to such an experiment would be essential. Detailed mapping and/or geophysical surveys that defined the three-dimensional distribution and spacing of sheeting joints would help test the proposed mechanism. Perhaps the sheeting mechanism could be reproduced in the laboratory using a suitable fine-grained brittle model material.

Additional advances in several areas would pave the way for an improved understanding of sheeting joints. The near-surface ambient stress fields arising from different combinations of topographic wavelength, topographic amplitude, tectonic horizontal compression, and water pressure need to be understood more completely, starting with simple, idealized two-dimensional cases, and extending to three dimensional cases, using a variety of available modeling techniques (e.g., Liu and Yang, 2003; Ziegler, 2013; Ziegler et al., 2014b; St. Clair et al., 2015). A better understanding of possible sources of the large surface-parallel compressive stresses needed for sheeting joints would also illuminate other areas of structural geology, tectonics, and engineering. Thermo-mechanical processes associated with uplift and erosion provide one potential source (e.g., Nadan and Engelder, 2009), but other sources cannot be ruled out, such as crustal flexure associated with major faults (e.g., Vening Meinesz, 1950). Measurements of stresses and mapping of sheeting joints at sites where sheeting joints are young, the maximum

depth of sheeting joints can be determined, and the topography has not been strongly modified by quarrying would be extremely valuable in better constraining model parameters and testing model predictions. Grimsel, Switzerland is one such area (Ziegler, 2013; Ziegler et al., 2014b). Advances in our ability to predict the twisted and curved paths of fractures growing parallel to and near to a curved traction-free surface subject to a strong surface-parallel compression would be a major contribution. Improved techniques that permit accurate dating of sheeting joints also would be of immense value. Shared research in these areas could greatly improve our understanding of fractured rock masses in general, our ability to interpret what sheeting joints reveal about the stress state near the topographic surface and how landscapes evolve over time (e.g., Römer, 2007; Goodfellow et al., 2014)

Acknowledgments

Many people have contributed to this study. Dick Jahns notified me that sheeting joints merited additional scrutiny. David Pollard has helped in many ways, and his impact has been profound. Tim Horscroft and William Dunne patiently encouraged this manuscript. Robert Viesca provided the code used to produce Figure 13. Clint Conrad, Bernhard Grasemann, Garrett Ito, Penny Larin, Linda Martel, Louis Martel, Owen Martel, Larry Mastin, Kelly Mitchell, Peter Molnar, Seulgi Moon, Carolyn Parcheta, Richard Schulz, Greg Stock, Taylor Perron, and Paul Wessel helped provide technical, editorial, field and/or financial support for which I am most grateful. Tom Blensinkop, Brian Collins, Larry Mastin, and (especially) Michele Cooke provided constructive critical comments on the manuscript – thank you. Shortcomings of this manuscript, however, are solely my responsibility. Financial support from the National Science Foundation (grant EAR05-38334), the Yosemite Conservancy through the Hawaii-Pacific Islands Cooperative Ecosystems Studies Unit (agreement J8834110001), JPL (agreement 1290138), and

the Army Research Office (subaward 5710003647) is gratefully acknowledged. This is SOEST contribution no. xxxx.

References

- Anderson, Robert, S., 1998. Near-surface thermal profiles in alpine bedrock: implications for the frost weathering of rock. *Arct. Alp. Res.* 30, 362–372.
- Atkinson, B.K., Meredith, P.G., 1987a. Experimental fracture mechanics data for rocks and minerals, in: Atkinson, B.K. (Ed.), Atkinson, B.K. Meredith, P.G. Academic Press, London, pp. 477–525.
- Atkinson, B.K., Meredith, P.G., 1987b. The theory of subcritical crack growth with applications to minerals and rocks, in: Atkinson, B.K. (Ed.), *Fracture Mechanics of Rock*. Academic Press, London, pp. 111–166.
- Bahat, D., Grossenbacher, K., Karasaki, K., 1995. Investigation of exfoliation joints in Navajo Sandstone at the Zion National Park and in Graithe at the Yosemite National Park by tectonofractographic techniques. Berkeley.
- Bahat, D., Grossenbacher, K., Karasaki, K., 1999. Mechanism of exfoliation joint formation in granitic rocks, Yosemite National Park. *J. Struct. Geol.* 21, 85–96.
- Bai, T., Pollard, D.D., 2000a. Closely spaced fractures in layered rocks: Initiation mechanism and propagation kinematics. *J. Struct. Geol.* 22, 1409–1425. doi:10.1016/S0191-8141(00)00062-6
- Bai, T., Pollard, D.D., 2000b. Fracture spacing in layered rocks: A new explanation based on the stress transition. *J. Struct. Geol.* 22, 43–57. doi:10.1016/S0191-8141(99)00137-6
- Bai, T., Pollard, D., Gao, H., 2000. Explanation for fracture spacing in layered materials. *Nature* 403, 753–6. doi:10.1038/35001550

- Bain, G.W., 1931. Spontaneous rock expansion. *J. Geol.* 39, 715–735.
- Balk, R., 1939. Disintegration of glaciated cliffs. *J. Geomorphol.* 2, 306–312.
- Balk, R., 1937. Structural behavior of igneous rocks (with special reference to interpretations by H. Cloos and collaborators). Geological Society of America, New York.
- Bergbauer, S., Martel, S.J., 1999. Formation of joints in cooling plutons. *J. Struct. Geol.* 21, 821–835.
- Billings, M.P., 1942. Structural geology. Prentice-Hall, New York.
- Blackwelder, E., 1925. Exfoliation as a phase of rock weathering. *J. Geol.* 33, 793–806.
- Borchers, J.W., 1996. Ground-water resources and water-supply alternatives in the Wawona area of Yosemite National Park, California, Water-Resources Investigations Report 77.
- Bowie, O.L., 1956. Analysis of an infinite plate containing radial cracks originating at the boundary of an internal circular hole. *J. Math. Phys.* 35, 60–71. doi:DOI: 10.1002/sapm195635160
- Brace, W.F., Bombolakis, E.G., 1963. A Note on Brittle Crack Growth in Compression. *J. Geophys. Res.* 68, 3709–3713.
- Bradley, W.C., 1963. Large-Scale Exfoliation in Massive Sandstones of the Colorado Plateau. *Geol. Soc. Am. Bull.* 74, 519–528. doi:10.1130/0016-7606(1963)74
- Branner, J.C., 1896. Decomposition of rocks in Brazil. *Geol. Soc. Am. Bull.* 7, 255–314.
- Brunner, F.K., Scheidegger, A.E., 1973. Exfoliation. *Rock Mech.* 5, 43–62.
- Cadman, J., 1970. The origin of exfoliation joints in granitic rocks. University of California at Berkeley.
- Chigara, M., 2001. Micro-sheeting of granite and its relationship with landsliding after the heavy rainstorm in June, 1999, Hiroshima Prefecture, Japan. *Eng. Geol.* 59, 219–231.

- Cohen, A.J.B., 1993. Hydrogeologic characterization of a fractured granitic rock aquifer, Raymond, California. University of California at Berkeley.
- Collins, B.D., Stock, G.M., 2016. Rockfall triggering by cyclic thermal stressing of exfoliation fractures. *Nat. Geosci.* doi:10.1038/ngeo2686
- Cooke, M.L., Underwood, C.A., 2001. Fracture termination and step-over at bedding interfaces due to frictional slip and interface opening. *J. Struct. Geol.* 23, 223–238.
- Cosgrove, J.W., Engelder, T. (Eds.), 2004. The initiation, propagation, and arrest of joints and other fractures. Geological Society of London, London.
- Cotterell, B., Rice, J.R., 1980. Slightly curved or kinked cracks. *Int. J. Fract.* 16, 155–169.
- Cressler, C.W., Thurmond, C.J., Hester, W.G., 1983. Ground water in the greater Atlanta region, Georgia.
- Crouch, S.L., Starfield, A.M., 1983. Boundary element methods in solid mechanics. George Allen & Unwin, London.
- Da Costa Nunes, A.J., Costa Couto e Fonseca, A.M.M., Hunt, R.E., 1979. Landslides of Brazil, in: *Rockslides and Avalanches, 2, Engineering Sites*. Elsevier, New York, pp. 419–446.
- Dale, T.N., Smith, G.O., 1907. The granites of Maine, Bulletin 313. Washington, D.C.
- Dale, T.N., 1923. The Commercial Granites of New England, United States Geological Survey, Bulletin 738. U.S. Government Printing Office.
- Das, S.B., Joughin, I., Behn, M.D., Howat, I.M., King, M.A., Lizarralde, D., Bhatia, M.P., 2008. Fracture Propagation to the Base of the Greenland Ice Sheet During Supraglacial Lake Drainage. *Science* (80-.). 1, 778–781. doi:10.1017/CBO9781107415324.004
- Delaney, P.T., Pollard, D.D., Ziony, J.I., McKee, E.H., 1986. Field relations between dikes and joints: emplacement processes and paleostress analysis. *J. Geophys. Res.* 91, 4920–4938.

- Dyskin, A.V., Germanovich, L.N., Ustinov, K.B., 2000. Asymptotic analysis of crack interaction with free boundary. *Int. J. Solids Struct.* 37, 857–886. doi:10.1016/S0020-7683(99)00063-3
- Ericson, K., Olvmo, M., 2004. A-Tents in the Central Sierra Nevada, California: A Geomorphological Indicator of Tectonic Stress. *Phys. Geogr.* 25, 291–312. doi:10.2747/0272-3646.25.4.291
- Faust, G.T., 1978. Joint systems in the Watchung Basalt flows, New Jersey, Professional Paper. Washington, D.C.
- Fox, A., Pointe, P. La, Hermanson, J., Öhman, J., 2007. Statistical geological discrete fracture network model Forsmark modelling stage 2.2. Stockholm.
- Friedman, M., 1972. Residual elastic strain in rock. *Tectonophysics* 15, 287–330.
- Gauss, K.F., 2005. General Investigations of Curved Surfaces. Dover, Mineola, New York.
- Geikie, J., 1905. Structural and field geology, for students of pure and applied science. Oliver and Boyd, Edinburgh.
- Geier, J., Bath, A., Stephansson, O., 2012. Comparison of site descriptive models for Olkiluoto, Finland and Forsmark, Sweden. Helsinki.
- Gilbert, G.K., 1904. Domes and dome structure of the High Sierra. *Bull. Geol. Soc. Am.* 15, 29–36.
- Glazner, A.F., Stock, G.M., 2010. Geology Underfoot in Yosemite National Park and Vicinity. Mountain Press Publishing Company, Missoula, Montana.
- Goodfellow, B.W., Skelton, A., Martel, S.J., Stroeve, A.P., Jansson, K.N., Hättestrand, C., 2014. Controls of tor formation, Cairngorm Mountains, Scotland. *J. Geophys. Res. Earth Surf.* 119, 225–246. doi:doi:10.1002/2013JF002862

- Griggs, D.T., 1936. Deformation of Rocks under High Confining Pressures: I. Experiments at Room Temperature. *J. Geol.* 44, 541–577.
- Gross, M.R., Fischer, M.P., Engelder, T., Greenfield, R.J., 1995. Factors controlling joint spacing in interbedded sedimentary rocks: integrating numerical models with field observations from the Monterey Formation, USA. *Fractography Fract. Topogr. as a tool Fract. Mech. Stress Anal.* 92, 215–233. doi:10.1144/GSL.SP.1995.092.01.12
- Harland, W.B., 1957. Exfoliation joints and ice action. *J. Glaciol.* 3, 8–10.
- Harris, G.F., 1888. *Granites and Our Granite Industries*. Crosby Lockwood and son, London.
- Hatheway, A.W., Kiersch, G. V., 1989. Engineering properties of rock, in: Carmichael, R.S. (Ed.), *Physical Properties of Rocks and Minerals*. CRC Press, Inc., Boca Raton, pp. 671–715.
- Helgeson, D.E., Aydin, A., 1991. Characteristics of joint propagation across layer interfaces in sedimentary rocks. *J. Struct. Geol.* 13, 897–911.
- Hencher, S.R., Lee, S.G., Carter, T.G., Richards, L.R., 2011. Sheeting joints: Characterisation, shear strength and engineering. *Rock Mech. Rock Eng.* 44, 1–22. doi:10.1007/s00603-010-0100-y
- Hermanns, R.L., Strecker, M.R., 1999. Structural and lithological controls on large quaternary rock avalanches (sturzstroms) in arid northwestern Argentina. *Bull. Geol. Soc. Am.* 111, 934–948. doi:10.1130/0016-7606(1999)111<0934:SALCOL>2.3.CO;2
- Hitchcock, E., 1841. *Geology of Massachusetts*. J.H. Butler, Northampton.
- Hoek, E., Bieniawski, Z.T., 1965. Brittle rock fracture propagation In rock under compression. *Int. J. Fract. Mech.* 1, 137–155. doi:10.1007/BF00186851

- Holman, W.R., 1976. The origin of sheeting joints: A hypothesis. University of California at Los Angeles.
- Holzhausen, G.R., 1977. Sheet structure in rock and some related problems in rock mechanics. Stanford.
- Holzhausen, G.R., 1989. Origin of sheet structure, 1. morphology and boundary conditions. Eng. Geol. 27, 225–278.
- Hooker, V.E., Johnson, C.F., 1969. Near-surface horizontal stresses including the effects of rock anisotropy. Bureau of Mines Report of Investigations 7224.
- Horii, H., Nemat-Nasser, S., 1985. Compression-induced microcrack growth in brittle solids: Axial splitting and shear failure. J. Geophys. Res. 90, 3105. doi:10.1029/JB090iB04p03105
- Hutton, J., 1899. Theory of the Earth: With Proofs and Illustrations. Geological Society, London.
- Ivars, D.M., Hakami, H., 2005. Effect of a sub-horizontal fracture zone and rock mass heterogeneity on the stress field in Forsmark area – A numerical study using 3DEC. Stockholm.
- Jaeger, J.C., Cook, N.G.W., Zimmerman, R., 2007. Fundamentals of rock mechanics, 4th ed. Wiley-Blackwell, Oxford.
- Jahns, R.H., 1943. Sheet structure in granites: its origin and use as a measure of glacial erosion in New England. J. Geol. 51, 71–98.
- Jeffreys, H., 1924. The Earth, its origin, history and physical constitution, 1st ed. University Press, Cambridge.
- Johansson, P., 2008. Description of surface hydrology at Forsmark - Site descriptive modelling, Waste Management. Stockholm.

- Jones, F.O., 1973. Landslides of Rio de Janeiro and the Serra das Araras escarpment, Brazil, Professional Paper 697. Washington, D.C.
- Joutsen, A., 2012. The use of geological data from pilot holes for predicting FPI (Full Perimeter Intersection) fractures, Working Report 2012-12. Olkiluoto, Finland.
- Lawn, B.R., Wilshaw, T.R., 1975. Fracture of brittle solids. Cambridge University Press, Cambridge.
- LeGrand, H.E., 1949. Sheet structure, a major factor in the occurrence of ground water in the granites of Georgia. *Econ. Geol.* 44, 110–118. doi:10.2113/gsecongeo.44.2.110
- Leith, K., Moore, J.R., Amann, F., Loew, S., 2014a. In situ stress control on microcrack generation and macroscopic extensional fracture in exhuming bedrock. *J. Geophys. Res. Solid Earth* 119, 594–615. doi:10.1002/2012JB009801
- Leith, K., Moore, J.R., Amann, F., Loew, S., 2014b. Subglacial extensional fracture development and implications for Alpine Valley evolution. *J. Geophys. Res. Earth Surf.* 119, 62–81. doi:10.1002/2012JF002691
- Liljedahl, L.C., Munier, R., Sandström, B., Drake, H., Tullborg, E.-L., 2011. Assessment of fractures classified as non-mineralised in the Sicada database. SKB R-11-02 172.
- Liu, M., Yang, Y., 2003. Extensional collapse of the Tibetan Plateau: Results of three-dimensional finite element modeling. *J. Geophys. Res.* 108, 1–15. doi:10.1029/2002JB002248
- Malvern, L.E., 1969. Introduction to the mechanics of a continuous medium. Prentice-Hall, Upper Saddle River, New Jersey.
- Marrett, R., Ortega, O.J., Kelsey, C.M., 1999. Extent of power-law scaling for natural fractures in rock. *Geology* 27, 799–802. doi:10.1130/0091-7613(1999)027<0799:EOPLSF>2.3.CO

- Martel, S.J., 2000. Modeling elastic stresses in long ridges with the displacement discontinuity method. *Pure Appl. Geophys.* 157, 1039–1057. doi:10.1007/s000240050016
- Martel, S.J., 2006. Effect of topographic curvature on near-surface stresses and application to sheeting joints. *Geophys. Res. Lett.* 33, 1–5. doi:10.1029/2005GL024710
- Martel, S.J., 2011. Mechanics of curved surfaces, with application to surface-parallel cracks. *Geophys. Res. Lett.* 38, 1–6. doi:10.1029/2011GL049354
- Martel, S.J., 2016. Effects of small-amplitude periodic topography on combined stresses due to gravity and tectonics. *Int. J. Rock Mech. Min. Sci.* 89, 1–13. doi:10.1016/j.ijrmms.2016.07.026
- Martin, C.D., Kaiser, P.K., Christiansson, R., 2003. Stress, instability and design of underground excavations. *Int. J. Rock Mech. Min. Sci.* 40, 1027–1047. doi:10.1016/S1365-1609(03)00110-2
- Matthes, F.E., 1930. *Geologic history of the Yosemite Valley.*
- McClintock, F.A., Argon, A.S., 1966. *Mechanical behavior of materials.* Addison-Wesley, Reading, Massachusetts.
- Miller, D.J., Dunne, T., 1996. Topographic perturbations of regional stresses and consequent bedrock fracturing. *J. Geophys. Res.* 101, 25,523–25,536. doi:10.1029/96JB0253
- Mitchell, K.J., 2010. *Factors contributing to the formation of sheeting joints: a study of sheeting joints on a dome in Yosemite National Park.* University of Hawaii.
- Molnar, P., 2004. Interactions among topographically induced elastic stress, static fatigue, and valley incision. *J. Geophys. Res.* 109, 1–9. doi:10.1029/2003JF000097

- Nadan, B.J., Engelder, T., 2009. Microcracks in New England granitoids: A record of thermoelastic relaxation during exhumation of intracontinental crust. *Bull. Geol. Soc. Am.* 121, 80–99. doi:10.1130/B26202.1
- Nemat-Nasser, S., Horii, H., 1982. Compression-induced nonplanar crack extension with application to splitting, exfoliation, and rockburst. *J. Geophys. Res.* 87, 6805. doi:10.1029/JB087iB08p06805
- Niles, W.H., 1871. Peculiar phenomena observed in quarrying. *Proc. Bost. Soc. Nat. Hist.* 14, 80–87.
- Nygård, R., Gutierrez, M., Bratli, R.K., Høeg, K., 2006. Brittle-ductile transition, shear failure and leakage in shales and mudrocks. *Mar. Pet. Geol.* 23, 201–212. doi:10.1016/j.marpetgeo.2005.10.001
- Olson, J., Pollard, D., 1989. Inferring paleostresses from natural fracture patterns: A new method. *Geology* 17, 345–348. doi:10.1130/0091-7613(1989)017<0345
- Olson, J.E., Pollard, D.D., 1991. The initiation and growth of en echelon veins. *J. Struct. Geol.* 13, 595–608. doi:10.1016/0191-8141(91)90046-L
- Paterson, M.S., Wong, T., 2005. *Experimental rock deformation – the brittle field*, 2nd ed. Springer, Berlin.
- Peng, S., 1970. *Fracture and failure of Chelmsford Granite*. Stanford University.
- Perron, J.T., Kirchner, J.W., Dietrich, W.E., 2008. Spectral signatures of characteristic spatial scales and nonfractal structure in landscapes. *J. Geophys. Res. Earth Surf.* 113, 1–14. doi:10.1029/2007JF000866

- Plumb, R., Engelder, T., Sbar, M., 1984. Near-surface in situ stress: 2. A comparison with stress directions inferred from earthquakes, joints, and topography near Blue Mountain Lake, New York. *J. Geophys. Res.* 89, 9333–9349. doi:10.1029/JB089iB11p09333
- Pollard, D.D., Aydin, A., 1988. Progress in understanding jointing over the past century. *Geol. Soc. Am. Bull.* 100, 1181–1204. doi:10.1130/0016-7606(1988)100<1181
- Pollard, D.D., Aydin, A., 1984. Propagation and linkage of oceanic ridge segments. *J. Geophys. Res.* 89, 10,017–10,028.
- Pollard, D.D., Holzhausen, G., 1979. On the mechanical interaction between a fluid-filled fracture and the Earth's surface. *Tectonophysics* 53, 27–57.
- Pollard, D.D., Muller, O.H., 1976. The effect of gradients in regional stress and magma pressure on the form of sheet intrusions in cross section. *J. Geophys. Res.* 81, 975–984.
- Pollard, D.D., Segall, P., 1987. Theoretical displacements and stress near fractures in rock: with applications to faults, joints, veins, dikes, and solution surfaces, in: Atkinson, B.K. (Ed.), *Fracture Mechanics of Rock*. Academic Press, London, pp. 227–349. doi:10.1016/B978-0-12-066266-1.50013-2
- Pötzsch, C.G., 1803. Bemerkungen und Beobachtungen über das Vorkommen des Granits in geschichteten Lagen oder Bänken besonders in der Oberlausitz und dessen relatives Alter, wie auch über den Sienit. *Waltherische Hofbuchhandlung, Dresden*.
- Price, N.J., 1966. *Fault and joint development in brittle and semi-brittle rock*. Pergamon Press, Oxford.
- Ramsay, J.G., Huber, M.I., 1987. *The techniques of modern structural geology. Volume 2: Folds and Fractures*. Academic Press, London.

- Renshaw, C.E., Park, J.C., 1997. Effect of mechanical interactions on the scaling of fracture length and aperture. *Nature*. doi:10.1038/386482a0
- Renshaw, C.E., Pollard, D.D., 1995. An experimentally verified criterion for propagation across unbonded frictional interfaces in brittle, linear elastic materials. *Int. J. Rock Mech. Min. Sci. Geomech. Abstr.* 32, 237–249.
- Römer, W., 2007. Differential weathering and erosion in an inselberg landscape in southern Zimbabwe: A morphometric study and some notes on factors influencing the long-term development of inselbergs. *Geomorphology* 86, 349–368.
doi:10.1016/j.geomorph.2006.09.008
- Savage, W.Z., Swolfs, H.S., Powers, P.S., 1985. Gravitational stresses in long symmetric ridges and valleys. *Int. J. Rock Mech. Geomech. Abstr.* 22, 291–302. doi:10.1016/0148-9062(85)92061-3
- Savage, W.Z., Swolfs, H.S., 1986. Tectonic and gravitational stress in long symmetric ridges and valleys. *J. Geophys. Res.* 91, 367–3685. doi:10.1029/JB091iB03p03677
- Segall, P., Pollard, D.D., 1983. Joint formation in granitic rock of the Sierra Nevada. *Geol. Soc. Am. Bull.* 563–575. doi:10.1130/0016-7606(1983)94<563
- Shaler, N.S., 1869. Notes of the concentric structure of granitic rocks. *Proc. Bost. Soc. Nat. Hist.* 12, 289–293.
- Slim, M., Perron, J.T., Martel, S.J., Singha, K., 2014. Topographic stress and rock fracture: a two-dimensional numerical model for arbitrary topography and preliminary comparison with borehole observations. *Earth Surf. Process. Landforms* 529, n/a–n/a.
doi:10.1002/esp.3646

- Smith, R.A., 1976. The application of fracture mechanics to the problem of crevasse penetration. *J. Glaciol.* 17, 223–228.
- St. Clair, J., Moon, S., Holbrook, W.S., Perron, J.T., Riebe, C.S., Martel, S.J., Carr, B., Harman, C., Singha, K., Richter, D. deB., 2015. Geophysical imaging reveals topographic stress control of bedrock weathering. *Science* (80-.). 350, 534–539. doi:10.1126/science.aab2210
- Stock, G.M., Martel, S.J., Collins, B.D., Harp, E.L., 2012. Progressive failure of sheeted rock slopes: The 2009-2010 Rhombus Wall rock falls in Yosemite Valley, California, USA. *Earth Surf. Process. Landforms* 37, 546–561. doi:10.1002/esp.3192
- Tada, H., Paris, P.C., Irwin, G.R., 2000. *The stress analysis of cracks handbook*, 3rd ed. ASME Press.
- Talbot, C., 1999. Ice ages and nuclear waste isolation. *Eng. Geol.* 52, 177–192. doi:10.1016/S0013-7952(99)00005-8
- Terzaghi, K., 1962. Dam foundation on sheeted granite. *Geotechnique* 12, 199–208.
- Timoshenko, S.P., Goodier, J.N., 1970. *Theory of elasticity*, 3rd ed. McGraw-Hill, New York.
- Tokunaga, T.K., Wan, J., 1997. Water film flow along fracture surfaces of porous rock. *Water Resour. Res.* 33, 1287–1295. doi:10.1029/97WR00473
- Tokunaga, T.K., Wan, J., 2001. Surface-zone flow along unsaturated rock fractures. *Water Resour. Res.* 37, 287–296. doi:10.1029/2000WR900242
- Trainer, F.W., 1988. Hydrogeology of the plutonic and metamorphic rocks, in: *The Geology of North America, Vol. O2, Hydrogeology*. Geological Society of America, Boulder, Colorado, pp. 367–380.
- Twidale, C.R., 1971. *Structural landforms*. Australian National University Press, Canberra.
- Twidale, C.R., 1973. On the origin of sheet jointing. *Rock Mech.* 5, 163–187.

- Twidale, C.R., 1982. Granite landforms. Elsevier, Amsterdam.
- Twidale, C.R., Bourne, J.A., 2003. Active dislocations in granitic terrains of the Gawler and Yilgarn cratons, Australia, and some implications. *South African J. Geol.* 106, 71–84.
- Van Hise, C.R., 1904. A treatise on metamorphism. Washington, D.C.
- doi:<http://dx.doi.org/10.5962/bhl.title.45549>
- Vening Meinesz, F.A., 1950. Les graben africains resultant de compression ou de tension dans la croûte terrestre? *Inst. R. Colon. Belge, Bull.* 21, 539–552.
- Vidal Romaní, J.R., Twidale, C.R., 1999. Sheet fractures, other stress forms and some engineering implications. *Geomorphology* 31, 13–27. doi:10.1016/S0169-555X(99)00070-7
- Warth, H., 1895. The quarrying of granite in India. *Nature* 51, 272.
- Weertman, J., 1971. Theory of water-filled crevasses in glaciers applied to vertical magma transport beneath oceanic ridges. *J. Geophys. Res.* 76, 1171–1183.
- White, W.S., 1946. Rock-bursts in the granite quarries at Barre , Vermont.
- Whitney, J.D., 1865. Geology of California. Caxton Press of Sherman & Co., Philadelphia.
- doi:10.1017/CBO9781107415324.004
- Whitney, J.D., 1869. The Yosemite book. Julius Bien, New York.
- Wieczorek, G.F., Snyder, J.B., 1999. Rock falls from Glacier Point above Camp Curry, Yosemite National Park, California. *US Geol. Surv. Open-File Rep.* 1–12.
- Wieczorek, G.F., Jäger, S., 1996. Triggering mechanisms and depositional rates of postglacial slope-movement processes in the Yosemite Valley, California. *Geomorphology* 15, 17–31.
- Witherspoon, P.A., Wang, J.S.Y., Iwai, K., Gale, J.E., 1980. Validity of cubic law for fluid flow in a deformable rock fracture. *Water Resour. Res.* 16, 1016-1024.

- Wong, T.-F., 1982. Micromechanics of faulting in westerly granite. *Int. J. Rock Mech. Min. Sci.* 19, 49–64. doi:10.1016/0148-9062(82)91631-X
- Wyrick, G.G., Borchers, J.W., 1981. Hydrologic effects of stress-relief fracturing in an Appalachian valley. *U.S. Dept. Inter. Geol. Surv.* 51.
- Zhang, X., Jeffrey, R., Detournay, E., 2002. Propagation of a fluid-driven penny-shaped fracture parallel to the free-surface of an elastic solid. *Int. J. Fract.* 125–158.
- Zhang, X., Jeffrey, R.G., 2014. Role of overpressurized fluid and fluid-driven fractures in forming fracture networks. *J. Geochemical Explor.* 144, 194–207. doi:10.1016/j.gexplo.2014.03.021
- Ziegler, M., 2013. Age and formation mechanisms of exfoliation joints in the Aar Granites of the Central Alps (Grimsel region, Switzerland). *Swiss Federal Institute of Technology, Zurich.*
- Ziegler, M., Loew, S., Moore, J.R., 2013. Distribution and inferred age of exfoliation joints in the Aar Granite of the central Swiss Alps and relationship to Quaternary landscape evolution. *Geomorphology* 201, 344–362.
- Ziegler, M., Loew, S., Bahat, D., 2014a. Growth of exfoliation joints and near-surface stress orientations inferred from fractographic markings observed in the upper Aar valley (Swiss Alps). *Tectonophysics* 626, 1–20. doi:10.1016/j.tecto.2014.03.017
- Ziegler, M., Loew, S., Valley, B., Amann, F., 2014b. Near-surface principal stress trajectories in Alpine valleys (Grimsel region, Switzerland) as inferred from exfoliation fracture plumose structure axes and numerical modeling, in: Labuz, J.F. (Ed.), 48th US Rock Mechanics/Geomechanics Symposium. American Rock Mechanics Association (ARMA), Minneapolis, Minnesota.

Figure captions

Figure 1. Examples of sheeting joints. All, except as noted, are from Yosemite National Park and vicinity, Sierra Nevada, California. (a) Little Shuteye Pass. From

<https://www.sciencebase.gov/catalog/item/51dc8ee8e4b097e4d3839beb>

(b) “Tabular joints” at the summit of Goatfell in Arran, Scotland (from Geikie, 1905). (c) Back of Half Dome (from Martel, 2011). (d) Face of Half Dome. (e) Dome along Tenaya Creek. (f) Hanging valley of Tenaya Creek. (g) Tioga Road quarry. (h) Curved sheeting joints at a roadcut along Tioga Road. (i) At roadcut near Olmsted Point. (j) Sheeting joint in sandstone cliff, Utah. Based on the height of vegetation, the height of people, or measurements, the typical spacing of sheeting joints in these photographs is several decimeters to about two meters.

Figure 2. Water issuing from sheeting joints in Tenaya Canyon. Based on the height of vegetation and an inspection of the area, the typical spacing of sheeting joints in this photograph is between several centimeters and a few decimeters.

Figure 3. Variation of sheeting joints with depth. (a) Idealized cross section showing pattern of sheeting joints at Fletcher Hill, Massachusetts with vertical exaggeration of a factor of 4 (upper) and without vertical exaggeration (lower) (modified from Jahns, 1943). (b) Variation in thickness of sheets of granite vs. depth beneath the exposed rock surface (modified from Jahns, 1943).

Figure 4. Surface textures on sheeting joints. (a) Above Tenaya Lake; note rock climbers (two are marked by arrows) for scale. (b) On ridge northwest of Tioga Road quarry, with clumps of

grass for scale. Each photograph shows some radiating hackles and concentric arrest marks (or ribs).

Figure 5. Hook-shaped sheeting joints (marked by arrows) bound a lens of granite in the wall of a quarry in Maine (from Dale and Smith, 1907). Dale (1923) described the spacing between sheeting joints as being 1-3 meters. From

<http://library.usgs.gov/photo/#/item/51dc3932e4b0f81004b7a656>

Figure 6. Photographs showing relative displacement across sheeting joints. (a) Sheeting joint cutting an inclusion and dike but not offsetting them. The maximum aperture is ~ 5 cm. Note pencil for scale. (b) Buckled slab of rock above a sheeting joint (from Matthes, 1930, Plate 48a).

Figure 7. Stress field changes accompanying the opening of a fracture. The terms σ_1 (the most tensile stress) and σ_3 (the least tensile stress) describe the ambient stress field; $\Delta\sigma$ is the perturbation of the stress in the direction of σ_1 , as evaluated along the fracture; and σ_D is the driving stress.

Figure 8. Threshold curves for positive driving stress gradients at the crests of a ridge ($k_1 = 0$, $k_2 = 0$) and an axisymmetric dome where the surface-parallel stresses are for isotropic compression ($\sigma_{11} = \sigma_{22} = \sigma$).

Figure 9. Boundary element solutions for the stress field beneath cosinusoidal topography subject to gravity and a uniform horizontal tectonic compression, with $A/L = 0.03$ and $T = -63\rho gA$. (a)

$\sigma_1/(-T)$. (b) $\sigma_D^{sat}/(-T)$. (c) Trajectories perpendicular to the most tensile stress superposed on the contours bounding regions where the most tensile stress (or driving stress) is positive.

Figure 10. Boundary element solutions for the stress field beneath cosinusoidal topography subject to gravity and a uniform horizontal tectonic compression, with $A/L = 0.03$ and $T = -84\rho gA$. (a) $\sigma_1/(-T)$. (b) $\sigma_D^{sat}/(-T)$. (c) Trajectories perpendicular to the most tensile stress superposed on the contours bounding regions where the most tensile stress (or driving stress) is positive.

Figure 11. Relative displacements near a fracture tip (modes I, II, and III).

Figure 12. Normalized mode I stress intensity factors for cracks emanating from a circular hole under biaxial stress, where σ_1 can be positive, negative, or zero, and σ_3 is negative (Bowie, 1956; Tada et al. 2000). The stress intensity factors are normalized by the stress intensity factor for a fracture of half-length R with a driving stress of $-\sigma_3$. The stress intensity factors K_{II} and K_{III} equal zero.

Figure 13. (a) Normalized stress intensity factors K_I (mode I) and K_{II} (mode II) for a uniformly pressurized two-dimensional planar fracture parallel to a planar traction-free surface as a function of the depth/half-length ratio of the crack. The stress intensity factors are normalized by K_I for a uniformly pressurized fracture in an infinite body. Stress intensity factors are calculated by the approach of Dyskin et al. (2000). (b) Ratio of K_{II} to K_I as a function of the depth/half-length ratio of the fracture. The increase in the ratio as d/a approaches zero means the fracture

would tend to propagate towards the surface as it grows.

Figure 14. Boundary element solutions for the stress field beneath cosinusoidal topography with a relatively long wavelength and relatively high amplitude topography subject to gravity and a uniform horizontal tectonic compression, with $A = 40\text{m}$, $L = 2000\text{m}$, $A/L = 0.02$, $\rho = 2.7 \times 10^3 \text{ kg/m}^3$, and $T = -85\rho gA = -45 \text{ MPa}$. (a) $\sigma_1/(-T)$. (b) $\sigma_D^{sat}/(-T)$. (c) Trajectories perpendicular to the most tensile stress superposed on the contour bounding the base of the region where the driving stress in (b) is positive.

Figure 15. Boundary element solutions for the stress field beneath cosinusoidal topography with a relatively short wavelength and relatively low amplitude topography subject to gravity and a uniform horizontal tectonic compression, with $A = 5\text{m}$, $L = 500\text{m}$, $A/L = 0.01$, $\rho = 2.7 \times 10^3 \text{ kg/m}^3$, and $T = -320\rho gA = -45 \text{ MPa}$. (a) $\sigma_1/(-T)$. (b) $\sigma_D^{sat}/(-T)$. (c) Trajectories perpendicular to the most tensile stress superposed on the contour bounding the base of the region where the driving stress in (b) is positive.

Figure 16. Simulated joint traces grown from the same random distribution of starting flaws by the boundary element method using two different ratios of driving stress (σ_D) to differential stress (σ_{Diff}), with the most compressive ambient stress parallel to the long sides of the boxes (redrawn from Olson and Pollard, 1989). (a) Driving stress is high relative to the differential stress ($\sigma_D/\sigma_{Diff} = 5$). (b) Driving stress is low relative to the differential stress ($\sigma_D/\sigma_{Diff} = 0.5$).

Tables

Table 1. Near-surface horizontal stresses from overcoring measurements at sites with sheeting joints.

Location	Most tensile stress (MPa)	Least tensile stress (MPa)
Canital Quarry Manitoba (a)	-9.0	-19.5
Granite Mountain Marble Falls, Texas (b)	-10.3	-15.3
Kittredge Hill New Hampshire (c)	-4.5	-26.7
Fletcher Quarry Milford, New Hampshire (c)	-2.6	-6.5
Oak Hill Quarry Westford, Massachusetts (b)	-12.1	-22.6
Pine Mountain Georgia (b)	-5.9	-7.2
Redstone Quarry North Conway, New Hampshire (c)	-3.7	-8.6
Stone Mountain Georgia (b)	-6.9	-10.3
Fletcher Quarry Westford, Massachusetts (d)	-21.0	-36.0

References: (a) Martin et al. (2003), (b) Hooker and Johnson (1969), (c) Plumb et al. (1984), (d) Holzhausen (1989).

Figure 1

Figure 1. Examples of sheeting joints. All, except as noted, are from Yosemite National Park and vicinity, Sierra Nevada, California. (a) Little Shuteye Pass. From <https://www.sciencebase.gov/catalog/item/51dc8ee8e4b097e4d3839beb> (b) "Tabular joints" at the summit of Goatfell in Arran, Scotland [from Geikie, 1905]. (c) Back of Half Dome (from Martel, 2011). (d) Face of Half Dome. (e) Dome along Tenaya Creek. (f) Hanging valley of Tenaya Creek. (g) Tioga Road quarry. (h) Curved sheeting joints at a roadcut along Tioga Road. (i) At roadcut near Olmsted Point. (j) Sheeting joint in sandstone cliff, Utah. Based on the height of vegetation, the height of people, or measurements, the typical spacing of sheeting joints in these photographs is several decimeters to about two meters.

Figure 2

Figure 2. Water issuing from sheeting joints in Tenaya Canyon. Based on the height of vegetation and an inspection of the area, the typical spacing of sheeting joints in this photograph is between several centimeters and a few decimeters.

Figure 3

Figure 3. Variation of sheeting joints with depth. (a) Idealized cross section showing pattern of sheeting joints at Fletcher Hill, Massachusetts with vertical exaggeration of a factor of 4 (upper) and without vertical exaggeration (lower) (modified from Jahns, 1943). (b) Variation in thickness of sheets of granite vs. depth beneath the exposed rock surface (modified from Jahns, 1943).

Figure 4. Surface textures on sheeting joints. (a) Above Tenaya Lake; note rock climbers (two are marked by arrows) for scale. (b) On ridge northwest of Tioga Road quarry, with clumps of grass for scale. Each photograph shows some radiating hackles and concentric arrest marks (or ribs).

Figure 5

Figure 5. Hook-shaped sheeting joints (marked by arrows) bound a lens of granite in the wall of a quarry in Maine (from Dale and Smith, 1907). Dale (1923) described the spacing between sheeting joints as being 1-3 meters. From <http://library.usgs.gov/photo/#/item/51dc3932e4b0f81004b7a656>

Figure 6

Figure 6. Photographs showing relative displacement across sheeting joints. (a) Sheeting joint cutting an inclusion and dike but not offsetting them. The maximum aperture is ~ 5 cm. Note pencil for scale. (b) Buckled slab of rock above a sheeting joint (from Matthes, 1930, Plate 48a).

Figure 7

Figure 7. Stress field changes accompanying the opening of a fracture. The terms σ_1 (the most tensile stress) and σ_3 (the least tensile stress) describe the ambient stress field; $\Delta\sigma$ is the perturbation of the stress in the direction of σ_1 , as evaluated along the fracture; and σ_D is the driving stress.

Figure 8

Figure 8. Threshold curves for positive driving stress gradients at the crests of a ridge ($k_1 = 0, k_2 = k$) and an axisymmetric dome ($k_1 = k_2 = k$) where the surface-parallel stresses are for isotropic compression ($\sigma_{11} = \sigma_{22} = \sigma$).

Figure 9

Figure 9. Boundary element solutions for the stress field beneath cosinusoidal topography subject to gravity and a uniform horizontal tectonic compression, with $A/L = 0.03$ and $T = -63\text{pgA}$. (a) $\sigma_1/(-T)$. (b) $\sigma_D^{sat}/(-T)$. (c) Trajectories perpendicular to the most tensile stress superposed on the contours bounding regions where the most tensile stress (or driving stress) is positive.

Figure 10

Figure 10. Boundary element solutions for the stress field beneath cosinusoidal topography subject to gravity and a uniform horizontal tectonic compression, with $A/L = 0.03$ and $T = -84\text{pgA}$. (a) $\sigma_1/(-T)$. (b) $\sigma_D^{sat}/(-T)$. (c) Trajectories perpendicular to the most tensile stress superposed on the contours bounding regions where the most tensile stress (or driving stress) is positive.

Figure 11

Figure 11. Relative displacements near a fracture tip (modes I, II, and III).

Figure 12

Figure 12. Normalized mode I stress intensity factors for cracks emanating from a circular hole under biaxial stress, where σ_1 can be positive, negative, or zero, and σ_3 (Bowie, 1956; Tada et al. 2000). The stress intensity factors are normalized by the stress intensity factor for a fracture of half-length R with a driving stress of $-\sigma_3$. Modify vertical axis. The stress intensity factors K_{II} and K_{III} are equal zero.

Figure 13

Figure 13. (A) Normalized stress intensity factors K_I (mode I) and K_{II} (mode II) for a uniformly pressurized two-dimensional planar fracture parallel to a planar traction-free surface as a function of the depth/half-length ratio of the fracture. The stress intensity factors are normalized by K_I for a uniformly pressurized crack in an infinite body. Stress intensity factors are calculated by the approach of Dyskin et al. (2000). (B) Ratio of K_{II} to K_I as a function of the depth/half-length ratio of the fracture. The increase in the ratio as d/a approaches zero means the fracture would tend to propagate towards the surface as it grows.

Figure 14

Figure 14. Boundary element solutions for the stress field beneath cosinusoidal topography with a relatively long wavelength and relatively high amplitude topography subject to gravity and a uniform horizontal tectonic compression, with $A = 40\text{m}$, $L = 2000\text{m}$, $A/L = 0.02$, $\rho = 2.7 \times 10^3 \text{ kg/m}^3$, and $T = -85\rho g A = -45 \text{ MPa}$. (a) $\sigma_1/(-T)$. (b) $\sigma_D^{sat}/(-T)$. (c) Trajectories perpendicular to the most tensile stress superposed on the contour bounding the base of the region where the driving stress in (b) is positive.

Figure 15

Figure 15. Boundary element solutions for the stress field beneath cosinusoidal topography with a relatively short wavelength and relatively low amplitude topography subject to gravity and a uniform horizontal tectonic compression, with $A = 5\text{m}$, $L = 500\text{m}$, $A/L = 0.01$, $\rho = 2.7 \times 10^3 \text{ kg/m}^3$, and $T = -320\text{pgA} = -45 \text{ MPa}$. (a) $\sigma_1/(-T)$. (b) $\sigma_D^{sat}/(-T)$. (c) Trajectories perpendicular to the most tensile stress superposed on the contours bounding regions where the driving stress in (b) is positive.

Figure 16

Figure 16. Simulated joint traces grown from the same random distribution of starting flaws by the boundary element method using two different ratios of driving stress (σ_D) to differential stress (σ_{Diff}), with the most compressive ambient stress parallel to the long sides of the boxes [redrawn from Olson and Pollard, 1989]. (a) Driving stress is high relative to the differential stress ($\sigma_D/\sigma_{Diff} = 5$). (b) Driving stress is low relative to the differential stress ($\sigma_D/\sigma_{Diff} = 0.5$).