Linking instantaneous rate of injection to x-ray needle lift measurements for a direct-acting piezoelectric injector

Juan P. Viera^{a,*}, Raul Payri^a, Andrew B. Swantek^b, Daniel J. Duke^b,
Nicolas Sovis^b, Alan L. Kastengren^c, Christopher F. Powell^b

^a*CMT-Motores Térmicos, Universitat Politècnica de València, Camino de Vera s/n,
46022 Valencia, Spain*

^b*Argonne National Laboratory, Energy Systems Division, Argonne, IL 60439 USA*

^c*Argonne National Laboratory, Advanced Photon Source, X-ray Science Division,
Argonne, IL 60439 USA*

Abstract

Internal combustion engines have been and still are key players in today's world. Ever increasing fuel consumption standards and the ongoing concerns about exhaust emissions have pushed the industry to research new concepts and develop new technologies that address these challenges. To this end, the diesel direct injection system has recently seen the introduction of direct-acting piezoelectric injectors, which provide engineers with direct control over the needle lift, and thus instantaneous rate of injection (ROI). Even though this type of injector has been studied previously, no direct link between the instantaneous needle lift and the resulting rate of injection has been quantified. This study presents an experimental analysis of the relationship between instantaneous partial needle lifts and the corresponding ROI. A prototype direct-acting injector was utilized to produce steady injections of different magnitude by partially lifting the needle. The ROI measurements were carried out at CMT-Motores Térmicos utilizing a standard injection rate discharge curve indicator based on the Bosch method (anechoic tube). The needle lift measurements were performed at the Advanced Photon Source at Argonne National Laboratory. The analysis seeks both to contribute to the current understanding of the influence that partial needle lifts have over

*Corresponding author

Email address: juavieso@mot.upv.es (Juan P. Viera)

the instantaneous ROI and to provide experimental data with parametric variations useful for numerical model validations. Results show a strong relationship between the steady partial needle lift and the ROI. The effect is non-linear, and also strongly dependent on the injection pressure. The steady lift value at which the needle ceases to influence the ROI increases with the injection pressure. Finally, a transient analysis is presented, showing that the needle velocity may considerably affect the instantaneous ROI, because of the volume displaced inside the nozzle. Results presented in this study show that at constant injection pressure and energizing time, this injector has the potential to control many aspects of the ROI and thus, the heat release rate. Also, data presented are useful for numerical model validations, which would provide detailed insight into the physical processes that drive these observations, and potentially, to the effects of these features on combustion performance.

Keywords:

Diesel direct injection, rate of injection, synchrotron, x-ray imaging, needle lift.

1 **1. Introduction**

2 Internal combustion engines have played a significant part in shaping the
3 world and people’s way of life since their introduction over a century ago.
4 Nevertheless, the ever increasing fuel consumption standards and the ongoing
5 concerns about exhaust emissions have pushed the industry to research
6 new concepts and develop new technologies that address these concerns and
7 challenges.

8 A large part of this research and development process has been carried out
9 on the fuel injection system because injection conditions play a determinant
10 role in fuel spray formation, fuel/air mixing, and combustion performance
11 [1, 2]. The injection system hardware has seen several developments over
12 the last two decades. Among these was the introduction of piezo-actuated
13 injectors, which offer faster response and better control characteristics when
14 compared to solenoid-actuated models [3, 4]. These injectors are similar to
15 each other in concept: the injector is remotely actuated and the needle is
16 lifted through hydraulic pressure differentials. Therefore, from the control
17 point of view, all these injectors behave in “binary” fashion: the fuel rate of
18 injection (ROI) is mainly controlled by the injection pressure, and the total

19 injected mass is a function of both injection pressure and energizing time
20 (ET). To a certain extent, this limits combustion control, since the ET also
21 determines heat release phasing and rates [5–7]. The recent introduction of
22 direct-acting piezoelectric injectors [8] provides engineers with direct control
23 over the needle lift—thus, over the instantaneous fuel flow—which opens a
24 wide range of possibilities for controlling the injection event and combustion
25 process [9–11].

26 Interest in understanding injector and spray behavior under partial needle
27 lift conditions is not bound exclusively to direct-acting injectors, since
28 conventional injectors also operate under these conditions in various situations
29 (i.e., pilot injections and the start or end of injections). Chiavola and
30 Palmieri [12] utilized a numerical computational fluid dynamics (CFD) model
31 to study the effect of needle radial motion (needle wobble) on cavitation and
32 flow patterns within a valve covered orifice nozzle, showing that the radial
33 needle location (and speed) can greatly affect the hole-to-hole symmetry of
34 the flow. Later, Som et al. [13] presented numerical results of the effects of
35 needle lift over in-nozzle flow, showing that needle lift significantly affects the
36 velocity fields through the needle seat, the nozzle sac, and the orifice. Ferrari
37 and Mittica [14] presented a finite element model of a direct-acting piezoelectric
38 injector that included electrical, mechanical, and hydraulic submodels,
39 concluding that the injection pressure strongly affects the behavior of the
40 direct-acting mechanism. Payri et al. [15–17] employed a prototype direct-
41 acting injector to study the effect of steady partial needle lift on nozzle flow
42 characteristics and macroscopic spray development. Their studies showed a
43 strong relationship between fuel mass flow rates through the nozzle and estimated
44 needle lift, also finding that needle lift and piezo actuator response
45 are strongly affected by the injection pressure. Moreover, a strong correlation
46 between the liquid length, vapor spray penetration rate, and needle lift
47 was evidenced. Recently, Desantes et al. [18] employed a numerical CFD
48 model to study the relationship between needle lift and ROI for a micro-sac
49 multi-hole nozzle with cylindrical orifices. In their study, the authors show
50 that the onset of the cavitation void occurs at the needle seat for low needle
51 lift conditions, and moves downstream to the orifice when needle lift is high
52 enough.

53 It is important to point out that actual needle lifts in the studies presented
54 by Payri et al. [15–17] are unknown and were not directly controlled, so
55 existing studies do not establish a direct link between needle lift values and
56 spray formation response, for example, to validate CFD models.

Measuring instantaneous needle lift of diesel injectors under realistic operating conditions presents a considerable challenge. X-ray imaging is advantageous for this particular application, as the rays are able to penetrate the steel nozzle wall, eliminating the need for any modification of the injector. Synchrotron x-rays provide detailed measurements of the internal geometry of fuel injectors by exploiting the phase contrast that occurs when highly collimated x-rays are weakly diffracted by the phase boundaries at the nozzle walls [19]. Owing to the high flux of the synchrotron source, time-resolved measurements of the internal needle motion can be made with microscale precision using a high-speed camera [20]. These measurements have been coupled with observations of cavitation and gas ingestion inside the injector and changes in the external flow [21–23].

This paper presents an experimental analysis of the relationship between instantaneous partial needle lifts and ROI. A prototype direct-acting injector is utilized to produce steady injections of different magnitude by partially lifting the needle. Also, transient features such as ramp rates and injection rate shaping are explored. The ROI measurements were carried out at CMT-Motores Térmicos (CMT) utilizing a standard injection rate discharge curve indicator (IRDCI) based in the Bosch method [24]. The needle lift measurements were performed at the Advanced Photon Source (APS) located at Argonne National Laboratory. The analysis pursues two different goals: first, to contribute to the understanding of the influence that partial needle lifts have over the instantaneous ROI; second, to provide extensive experimental data with parametric variations useful for numerical model validations, which could potentially be later employed to enhance the current understanding of partial needle lift and injection rate shaping over global combustion performance.

2. Materials and methods

2.1. Rate of injection measurements

The ROI measurements were carried out utilizing a commercial Injection Discharge Rate Curve Indicator (IRDCI)[24], which consists of injecting fuel into a fuel-filled long tube. The instantaneous ROI is proportional to the pressure signal measured by a piezoelectric pressure sensor [25]. For these experiments, a total of 50 injections were acquired at each test condition. Details of the full apparatus and technique can be found in the work of Payri et al. [25, 26]. Injection pressure was measured at the common rail.

Figure 1: Schematic diagram of x-ray phase-contrast imaging experiment at the 32-ID beamline of the Advanced Photon Source at Argonne National Laboratory (not to scale).

93 Note that the final repetition-averaged ROI signal for a given test condition
 94 is scaled/corrected with the total injected mass, which is simultaneously
 95 measured by a precision electronic scale [25]. The fuel utilized for the ROI
 96 experiments was ISO 4113 calibration fluid. Details of the test conditions
 97 covered are presented in Table 1.

Table 1: Rate of injection experiments test plan

Parameter	Test conditions					
Inj. press. [bar]	500	500	1500	1500	500	500
Back press. [bar]	50; 11	50	50; 11	50	50	50
Control volt. [V]	135; 120; 105; 90; 85	150; 132; 126	150, 118; 116	85 → 120	95 → 120	
	100; 95		114			
Ramp rate [V/μs]	1	1	1	2	2	2
Injection shape	square	square	square	square	boot	boot

98 2.2. Phase-contrast imaging

99 X-ray measurements of needle displacement were performed at the 32-ID
 100 beamline of the Advanced Photon Source at Argonne National Laboratory
 101 [27]. The experiment setup is shown in Figure 1, and the test conditions
 102 covered are presented in Table 2. A common-rail diesel injection system
 103 powered by an electrically driven mechanical pump delivered fuel to the in-
 104 jector. Injection pressure was measured at the common rail. The fuel was
 105 sprayed into a chamber pressurized with N_2 . Kapton windows allowed the
 106 x-rays to pass through the chamber with minimum absorption. The experi-
 107 ments were conducted at room temperature. The fuel used was a commercial

108 diesel surrogate with approximately 2 % (by mass) cerium additive. The fuel
 109 had a density of 865.6 kg/m³ and a viscosity of 3.22 cSt at 25 °C. For these
 110 experiments, a total of 21 injections were acquired for each test condition.

111 The peak irradiance of the x-ray beam was approximately 3×10^{12} ph/s/mm²/0.1 %BW
 112 with an undulator gap of 17 mm. The distance from the source to the ex-
 113 periment was approximately 35.5 m. A 5 mm Si filter was used to remove
 114 low-energy photons from the raw x-ray source. A 150 µm LuAG:Ce scintilla-
 115 tor [28] converted the x-rays to visible light, which was recorded by a Photron
 116 SA-Z high-speed camera at 150 kHz frame rate and 566 ns exposure time, fit-
 117 ted with a 10× long-distance microscope. The propagation distance from
 118 the experiment to the scintillator was approximately 600 mm. The spatial
 119 resolution achieved with this system was 1.95 µm per pixel.

Table 2: Phase-contrast imaging experiments test plan

Parameter	Test conditions		
Inj. press. [bar]	500	500	1500
Back press. [bar]	1	1;11	1
Control volt. [V]	135; 105; 100	120; 85	150; 132; 126
	95; 90; 80		118
Ramp rate [V/µs]	1	1	1
Injection shape	square	square	square

120 Note that there is not complete overlap between the ROI and phase-
 121 contrast imaging test plans. Since the time window available for both ex-
 122 periments was limited, only a select group of test conditions overlap between
 123 them, and the rest comprise particular tests of interest for each of the vari-
 124 ables being measured.

125 2.3. The direct-acting prototype injector

126 Figure 2 shows a sample image of the nozzle. The figure depicts how
 127 the needle tip and seat geometries are quite different from conventional sac
 128 designs, where the needle tip occupies less of the sac volume, and the seat
 129 angles are smaller [20]. During and injection event, the needle lifts towards
 130 the upper-left corner of the image, allowing fuel to flow through the needle
 131 seat and towards the outlet orifices.

132 The direct-acting mechanisms consist of a rocker or lever system that con-
 133 nects the needle to the piezo-stack linear actuator, similar to the mechanism
 134 detailed by Ferrari and Mittica [14]. The needle rests in zero-lift position

Figure 2: Raw image of the nozzle obtained from x-ray phase contrast imaging. Note that there is no lift in this figure and the needle is resting on the seat, which is at the upper left and right corners of the image. Fuel flows from the needle seat towards the outlet orifices as indicated by the blue arrows.

135 when the piezo-stack is not charged because injection pressure and a me-
 136 chanical spring push it against its seat.

137 Needle lift is controlled through the voltage applied to the piezo-stack
 138 linear actuator. Figure 3 shows an example of a set of various control sig-
 139 nals utilized to produce injections with different needle lifts. For all results
 140 presented in this paper, the ET was kept constant at 3.2 ms, which was pur-
 141 posely set to obtain long ROI and needle lift signals with both transient and
 142 steady state stages. Note that Figure 3 shows time values measured after
 143 the start of energizing (SOE), which is convenient for control signals. For
 144 measurements of spray characteristics, time values are often referenced to
 145 the start of injection (SOI), which is usually several hundred microseconds
 146 after the SOE.

147 Each control signal steady voltage level shown in Figure 3 is reached at a
 148 rising ramp rate of 1 V/ μ s. Even though the steady voltage level determines
 149 the steady needle lift behavior, transient needle displacements are strongly
 150 affected by the slope of the control signal. Control signal de-energizing ramp
 151 rates were kept constant at 1 V/ μ s through all experiments presented in this
 152 paper.

Figure 3: Injector control signals of different amplitude but equal energizing time of 3.2 ms and rising ramp rate of 1 V/ μ s.

3. Results and discussion

3.1. Rate of injection measurements

Figure 4 illustrates how partial needle lifts are able to throttle the instantaneous ROI down to very low rates, even though the pressure drop along the nozzle remains constant for all cases shown. In particular, these ROI signals correspond to the control signals presented in Figure 3. These results are similar to the observations of Payri et al. [15], but in this case, ROI throttling could be taken to a lower limit because direct control of the signal was possible, instead of utilizing a modified electronic control unit. In these high throttling situations, an initial overshoot of the steady injection rate is observed, even though all cases have control signals with equal ramp rates of 1 V/ μ s. It is possible to suppress this overshoot by tuning the control signal appropriately to the response frequency of the system, however, this was not the objective of these experiments as the overshoot shows interesting features in the transient response of the system. Moreover, it is important to note that ROI response is of second order, with moderate damping, which is related to (but not directly linked to) the expected second order response for a piezo-actuated damped system with inertia. On the other hand, all injection rates show a high frequency component, especially strong for the 135 V case.

Figure 4: Instantaneous ROI for different drive signal voltages at an injection pressure of 500 bar and a back pressure of 50 bar. The ramp rate of the control signal for all the different voltages is $1 \text{ V}/\mu\text{s}$.

172 These are pressure waves initiated when the needle suddenly stops lifting,
 173 which are artifacts of the fuel-filled injection discharge tube and are not to
 174 be mistaken for ROI fluctuations actually caused by needle vibration.

175 The injection pressure, which pushes to close the needle, strongly affects
 176 the span of effective throttling at higher injection pressures, as Figure 5
 177 illustrates. In this case, the 132 V ROI signal features a slower ramp when
 178 compared to the full lift (150 V) case, even though both cases have control
 179 signals with equal ramp rates of $1 \text{ V}/\mu\text{s}$. Also, it is important to point out
 180 that steady signal voltages between 131 V to 127 V produced very unsteady
 181 behaviors, where each single injection could produce signals that would fall
 182 between the 132 V and 126 V signals. This is believed to occur because
 183 deformations in the rocker mechanism—which counteracts the force produced
 184 by the injection pressure—widen the pivot point and reduce the mechanical
 185 advantage [14], deteriorating the rocker pivoting action. Therefore, at high
 186 injection pressures, more energy is necessary to overcome the increased force
 187 imparted by the higher pressure and the distorted pivot. Control signals
 188 with ramps of $1 \text{ V}/\mu\text{s}$ and steady signal voltages below 126 V did not give the
 189 piezo-stack enough energy to keep the needle lifted after the initial overshoot,
 190 which made the injections behave similar to pilot injections of very short

Figure 5: Instantaneous ROI for different drive signal voltages at an injection pressure of 1500 bar and a back pressure of 50 bar. The ramp rate of the control signal for all the different voltages is $1 \text{ V}/\mu\text{s}$.

191 effective ET.

192 A faster ramp in the control signal would energize the piezo-stack actuator
 193 more rapidly, which can help overcome the force produced by the injection
 194 pressure at the beginning of the injection event. Figure 6 illustrates how
 195 changing the ramp rate from $1 \text{ V}/\mu\text{s}$ to $2 \text{ V}/\mu\text{s}$ aids lifting the needle in high
 196 injection pressure scenarios. This enables the possibility of applying control
 197 signals with lower steady voltages, enhancing the ROI throttling span at this
 198 injection pressure. As expected, for this faster ramp rate there is still a range
 199 of steady voltages that produce inconsistent injections. Finally, looking at the
 200 114 V signal, the high frequency vibration at the latter part of the injection
 201 event is a pressure wave oscillation because of the fuel-filled IRDCI, not to
 202 be mistaken for a real fluctuation in the ROI caused by needle lift behavior.

203 Taking the steady, time-averaged ROI value of each signal facilitates the
 204 analysis of the control signal steady voltage effects over the ROI. Figure 7
 205 illustrates the global effect of the control signal steady voltage over the ROI
 206 and thus, the discharge coefficient. For injection pressures of 500 bar the
 207 wide span of steady ROIs possible is evident. As expected, the span width
 208 decreases as injection pressure increases. Also as depicted by Figures 5 and
 209 6, the span of throttling ability can be stretched by properly preparing the

Figure 6: Instantaneous ROI for different drive signal voltages at an injection pressure of 1500 bar and a back pressure of 50 bar. The ramp rate of the control signal for all the different voltages is $2 \text{ V}/\mu\text{s}$.

control signal (in this study, just the rising ramp rate effect is presented). The discharge coefficient of the complete nozzle (Figure 7-bottom) also shows how the needle lift is able to throttle the ROI, lowering the discharge coefficients from 0.81 to as low as 0.11. Note that discharge coefficients converge to a maximum value as full lift is reached. Finally, it is important to point out that the effect of the voltage over the ROI is not linear.

The direct-acting feature of the injector enables control not only of partial needle lift but also of ROI profiling [17]. In addition to the reference case—a full lift ‘square’ shaped injection at a rail pressure of 500 bar and a back pressure of 50 bar—two ‘boot’ shaped profiles were tested for comparison. The ‘boot’ profile is produced by introducing a step in the control signal, as depicted in Figure 8. Note that even though the ‘square’ shaped injection is produced by a control signal with a higher steady voltage in the first stage of the injection event, the ROI of the ‘boot2’ shaped injection overshoots past it, due to the faster control signal ramp rate. On the same lines, these rapid needle movements and stops produce the pressure waves that are observed as higher frequency fluctuations in the ROI signals.

Figure 7: Time-averaged steady ROI response to the control signal steady voltage at three different injection pressures and two control signal ramp rates. Note that injection pressures are indicated by different colors, while control signal ramp rates are indicated by different symbols. In this case, ambient pressure is constant at 50 bar.

Figure 8: Comparison of three different injection rate shapes at an injection pressure of 500 bar and a back pressure of 50 bar. The voltage levels indicated in the figure legend correspond to the voltages of the first step of the control signal—constant for the ‘square’ shaped injection. Note that after this first step, all voltages equalize at 120 V.

Figure 9: Sequence of x-ray images of needle lift for a single test at an injection pressure of 1500 bar, back pressure of 1 bar, with a control signal ramp rate of 1 V/ μ s and a steady voltage of 150 V.

3.2. Needle displacement

X-ray phase-contrast images were used for time-resolved tracking of needle displacement. The tracking algorithm consists of a simple 2D cross-correlation routine that evaluates the cross-correlation between an interrogation sector of the first images (before any needle displacement) to the subsequent images [20–22]. Figure 9 is a typical sequence of raw images that permit observation of needle displacement.

As shown in Figure 10, needle motion in the seat region was also imaged for particular test conditions. Note the angle between the needle and seat surfaces, which promotes a positive seal when the needle is fully closed. These images were obtained at the reference, full lift condition: an injection pressure of 500 bar, control signal ramp rate of 1 V/ μ s and steady voltage level of 120 V.

Due to the limited time available for measurements, only a select group of test conditions could be imaged. Thus, the experiments focused on measurements that could enhance the current understanding of the link between needle lift and ROI. Figure 11 depicts needle lifts measured at the different drive voltage levels. This figure explains the results observed for the ROI in Figure 4 at comparable test conditions: the injector is able to successfully and consistently throttle the ROI by partially lifting the needle. Note that the overshoots in the transients of the ROI curves in Figure 4 are also present in the needle lifts shown in Figure 11, as is the second order response, which again underscores the direct link between instantaneous needle lift and ROI. Needle lift measurements at higher injection pressure, illustrated in Figure

Figure 10: Sequence of x-ray images of the needle seat region. The test was performed at an injection pressure of 500 bar and a back pressure of 1 bar, with a control signal ramp rate of 1 V/ μs and a steady voltage level of 120 V. Fuel flows from top to bottom in these images.

12, also correlate well to the ROI observations of Figure 5. Note the considerably slower lift velocity for the 132 V signal, which clearly explains the slower slope in the mass flow rate previously observed for the same voltage case.

The effect of small back pressure differences was evaluated by comparing two back pressure cases at the two limits of needle lift. Figure 13 illustrates the comparison, showing that 10 bar of back pressure difference has no significant effect on the needle lift, confirming that the rest of the lift measurements would represent the real lifts during the ROI experiments performed at a back pressure of 11 bar. This was important to assess, especially for the low lift critical cases where a further increase in back pressure could impact the lift.

As previously done with the ROI, taking time-averaged values in the steady parts of the signals allows for easier observation of the link between steady needle lift and control signal voltage. Figure 14 illustrates that, unlike the case of ROIs, the relationship between the steady needle lift and the control signal voltage is quite linear. Note that in some cases, several measurements are shown at the same control signal voltage level, because the plot includes back pressure variations. The two outliers at injection pressures of 1500 bar that do not follow the linear trend correspond to those cases where the needle is not lifted properly due to deformations in the rocker mechanism, which was also seen in the ROI results. Payri et al. [15] reached similar conclusions through numerical analysis of the flow inside the nozzle, estimating the necessary needle lifts to produce the mass flow rates measured at each

Figure 11: Instantaneous needle lift for different drive signal voltages at an injection pressure of 500 bar and a back pressure of 1 bar. The ramp rate of the control signal for all the different voltages is $1 \text{ V}/\mu\text{s}$.

Figure 12: Instantaneous needle lift for different drive signal voltages at an injection pressure of 1500 bar and a back pressure of 1 bar. The ramp rate of the control signal for all the different voltages is $1 \text{ V}/\mu\text{s}$.

Figure 13: Evaluation of the effect of small increase in back pressure over the instantaneous needle lift. All tests were performed at an injection pressure of 500 bar. The ramp rate of the control signal for all cases is $1 \text{ V}/\mu\text{s}$.

274 piezo charge. The results presented here confirm and quantify the estimates
 275 of Payri et al. [15].

276 3.3. Instantaneous relationship between the rate of injection and needle lift

277 In this section the instantaneous relationship between the rate of injection
 278 and needle lift is evaluated. Note that the correlation between these
 279 variables is done for the repetition-average time-resolved responses of each
 280 variable, where the ROI experiments comprise a total of 50 injections while
 281 the needle lift experiments comprise 21 injections. This difference, however,
 282 is not expected to affect the results presented since shot-to-shot dispersion of
 283 either measurement is remarkably low, approximately 3% for lift measurements
 284 and 4% for ROI measurements.

285 Note that only the ROIs measured at a back pressure of 11 bar are con-
 286 sidered, to guarantee that the needle lifts measured are relevant to the corre-
 287 sponding ROI at similar test conditions. Unfortunately, it was not possible
 288 to perform the same number of ROI experiments at a back pressure of 11 bar
 289 as were performed for 50 bar. Therefore, this section correlates only the test
 290 conditions that were available in both ROI and needle lift measurements.
 291 Note also that ROIs were sampled at 100 kHz while x-ray phase contrast
 292 images were acquired at 150 kHz. In order to make it possible to establish
 293 an instantaneous link between the two responses, the needle lift signals were

Figure 14: Time-averaged steady needle lift response to the control signal steady voltage at the two injection pressures tested.

down-sampled to the time domain of the ROI signals.

Figure 15 illustrates the ROI as a function of instantaneous needle lifts. Injection pressures are separated into two sub-figures for clarity. The “clouds” of points represent steady state ROI and lift conditions (including points before and after the injection event, which comprise the cloud near the origin), while the transients are represented by the points going from zero up to their corresponding steady state cloud. Note that the complete injection event goes anti-clockwise in this figure, as indicated by the light-gray arrows. Therefore, for each voltage, the injection event starts at the origin, travels through the bottom-right corner of the plot up to the corresponding steady state lift-ROI combination, and finally returns to zero through the top-left corner of the plot.

The steady state shows an asymptotic behavior, where increasing needle lift after a certain point (the “full lift” definition) has no effect on the steady ROI. As observed in the ROI results, the “full lift” height depends on the injection pressure: at a rail pressure of 500 bar, the needle lift ceases to have an effect over the ROI near 50 μm, while at 1500 bar this condition is reached near 70 μm. For a given injection pressure, the needle ceases to affect the ROI once lifted past this “full lift” point, from where the orifices take over fuel flow control. Note that overshoots of both needle lift and ROI are observed in the plot, especially for low-lift scenarios where the overshoots were largest. The steady state trends found in this study are similar to those estimated

Figure 15: Instantaneous relationship between the ROI and needle lift. The light-gray arrows indicate the time evolution of the complete injection event, which goes anti-clockwise, from zero ROI and lift, to the steady state clouds of points corresponding to each test condition, and back.

316 by Payri et al. [15], but to the authors' knowledge this is the first time this
317 result is presented purely from experiments, and also the first time that the
318 instantaneous link between needle lift and ROI has been analyzed.

319 Figure 15 provides interesting information regarding transients. Note that
320 the needle opening initially causes a negative ROI—usually seen in instan-
321 taneous ROI measurements, as Figures 4, 5, and 6 show—due to the volume
322 suddenly displaced in the nozzle sac. The opposite can be observed during
323 the needle closing, where the sac volume is rapidly decreasing and therefore,
324 fuel is pumped out even though the needle seat is being ever more restricted.
325 This is the effect of rapid needle velocities and also occurs because the injec-
326 tion rate meter is filled with fuel. Thus, if the needle lift velocity is slower,
327 the volume displacement effect should be decreased. At a rail pressure of
328 1500 bar, a control signal voltage of 132 V produced a slower needle lift ve-
329 locity, as shown in Figure 12. Slower needle lift velocities are evidenced in
330 Figure 15-(b) as points going from zero to the steady state condition through
331 the center of the plot, almost following the expected trend of steady state
332 ROI vs. needle lift. This suggests that producing injections with even slower
333 needle lift velocities—which was possible but not thought to be of interest
334 at the time of test planning—would render the full span of points for the
335 link between quasi-steady needle lifts and ROIs. Note that these observa-
336 tions in the transient stages imply that there will always be a hydraulic delay
337 in the steady ROI with respect to the reference energizing signal, even for
338 direct-acting injectors.

339 4. Conclusions

340 In this study, experiments were carried out to measure both instantaneous
341 rate of injection and needle lift for a prototype direct-acting injector capable
342 of consistently producing injections with partial needle lifts. A series of test
343 conditions and configurations were evaluated and their effects analyzed, and
344 from these analyses the following conclusions can be drawn:

- 345 • The direct-acting injector is able to consistently throttle rates of injec-
346 tion by partially lifting the needle. The spectrum of possible throttling
347 levels depended strongly on injection pressure—higher rail pressures
348 reduce the throttling capabilities considerably. Pressure-induced dis-
349 tortions of the injector rocker mechanism appeared to limit needle lift
350 control at high injection pressures. Two control signal rising ramp

351 rates were evaluated, showing that they can indeed help in these low-
352 lift limit situations. In general, partial needle lifts were able to decrease
353 the discharge coefficient from approximately 0.81 to as low as 0.11.

- 354 • The direct-acting feature of the injector can be utilized to consistently
355 shape the injection rate signal as desired. Two ‘boot’ shaped rate
356 of injection profiles were presented. The ‘boot’ shaped ROI signals
357 were similar in consistency when compared to the conventional ‘square’
358 shaped ROI signals.
- 359 • The needle lift response—and with it, the rate of injection response—
360 was found to be of second order. The control signals were purposely
361 maintained simple and square shaped to generate this behavior that,
362 for low lift situations, produced a needle lift and thus, rate of injection
363 overshoots in the initial stage of the injection event.
- 364 • The relationship between steady rate of injection and control signal
365 voltage was found to be non-linear, while the relationship between
366 steady needle lift and control signal voltage was found to be linear
367 (except when rocker deformation interfered with needle lift).
- 368 • The rate of injection is affected by needle lift only up to a certain point.
369 This point is dependent on injection pressure: at an injection pressure
370 of 500 bar, the needle had to be lifted to approximately 50 μm for it to
371 cease throttling the rate of injection, while at 1500 bar it needed to be
372 lifted to approximately 70 μm for the same purpose.
- 373 • Fast needle movements displace volume in the sac, which alters the
374 instantaneous rate of injection. This implies that there will always
375 be a hydraulic delay between the control signal stabilization and the
376 rate of injection, even for direct-acting injectors. The opening effect is
377 expected to be reduced when injecting into a gas ambient.

378 Finally, the authors believe that it would be illuminating to study these
379 results through multi-phase numerical models, and with them, to further
380 evaluate the effects of needle lift and needle velocity over the instantaneous
381 rate of injection and cavitation regimes in the needle seat. This may provide
382 detailed insights into the physical processes that drive these observations,
383 and potentially, to the effects that these features could have on combustion
384 performance.

385 Acknowledgements

386 This research was performed at the 32-ID beam line of the APS at Ar-
387 gonne National Laboratory. Use of the APS is supported by the U.S. De-
388 partment of Energy (DOE) under Contract No. DE-AC02-06CH11357. The
389 fuel spray research is sponsored by the DOE Vehicle Technologies Program.
390 The authors wish to thank Gurpreet Singh and Leo Broten for their sup-
391 port of this work. Raul Payri was funded by a Fulbright visiting scholar
392 grant in collaboration with the Ministry of Education, Culture and Sports
393 of Spain (reference PRX14/00331) while performing this work. J.P. Viera
394 was funded by the Spanish MINECO grant EEBB-I-15-0976 under project
395 TRA2012-36932.

396 The submitted manuscript has been created by UChicago Argonne, LLC,
397 Operator of Argonne National Laboratory (Argonne). Argonne, a U.S. De-
398 partment of Energy Office of Science laboratory, is operated under Contract
399 No. DE-AC02-06CH11357. The U.S. Government retains for itself, and
400 others acting on its behalf, a paid-up nonexclusive, irrevocable worldwide li-
401 cense in said article to reproduce, prepare derivative works, distribute copies
402 to the public, and perform publicly and display publicly, by or on behalf of
403 the Government.

404 References

- 405 [1] S. Soid, Z. Zainal, Spray and combustion characterization for in-
406 ternal combustion engines using optical measuring techniques - A
407 review, Energy 36 (2) (2011) 724 – 741, ISSN 0360-5442, doi:
408 <http://dx.doi.org/10.1016/j.energy.2010.11.022>.
- 409 [2] F. Wang, Z. He, J. Liu, Q. Wang, Diesel nozzle geometries on spray
410 characteristics with a spray model coupled with nozzle cavitating flow,
411 International Journal of Automotive Technology 16 (4) (2015) 539 – 549,
412 ISSN 1229-9138, doi:10.1007/s12239-015-0055-9.
- 413 [3] R. Payri, F. J. Salvador, J. Gimeno, J. de la Morena, Influence of injector
414 technology on injection and combustion development - Part 1: Hydraulic
415 characterization, Applied Energy 88 (4) (2011) 1068 – 1074, ISSN 0306-
416 2619, doi:<http://dx.doi.org/10.1016/j.apenergy.2010.10.012>.
- 417 [4] R. Payri, F. J. Salvador, J. Gimeno, J. de la Morena, Influence of in-
418 jector technology on injection and combustion development - Part 2:

- 419 Combustion analysis, *Applied Energy* 88 (4) (2011) 1130 – 1139, ISSN
420 0306-2619, doi:<http://dx.doi.org/10.1016/j.apenergy.2010.10.004>.
- 421 [5] R. Mobasheri, Z. Peng, S. M. Mirsalim, Analysis the effect of advanced
422 injection strategies on engine performance and pollutant emissions in
423 a heavy duty DI-diesel engine by CFD modeling, *International Journal*
424 *of Heat and Fluid Flow* 33 (1) (2012) 59 – 69, ISSN 0142-727X, doi:
425 <http://dx.doi.org/10.1016/j.ijheatfluidflow.2011.10.004>.
- 426 [6] J. Benajes, S. Molina, A. García, J. Monsalve-Serrano, Effects
427 of direct injection timing and blending ratio on RCCI com-
428 bustion with different low reactivity fuels, *Energy Conversion*
429 *and Management* 99 (2015) 193 – 209, ISSN 0196-8904, doi:
430 <http://dx.doi.org/10.1016/j.enconman.2015.04.046>.
- 431 [7] P. Das, P. Subbarao, J. Subrahmanyam, Effect of main injection tim-
432 ing for controlling the combustion phasing of a homogeneous charge
433 compression ignition engine using a new dual injection strategy, *En-
434 ergy Conversion and Management* 95 (2015) 248 – 258, ISSN 0196-8904,
435 doi:<http://dx.doi.org/10.1016/j.enconman.2015.02.018>.
- 436 [8] D. Schöppe, S. Zülch, M. Hardy, D. Geurts, R. W. Jorach, N. Baker,
437 Delphi Common Rail system with direct acting injector, *MTZ World-
438 wide* 69 (10) (2008) 32 – 38, doi:10.1007/BF03226918.
- 439 [9] G. Dober, S. Tullis, G. Greeves, N. Milovanovic, M. Hardy, S. Zuelch,
440 The impact of injection strategies on emissions reduction and power
441 output of future diesel engines, SAE Technical Paper 2008-01-0941, doi:
442 10.4271/2008-01-0941.
- 443 [10] F. Atzler, O. Kastner, R. Rotondi, A. Weigand, Multiple injection and
444 rate shaping Part 1: Emissions reduction in passenger car diesel en-
445 gines, SAE Technical Paper 2009-24-0004, doi:10.4271/2009-24-0004,
446 URL <http://dx.doi.org/10.4271/2009-24-0004>.
- 447 [11] G. Dober, N. Guerrassi, K. Karimi, Mixture preparation and combus-
448 tion analysis, a key activity for future trends in diesel fuel injection
449 equipment, in: SIA, Rouen, France, 2012.

- 450 [12] O. Chiavola, F. Palmieri, Modeling needle motion influence on nozzle
451 flow in high pressure Injection System, SAE Technical Paper 2007-01-
452 0250, doi:10.4271/2007-01-0250.
- 453 [13] S. Som, S. K. Aggarwal, E. M. El-Hannouny, D. E. Longman, Inves-
454 tigation of nozzle flow and cavitation characteristics in a diesel injec-
455 tor., Journal of Engineering for Gas Turbines and Power 132 (4) (2010)
456 042802, doi:doi:10.1115/1.3203146.
- 457 [14] A. Ferrari, A. Mittica, FEM modeling of the piezoelectric
458 driving system in the design of direct-acting diesel injectors,
459 Applied Energy 99 (2012) 471 – 483, ISSN 0306-2619, doi:
460 <http://dx.doi.org/10.1016/j.apenergy.2012.05.048>.
- 461 [15] R. Payri, J. Gimeno, O. Venegas, A. H. Plazas, Experimental and com-
462 putational study of the influence of partial needle lift on nozzle flow in
463 diesel fuel injectors, Atomization and Sprays 22 (8) (2012) 687 – 714,
464 ISSN 1044-5110, doi:10.1615/AtomizSpr.2012005810.
- 465 [16] R. Payri, J. Gimeno, M. Bardi, A. H. Plazas, Study liquid length
466 penetration results obtained with a direct acting piezo electric in-
467 jector, Applied Energy 106 (2013) 152 – 162, ISSN 0306-2619, doi:
468 <http://dx.doi.org/10.1016/j.apenergy.2013.01.027>.
- 469 [17] R. Payri, J. Gimeno, J. P. Viera, A. H. Plazas, Needle lift profile influ-
470 ence on the vapor phase penetration for a prototype diesel direct acting
471 piezoelectric injector, Fuel 113 (2013) 257 – 265, ISSN 0016-2361, doi:
472 <http://dx.doi.org/10.1016/j.fuel.2013.05.057>.
- 473 [18] J. M. Desantes, F. J. Salvador, M. Carreres, J. Martínez-López, Large-
474 eddy simulation analysis of the influence of the needle lift on the cav-
475 itation in diesel injector nozzles, Proceedings of the Institution of Me-
476 chanical Engineers, Part D: Journal of Automobile Engineering 229 (4)
477 (2015) 407–423.
- 478 [19] W. Lee, K. Fezzaa, J. Wang, Metrology of steel micronozzles using x-
479 ray propagation-based phase-enhanced microimaging, Applied Physics
480 Letters 87 (8) (2005) 084105.
- 481 [20] A. L. Kastengren, F. Z. Tilocco, C. Powell, J. Manin, L. M. Pickett,
482 R. Payri, T. Bazyn, Engine Combustion Network (ECN): measurements

- 483 of nozzle geometry and hydraulic behavior, *Atomization and Sprays*
484 22 (12) (2012) 1011–1052.
- 485 [21] A. Kastengren, C. Powell, F. Tilocco, Z. Liu, S. Moon, X. Zhang, J. Gao,
486 Correlation of split-injection needle lift and spray structure, *SAE Tech-*
487 *nical Paper* 2011-01-0383.
- 488 [22] C. Powell, A. L. Kastengren, Z. Liu, K. Fezzaa, The effects of diesel
489 injector needle motion on spray structure, *Journal of Engineering for*
490 *Gas Turbines and Power* 133 (1) (2011) 012802.
- 491 [23] D. J. Duke, A. Swantek, Z. Tilocco, A. Kastengren, K. Fezzaa,
492 K. Neroorkar, M. Moulai, C. Powell, D. Schmidt, X-ray imaging of cav-
493 itation in diesel injectors, *SAE Int. J. Engines* 7 (2) (2014) 1003–1016,
494 doi:10.4271/2014-01-1404.
- 495 [24] W. Bosch, The fuel rate indicator: a new measuring instrument for dis-
496 play of the characteristics of individual injection, *SAE Technical Paper*
497 660749, doi:10.4271/660749.
- 498 [25] R. Payri, F. J. Salvador, J. Gimeno, G. Bracho, A new methodology for
499 correcting the signal cumulative phenomenon on injection rate measure-
500 ments, *Experimental Techniques* 32 (1) (2008) 46–49, ISSN 1747-1567,
501 doi:10.1111/j.1747-1567.2007.00188.x.
- 502 [26] R. Payri, J. M. García, F. J. Salvador, J. Gimeno, Using spray mo-
503 mentum flux measurements to understand the influence of diesel nozzle
504 geometry on spray characteristics, *Fuel* 84 (5) (2005) 551 – 561, ISSN
505 0016-2361, doi:http://dx.doi.org/10.1016/j.fuel.2004.10.009.
- 506 [27] Q. Shen, W. Lee, K. Fezzaa, Y. S. Chu, F. De Carlo, P. Jemian,
507 J. Ilavsky, M. Erdmann, G. G. Long, Dedicated full-field X-ray imaging
508 beamline at Advanced Photon Source, *Nuclear instruments and methods*
509 *in physics research section A* 582 (1) (2007) 77–79.
- 510 [28] J. A. Mares, A. Beitlerova, M. Nikl, N. Solovieva, C. D’Ambrosio,
511 K. Blazek, P. Maly, K. Nejezchleb, F. de Notaristefani, Scintilla-
512 tion response of Ce-doped or intrinsic scintillating crystals in the
513 range up to, *Radiation Measurements* 38 (4-6) (2004) 353–357, doi:
514 10.1016/j.radmeas.2004.04.004.