Convective drying of fruit: role and impact of moisture transport properties in modelling

Thijs Defraeye ^{a,b,*}, Pieter Verboven ^c

^a *Multiscale Studies in Building Physics, Empa, Überlandstrasse 129, 8600 Dübendorf, Switzerland*

^b *Chair of Building Physics, ETH Zurich, Stefano-Franscini-Platz 5, 8093 Zürich, Switzerland*

^c *MeBioS, Department of Biosystems, KU Leuven – University of Leuven, Willem de Croylaan 42, 3001 Heverlee, Belgium*

* Corresponding author

- E-mail thijs.defraeye@empa.ch
- Tel. +41 (0)58 765 4790
- Fax. +41 44 633 10 41

Keywords: apple; permeability; diffusivity; convective heat transfer coefficient; COMSOL; evaporation

ABSTRACT

Continuum modelling of fruit dehydration relies on accurate predictions of moisture permeability or diffusivity. These properties are often taken from literature instead of being explicitly determined for the species, cultivar or drying application of interest. As a large variability on these moisture transport properties is reported, this study targets their role and impact on simulations of the fruit drying process. Using a validated hygrothermal model, significant differences in drying rate and internal moisture content distribution are quantified for a realistic range of tissue permeabilities. Particular differences in drying kinetics are identified between constant permeability and diffusivity formulations, but in general both exhibited roughly similar drying behavior. Previous contradictory findings on the impact of the air speed, thus convective transfer coefficients (CTCs), on the drying process are shown to be most likely related to the magnitude of the tissue permeability. A lower sensitivity of the drying process to the CTCs is found for low permeabilities. A new parameter is introduced to facilitate quantitative comparison of multiple drying processes, namely by characterizing each drying curve with a single characteristic value. This modelling study provides a better quantitative insight in the fruit drying behavior and its link to the moisture transport properties of the tissue.

1. INTRODUCTION

Dehydration is a key technology to preserve fresh fruits in rural areas, and thereby reduce food waste. Fruit drying is also increasingly performed on an industrial scale to produce healthy snacks. Understanding the fruit dehydration kinetics is critical for optimizing such drying processes in order to obtain prime quality of the dried fruit, to enhance shelf life and to guarantee food safety. At the same time, the energy consumption of the process should be minimized.

Next to experimental research, numerical simulations, based on continuum modelling, are commonplace to evaluate various types of drying processes (Datta, 2008; Defraeye, 2014; Nilnont et al., 2012; Tsotsas and Mujumdar, 2007). A particular advantage is that all process variables within the product and at its interface with the environment are known at very high spatial and temporal resolution, including temperatures and moisture content and the associated heat and mass flows. This allows to identify their internal distribution and gradients, including at locations or scales which are experimentally difficult to target. Also, sensitivity to small changes, for example of drying conditions, can be detected much more precise, and no problems of repeatability arise. Such simulation-based information leads to a deeper physical insight in the drying process, hence complementing experimental research.

The critical point with such hygrothermal continuum models is that their accuracy is strongly dependent on the material properties that are used in the macroscopic conservation equations to calculate heat and mass transport processes. These effective transport properties, such as moisture diffusivity and thermal conductivity, actually lump all microscopic transport phenomena into a macroscopic property. They are usually determined experimentally, in some cases as a function of the moisture content or temperature.

For drying, the most relevant moisture transport property is the moisture permeability (K_m [s], also called hydraulic conductivity) or moisture diffusivity (D_m [$\text{m}^2 \text{s}^{-1}$], also called diffusion coefficient), next to the sorption isotherm. Both are related via the moisture capacity C_m ($[\text{s}^2 \text{m}^{-2}]$, $K_m = D_m \times C_m$), which can be determined from the sorption isotherm. For a soft, deformable cellular material such as fresh fruit (Figure 1), the moisture transport pathways are very complex. Its properties are often difficult to determine and require time-consuming measurements with specialized equipment and expertise (Datta, 2007a; Gulati and Datta, 2013; McMinn and Magee, 1999). The moisture diffusivity or permeability are determined, amongst others, in following ways: (1) using a measured moisture loss curve in combination with an analytical, thin-layer solution of this drying curve, based on Fick's law (Kaya et al., 2007; Vega-Gálvez et al., 2012; Velić et al., 2004; Zlatanović et al., 2013); (2) determining the moisture content profiles over a sample, destructively (Nguyen et al., 2006; Veraverbeke et al., 2003) or by non-destructively imaging (Léonard et al., 2005), and combining this information with inverse modelling using Fick's law; (3) by numerical modelling of water transport through the cellular tissue at the microscale level (Fanta et al., 2013). The moisture diffusivity has been found to vary with fruit tissue temperature and moisture content. The obtained diffusivities were also found to vary with drying conditions, such as air speed and temperature. Even for a single fruit species, such as apple, a large variability in the magnitude of the moisture

diffusivity is found within a single study, e.g. due to other drying conditions, and between different studies (Figure 2).

Continuum models rely on these, mostly empirically-determined, moisture transport properties (K_m or D_m), which are a cornerstone for successful modelling. However, when a modelling study is undertaken, these values are often not explicitly determined for the corresponding cultivar or drying conditions of interest, but instead taken from literature. This is surprising given the large variability that is found on the magnitude of these properties (Figure 2). Although the chosen value of the parameter will affect the predicted drying kinetics, the impact of this choice is rarely acknowledged and looked at in detail. In addition, the type of transport parameter (K_m or D_m) that is determined empirically with any of the above methods and subsequently used in the model will also affect the predicted moisture transport. The reason is that both are related via the capacity C_m , which is a strong nonlinear function of the moisture content. In modelling, often a constant value of K_m or D_m is implemented. A constant diffusivity will thus lead to a varying K_m in space (sample) and time during dehydration, and vice versa. The impact of such property formulation has not been investigated in detail for fruit drying to our best knowledge.

The aim of this paper is to identify the impact of both magnitude and formulation of the moisture transport properties (K_m or D_m), on the simulated drying process of apple fruit tissue. The impact of other model input parameters (convective transfer coefficients and environmental conditions) is also explored. To this end, a validated hygrothermal continuum model is developed and a parametric analysis is performed. This study provides a better quantitative insight in how the drying process kinetics and the moisture transport in apple fruit are influenced by the input parameters of the hygrothermal model. Instead of taking the moisture transport property as a known input, this study evaluates the dependency of its chosen value. The results give drying technologists a clearer idea on what to expect in terms of drying behavior, for specific (measured) model input parameters. This study considers apple fruit, as it is a frequently applied material to study fruit drying with a significant economic relevance. Due to the large range of transport properties that is evaluated, the results are also relevant for other food materials.

2. MATERIALS AND METHODS

2.1 Continuum model for fruit tissue

A continuum model is developed to calculate heat and moisture transport in fruit tissue during drying. The model is based on the porous medium model presented in (Defraeye et al., 2012b), but some model adjustments are made to account for the specific case of drying of apple fruit. The main characteristics are highlighted below. The main model assumptions are:

- Evaporation is assumed to occur only at the surface
- Shrinking and swelling of the tissue are not modelled
- Moisture transport is driven by water potential
- Osmotically-driven water transport is not explicitly modelled
- Thermal equilibrium between all phases exists

Conservation equations

The following conservation equations for moisture and energy are solved to the dependent variables temperature T [K] and water potential ψ [Pa]:

$$\frac{\partial w_m}{\partial \psi} \frac{\partial \psi}{\partial t} + \nabla \cdot (-K_m \nabla \psi) = 0 \quad (1)$$

$$h_l \frac{\partial w_m}{\partial \psi} \frac{\partial \psi}{\partial t} + (c_{p,s} w_s + c_{p,l} w_m) \frac{\partial T}{\partial t} + \nabla \cdot (-h_l K_m \nabla \psi) + \nabla \cdot (-\lambda_{PM} \nabla T) = 0 \quad (2)$$

where w_s and w_m are the dry matter density (solid) and moisture content of the tissue, respectively [kg m^{-3}]. K_m is the moisture permeability of the tissue [s], h_l is the enthalpy of liquid water [J kg^{-1}], λ_{PM} is the thermal conductivity of the tissue (porous medium) [$\text{W m}^{-1} \text{K}^{-1}$], $c_{p,s}$ and $c_{p,l}$ are the specific heat capacities of dry matter and liquid water [$\text{J kg}^{-1} \text{K}^{-1}$], respectively. These material properties are given in Table 1.

Note that moisture transport is not split up in vapor and liquid water transport, leading to only one conservation equation, as done in several other studies (Aregawi et al., 2013b; Esfahani et al., 2014; Tzempelikos et al., 2015). Evaporation is only assumed to occur at the surface, implying that moisture transport occurs via the liquid phase and not by water vapor. This assumption is less accurate during the final stages of drying, so at very low moisture contents. Although some advanced models do account for both phases (Gulati and Datta, 2015; Halder and Datta, 2012; Kurnia et al., 2013), the diffusivity for liquid transport is difficult to determine separately for a complex soft material as fruit tissue. Furthermore, for modelling the rate of evaporation, also empirical rate constants are required if vapor and liquid phases are assumed to be not in equilibrium. As such, the accuracy of such more physically correct models still relies on the used parameters.

Note that in the present study, a constant K_m (or a constant D_m) is implemented (Table 1), as done in several other studies. The K_m for the base case was taken from (Aregawi et al., 2013a), at high moisture content. Also the same sorption isotherm was used.

In the energy conservation equation, the first and the third term on the left-hand side originate from a derivation of the general conservation equation to the dependent variables T and ψ (Defraeye et al., 2012b). The impact of the first and third term is actually very low for the present study due to the low drying rates. The difference of simulations with and without these terms could almost not be noticed in the drying curves. These terms are not accounted for in many studies, and the same holds for the moisture content dependency of the thermal capacity in the second term. In many studies, a very simple, more well-known, energy conservation equation is applied (Datta, 2007b), which is not a function of moisture transport:

$$\rho_{PM} c_{p,PM} \frac{\partial T}{\partial t} + \nabla \cdot (-\lambda_{PM} \nabla T) = 0 \quad (3)$$

where ρ_{PM} and $c_{p,PM}$ are the effective density and the specific heat capacity of the tissue, respectively. In the present study however, Eq.(2) was implemented. Validation of the porous medium model was already done previously for other materials, but is performed specifically for fruit drying in section 3.1.

In order to implement a constant diffusivity, following definition was used for D_m :

$$K_m = D_m C_m = D_m \frac{\partial w_m}{\partial \psi} \quad (4)$$

When this is substituted in Eq.(1), we get the implementation that was used for a constant diffusivity in this study:

$$\frac{\partial w_m}{\partial \psi} \frac{\partial \psi}{\partial t} + \nabla \cdot \left(-D_m \frac{\partial w_m}{\partial \psi} \nabla \psi \right) = 0 \quad (5)$$

Note that this equation can also be rewritten to a general diffusivity formulation (Datta, 2007b):

$$\frac{\partial w_m}{\partial t} + \nabla \cdot (-D_m \nabla w_m) = 0 \quad (6)$$

Boundary conditions

The boundary conditions at the air-tissue interface (continuity of fluxes) are specified as:

$$\mathbf{n} \cdot (-K_m \nabla \psi) = g_m = h_{c,m} (p_{v,w} - p_{v,ref}) \quad (7)$$

$$\mathbf{n} \cdot (-h_1 K_m \nabla \psi - \lambda_{PM} \nabla T) = g_T = (h_{c,T} (T_w - T_{ref}) - h_v g_m) \quad (8)$$

where g_m [$\text{kg m}^{-2} \text{s}^{-1}$] and g_T [$\text{J m}^{-2} \text{s}^{-1}$] are the mass and heat fluxes at the interface, $\mathbf{n}$ is the unit vector normal to the interface, $h_{c,m}$ is the convective mass transfer coefficient (CMTC [s m^{-1}]), $h_{c,T}$ is the convective heat transfer

coefficient (CHTC [$\text{W m}^{-2} \text{K}^{-1}$]), $p_{v,w}$ and $p_{v,ref}$ are the vapor pressures at the interface and of the ambient air [Pa], T_w and T_{ref} are the temperatures at the interface and of the ambient air [K], h_v and h_l are the enthalpies of water vapor and liquid water [J kg^{-1}].

For mass transfer, the boundary condition states that moisture loss from the tissue equals the convective vapor removal from the surface. For heat transfer, the boundary condition states that heat loss/gain from the tissue, due to conduction and liquid water removal, equals the convective (sensible) heat exchange with the environment and the heat removal due to the water vapor loss due to evaporation. In the present study, long-wave radiation exchange of the tissue with the environment via the surface was not modelled. Very little studies on convective fruit drying actually account for such radiation.

Constitutive equations

The enthalpies of water vapor and liquid water, h_v and h_l [J kg^{-1}], are:

$$h_l = c_{p,l} (T - T_{ref,0}) \quad (9)$$

$$h_v = c_{p,v} (T - T_{ref,0}) + L_v \quad (10)$$

where L_v is the heat of vaporization [J kg^{-1}], also called latent heat, which is the energy needed for the phase change from liquid to vapor. $T_{ref,0}$ is a reference temperature, taken equal to 273.15 K (0°C).

To determine the moisture capacity C_m , the sorption isotherm (w_m vs. water activity a_w) is required (see Table 1), as well as the relation of water activity to water potential ψ . The latter is given by:

$$\psi = \rho_l R_v T \ln(a_w) \quad (11)$$

The vapor pressures $p_{v,w}$ and $p_{v,ref}$ are determined based on the water activity at the interface ($a_{w,w}$) and the relative humidity of the ambient air (RH_{ref}), together with the corresponding temperatures, via the saturated vapor pressure ($p_{v,sat}$ [Pa]):

$$p_{v,w} = a_{w,w} p_{v,sat}(T_w) \quad (12)$$

$$p_{v,ref} = RH_{ref} p_{v,sat}(T_{ref}) \quad (13)$$

$$p_{v,sat}(T) = e^{\frac{65.8094}{T} - \frac{7066.27}{T^2} - 5.976 \ln T} \quad (14)$$

Analytical comparison

When evaluating drying processes by numerical modelling, it is always advised to verify if the model predictions are in the right range. To this end, a comparison with the conditions during the constant drying rate period (CDRP) could prove useful, as detailed below. This CDRP is found during the first stage of the drying process.

The CDRP is characterized by a high relative humidity (RH) at the surface ($\approx 100\%$), a constant drying rate and a constant material temperature, which is close to the wet bulb temperature (T_{wb}) if no radiative heat flows at the surface and no (conductive) heat flows from the interior of the porous material are present. In this case, the convective heat supply to the interface is quasi entirely used for the evaporation of water.

The drying rate during the constant drying rate period can be estimated analytically, namely by assuming a moist surface (RH $\approx 100\%$) which is at the wet bulb temperature. The wet bulb temperature can be determined from psychrometrics. From these conditions at the fruit surface and those of the ambient air, the moisture flux during the CDRP can be calculated as follows:

$$g_m = h_{c,m} (p_{v,w,CDRP} - p_{v,ref}) \quad (15)$$

$$p_{v,w,CDRP} = a_{w,ini} p_{v,sat}(T_{wb}) \quad (16)$$

where $a_{w,ini}$ is the initial water activity of the fresh tissue, which was 0.9896 in the present study, as derived from the initial moisture content and the sorption isotherm.

The CDRP drying rate is higher than for the subsequent decreasing drying rate period (DDRP), so it should be the maximal slope of the mass loss curve. The temperature during drying can be compared to the wet bulb temperature. The latter should be the lowest temperature which the material can attain, due to the high cooling rate due to evaporation.

2.2 Configuration and computational model

The configuration used to evaluate convective drying of fresh-cut apple tissue is a cubic piece (length $L_c = 20$ mm) suspended in the surrounding air. Such simple 3D geometries have often been applied for fruit drying and are sufficient for the purpose of this study, namely to evaluate the impact of several model parameters and drying conditions. The base case is detailed below, as well as the other variants that are simulated. Only one sample size was modelled, but note that the drying kinetics are strongly dependent on the size and shape. As such, a one-on-one comparison to previous drying studies is often not possible.

Base case

The computational model and the imposed boundary conditions are specified in Figure 3. Only one eighth of the fruit cube needs to be modelled due to symmetry. The porous material is apple fruit (cv. *Braeburn*). The relevant material properties and boundary/initial conditions used for modelling are specified in Table 1. The fruit is assumed to be initially (fresh-cut state) at a uniform moisture content $w_{m,ini}$ of 780 kg m^{-3} at a uniform temperature T_{ini} of 20°C . This moisture content leads to a dry matter moisture content X_{ini} of 6 ($= w_{m,ini}/w_s [\text{kg kg}_{dm}^{-1}]$).

The airflow around the cube is not modelled explicitly, but its impact on the drying process is accounted for by means of convective transfer coefficients (CTCs). The same CTC value is assumed on all sides of the cube. This is a simplified representation as in reality a spatial CTC variation between the sides of the cube exists for forced convection (Ateeque et al., 2014; Kaya et al., 2006). Within the scope of this study, including such a spatial variation is not necessary. The ambient air is kept at a constant temperature (T_{ref}) and relative humidity (RH_{ref}). The convective heat transfer coefficient was $10 \text{ W m}^{-2}\text{K}^{-1}$ for the base case, implying rather low convection rates. The CMTC is estimated from the CHTC using the heat and mass transfer analogy, similar as in (Defraeye et al., 2012b), leading to a CMTC/CHTC ratio (analogy factor) of 7.03×10^{-9} .

An appropriate grid is built for the porous material, based on a grid sensitivity analysis. The grid consists of 27000 hexahedral finite elements, namely 30 divisions on each side of the cube ($1/8^{\text{th}}$). A gradual refinement towards the air-tissue interface is applied to enhance numerical accuracy and stability as the largest gradients occur there at the start of the drying process.

Variants

In addition to the base case, other variants were simulated as well (Table 2).

A first type is related to the moisture permeability K_m and corresponding diffusivity D_m . In the base case, K_m was assumed constant. As K_m is related to the diffusivity, namely the ratio of K_m with the moisture capacity ($D_m = K_m/C_m$), a constant K_m will lead to a varying D_m with moisture content (and water potential). Vice versa, if a constant D_m would be assumed, this would lead to a variable K_m with moisture content in Eq.(1). This is illustrated in Figure 4 (black lines), where the diffusivity for a constant permeability (Figure 4 a-b, K_m from base case) is shown as a function of water potential and scaled moisture content. Also the permeability for a constant diffusivity is shown (Figure 4 c-d). For the latter, the constant diffusivity value was calculated as the average value of D_m for the base case Figure 4a, over the relevant moisture content range ($X = 0-6 \text{ [kg kg}_{\text{dm}}^{-1}]$), leading to $D_m = 2.47 \times 10^{-11} \text{ s}$ (red line in Figure 4a). The diffusivity formulation implies that the permeability in Eq.(1) is replaced by $D_m \times C_m$, leading to Eq.(5). For fresh fruit tissue, the water potential is typically in the range of a few MPa (Fanta et al., 2013). The effect of this formulation of moisture transport properties (K_m or D_m) on the drying process is investigated by evaluating both formulations, namely constant K_m Eq.(1) and constant D_m Eq.(5). Furthermore, due to the large spread found in these properties (Figure 2), a range of values for K_m and D_m is evaluated as well (Table 2), which are also represented in Figure 4 by the grey lines.

A second type of variant (Table 2) involves other drying conditions: (1) different airflow conditions (speed), so CHTC but also CMTC, as it is calculated from the CHTC by means of the analogy, for two different permeabilities; (2) a higher drying temperature.

2.3 Numerical simulations

The continuum model was implemented in COMSOL Multiphysics (version 5.0), which is a finite-element based solver. The partial differential equations interface (coefficient form) was used for this purpose, in which the aforementioned conservation equations were implemented. Transient simulations calculated a drying process of 100 hours, starting from the specified initial conditions. All simulations applied adaptive time stepping, as determined from a temporal sensitivity analysis. The tolerances for convergence and other solver settings were determined based on sensitivity analysis as well. A fully coupled solver was used to solve to the dependent variables ψ and T . The simulations (for a 100h drying period) took roughly 1.5 hours on a 12 core Intel Xeon processor (2 x 3.47 GHz) with 48GB RAM memory.

3. RESULTS

3.1 Validation

In this section, the porous medium model with the material properties of the base case is compared with experiments to identify its accuracy in predicting dehydration of fruit. A slightly different geometry is considered, namely a cylindrical apple sample (diameter 14 mm, height 14 mm), which is placed in a climatic chamber with forced airflow circulation ($CHTC = 15 \text{ W m}^{-2} \text{ K}^{-1}$, $T_{ref} = 23^\circ\text{C}$, $RH_{ref} = 40\%$). Other details of the validation experiment and simulations are described in the Supplementary material. Note that some boundary and initial conditions differed from the base case.

In Figure 5, a comparison of experiments and simulations is made. To this end, the mass loss (change in dry matter moisture content) and drying rate are shown versus time, as well as the core temperature. The drying rate equals the surface-averaged moisture flux at the surface. Note that most validation studies on fruit drying only compare mass loss, although other quantities such as drying rate (derivative of the drying curve) are more critical to predict correctly. To obtain the mass loss experimentally, gravimetical measurements by continuous monitoring (on 1 sample, red dots) and discrete measurements in time (on 5 samples, green dots) are shown. As described in section 2.1, also the analytical prediction of the CDRP drying rate (and corresponding mass loss), as well as the wet bulb temperature are shown, as simple indicators for the predicted drying kinetics.

Next to evaluating a constant permeability, simulation results with constant diffusivities are also shown for comparison purposes. It has to be mentioned that the used diffusivities are not explicitly measured, in contrast to the used permeability (from (Aregawi et al., 2013a)), but are obtained in another way: (case 1) a diffusivity was chosen so that it matched the experimental mass loss curve quite well, leading to $D_m = 1.5 \times 10^{-10} \text{ s}$; (case 2) a diffusivity was determined by averaging K_m/C_m over the moisture content range $0-w_{ini}$, where the K_m of the base case was taken, leading to $D_m = 2.47 \times 10^{-11} \text{ s}$. These diffusivity results are indicated by the blue lines.

In general, the simulation results for a constant permeability match the experimental data well. Note that there is some uncertainty on the choice of the CHTC (thus CMTC), as it was not exactly known. Also a variation on K_m

between the fruits used and those of previous measurements (Aregawi et al., 2013a) could be present. Although both used the same cultivar (*Braeburn*), properties can vary with harvest year and location. The differences with the experimental data are mainly attributed to such uncertainties. Based on a sensitivity analysis (results not reported), rather small variations in both parameters were found to induce noticeable changes in the result. In principle, the material properties (e.g. K_m) or environmental conditions (e.g. CTCs) could be tuned to match the experimental data better, within the bounds of their uncertainty, but this was not performed in the present study. In conclusion, the main characteristics of the drying processes and the magnitude of drying rates are predicted sufficiently accurate with the model, using a constant K_m .

The simulations using a constant diffusivity (Eq.(5)) provide less accurate results. Although the mass loss is approximated quite well for case 1, the drying rate and temperature show larger discrepancies, particularly with respect to the shape of the curves. From case 2, it is clear that determining a diffusivity by averaging its profile (K_m/C_m) over the moisture content range for a constant K_m leads to unrealistic drying rates. In conclusion, using a constant permeability seems to provide more realistic drying predictions than using a constant diffusivity.

This comparison also brings insight on the physics of the drying process. The CDRP is non present, even though the convective conditions (CTCs, T_{ref}) are mild. A lot of fruits have a very short CDRP or none at all, including apples, as reported before (Ateeque et al., 2014; Ben Mabrouk et al., 2012; Mcminn and Magee, 1999). The occurrence of a CDRP and its length are however strongly dependent on the drying conditions, as detailed below. A particular advantage of the simulations is that the occurrence and duration of a constant drying rate period can be identified more precisely than in experiments. The reason is that the surface quantities like moisture flux, temperature and relative humidity, which should remain quasi constant during the CDRP, can be determined accurately at any location on the sample. Obtaining these parameters is much more challenging in experiments. Furthermore, the fruit temperature is found to remain several degrees lower than the ambient air (23°C), due to evaporation of water. The fact that the surface (not shown) and core temperature were about the same in both experiments and simulations indicates that the evaporation is sufficiently slow to cancel out temperature gradients, leading to small temperature variations over the sample.

3.2 Moisture permeability and moisture diffusivity

The moisture permeability, or moisture diffusivity, is one of the most important model parameters that determines model accuracy of drying kinetics predictions. The impact of two aspects is addressed here: (1) its magnitude, as a large variability of this transport parameter (K_m and D_m) has been reported (see Figure 2); (2) its formulation, namely in terms of constant K_m or D_m , which are related to one another via the moisture capacity ($K_m = D_m \times C_m$). As such, the dependency of the drying kinetics on the moisture content (and water potential) will be different whether a (constant) moisture permeability or a moisture diffusivity is used. To identify the impact of both magnitude as well as parameter formulation, a parametric study is performed (Table 2) where different values of both D_m and K_m (constant value) are evaluated, based on the range found in literature.

General drying characteristics

The results are shown in Figure 6, where, the mass loss (dry matter moisture content) and drying rate are shown versus time, as well as the surface-averaged temperature and relative humidity (or water activity) at the air-tissue interface. The volume-averaged fruit temperature was very similar to the surface temperature, which is why it is not reported. The base case (Table 2) is indicated with a bold black line in all graphs. Note that the permeability of this base case ($K_m = 8 \times 10^{-16}$ s) was the same as in the validation experiment, so it reflects realistic drying kinetics.

For both formulations, clear differences in drying kinetics are observed for different magnitudes of the moisture transport parameter. For very high K_m ($\sim 10^{-14}$) or D_m ($\sim 10^{-8}$), even a CDRP is found, as indicated by an almost constant drying rate, so linear mass loss over time, a constant (low) temperature and a high humidity at the surface. For all cases, the temperature of the fruit decreases, due to the evaporation of water at the surface, to a value close to the wet bulb temperature. Note that an exact match is not obtained, which is probably attributed to the enthalpy loss of water (Eq. (2)) which is not accounted for in the wet bulb temperature predictions. Some modelling studies, which did not account for the latent heat of evaporation (Cai et al., 2014; Chandramohan, 2015; Esfahani et al., 2014), found a steadily increasing temperature without this initial temperature drop.

The two parameter formulations can be compared in Figure 6 by evaluating the constant K_m simulations with the constant D_m simulations. At first sight, the simulations show that both parameter formulations (constant K_m and D_m) lead to roughly similar drying behavior, including the change in moisture content, drying rate and temperature over time. However, from the comparison made in section 3.1, the differences are quite significant when compared to experimental data, especially in terms of shape of the curves. As such, the drying process clearly depends on how the K_m and D_m evolve with moisture content (or potential). Therefore it is imperative that the used value for the moisture transport parameter should be verified, preferably with comparison with experimental drying kinetics, as done in section 3.1.

Moisture content profiles

A cross section through the center of the cube is presented in Figure 7, showing the dry matter moisture content (X) at different points in time, for the base case and for the case with a 10 times higher permeability ($K_m = 8 \times 10^{-15}$ s). It should be kept in mind that in reality, shrinkage of the sample will occur, predominantly in the dry tissue regions (blue zones). For a large part of the drying process, the volume change is linearly proportional to the change in water content of the tissue, which is called free shrinkage (Mayor and Sereno, 2004). As shrinkage was not modelled in the present study, the dry (blue) layer in these figures appears thicker than in reality. This will affect the moisture transport near the final stages of drying as the pathway to the surface is longer than in reality.

For the base case, the moisture gradients near the drying front are very high, so concentrated within a small zone. Apart from the dry layer, the tissue has a quite uniform moisture content distribution, with a quite high moisture content. This behavior has been observed in experiments as well (Aregawi et al., 2013a; Defraeye et al., 2016,

2012a). For a larger tissue permeability, moisture gradients are much smaller, leading to a less uniform distribution in moisture content throughout the sample and no clear drying front. Several numerical studies report such non-uniform moisture content distribution inside the tissue during drying (Ateeque et al., 2014; Esfahani et al., 2014). These results seem to be in contrast with previous experimental observations and with the present study (base case), which show moist tissue with a uniform moisture distribution that is separated from the environment by a thin dry tissue layer. From Figure 7, the reported large non-uniformities in other studies are most likely a result of a too high permeability or diffusivity that was used in the numerical model, rather than a physical phenomenon.

3.3 CTCs

The impact of the convective transfer coefficients on the drying process is evaluated since contradicting findings have been reported for fruit drying: some experimental studies report a limited impact of air speed (so CTCs) on the drying rate (Kaya et al., 2007; Kumar et al., 2014; Zlatanović et al., 2013), while other (mainly numerical) studies report a rather large dependency on the CTCs (Ateeque et al., 2014; Barati and Esfahani, 2011; Chandra Mohan and Talukdar, 2010; Velić et al., 2004). We evaluate the impact of CTCs here since these contradicting findings might be explained by the magnitude of the moisture permeability of the fruit tissue. For low permeabilities, the main resistance to moisture transport lies predominantly within the tissue, rather than in the boundary layer. Changing the speed, thus CTCs, will thereby have a rather small impact. For larger tissue permeabilities, the boundary layer transport plays a more important role in the drying kinetics. The actual permeability of the fruit tissue, or the permeability that is used in a continuum model, will thereby determine the resulting impact of the CTCs on the drying process. To verify this hypothesis, simulations using different CTCs were compared in Figure 8, by means of the mass loss, for the permeability of the base case and for a 10 times higher moisture permeability (Table 2, $K_m = 8 \times 10^{-15}$). Note that a different time frame is depicted in Figure 8 for the higher permeability, as the drying process is faster.

For typical CTCs found for convective drying processes, the base case is much less sensitive to the CTCs than the case with a higher permeability. A noticeable CTC impact is still found for the base case, but note that the evaluated CTC range is rather large (factor 100), compared to previous studies (factor 2 or 3). The predicted impact of the air speed on the drying process thus strongly depends on the moisture permeability of the tissue. The aforementioned contradictory findings on the impact of the CTCs on drying could be explained by the strong link to the transport inside the material.

In any case, proper estimates of CTCs are essential to predict drying rates accurately, but they can be considered less critical for lower tissue permeabilities, due to the lower sensitivity of the drying kinetics to airflow (Figure 8). The sensitivity of heat transfer in the tissue to the CHTC and mass transfer to the CMTC is however not the same: the Biot numbers differ at least an order of magnitude for the present study. As the convective heat supply to the

tissue via the boundary layer is essential to evaporate water, the sensitivity of the drying kinetics to the CHTC might be more important than the CMTC.

To identify their separate impact on the drying rate, simulations are performed starting from the base case, but where only the CHTC or only the CMTC is increased with a factor 3.16 ($=10^{0.5}$), so separately, without increasing the other one (see Table 2). Such scenarios can only be mimicked with simulations as one cannot increase the CHTC without affecting the CMTC in reality. Similar simulations are performed as well for a higher ambient air temperature ($T_{ref} = 60^{\circ}\text{C}$). The results are shown in Figure 9. At both temperatures, increasing only the CMTC (blue lines) leads to a lower increase in drying rate compared to increasing only the CHTC (red lines). Increasing the CMTC becomes rather negligible at high temperatures, indicating the simulated drying process is governed by an accurate CHTC prediction. The convective heat supply is thus clearly a critical determinant for the drying kinetics and accurate CHTC estimates are required. In addition, the use of the heat and mass transfer analogy to estimate the CMTC, which relies on particular simplifications (Defraeye et al., 2012b), can therefore still be justified.

4. DISCUSSION AND OUTLOOK

Comparing drying processes

Comparing drying processes based on drying curves (e.g. Figure 8) is not that straightforward in a quantitative way. To this end, a new parameter is introduced: the critical drying time (t_{crit}). It is the time needed for the sample to reach the critical moisture content (w_{crit}). The latter is defined as the (volume-)averaged moisture content in the sample that corresponds, via the sorption isotherm, to an equilibrium water activity below which no spoilage occurs ($a_{w,crit}$). For dried fruit, this $a_{w,crit}$ is about 0.6 (Bonazzi and Dumoulin, 2011). In principle, if the drying process is stopped at w_{crit} and the sample is equilibrated at the same water activity or lower, the average final water activity in the tissue will be below $a_{w,crit}$. For the present study, w_{crit} was 37.8 kg m^{-3} , leading to a X_{crit} of $0.29 \text{ kg kg}_{dm}^{-1}$. With t_{crit} , only one characteristic value is obtained per drying curve which facilitates quantifying differences between drying kinetics. Furthermore, it can serve as a useful indication when to stop a drying process. By stopping the process at the right point in time, over-drying is avoided which could help save energy. To illustrate the use of this parameter, the t_{crit} for all data from Figure 8 is presented in Figure 10, as a function of the CHTC. In this figure, the differences in drying times for the two permeabilities clearly come forward. Depending on the CHTC, the drying time (t_{crit}) between the two permeabilities differ with a factor 1.5 to 8.

Permeability magnitude

The **magnitude** of the moisture permeability is shown to have an impact on the drying kinetics and moisture distribution inside fruit tissue. The large sensitivity to this moisture transport property indicates the need for explicit quantification for the specific fruit species, and preferably cultivar, of interest before starting a modelling study. This can be direct, by measurements of K_m (or D_m), or indirect, by taking a K_m from literature and verifying the simulated drying process with measurements, as was done in the present study (section 3.1). The K_m can also be tuned in the simulations to match the experimental data. In addition, verification with analytical CDRP solutions proved to be useful for evaluating if drying rates are in the right range. Using values from literature without further verification is discouraged as this study showed a large spread on such moisture transport properties exists (Figure 2), by which completely different drying rates are predicted (Figure 6).

Another important aspect is the moisture distribution inside the material, as zones of high water activity at the end of drying can lead to spoilage and food safety issues. Typically, the outer layer dries out first and the moisture distribution stays rather uniform (moist) in the sample (Figure 7). Limited experimental studies look at such internal moisture distribution during drying, and redistribution after drying, for which mainly non-destructive techniques are used (Defraeye et al., 2016, 2012a). In the present study, simulations provided a useful alternative to probe inside the material.

Moisture transport property formulation

A constant value of K_m or D_m was used, but it would actually be beneficial if the dependency of K_m or D_m to the temperature, moisture content and shrinkage would be known and incorporated. This implies much more

detailed material characterization over a wide range of conditions, which is challenging for a soft material such as fruit tissue. A recent study compared different diffusivity formulations (Kumar et al., 2014), clearly identifying an impact on the drying process. More research on unveiling their dependency on process parameters is welcome, and could be achieved for example by simulations at the microscale of water transport through the cellular tissue (Fanta et al., 2014, 2013). However, despite the fact that a constant K_m or D_m was used in the present study, the drying kinetics were predicted accurately (Figure 5), which is sufficient for engineering problems.

Hygrothermal simulations

Apart from the continuum model parameters, the hygrothermal simulations could be enhanced in several ways to improve moisture transport predictions. First, mechanical deformation could be implemented, since due to shrinkage of the tissue into a thin layer, the path length for moisture transport will be shortened, which will affect moisture transport. Furthermore, evaporation is assumed to occur at the surface. Although this assumption is acceptable during free shrinkage, it becomes less accurate towards the end of the drying process as then the evaporation front is located deep inside the material (Dhall and Datta, 2011; Gulati and Datta, 2015). This can alter the moisture transport as the resistance of the pathway for water vapor differs from that of liquid water. However, the impact on the location of evaporation on the heat transport calculations will probably be limited as, in the present study, the fruit temperature was quasi uniform due to the fast heat distribution by conduction. Finally, radiation at the surface with the environment could be included. Although this is relevant for drying, due to the temperature difference between the fruit surface and environment, it has been accounted for very rarely for convective fruit drying.

5. CONCLUSIONS

This study targeted the role and impact of moisture transport properties in simulations on the drying process of fruit tissue. Validation showed that the use of a constant moisture permeability (K_m) or diffusivity (D_m) in the continuum model already provided satisfactory accuracy, which is sufficient for engineering calculations. Both parameter formulations (constant K_m and D_m) led to roughly similar drying behavior but a constant permeability matched the experimental data better.

For the range of diffusivities that is reported in literature for apple fruit, significant differences in drying rates and internal moisture distribution were identified. For low permeabilities, the inner tissue had at a rather uniform moisture content distribution and was separated from the environment by a dry tissue layer. The dependency of the drying process on the permeability shows that it is critical that its magnitude is verified, preferably by comparison with experimental drying kinetics.

In addition, the impact of the air speed, thus convective transfer coefficients (CTCs), on the drying process was shown to be strongly dependent on the tissue's moisture permeability. Drying was found to be less sensitive to the CTCs for low permeabilities. This finding explained previous contradictory findings on the impact of CTCs on the drying process. In addition, an accurate estimate of the convective heat transfer coefficient was shown to be

more critical than an accurate estimate of the convective mass transfer coefficient. For the latter, using the heat and mass transfer analogy is therefore justified. Finally, a new parameter was introduced, namely the critical drying time. This parameter facilitates quantitative comparison of multiple drying processes as only one characteristic value is obtained per drying curve.

This study provides a better quantitative insight in the drying behavior of (apple) fruit and how it is linked to the moisture transport properties of the tissue, which are used in the hygrothermal model. Due to the large range of transport properties that was evaluated, the results are also relevant for other food materials.

ACKNOWLEDGEMENTS

We acknowledge the support of the World Food System Center (WFSC) of ETH Zürich (www.worldfoodsystem.ethz.ch) and the support of the Swiss National Science Foundation SNSF (project 200021_160047). This research was carried out in the context of the European COST Action FA1106 ('QualiFruit').

REFERENCES

- Aregawi, W., Defraeye, T., Saneinejad, S., Vontobel, P., Lehmann, E., Carmeliet, J., Derome, D., Verboven, P., Nicolai, B., 2013a. Dehydration of apple tissue: Intercomparison of neutron tomography with numerical modelling. *Int. J. Heat Mass Transf.* 67, 173–182. doi:10.1016/j.ijheatmasstransfer.2013.08.017
- Aregawi, W., Defraeye, T., Verboven, P., Herremans, E., Roeck, G., Nicolai, B., 2013b. Modeling of coupled water transport and large deformation during dehydration of apple tissue. *Food Bioprocess Technol.* 6, 1963–1978. doi:10.1007/s11947-012-0862-1
- ASHRAE, 2010. *ASHRAE Handbook - Refrigeration: systems and applications* (SI edition). Atlanta.
- Ateeque, M., Mishra, R.K., Chandramohan, V.P., Talukdar, P., 2014. Numerical modeling of convective drying of food with spatially dependent transfer coefficient in a turbulent flow field. *Int. J. Therm. Sci.* 78, 145–157. doi:10.1016/j.ijthermalsci.2013.12.003
- Barati, E., Esfahani, J. A., 2011. A new solution approach for simultaneous heat and mass transfer during convective drying of mango. *J. Food Eng.* 102, 302–309. doi:10.1016/j.jfoodeng.2010.09.003
- Ben Mabrouk, S., Benali, E., Oueslati, H., 2012. Experimental study and numerical modelling of drying characteristics of apple slices. *Food Bioprod. Process.* 90, 719–728. doi:10.1016/j.fbp.2012.02.001
- Bonazzi, C., Dumoulin, E., 2011. Quality changes in food materials as influenced by drying processes, in: Tsotsas, E., Mujumdar, A.S. (Eds.), *Modern Drying Technology - Product Quality and Formulation*. Wiley-VHC Verlag GmbH, Weinheim, Germany, pp. 1–20.
- Cai, W., Zhu, L., Dong, S., Xie, G., Li, J., 2014. Effect of Thermophysical Properties on Coupled Heat and Mass Transfer in Porous Material during Forced Convective Drying. *Adv. Mech. Eng.* 2014, 1–7. doi:10.1155/2014/830387
- Chandra Mohan, V.P., Talukdar, P., 2010. Three dimensional numerical modeling of simultaneous heat and moisture transfer in a moist object subjected to convective drying. *Int. J. Heat Mass Transf.* 53, 4638–4650. doi:10.1016/j.ijheatmasstransfer.2010.06.029
- Chandramohan, V.P., 2015. Numerical prediction and analysis of surface transfer coefficients on moist object during heat and mass transfer application. *Heat Transf. Eng.* 7632, 00–00. doi:10.1080/01457632.2015.1042341
- Datta, A.K., 2007a. Porous media approaches to studying simultaneous heat and mass transfer in food processes. II: Property data and representative results. *J. Food Eng.* 80, 96–110. doi:10.1016/j.jfoodeng.2006.05.012
- Datta, A.K., 2007b. Porous media approaches to studying simultaneous heat and mass transfer in food processes. I: Problem formulations. *J. Food Eng.* 80, 80–95. doi:10.1016/j.jfoodeng.2006.05.013
- Datta, A.K., 2008. Status of physics-based models in the design of food products, processes, and equipment. *Compr. Rev. Food Sci. Food Saf.* 7, 121–129.

- Defraeye, T., 2014. Advanced computational modelling for drying processes - a review. *Appl. Energy* 131, 323–344.
- Defraeye, T., Aregawi, W., Saneinejad, S., Vontobel, P., Lehmann, E., Carmeliet, J., Verboven, P., Derome, D., Nicolai, B., 2012a. Novel application of neutron radiography to forced convective drying of fruit tissue. *Food Bioprocess Technol.* 6, 3353–3367. doi:10.1007/s11947-012-0999-y
- Defraeye, T., Blocken, B., Carmeliet, J., 2012b. Analysis of convective heat and mass transfer coefficients for convective drying of a porous flat plate by conjugate modelling. *Int. J. Heat Mass Transf.* 55, 112–124. doi:10.1016/j.ijheatmasstransfer.2011.08.047
- Defraeye, T., Nicolai, B., Mannes, D., Aregawi, W.A., Verboven, P., Derome, D., 2016. Probing inside fruit slices during convective drying by quantitative neutron imaging. *J. Food Eng.*
- Dhall, A., Datta, A.K., 2011. Transport in deformable food materials: A poromechanics approach. *Chem. Eng. Sci.* 66, 6482–6497. doi:10.1016/j.ces.2011.09.001
- Esfahani, J. A., Majdi, H., Barati, E., 2014. Analytical two-dimensional analysis of the transport phenomena occurring during convective drying: Apple slices. *J. Food Eng.* 123, 87–93. doi:10.1016/j.jfoodeng.2013.09.019
- Fanta, S.W., Abera, M.K., Aregawi, W., Ho, Q.T., Verboven, P., Carmeliet, J., Nicolai, B.M., 2014. Microscale modeling of coupled water transport and mechanical deformation of fruit tissue during dehydration. *J. Food Eng.* 124, 86–96. doi:10.1016/j.jfoodeng.2013.10.007
- Fanta, S.W., Abera, M.K., Ho, Q.T., Verboven, P., Carmeliet, J., Nicolai, B.M., 2013. Microscale modeling of water transport in fruit tissue. *J. Food Eng.* 118, 229–237. doi:10.1016/j.jfoodeng.2013.04.003
- Gulati, T., Datta, A.K., 2013. Enabling computer-aided food process engineering: Property estimation equations for transport phenomena-based models. *J. Food Eng.* 116, 483–504. doi:10.1016/j.jfoodeng.2012.12.016
- Gulati, T., Datta, A.K., 2015. Mechanistic understanding of case-hardening and texture development during drying of food materials. *J. Food Eng.* 166, 119–138. doi:10.1016/j.jfoodeng.2015.05.031
- Halder, A., Datta, A.K., 2012. Surface heat and mass transfer coefficients for multiphase porous media transport models with rapid evaporation. *Food Bioprod. Process.* 90, 475–490. doi:10.1016/j.fbp.2011.10.005
- Halder, A., Datta, A.K., Spanswick, R.M., 2011. Water transport in cellular tissues during thermal processing. *AIChE J.* 57, 2574–2588. doi:10.1002/aic
- Herremans, E., Verboven, P., Bongaers, E., Estrade, P., Verlinden, B.E., Wevers, M., Hertog, M.L.A.T.M., Nicolai, B., 2013. Characterisation of “Braeburn” browning disorder by means of X-ray micro-CT. *Postharvest Biol. Technol.* 75, 114–124. doi:10.1016/j.postharvbio.2012.08.008
- Kaya, A., Aydın, O., Demirtaş, C., 2007. Drying Kinetics of Red Delicious Apple. *Biosyst. Eng.* 96, 517–524. doi:10.1016/j.biosystemseng.2006.12.009
- Kaya, A., Aydın, O., Dincer, I., 2006. Numerical modeling of heat and mass transfer during forced convection

- drying of rectangular moist objects. *Int. J. Heat Mass Transf.* 49, 3094–3103.
doi:10.1016/j.ijheatmasstransfer.2006.01.043
- Kumar, C., Millar, G.J., Karim, M. a., 2014. Effective Diffusivity and Evaporative Cooling in Convective Drying of Food Material. *Dry. Technol.* 33, 227–237. doi:10.1080/07373937.2014.947512
- Kurnia, J.C., Sasmito, A.P., Tong, W., Mujumdar, A.S., 2013. Energy-efficient thermal drying using impinging-jets with time-varying heat input – A computational study. *J. Food Eng.* 114, 269–277.
doi:10.1016/j.jfoodeng.2012.08.029
- Léonard, A., Blacher, S., Marchot, P., Pirard, J.-P., Crine, M., 2005. Moisture profiles determination during convective drying using X-ray microtomography. *Can. J. Chem. Eng.* 83, 127–131.
doi:10.1002/cjce.5450830121
- Mayor, L., Sereno, A.M., 2004. Modelling shrinkage during convective drying of food materials: a review. *J. Food Eng.* 61, 373–386. doi:10.1016/S0260-8774(03)00144-4
- Mcminn, W.A.M., Magee, T.R.A., 1999. Principles, methods and applications of the convective drying of foodstuffs. *Food Bioprod. Process.* 77, 175–193.
- Nguyen, T.A., Verboven, P., Scheerlinck, N., Vandewalle, S., Nicolaï, B.M., 2006. Estimation of effective diffusivity of pear tissue and cuticle by means of a numerical water diffusion model. *J. Food Eng.* 72, 63–72.
doi:10.1016/j.jfoodeng.2004.11.019
- Nilnont, W., Thepa, S., Janjai, S., Kasayapanand, N., Thamrongmas, C., Bala, B.K., 2012. Finite element simulation for coffee (*Coffea arabica*) drying. *Food Bioprod. Process.* 90, 341–350. doi:10.1016/j.fbp.2011.06.007
- Tsotsas, E., Mujumdar, A.S., 2007. *Modern Drying Technology - Volume 1 - Computational Tools at Different Scales*. Wiley-VHC Verlag GmbH, Weinheim, Germany.
- Tzempelikos, D.A., Mitrakos, D., Vouros, A.P., Bardakas, A. V., Filios, A.E., Margaris, D.P., 2015. Numerical modeling of heat and mass transfer during convective drying of cylindrical quince slices. *J. Food Eng.* 156, 10–21. doi:10.1016/j.jfoodeng.2015.01.017
- Vega-Gálvez, A., Ah-Hen, K., Chacana, M., Vergara, J., Martínez-Monzó, J., García-Segovia, P., Lemus-Mondaca, R., Di Scala, K., 2012. Effect of temperature and air velocity on drying kinetics, antioxidant capacity, total phenolic content, colour, texture and microstructure of apple (var. Granny Smith) slices. *Food Chem.* 132, 51–59. doi:10.1016/j.foodchem.2011.10.029
- Velić, D., Planinić, M., Tomas, S., Bilić, M., 2004. Influence of airflow velocity on kinetics of convection apple drying. *J. Food Eng.* 64, 97–102. doi:10.1016/j.jfoodeng.2003.09.016
- Veraverbeke, E. a., Verboven, P., Scheerlinck, N., Hoang, M.L., Nicolaï, B.M., 2003. Determination of the diffusion coefficient of tissue, cuticle, cutin and wax of apple. *J. Food Eng.* 58, 285–294. doi:10.1016/S0260-8774(02)00387-4
- Zlatanović, I., Komatina, M., Antonijević, D., 2013. Low-temperature convective drying of apple cubes. *Appl.*

TABLES

Table 1. Material properties, boundary conditions and initial conditions for the base case.

Material properties	Symbol	Value
Moisture permeability fruit tissue (Aregawi et al., 2013a)	K_m	8×10^{-16} [s]
Thermal conductivity fruit tissue (ASHRAE, 2010)	λ_{PM}	0.418 [$\text{W m}^{-1} \text{K}^{-1}$]
Specific heat capacity of dry matter (ASHRAE, 2010)	$c_{p,s}$	1634 [$\text{J kg}^{-1} \text{K}^{-1}$]
Specific heat capacity of liquid water	$c_{p,l}$	4182 [$\text{J kg}^{-1} \text{K}^{-1}$]
Specific heat capacity water vapor	$c_{p,v}$	1880 [$\text{J kg}^{-1} \text{K}^{-1}$]
Dry matter density	w_s	130 [kg m^{-3}]
Sorption isotherm (as a function of water activity) (Aregawi et al., 2013a)	$w_m(a_w)$	$w_s \left(\frac{0.15926}{\ln \left(\frac{1.0177}{a_w} \right)} \right)^{\frac{1}{0.97014}}$ [kg m^{-3}]
Density liquid water	ρ_l	1000 [kg m^{-3}]
Latent heat	L_v	2.5×10^6 [J kg^{-1}]
Specific gas constant for water vapor	R_v	461.52 [$\text{J kg}^{-1} \text{K}^{-1}$]
Boundary and initial conditions	Symbol	Value
Initial tissue temperature	T_{ini}	20 [$^{\circ}\text{C}$]
Initial tissue moisture content (dry base)	X_{ini}	6 [kg kg_{dm}^{-1}]
Initial tissue moisture content	$w_{m,ini}$	780 [kg m^{-3}]
Ambient air temperature	T_{ref}	20°C
Ambient relative humidity	RH_{ref}	30%
Convective heat transfer coefficient	$h_{c,T}$	10 [$\text{W m}^{-2} \text{K}^{-1}$]
Convective mass transfer coefficient	$h_{c,m}$	7.03×10^{-8} [s m^{-1}]

Table 2. Material properties and environmental conditions for different variants. If no value is specified (indicated by a dash), the same one is taken as the base case (AF is the analogy factor = 7.03×10^{-9}).

Variant name	Permeability K_m [s]	Diffusivity D_m [$\text{m}^2 \text{s}^{-1}$]	CHTC [$\text{W m}^{-2} \text{K}^{-1}$]	T_{ref} [°C]
Base case	8×10^{-16}	-	10	20
Type 1: Moisture properties				
Km_8e-14	8×10^{-14}	-	-	-
Km_8e-15	8×10^{-15}	-	-	-
Km_8e-17	8×10^{-17}	-	-	-
Dm_1e-8	$D_m \times C_m$	1×10^{-8}	-	-
Dm_1e-9	$D_m \times C_m$	1×10^{-9}	-	-
Dm_1e-10	$D_m \times C_m$	1×10^{-10}	-	-
Dm_1e-11	$D_m \times C_m$	1×10^{-11}	-	-
Type 2: Drying conditions				
CHTC_3	-	-	3.16	-
CHTC_31	-	-	31.6	-
CHTC_100	-	-	100	-
CHTC_316	-	-	316	-
CHTC_3-Km_8e-15	8×10^{-15}	-	3	-
CHTC_31-Km_8e-15	8×10^{-15}	-	31	-
CHTC_100-Km_8e-15	8×10^{-15}	-	100	-
CHTC_316-Km_8e-15	8×10^{-15}	-	316	-
T_60-CHTC_10	-	-	10	60
T_60-CHTC_31	-	-	31.6	60
T_60-CHTC_31-CMTC_10	-	-	CHTC = 31.6 & CMTC = $10 \times \text{AF}$	60
T_60-CHTC_10-CMTC_31	-	-	CHTC = 10 & CMTC = $31.6 \times \text{AF}$	60
CHTC_31-CMTC_10	-	-	CHTC = 31.6 & CMTC = $10 \times \text{AF}$	-
CHTC_10-CMTC_31	-	-	CHTC = 10 & CMTC = $31.6 \times \text{AF}$	-

FIGURES

Figure 1. Cellular fruit tissue: (a) Apple parenchyma cells of fresh tissue imaged with X-ray tomography and segmented for visualization (Herremans et al., 2013), (b) Moisture transport pathways (adjusted from (Halder et al., 2011)).

Figure 2. Moisture diffusivity range reported in literature for apple fruit. The experiments start from fresh tissue, but dehydration is performed in most cases in order to determine the diffusivity. If different approach flow conditions were evaluated, they are indicated by U (speed), T (temperature) and RH (humidity).

Figure 3. Computational model with boundary conditions.

Figure 4. Moisture diffusivity (a-b) and permeability (c-d) using different formulations as a function of water potential and moisture content. The grey lines represent the range of constant values that are evaluated (Table 2).

Figure 5. Comparison between simulation (constant K_m and constant D_m) and experiment for drying of apple fruit: Dry base moisture content (a), drying rate (b), temperature in center of the fruit (c), as a function of time. The analytically-determined mass loss and drying rate for CDRP conditions and the wet bulb temperature are indicated with the dotted grey lines.

Figure 6. Comparison between simulations with constant moisture permeability and diffusivity: Dry matter moisture content (a), drying rate (b), temperature at the surface of the fruit (c) and corresponding water activity (relative humidity) at the surface of the fruit (d), as a function of time. The analytically-determined mass loss and drying rate at CDRP conditions and the wet bulb temperature are indicated with the dotted grey lines. The same color legends are used for all graphs of K_m and D_m respectively.

Base case ($K_m = 8 \times 10^{-16} \text{ s}$)

Higher moisture permeability ($K_m = 8 \times 10^{-15} \text{ s}$)

1 hour

5 hours

10 hours

15 hours

20 hours

0 kg/kg_{dm}

6 kg/kg_{dm}

Figure 7. Dry matter moisture content (X) in a center plane of the cube (1/4 of cube depicted due to symmetry) at different points in time for the base case and a case with a 10 times higher permeability.

Figure 8. Comparison of dry matter moisture content during drying for simulations with different CTCs: base case permeability versus a case with a 10 times higher permeability. Note that the reported time frames differ.

Figure 9. Comparison of dry matter moisture content and drying rate at two different ambient temperatures for four different combinations of convective heat and mass transfer coefficients.

Figure 10. Critical drying time as a function of the CHTC (scaled with the CHTC of the base case) for two tissue permeabilities (log-log scale).