This manuscript is for the proposed special volume of:

“Characterization of hydrate-bearing sediments from the 2012-13 Methane Hydrate Resources in Japan drilling program in the Eastern Nankai Trough (Gas hydrate drilling in Eastern Nankai)”

• ***Title***

Hydro-Bio-Geomechanical Properties of Hydrate-Bearing Sediments from Nankai Trough

• ***Authors and affiliations***

Santamarina, J.C.^a, Dai, S.^{a,1}, Terzariol, M.^a, Jang, J.^a, Waite, W.F.^b, Winters, W.J.^b, Nagao, J.^c,
Yoneda, J.^c, Konno, Y.^c, Fujii, T.^d, Suzuki, K.^d

^a Georgia Institute of Technology, Atlanta, GA, United States

^b U.S. Geological Survey, Woods Hole, MA, United States

^c National Institute of Advanced Industrial Science and Technology, Sapporo, Japan

^d Japan Oil, Gas and Metals National Corporation, Tokyo, Japan

• ***Corresponding Author***

William F. Waite
U.S. Geological Survey
384 Woods Hole Road
Woods Hole, MA 02543
United States of America

Phone: (508) 457-2346
Email: wwaite@usgs.gov

• ***Present affiliation***

¹ S. Dai now at: National Energy Technology Laboratory, Morgantown, WV, United States

• ***Keywords***

Methane hydrate; Hydrate-bearing sediment; Nankai Trough; Physical properties; Pressure core

Abstract:

Natural hydrate-bearing sediments from the Nankai Trough, offshore Japan, were studied using the Pressure Core Characterization Tools (PCCTs) to obtain geomechanical, hydrological, electrical, and biological properties under in situ pressure, temperature, and restored effective stress conditions. Measurement results, combined with index-property data and analytical physics-based models, provide unique insight into hydrate-bearing sediments in situ. Tested cores contain some silty-sands, but are predominantly sandy- and clayey-silts. Hydrate saturations S_h range from 0.15 to 0.74, with significant concentrations in the silty-sands. Wave velocity and flexible-wall permeameter measurements on never-depressurized pressure-core sediments suggest hydrates in the coarser-grained zones, the silty-sands where S_h exceeds 0.4, contribute to soil-skeletal stability and are load-bearing. In the sandy- and clayey-silts, where $S_h < 0.4$, the state of effective stress and stress history are significant factors determining sediment stiffness. Controlled depressurization tests show that hydrate dissociation occurs too quickly to maintain thermodynamic equilibrium, and pressure-temperature conditions track the hydrate stability boundary in pure-water, rather than that in seawater, in spite of both the in situ pore water and the water used to maintain specimen pore pressure prior to dissociation being saline. Hydrate dissociation accompanied with fines migration caused up to 2.4% vertical strain contraction. The first-ever direct shear measurements on never-depressurized pressure-core specimens show hydrate-bearing sediments have higher sediment strength and peak friction angle than post-dissociation sediments, but the residual friction angle remains the same in both cases. Permeability measurements made before and after hydrate dissociation demonstrate that water permeability increases after dissociation, but the gain is limited by the transition from hydrate saturation before dissociation to gas saturation after dissociation. In a proof-of-concept

study, sediment microbial communities were successfully extracted and stored under high-pressure, anoxic conditions. Depressurized samples of these extractions were incubated in air, where microbes exhibited temperature-dependent growth rates.

1. Introduction

A hydraulic, geomechanical, and biological characterization of hydrate-bearing sediments from the Nankai Trough, offshore Japan, was conducted during the first deployment of a suite of Pressure Core Characterization Tools (PCCTs) as part of a collaborative pressure-core study led by the Research Consortium for Methane Hydrate Resources in Japan (MH21) and funded by the Ministry of Economy, Trade and Industry (METI) (Yamamoto et al., 2012; Yamamoto, 2015). PCCTs are designed to maintain the high pressure needed to keep hydrate stable during the entire process of transferring, subsampling, and testing hydrate-bearing sediments in cores collected and retained at near-in situ pressures (Santamarina et al., 2012a; 2012b). PCCT measurements provide a comprehensive set of parameters needed for borehole-stability analyses, reservoir-production simulations, and in situ characterization of the hydrate-bearing system.

The Nankai Trough is located southeast of Japan, from offshore Tokai to offshore Kyushu, and has extensively developed forearc basins and accretionary prisms. Thrust and growth faults, as well as bottom-simulating reflectors (BSRs) suggestive of the presence of hydrate, have been extensively investigated since 1971 with seismic surveys, coring, and logging (Matsumoto et al., 2004; Takahashi and Tsuji, 2005; Tsuji et al., 2004; Uchida et al., 2004; Waseda and Uchida, 2004a, b). The total amount of gas in place in the eastern Nankai Trough is estimated to be 1.1 trillion (10^{12}) cubic meters (Fujii et al., 2008). Isotope analyses suggest the methane gas in shallow sections of the Nankai Trough at the coring site for this study is mostly

1
2
3
4 microbial, with only a slight increase of higher hydrocarbon concentrations with depth (Kida et
5 al., 2015). A minor contribution of thermogenic methane near mud volcanoes at the Kumano-
6
7
8 nada area has also been observed (Uchida et al., 2009).
9

10
11 This pressure-core characterization study reported herein is a joint effort of the Georgia
12
13 Institute of Technology (Georgia Tech), U.S. Geological Survey (USGS), Japan Oil Gas and
14
15 Metals National Corporation (JOGMEC), and the National Institute of Advanced Industrial
16
17 Science and Technology (AIST). The study utilizes pressure cores recovered from hydrate-
18
19 bearing sediments in hole AT1-C, on the north slope of Daini Atsumi Knoll off the Atsumi and
20
21 Shima peninsulas. A location overview is provided by Yamamoto (2015), and a more precise
22
23 location map is given by Fujii et al. (2015). Pressure cores were collected during the third
24
25 hydrate drilling program at Nankai Trough from June 29th to July 4th of 2012 (Yamamoto et al.,
26
27 2012). Water depth at this drilling location is ~1000m and hydrate deposits are approximately
28
29 300m below the seafloor within the deep submarine-fan turbidite system. The 60-m coring
30
31 interval, from ~1270m to ~1330m below sea level, includes a clayey-silt overburden zone and a
32
33 methane hydrate concentration zone (MHCZ) containing clayey-silt, sandy-silt and silty-sand
34
35 layers (Ito et al., 2015). Most gas hydrates at this site occur in the pore spaces of unconsolidated
36
37 silty-sand sediments. The first methane production test from marine gas hydrates was
38
39 accomplished at this AT1 site in early 2013 (Fujii et al., 2013; Yamamoto, 2013).
40
41
42
43
44
45
46
47
48
49

50 **2. Core Handling**

51
52 The 2012 Nankai Trough pressure-coring program provided an opportunity to examine
53
54 minimally-disturbed, hydrate-bearing sediment acquired and continuously held at high pressure
55
56 and within the hydrate-stability conditions. Pressure cores were cut and stored at sea in 1.2 m-
57
58
59
60
61
62
63
64
65

1
2
3
4 long pressurized storage vessels held at 20MPa in a refrigerated van (Inada et al., 2015). Post
5
6
7 cruise, the storage vessels were transferred to the AIST facility in Sapporo, where they were
8
9 monitored and held at a pressure of ~20MPa and a temperature of ~5°C. For PCCT analysis,
10
11
12 cores were transported to cold rooms held at ~4-6°C. Suzuki et al. (2015) show the pressure and
13
14 temperature history of one pressure core throughout the collection, transport and storage process.

15
16 To reduce stress on PCCT pressure seals and pumps, the operating pressure was chosen
17
18 to be 10MPa rather than the 20MPa at which the cores were stored. Because methane hydrate is
19
20 stable above 4.7MPa at 6°C (Sloan and Koh, 2007), depressurizing from 20 to 10MPa prior to
21
22 PCCT testing does not induce any of the sample degradation associated with departures from the
23
24 methane hydrate stability conditions (Waite et al., 2008). The solubility of methane in the pore
25
26 water is also a consideration because in the absence of methane hydrate, methane solubility
27
28 drops during depressurization, and methane coming out of solution as gas can severely affect the
29
30 mechanical properties of unconsolidated sediment during depressurization (Yun et al., 2006). In
31
32 the presence of stable hydrate however, methane does not come out of solution to form gas
33
34 bubbles during depressurization because the methane solubility actually increases slightly as
35
36 pressure decreases (Lu et al., 2008). Based on the analysis of Dai and Santamarina (2014), the
37
38 solubility increase is expected to result in a negligible 0.1% hydrate saturation decrease for the
39
40 Nankai Trough cores analyzed in this study.

41
42 The three pressure cores described in this study are: AT1-C-8P(133-227), AT1-C-
43
44 10P(33-152.5), and AT1-C-20P(72-145), denoted here as 8P, 10P and 20P, respectively. All
45
46 pressure cores in this study had a diameter of 50.8mm and a maximum length of 1.2m.

47 48 49 50 51 52 53 54 55 56 57 58 **3. Devices, Procedure, and Data Reduction**

Pressure core characterization tools PCCTs are shown schematically in Fig. 1 (Santamarina et al., 2012a; 2012b). These tools were deployed in the AIST facility in Sapporo, Japan to transfer, subsample, and characterize the AT1-C Nankai Trough pressure cores while maintaining near in situ pressure and temperature conditions. Throughout the PCCT testing program, unless specifically noted, the pressurizing fluid is an artificial brine made by mixing ~30 parts per thousand iodine-free salt with pure water. Cores were extracted from their storage chambers at pressure and held using the PCCT manipulator (Fig. 1A). Cores 8P and 10P were tested in the Instrumented Pressure Testing Chamber IPTC prior to being subsectioned under pressure using the PCCT saw for study in other PCCT devices. Cut and measurement locations are shown in Fig. 2. Test procedures used in the individual PCCTs are given below.

3.1. Instrumented Pressure Testing Chamber, IPTC

The IPTC measures P- and S-wave velocities, undrained shear strength, and electrical conductivity at preselected locations along a core (Yun et al., 2006). Four opposing sensor port pairs are spaced along the length of the IPTC (Fig. 1A). The first sensor pair contains drills for penetrating the core liner. As the core is advanced through the IPTC, sensors are inserted through the holes in the liner and brought directly into contact with the core sediment. Measurements are made at a given hydrostatic stress, but with no applied effective stress. P-wave velocity measurements V_P are made using 1 MHz P-wave pinducers. S-wave velocity measurements V_S are made using S-wave bender elements, each encased in silicone to make a circular pad with which to contact the specimen and transmit/receive a shear wave. The final port pair contains a 5.6 mm-diameter cone penetrometer in the top port for measuring undrained shear strength S_u and a 2.1 mm-diameter, single-wedge, 20 kHz electrical conductivity σ_{el} needle probe in the bottom port.

3.2. Effective Stress Chamber, ESC

The ESC chamber, shown schematically in Fig. 1B, not only maintains hydrate pressure-temperature P-T stability conditions, but is also capable of directly accepting a core at pressure and restoring stress-controlled boundary conditions: the lateral stress σ_h' is controlled using the pressurizing brine against a soft membrane jacket. The effective vertical stress σ_v' is controlled using a loading piston reacted against an external load frame. The in situ σ_v' is calculated from the sub-sea floor depth of each core and the average unit weight of the overlying sediment, 8.16 kN/m³ (Fig. 2 shows overburden data for each core). For this study, the ESC is equipped to measure stress-volume responses and provides water permeability values for pressure-core specimens tested under in situ P - T - σ_v' conditions.

A typical test sequence using the ESC consists of four stages: 1) accept and restore a specimen to the in situ effective stress using a standard oedometer test protocol; 2) characterize the hydrate-bearing specimen at in situ P - T - σ' conditions; 3) monitor the specimen behavior during hydrate dissociation and gas production; and 4) characterize the specimen post-production. The pore fluid pressure, temperature, boundary stresses, and vertical deformation are continuously monitored during all stages.

To accept a pressure-core specimen, the ESC is set horizontally, aligned and coupled to the manipulator core transfer system, referred to as the MAN, and the PCCT saw, as described by (Santamarina et al., 2012a; 2012b). Once the specimen and core liner are cut to length, they are pushed into the ESC liner trap. The MAN control arm is retracted to the storage chamber so the ball valves on the ESC and MAN can be closed. Once the bridge between the ESC and MAN is depressurized, the ESC is decoupled and placed vertically within an external frame. A loading piston is then attached to the ESC and used to push the specimen out of the rigid core liner into

the rubber jacket (Fig. 1B). Because the ESC does not contain an internal load cell, and the chamber pressure u_{cell} is not measured in the specimen pore space, stresses on the specimen are expressed in terms of applied stress $F/A - u_{cell}$ rather than as effective vertical stress σ_v' . Values of $F/A - u_{cell}$ are directly measured and do not necessarily equal the actual effective vertical stress σ_v' experienced by the core specimen if transient pore pressures u_{pore} exist inside the core. Note that force equilibrium gives: $F/A - u_{cell} = u_{pore} + \sigma_v'$, where F is the implied force through the loading piston, A is the specimen cross section, and u_{cell} is the chamber pressure. The Direct Shear Chamber (introduced in section 3.3) adopts the same stress definition.

Water permeability is measured directly in both stage 2 (before hydrate dissociation) and stage 4 (after hydrate dissociation) at the in situ stress state, though with the confining fluid raised to 40-50 kPa above the pore pressure to ensure there is no preferential fluid flow along the specimen boundary. According to Darcy's law, the intrinsic permeability of a porous medium k can be computed as:

$$k = \frac{q}{\nabla P / \mu}, \quad (1)$$

where q is the fluid flux, ∇P is the pressure gradient given by the measured differential pressure Δu over the specimen length L , and μ is the fluid viscosity. The water permeability of the hydrate-bearing sediment was obtained by pumping water at a constant flux q while measuring the pressure difference Δu across the specimen. The constant flow rate was controlled by a Teledyne ISCO 500D pump, and the differential pressure was measured using a high accuracy (~1kPa for in-line pressures of 10 MPa) Validyne, DP303 differential pressure transducer. Porous stones were placed on the loading pad and pedestal to spread the injected flow uniformly across the specimen's cross section.

The hydraulic gradient used to measure water permeability is carefully selected. A small gradient requires a long test duration, and the measured pressure difference may fall below noise levels; on the other hand, large gradients impose pronounced effective stress gradients that unevenly compact the specimen and may cause fines migration. To avoid specimen compaction, the imposed fluxes were low, only large enough to generate differential pressures exceeding the transducer's ~1kPa resolution limit at 10MPa. All tests in this study involved hydraulic gradients between 1 and 10.

3.3. Direct Shear Chamber, DSC

Cylindrical specimens tested under triaxial conditions will be affected by seating effects; this situation is aggravated by sub-sampling and transfer under high-pressure, as no remedial boundary trimming/correction can be implemented. Consequently, a double plane shear device was designed to determine shear strength by causing shear away from subsampling cutting surfaces. The shear box consists of a sliding stainless steel ring connected to an internal horizontal loading piston that generates a maximum shear displacement of 15mm. At all times, P-waves, temperature, water pressure, forces and displacements can be monitored.

The DSC is the first chamber to accurately measure shear strength of never-depressurized methane hydrate-bearing pressure cores under in situ hydrostatic pressure and vertical effective stress. This chamber includes (Fig. 1C): 1) the vertical loading piston, which like its counterpart in the ESC, is used to extrude the specimen from its rigid core liner and restore the in situ vertical effective stress. Piezo-crystals and thermocouples located in the base of the loading piston and in the pedestal are used to measure P-wave velocity and temperature respectively; 2) the transfer coupler with a flange for connecting with the PCCT manipulator; 3) liner trap and 4) shear box.

Specimens are loaded into the shear box using the same steps described for the ESC in Section 3.2. An ISCO pump is connected to the chamber in order to maintain water pressure at 10MPa, with an accuracy of ± 0.2 MPa. The effective vertical stress σ_v' is calculated following the same analysis used for the ESC.

The test sequence starts by restoring the in situ vertical effective stress σ_v' using the loading piston. P-wave velocities are measured during this consolidation process. Once consolidation is complete, the specimen is held at its near in situ σ_v' , and the specimen is sheared. Because the loading piston provides constant displacement rather than constant stress, stresses can change during shear. To perform the shear test at the given initial stress state, the shearing is accomplished through a series of 1mm horizontal displacements and left to relax after each shear displacement. Once the shear loading is finished, the vertical loading piston is retracted to bring the sediment to zero vertical stress, the internal horizontal displacement ring is restored to its initial position and the specimen, still containing hydrate, is reloaded to $\sigma_v'=3$ MPa. This is the initial condition for hydrate dissociation.

After hydrate dissociation, the specimen is subjected to a set of tests performed to characterize the hydrate-free sediment. The sequence reported here consists of the following steps: (1) specimen overburden is verified to be $\sigma_v'=3$ MPa; (2) shear test; (3) vertical unloading and realignment of the shear ring; (4) reloading to $\sigma_v'=7.5$ MPa; (5) shear test. Deformations and P-wave propagation velocities are determined throughout the complete test sequence.

3.4. Bio-Chamber, BIO

The BIO chamber deployment is intended as a proof-of-concept that sediment subsections can be collected and stored at pressure under anoxic conditions for subsequent biological studies. BIO consists of a sub-sampling chamber designed to collect multiple soil

specimens and exchangeable high-pressure bio-reactors into which specimens can be transferred at pressure (Fig. 1D). The BIO system is loaded with a pressure-core subsection using the same steps described for the ESC chamber (Section 3.2). Once the BIO chamber is loaded with a pressure core, it is decoupled from the manipulator system and remains oriented with the core lying horizontally for the remainder of the test. A self-drilling thermocouple and a pressure transducer on the chamber record the chamber's temperature and pressure throughout the test sequence, and locking pins hold the specimen in position during the BIO subsampling process (Santamarina et al., 2012a).

The set sequence involves four main stages: in stage one, the chamber is held at pressure and temperature conditions within the stability field while the chamber-pressurizing water surrounding the specimen is replaced with argon gas. Gas is introduced into the system until gas begins flowing through the fluid drain at the lowest point in the BIO chamber. This replacement is conducted under almost constant pressure inside the stability field; the argon gas environment preserves anaerobic conditions and prevents contamination during bio-subsampling for biologic studies.

In stage two, a front scraper rod is used to remove the first ~10mm thick layer at the front of the sediment to reach uncontaminated material. The scraper only cores into the central portion of the core face to avoid contamination from material along the cylindrical sides of the specimen.

In stage three, a sterile bio-reactor chamber is attached to the BIO chamber. These exchangeable bio-reactors have been previously autoclaved along with the additional culturing equipment, nutrients, and solutions for 40 minutes at 100kPa and 120°C. Uncontaminated sediment is scraped from the circular face of the pressure core, collected at the head of the scraper, and dropped into the sterile bio-reactor chamber. For this particular study, the

1
2
3
4 concentration of the NaCl solution used as a buffer is 8g/l, and the nutrient is Lysogeny Broth
5
6 (LB)-Miller formula consisting of 10g of tryptone, 5g of yeast extract, and 10g of NaCl in one
7
8 liter of distilled water. The LB-Miller formula is a complex nutrient that prompts the growth of
9
10 unspecified targets; it is selected for these studies to nourish the greatest breadth of
11
12 microorganisms.
13
14

15
16 In stage four, a dissociation and gas-production test is run to recover methane from the
17
18 hydrate-bearing pressure core specimen remaining in the BIO-chamber. To facilitate the
19
20 measurement of produced gas during dissociation, the chamber-pressurizing argon gas
21
22 surrounding the specimen is displaced, at pressure and prior to dissociation, with the laboratory-
23
24 simulated seawater used to pressurize the PCCTs throughout this study. Water is introduced into
25
26 the chamber from below, and the water injection continues until water is forced through the
27
28 uppermost port in the BIO chamber. To measure the volume of residual argon remaining in the
29
30 chamber, the chamber pressure is briefly increased while measuring the injected water volume
31
32 required for that pressure increase. Based on the volume response, the residual argon volume is
33
34 calculated. Expansion of the residual argon volume during depressurization-induced hydrate
35
36 dissociation is then calculated and subtracted from the overall volume expansion attributed to
37
38 methane release during dissociation.
39
40
41
42
43
44

45
46 Ideally, bio-reactor vessels will either be used to incubate specimens at pressure or will
47
48 be depressurized in an anoxic environment in which the incubation can be run. Once incubated,
49
50 the specimens can be examined using a staining or biomarker process to uncover the breadth and
51
52 function of the biologic communities present in the test sediment. Due to time limitations in this
53
54 study, the bio-reactor vessels were depressurized at different rates (to study the effect of the rate
55
56 in pressure change on bio-survivability) and cultured under aerobic conditions at different
57
58
59
60
61
62
63
64
65

temperatures to examine the dependence of microbial growth on temperature. Depressurizations from 7 MPa to atmospheric pressure are accomplished over one of three time intervals: 2 seconds (i.e., a fast depressurization rate), 1 minute, and 30 minutes (i.e., a slow depressurization rate). The spread-plate method is used to count cells, which grow on 60mm diameter Petri-dishes containing 15g of nutrients made of agar (15g/L) and the LB-Miller formula. Dilutions are 10^{-1} and 10^{-3} and the specimens are cultured in air at atmospheric pressure and temperatures of 4, 10, or 30°C. 4°C is approximately the temperature at which the cores were stored, 10°C is the room temperature during the study period and is close to the 12°C in situ temperature, and 30°C is the incubator temperature. During incubation, cell growth is recorded periodically by taking photographs.

4. Experimental Results

Cores 8P and 10P were taken from the upper third of the methane hydrate concentration zone (MHCZ), while core 20P was from the lower third of the MHCZ (see Fujii et al., 2015, and Inada et al., 2015, for additional coring interval information). Testing locations along each pressure core for all PCCT devices are shown in Fig. 2. Device-specific results are given below.

To identify hydrate-rich sections and choose locations for testing, the X-ray scans (Fig. 2) were paired with P-wave velocity data, both measured using the Pressure Core Analysis and Transfer System PCATS through the core liner (Suzuki et al., 2015). The DSC and ESC test location choices (red and yellow outlines in Fig. 2, respectively) were further restricted by their requirement of coherent sections. The BIO subsection was chosen from an adjacent section in which the sediment was transitioning to finer-grained material (grey outline in Fig. 2a).

Not all IPTC sensors were used in every measurement location. In core 8P, the electrical

conductivity probe failed prior to completing the core. The shear and strength probes were yielding effective stress-dependent results in low-hydrate-saturation sections, as observed in Core 10P (see sections 5.1 and 5.2). For efficiency, and given the absence of effective stress control in the IPTC, these probes were not used in regions of core 8P where the hydrate saturation was expected to be low. In core 10P, the penetrating strength and electrical conductivity probes were not used in the DSC specimen section to prevent probe penetration holes from compromising the shear strength of the DSC specimen.

4.1. Instrumented Pressure Testing Chamber

Fig. 2 shows the IPTC results and measurement locations for cores 8P and 10P, which include silty-sands with high-hydrate saturation (high S_h), and sandy- or clayey-silts with low-hydrate saturation (low S_h). The IPTC results illustrate the correlation between high S_h and high wave velocities, high strength and a large electrical conductivity drop with probe penetration into the specimen (See Table 1). The significant difference in stiffness of the high- S_h silty-sand sediment relative to the low- S_h sandy- and clayey-silts is apparent in the functionality of the IPTC probes:

Compressional Wave Velocity V_P : The P-wave pinducers produce an acoustic signal with a flat baseline and an abrupt first break when measurements are made in low- S_h sandy- and clayey-silts, indicating good contact between the pinducer and sediment. In high- S_h silty-sands, it is possible to press the pinducers against the specimen too hard, straining the transducer crystal to the point of generating a large-amplitude, low frequency baseline in the measured waveform from which the acoustic signal's first arrival must be picked.

Shear Wave Velocity V_S : The shear bender element blades are encased in a weak silicone cylinder, allowing the bender tip and front face of the silicone cylinder to contact a solid

specimen to impart a shear wave. In the relatively soft, low- S_h silts and clays, the silicone-encased bender elements can penetrate into the specimen, allowing the vibration of the sides of the cylindrical silicone to also produce a significant P-wave signal that obscures the S-wave arrival. S-wave velocity values in relatively soft, low- S_h sediments with no applied effective stress are likely to be overestimates. When pressed against hard, high- S_h material, the silicone-encased bender elements are too weak to penetrate the specimen without breaking. The circular front face of the probe produces relatively little P-wave energy, facilitating the S-wave arrival pick.

Strength S_u : Because there is no effective stress applied in the IPTC, the undrained shear strength S_u can be estimated from the force F_c measured by the cone penetrometer during penetration into the specimen via (Terzaghi et al., 1996):

$$S_u = \frac{q_c}{N_k} = \frac{F_c}{A_c \cdot N_k}. \quad (2)$$

The cone penetrometer tip resistance q_c is the ratio of the measured force F_c and the cone's cross-sectional area $A_c = 22 \text{ mm}^2$. The probe constant N_k is a function of soil type. Yun et al. (2011; 2006) took N_k to be ~ 10 in previous IPTC deployments, where hydrate appeared as lenses or nodules within fine-grained, relatively soft sediment into which the probe could be inserted its full $\sim 18\text{mm}$ travel.

In stiffer, high- S_h silty-sands from the Nankai Trough, the cone penetrometer's tip resistance rapidly increases during insertion, but then drops sharply before the full $\sim 18\text{mm}$ travel can be completed (Fig. 3). The sharp drop in tip resistance indicates brittle failure as the specimen fractures ahead of the cone. Brittle failure in high- S_h silty-sands is also observed in this study by Yoneda et al. (2015). Because cone penetrometers have not been used extensively in hydrate-bearing sands, the empirical parameter N_k is chosen based on the work of Beringen et al.

(1982), who found N_k to be in the range of 15-20 in their study of calcareous soils. Using the binding in calcareous soils as an analog for the strengthening behavior of gas hydrate in sands, N_k is also taken to be 15-20 in Table 1, which shows the shear strength S_u for the peak tip load in each measured location.

Electrical Conductivity σ_{el} : Regardless of sediment stiffness, the σ_{el} measurement initially decreases as the probe passes from the conductive core-pressurizing fluid into the core itself. An σ_{el} minimum is reached before σ_{el} begins increasing again with continued insertion. The largest σ_{el} range occurs for the high- S_h silty-sands. During the measurement of σ_{el} in core 8P at 190 cm, the 2.1mm-diameter probe was not strong enough to penetrate the specimen and bent during the attempted insertion.

4.2. Effective Stress Chamber

Stress-Volume Response: Fig. 4 shows the complete stress-volume change history of the two tested specimens. Prior to hydrate dissociation, core 8P is loaded up to an applied stress of 6MPa and then unloaded back to 3MPa in order to study the stress-volume response of hydrate-bearing sediments. The stress-volume responses of this specimen after hydrate dissociation is also measured using several loading-unloading cycles. Core 10P is initially loaded to an applied stress of 3MPa to conduct permeability and gas production tests. After the hydrate dissociates, core 10P is taken through loading-unloading cycles up to an applied stress of 9MPa. The stress-volume responses provide the compression index C_c and recompression index C_r (or swelling index) before and after hydrate dissociation for both cores (Table 2).

Water Permeability: Measured differential pressure Δu under a constant flux q oscillates with time (Fig. 5A), so the slope of Δu integrated over time (Fig 5B) is used as the “mean” differential pressure for computing water permeability based on Eq. 1. Water permeability

1
2
3
4 measurements are repeated for three to four different fluid fluxes q . Each water permeability
5
6 value is determined through the regression of a series of measured q vs. $\nabla P/\mu$ data (Fig. 5C).
7
8

9 Measured water permeability values for of the two tested specimens are summarized in
10
11 Table 2. The permeability increases ~ 5.3 times after hydrate dissociation for core 8P (initial
12
13 hydrate saturation $S_h = 0.18$), and ~ 47 times for core 10P (initial hydrate saturation $S_h = 0.74$).
14
15 The water permeability in hydrate-free sediment in both cases is similar (tenths of a Darcy, see
16
17 Table 2); this result highlights the blocking effect of hydrate, lowering the flow permeability of
18
19 its host sediments when water is the only mobile phase. This comparison can be made here
20
21 because the water permeability of hydrate-free sediments is measured at a pore pressure of
22
23 10MPa for which the specimen is essentially water-saturated. As the pore pressure is lowered
24
25 and residual gas expands, the system becomes more analogous to natural systems during gas
26
27 production from hydrate in which gas and water are both mobile and relative permeability must
28
29 be considered for water and gas (see section 5.4).
30
31
32
33
34

35
36 Gas Production: Gas production tests for both specimens are conducted using
37
38 depressurization. Although specimens are immersed in saline water throughout the collection,
39
40 storage, and testing process, measured P - T signatures evolved along the phase boundary for pure
41
42 water (Fig. 6A,B). This is likely due to hydrate crystals directly contacting newly produced fresh
43
44 water from hydrate dissociation. Fig. 6C,D shows the collected methane gas volume during the
45
46 production tests. The methane production rates in the first ~ 4 minutes for both specimens are
47
48 almost identical, probably constrained by the maximum flux through a small outlet (1/8-inch
49
50 stainless steel tubing with an inner diameter of 1.75mm). After ~ 250 seconds, the production rate
51
52 slows down for both specimens. Eventually, ~ 1.4 L methane is collected from core 8P and ~ 7.0 L
53
54 from core 10P.
55
56
57
58
59
60
61
62
63
64
65

Hydrate saturation S_h is computed from the amount of gas extracted as:

$$S_h = \frac{\frac{V_g}{nV_c} - \chi_{CH_4}}{c_0\beta - \chi_{CH_4}} \quad (3)$$

where V_g is the volume of gas collected at atmospheric pressure, n is the porosity, V_c is the specimen volume, χ_{CH_4} is the methane solubility in water, taken to be 2.52 and 2.55L/L for the 8P and 10P specimens respectively (Fujii et al., 2015, c_o is the cage occupancy, taken to be 0.9425 based on directly measuring a hydration number of 6.1 for the ATC-1 site (Kida et al., 2015), and $\beta = 172$ is the gas volume expansion factor (Kida et al., 2015).

4.3. Direct Shear Chamber

Stress-Volume Response: Fig. 7A shows the relaxation behavior after the initial load step in hydrate-bearing core 20P prior to dissociating the hydrate. It can be seen that the total relaxed strain during each displacement step gradually decreases. As with the ESC, the stress-volume response is also used to calculate the compression indices C_c and C_r (See Table 3).

Undrained Shear Strength & Friction Angle: Fig. 7B is the measured shear strength in hydrate-bearing core 20P, calculated as $\tau = H/2A - u_{cell}$ where H is the applied force on the horizontal loading piston and A is again the cross-sectional area of the core specimen. The shearing load is applied in displacement steps of one millimeter each, and the system is left to relax before the next displacement step. Blue squares and green dots represent measurements made before and after specimen relaxation, respectively. Fig. 8 shows the mobilized friction ϕ angle as a function of displacement during the shear-strength tests carried out before and after hydrate dissociation.

Compressional Wave Velocity: Fig. 9 shows P-wave signals collected during hydrate dissociation. To test whether gas bubbles produced during hydrate dissociation could be

responsible for the observed amplitude loss, the water saturation S_w is related to the P-wave attenuation using an empirical relationship in which the attenuation $1/Q_P$ is related to the waveform amplitude A by (Murphy, 1982; Santamarina et al., 2001):

$$A = A_1 e^{\frac{-1}{Q_P} \pi \cdot f \cdot V_P \cdot L}, \quad (5)$$

where f is the P-wave frequency, V_P is the P-wave velocity, and L is the specimen length. A_1 is the amplitude in the absence of attenuation, taken from the waveform at $u_{cell} = 5\text{MPa}$. The waveform amplitude at $u_{cell} = 4.7\text{MPa}$ is as expected for a gas saturation of 0.15.

Gas Production: The dissociation results for the procedure described in section 3.2 are collected in Table 3. Like the ESC results (Fig. 6A), dissociation in the DSC is observed to primarily follow the phase boundary for pure water.

4.4. BIO-Chamber

Table 4 contains the observed cell counts, growth times and specimen histories for the biological test sequence. We observe colony-forming units CFUs 43 hours after introducing nutrient solutions containing pressure core material to the agar plates incubated at 30°C. The largest colonies are on the 10^{-3} dilution plate supporting material from the fast depressurization, reaching 2 – 4.7mm in diameter within their ~2 day incubation period.

The remaining plates require 11 to 18 days to grow observable CFUs, and are observed for 32 days. Given these longer growth periods, final colony sizes range from 1 – 10mm in diameter. As shown in Fig. 10, the colonies have a variety of colors, sizes and edge types. This suggests a range of microbe species have been successfully cultured, even using oxic, atmospheric pressure conditions. Microbe identification is not included in this proof-of-concept study intended to show that culturable material can be acquired at pressure from pressure-core sediments.

Once the biologic samples are collected, the BIO chamber with the remaining hydrate-bearing sediment is depressurized to measure the specimen's hydrate content. Approximately three liters of gas were produced from this core 8P specimen. For a specimen porosity of 0.475, the average hydrate saturation in the specimen is 0.27. This value is an upper bound, because even though the presence of residual argon gas is accounted for in the calculation, an underestimate of this residual volume would overestimate the volume of methane produced by the dissociating hydrate and lead to an overestimate of the hydrate saturation.

5. Analyses and Discussion

Here we discuss PCCT results in the context of index properties, morphology-based analytical models and complimentary studies made during this MH21 Nankai Trough program. Correlations with modeling predictions and complimentary measurements provide insight into the in situ environment and the condition of the pressure cores themselves.

5.1. Small-strain properties: wave velocities and moduli

Velocity measurements have been used extensively to study the pore-scale distribution of hydrate within sands (e.g. Choi et al., 2014; Lee et al., 2013; Priest et al., 2009), estimate the small-strain bulk-, shear- and compressional-moduli as well as the Poisson's ratio (Helgerud et al., 2009; Lee et al., 2010a), and link seismic and well log measurements to in situ hydrate saturations (e.g. Fohrmann and Pecher, 2012; Hunter et al., 2011; Shankar and Riedel, 2014; Sheldner et al., 2012). In this study, compressional and shear wave velocities, V_p and V_s respectively, are collected at zero effective stress in the IPTC, and over a range of effective stresses in the DSC.

P- and S-wave Velocities at Hydrostatic Pressure (IPTC): The relationship between V_p

and V_S in the high- S_h silty-sand section of 8P (solid circles for V_P and V_S in Fig. 2) suggests the core contains non-cementing gas hydrates. Using the Gassmann formulation, we can estimate V_P from V_S (Santamarina et al., 2001; Santamarina and Ruppel, 2008):

$$V_P^2 = V_S^2 \left(\frac{1-\nu_{sk}}{1-2\nu_{sk}} + \frac{4}{3} \right) + \frac{1}{\rho_{mix}} \left(\frac{1-n}{B_m} + n \left(\frac{S_h}{B_h} + \frac{1-S_h}{B_w} \right) \right)^{-1}, \quad (6)$$

$$\rho_{mix} = \rho_m(1-n) + \rho_h n S_h + \rho_w n(1-S_h), \quad (7)$$

where ν is the Poisson's ratio for the sediment skeleton, n is the sediment porosity, ρ is density, and B is bulk modulus. The subscript "mix" refers to the sediment/hydrate/water mixture, and the subscripts m , h and w refer to the sediment minerals, hydrate and water, respectively. Following Santamarina and Ruppel (2010), we take ν_{sk} to be 0.1 for $S_h < 0.4$, and 0.2 for $S_h > 0.5$. Remaining parameters are taken from Table 5. From the measured V_S in the high- S_h silty-sand section of 8P, the predicted V_P from Eq. 6 within ~7% of the measured V_P (solid circles for V_P and V_S in Fig. 2, see also Table 1). Fig. 11 presents the measured V_P and V_S results in comparison with the four homogeneous hydrate morphology models described by Dvorkin et al. (2000), as well as the patchy hydrate morphology model by Berryman (1995). Measured wave velocities are in agreement with hydrate nucleation on mineral surfaces (low hydrate saturation), followed by growth into the pore space to eventually contact neighboring particles as hydrate becomes load bearing (high hydrate saturation).

In the low- S_h regions, Eq. 6 overpredicts the measured V_P by 15 - 27%. We attribute this to an overestimate of the measured shear velocities in the low- S_h regions due to P-wave energy obscuring the shear wave's first arrival. Even if the S-wave arrival were clear, because the IPTC is a hydrostatic chamber with no applied effective stress, the measured wave velocities in sections where $S_h < \sim 50\%$ are expected to be low relative to in situ values.

P-wave Velocity Dependence on Effective Vertical Stress (DSC): Hydrate-bearing cores

recovered from the subsurface inevitably experience unloading due to the removal of the overburden sediments during drilling. Only very limited stress, if any, may get locked within the sediments due to friction between the sediment and core liner. The DSC subsection of core 10P has a low $S_h \sim 0.13$, and V_P should depend strongly on effective stress for $S_h < \sim 50\%$ (Lee et al., 2010a). This stress dependence and the additional impact of long-term core storage in the absence of effective stress are evident when comparing V_P measurements made by the DSC, IPTC and the Pressure Core Analysis and Transfer System PCATS (Fig. 12).

As shown in Fig. 12, the expected V_P as the specimen undergoes the rapid unloading that would occur during collection (black squares) is higher than V_P measured using PCATS (Suzuki et al., 2015) one week after collecting core 10P (red star in Fig. 12) and V_P measured in the IPTC (red open circle in Fig. 12) 27 weeks after the PCATS measurement. The IPTC measures V_P by direct contact with the sediment, while PCATS measures V_P through the core liner. Although this difference in measurement technique likely causes a discrepancy between IPTC and PCATS results, we attribute the majority of the drop in V_P to core material relaxation and aging, as is demonstrated to occur in the Anelastic Strain Recovery (ASR) study (Nagano et al., 2015). Core relaxation and aging weakens the sediment fabric, further reducing the constrained stiffness, M , and hence the compressional wave velocity (Eq. 9, below). Restoring the applied stress $F/A - u_{cell}$ to the specimen in the DSC reconsolidates the core material, increasing V_P .

In Fig. 12, the shift from a rapidly increasing velocity with increasing applied stress (filled black circles in Fig. 12) to a slower increase suggests the specimen has returned to its in situ effective stress near 2.8MPa. The compressibility after hydrate dissociation (not shown), again shows a pre-consolidation value of 3MPa because the specimen is loaded during dissociation. The in situ σ_v' calculated from well log data for this core is estimated to be

2.32MPa from logging results of the 2011 Nankai Trough campaign.

Small-strain Moduli and Poisson's Ratio: From the PCCT wave velocity measurements and bulk density information, we estimate small-strain moduli and Poisson's ratio from the following relations (Mavko et al., 1998):

$$\text{Bulk stiffness: } = \rho_{mix} \cdot \left(V_P^2 - \frac{4}{3} V_S^2 \right), \quad (8)$$

$$\text{Constrained stiffness: } M = \rho_{mix} \cdot V_P^2, \quad (9)$$

$$\text{Shear stiffness: } G = \rho_{mix} \cdot V_S^2, \quad (10)$$

$$\text{Poisson's Ratio: } = \frac{1}{2} \cdot \frac{V_P^2 - 2V_S^2}{V_P^2 - V_S^2}. \quad (11)$$

These results are gathered in Table 6.

5.2. Large-strain properties: shear strength and friction angle

Shear Strength: In the high- S_h silty-sands in core 8P, the undrained shear strength S_u ranges from 1.7 to 1.9 MPa ($N_k = 20$) or 2.3 to 2.6 MPa ($N_k = 15$) for $S_h = .49$ and $.58$, respectively. The cone penetrometer results are in agreement with results measured in a triaxial apparatus by Yoneda et al. (2015) on a separate Nankai Trough core subsection. Agreement between strength measurements made with and without an applied stress indicates the sediment strength in the high- S_h silty-sands is controlled primarily by the presence of hydrate rather than the state of stress. This is not the case in the low- S_h sediment.

In low- S_h sediment, the undrained shear strength does not peak during probe insertion as it does in the high- S_h silty-sands. Instead, S_u rises until the penetrometer stops moving, having reached its full travel, after which the pore pressure relaxes (Fig. 3). Taking the maximum S_u as a lower bound on the in situ value, the measured strength in the low- S_h regions is at or below the expected strength of normally consolidated, uncemented clay given by (Mesri, 1989):

$$S_u = 0.22 \cdot \sigma'_v, \quad (12)$$

where the vertical effective stress, σ_v' , or overburden, is 2.27 MPa and 2.32 MPa for cores 8P and 10P, respectively (open circles for S_u in Fig. 2). Since there is no applied effective stress in the IPTC, $\sigma_v' = 0$, results below values predicted by Eq. 12 are expected, particularly for silty and sandy sediments.

The first direct shear measurement made on hydrate-bearing pressure core material was accomplished on the DSC subsection of core 20P, which has $S_h = 0.27$. The undrained peak shear result is within the range of published values given by Yoneda et al. (2015). The shear strength, measured with an applied stress of 3MPa, drops by $\sim 30\%$ after hydrate dissociation. The residual shear strength is much less sensitive to the presence of hydrate, decreasing only 14% after hydrate dissociation.

Mobilized Friction Angle: The peak friction angle drops by $\sim 37\%$, a significant response to hydrate dissociation, but the residual friction angle is much less sensitive to the presence of hydrate (Fig. 8) (Jung et al., 2012a). The peak and residual friction angles of core 20P after hydrate dissociation are likely controlled by the type and concentration of fine-grained sediment (fines) in the specimen (Fig. 8B). Although the impact of fines can be significant, the friction angle is not simply proportional to the fines content. For example, friction angles in most pure quartz sands are $38-40^\circ$, but increase up to $44-49^\circ$ when 5 wt% bentonite (smectite) is added, then decrease to $27-31^\circ$ when the bentonite content reaches 20 wt% (Mollins et al., 1999). Note in Fig. 8B that the DSC subsection of core 20P contains 12-15 wt% smectite, and 69-70 wt% quartzitic sands (Egawa et al., 2015).

5.3. Electrical conductivity

Relative to the saline water used to hold hydrostatic pressure on the measured cores, hydrate and sediment grains are electrical insulators. The measured conductivity drops as the

conductivity probe penetrates the core and the probe tip transitions from being surrounded by a conductive pressurization fluid to being increasingly surrounded by low-conductivity material. Conductivity can drop further in high- S_h silty-sands where conductive pore fluid is replaced by insulative gas hydrate (Lee et al., 2010b; Pearson et al., 1983; Spangenberg and Kulenkampff, 2006).

The measured electrical conductivity σ_{el} is a function of the pore fluid conductivity σ_f as well as the porosity n and properties of the host sediment. Archie's law (Archie, 1942):

$$\sigma_{el} = \frac{\sigma_f}{an^{-m}}, \quad (13)$$

is often used to predict conductivities in marine sediment, and can be used here to anticipate the measured conductivity drop as the probe passes from the salt water surrounding the specimen and into the sediment itself. Taking $\sigma_f = 3.09$ S/m as measured for the pressurizing water via a YSI conductivity meter, and the Archie parameters $\alpha = 1$ and either $m = 2-2.4$ from IODP studies of the Nankai Trough (Conin et al., 2011; Reuschle, 2011) or $m \sim 2$ based on estimates for hydrate-bearing sediments (Spangenberg, 2001), the predicted σ_s for core 8P, with a measured porosity, n , of ~ 0.49 , is $0.56 - 0.74$ S/m. For core 10P, with a measured porosity n of ~ 0.46 , the anticipated specimen σ_s is $0.48 - 0.66$ S/m. We do not observe such low conductivities because with continued electric probe insertion, the measured conductivity tends to stop decreasing and begin increasing. This increase, which is particularly noticeable in the high- S_h silty-sands, may be because the wider shoulder of the probe enters the sediment, spreading the sediment and allowing high-conductivity core-barrel water to penetrate to the probe tip, preventing the probe from measuring the true in situ conductivity. This process is consistent with our observations of brittle fracture during insertion of the cone penetrometer (Fig. 3).

5.4. Water Permeability

1
2
3
4 In natural hydrate systems, permeability governs fluid flow processes, affects methane
5 supply and thus methane hydrate accumulation and distribution, and determines gas production
6 efficiency. Permeability is thus one of the most important properties for natural hydrate-bearing
7 sediments, yet very little data is available, primarily due to experimental challenges in preventing
8 naturally-occurring hydrate from dissociating or dissolving during the collection, storage and
9 measurement process. Our study provides direct, soft-walled permeameter measurement of the
10 water permeability of naturally-occurring hydrate-bearing sediments held continuously within
11 the hydrate-stability field.
12
13
14
15
16
17
18
19
20
21
22

23 *S_h Effect on Water Permeability:* The presence of hydrate decreases sediment porosity,
24 increases hydraulic flow tortuosity, and thus, decreases the water permeability. The water
25 permeability of Nankai Trough cores is measured both with and without hydrates under in situ
26 stress and pore pressure conditions. The hydrate-saturation-dependent water permeability,
27 relative to the hydrate-free case, in Nankai Trough cores is shown in Fig. 13, together with four
28 morphology-based models. Results obtained in this study suggest hydrate grows into the pore
29 space and avoids grain contacts, as is also concluded from the wave velocity analysis (Fig. 11).
30
31
32
33
34
35
36
37
38
39
40

41 In the sand-rich, highly hydrate-saturated specimens ($S_h \geq 0.7$), permeability is largely
42 controlled and limited by the presence of hydrate; the ESC result of 6.12mD (core 10P-2, $S_h =$
43 0.74) is in good agreement with the shipboard permeability result of 19mD (core 18P-5, $S_h =$
44 0.7) measured using the PCATS triaxial system (Priest et al., 2015) and the 19.1mD (13P-2, $S_h =$
45 0.75) measured on a core preserved in liquid nitrogen (Konno et al. 2015). As expected, at lower
46 hydrate saturations ($S_h \leq 0.2$), permeability results vary dramatically between specimens in
47 response to variations in index properties such as sediment porosity and grain size (see Table 2
48 and Priest et al., 2015).
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65

Estimation of Relative Water Permeability in the Presence of Gas: The water permeability in core 8P in hydrate-free sediments after the production test is measured in the ESC under different fluid pressures and hence different water/gas saturations. Results, plotted in terms of water saturation S_w in Fig. 14, show the presence of gas reduces the water permeability, but less effectively than does the presence of hydrate itself (Fig. 13). The following assumptions are made to estimate the relative water permeability curve in this study: (1) the initial water saturation after hydrate dissociation is assumed to be 0.55, based on results of recoverable gas analysis for sediment with $S_h = 0.15 - 0.20$ (note: $S_h = 0.18$ in core 8P) (Jang and Santamarina, 2011); (2) the residual water saturation S_{rw} in this specimen is assumed to be the water content measured after complete depressurization of the specimen, which is 0.16; (3) the pressure dependent volume change of methane gas follows a modified Peng-Robinson equation of state (Stryjek and Vera, 1986). Pressure and volume are inversely related, meaning the higher the pressure, the smaller the gas volume and higher the water saturation; and (4) the loss of gas within the sediments during the permeability measurement is neglected. Note that permeability is measured at an extremely low constant total flux $q = 1\text{ml/min}$ and each measurement takes ~ 100 seconds, so the total loss of pore constituents (water and gas) during each measurement is $\sim 1.6\text{ml}$, which accounts for $<0.1\%$ by volume of the core's total pore space $\sim 2000\text{ml}$. As shown in Fig. 14, results are best fitted by an empirical exponential model (Brooks and Corey, 1964).

5.5. Thermal Properties

Although no thermal properties are directly measured in this PCCTs study, they can be assessed based on the total temperature drop ΔT of the BIO chamber and hydrate-bearing core during hydrate dissociation due to the endothermic heat H_{Diss} and the geometrical and geophysical properties of the system:

$$\Delta T = \frac{H_{Diss}}{\sum c_i \rho_i V_i} = \frac{L_h \rho_h V_h}{c_{ss} \rho_{ss} V_{ss} + c_q \rho_q V_q + c_w \rho_w V_w + c_h \rho_h V_h}, \quad (13)$$

where L is the latent heat, ρ is the density, V is the volume, and c is the specific heat capacity. Subscripts ss , q , w , and h represent the stainless steel, quartz, water, and hydrate components in the system. Table 7 lists the values from the BIO chamber as an example. The estimated temperature change due to hydrate dissociation in the BIO chamber is -0.19°C , which is in close agreement with the measured temperature change of -0.13°C . This agreement underscores the reliability of published thermal properties for gas hydrate.

5.6. Settlement during Gas Production: Fines Migration

The mechanical and hydrological properties of soils can be altered significantly if the soil grains themselves are mobilized. A critical concept, even for generally coarse-grained hydrate-bearing sands, is the impact of fines migrating within the sediment in the direction of fluid flow (i.e., toward the depressurization boundary) during gas production. Even at very low fines content, fracture formation and sediment collapse can occur where fines have been swept away. Conversely, permeability shutdown can occur where the fines collect downstream (Jung et al., 2012b). As shown in Fig. 4a, core settlement due to hydrate dissociation in core 8P, for which the depressurization boundary is sealed and escaping gas and fluid has to pass through a 4.7mm-thick porous stone, was only 0.09mm. This corresponds to a 0.02% vertical strain. In contrast, core 10P is depressurized at the top boundary, which is open to an upper, fluid-filled cavity in the chamber. This allows escaping gas, fluid, and sediment to migrate around, rather than through, the upper porous stone. Because the porous stone has a diameter of 50.8mm and the inner diameter of the core holder is 52.6mm, sediment could have a gap as wide as 1.8mm through which to pass. The total settlement caused by hydrate dissociation is 1.5mm, or 2.4% vertical strain for core 10P. At the end of the test, we found a significant volume of fine particles

1
2
3
4 had bypassed the porous stone and been flushed into the upper cavity in the chamber during gas
5
6 production from the top boundary. The sediment re-settled on top of the porous stone, forming a
7
8 nearly 5mm-thick mud cake. This result highlights that significant sediment deformation can be
9
10 induced by fines migration during gas production; sturdy, large-deformation resisting filters are
11
12 needed with an opening size less than ~5 times the migratory particle diameter (Valdes and
13
14 Santamarina, 2007).
15
16
17

18 19 **5.7. Biological test**

20
21 Cell counts in this study are lower than those of previous studies (Fig. 15); in part, this
22
23 may be due to factors related to the collection and measurement strategies. In this proof-of-
24
25 concept study, we counted microorganisms that survive depressurization and grow in an oxic
26
27 incubation environment. The differences in pressure, temperature and oxygen levels between the
28
29 in situ and laboratory conditions can be lethal to some species of microorganisms. Moreover,
30
31 even for the microbes that survive, less than 1% of the total number of microorganisms are
32
33 culturable (Madigan et al., 2009). In contrast, previous studies using staining methods are able to
34
35 include all types of microorganisms, both dead and alive.
36
37
38
39

40
41 Cultured microorganisms show temperature-dependent growth. The in situ sediment
42
43 temperature is ~12°C, so the cultured microorganisms like mesophiles, may prefer warmer
44
45 temperatures. There is no obvious dependence of colony-forming unit CFU count on
46
47 depressurization rate, with the trends observed at 10^{-1} dilution being opposite those observed for
48
49 10^{-3} dilution.
50
51
52
53

54 55 **6. Conclusions**

56
57 Pressure core characterization tools PCCTs allow the study of minimally-disturbed,
58
59
60
61
62
63
64
65

1
2
3
4 naturally-occurring hydrate-bearing sediments by maintaining the recovered specimens within
5
6 methane hydrate stability pressure and temperature conditions throughout the experimental
7
8 program. PCCT devices are designed to measure the most relevant parameters necessary for
9
10 borehole stability and gas production analyses and coupled hydro-thermo-chemo-mechanical
11
12 reservoir simulators.
13
14

15
16 A broad set of PCCTs was deployed for the first time in Japan for characterizing pressure
17
18 cores recovered from the Nankai Trough. Data interpretation benefited from complementary
19
20 index properties and mineralogy data, and parallel measurements made within separate PCCT
21
22 chambers and other devices. Salient observations follow:
23
24

25
26 The tested Nankai Trough sediments consist of clayey-silt and sandy-silt layers
27
28 interbedded with frequent occurrences of silty-sand layers. Hydrates concentrate in the silty-
29
30 sands, where pore-space hydrate saturations range between $S_h = 0.15$ and 0.74. In these layers,
31
32 compressional and shear-wave velocities are in agreement with hydrate nucleation on mineral
33
34 surfaces, followed by growth into the pore space to eventually connect grains together. In these
35
36 layers, cone penetrometer measurements of undrained shear strength S_u made with no effective
37
38 stress agree with triaxial shear tests made on core material of similar hydrate saturation: S_u scales
39
40 primarily with hydrate saturation rather than effective stress as hydrate binds the sediment
41
42 together in highly hydrate-saturated silty-sands. Both the penetrometer and electrical
43
44 conductivity measurements indicate these high S_h sediments are prone to fracturing in response
45
46 to probe penetration.
47
48
49
50
51

52
53 The clayey- and sandy-silt layers have hydrate saturations lower than $S_h \approx 0.30$; the
54
55 mechanical properties in these sediments are primarily controlled by effective stress and are
56
57 affected by clay content. The compressional wave velocity V_p measured at zero effective stress
58
59
60
61
62

1
2
3
4 in the Pressure Core Analysis and Transfer System PCATS one week after collecting the core is
5
6 slightly higher than the P-wave velocity measured at zero effective stress in the IPTC 28 weeks
7
8 after collection. The effects of expansion and relaxation-induced aging during storage at zero
9
10 effective vertical stress are reversed when the in situ effective vertical stress is reapplied.
11
12
13

14 The direct shear test of the hydrate-bearing clayey-sand specimen with $S_h = 0.27$ shows
15
16 that the peak friction angle drops by 30% after hydrate dissociation, yet, the residual friction
17
18 remains nearly unchanged. The low residual friction angle $\phi_{\text{res}} = 25^\circ$ confirms the strong effect
19
20 that clay content (in this case, 12-15 wt% smectite) can exert on shear resistance.
21
22
23

24 Temperature changes during dissociation in the BIO chamber can be adequately modeled
25
26 using published latent heat and specific heat capacity values for the different system components.
27
28 The agreement between measured and predicted thermal changes confirms the effectiveness of
29
30 simple mass-averaging for the analysis of thermal changes during dissociation.
31
32
33

34 Flexible-wall permeameter measurements are conducted on a hydrate-bearing pressure
35
36 core specimen before and after hydrate dissociation. The water permeability in the presence of
37
38 hydrate relative to that in the hydrate-free sediment k_r is a function of hydrate saturation as
39
40 predicted with physical models where hydrate forms preferentially in the largest pores. During
41
42 dissociation, the relative permeability of water can be related to the water saturation using the
43
44 model by Brooks and Corey (1964); the presence of gas during dissociation reduces water
45
46 permeability and limits the gain in permeability associated with the reduction in solid hydrate
47
48 mass.
49
50
51

52
53 Sediments contract during depressurization-driven dissociation. Volume contraction is
54
55 aggravated by fines migration and removal, i.e., fines production. Deliberate steps must be taken
56
57 to prevent fines migration/removal in laboratory tests as well as field production studies. Screens
58
59
60
61
62
63
64
65

1
2
3
4 must be able to accommodate large deformations; filters with an opening size less than ~5 times
5
6 the characteristic size of migratory particles should prevent loss of fines.
7
8

9 Uncontaminated, biologically-active samples can be successfully acquired for biological
10
11 studies under anaerobic conditions and within hydrate PT-stability. Specimens from the Nankai
12
13 Trough show the presence of viable cells; preliminary tests show no influence of
14
15 depressurization rate, but growth rates are temperature dependent.
16
17

18 The study of Nankai Trough specimens reported here documents the evolving
19
20 methodology for comprehensively characterizing hydrate-bearing sediments. Data gathered with
21
22 pressure core characterization tools play a central role, but additional information is gained from
23
24 borehole logging measurements (see other manuscripts in this special issue) and through post
25
26 decompression sediment analyses, including index properties. Finally, all data are considered
27
28 within the framework of physical models and correlations that reflect worldwide sediment data.
29
30 This methodology provides adequate estimates of parameters necessary for reservoir analyses
31
32 and simulators.
33
34
35
36
37
38
39
40
41

42 **Acknowledgements**

43
44 This study benefitted from the experimental assistance of Efthymios Papadopoulos
45
46 (Georgia Tech), David Mason, Emile Bergeron (USGS), as well as discussions with Yusuke Jin,
47
48 Masato Kida, Kosuke Egawa, and Takuma Ito (AIST). PCCTs were developed with funding to
49
50 Georgia Tech from the DOE/ Chevron Joint Industry Project (JIP), with additional funds from
51
52 the Joint Oceanographic Institutions, Inc. The JIP also funded the Georgia Tech participation in
53
54 Sapporo. USGS participation in Sapporo was funded through a technical assistance agreement
55
56 with Chevron (TAA-12-2135/CW928359). Some USGS developments on the IPTC were funded
57
58
59
60
61
62
63
64
65

1
2
3
4 under Interagency Agreement DE-FE0002911 with the U.S. Department of Energy, with
5
6 additional support from the U.S. Geological Survey. Core acquisition and Japanese participation
7
8 in this study was supported by the Research Consortium for Methane Hydrate Resources in
9
10 Japan (MH21 Research Consortium) to carry out Japan's Methane Hydrate R&D Program
11
12 conducted by the Ministry of Economy, Trade and Industry (METI).
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65

Tables

Table 1. IPTC core characterization. Measured results include compressional- and shear-wave velocity, V_P and V_S , respectively, undrained shear strength S_u and electrical conductivity σ_{el} . Porosity n and hydrate saturation S_h assume hydrate is concentrated in the silty-sands^a. Saturations in finer-grained material^b assume hydrate is uniformly distributed within the measured section, and likely overestimates the location-specific S_h . Predictions for V_P based on the measured V_S and Eq. 6 are given for the high-hydrate-saturation locations^c.

Core	Location [cm]	n [-]	S_h [-]	V_P [m/s]	V_S [m/s]	S_u [MPa]	σ_{el} [S/m]
8P	217.38	0.489	0.33 ^b	1500	< 444	0.153-0.204	2.88-3.09
	203.79	0.448	0.58 ^a	2760	956	1.923-2.564	2.19-3.09
				2575 ^c			
	190.20	0.448	0.49 ^a	2302	861	1.703-2.270	–
				2373 ^c			
10P	176.61	0.475	0.27 ^b	1521	–	0.618-0.824	–
	163.02	0.475	0.27 ^b	1511	–	0.469-0.626	–
	149.43	0.475	0.27 ^b	1448	–	0.082-0.109	–
	143.13	0.461	0.15 ^b	1513	< 488	0.019-0.026	2.96-3.09
	129.54	0.461	0.15 ^b	1582	< 532	0.285-0.380	2.77-3.09
	115.95	0.461	0.15 ^b	1587	< 504	–	–

Table 2. ESC measured results, before, during and after hydrate dissociation. Water permeability is given in milli-Darcy (mD). To convert to m^2 , multiply by 9.87×10^{-16} .

Properties		Core 8P	Core 10P
Pre-dissociation	Compression index, C_c [-]	0.608	0.407
	Recompression index, C_r [-]	0.065	0.047
	Water permeability, k [mD]	128.28	6.12
	Coef. of volume compressibility, m_v [m^2/MN]	0.06	0.012
	Coef. of consolidation, c_v [m^2/s]	5.88×10^{-7}	7.34×10^{-7}
	Initial height, H_0 [mm]	45.25	71.0
Dissociation	Volume of extracted gas, V_g [cc]	1366	6952
	Hydrate saturation, S_h [-]	0.18	0.74
	Settlement, δ [mm]	0.09	1.5
	Axial strain change during dissociation, $\Delta \varepsilon_z$ [-]	2×10^{-4}	2.4×10^{-2}
Post-dissociation	Compression index, C_c [-]	0.250	0.109
	Recompression index, C_r [-]	0.034	0.023
	Water permeability, k [mD]	674.23	289.98
	Coef. of volume compressibility, m_v [m^2/MN]	0.005	0.004
	Coef. of consolidation, c_v [m^2/s]	3.47×10^{-5}	2.7×10^{-5}
	Specimen final height, H_f [mm]	33.6	60.2

Table 3. DSC measured results before, during and after hydrate dissociation.

Properties		8P	10P	20P
Pre-dissociation	Coef. of volume compressibility, m_v [m ² /MN]	0.108	0.083	0.038
	Coef. of consolidation, c_v [m ² /s]	8.8×10^{-7}	4.4×10^{-6}	9.0×10^{-7}
	Peak shear strength, τ [MPa] @ $\sigma' = 3$ MPa			2.20
	Peak friction angle, ϕ_{peak} [°]			36
	Residual friction angle, ϕ_{res} [°]			27
	Wave velocity (@ $\sigma' = 3$ MPa), V_p [m/s]		1890	
	Initial height, H_0 [mm]	60.0	117	160
Dissociation	Volume of extracted gas, V_g [cc]	2620	4330	5030
	Hydrate saturation, S_h [-]	0.21	0.15	0.27
	Settlement, δ [mm]	2.5	4.58	3.68
	Axial strain during dissociation, ε_v [-]	4.8×10^{-2}	4.5×10^{-2}	2.3×10^{-2}
Post-dissociation	Compression index, C_c [-]	0.39	0.13	0.14
	Recompression index, C_r [-]	0.018	0.001	0.011
	Peak shear strength, τ [MPa] @ $\sigma' = 3$ MPa			1.36
	Peak shear strength, τ [MPa] @ $\sigma' = 7.6$ MPa			3.69
	Peak friction angle, ϕ_{peak} [°]			27
	Residual friction angle, ϕ_{res} [°]			25

Table 4. BIO measurements of depressurization rate and incubation temperature effects on the number of observed colony-forming units per gram of specimen collected (CFU/g).

Temperature [°C]		4			10			30		
Duration of depressurization from 7MPa to 0.1 MPa		30min	1min	2sec	30min	1min	2sec	30min	1min	2sec
Colony-forming time [days]		N/A	11	11	18	11	11	11	2	2
Total cell count [CFU/g]	10 ⁻¹ dilution	N/A	2864	8901	3560	4687	11539	20174	4948	15372
	10 ⁻³ dilution	N/A	N/A	24727	N/A	78125	45333	N/A	520834	32969

Table 5. Constituent properties for small-strain wave velocity and stiffness analysis (Waite et al., 2009).

Components	Density (kg/m ³)	Bulk Moduli (GPa)
Quartz	2650	36.6
Seawater	1000	2.25
Methane Hydrate	925	8.41

Table 6. Bulk small-strain stiffnesses and Poisson's ratio, calculated from Eqs. 7-10.

Core	Location [cm]	n []	S_h []	ρ_{mix} [kg/m ³]	V_p [m/s]	V_s [m/s]	B [GPa]	M [GPa]	G [GPa]
8P, IPTC	203.79	0.448	0.58	1838	2760	956	11.76	14.00	1.68
	190.20	0.448	0.49	1838	2302	861	7.92	9.74	1.36
10P, DSC	102-122	0.461	0.15	1851	1900	-	-	6.68	-

Table 7. Constituent properties for thermal property analysis.

Property	Stainless steel, ss^a	Quartz, q	Water, w^b	Hydrate, h
Latent heat, L [kJ/kg]				435 ^c
Density, ρ [kg/m ³]	8000	2650	1000	929 ^d
Specific heat, c [kJ/kg/K]	0.5	0.73	4.2	2.03 ^d
Volume, V [m ³]	0.008592245	0.00016	0.001018	0.0000181

^a *ASM International* (2002)^c *Handa* (1986)^b *Weast* (1987)^d *Waite et al.* (2007)

Figure Captions

Figure 1. Pressure Core Characterization Tools PCCTs, configured for 50.8-mm-diameter Nankai Trough cores. (A) Instrumented Pressure Testing Chamber IPTC; (B) Effective Stress Chamber ESC; (C) Direct Shear Chamber DSC; (D) Biological Sampling Cell BIO. Additional details are provided in Santamarina et al., (2012a; 2012b). Ball-valve closures are in deep red, flange clamps are in green, thermocouples are shown as thin red lines. Measurement sensors shown: compressional- and shear-wave velocity, V_P and V_S , respectively; undrained shear strength S_u ; electrical conductivity σ_{el} ; specimen length changes are measured with linear voltage displacement transducers LVDT.

Figure 2. Pressure Core Analysis and Transfer System PCATS X-ray core scans (Suzuki et al., 2015), aligned with Pressure Core Characterization Tool measurement locations and Instrumented Pressure Testing Chamber IPTC results. Shepard-classification soil descriptions are from Ito et al. (2015). (A) Core 8P was tested in the IPTC (orange arrows mark measurement locations), then subsampled for testing in the Biologic Chamber BIO, Direct Shear Cell DSC, and Effective Stress Cell ESC. IPTC results for compressional wave velocity V_P , shear wave velocity V_S , undrained shear strength S_u , and electrical conductivity σ_{el} , are given in panels B-E. Solid circles represent locations with high hydrate saturation silty-sands, open circles represent locations with low hydrate saturation sediment, primarily clayey-silt. Solid lines represent expected baseline values for hydrate-free sediment. See Table 1 for IPTC results. (F) Core 10P was tested in the IPTC, then subsampled for testing in the DSC and ESC. IPTC results are given in panels G-J. (K) Core 20P was subsampled for testing in the DSC.

Figure 3. IPTC cone penetrometer probe response difference between locations with high hydrate saturations (high S_h , blue solid circles), and low hydrate saturations (low S_h , green open circles). High S_h locations tend to fracture during probe insertion, as indicated by the sudden post-peak softening (~7.0-mm insertion when peak strength was recorded). In low- S_h locations, the penetrometer reaches full insertion (17.6-mm insertion) and load relaxation occurs only when the probe is stationary.

Figure 4. Evolution of specimen void ratio during the complete loading history for ESC core 8P (A) and core 10P (B). Significant specimen shortening during dissociation in core 10P relative to that observed in core 8P is due to fines migration through gaps around the specimen's upper porous stone. The lower stone through which core 8P was vented has a sealed perimeter. Arrows indicate the experimental path in time.

Figure 5. Water permeability measurement in the ESC for core 8P before dissociation. (A) Measured differential pressure versus time during pore fluid extraction under constant flux, with effective pressure $\sigma_v' = 3\text{MPa}$, pore pressure $u = 10\text{MPa}$. (B) The average differential pressure is determined using the slope of the integration of the measured differential pressure in A to cancel random noise. (C) Permeability is determined based on measurements under several different fluxes. The best fit of the q versus P/μ slope gives the final permeability value.

Figure 6. Gas production test at an effective stress of 3MPa in the ESC. Pressure and temperature changes during dissociation of core 8P (A) and 10P (B). The solid line is the phase boundary for methane hydrate in pure water and the dashed line is the phase boundary in

seawater. Stability curves from Sloan and Koh (2007). Dissociation occurs along the freshwater stability curve, likely in response to dissociating hydrate being bathed in the freshwater generated as hydrate dissociates. Evolution along the freshwater stability curve is more noticeable in core 8P, which is depressurized from its base so dissociating fluids flow over the ESC thermocouple. Core 10P is depressurized at the specimen top, so dissociating fluids flow away from the thermocouple, reducing the measurement sensitivity to temperature changes. Gas volume collected during the dissociation for core 8P (C) and 10P (D). Dissociation occurs too rapidly to establish thermal or chemical equilibrium with the surrounding material or pore water, leading to temperatures depressed close to 0°C and fresh water concentrations large enough to control dissociation conditions.

Figure 7. Typical results from the DSC. (A) Relaxation test after first loading; (B) shear test: blue dots show peak shear before relaxation, green dots show shear strength after shear relaxation. Dotted box indicates the initial “seating effect” as the specimen responds to the axial load contacting the non-parallel top and bottom faces of the specimen.

Figure 8. Mobilized friction angle, ϕ , measured in the DSC before (A) and after (B) hydrate dissociation in Core 20P. Blue squares and green circles, respectively, represent measurements made before and after the specimen relaxes after each displacement (see **Fig. 7B**). Hydrate significantly alters the friction angle when measured immediately after a displacement (blue squares), but values measured after the system relaxes (green circles) are controlled primarily by mineralogy. The specimen contains 12-15 wt% smectite (Egawa et al., 2015). For reference,

crosses are plotted for measurements on dry mixtures of quartz sand and 20 wt% smectite (Mollins et al., 1999).

Figure 9. P-waveforms measured in the DSC for Core 10 while depressurizing the cell to cause dissociation. Depressurization progresses from top to bottom in the figure. Waveforms are normalized by their specimen lengths to cancel the effects of specimen shortening during dissociation. Black curves are measured while the specimen is within the hydrate stability conditions, red curves are measured after u_{cell} is reduced below the hydrate stability pressure at 6°C. Amplitude loss for pressures below the hydrate stability pressure (red curves) is in agreement with empirical results for the addition of gas to an otherwise water-saturated porous material (Murphy, 1982; Santamarina et al., 2001).

Figure 10. Sampling of the biological diversity in core 8P using the BIO chamber. Images are taken after culturing for 32 days at atmospheric pressure, under oxic conditions. Top row cultured at 4°C, bottom row cultured at 30°C. Depressurization rates and dilutions vary: (A) 7MPa/2 sec, 10^{-3} dilution; (B) 7MPa/2 sec, 10^{-1} dilution; (C) 7MPa/1 min, 10^{-3} dilution; (D) 7MPa/30 min, 10^{-1} dilution. Variety in colony color and edge morphology likely indicate the presence of several microbial species. Microbial identification is not part of the BIO chamber's specimen acquisition "proof-of-concept" test.

Figure 11. (A) Compressional V_P and (B) Shear V_S wave velocity in hydrate-bearing sands. Under gas-limited conditions in marine sands, hydrate nucleates and initially grows into the pore space (i.e. "pore filling"), to eventually become "load bearing" as the hydrate volume in the pore increases (Dvorkin et al., 2000; Yun et al., 2005). IPTC measurements in a high S_h section of

core 8P (filled circles), and DSC measurement in a low S_h section of core 10P (filled diamond in A) can all be fitted by the model that assumes hydrate is homogeneously distributed as a load-bearing component of the sediment (Dvorkin et al., 2000). Schematics show grey, circular sand grains and black hydrate mass. Cementation curves are also calculated from Dvorkin et al. (2000), and curves for sand with spherical hydrate patches are calculated from Berryman (1995). Theoretical curve color scheme is the same in A and B. are best fit by assuming hydrate is homogeneously distributed as a load-bearing component of the sediment. Schematics show grey, circular sand grains and black hydrate mass. Curves for sand with spherical hydrate patches are calculated from, remaining curves are calculated from. Theoretical curve color scheme is the same in A and B.

Figure 12. Dependence of compressional wave velocity V_P on effective stress in the DSC specimen from core 10P. Pressure cores are collected and stored with no effective stress. The PCATS measurement of V_P (red star, Suzuki et al., 2015) one week after collecting core 10P shows evidence of V_P reduction from in situ values that is more significant than the reduction expected from rapid removal of the effective stress (filled black squares, measured in DSC). The core expansion, or aging observed by Nagano et al. (2015), is likely responsible for the remaining drop in V_P apparent in the PCATS measurement. Additional expansion and unloading at sediment grain contacts occurs during the subsequent 27 weeks of storage at zero effective stress, but within the hydrate stability conditions, causing an additional 5% drop in V_P (IPTC measurement, co-located with PCATS measurement, red circle). DSC reapplication of a vertical effective stress to the specimen reverses the unloading and aging effects on V_P (filled black

circles). The break in slope near 2.8MPa applied stress is in good agreement with the in situ vertical effective stress, estimated to be 2.32MPa.

Figure 13. Measured permeability in hydrate-bearing sediment relative to the permeability in hydrate-free sediment (filled circle at $S_h = 0.18$ for core 8P, and 0.74 for core 10P). Theoretical trends are shown for several possible hydrate morphologies (schematics have sediment shown in grey, hydrate in black). Results suggest hydrate is primarily forming as a non-cementing pore-fill (model in Kleinberg et al., (2003)), as can be expected if hydrate initially forms in the largest pores through which pore fluid advection is strongest. If hydrate is assumed to be distributed in patches throughout the sediment, the relative permeability is overpredicted in the spherical-grain case (Berryman, 1995), but is in agreement with a modified Kozeny-Carman approach in which the pore space is assumed to be a network of water-filled capillaries (white segments) with hydrate forming a patchy filling of the larger-diameter capillaries (black segments, model in Dai and Seol, (2014)).

Figure 14. Permeability measurements for core 8P in the ESC after hydrate dissociation (blue circles), while the specimen pore space contains gas and the water saturation $S_w < 1$. Permeability measurements are made at different pore pressure levels as the specimen is repressurized with water to $u_{cell} = 10\text{MPa}$ at 18°C to resaturate the specimen without reforming hydrate. The measured residual water saturation after depressurization for this specimen is $S_{rw} = 0.16$. Relative permeability k_{rw} dependence on S_w during repressurization can be estimated (solid curve) with the Brooks and Corey (1964) model, where the best fit curve is nearly identical to the prediction using the parameters from Kurihara et al., (2011).

Figure 15. Dependence of cell count on depth from the ground surface. Cells can only occupy pores larger than the cell size; the probability of finding pores of viable host size decreases with depth due to compaction, and with grain specific surface S_s due to the presence of fine particles in the pore space (Phadnis and Santamarina, 2011). Nankai Trough data from other studies are included (Kormas et al., 2003; Li et al., 1999; Mills et al., 2012; Newberry et al., 2004; Reed et al., 2002). The shaded region represents results from other locations compiled in Parkes et al. (1994; 2009). Cell counts in this study were taken from a BIO specimen with $S_s = 19.4 \text{ m}^2/\text{g}$, but the cell counts include only live, culturable aerobes, so a reduced cell count is expected relative to theoretical estimates (dashed curves) and compiled data (symbols and shaded region), which all include living and dead organisms. Compiled data points are obtained based either on cell weight (x) or a staining method (solid diamonds).

References

- Archie, G.E., 1942. The electrical resistivity log as an aid in determining some reservoir characteristics. Transactions of The American Institute of Mining, Metallurgical, and Petroleum Engineers 146, 54-62.
- ASM International Materials Properties Database Committee, 2002. ASM Ready Reference: Thermal Properties of Metals, F. Cervera (ed.). ASM International, Materials Park, OH.
- Beringen, F.L., Kolk, H.J., Windle, D., 1982. Cone penetration and laboratory testing in marine calcareous sediments, in: Demars, K.R., Chaney, R.C. (Eds.), Geotechnical Properties, Behavior, and Performance of Calcareous Soils. American Society for Testing and Materials, pp. 179-209.
- Berryman, J.G., 1995. Mixture theories for rock properties, in: Ahrens, T.J. (Ed.), A Handbook of Physical Constants. American Geophysical Union, Washington, D.C., pp. 205-228.
- Brooks, R.H., Corey, A.T., 1964. Hydraulic properties of porous media. Colorado State University, Hydrology Papers, 24 pp.
- Choi, J.-H., Dai, S., Cha, J.-H., Seol, Y., 2014. Laboratory formation of noncementing hydrates in sandy sediments. Geochemistry Geophysics Geosystems 15, doi:10.1002/2014GC005287, 1648-1656.
- Conin, M., Henry, P., Bourlange, S., Raimbourg, H., Reuschlé, T., 2011. Interpretation of porosity and LWD resistivity from the Nankai accretionary wedge in light of clay physicochemical properties: Evidence for erosion and local overpressuring. Geochemistry, Geophysics, Geosystems, 12(3), Q0AD07, doi:10.1029/2010GC003381, 17 p.
- Dai, S., Santamarina, J.C., 2014. Sampling disturbance in hydrate-bearing sediment pressure cores: NGHP-01 expedition, Krishna–Godavari Basin example. Marine and Petroleum Geology 58, doi: 10.1016/j.marpetgeo.2014.07.013, 178-186.
- Dai, S., Seol, Y., 2014. Water permeability in hydrate-bearing sediments: A pore-scale study. Geophysical Research Letters 41(12), doi:10.1002/2014GL060535, 4176–4184.
- Dvorkin, J., Helgerud, M.B., Waite, W.F., Kirby, S.H., Nur, A., 2000. Introduction to physical properties and elasticity models, in: Max, M.D. (Ed.), Natural Gas Hydrate In Oceanic and Permafrost Environments. Kluwer Academic Publishers, Dordrecht, Netherlands, pp. 245-260.
- Egawa, K., Nishimura, O., Izumi, S., Fukami, E., Jin, Y., Kida, M., Konno, Y., Yoneda, J., Ito T, Suzuki, K., Nakatsuka, Y. and Nagao, J. 2015. Bulk sediment mineralogy of gas hydrate reservoir at the East Nankai offshore production test site, Marine and Petroleum Geology, in this issue.
- Fohrmann, M., Pecher, I.A., 2012. Analysing sand-dominated channel systems for potential gas-hydrate-reservoirs using an AVO seismic inversion technique on the Southern Hikurangi Margin, New Zealand. Marine and Petroleum Geology 38, 19-34.
- Fujii, T., Noguchi, S., Takayama, T., Suzuki, K., Yamamoto, K., Saeki, T., 2013. Site selection and formation evaluation at the 1st offshore methane hydrate production test site in the Eastern Nankai Trough, Japan, 75th EAGE Conference, London, UK, paper B10.
- Fujii, T., Saeki, T., Kobayashi, T., Inamori, T., Hayashi, M., Takano, O., Takayama, T., Kawasaki, T., Nagakubo, S., Nakamizu, M., Yokoi, K., 2008. Resource assessment of methane hydrate in the eastern Nankai Trough, Japan, in: Englezos, P., Ripmeeser, J. (Eds.), Proceedings of the 6th International Conference on Gas Hydrates, Vancouver, Canada, Paper 5673, 12 p.
- Fujii, T., Suzuki, K., Takayama, T., Tamaki, M., Komatsu, Y., Konno, Y., Yoneda, J., Yamamoto, K. and Nagao, J. (2015): Geological settings and characterization of methane hydrate reservoir distributed on the Daini-Atsumi knoll in the Eastern Nankai Trough, Japan., Marine and Petroleum Geology, in this issue.
- Handa, Y.P., 1986. Compositions, enthalpies of dissociation, and heat capacities in the range 85 to 270 K for clathrate hydrates of methane, ethane, and propane, and enthalpy of dissociation of isobutane hydrate, as determined by a heat-flow calorimeter. Journal of Chemical Thermodynamics 18, 915-921.

- 1 Helgerud, M.B., Waite, W.F., Kirby, S.H., Nur, A., 2009. Elastic wave speeds and moduli in
2 polycrystalline ice Ih, sI methane hydrate, and sII methane-ethane hydrate. *Journal of Geophysical*
3 *Research* 114, B02212, doi:10.1029/2008JB006132, 11p.
- 4 Hunter, R.B., Collett, T.S., Boswell, R., Anderson, B.J., Digert, S.A., Pospisil, G., Baker, R., Weeks, M.,
5 2011. Mount Elbert Gas Hydrate Stratigraphic Test Well, Alaska North Slope: Overview of scientific
6 and technical program. *Marine and Petroleum Geology* 28, 295-310.
- 7 Inada, N. and Yamamoto, K., 2015: Data Report: Pressure coring and shipboard core handling in the
8 Nankai Project, *Marine and Petroleum Geology*, in this issue.
- 9 Ito, T., Komatsu, Y., Fujii, T., Suzuki, K., Egawa, K., Nakatsuka, Y., Konno, Y., Yoneda, J., Jin, Y.,
10 Kida, M., Nagao, J. and Minagawa, H., 2015: Lithological features of hydrate-bearing sediments and
11 their relationship with gas hydrate saturation in the eastern Nankai Trough, Japan, *Marine and*
12 *Petroleum Geology*, in this issue.
- 13 Jang, J., Santamarina, J.C., 2011. Recoverable gas from hydrate-bearing sediments: Pore network model
14 simulation and macroscale analyses. *Journal of Geophysical Research: Solid Earth* (1978–2012) 116.
- 15 Jung, J.-W., Santamarina, J.C., Soga, K., 2012a. Stress-strain response of hydrate-bearing sands:
16 Numerical study using discrete element method simulations. *Journal of Geophysical Research* 117,
17 doi:10.1029/2011jb009040, 12 p.
- 18 Jung, J.W., Jang, J., Santamarina, J.C., Tsouris, C., Phelps, T.J., Rawn, C.J., 2012b. Gas Production from
19 Hydrate-Bearing Sediments: The Role of Fine Particles. *Energy & Fuels* 26, 480-487.
- 20 Kida, M., Jin, Y., Watanabe, M., Konno Y., Yoneda, J., Egawa, K., Ito, T., Nakatsuka, Y., Suzuki, K.,
21 Fujii, T. and Nagao, J., 2015: Chemical and crystallographic characterizations of natural gas hydrates
22 recovered from a production test site in the Eastern Nankai Trough, *Marine and Petroleum Geology*, in
23 this issue.
- 24 Kleinberg, R.L., Flaum, C., Griffin, D.D., Brewer, P.G., Malby, G.E., Peltzer, E.T., Yesinowski, J.P.,
25 2003. Deep sea NMR: Methane hydrate growth habit in porous media and its relationship to hydraulic
26 permeability, deposit accumulation, and submarine slope stability. *Journal of Geophysical Research*
27 108(B10), 2508, doi:10.1029/2003JB002389, 17p.
- 28 Konno, Y., Yoneda, J., Egawa, K., Ito, T., Jin, Y., Kida, M., Suzuki, K., Fujii, T. and Nagao, J., 2015:
29 Permeability of sediment cores from methane hydrate deposit in the Eastern Nankai Trough, *Marine*
30 *and Petroleum Geology*, in this issue.
- 31 Kormas, K.A., Smith, D.C., Edgcomb, V., Teske, A., 2003. Molecular analysis of deep subsurface
32 microbial communities in Nankai Trough sediments (ODP Leg 190, Site 1176). *Fems Microbiology*
33 *Ecology* 45, 115-125.
- 34 Kurihara, M., Sato, A., Funatsu, K., Ouchi, H., Masuda, Y., Narita, H., Collett, T.S., 2011. Analysis of
35 formation pressure test results in the Mount Elbert methane hydrate reservoir through numerical
36 simulation. *Marine and Petroleum Geology* 28, 502-516.
- 37 Lee, J.Y., Francisca, F.M., Santamarina, J.C., Ruppel, C., 2010a. Parametric study of the physical
38 properties of hydrate-bearing sand, silt, and clay sediments: 2. Small-strain mechanical properties.
39 *Journal of Geophysical Research* 115(B11), B11105, doi: 10.1029/2009jb006670, 11p.
- 40 Lee, J.Y., Jung, J.W., Lee, M.H., Bahk, J.J., Choi, J., Ryu, B.J., Schultheiss, P., 2013. Pressure core based
41 study of gas hydrates in the Ulleung Basin and implication for geomechanical controls on gas hydrate
42 occurrence. *Marine and Petroleum Geology* 47, 85-98.
- 43 Lee, J.Y., Santamarina, J.C., Ruppel, C., 2010b. Parametric study of the physical properties of hydrate-
44 bearing sand, silt, and clay sediments: 1. Electromagnetic properties. *Journal of Geophysical Research*
45 115(B11), B11104, doi:10.1029/2009JB006669, 9 p.
- 46 Li, L., Guenzennec, J., Nichols, P., Henry, P., Yanagibayashi, M., Kato, C., 1999. Microbial diversity in
47 Nankai Trough sediments at a depth of 3,843 m. *Journal of Oceanography* 55, 635-642.
- 48 Lu, W., Chou, I.M., Burruss, R.C., 2008. Determination of methane concentrations in water in
49 equilibrium with sI methane hydrate in the absence of a vapor phase by in situ Raman spectroscopy.
50 *Geochimica et Cosmochimica Acta* 72, 412-422.

- Madigan, M.T., Martinko, J.M., Dunlap, P.V., Clark, D.P., 2009. Brock Biology of Microorganisms, 12th ed. Pearson Education, Inc.
- Matsumoto, R., Tomaru, H., Lu, H., 2004. Detection and Evaluation of Gas Hydrates in the Eastern Nankai Trough by Geochemical and Geophysical Methods. *Resource Geology* 54, 53-67.
- Mavko, G., Mukerji, T., Dvorkin, J., 1998. The rock physics handbook: Tools for seismic analysis in porous media. Cambridge University Press, Cambridge.
- Mesri, G., 1989. A Reevaluation of $S_u = 0.22\sigma'_p$ Using Laboratory Shear Tests. *Canadian Geotechnical Journal* 26, 162-164.
- Mills, H.J., Reese, B.K., Shepard, A.K., Riedinger, N., Dowd, S.E., Morono, Y., Inagaki, F., 2012. Characterization of metabolically active bacterial populations in subseafloor Nankai Trough sediments above, within, and below the sulfate-methane transition zone. *Frontiers in Microbiology* 3, doi: 10.3389/fmicb.2012.00113, 12p.
- Mollins, L.H., Stewart, D.I., Cousens, T.W., 1999. Drained strength of bentonite-enhanced sand. *Geotechnique* 49, 523-528.
- Murphy, W.F., 1982. Effects of Partial Water Saturation on Attenuation in Massillon Sandstone and Vycor Porous-Glass. *Journal of the Acoustical Society of America* 71, 1458-1468.
- Nagano, Y., Lin, W. and Yamamoto, K., 2015: In-situ stress analysis using the anelastic strain recovery (ASR) method at the first offshore gas production test site in the eastern Nankai Trough, Japan, *Marine and Petroleum Geology*, in this issue.
- Newberry, C.J., Webster, G., Cragg, B.A., Parkes, R.J., Weightman, A.J., Fry, J.C., 2004. Diversity of prokaryotes and methanogenesis in deep subsurface sediments from the Nankai Trough, Ocean Drilling Program Leg 190. *Environmental Microbiology* 6, 274-287.
- Parkes, R.J., Cragg, B.A., Bale, S.J., Getliff, J.M., Goodman, K., Rochelle, P.A., Fry, J.C., Weightman, A.J., Harvey, S.M., 1994. Deep Bacterial Biosphere in Pacific-Ocean Sediments. *Nature* 371, 410-413.
- Parkes, R.J., Sellek, G., Webster, G., Martin, D., Anders, E., Weightman, A.J., Sass, H., 2009. Culturable prokaryotic diversity of deep, gas hydrate sediments: first use of a continuous high-pressure, anaerobic, enrichment and isolation system for subseafloor sediments (DeepIsoBUG). *Environmental Microbiology* 11, 3140-3153.
- Pearson, D.F., Halleck, P.M., McGuire, P.L., Hermes, R., Matthews, M., 1983. Natural Gas Hydrate Deposits: A Review of In Situ Properties. *Journal of Physical Chemistry* 87(21), 4180-4185.
- Phadnis, H.S., Santamarina, J.C., 2011. Bacteria in sediments: pore size effects. *Geotechnique Letters* 1, doi: 10.1680/geolett.11.00008, 91-93.
- Priest, J.A., Rees, E.V.L., Clayton, C.R.I., 2009. Influence of gas hydrate morphology on the seismic velocities of sands. *Journal of Geophysical Research* 114(B11), B11205, doi: 10.1029/2009jb006284, 13 p.
- Priest, J. A., Druce, M., Roberts, J., Schultheiss, P., Nakatsuka, Y. and Suzuki, K. (2014): Shipboard triaxial strength measurements of hydrate-bearing pressure core from the Nankai Trough, *Marine and Petroleum Geology*, in this issue.
- Reagan, M.T., Moridis, G.J., 2008. Dynamic response of oceanic hydrate deposits to ocean temperature change. *Journal of Geophysical Research* 113, C12023, doi:10.1029/2008JC004938, 21p.
- Reed, D.W., Fujita, Y., Delwiche, M.E., Blackwelder, D.B., Sheridan, P.P., Uchida, T., Colwell, F.S., 2002. Microbial communities from methane hydrate-bearing deep marine sediments in a forearc basin. *Applied and Environmental Microbiology* 68, 3759-3770.
- Reuschle, T., 2011. Data report: permeability measurements under confining pressure, Expeditions 315 and 316, Nankai Trough, in: Kinoshita, M., Tobin, H., Ashi, J., Kimura, G., Lallemand, S., Screaton, E.J., Curewitz, D., Masago, H., Moe, K.T., Expedition 314/315/316 Scientists (Eds.), *Proceedings of the Integrated Ocean Drilling Program*. IODP, Washington D.C., doi:10.2204/iodp.proc.314315316.205.2011, 17p.
- Rutqvist, J., Moridis, G.J., 2007. Numerical Studies of Geomechanical Stability of Hydrate-Bearing Sediments, Offshore Technology Conference, paper OTC 18860, Houston, Texas, U.S.A, p. 21 p.

- 1
- 2
- 3
- 4 Santamarina, J.C., Dai, S., Jang, J., Terzariol, M., 2012a. Pressure core characterization tools for hydrate-
- 5 bearing sediments. *Scientific Drilling* 14, 44-48.
- 6 Santamarina, J.C., Klein, K.A., Fam, M.A., 2001. *Soils and Waves: Particulate materials behavior,*
- 7 *characterization and process monitoring.* John Wiley & Sons, Ltd., New York.
- 8 Santamarina, J.C., Ruppel, C., 2008. The impact of hydrate saturation on the mechanical, electrical, and
- 9 thermal properties of hydrate-bearing sand, silts, and clay, in: Englezos, P., Ripmeeser, J. (Eds.),
- 10 *Proceedings of the 6th International Conference on Gas Hydrates, Vancouver, Canada*, pp. Paper
- 11 5817, 5812 p.
- 12 Santamarina, J.C., Ruppel, C., 2010. The impact of hydrate saturation on the mechanical, electrical, and
- 13 thermal properties of hydrate-bearing sand, silts, and clay, in: Riedel, M., Willoughby, E.C., Chopra,
- 14 S. (Eds.), *Geophysical Characterization of Gas Hydrates.* Society of Exploration Geophysicists
- 15 *Geophysical Developments*, pp. 373-384.
- 16 Santamarina, J.C., Winters, W.J., Dai, S., Jang, J., Terzariol, M., Papadopoulos, E., Mason, D., Waite,
- 17 W., Bergeron, E., 2012b. Pressure core characterization tools to enhance gas hydrate field programs.
- 18 *Fire in the Ice: Department of Energy, Office of Fossil Energy, National Energy Technology*
- 19 *Laboratory, Methane Hydrate News Letter* 12, 7-9.
- 20 Shankar, U., Riedel, M., 2014. Assessment of gas hydrate saturation in marine sediments from resistivity
- 21 and compressional-wave velocity log measurements in the Mahanadi Basin, India. *Marine and*
- 22 *Petroleum Geology* 58, 265-277.
- 23 Shelandar, D., Dai, J.C., Bunge, G., Singh, S., Eissa, M., Fisher, K., 2012. Estimating saturation of gas
- 24 hydrates using conventional 3D seismic data, Gulf of Mexico Joint Industry Project Leg II. *Marine and*
- 25 *Petroleum Geology* 34, 96-110.
- 26 Sloan, E.D., Koh, C.A., 2007. *Clathrate Hydrates of Natural Gases*, Third Edition. CRC Press, Boca
- 27 Raton.
- 28 Spangenberg, E., 2001. Modeling of the influence of gas hydrate content on the electrical properties of
- 29 porous sediments. *Journal of Geophysical Research* 106, 6535-6548.
- 30 Spangenberg, E., Kulenkampff, J., 2006. Influence of methane hydrate content on electrical sediment
- 31 properties. *Geophysical Research Letters* 33, L24315, doi:10.1029/2006GL028188, 5p.
- 32 Stryjek, R., Vera, J.H., 1986. Prsv - an Improved Peng-Robinson Equation of State for Pure Compounds
- 33 and Mixtures. *Canadian Journal of Chemical Engineering* 64, 323-333.
- 34 Suzuki, K., Schultheiss, P., Ito, T., Nakatsuka, Y., Egawa, K. and Yamamoto, K., 2015: Overview:
- 35 Physical properties and sedimentological features of hydrate-bearing samples recovered from the first
- 36 gas production test site on Daini-Atsumi knoll around Eastern Nankai Trough, *Marine and Petroleum*
- 37 *Geology*, in this issue.
- 38 Takahashi, H., Tsuji, Y., 2005. Multi-well exploration program in 2004 for natural hydrate in the Nankai-
- 39 Trough offshore Japan. *Offshore Technology Conference*, Houston, TX. May 2-5, 2005, paper OTC
- 40 17162, 10p.
- 41 Terzaghi, K., Peck, R.B., Mesri, G., 1996. *Soil mechanics in engineering practice*, 3rd ed. John Wiley and
- 42 Sons, New York.
- 43 Tsuji, Y., Ishida, H., Nakamizu, M., Matsumoto, R., Shimizu, S., 2004. Overview of the MITI Nankai
- 44 Trough Wells: A Milestone in the Evaluation of Methane Hydrate Resources. *Resource Geology* 54,
- 45 3-10.
- 46 Uchida, T., Lu, H., Tomaru, H., 2004. Subsurface Occurrence of Natural Gas Hydrate in the Nankai
- 47 Trough Area: Implication for Gas Hydrate Concentration. *Resource Geology* 54, 35-44.
- 48 Uchida, T., Waseda, A., Namikawa, T., 2009. Methane accumulation and high concentration of gas
- 49 hydrate in marine and terrestrial sandy sediments, in: Collett, T., Johnson, A., Knapp, C., Boswell, R.
- 50 (Eds.), *Natural Gas Hydrates - Energy Resource and Associated Geologic Hazards.*
- 51 *AAPG/NETL/AAPG Foundation/AAPG EMD, AAPG Memoir* 89, pp. 401-413.
- 52 Valdes, J.R., Santamarina, J.C., 2007. Particle transport in a nonuniform flow field: Retardation and
- 53 clogging. *Applied Physics Letters* 90, 244101, doi:10.1063.1.2748850, 3p.
- 54
- 55
- 56
- 57
- 58
- 59
- 60
- 61
- 62
- 63
- 64
- 65

- 1
2
3
4 Waite, W.F., Kneafsey, T.J., Winters, W.J., Mason, D.H., 2008. Physical property changes in hydrate-
5 bearing sediment due to depressurization and subsequent repressurization. *Journal of Geophysical*
6 *Research* 113, B07102, doi:10.1029/2007JB005351, 12p.
- 7 Waite, W.F., Santamarina, J.C., Cortes, D.D., Dugan, B., Espinoza, D.N., Germaine, J., Jang, J., Jung,
8 J.W., Kneafsey, T.J., Shin, H., Soga, K., Winters, W.J., Yun, T.S., 2009. Physical properties of
9 hydrate-bearing sediments. *Reviews of Geophysics* 47, RG4003, doi:10.1029/2008RG000279, 38p.
- 10 Waite, W.F., Stern, L.A., Kirby, S.H., Winters, W.J., Mason, D.H., 2007. Simultaneous determination of
11 thermal conductivity, thermal diffusivity and specific heat in sl methane hydrate. *Geophysical Journal*
12 *International* 169, doi: 10.1111/j.1365-246X.2007.03382.x, 767-774.
- 13 Waseda, A., Uchida, T., 2004a. The Geochemical Context of Gas Hydrate in the Eastern Nankai Trough.
14 *Resource Geology* 54, 69-78.
- 15 Waseda, A., Uchida, T., 2004b. Origin and migration of methane in gas hydrate-bearing sediments in the
16 Nankai Trough, in: Ronald J. Hill, J.L.Z.A.M.J.B.G.C.R.E.M.G., Kenneth, P. (Eds.), *The Geochemical*
17 *Society Special Publications*. Elsevier, pp. 377-387.
- 18 Weast, R.C., 1987. *CRC Handbook of Chemistry and Physics*, 68 ed. CRC Press, Inc., Boca Raton.
- 19 Yamamoto, K., 2013. Japan completes first offshore methane hydrate production test - methane
20 successfully produced from deepwater hydrate layers. *Fire in the Ice: Department of Energy, Office of*
21 *Fossil Energy, National Energy Technology Laboratory, Methane Hydrate News Letter* 13, 1-2.
- 22 Yamamoto, K., Inada, N., Kubo, S., Fujii, T., Suzuki, K., Konno, Y., Shipboard Scientists for the
23 Methane Hydrate Offshore Production Test, 2012. Pressure core sampling in the Eastern Nankai
24 Trough. *Fire in the Ice: Department of Energy, Office of Fossil Energy, National Energy Technology*
25 *Laboratory, Methane Hydrate News Letter* 12, 1-6.
- 26 Yamamoto, K., 2015, Overview and introduction: pressure core-sampling and analyses in the 2012–2013
27 MH21 offshore test of gas production from methane hydrates in the eastern Nankai Trough, *Marine*
28 *and Petroleum Geology*, in this issue.
- 29 Yoneda, J., Masui, A., Konno, Y., Jin, Y., Egawa, K., Kida, M., Ito, T., Nagao, J. and Tenma, N., 2015:
30 Mechanical properties of hydrate-bearing turbidite reservoir in the first gas production test site of the
31 Eastern Nankai Trough, *Marine and Petroleum Geology*, in this issue.
- 32 Yun, T.S., Francisca, F.M., Santamarina, J.C., Ruppel, C., 2005. Compressional and shear wave velocities
33 in uncemented sediment containing gas hydrate. *Geophysical Research Letters* 32, L10609,
34 doi:10610.11029/12005GL022607.
- 35 Yun, T.S., Lee, C., Lee, J.-S., Bahk, J.J., Santamarina, J.C., 2011. A pressure core based characterization
36 of hydrate-bearing sediments in the Ulleung Basin, Sea of Japan (East Sea). *Journal of Geophysical*
37 *Research* 116, B02204, doi:10.1029/2010JB007468, 12p.
- 38 Yun, T.S., Narsilio, G.A., Santamarina, J.C., Ruppel, C., 2006. Instrumented pressure testing chamber for
39 characterizing sediment cores recovered at in situ hydrostatic pressure. *Marine Geology* 229, 285-293.
- 40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65

Figure 1

Figure 1. Pressure Core Characterization Tools PCCTs, configured for 50.8-mm-diameter Nankai Trough cores. **(A)** Instrumented Pressure Testing Chamber IPTC; **(B)** Effective Stress Chamber ESC; **(C)** Direct Shear Chamber DSC; **(D)** Biological Sampling Cell BIO. Additional details are provided in Santamarina et al. (2012a,b). Ball-valve closures are in deep red, flange clamps are in green, thermocouples are shown as thin red lines. Measurement sensors shown: compressional- and shear-wave velocity, V_p and V_s , respectively; undrained shear strength S_u ; electrical conductivity σ_{el} ; specimen length changes are measured with linear voltage displacement transducers LVDT.

Figure 2

Figure 2. Pressure Core Analysis and Transfer System PCATS X-ray core scans (Suzuki et al., this volume), aligned with Pressure Core Characterization Tool measurement locations and Instrumented Pressure Testing Chamber IPTC results. Shepard-classification soil descriptions are from Ito et al. (this volume). (A) Core 8P was tested in the IPTC (orange arrows mark measurement locations), then subsampled for testing in the Biologic Chamber BIO, Direct Shear Cell DSC, and Effective Stress Cell ESC. IPTC results for compressional wave velocity V_p , shear wave velocity V_s , undrained shear strength S_u , and electrical conductivity σ_{el} , are given in panels B-E. Solid circles represent locations with high hydrate saturation silty-sands, open circles represent locations with low hydrate saturation sediment, primarily clayey-silt. Solid lines represent expected baseline values for hydrate-free sediment. See Table 1 for IPTC results. (F) Core 10P was tested in the IPTC, then subsampled for testing in the DSC and ESC. IPTC results are given in panels G-J. (K) Core 20P was subsampled for testing in the DSC.

Figure 3

Figure 3. IPTC cone penetrometer probe response difference between locations with high hydrate saturations (high S_h , blue solid circles), and low hydrate saturations (low S_h , green open circles). High- S_h locations tend to fracture during probe insertion, as indicated by the sudden post-peak softening (~ 7.0 -mm insertion when peak strength was recorded). In low- S_h locations, the penetrometer reaches full insertion (17.6-mm insertion) and load relaxation occurs only when the probe is stationary.

Figure 4

Figure 4. Evolution of specimen void ratio during the complete loading history for ESC core 8P (A) and core 10P (B). Significant specimen shortening during dissociation in core 10P relative to that observed in core 8P is due to fines migration through gaps around the specimen’s upper porous stone. The lower stone through which core 8P was vented has a sealed perimeter. Arrows indicate the experimental path in time.

Figure 5

Figure 5. Water permeability measurement in the ESC for core 8P before dissociation. (A) Measured differential pressure versus time during pore fluid extraction under constant flux, with effective pressure $\sigma_v' = 3\text{MPa}$, pore pressure $u = 10\text{MPa}$. (B) The average differential pressure is determined using the slope of the integration of the measured differential pressure in A to cancel random noise. (C) Permeability is determined based on measurements under several different fluxes. The best fit of the q versus $\nabla P/\mu$ slope gives the final permeability value.

Figure 6

Figure 6. Gas production test at an effective stress of 3MPa in the ESC. Pressure and temperature changes during dissociation of core 8P (A) and 10P (B). The solid line is the phase boundary for methane hydrate in pure water and the dashed line is the phase boundary in seawater. Stability curves from Sloan and Koh (2007). Dissociation occurs along the freshwater stability curve, likely in response to dissociating hydrate being bathed in the freshwater generated as hydrate dissociates. Evolution along the freshwater stability curve is more noticeable in core 8P, which is depressurized from its base so dissociating fluids flow over the ESC thermocouple. Core 10P is depressurized at the specimen top, so dissociating fluids flow away from the thermocouple, reducing the measurement sensitivity to temperature changes. Gas volume collected during the dissociation for core 8P (C) and 10P (D). Dissociation occurs too rapidly to establish thermal or chemical equilibrium with the surrounding material or pore water, leading to temperatures depressed close to 0 $^{\circ}\text{C}$ and fresh water concentrations large enough to control dissociation conditions.

Figure 7

Figure 7. Typical results from the DSC. (A) Relaxation test after first loading; (B) shear test: blue dots show peak shear before relaxation, green dots show shear strength after shear relaxation. Dotted box indicates the initial “seating effect” as the specimen responds to the axial load contacting the non-parallel top and bottom faces of the specimen.

Figure 8

Figure 8. Mobilized friction angle, ϕ , measured in the DSC before (A) and after (B) hydrate dissociation in Core 20P. Blue squares and green circles, respectively, represent measurements made before and after the specimen relaxes after each displacement (see Fig. 7B). Hydrate significantly alters the friction angle when measured immediately after a displacement (blue squares), but values measured after the system relaxes (green circles) are controlled primarily by mineralogy. The specimen contains 12-15 wt% smectite (Egawa et al., this volume). For reference, crosses are plotted for measurements on dry mixtures of quartz sand and 20 wt% smectite (Mollins et al., 1999).

Figure 9

Figure 9. P-waveforms measured in the DSC for Core 10 while depressurizing the cell to cause dissociation. Depressurization progresses from top to bottom in the figure. Waveforms are normalized by their specimen lengths to cancel the effects caused by specimen shortening during dissociation. Black curves are measured while the specimen is within the hydrate stability conditions, red curves are measured after u_{cell} is reduced below the hydrate stability pressure at 6°C. Amplitude loss for pressures below the hydrate stability pressure (red curves) is in agreement with empirical results for the addition of gas to an otherwise water-saturated porous material (Murphy, 1982; Santamarina et al., 2001).

Figure 10. Sampling of the biological diversity in core 8P using the BIO chamber. Images are taken after culturing for 32 days at atmospheric pressure, under oxic conditions. Top row cultured at 4°C, bottom row cultured at 30°C. Depressurization rates and dilutions vary: (A) 7MPa/2 sec, 10^{-3} dilution; (B) 7MPa/2 sec, 10^{-1} dilution; (C) 7MPa/1 min, 10^{-3} dilution; (D) 7MPa/30 min, 10^{-1} dilution. Variety in colony color and edge morphology likely indicate the presence of several microbial species. Microbial identification is not part of the BIO chamber's specimen acquisition "proof-of-concept" test.

Figure 11. (A) Compressional V_p and (B) Shear V_s wave velocity in hydrate-bearing sands. Under gas-limited conditions in marine sands, hydrate nucleates and initially grows into the pore space (i.e. “pore filling”), to eventually become “load-bearing” as the hydrate volume in the pore increases (Yun et al., 2005). IPTC measurements in a high S_h section of core 8P (filled circles), and DSC measurement in a low S_h section of core 10P (filled diamond in A) can all be fitted by the model that assumes hydrate is homogeneously distributed as a load-bearing component of the sediment (Dvorkin et al. 2000). Schematics show grey, circular sand grains and black hydrate mass. Cementation curves are also calculated from Dvorkin et al. (2000), and curves for sand with spherical hydrate patches are calculated from Berryman (1995). Theoretical curve color scheme is the same in A and B.

Figure 12

Figure 12. Dependence of compressional wave velocity V_p on effective stress in the DSC specimen from core 10P. Pressure cores are collected and stored with no effective stress. The PCATS measurement of V_p (red star, Suzuki et al., this volume) one week after collecting core 10P shows evidence of V_p reduction from in situ values that is more significant than the reduction expected from rapid removal of the effective stress (filled black squares, measured in DSC). The core expansion, or aging observed by Nagano et al. (this volume), is likely responsible for the remaining drop in V_p apparent in the PCATS measurement. Additional expansion and unloading at sediment grain contacts occurs during the subsequent 27 weeks of storage at zero effective stress, but within the hydrate stability conditions, causing an additional 5% drop in V_p (IPTC measurement, co-located with PCATS measurement, red circle). DSC reapplication of a vertical effective stress to the specimen reverses the unloading and aging effects on V_p (filled black circles). The break in slope near 2.8MPa applied stress coincides with the in situ vertical effective stress, estimated to be 2.32MPa.

Figure 13

Figure 13. Measured permeability in hydrate-bearing sediment relative to the permeability in hydrate-free sediment (filled circle at $S_h = 0.18$ for core 8P, and 0.74 for core 10P). Theoretical trends are shown for several possible hydrate morphologies (schematics have sediment shown in grey, hydrate in black). Results suggest hydrate is primarily forming as a non-cementing pore-fill (model in Kleinberg et al., 2003), as can be expected if hydrate initially forms in the largest pores through which pore fluid advection is strongest. If hydrate is assumed to be distributed in patches throughout the sediment, the relative permeability is overpredicted in the spherical-grain case (Berryman, 1995), but is in agreement with a modified Kozeny-Carman approach in which the pore space is assumed to be a network of water-filled capillaries (white segments) with hydrate forming a patchy filling of the larger-diameter capillaries (black segments, model in Dai and Seol, 2014).

Figure 14

Figure 14. Permeability measurements for core 8P in the ESC after hydrate dissociation (blue circles), while the specimen pore space contains gas and the water saturation $S_w < 1$. Permeability measurements are made at different pore pressure levels as the specimen is repressurized with water to $u_{cell} = 10\text{MPa}$ at 18°C to resaturate the specimen without reforming hydrate. The measured residual water saturation after depressurization for this specimen is $S_{rw} = 0.16$. Relative permeability k_{rw} dependence on S_w during repressurization can be estimated (solid curve) with the Brooks and Corey (1964) model, where the best fit curve is nearly identical to the prediction using the parameters from Kurihara et al., (2011).

Figure 15

Figure 15. Dependence of cell count on depth from the ground surface. Cells can only occupy pores larger than the cell size; the probability of finding pores of viable host size decreases with depth due to compaction, and with grain specific surface S_s due to the presence of fine particles in the pore space (Phadnis and Santamarina, 2011). Nankai Trough data from other studies are included (Reed et al., 2002; Li et al., 1999; Kormas et al., 2003; Mills et al., 2012; Newberry et al., 2004). The shaded region represents results from other locations compiled in Parkes et al. (1994, 2000). Cell counts in this study were taken from a BIO specimen with $S_s = 19.4$ m²/g, but the cell counts include only live, culturable aerobes, so a reduced cell count is expected relative to theoretical estimates (dashed curves) and compiled data (symbols and shaded region), which all include living and dead organisms. Compiled data points are obtained based either on cell weight (x), or a staining method (solid diamonds).