SUBMISSION TO ‘COMPUTERS AND GEOTECHNICS’

DATE:

01/12/2016

TITLE:

Multi-timescale high-accuracy modeling of hydro-mechanically coupled processes in fluid-saturated poroelastic media

AUTHORS:

Gen Li ^{a, b, *}, Kai Wang ^{a, b}, You-Wei Li ^c

CORRESPONDING AUTHOR:

Gen Li (E-mail: ligen8@dlut.edu.cn)

POSITIONS AND AFFILIATIONS:

- ^a State Key Laboratory of Coastal and Offshore Engineering, Dalian University of Technology, Dalian 116024, China
^b Ocean Engineering Joint Research Center of DUT-UWA, Dalian 116024, China
^c Liaoning Provincial Department of Water Resources, Shenyang 110003, China

CONTACT ADDRESS:

Dalian University of Technology,
No.2 Linggong Road,
Ganjingzi District,
Dalian City,
Liaoning Province,
P.R.China

EDITION:

R2

NUMBER OF WORDS, FIGURES AND TABLES:

Words: 4169

Figures: 10

Tables: 3

Multi-timescale high-accuracy modeling of hydro-mechanically coupled processes in fluid-saturated poroelastic media

Gen Li ^{a, b, *}, Kai Wang ^{a, b}, You-Wei Li ^c

^a State Key Laboratory of Coastal and Offshore Engineering, Dalian University of Technology, Dalian 116024, China

^b Ocean Engineering Joint Research Center of DUT-UWA, Dalian 116024, China

^c Liaoning Provincial Department of Water Resources, Shenyang 110003, China

Abstract

In order to accurately model the behaviour of geostructures, the interaction between solid-deformation and fluid-flow needs to be considered for porous geomaterials. However, a dilemma in the selection of suitable time-step size and high computational accuracy always exists in temporal finite difference-based numerical methods. Especially, the load is long-term, cyclically varied and highly time-dependent. The goal of the paper is to develop a new computational scheme for high-accuracy modeling of hydro-mechanically coupled processes for fluid-saturated poroelastic media, in which high-accuracy computation is achieved through a multi-timescale approach consisting of the precise integration of an exponential matrix.

Keywords: Hydro-mechanically coupled processes; Finite element method; Poroelasticity; Exponential matrix; Multi-timescale

* Corresponding author.

E-mail addresses: ligen8@dlut.edu.cn (G. Li).

1. Introduction

Rock and soil are natural geomaterials containing a lot of micropores. These micropores are usually filled by water, resulting in formation of fluid-saturated porous media. Interaction between fluid-flow and solid-deformation in geomaterials may lead to serious consequences, such as hydraulic fracturing, water inrush in mines or tunnels, slope instability, subsidence or tilting of building foundation [1,2]. The mathematical framework describing the fully coupled hydro-mechanical (FCHM) processes, i.e., the poroelastic model, can be dated back to the mid-20th century [3-5]. As recently extensive studies have demonstrated, the deformation of a porous medium can cause a considerable change in the porosity and permeability of the porous medium [6,7]. In particular, both the physical dissolution [8,9] and the chemical dissolution [10,11] of dissolvable materials in fluid-saturated porous media can also cause a significant change in the porosity and permeability of the porous media. It has been also demonstrated that some important factors, such as the particle shape of the porous medium [12], pore-fluid and medium compressibility [13], solute dispersion [14] and mineral dissolution ratio [15], can significantly affect the distribution patterns of the porosity and permeability in the porous medium. This indicates that both the porosity and the permeability should depend on the skeleton deformation (including thermal deformation [16,17]). Nevertheless, due to the limitation of using Biot's theory, the above-mentioned factors are not considered in this study. Even so, due to the complex physical interaction and complicated boundary conditions, the analytical solutions of FCHM problems are available for only a few situations. Since Biot's theory was presented more than 75 years ago [4], it has certain limitations when numerical computational techniques are widely used to solve scientific and engineering problems today [6,7,18]. Hence, numerical techniques are commonly used, which are active research areas at present [19-24]. The treatment of FCHM-controlled differential equations by a numerical scheme usually contains two processes, i.e., spatial and temporal discretization of basic variables. It should be noted that, in most cases, the numerical methods focus on approximation in the space domain for basic variables so as to achieve better numerical performance and a wider application scope. The finite difference (FD) is usually used by various numerical schemes to replace the time derivative for discretization in the time domain and little work has been devoted to the development of the time discretization algorithms for numerical poroelastic model. Generally, the temporal discretization FD techniques, such as the generalized trapezoidal θ -method, are used in most numerical methods, for instance, the finite element method (FEM), where θ is an integration parameter varying from 1.0 (fully implicit) to 0 (fully explicit). It is proven that the value of θ has an important influence on the stability as well as the accuracy of the numerical method. The approximation is unconditionally stable when $\theta \geq 0.5$, but for any value of $\theta \neq 1$ (semi-implicit scheme), the numerical solution can exhibit a spurious rippling effect [25]. When $\theta = 0$, even though the fully explicit algorithm is simple, it is stable for only extremely small time-step sizes, and perhaps the step size is so small that a real time of interest would require an excessive number

of steps. Therefore, this fully explicit scheme is not of practical value. Instead, a fully implicit ($\theta = 1$) scheme is commonly used. However, the FD-based methods are either first- or second-order accurate approximations, and therefore their accuracy is relatively low, especially the accuracy of results is sensitive to the time-step size.

With the emerging computational geoscience [7,18] and some deep underground excavation problems, for some long-term problems, the timescale for multi-field evolution can range from 10^0 to 10^5 years [26-28], and in most cases, the load is highly time-dependent and varies cyclically [29,30]. This undoubtedly brings great challenges to the FD-based numerical methods. On one hand, large time-step sizes have to be adopted due to considerations on computational efficiency, which leads to relatively large error and inevitable missing of field characteristics in many time scales; on the other hand, small time-step sizes shall be adopted in order to achieve higher computational accuracy. Especially for cyclic loading, the long timescale coupling process requires intensive computational effort. Some researchers tried to achieve a compromise between computational accuracy and efficiency by improving the differential schemes (such as the three-point discretization scheme and multiple-time-step technique) [31,32], developing the self-adaption schemes (such as adaptive time-stepping methods) [33-35], or changing the coupling sequence (such as iteratively/explicitly/loosely coupled algorithm) [36-38]. However, a dilemma in selecting between a suitable time-step size and high computational accuracy still exists. Recently, an explicit numerical algorithm for the fully coupled hydro-mechanical analysis of fluid-saturated poroelastic media based on direction integration in time domain has been proposed [39], which can better resolve the dilemma. In this paper, based on the above-mentioned global algorithm and precise integration of exponential matrix, a novel multi-timescale high-accuracy modeling scheme is proposed. Its advantages are verified by theoretical analysis and numerical modeling.

2. Differential formulation

For porous medium deformation-water flow coupled problems, there are two sets of governing equations [1,5]:

- *Equilibrium equation for mechanical deformation*

$$\nabla \cdot (\boldsymbol{\sigma}' - \alpha p \mathbf{l}) + \mathbf{b} = \mathbf{0} \quad (1)$$

where $\boldsymbol{\sigma}'$ is the effective stress tensor, $\alpha = 1 - \frac{K_{dr}}{K_s}$ is the Biot's coefficient, K_s is the

bulk modulus of the solid grain, and K_{dr} is the drained bulk modulus, p is the (excess) pore pressure, $\mathbf{l}$ is the second-order unit tensor, $\mathbf{b}$ is the body force vector. The constitutive law of

the solid phase is

$$\boldsymbol{\sigma}' = \boldsymbol{\square} : \boldsymbol{\varepsilon} \quad (2)$$

where $\boldsymbol{\square}$ is the solid skeleton stiffness tensor and $\boldsymbol{\varepsilon}$ is the linearized strain tensor under the assumption of infinitesimal transformation, as

$$\boldsymbol{\varepsilon} = \nabla^s \cdot \mathbf{u} = \frac{1}{2} (\nabla \cdot \mathbf{u} + \nabla \cdot \mathbf{u}^T) \quad (3)$$

where $\mathbf{u}$ is the displacement for the solid matrix.

• *Continuity equation for fluid flow*

$$\alpha \dot{\varepsilon}_v + \frac{\dot{p}}{Q^*} + \nabla \cdot \mathbf{v} = Q \quad (4)$$

where $\varepsilon_v = \text{tr} \boldsymbol{\varepsilon}$ is the volumetric strain, Q^* is the Biot's modulus and $\frac{1}{Q^*} = \frac{\alpha - n}{K_s} + \frac{n}{K_f}$,

K_f is the bulk modulus of the fluid, n is the porosity, Q is the fluid mass flux from sink or source and $\mathbf{v}$ is the Darcy's velocity vector of fluid flow. The constitutive relationship for fluid flow in porous media is Darcy's law.

$$\mathbf{v} = -\frac{\mathbf{k}}{\gamma_f} \cdot \nabla p \quad (5)$$

where $\gamma_f = \rho_f g$ is the specific weight of fluid, ρ_f is the fluid density, g is the gravitational acceleration and $\mathbf{k}$ is the hydraulic conductivity tensor. For simplicity, here $\mathbf{k}$ is considered to be constant and isotropic, i.e., $\mathbf{k} = k\mathbf{I}$.

Boundary conditions for solid skeleton boundary and fluid boundary can be written as $\mathbf{u} = \bar{\mathbf{u}}$ on Γ_u (specified displacement); $\boldsymbol{\sigma} \cdot \mathbf{n} = \bar{\boldsymbol{\sigma}}$ on Γ_σ (specified traction); $p = \bar{p}$ on Γ_p (specified pressure); $\mathbf{v} \cdot \mathbf{n} = \bar{q}$ on Γ_q (specified flux), where $\boldsymbol{\sigma}$ is the total stress tensor, $\mathbf{n}$ is the unit normal vector at the domain boundary Γ , Γ_u is the displacement boundary, Γ_σ is the solid traction boundary, Γ_p is the pore pressure boundary and Γ_q is the velocity (flux) boundary. It must be pointed out that the above boundary conditions are only suitable for the problems of finite computational domains. However, since most of geoscience and geotechnical engineering problems may involve infinite computational domains [40], the dynamic and transient infinite elements [41,42] should be used to simulate the far field of such geoscience and geotechnical engineering problems [43]. The initial conditions at time $t = 0$ can be written as $\mathbf{u}|_{t=0} = \mathbf{u}_0$, $p|_{t=0} = p_0$ in Ω and on Γ , where Ω is the domain.

3. Numerical implementation

3.1. Discretization in space

For the spatial discretization of the above governing equations, it is necessary to transform the strong forms Eqs. (1) and (4) into a matrix form. First, let the space domain be partitioned into non-overlapping elements, $\Omega = \bigcup_{i=1}^{n_{ele}} \Omega_i^h$, where n_{ele} represents the number of elements; and the superscript h indicates the spatially discrete quantities. Then, the weighted residual method can be applied for the deduction of FE formulations, the reader can be referred to [1,25]. Eventually, a matrix formulation is derived. An integration in the space domain yields a rate form of the first-order global coupled pressure-displacement differential matrix system, which is assembled using the nodal matrices or vectors and can be written as follows:

$$\begin{bmatrix} \mathbf{K} & -\mathbf{Q} \\ \mathbf{Q}^T & \mathbf{S} \end{bmatrix} \begin{Bmatrix} \dot{\mathbf{u}} \\ \dot{\mathbf{p}} \end{Bmatrix} + \begin{bmatrix} \mathbf{0} & \mathbf{0} \\ \mathbf{0} & \mathbf{H} \end{bmatrix} \begin{Bmatrix} \mathbf{u} \\ \mathbf{p} \end{Bmatrix} = \begin{Bmatrix} \dot{\mathbf{f}}^u \\ \mathbf{f}^p \end{Bmatrix} \quad (\text{Simplified as } \bar{\mathbf{M}}\dot{\mathbf{x}} + \bar{\mathbf{K}}\mathbf{x} = \mathbf{f}) \quad (6)$$

where $\mathbf{K}$, $\mathbf{H}$, $\mathbf{S}$ and $\mathbf{Q}$ are the elastic stiffness, flow stiffness, flow capacity and flow-stress coupling matrices, respectively; $\mathbf{x} = [\mathbf{u} \ \mathbf{p}]^T$ and $\dot{\mathbf{x}} = [\dot{\mathbf{u}} \ \dot{\mathbf{p}}]^T$ are the vectors of unknown variables and the corresponding time derivatives, respectively; $\dot{\mathbf{f}}^u$, $\dot{\mathbf{f}}^p$ and $\mathbf{f}^p$ are the vectors of the nodal loads, loading rate and flow sources, respectively. It is well known that $\mathbf{K}$, $\mathbf{H}$ and $\mathbf{S}$ are symmetrically positive definite matrices. Therefore, $\bar{\mathbf{M}}$ is invertible but $\bar{\mathbf{K}}$ is not. As the detailed matrices and vectors shown here, the reader can be referred to [1,25].

3.2. Explicit direct integration in time

3.2.1 Time integration

In this section, a novel fully explicit multi-timescale high-accuracy modeling scheme will be constructed based on the precise time step integration method (PTSIM) [44]. First, we rewrite Eq. (6) as follows

$$\dot{\mathbf{x}}(t) = -\bar{\mathbf{M}}^{-1}\bar{\mathbf{K}}\mathbf{x}(t) + \bar{\mathbf{M}}^{-1}\mathbf{f}(t) \quad (7)$$

The general solution of Eq. (7) can be written as follows

$$\mathbf{x}(t) = \exp(\bar{\mathbf{H}}t)\mathbf{x}(0) + \int_0^t \exp[\bar{\mathbf{H}}(t-\xi)]\bar{\mathbf{M}}^{-1}\mathbf{f}(\xi)d\xi \quad (8)$$

with $\bar{\mathbf{H}} = -\bar{\mathbf{M}}^{-1}\bar{\mathbf{K}}$. The time-step size is designated as Δt whereas the discrete time t_{k+1} for numerical computation can be given by $t_{k+1} = t_k + \Delta t$ ($k = 0, 1, 2 \dots$) for iteration, then Eq. (8) can be updated as

$$\mathbf{x}(t_{k+1}) = \mathbf{T} \cdot \mathbf{x}(t_k) + \mathbf{RHS}(\Delta t) \quad (9)$$

with $\mathbf{T} = \exp(\bar{\mathbf{H}}\Delta t)$ and $\mathbf{RHS}(\Delta t) = \int_0^{\Delta t} \exp[\bar{\mathbf{H}}(\Delta t - \xi)] \bar{\mathbf{M}}^{-1} \mathbf{f}(t_k + \xi) d\xi$.

3.2.2 Multi-timescale high-accuracy numerical computation matrix $\mathbf{T}$

Let $\tau = \Delta t / m$ be a downscaling extremely small time-step size, where the integer m is suggested as $m = 2^N$, and N is a positive integer. The exponential matrix $\mathbf{T}$ can be obtained accurately using the PTSIM with a downscaling time interval as follows

$$\mathbf{T} = [\exp(\bar{\mathbf{H}}\tau)]^m \quad (10)$$

Using a Taylor expansion, the finite Taylor series with the remainder term reads as follows

$$\exp(\bar{\mathbf{H}}\tau) = \sum_{i=0}^L \frac{(\bar{\mathbf{H}}\tau)^i}{i!} + O(\tau^{L+1}) \quad (11)$$

Because τ is extremely small, the several term (i.e., the truncation order is L) series expansion should be enough. The exponential matrix $\mathbf{T}$ departs from the unit matrix $\mathbf{I}$ to a small extent $\mathbf{T}_a$ as follows

$$\exp(\bar{\mathbf{H}}\tau) \approx \mathbf{I} + \sum_{i=1}^L \frac{(\bar{\mathbf{H}}\tau)^i}{i!} = \mathbf{I} + \mathbf{T}_a(\tau) \quad (12)$$

Next, the upscaling time series need to compute, i.e. $\tau \rightarrow 2\tau \rightarrow \dots \rightarrow 2^N \tau = \Delta t$. The reduplication can be updated as follows

$$\mathbf{T}_a(2\tau) = 2\mathbf{T}_a(\tau) + \mathbf{T}_a^2(\tau) \quad (13)$$

After being multiplied N times, we have

$$\mathbf{T} = \mathbf{I} + \mathbf{T}_a(\Delta t) \quad (14)$$

The algorithm presented above composes the precise computation for the exponential matrix $\mathbf{T}$, the numerical result can reach the computer precision (see *Section 5*).

3.2.3 Multi-timescale high-accuracy numerical computation item $\mathbf{RHS}$

Accurate calculation of the item $\mathbf{RHS}$ in Eq. (9) is the second key to high-accuracy modeling of hydro-mechanically coupled processes. Generally, the item $\mathbf{RHS}$ cannot be analytically integrated as the matrix $\bar{\mathbf{H}}$ is invertible. Li et al. [39] calculated the item $\mathbf{RHS}$ by using the Gauss integration. The computational accuracy can only be improved by increasing the number of integration points or reducing the time-step size, without utilizing high accuracy achieved by numerical computation of exponential matrix. In order to utilize the advantages of this algorithm and in view of the effect of $\mathbf{f}$ on $\mathbf{RHS}$, high-accuracy approximation of $\mathbf{f}$ is performed to calculate the item $\mathbf{RHS}$ for the time in the range of $[t_k, t_{k+1}]$. $\mathbf{f}$ can be approximated by:

$$\mathbf{f}(t) = \mathbf{f}(t_k + \xi) \approx \bar{\mathbf{f}}_0 \phi_0(\xi) + \bar{\mathbf{f}}_1 \phi_1(\xi) + \dots + \bar{\mathbf{f}}_n \phi_n(\xi), \quad \xi \in [0, \Delta t] \quad (15)$$

Then, the item **RHS** can be written as:

$$\mathbf{RHS}(\Delta t) = \mathbf{R}_0 \bar{\mathbf{f}}_0 + \mathbf{R}_1 \bar{\mathbf{f}}_1 + \cdots + \mathbf{R}_n \bar{\mathbf{f}}_n \quad (16)$$

where $\bar{\mathbf{f}}_n$ is the coefficient vector, $\mathbf{R}_n = \int_0^{\Delta t} \exp[\bar{\mathbf{H}}(\Delta t - \xi)] \phi_n(\xi) d\xi \cdot \bar{\mathbf{M}}^{-1}$ which is the response matrix corresponding to the basic function ϕ_n . Based on the concept of precise calculation and Eq. (11), $\mathbf{R}_n(\tau)$ can be expressed as:

$$\mathbf{R}_n(\tau) = \sum_{i=0}^q \int_0^\tau \frac{\bar{\mathbf{H}}^i(\tau - \xi)^i}{i!} \phi_n(\xi) d\xi \cdot \bar{\mathbf{M}}^{-1} = \sum_{i=0}^q \psi_n^i(\tau) \bar{\mathbf{H}}^i \bar{\mathbf{M}}^{-1} \quad (17)$$

where q is the truncation order and $\psi_n^i(\tau) = \frac{1}{i!} \int_0^\tau (\tau - \xi)^i \phi_n(\xi) d\xi$. In this equation, selection of ϕ_n is extremely important for accurate calculation of ψ_n^i . When ϕ_n is polynomial or trigonometric, the value of ψ_n^i can be obtained analytically.

- *Polynomial expansion*

If $\mathbf{f}$ is sufficiently smooth in the time interval of $[t_k, t_{k+1}]$, the coefficient vector of the polynomial $\mathbf{f}$ can be obtained by Taylor expansion. If n^{th} -order expansion is performed for $\mathbf{f}$ at

$t = t_k$, then $\bar{\mathbf{f}}_n = \frac{1}{n!} \frac{d^{(n)} \mathbf{f}(t)}{dt^{(n)}} \bigg|_{t=t_k}$, $\phi_n = \xi^n$. Hence,

$$\psi_n^i(\tau) = \frac{1}{i!} \int_0^\tau (\tau - \xi)^i \xi^n d\xi \quad (18)$$

Obviously, ψ_n^i can be obtained analytically and highly accurate numerical results of $\mathbf{R}_n(\tau)$ can then be achieved. In order to calculate $\mathbf{R}_n(\Delta t)$, the upscaling time series algorithm can be performed according to the following multiplicative relationship,

$$\begin{aligned} \mathbf{R}_n(2\tau) &= \int_0^{2\tau} \exp[\bar{\mathbf{H}}(2\tau - \xi)] \xi^n d\xi \cdot \bar{\mathbf{M}}^{-1} \\ &= \mathbf{T}(\tau) \mathbf{R}_n(\tau) + \int_0^\tau \exp[\bar{\mathbf{H}}(\tau - \xi)] (\tau + \xi)^n d\xi \cdot \bar{\mathbf{M}}^{-1} \\ &= \mathbf{T}(\tau) \mathbf{R}_n(\tau) + \sum_{k=0}^n C_n^k \tau^{n-k} \mathbf{R}_k(\tau) \end{aligned} \quad (19)$$

with $C_n^k = \frac{n!}{k!(n-k)!}$.

- *Fourier expansion*

For a cyclic loading $\mathbf{f}$, it can be expanded into a Fourier series [45],

$$\mathbf{f}(t) = \sum_{n=0}^M [A_n \cos(\omega_n t) + B_n \sin(\omega_n t)] \quad (20)$$

where the series amplitudes $A_n = \frac{2}{T} \int_0^T \mathbf{f}(t) \cos(\omega_n t) dt$ and $B_n = \frac{2}{T} \int_0^T \mathbf{f}(t) \sin(\omega_n t) dt$ with

the frequency $\omega_n = 2n\pi/T$ and T is the time period of $\mathbf{f}$. It should be noted that the Fourier expansion of $\mathbf{f}$ may in practice be achieved by summing a finite number of terms M . Some examples will be presented in the next sections. The series in this equation, in fact, converges rapidly. When $\mathbf{f}$ is represented at intervals by constant or linear functions, which is often the case, closed-form expressions can be readily obtained by solving the integrals in A_k and B_k . This makes the Fourier expansion of $\mathbf{f}$ very attractive from a practical point of view. In this case, $\mathbf{f}$ can be approximated by the basic function composed of $\phi_{sn} = \sin(\omega_n \xi)$ and $\phi_{cn} = \cos(\omega_n \xi)$. Correspondingly, in the relevant matrices $\mathbf{R}_{sn}(\tau)$ and $\mathbf{R}_{cn}(\tau)$,

$$\psi_{sn}^i(\tau) = \frac{1}{i!} \int_0^\tau (\tau - \xi)^i \sin(\omega_n \xi) d\xi \quad (21)$$

$$\psi_{cn}^i(\tau) = \frac{1}{i!} \int_0^\tau (\tau - \xi)^i \cos(\omega_n \xi) d\xi \quad (22)$$

ψ_{sn}^i and ψ_{cn}^i can be obtained analytically. In order to calculate $\mathbf{R}_n(\Delta t)$, a multiplicative relationship between $\mathbf{R}_{sn}(\tau)$ and $\mathbf{R}_{cn}(\tau)$ for upscaling time series needs to be established. For $\mathbf{R}_{sn}$,

$$\begin{aligned} \mathbf{R}_{sn}(2\tau) &= \int_0^{2\tau} \exp[\bar{\mathbf{H}}(2\tau - \xi)] \sin(\omega_n \xi) d\xi \cdot \bar{\mathbf{M}}^{-1} \\ &= \mathbf{T}(\tau) \mathbf{R}_{sn}(\tau) + \int_0^\tau \exp[\bar{\mathbf{H}}(\tau - \xi)] \sin[\omega_n(\tau + \xi)] d\xi \cdot \bar{\mathbf{M}}^{-1} \\ &= \mathbf{T}(\tau) \mathbf{R}_{sn}(\tau) + \sin(\omega_n \tau) \mathbf{R}_{sn}(\tau) + \cos(\omega_n \tau) \mathbf{R}_{cn}(\tau) \end{aligned} \quad (23)$$

Similarly,

$$\mathbf{R}_{cn}(2\tau) = \mathbf{T}(\tau) \mathbf{R}_{cn}(\tau) + \cos(\omega_n \tau) \mathbf{R}_{cn}(\tau) - \sin(\omega_n \tau) \mathbf{R}_{sn}(\tau) \quad (24)$$

Then,

$$\mathbf{R}_n(2\tau) = \mathbf{R}_{sn}(2\tau) + \mathbf{R}_{cn}(2\tau) \quad (25)$$

For both the polynomial expansion and the Fourier expansion, the key to highly accurate calculation of $\mathbf{R}_n$ is an analytical expression for ψ_n^i , which is selected for the basic function ϕ_n , so that $\mathbf{R}_n$ is independent of the timescale and the computational process is irrelevant to the singularity of $\bar{\mathbf{H}}$. In this way, better numerical stability and applicability can be achieved and the numerical error in the item **RHS** is only caused by approximation of $\mathbf{f}$.

4. Numerical examples

In this section, an infinitely long, elastic and fluid-saturated geomaterials foundation with a 10m permeable layer subjected to a time-dependent load on the surface is considered (Fig.1a). The proposed scheme is applied for three loading conditions in order to verify and calibrate the calculation accuracy. The modeling results are compared with the analytical solutions

and/or the numerical solution of the standard FD-based FEM. In the standard FD-based FEM [5], the time integration is performed with the default implicit scheme ($\theta = 1$) and a constant time step. For spatial discretization of the geometric model, regular Q4P4 elements with 2×2 Gauss points and element size $h = 1\text{m}$ are adopted for the FEM mesh, as shown in Fig.1b. The FEM model is restrained in the horizontal direction but allowed to move vertically. The lower boundary is fixed in the vertical direction, the upper boundary is fully drained and the other boundaries are impermeable. The downward direction is positive for the z-axis. The numerical schemes based on the polynomial and Fourier expansions are abbreviated as PTSIM-P and PTSIM-T, respectively. The values of $q = L = 4$ and $N = 20$ are generally recommended [44].

4.1. Case 1: Step loading problems

In order to evaluate the performance of the PTSIM-P scheme, the considered step loading condition is provided in Fig. 2a. For a time-step load on the upper boundary, the distributed load of $\sigma_0 = 10^4\text{Pa}$ is applied during a time period of $t_0 = 100\text{s}$, and the ramp load remains constant thereafter. In this case, the hydraulic and mechanical properties for the poroelastic medium, $E = 100\text{MPa}$, $\nu = 0.25$, $n = 0.375$, $Q^* = +\infty\text{MPa}$, $k = 10^{-5}\text{m/s}$, $\rho_f = 1000\text{kg/m}^3$, $\alpha = 1.0$. Both the initial pore pressure and the displacement are zero. The analytical solutions for pore pressure and vertical displacement had been described in [46,47].

Let the time-step size $\Delta t = 5\text{s}$. The numerical results and the analytical solutions at different moments are compared in Figs. 3 and 4. It can be seen that both the pressure profiles and the vertical displacements are consistent with the analytical solutions. Table 1 presents the surface settlement obtained using the PTSIM-P scheme and the analytical approach. The table indicates that the numerical results are exactly the same as the analytical solutions and are independent of the time-step size. In another word, the timescale effect is completely eliminated. However, the solutions using the standard FD-based FEM are affected significantly by the time-step size, and a larger time-step size leads to a larger error. It should be noted that the results obtained using the PTSIM-P scheme in Table 1 are presented to only 2 digits after the decimal point. In fact, the next 10 digits after the decimal point are also the same for the numerical and analytical solutions.

Fig. 1

Fig. 2

Fig. 3

Fig. 4

Table 1

4.2. Case 2: Cyclic loading problems

In order to evaluate the performance of the PTSIM-T scheme, a cyclic loading problem is considered. The loading varies in a manner shown in Fig. 2b, where $\sigma_0 = 10^6 \text{Pa}$ and duration of $T = t_a + t_b = 100\text{s} + 200\text{s} = 300\text{s}$. Let $E = 100\text{MPa}$, $\nu = 0.25$, $n = 0.375$, $K_s = +\infty\text{MPa}$, $K_f = 0.23 \times 10^4 \text{MPa}$, $k = 10^{-4} \text{m/s}$, $\rho_f = 1000 \text{kg/m}^3$, $\alpha = 1.0$. The initial pore pressure and displacement are zero. The analytical solution for the pore pressure can be derived according to Conte and Troncone [48].

In the PTSIM-T scheme, the prescribed loading needs to be expanded into a number (M) of harmonic components of Fourier series. Let the time-step size $\Delta t = 5\text{s}$. Fig. 5 compares the pore water pressures at the model bottom obtained by numerical modeling and theoretical analysis during a certain period for different M values. When $M = 20$, the simulation results are convergent and close to those for $M = 30$. Figs. 6 and 7 compare the numerical results and the analytical solutions at different moments. It can be seen that the pore water pressure and the vertical displacement obtained by numerical modeling agree very well with the analytical solutions. Table 2 compares the pore water pressures obtained by numerical modeling and theoretical analysis at different locations for various time-step sizes. It can be seen that the numerical results are stable and close to the analytical solutions when the time-step size Δt changes from 5s to 300s, and the precision is unaffected by the time-step size. Obviously, the computational efficiency is greatly enhanced. It is demonstrated that the PTSIM-T scheme is suitable for problems considering long time durations and multi-timescales.

Fig. 5

Fig. 6

Fig. 7

Table 2

4.3. Case 3: Harmonic loading problems

In this case, a cyclic harmonic loading of $\sigma_0 = A(1 - \cos \omega t)$ is considered, where A is the multiplication factor and $\omega = 2\pi/T$, as indicated in Fig. 2c. Let $A = 5000$, $T = 200\text{s}$. The initial pore pressure and displacement are zero. The analytical solution for the pore pressure and displacement can be derived according to Conte and Troncone [48]. In order to examine the accuracy of the PTSIM-P and PTSIM-T schemes, the numerical results are compared with the

results obtained by standard FD-based FEM and the analytical solutions. Let $E = 100\text{MPa}$, $\nu = 0.25$, $n = 0.375$, $K_s = +\infty\text{MPa}$, $K_f = 0.23 \times 10^4\text{MPa}$, $k = 10^{-5}\text{m/s}$, $\rho_f = 1000\text{kg/m}^3$, $\alpha = 1.0$.

Fig. 8 compares the pressure profiles obtained by numerical modeling and theoretical analysis at different moments. It can be seen that the numerical results using the PTSIM-P and PTSIM-T schemes are in good agreement with the analytical solutions, which are better than the standard FD-based FEM. Fig. 9 compares the numerical results and analytical solutions for pore water pressures at the model bottom. It can be seen that the results by the two numerical schemes are consistent. The peak and valley pore water pressures at the model bottom tend to be stable after a few cycles. Correspondingly, the surface subsidence also tends to be stable, as shown in Fig. 10. This is consistent with the conclusion obtained by Razouki et al. [49] and the simulation results obtained by the two schemes are in good agreement. Table 3 presents the numerical solutions obtained by the PTSIM-P and PTSIM-T schemes and the analytical solutions for ten monitoring points at $t = 360\text{s}$ with various time-step sizes. It can be observed that the precision of the standard FD-based FEM decreases remarkably with increasing time-step size. The precision of the proposed schemes is significantly better than that of the standard FD-based FEM under different time-step sizes, and the results are extremely stable. The modeling results also indicate that the proposed method is not sensitive to the numerical error caused by loading approximation and has great advantages when dealing with problems involving large timescales. On one hand, computational accuracy can be maintained even for large time-step sizes; on the other hand, the computational efficiency can be improved significantly.

Fig. 8

Fig. 9

Fig. 10

Table 3

5. Discussion

5.1. Stability analysis

To investigate the stability of a direct time-integration scheme, it is necessary to prove that the spectral radius ρ of the approximation operator matrix $\mathbf{T}$ is less than or equal to unity [38].

We perform a modal decomposition of Eq. (9), where item **RHS** has been set to zero, like

$$\mathbf{x}_{k+1} = \mathbf{T}\mathbf{x}_k = \exp(\bar{\mathbf{H}}\Delta t)\mathbf{x}_k \quad (26)$$

The specific form of the $\bar{\mathbf{H}}$ reads

$$\bar{\mathbf{H}} = -\bar{\mathbf{M}}^{-1}\bar{\mathbf{K}} = \begin{bmatrix} \mathbf{0} & -\mathbf{K}^{-1}\mathbf{Q}(\mathbf{S} + \mathbf{Q}^T\mathbf{K}^{-1}\mathbf{Q})^{-1}\mathbf{H} \\ \mathbf{0} & -(\mathbf{S} + \mathbf{Q}^T\mathbf{K}^{-1}\mathbf{Q})^{-1}\mathbf{H} \end{bmatrix} \quad (27)$$

It is assumed that the dimension of the square matrix $\mathbf{K}$ is n_u and its rank $r(\mathbf{K}) = n_u$. n_p is the dimension of the square matrix $\mathbf{H}$ and $r(\mathbf{H}) = n_p$. $\mathbf{S} + \mathbf{Q}^T\mathbf{K}^{-1}\mathbf{Q}$ and $\mathbf{H}$ are positive definite matrices, let $\lambda_1, \lambda_2, \dots, \lambda_{n_p}$ be the distinct generalized eigenvalues of $\mathbf{S} + \mathbf{Q}^T\mathbf{K}^{-1}\mathbf{Q}$ to $\mathbf{H}$. By matrix theory, λ_i ($i = 1, \dots, n_p$) all are positive real number, thus the eigenvalues of $\bar{\mathbf{H}}$ are 0 (n_u order) and $-\lambda_i$, respectively. Let λ_j ($j = 1, \dots, n_u + n_p$) represent all the eigenvalues. Then, the homogeneous form of Eq. (26) decomposes into $n_u + n_p$ equations,

$$x_{k+1}^j = T_j x_k^j \quad (28)$$

where x^j denote the scalar values, obtained by premultiplying the vector $\mathbf{x}$ by the eigenvectors $\boldsymbol{\eta}_j^T$ of $\bar{\mathbf{H}}$ as

$$x^j = \boldsymbol{\eta}_j^T \mathbf{x} \quad (29)$$

and

$$T_j = \begin{cases} 1 & , \lambda = 0 \\ 1 + \lambda\tau + \frac{(\lambda\tau)^2}{2} + \frac{(\lambda\tau)^3}{3!} + \dots + \frac{(\lambda\tau)^L}{L!} \rightarrow e^{\lambda\tau} & , \lambda = -\lambda_i \end{cases} \quad (30)$$

then

$$|T_j| \leq 1 \quad (31)$$

Hence, for an arbitrary time-step size,

$$\rho(\mathbf{T}) \equiv 1 \quad (32)$$

It can be seen that the spectral radius $\rho(\mathbf{T})$ of the differential matrix system is equal to 1. $\rho(\mathbf{T})$ can be seen as the amplification factor for whether the numerical errors are bounded or grown. Therefore, the current FE modeling scheme is unconditionally stable.

5.2. Precise estimation and convergence analysis

To estimate the algorithmic error, it can be defined that

$$\|\mathbf{e}_{Tot}\| = \|\mathbf{e}_h\| + \|\mathbf{e}_T\| + \|\mathbf{e}_{RHS}\| \quad (33)$$

where $\mathbf{e}_{Tot}$ is the total error between the exact solution and the numerical solution; and the symbol $\|\cdot\|$ indicates an appropriate norm (e.g., L^2 -norm). If the norm of each part of $\mathbf{e}_{Tot}$ is negligibly small, $\mathbf{e}_{Tot}$ is also negligible. The discretization error $\mathbf{e}_h$ in the space domain is caused by the standard FE process as the derivation of Eq. (6). If an r -order complete polynomial is used in the FEM for an element with a size of h , the local fitting precision can be of the r -order, i.e., the solution error is $\mathbf{e}_h = O(h^{r+1})$. The consistency and convergence of the FE discretization in the space domain can be satisfied by enhancing the spatially discrete quantities and using proper continuous piecewise interpolation polynomials for $\mathbf{u}$ and p . $\mathbf{e}_T$ is the computational errors of the exponential matrix $\mathbf{T}$. Let Φ is an n_u+n_p order matrix composed of all the eigenvectors of $\bar{\mathbf{H}}$ as its columns η_j and $\text{diag}[\cdot]$ means diagonal matrix.

Then have

$$\exp(\bar{\mathbf{H}}\tau) = \Phi \exp(\text{diag}[\lambda_j]\tau) \Phi^{-1} = \Phi \text{diag}[\exp(\lambda_j\tau)] \Phi^{-1} \quad (34)$$

Thus, the truncation

$$\exp(\lambda_j\tau) \approx 1 + \lambda_j\tau + \frac{(\lambda_j\tau)^2}{2} + \frac{(\lambda_j\tau)^3}{3!} + \dots + \frac{(\lambda_j\tau)^L}{L!} \quad (35)$$

The above analysis distinguishes the errors coming from eigenvalues. The relative errors in Eq. (34) for each eigensolution being of the order of $L+1$. Except for the round-off error in the conventional computer arithmetic used in the matrix multiplication, $\mathbf{e}_T$ can be induced from only the power series expansion truncation. In theory, the arbitrary numerical accuracy of $\mathbf{T}$ can be met by setting the selected parameters N and L . Note the double precision of real type number in today's computer has 16 decimal digits. Therefore, within the computer double precision, requirement is

$$\left(\frac{|\lambda_j| \cdot \Delta t}{2^N} \right)^L / L! < 10^{-16} \quad (36)$$

Based on numerical experience and balanced between computational complexity and accuracy, for instance, if $N = 20$ and $L = 4$, Eq. (36) can meet the vast majority of cases, the numerical result reaches the computer precision, while $\mathbf{e}_T = O(\Delta t^5) = 10^{-30} O(\tau^5)$, which is on the order of the round-off error for ordinary computers. Furthermore, it is known that if the time discretization error $O(\Delta t^i)$, where $i > 0$, the numerical scheme is convergent [38]. Then,

$\mathbf{e}_{RHS}$ represents the computational errors of item **RHS**. If the **RHS** can be expressed analytically, $\mathbf{e}_{RHS}$ can be neglected. For a general case with time-dependent loading, the error

is entirely caused by the approximation of $\mathbf{f}$. For Taylor expansion, the order of accuracy of Eq. (15) is $O(\xi^{n+1})$, therefrom $\mathbf{e}_{RHS} = O(\Delta t^{n+q+2})$. Therefore, an arbitrary order of accuracy can be met by prescribing a suitable value of n . Moreover, $\mathbf{f}$ can be expanded by using multi-step techniques, so as to further enhance the calculation accuracy and avoid derivative information of $\mathbf{f}$. Finally it should be noted that the initial condition is known, the initial error is zero, and $\|\mathbf{T}\| \leq 1$ is verified, which is a necessary and sufficient condition for the convergence of iterations defined by Eq. (9) (consistency).

6. Conclusions

In this paper, a multi-timescale high-accuracy modeling scheme is proposed for the hydro-mechanically coupled processes for fluid-saturated poroelastic media. The FE configuration is used for spatial discretization of the governing equations. Explicit direct integration is constructed for discretization in the time domain. The first key to multi-timescale high-accuracy modeling is precise calculation of the exponential transfer matrix based on the downscaling time step integration method, so as to achieve accurate results in the computer sense. The second key is continuous approximation of the basic function in a polynomial or trigonometric form under complex time-dependent load and highly accurate calculation of the response matrix for the load item **RHS** by taking advantages of the high calculation accuracy of the exponential transfer matrix. Theoretically speaking, the computational error in the entire process is caused by spatial discretization of the FE model and approximation of $\mathbf{f}$. Computer precision can be achieved for numerical calculation of time differentials. The advantages of the proposed scheme can be summarized as follows:

- The computational scheme is fully explicit and unconditionally stable;
- For a complex time-dependent load, high-accuracy can be achieved even in case of large time-step sizes. The error is only caused by mesh discretization;
- It has a simple algorithm structure, in which the mathematical operation can be easily implemented.

The proposed scheme has been applied for the benchmark problems as well as the step, cyclic and harmonic loading cases. High-accuracy is achieved even for extremely large timescales. The proposed scheme has great potential in engineering applications for problems involving long time durations and multiple timescales at relatively low computational cost. In addition, due to the limitation of using Biot's theory, many important factors, such as the particle shape of the porous medium, pore-fluid and medium compressibility, solute dispersion and mineral dissolution ratio [50-52], have been neglected in this study, which

needs to be considered in the future research work.

Acknowledgements

This work is supported in part by the 973 program (2014CB047100), the Science Fund for Creative Research Groups of the National Natural Science Foundation of China (51121005), the National Science Foundation of China (51679028, 51309261) and the Fundamental Research Funds for the Central Universities (DUT15RC(3)082).

References

- [1] Wang HF. Theory of Linear Poroelasticity with Applications to Geomechanics and Hydrogeology. Princeton University Press: New Jersey, 2000.
- [2] Rutqvist J, Stephansson O. The role of hydromechanical coupling in fractured rock engineering. *Hydrogeol J* 2003; 11:7-40.
- [3] Terzaghi K. *Erdbaumechanik auf Bodenphysikalischer Grundlage*. F. Duticke, Vienna, 1925.
- [4] Biot MA. General theory of three-dimensional consolidation. *J Appl Phys* 1941; 12:155-64.
- [5] Lewis RW, Schrefler BA. *The Finite Element Method in the Static and Dynamic Deformation and Consolidation of Porous Media*. 2nd ed. Chichester: Wiley, 1998.
- [6] Zhao C, Hobbs BE, Ord A. *Convective and Advective Heat Transfer in Geological Systems*. Springer, Berlin, 2008.
- [7] Zhao C, Hobbs BE, Ord A. *Fundamentals of Computational Geoscience: Numerical Methods and Algorithms*. Springer, 2009.
- [8] Hobbs BE, Ord A. Theoretical analyses of nonaqueous-phase-liquid dissolution induced instability in two-dimensional fluid-saturated porous media. *Int J Numer Anal Meth Geomech* 2010; 34(17):1767-96.
- [9] Poulet T, Regenauer-Lieb K. Numerical modeling of toxic nonaqueous-phase-liquid removal from contaminated groundwater systems: mesh effect and discretization error estimation. *Int J Numer Anal Meth Geomech* 2015; 39:571-93.
- [10] Hornby P, Ord A, Peng S, Liu L. Theoretical and numerical analyses of chemical-dissolution front instability in fluid-saturated porous rocks. *Int J Numer Anal Meth Geomech* 2008; 32:1107-30.
- [11] Hobbs BE, Ord A. Theoretical analyses of acidization-dissolution front instability in fluid-saturated carbonate rocks. *Int J Numer Anal Meth Geomech* 2013; 37:2084-105.
- [12] Hornby P, Peng S. Effect of reactive surface areas associated with different particle shapes on chemical-dissolution front instability in fluid-saturated porous rocks. *Transport Porous Med* 2008; 73:75-94.
- [13] Hobbs, BE, Ord A. Effects of medium and pore-fluid compressibility on chemical-dissolution front instability in fluid-saturated porous media. *Int J Numer Anal Meth Geomech* 2012; 36:1077-100.
- [14] Hobbs BE, Ord A. Theoretical analyses of the effects of solute dispersion on chemical-dissolution front instability in fluid-saturated porous rocks. *Transport Porous Med* 2010; 84:629-53.
- [15] Ord A, Peng S. Effects of mineral dissolution ratios on chemical-dissolution front instability in fluid-saturated porous media. *Transport Porous Med* 2010; 82:317-35.

-
- [16] Hobbs BE, Ord A. Computational simulation of chemical dissolution-front instability in fluid-saturated porous media under non-isothermal conditions. *Int J Numer Meth Eng* 2015; 102:135-56.
- [17] Hobbs BE, Ord A. Theoretical analyses of chemical dissolution-front instability in fluid-saturated porous media under non-isothermal conditions. *Int J Numer Anal Meth Geomech* 2015; 39:799-820.
- [18] Reid LB, Regenauer-Lieb K, Poulet T. A porosity-gradient replacement approach for computational simulation of chemical-dissolution front propagation in fluid-saturated porous media including pore-fluid compressibility. *Computat Geosci* 2012; 16:735-55.
- [19] Meschke G, Leonhart D. A Generalized Finite Element Method for hydro-mechanically coupled analysis of hydraulic fracturing problems using space-time variant enrichment functions. *Comput Methods Appl Mech Engrg* 2015; 290:438-65.
- [20] Abbasi N, Rahimi H, Javadi AA, Fakher A. Finite difference approach for consolidation with variable compressibility and permeability. *Comput Geotech.* 2007; 34:41-52.
- [21] Li G. A four-node plane parametric element based on quadrilateral area coordinate and its application to coupled solid-deformation/fluid-flow simulation for porous geomaterials. *Int J Numer Anal Meth Geomech* 2015; 39:251-76.
- [22] Ferronato M, Castelletto N, Gambolati G. A fully coupled 3-D mixed finite element model of Biot consolidation. *J Comput Phys* 2010; 229:4813-30.
- [23] Khoshghalb A, Khalili N. An alternative approach for quasi-static large deformation analysis of saturated porous media using meshfree method. *Int J Numer Anal Meth Geomech* 2015; 39:913-36.
- [24] Samimi S, Pak A. Three-dimensional simulation of fully coupled hydro-mechanical behavior of saturated porous media using Element Free Galerkin (EFG) method. *Comput Geotech* 2012; 46:75-83.
- [25] Zienkiewicz OC, Taylor RL. *The Finite Element Method for Solid and Structural Mechanics*. 6th Edition. Oxford: Elsevier Butterworth-Heinemann, 2005.
- [26] Hudson JA, Stephansson O, Andersson J. Guidance on numerical modelling of thermo-hydro-mechanical coupled processes for performance assessment of radioactive waste repositories. *Int J Rock Mech Min Sci* 2005; 42:850-70.
- [27] Parka J-W, Rutqvist J, Ryu D, Park E-S, Synn J-H. Coupled thermal-hydrological-mechanical behavior of rock mass surrounding a high-temperature thermal energy storage cavern at shallow depth. *Int J Rock Mech Min Sci* 2016; 83:149-61.
- [28] Yasuhara H, Kinoshita N, Ogata S, Cheonb D-S, Kishida K. Coupled thermo-hydro-mechanical-chemical modeling by incorporating pressure solution for estimating the evolution of rock permeability. *Int J Rock Mech Min Sci* 2016; 86:104-14.
- [29] Wang ZC, Li SC, Qiao LP, Zhang QS. Finite element analysis of the hydro-mechanical behavior of an underground crude oil storage facility in granite subject to cyclic loading during operation. *Int J Rock Mech Min Sci* 2015; 73:70-81.
- [30] Khaledi K, Mahmoudi E, Datcheva M, Schanz T. Stability and serviceability of underground energy storage caverns in rock salt subjected to mechanical cyclic loading. *Int J Rock Mech Min Sci* 2016; 8:115-31.
- [31] Khoshghalb A, Khalili N, Selvadurai APS. A three-point time discretisation technique for parabolic partial differential equations. *Int J Numer Anal Meth Geomech* 2011; 35(3):406-18.
- [32] Rybak I, Magiera J. A multiple-time-step technique for coupled free flow and porous medium systems. *J Comput Phys* 2014; 272:327-42.
- [33] Sloan SW, Abbo AJ. Biot consolidation analysis with automatic time stepping and error control part I: Theory and implementation. *Int J Numer Anal Meth Geomech* 1999; 23:467-92.

-
- [34] Minkoff SE, Kridler NM. A comparison of adaptive time stepping methods for coupled flow and deformation modeling. *Appl Math Model* 2006; 30:993-1009.
- [35] Larsson F, Runesson K. A sequential-adaptive strategy in space-time with application to consolidation of porous media. *Comput Methods Appl Mech Engrg* 2015; 288:146-71.
- [36] Turska E, Wisniewski K., Schrefler BA. Error propagation of staggered solution procedures for transient problems. *Comput Methods Appl Mech Engrg* 1994; 144:177-88.
- [37] Turska E, Schrefler BA. On convergence conditions of partitioned solution procedures for consolidations problems. *Comput Methods Appl Mech Engrg* 1993; 106:51-63.
- [38] Kim J, Tchelepi HA, Juanes R. Stability and convergence of sequential methods for coupled flow and geomechanics: Drained and undrained splits. *Comput Methods Appl Mech Engrg* 2011; 200:2094-116.
- [39] Li G, Tang CA, Li LC, Li H. An unconditionally stable explicit and precise multiple timescale finite element modeling scheme for the fully coupled hydro-mechanical analysis of saturated poroelastic media. *Comput Geotech* 2016; 71:69-81.
- [40] Zhao C. *Dynamic and Transient Infinite Elements: Theory and Geophysical, Geotechnical and Geoenviromental Applications*. Springer, Berlin, 2009.
- [41] Zhao C, Valliappan S, Wang Y. A numerical model for wave scattering problems in infinite media due to P and SV wave incidences. *Int J Numer Meth Eng* 1992; 33: 1661-82.
- [42] Zhao C. Computational simulation of wave propagation problems in infinite domains. *Sci China Ser G* 2010; 53(8):1397-407.
- [43] Zhao C, Valliappan S. Seismic wave scattering effects under different canyon topographic and geological conditions. *Soil Dyn Earthq Eng* 1993; 12:129-43.
- [44] Zhong WX. On precise integration method. *J Comput Appl Math* 2004; 163:59-78.
- [45] Lin JH, She WP, Williams FW. A high precision direct integration scheme for structures subjected to transient dynamic loading. *Comput Struct* 1995; 56:113-20.
- [46] Asadi R, Ataie-Ashtiani B, Simmons CT. Finite volume coupling strategies for the solution of a Biot consolidation model. *Comput Geotech* 2014; 55:494-505.
- [47] Olson RF. Consolidation under time-dependent loading. *J Geotech Eng Div (ASCE)* 1977; 103(GT1):55-60.
- [48] Conte E, Troncone A. One-dimensional consolidation under general time-dependent loading. *Can Geotech J* 2006; 43:1107-16.
- [49] Razouki SS, Bonnier P, Datcheva M, Schanz T. Analytical solution for 1D consolidation under haversine cyclic loading. *Int J Numer Anal Meth Geomech* 2013; 37:2367-72.
- [50] Ord A, Hobbs BE. Analytical solutions of nonaqueous-phase-liquid dissolution problems associated with radial flow in fluid-saturated porous media. *J Hydrol* 2013; 494:96-106.
- [51] Zhao C. *Physical and Chemical dissolution Front Instability in Porous Media: Theoretical Analyses and Computational Simulations*, Springer, Berlin, 2014.
- [52] Poulet T, Regenauer-Lieb K. Computational modeling of moving interfaces between fluid and porous medium domains. *Computat Geosci* 2013; 17:151-66.

List of tables

Table 1 Surface settlement obtained by theoretical analysis and numerical simulation (Unit: 10^{-4} m).

Table 2 Pore water pressures at various depths obtained by theoretical analysis and numerical simulation (Unit: kPa).

Table 3 Pore water pressures at various depths obtained by numerical simulation and theoretical analysis for $t = 360$ s (Unit: kPa).

List of figures

Fig. 1. For a time-dependent loading on a water-saturated elastic porous medium, surface subsidence occurs after drainage through permeable surface. (a) The FEM model is considered as a plane-strain model. (b) A bilinear-displacement/bilinear-pressure quadrangular (Q4P4) element, used for modeling.

Fig. 2. Three examples of time-dependent loading. (a) Step load, (b) cyclic load, and (c) harmonic load.

Fig. 3. Comparison of pore water pressure profiles obtained by the PTSIM-P scheme and analytical solutions (a) $t \leq 100$ s and (b) $t \geq 100$ s.

Fig. 4. Comparison of vertical displacement obtained by the PTSIM-P scheme and analytical solutions (a) $t \leq 100$ s and (b) $t \geq 100$ s.

Fig. 5. Comparison of pore water pressure at the model bottom obtained by the PTSIM-T scheme and analytical solutions.

Fig. 6. Comparison of normalized pore water pressure profiles obtained by the PTSIM-T scheme and analytical solutions.

Fig. 7. Comparison of vertical displacements obtained by the PTSIM-T scheme and analytical solutions.

Fig. 8. Comparison of pore water pressure profiles obtained by numerical methods and analytical solutions.

Fig. 9. Comparison of pore water pressure at the model bottom obtained by numerical methods and analytical solutions.

Fig. 10. Comparison of surface settlement obtained by numerical methods and analytical solutions.

Figures

Fig. 1. For a time-dependent loading on a water-saturated elastic porous medium, surface subsidence occurs after drainage through permeable surface. (a) The FEM model is considered as a plane-strain model. (b) A bilinear-displacement/bilinear-pressure quadrangular (Q4P4) element, used for modeling.

Fig. 2. Three examples of time-dependent loading. (a) Step load, (b) cyclic load, and (c) harmonic load.

Fig. 3. Comparison of pore water pressure profiles obtained by the PTSIM-P scheme and analytical solutions (a) $t \leq 100s$ and (b) $t \geq 100s$.

Fig. 4. Comparison of vertical displacement obtained by the PTSIM-P scheme and analytical solutions (a) $t \leq 100s$ and (b) $t \geq 100s$.

Fig. 5. Comparison of pore water pressure at the model bottom obtained by the PTSIM-T scheme and analytical solutions.

Fig. 6. Comparison of normalized pore water pressure profiles obtained by the PTSIM-T scheme and analytical solutions.

Fig. 7. Comparison of vertical displacements obtained by the PTSIM-T scheme and analytical solutions.

Fig. 8. Comparison of pore water pressure profiles obtained by numerical methods and analytical solutions.

Fig. 9. Comparison of pore water pressure at the model bottom obtained by numerical methods and analytical solutions.

Fig. 10. Comparison of surface settlement obtained by numerical methods and analytical solutions.

Tables

Table 1 Surface settlement obtained by theoretical analysis and numerical simulation (Unit: 10^{-4} m)

Time (s)	Analytical solution	PTSIM-P				FEM				
		$\Delta t = 5$	$\Delta t = 10$	$\Delta t = 20$	$\Delta t = 100$	$\Delta t = 2$	$\Delta t = 5$	$\Delta t = 10$	$\Delta t = 20$	$\Delta t = 100$
20	0.19	0.19	0.19	0.19	-	0.20	0.21	0.23	0.26	-
40	0.55	0.55	0.55	0.55	-	0.56	0.57	0.60	0.65	-
60	1.01	1.01	1.01	1.01	-	1.02	1.04	1.07	1.13	-
80	1.55	1.55	1.55	1.55	-	1.57	1.59	1.63	1.69	-
100	2.17	2.17	2.17	2.17	2.17	2.19	2.21	2.25	2.33	2.87
140	3.05	3.05	3.05	3.05	-	3.06	3.07	3.09	3.14	-
200	3.97	3.97	3.97	3.97	3.97	3.97	3.98	4.00	4.03	4.25

Table 2 Pore water pressures at various depths obtained by theoretical analysis and numerical simulation (Unit: kPa)

Scheme	Depth (m)	Time-step size Δt (s)	Time (s)					
			$t = 3T + 50$	$t = 3T + 100$	$t = 3T + 150$	$t = 3T + 200$	$t = 3T + 250$	$t = 3T + 300$
Analytical	$z = 6$		94.77	201.25	17.76	-69.01	-112.50	-132.23
		$\Delta t = 5$	95.15	201.67	17.60	-69.27	-112.73	-132.39
		$\Delta t = 50$	95.15	201.67	17.60	-69.27	-112.73	-132.39
		$\Delta t = 100$	-	201.67	-	-69.27	-	-132.39
PTSIM-T	$z = 6$	$\Delta t = 200$	-	201.67	-	-	-	-132.39
		$\Delta t = 300$	-	-	-	-	-	-132.39
Analytical	$z = 10$		108.84	260.20	37.66	-84.96	-146.47	-175.23
		$\Delta t = 5$	109.37	260.79	37.44	-85.32	-146.78	-175.45
		$\Delta t = 50$	109.37	260.79	37.44	-85.32	-146.78	-175.45
		$\Delta t = 100$	-	260.79	-	-85.32	-	-175.45
PTSIM-T	$z = 10$	$\Delta t = 200$	-	260.79	-	-	-	-175.45
		$\Delta t = 300$	-	-	-	-	-	-175.45

Table 3 Pore water pressures at various depths obtained by numerical simulation and theoretical analysis for $t = 360s$ (Unit: kPa)

Scheme	Depth (m)									
	$z = 1$	$z = 2$	$z = 3$	$z = 4$	$z = 5$	$z = 6$	$z = 7$	$z = 8$	$z = 9$	$z = 10$
FEM										
$\Delta t = 4$	-1.34	-1.77	-1.65	-1.24	-0.73	-0.24	0.17	0.46	0.64	0.70
$\Delta t = 9$	-1.28	-1.69	-1.55	-1.16	-0.67	-0.21	0.17	0.44	0.61	0.67
$\Delta t = 18$	-1.19	-1.53	-1.39	-1.02	-0.58	-0.17	0.17	0.42	0.57	0.62
PTSIM-P										
$\Delta t = 4$	-1.38	-1.85	-1.73	-1.31	-0.78	-0.26	0.17	0.48	0.67	0.73
$\Delta t = 9$	-1.38	-1.85	-1.74	-1.32	-0.78	-0.27	0.16	0.48	0.67	0.73
$\Delta t = 18$	-1.39	-1.87	-1.77	-1.35	-0.82	-0.30	0.13	0.45	0.64	0.70
PTSIM-T										
$\Delta t = 4$	-1.38	-1.85	-1.73	-1.31	-0.78	-0.26	0.17	0.48	0.67	0.74
$\Delta t = 9$	-1.38	-1.85	-1.73	-1.31	-0.78	-0.26	0.17	0.48	0.67	0.73
$\Delta t = 18$	-1.38	-1.85	-1.73	-1.31	-0.78	-0.26	0.17	0.48	0.67	0.74
Exact solution	-1.38	-1.83	-1.71	-1.29	-0.76	-0.25	0.17	0.48	0.66	0.73