Infiltration and interrill erosion rates after a wildfire in western Montana, USA

Peter R. Robichaud^{a*}, Joseph W. Wagenbrenner^{a1}, Fredrick B. Pierson^b, Kenneth E. Spaeth^c,
Louise E. Ashmun^a, Corey A. Moffet^{b2}

^aU.S. Department of Agriculture, Forest Service, Rocky Mountain Research Station, 1221 South Main Street,
Moscow, ID 83843, USA. Email address: probichaud@fs.fed.us; leashmun.work@gmail.com

^bU.S. Department of Agriculture, Agricultural Research Service, Northwest Watershed Research Center, 800 East
Park Boulevard, Plaza IV Suite 105, Boise, ID 83712, USA. Email address: Fred.Pierson@ars.usda.gov

^cU.S. Department of Agriculture, Natural Resources Conservation Service, Central National Technology Support
Center, Fort Worth, TX 76115, USA. Email address: ken.spaeth@ftw.usda.gov

¹Present address: School of Forest Resources and Environmental Science, Michigan Technological University, 1400
Townsend Drive, Houghton, MI 49931, USA. Email address: jwwagenb@mtu.edu

²Present address: The Samuel Roberts Noble Foundation, 2510 Sam Noble Parkway, Ardmore, OK 73401, USA.
Email address: camoffet@noble.org

*Corresponding author: Tel: +1 208 883 2349; Fax: +1 208 883 2318; e-mail address: probichaud@fs.fed.us

Abstract

The 2000 Valley Complex wildfire burned in steep montane forests with ash cap soils in western Montana, USA. The effects of high soil burn severity on forest soil hydrologic function was examined using rainfall simulations (100 mm h^{-1} for 1 h) on 0.5-m^2 plots. Infiltration rates, sediment yields and sediment concentrations were compared among three treatments: control (unburned and undisturbed); bare (unburned with all surface vegetation, litter, and duff removed prior to each simulation); and burned. Rainfall simulations were done immediately after the fire and repeated in 2001, 2002, and 2005. Soil moisture, water repellency, and understory canopy and ground cover were measured and related to infiltration rates and sediment yields. The unburned forest soil was water repellent at the mineral surface. This surface repellency was no longer detected after it was burned at high severity, but a post-fire water repellent soil layer was observed at 1–2 cm below the surface. The control plots had high ground cover (90% overall), infiltration of 44–48 mm, and very low sediment concentrations (median values of $0.1\text{--}0.6 \text{ g L}^{-1}$) and sediment yields ($6\text{--}54 \text{ g m}^{-2}$) for all years despite changes in soil moisture and strong water repellency. The bare and control plots had similar water repellency values, but the interrill erosion in the bare plots was high throughout the study ($624\text{--}1277 \text{ g m}^{-2}$). In the year of the fire, the burned sites had high rates of soil water repellency (88%) and little ground cover (10%). This resulted in low infiltration rates (30 mm), high sediment concentrations (median value 21 g L^{-1}), and high sediment yields (1157 g m^{-2}). By 2005, the fire-altered water repellency decreased in occurrence (48%) and severity and the ground cover increased (42%). This resulted in much greater infiltration (84 mm), lower sediment concentration (median value 0.5 g L^{-1}), and lower sediment yields (15 g m^{-2}) on the burned plots. The importance of ground cover for preventing interrill erosion was demonstrated by the very low sediment yields on the control plots as compared to the bare and burned plots. The strength and occurrence of water repellency in both the unburned and burned sites decreased as soil moisture increased; however, strong soil water repellency was detected at the soil surface whenever unburned soils were dry. Fire-altered soil water repellency influenced the infiltration capacity and increased runoff rates immediately after

45 the fire; however, the loss of protective ground cover was a more significant factor for the
46 increased sediment concentrations and sediment yields.

47 **Keywords:**

48 *Ground cover, post-fire recovery, rainfall simulation, sediment yield, soil water repellency,*
49 *water drop penetration time*

50

1. Introduction

Post-fire increases in runoff, flooding, and erosion are generally attributed to the loss of vegetation and forest floor material which leaves the forest soil less protected and more vulnerable to the erosive effects of rainfall, overland flow, wind, and gravity. The direct effects of fire on forest soils, such as loss of organic matter and changes in soil water repellency, aggregate stability, and soil water retention, can change infiltration of water and runoff amounts and characteristics; thus contributing to post-fire erosion vulnerability as well (e.g., Bento-Gonçalves et al., 2012; Certini, 2005; DeBano et al., 1998; Inbar et al., 2014; Larsen et al., 2009; Leighton-Boyce et al., 2007; Shakesby and Doerr, 2006). Understanding fire effects on infiltration is vital for the prediction of post-fire flooding and erosion responses.

Many factors control infiltration rates, and in forest environments vegetation is a dominant factor (Castillo et al., 1997; Cerdà, 1999; Cerdà and Doerr, 2005; Cerdà and Robichaud, 2009; Faulkner, 1990). Vegetation increases infiltration rates by adding organic material to the soil, which improves soil structure and porosity, and by deepening the litter layer (Abrahams et al., 1995; Berndtsson and Larson 1987; Jiménez et al., 2006; Wilcox et al., 1988). The macropores developed by plant roots provide preferential flow paths (Beven and Germann, 2013) and also increase the water holding capacity of the soil. The litter and duff layers can further enhance infiltration by absorbing and storing water and allowing more time for infiltration into the soil (Brock and DeBano, 1982; Lowdermilk, 1930). Both the vegetation and the forest floor protect the mineral soil from direct impact of the rain drops and the subsequent destruction of the soil aggregates, compaction, slaking, particle segregation, and the filling and clogging of pores by the wash-in of fine material, all of which can form structural seals at the soil surface and reduce infiltration capacity (Assouline, 2004; Liu et al., 2011; Mataix-Solera et al., 2011; Woods and Balfour, 2010).

Fire-altered water repellency forms when surface vegetation, litter, and near-surface soil organic matter are burned and a fraction of the vaporized hydrocarbons condense on soil particles in the cooler layers beneath the surface (DeBano, 1981; Doerr et al., 2000). The degree and depth of

the fire-altered soil water repellent layer varies with the degree of soil heating over small spatial scales (Huffman et al., 2001), resulting in preferential flow paths through less water repellent areas and the formation of uneven wetting fronts (Dekker and Ritsema, 1994, 1995; Ritsema and Dekker, 1994, 2000). Macro-pores such as root channels that remain after roots burn can also serve as pathways for water to infiltrate through water repellent layers (Burch et al., 1989; Doerr et al. 2006a; Meeuwig, 1971; Shakesby et al., 2000). Because of the reduced infiltration rates, overlying layers of ash and/or soil may saturate, and this could lead to lateral surface or near-surface flow (Bodí et al., 2012; Doerr et al., 2006a; Ebel et al., 2012).

Soil water repellency has often served as a surrogate measurement of infiltration capacity in post-fire assessments (DeBano, 1981; Parson et al., 2010; Robichaud et al., 2008). Although there is a clear association between fire-altered soil water repellency and enhanced post-fire hydrologic and erosion response, the effect of soil water repellency often has been oversimplified (Doerr et al., 2009a; Leighton-Boyce et al., 2007). The contribution of fire-altered soil water repellency on runoff and erosion is difficult to separate from other fire impacts such as loss of vegetation and forest floor material, decreased surface roughness, soil disaggregation, soil sealing, etc. (Doerr and Moody, 2004; Larson et al., 2009; Leighton-Boyce et al., 2007; Shakesby and Doerr, 2006).

Soil water repellency is not only caused by fire, but is an inherent soil characteristic found in many types of soils with a range of textures, organic contents, vegetation, land uses, and locations (Doerr et al., 2006b; Jordán et al., 2009, 2013; Mataix-Solera et al., 2007). Long unburned forest soils with inherent soil water repellency at or near the soil surface have been observed worldwide in certain forest types (Doerr et al., 2006b; Doerr et al., 2009b). Although soil water repellency is classically associated with coarse-textured soils (Mataix-Solera et al., 2013; Moral García et al., 2005; Robichaud and Hungerford, 2000), the organic-rich surface layers of volcanic ash soils (andisols) have highly aggregated soil structure that retain water and are often water repellent when dry (Kawamoto et al., 2007). In addition, inherent soil water repellency in fine-textured soils more consistently decreases with depth and has a greater impact on infiltration than soil water repellency in coarser soils (Fox et al., 2007; Mataix-Solera et al.,

2013; Rodriguez-Alleres et al., 2007). In addition, inherent soil water repellency has been associated with vegetation that contains waxes, resins, or oils such as eucalyptus and pine trees and sagebrush and chaparral shrubs (DeBano, 1981; Lozano et al, 2013; Martínez-Zavala and Jordán-López, 2009; Mataix-Solera et al., 2007; Pierson et al., 2001). Generally, both inherent and fire-altered soil water repellency is lost during long wet periods and is re-established upon drying, causing short-term or seasonal variations (de Jonge et al., 1999; Dekker and Ritsema, 1996; Dekker et al., 2001; MacDonald and Huffman, 2004; Robichaud and Hungerford, 2000). The change in soil water repellency may occur over a range of soil moistures, or a “transition zone,” such that both water repellent and wettable soils may exist within the transition zone but only water repellent conditions exist when soil moisture is below the lower boundary and only wettable conditions exist above the upper boundary (Dekker and Ritsema, 1994; Dekker et al., 2001; Regalado and Ritter, 2005). The influence of forest floor material on infiltration rates into inherently water repellent soils is not easily determined. If the organic material that overlays the mineral soil helps maintain soil moisture above the threshold for wettability, it enhances infiltration (Feng et al., 2001; Lehty, 2001; Wang et al., 2000). However, short rainfall simulations may not capture this process. Leighton-Boyce et al. (2007) found that inherent soil water repellency in mature eucalyptus plantation sites persisted through a 30-min high intensity (107 mm h^{-1}) rainfall simulation and that the majority of rainfall which did not become overland flow was stored within the litter layer rather than infiltrating into the soil.

Several others have used rainfall simulation to evaluate the impact of fires in coniferous forests (Table 1; see review by Vieira et al., 2015). However, the small plot rainfall simulations, such as those used in our study, may not accurately represent infiltration and erosion processes at larger scales. The short lengths of the rainfall simulation plots restrict erosion to rain splash and sheetwash (interrill) processes (Bryan, 2000; Huang et al., 2001). At larger scales, however, hillslope processes include differential flow patterns, detention and storage of runoff and sediment, and rill erosion. Generally, small plots have greater per-unit-area runoff rates than

larger scales where the existence of preferential flow paths may create scattered “sink” areas across a hillside that allow water to infiltrate (Imeson et al., 1992; Nyman et al., 2010; Prosser and Williams, 1998; Stoof et al., 2012). Yet these studies can provide insight to fire effects especially when unburned plots are used for comparison (Table 1). Given the large, and occasionally extreme, post-fire runoff events and the associated flooding and erosion, the need to understand and accurately predict post-fire hydrologic and geomorphic responses continues to drive research (Moody et al., 2013). We measured the immediate and short-term effects (5 years) of high severity wildfire on infiltration rates, interrill erosion rates, and other related variables. Specifically, the objectives of the study were to use small-plot rainfall simulations to compare infiltration rates, sediment concentrations, and sediment yields among three treatments—unburned with no recent disturbance (control), unburned with surface litter, duff, and vegetation removed (bare), and burned at high soil burn severity (burned). Soil water repellency, canopy cover and ground cover were also compared. Rainfall simulations and other measurements were done immediately after the fire and repeated in post-fire years one, two, and five to measure temporal affects.

2 Materials and methods

2.1 Site description

We measured the runoff and sediment concentrations from simulated rainfall on seven forested sites within the 144,000 ha burn perimeter of the 2000 Valley Complex Fire in the Bitterroot Valley, Montana (Fig. 1). About a third of this area burned at high soil burn severity (USDA Forest Service 2000), our study site was in the high soil burn severity portion of the burned area and adjacent unburned area. Three unburned sites (U5–U7) and four high soil burn severity sites (B1–B4) (approximately 3 km south) were selected based on similarity of slopes (37–50%), elevations (1880–2050 m), aspects (200–285 degrees, with the exception of U5 with an aspect of 150 degrees), and road access. For all seven sites, the vegetation or pre-fire vegetation was sub-alpine fir (*Abies lasiocarpa*) and fool’s huckleberry (*Menziesia ferruginea*). Soils were derived from volcanic ash underlain by weathered granite with a soil classification of

sandy skeletal andic-dystrocryept (McBride, 2000; USDA Forest Service, 2000). The Daly Creek snow telemetry site was used to compare precipitation during the study period to the 1981–2006 average annual precipitation of 636 mm (NRCS, 2007). About two-thirds of the annual precipitation occurs as snow.

2.2 Plot preparation and measurements

A total of 102 plots were installed across burned and unburned sites with 14 plots at each of the three unburned sites and 15 plots at each of the four burned sites. On seven unburned plots at each unburned site, the litter, duff, vegetation, and surface roots were removed before each simulation for each year of simulation, leaving a surface of exposed (“bare”) mineral soil (Fig. 2). Longer roots, such as taproots, that extended below the surface were cut at the surface of the mineral soil. All of the overlying material that was removed from the bare plots in 2000 was dried and weighed and then saturated and weighed to determine the water storage capacity of the litter and duff layers from the unburned plots. The remaining unburned plots (21 plots—seven at each unburned site) were left undisturbed as controls.

Rainfall simulations were conducted on 0.75 by 0.75 m (0.5-m²) plots bounded by a 15 cm tall steel square frame. Each plot frame was inserted 5 cm into the ground leaving 10 cm extending above the ground surface. A covered tray at the downhill end of the frame captured runoff at the ground surface and routed the runoff into a pipe used for sampling. The interior edges of the plot were filled with a bentonite mixture to reduce the occurrence of preferential flow paths along the edges of the plot frames. The slope of each plot was measured using an Abney level on the sides of the plot frame. Plots were established and rainfall simulations conducted within a few weeks of fire containment, between 12 and 20 September 2000 (post fire year 0 [PF0]). The rainfall simulations were repeated on 14 plots (three control, three bare, and eight burned) shortly after snow melt, between 19 and 21 June 2001 (spring PF1) to evaluate the effects of higher soil moisture. Simulations repeated on all available plots between 7 and 10 August 2001 (PF1), 28 July and 5 August 2002 (PF2), and 28 July and 1 August 2005 (PF5). Some plot frames were damaged between annual measurements, leaving 20 control, 17 bare, and

54 burned plots to be tested in PF5. We present the results from the spring PF1 simulations separately because of the smaller number of replicates, and compare the results from spring PF1 to the same-plot results from PF0 and summer PF1.

Prior to the first rainfall simulation in PF0, five soil samples from two depths (0–5 cm and 5–10 cm) were obtained from each of the seven sites to determine soil bulk density (Blake and Hartge, 1986) and soil particle size distribution (Gee and Bauder, 1986). At each plot prior to every rainfall simulation, soil water repellency, understory canopy cover, ground cover, and soil moisture at a depth of 0–5 cm were measured. The soil water repellency was measured using the Water Drop Penetration Time (WDPT) test (DeBano, 1981) using eight drops on the mineral surface just outside of each plot frame. If any of the drops infiltrated within 5 s, the drop was repeated at a depth of 1 cm. This process was repeated at 1 cm depth increments until the WDPT time was greater than 5 s or a depth of 5 cm had been reached. For water drops that remained on the surface for more than 5 s, the time until infiltration was used to classify the soil water repellency—slight (5–60 s), moderate (60–180 s), or severe (180 s or more). The percent of the drops that remained on the soil for more than 5 s at depths of 0 to 3 cm was calculated for each plot and termed “water repellency occurrence.”

Understory canopy cover and ground cover were estimated visually to the nearest percent within each 0.5-m² rainfall plot using a scaled quadrat (Dethier et al., 1993). The canopy cover of each understory species was estimated (Elzinga et al., 1998) and added for a total canopy cover which sometimes exceeded 100% because of overlapping foliage layers. Similarly, coverage of each category of ground cover (moss, lichen, litter, tree roots, and surface rock < 5 mm) was estimated and then added to obtain the total plot ground cover. The proportion of bare soil was the difference between 100% and the sum of ground cover and basal plant cover. The canopy and

ground cover measurements were forced to zero for the bare plots, and these were not included in the statistical analysis.

2.3 Rainfall simulation

Rainfall simulations were used to measure *in situ* infiltration rates, and provide a mechanism for replicating the same rain storm over many plots (Peterson and Bubenzer, 1986). Rainfall was applied to each plot at a rate of 100 mm h⁻¹ for 60 min using a modified Purdue-type rainfall simulator located 3 m above the center of the plot (Bertrand and Parr, 1961). The vee-jet nozzle provides energy of 275 Kj ha-mm⁻¹ at 3 m height with an average drop diameter of 3 mm at a terminal velocity of 8.8 m sec⁻¹ (Meyer and Harmon, 1979). Prior to each simulation, the rainfall was collected in a calibration pan covering the plot and measured with a graduated cylinder. The flow rate to the nozzles was adjusted so that the same per-unit-surface area rainfall rate was applied by repeating the calibration process if the slope-adjusted rainfall rate differed from the target rate by more than 5%. The time from the start of rainfall until the start of runoff was recorded. Timed runoff samples were collected for 45–60 s of each minute during the first 30 min of the simulation and for 75–90 s of every 2 min for the last 30 min of the simulation. If necessary, sample times were adjusted so that samples would fit in a 1-L bottle. Any sediment remaining in the sample tray was collected after the simulation was complete.

Sediment-laden water samples were weighed in the lab, dried, and re-weighed to obtain the sample runoff volume (mm) and the sediment concentration (g L⁻¹). The weight of any residual sediment in the tray was also dried and included in the total sediment yield (g m⁻²) for each rainfall simulation.

After each simulation, the wetting front into the soil profile was measured. A trench was excavated adjacent to each plot to expose a 20-cm deep by 50-cm wide cut face. The presence of wet or dry soil was recorded for each 2-cm square (25 squares across and 10 squares deep) on the exposed face. The total wetted area was the percentage of 2-cm squares (250 squares total) that were designated as wet.

2.4 Calculations and statistical analysis

For each simulation, the total rainfall applied was calculated from the calibration sample volume and the duration of the simulation. The total runoff (mm) for each simulation was calculated from the runoff rates (mm h^{-1}) and the sample duration, and extrapolated over the time between samples. Infiltration rates (mm h^{-1}) were the difference between rainfall and runoff per unit time. The total sediment yield (g m^{-2}) was similarly extrapolated from the timed samples and the duration of the simulation, and included any sediment from the tray.

The results were statistically analyzed using an unbalanced split plot design in several different linear mixed-effects models (SAS Institute, 2012). The whole plot treatment (by site) was either unburned or burned. The split plot treatment (by plot) for the unburned sites was control or bare. Repeated measures analyses were conducted for soil moisture, runoff, and total infiltration using linear mixed-effects models (Littell et al., 2006), while canopy cover, ground cover, occurrence of soil water repellency, and sediment yield were analyzed using generalized linear models (Littell et al., 2006). In each case, treatment and number of years after fire were fixed factors, the spacing between measurements was the number of months after the fire, and plot and site were random variables. The significance of multiple comparisons among treatments was tested using the differences among least-squares means with a Tukey-Kramer adjustment (Ott and Longnecker, 2001). The canopy and ground cover data were transformed using the square-root function to increase the normality of the residual errors (Ott and Longnecker, 2001), and the transformed data were modeled using the Poisson distribution. The ground cover and canopy cover were not independent of the bare treatment, so univariate linear regressions were used to evaluate the effect of ground cover and canopy cover on runoff and sediment yields and the cover responses for the bare plots were not directly compared to the control or burned plots. The occurrence of water repellency was modeled as a binomial distribution using the ratio of the number of water drops that indicated water repellency divided by the total number of water drops tested. The sediment yield was modeled using the lognormal distribution. The soil moisture was also tested as a covariate for total infiltration and sediment yield and retained in the statistical

model if it was significant. The particle size distributions of burned and the unburned surface soil were compared using T tests on the $D_{15.9}$, D_{50} , and $D_{84.1}$ values of the composite surface soil samples taken the first year (2000) of the study. A significance level of 0.05 was used for all statistical tests.

3 Results

3.1 Site and plot characteristics

3.1.1 Fire effects on soil

There was little or no difference in soil bulk density by treatment (average $BD=0.46 \text{ g cm}^{-3}$ for burned and 0.44 g cm^{-3} for unburned) or by depth (average $BD = 0.45 \text{ g cm}^{-3}$ for both 0–5 cm and 5–10 cm depths). However, the particle size distribution in the burned soil was significantly finer than the size distribution in the unburned soil, with the burned soils having smaller diameter particles represented by the $D_{15.9}$, D_{50} , and $D_{84.1}$ fractions (Fig. 3).

3.1.2 Soil moisture

The annual precipitation in the four simulation years (PF0–PF2 and PF5) was less than the 25-yr mean (636 mm), with the lowest annual precipitation of the study occurring in PF0 (82% of the 25-yr mean). July and August of PF0 were much drier than normal, with precipitation just 34% of the 25-yr mean for the same 2-mo period (78 mm). This small amount of rainfall resulted in low soil moisture values at the end of summer when the initial rain simulations were done. In PF0, the control plots had 18% soil moisture, which was not significantly different from the bare or the burned plots (Table 2).

Precipitation in July and August of PF1 and PF2 was greater than normal, with precipitation being 147% and 127% respectively of the 25-yr mean for the same period. In PF1 and PF2, the average soil moisture on the unburned control plots (33% and 44%, respectively) and the bare plots (36% and 44%, respectively) was greater than in PF0, but the soil moisture on the burned plots remained consistently low (15 and 17%, respectively) and not significantly different from PF0 (Table 2).

The period from October 2004 to April 2005 was drier than the 25-yr mean but May 2005 was wetter than average and the mean precipitation for June 2005 was nearly double the 25-yr mean. This relatively wet period was followed by just 2.5 mm of precipitation in July—significantly less than the 25-yr mean value of 39 mm (Table 2). The PF5 rain simulations were done at the end of July 2005 and soil moistures on the control and bare plots (24% and 15%, respectively) were low and comparable to those measured immediately after the fire in PF0 (Table 2). Mean soil moisture on the burned plots was only 3%, which was the lowest value measured during the study, but not significantly different from mean values on the unburned plots in PF0 or the bare plots in PF5 (Table 2).

3.1.3 Understory Canopy and Ground Cover

There was no difference in understory canopy cover in the control plots between PF0 and PF1 (mean of 27%), but the canopy cover increased to 42% in PF2 and increased again to 59% in PF5. The burned plots had negligible canopy cover following the fire in PF0, but vegetation increased on these plots throughout the study resulting in canopy cover values of 7% in PF1, 33% in PF2, and 45% in PF5 (Table 2). In PF2, the influx of fireweed (*Chamerion angustifolium* L. Holub.) on the burned plots accounted for much of the increase in mean canopy cover. By PF5, the fireweed had subsided, but increases in Scouler's willow (*Salix scouleriana* Barratt ex Hook.) and thin leaf huckleberry (*Vaccinium membranaceum* Dougl. ex Torr.) increased canopy cover. These changes in vegetation resulted in no significant differences in mean canopy cover between the control and burned plots in either PF2 or PF5 (Table 2).

The ground cover on the control plots remained consistently high for the five years of the study with an overall mean of 90% (Table 2). The litter and understory vegetation was removed from the bare plots, and the water held by the dried litter, duff, and fine roots removed was equivalent to 17 mm. The ground cover on the burned plots was significantly less than the controls for the first 3 years of the study—10, 6, and 17% for PF0, PF1, and PF2, respectively.

Although the PF5 mean ground cover value on the burned plots (42%) was less than half of the value for the control plots, the wide variation in measured values resulted in a lack of statistical difference between the burned and control plots (Table 2).

3.1.4 Water repellency

In PF0, the soil was relatively dry (17-18%) following the period of low rainfall, and the occurrence of moderate to severe soil water repellency at depths to 3 cm was high (81% overall average) and showed no significant difference among treatments (Table 2). However, the soil water repellency was concentrated at the mineral soil surface in the unburned (control and bare) plots, and was concentrated 1 to 2 cm below the surface on the burned plots (Fig. 4).

In PF1, soil moisture had increased in the unburned plots (33-36%) and the mean soil water repellency occurrence values were significantly lower for the control (39%) and bare (38%) plots as compared to the burned plots (79%) (Table 2). The occurrence of soil water repellency in the control and bare plots remained concentrated on the soil surface, but the “severe” water repellency measurements that predominated in PF0 had nearly disappeared and most of the soil water repellency measurements were “slight” and “moderate” (Fig. 4). In the burned plots, soil water repellency occurrence was similar to PF0 (Table 2), but it was concentrated at 0–1 cm depth and the proportion of “severe” water repellency measurements decreased with a concomitant increase in “slight” water repellency measurements (Fig. 4).

In PF2, the soil moisture in the unburned plots remained high (44%). The mean soil water repellency occurrence in the control plots was 51% and the bare and burned plots did not differ statistically from this value (Table 2). However, the 48% mean soil water repellency occurrence in the burned plots was significantly less than in PF1, and the water repellency appeared evenly dispersed from 0–3 cm depth (Fig. 4). By PF5, the control and bare plots had low soil moisture and high occurrences of soil water repellency at the surface of the mineral soil with no

significant differences between years PF0 and PF5 in either variable (Table 2; Fig. 4). In contrast, despite the very low soil moisture, in PF5 the burned plots had only 45% occurrence of soil water repellency which was predominately “slight” and concentrated at the soil surface (Table 2; Fig. 4).

When substituted for measurement periods, soil moisture was a significant covariate for the occurrence of water repellency, and in this analysis, the treatment had no significant effect. This suggests that high soil moisture content reduced the occurrence of both inherent and fire-altered soil water repellency.

3.2 Rainfall simulation

3.2.1 Infiltration

In PF0 the mean start of runoff on the control plots was 1.4 min with the mean infiltration rate decreasing sharply for the next 6 min, and then decreasing very gradually throughout the remainder of the simulation (Fig. 5). The bare and the burned plots followed the same pattern, but the mean infiltration rates decreased more rapidly and leveled off at lower values (Fig. 5).

The mean total infiltration was 44 mm in the control plots as compared to the significantly smaller mean total infiltration in the burned plots of 31 mm, and even smaller 19 mm on the bare plots. Although the magnitudes of the total infiltration varied and the differences among the treatments were not always significant, the mean infiltration values were greatest in the control plots, followed by the burned plots, and least in the bare plots through PF2 (Table 2). During the same time period the mean wetted area profile values, which are an indication of the total infiltration, were fairly similar among the three treatments but differed by year with values ranging from 24–35% in PF0, 86–91% in PF1, and 72–76% in PF2 (Fig. 6).

In PF5, there was no difference between the mean total infiltration on the control and bare plots (47 and 41 mm, respectively), and these values were not significantly different from the PF0–PF2 results on the controls or the PF1–PF2 infiltration values on the bare plots (Table 2). However, the mean total infiltration on the burned plots increased to 84 mm, and this was more

than double the values measured in the first 3 years of the study and the largest total infiltration measured in the study (Table 2). The mean wetted area of mineral soil for the burned plots in PF5 (96%) was also the largest value measured in the study (Fig. 6).

3.2.2 Sediment

Sediment concentrations in the runoff generally peaked early in the simulation and then decreased (Fig. 7). The magnitude of the peak concentration, the rate of decrease in sediment concentration, and the amount of runoff determined the total sediment yield from the plots. In PF0 the mean peak sediment concentration in the control plots was 6.7 g L^{-1} (Fig. 7). In the control plots the sediment concentration quickly receded to a value near zero with the median value being 0.6 g L^{-1} of runoff (Fig. 7). The sediment concentration results in the control plots were very similar among the four years (Fig. 7).

The sediment concentrations (g L^{-1}) from the bare plots also peaked rapidly in the first 15 min of the simulation, but the magnitudes were much greater than in the control plots. The peak concentrations from the bare plots in PF0 and PF5 were about five times greater than the controls (36 and 38 g L^{-1} , respectively), while the peaks in PF1 and PF2 were about two to three times greater than the controls (Fig. 7). In PF0-PF2 the mean sediment concentration in the bare plots quickly receded to about 10 g L^{-1} for the last 50 min of the simulation. The concentration from the bare plots in PF5 also receded quickly, but the final concentration was greater than in PF0-PF2 (Fig. 7).

In PF0-PF1 the peak sediment concentration in the burned was about five times greater than the controls (38 and 35 g L^{-1} , respectively) (Fig. 7). The rate of decrease in sediment concentration from the peak was also less and the mean sediment concentration in these two years never fell below 15 g L^{-1} (Fig. 7). The peak and final sediment concentrations from the burned plots were much lower in PF2 than in the same plots in PF0-PF1, but the values were still greater than the control plots. In PF5 the mean sediment concentration response in the burned plots closely resembled the response in the control plots (Fig. 7).

Differences in sediment concentration and runoff were reflected in the sediment yields from the plots. In PF0–PF5, the mean runoff from the control plots was similar and mean sediment yields were very small (7 to 54 g m⁻²; Table 2). In PF0 and PF1, the mean sediment yields on the bare plots (849 and 677 g m⁻², respectively) and burned plots (1157 and 1099 g m⁻², respectively) were not significantly different from each other and both were much greater than on the control plots (Table 2). In PF2, the burned plots had a lower mean sediment yield (391 g m⁻²) than the bare plots (624 g m⁻²), but both the burned and bare plots still produced nearly two orders of magnitude more sediment than the control plots (Table 2). There was no significant change in the mean sediment yield from the bare plots in PF5 (1277 g m⁻²) as compared to earlier simulations, and this value was still about 20 times greater than the sediment yield from the controls (Table 2). In PF5 the sediment yield in the burned plots was only 15 g m⁻², and this was much lower than the values in PF0-2 but not significantly different from the mean value of 54 g m⁻² produced in the control plots (Table 2).

3.3 Spring PF1

Precipitation in April and May of PF1 was less than normal, but when combined with melting snow it was enough to increase the soil moisture in the control plots to 74% (Table 3). The soil moisture of 21% in the burned plots was significantly lower than in the control plots but this value was still greater than the moisture in the burned plots in any of the summer simulations. The soil moisture value of 52% in the bare plots was not significantly different from the other two treatments. Mean occurrences of soil water repellency decreased significantly from their high values in PF0 to 4%, 21%, and 36% for the control, bare, and burned plots, respectively (Table 3). The only seasonal differences in infiltration, runoff, or sediment yields were on the control plots where the mean infiltration value was greater in spring PF1 than the value on the same subset of plots in the summer PF1 (Table 3).

4 Discussion

4.1 Fire effects on infiltration

This study adds to the growing evidence that the effects of wildfire on water infiltration into soil are complex and involve several soil and hydrologic characteristics that vary within the spatial extent of the fire and across a temporal scale that extends many years after the fire. The measurements over the five years of this study allowed us to quantify the longer-term variability of post-wildfire infiltration in the ash cap soils that are characteristic of the forests of northern Montana and Idaho. In addition, both the seasonal and annual temporal variation in infiltration were associated with changes in soil water repellency.

The inherent surface soil water repellency, a common characteristic of ash cap soils (Kawamoto et al., 2007), was not detected in areas burned at high severity after the wildfire. A new, fire-altered water repellent soil layer was observed 1–2 cm below the surface (Fig. 4, Burned, PF0). Laboratory studies have shown that soil water repellency can be destroyed at high temperatures (DeBano, 1981; Robichaud and Hungerford, 2000), and it is possible that the surface water repellency was destroyed by heat and a new water repellent layer was created at the 1-2 cm depth. Translocation of soil water repellency from the surface to below the surface has also been demonstrated in areas burned by wildfire (e.g., Doerr et al., 2006a), and this is a more likely explanation for our results.

Both inherent and fire-altered soil water repellency were sensitive to soil moisture (Fig. 8). The occurrence of water repellency in the controls was similar under dry soil conditions (Table 2) whereas in Spring PF1 when the mean soil moisture was 74%, no inherent soil water repellency was detected (Fig. 8; Table 3). This result is consistent with findings of several previous studies that relate soil moisture to soil wettability (e.g., Bodí et al., 2013; Czachor et al., 2010; MacDonald and Huffman, 2004; Vogelmann et al., 2013; Zehe et al., 2007).

In contrast to the inherent soil water repellency, the fire-altered water repellency was essentially gone in PF5 (Fig. 4). Some water repellency was observed at the surface of the burned soil in PF5, and we attribute this to the very low soil moisture (Doerr et al., 2006b). Recovery of inherent water repellency after a wildfire is not well established. Jordán et al. (2009) reported that soil water repellency comparable to the unburned condition was practically re-established

just 18 months after an intense experimental fire in a Mediterranean heathland. However, Doerr et al. (2006a) found that inherent surface water repellency destroyed by a high severity fire did not show signs of recovering after two years. In the Mediterranean ecosystem of Israel, soil in the burned areas remained wettable two decades after forest fires had destroyed the inherent soil water repellency (Tessler et al., 2013). The re-establishment of inherent soil water repellency after wildfires is highly dependent on restoration of organic matter within the soil, which gradually returns as decayed organic matter builds up and micro-organisms and fine roots are re-established in the upper horizon of the soil—a process that may take decades (Tessler et al., 2013).

Several factors can affect the infiltration rate from rainfall simulations, including: the amount of interception and storage by understory canopy and ground cover; flow through macropores such as root holes; soil sealing by rain drop impact or mobilization of fine soil, ash, or organic particles into surface pores; or presence of a water repellent layer. Infiltration values on the control plots remained constant and high (44–48 mm) throughout this study despite variations in soil moisture and water repellency, likely due to the high porosity of the ash-cap soil (Shoji et al., 1993). The runoff ratios in our control plots are consistent with other studies in unburned pine forests where high rainfall intensities were simulated (Table 1).

Despite the relatively uniform runoff ratios through our study, the wetted areas from the post-simulation excavations on the control plots showed very little rainfall had infiltrated into the dry, water repellent soil in PF0 and PF5 (Fig. 6). Given that forest floor material in pine forests absorbs and holds large amounts of rainfall (Neris et al., 2013), much of the simulated rainfall attributed to infiltration on the control plots likely was stored in the litter and duff that covered the plots (Leighton-Boyce et al., 2007). The water stored in the litter, duff, and fine roots removed from the bare plots accounted for about 68% of the difference in infiltration between the control and the bare plots in PF0. We attribute the remaining 32% to lower infiltration capacity resulting from soil sealing and redistribution of fine soil particles in the bare plots. The lower

infiltration volumes in the bare plots than the controls in PF1–PF5 can be accounted for by mostly the loss of litter storage and some soil sealing.

The difference in infiltration between the burned and control plots in PF0–2 (7–13 mm) can be accounted for by the loss of litter storage in the burned plots. The burned plots also had some additional moisture storage capacity in the soil above the water repellent layer at 1 cm. We suspect that soil sealing was also a factor given the lack of soil structure and finer soil particle size distribution in the burned soil (Fig. 3).

The ground cover on the burned plots was less than half the value on the control plots, so litter storage does not explain the higher infiltration rate in the burned plots in PF5. Although we did not evaluate all of the soil in the plots, the cut faces we did expose showed no signs of macropore flow. We did not measure soil sealing directly but because of the much greater amount of litter in the control plots than in the burned plots in PF5, soil sealing either was not a factor. We therefore ascribe the greater infiltration rates in the burned plots to the very low occurrence and severity of the fire-altered soil water repellency as compared to the prevalent and severe inherent water repellency in the control and bare plots (Table 2).

These findings suggest that modeling infiltration rates in water repellent soils should account for: 1) the dynamic soil water repellency as a function of soil moisture; 2) the changes in severity of fire-altered soil water repellency in the first few years after wildfire; and 3) when present in unburned conditions, the longer term recovery of inherent water repellency in burned soils.

4.2 Fire effects on interrill erosion

The combination of treatments in our study provides some mechanistic understanding of rain splash erosion, specifically with regards to the protection of the soil surface provided by understory canopy and ground cover (Table 2). As a result, the control plots had consistently low sediment concentrations and sediment yields similar to those measured in other studies (Table 1). The main factor affecting of sediment production within the narrow range observed in the control plots was the amount of runoff produced under the various soil moisture and soil water

repellency conditions. In the case of the control plots, the soil water repellency was both a direct and indirect control on sediment production, as the water repellency allowed greater amount of rain splash erosion (Ahn et al., 2013) and it reduced the infiltration rates, leading to more overland flow for additional detachment and transport of sediment.

In contrast, the mineral soil in the bare plots was exposed to the full impact of the simulated rainfall. The small variation in sediment yields in the bare plots was related to the amount of disturbance required to remove the litter and vegetation, which was highest in PF0 and PF5. These periods also had the highest occurrence of soil water repellency in the bare plots because of the low soil moisture conditions, but the sediment yields from the bare plots during the other simulations did not correlate to soil water repellency (Table 2).

The 1757 g m^{-2} measured in the burned plots in PF0 was higher than the values from other rainfall simulation studies in burned pine forests ($17\text{--}1040 \text{ g m}^{-2}$; Table 1). We attribute the greater sediment yield to the higher rainfall intensity in the current study than the previous simulations. The sediment yields in our burned plots decreased as the ground cover increased (Table 2), and the ground cover was the best predictor of sediment yields in the burned plots (Benavides-Solorio and MacDonald, 2001; Johansen et al., 2001; Robichaud et al., 2013a). Consequently, post-fire prediction models should account for: 1) the expected rainfall intensity at the location of interest; 2) the short term (minutes) changes in interrill erosion rates within a rain event as measured in our simulations (Fig. 5); and 3) the long term (1-5 years) post-fire recovery of protective ground cover, which may vary with climate and soil conditions (Robichaud et al., 2013b).

5 Conclusions

This post-wildfire infiltration and erosion study took place in a steep montane conifer forest with inherently water repellent ash cap soils. Small-plot rainfall simulations (100 mm h^{-1} for 60 min) were applied to compare infiltration and sediment yields from interrill erosion among unburned plots that were untreated (control) or had surface vegetation, litter, and duff removed prior to each simulation (bare), and plots burned at high severity (burned). Rainfall simulations

and associated measurements were done immediately after the wildfire in 2000 (PF0). A sample of the simulations were repeated under high soil moisture conditions in spring 2001. Simulations were repeated on all available plots in the summers of 2001 (PF1), 2002 (PF2), and 2005 (PF5) making this one of very few post-fire studies to extend for 5 years.

The unburned soil was inherently water repellent at its surface and the burned soil had no surface water repellency but had a layer of water repellent soil at 1–2 cm deep. Both the inherent and fire-altered soil water repellency were stronger and more extensive under low soil moisture conditions. The occurrence and severity of the fire-altered soil water repellency decreased over time and by PF5 the fire-altered soil water repellency was significantly reduced in severity and occurrence. In contrast, there was no change over time in the inherent soil water repellency in the control and bare plots—it was equally pervasive in PF0 and PF5 (93-99%).

Despite the prevalent and severe water repellency in the control plots, the infiltration in the controls was 44–48 mm during the summer simulations. The control plots had extensive ground cover of litter and duff as well as understory canopy cover from low shrubs, forbs, and grasses which protected the mineral soil from rain splash erosion. The runoff collected from the control plots had consistently low sediment concentrations which resulted in low sediment yields. Infiltration on the bare plots, as determined by the runoff mass balance and by observing the wetness of the post-simulation excavated soil, was always less than the controls, but the differences were not always significant. Without any protective ground or canopy cover, the sediment concentrations in the runoff from the bare plots were always much greater than the controls, and the higher sediment concentrations and runoff amounts led to significantly greater sediment yields.

The infiltration and sediment responses on the burned plots changed over time reflecting some post-fire recovery over the five year study. In PF0 and PF1, the burned plots had high occurrence of soil water repellency, low infiltration, and little ground or canopy cover which resulted in very high sediment concentrations in the runoff and sediment yields. In PF2, the soil water repellency decreased, but this did not affect the infiltration rates. The increase in ground

and canopy cover in PF2 led to a mean sediment yield that was about a third of the amount measured in PF1. In PF5 the burned plots had significantly less water repellency and significantly greater ground and canopy cover and infiltration, and the result was very low sediment concentrations and a mean sediment yield (15 g m^{-2}) that was comparable to the yields from the controls.

Our results indicate that both ground cover and soil water repellency affect the infiltration capacity in ash cap soils. Comparisons between the bare and control plots showed that removal of the surface cover, with its requisite water storage capacity, explained most of the decrease in infiltration in the bare plots, and we attribute the remainder to sealing of the exposed soil. In the burned plots, the fire-altered water repellency changed during the five years of post-fire recovery, and the infiltration volumes decreased as the repellency diminished.

The interrill erosion was consistently high in the bare plots, and reflects their relatively consistent surface conditions. In contrast, the erosion in the burned plots decreased each year and was comparable to the interrill erosion in the controls in the fifth post-fire year. The higher initial rates can be attributed to lack of cover and subsequently high rain splash erosion rates, relatively low infiltration, and high availability of mobile soil particles. The interrill erosion in the burned plots diminished over time as the fire altered water repellency decreased, allowing greater infiltration, and as the surface cover recovered.

Acknowledgements

Funding for this project was provided in part by the U.S. Department of Agriculture (USDA), Forest Service and Department of Interior Joint Fire Science Program and the Rocky Mountain Research Station (USDA, Forest Service) and Northwest Watershed Research Center (USDA, Agricultural Research Service). The dedicated field crews from the Rocky Mountain Research Station and Northwest Watershed Research Center were essential to the success of this research. We thank the Bitterroot National Forest for their administrative and logistical support.

References

- Abrahams, A.D., Parsons, A.J., Wainwright, J., 1995. Effects of vegetation change on interrill runoff and erosion, Walnut Gulch, southern Arizona. *Geomorphology* 13, 37–48.
- Ahn, S., Doerr, S.H., Douglas, P., Bryant, R., Hamlett, C.A.E., McHale, G., Newton, M.I., Shirtcliffe, N.J., 2013. Effects of hydrophobicity on splash erosion of model soil particles by a single water drop impact, *Earth Surf. Process. Landf.* 38(11), 1225–1233.
- Assouline, S., 2004. Rainfall-induced soil surface sealing: A critical review of observations, conceptual models, and solutions. *Vadose Zone J.* 3, 570–591.
- Benavides-Solorio, J., MacDonald, L.H., 2001. Post-fire runoff and erosion from simulated rainfall on small plots, Colorado Front Range. *Hydrol. Processes* 15, 2931–2952.
- Bento-Gonçalves, A., Vieira, A.I., Úbeda, X., Martín, D., 2012. Fire and soils: Key concepts and recent advances. *Geoderma* 191, 3–13.
- Berndtsson, R., Larson, M., 1987. Spatial variability of infiltration in a semiarid environment. *J. Hydrology* 90, 117–133.
- Bertrand, A.R., Parr, J.F., 1961. Design and operation of the Purdue sprinkling infiltrometer. Research Bulletin No. 723. U.S. Department of Agriculture, Purdue University Agricultural Experiment Station, Lafayette, Indiana, USA.
- Beven, K.F., Germann, P., 2013. Macropores and water flow in soils revisited. *Water Resources Res.* 49(6), 3071–3092.
- Blake, G.R., Hartge, K.H. 1986. Bulk Density. In: Klute, A. (ed.), *Methods of Soil Analysis: Part 1*, American Society of Agronomy, Madison, Wisconsin, USA, pp. 363–382.
- Bodí, M.B., Doerr, S.H., Cerdà, A., Mataix-Solera, J., 2012. Hydrological effects of a layer of vegetation ash on underlying wettable and water repellent soil. *Geoderma* 191, 14–23.

599 Bodí, M.B., Muñoz-Santa, I., Armero, C., Doerr, S.H., Mataix-Solera, J., Cerdà, A., 2013. Spatial
600 and temporal variations of water repellency and probability of its occurrence in calcareous
601 Mediterranean rangeland soils affected by fires. *Catena* 108, 14–25.

602 Brock, J.H., DeBano, L.F., 1982. Runoff and sedimentation potentials influenced by litter and
603 slope on a chaparral community in central Arizona. In: Conrad, C.E., Oechel, W.C.
604 (Technical Coordinators), *Proceedings of the symposium on Dynamics and Management of*
605 *Mediterranean-Type Ecosystems*, General Technical Report PSW-58. U.S. Department of
606 Agriculture, Forest Service, Pacific Southwest Forest and Range Experiment Station,
607 Berkley, California, USA, pp. 372–377.

608 Bryan, R.B., 2000. Soil erodibility and processes of water erosion on hillslope. *Geomorphology*
609 32, 385–415.

610 Burch, G.J., Moore, I.D., Burns, J., 1989. Soil hydrophobic effects on infiltration and catchment
611 runoff. *Hydrol. Processes* 3, 211–222.

612 Castillo, V., Martínez-Mena, M., Albaladejo, J., 1997. Runoff and soil loss response to vegetation
613 removal in a semiarid environment, *Soil Science Soc. Amer. J.* 61, 1116–1121.

614 Cerdà, A., 1999. Parent material and vegetation affect soil erosion in eastern Spain. *Soil Science*
615 *Soc. Amer. J.* 63, 362–368.

616 Cerdà, A., Doerr, S.H., 2005. Influence of vegetation recovery on soil hydrology and erodibility
617 following fire: an 11-year investigation. *Int. J. Wildland Fire* 14, 423–437.

618 Cerdà, A., Doerr, S.H., 2008. The effect of ash and needle cover on surface runoff and erosion in
619 the immediate post-fire period. *Catena* 74, 256–263.

620 Cerdà, A., Robichaud, P.R., 2009. Fire effects on soil infiltration. In: Cerdà, A., Robichaud, P.R.
621 (Eds.), *Fire Effects on Soils and Restoration Strategies*. Science Publishers, Enfield, New
622 Hampshire, USA, pp.81–103.

623 Certini, G., 2005. Effects of fire on properties of forest soils: a review. *Oecologia* 143, 1–10.

624 Czachor, H., Doerr, S.H., Lichner, L., 2010. Water retention of repellent and subcritical repellent
625 soils: New insights from model and experimental investigations. *J. Hydrol.* 380, 104–111.

626 DeBano, L.F., 1981. Water repellent soils: a state-of-the-art, General Technical Report, PSW-46.
627 U.S. Department of Agriculture, Forest Service, Pacific Southwest Forest and Range
628 Experiment Station, Berkley, California, USA, 21pp.

629 DeBano, L.F., Neary, D.G., Ffolliott, P.F., 1998. *Fire's Effects on Ecosystems*. John Wiley &
630 Sons, New York, USA.

631 de Jonge, L.W., Jacobsen, O.H., Moldrup, P., 1999. Soil water repellency: effects of water
632 content, temperature, and particle size. *Soil Science Society of America Journal* 63, 437–442.

633 Dekker, L.W., Ritsema, C.J., 1994. How water moves in a water repellent sandy soil. I. Potential
634 and actual water repellency. *Water Resources Res.* 30, 2507–2517.

635 Dekker, L.W., Ritsema, C.J., 1995. Finger like wetting patterns in two water-repellent loam soils.
636 *J. Environ. Quality* 24, 324–333.

637 Dekker, L.W., Ritsema, C.J., 1996. Variation in water content and wetting patterns in Dutch
638 water repellent peaty clay and clayey peat soils. *Catena* 28, 89–105.

639 Dekker, L.W., Doerr, S.H., Oostindie, K., Ziogas, A.K., Ritsema, C.J., 2001. Water repellency
640 and critical water content in a dune sand. *Soil Science Soc. of Amer. J.* 65, 1667–1674.

641 Dethier, M.N., Graham, E.S., Cohen, S., Tear, L.M., 1993. Visual versus random-point percent
642 cover estimations: “objective” is not always better. *Marine Ecol. Progress Series* 96, 93–100.

643 Doerr, S.H., Shakesby, R.A., Walsh, R.P.D., 2000. Soil water repellency: its causes,
 644 characteristics and hydro-geomorphological significance. *Earth-Science Reviews* 15, 33–65.
 645 Doerr, S.H., Moody J., 2004. Hydrological effects of soil water repellency: on spatial and
 646 temporal uncertainties. *Hydrol. Processes* 18, 829–832.
 647 Doerr, S.H., Shakesby, R.A., Blake, W.H., Chafer, C.J., Humphreys, G.S., Wallbrink, P.J., 2006a.
 648 Effects of differing wildfire severities on soil wettability and implications for hydrological
 649 response. *J. Hydrology* 319, 295–311.
 650 Doerr, S.H., Shakesby, R.A., Dekker, L.W., Ritsema, C.J., 2006b. Occurrence, prediction and
 651 hydrological effects of water repellency amongst major soil and land-use types in humid
 652 temperate climate. *European J. Soil Science* 57, 741–754.
 653 Doerr, S.H., Shakesby, R.A., MacDonald, L.H. 2009a. Soil water repellency: A key factor in
 654 post-fire erosion. In: Cerdà, A., Robichaud, P.R. (Eds.), *Fire Effects on Soils and Restoration*
 655 *Strategies*. Science Publishers, Enfield, New Hampshire, USA, pp. 197–223.
 656 Doerr, S.H., Woods, S.W., Martin, D.A., Casimiro, M., 2009b. ‘Natural background’ soil water
 657 repellency in conifer forests of the north-western USA: Its prediction and relationship to
 658 wildfire occurrence. *J. Hydrol.* 371, 12–21.
 659 Ebel, B.A., Moody, J.A., Martin, D.A., 2012. Hydrologic conditions controlling runoff
 660 generation immediately after wildfire. *Water Resources Res.* 48, WO3529, 1–13.
 661 Elzinga, C.L., Salzer, D.W., Willoghby, J.W., 1998. Measuring and monitoring plant populations.
 662 USDI-BLM Technical Reference 1730-1. U.S. Department of Interior, Bureau of Land
 663 Management, Denver, Colorado, USA, 492 pp.
 664 <<http://www.blm.gov/nstc/library/pdf/MeasAndMon.pdf>> (date accessed: June 2015)

665 Faulkner, H., 1990. Vegetation cover density variations and infiltration patterns on piped alkali
 666 sodic soils: implications for the modeling of overland flow in semi-arid areas. In: Thornes,
 667 J.B. (ed.), *Vegetation and Erosion: Process and Environments*. John Wiley and Sons,
 668 Chichester, UK, pp. 317–346.

669 Ferreira, A.J.D., Coelho, C.O.A., Boulet, A.K., Lopes, F.P. 2005. Temporal patterns of solute loss
 670 following wildfires in Central Portugal. *Int. J. Wildland Fire* 14, 401–412.

671 Feng, G.L., Letey, J., Wu, L., 2001. Water ponding depths affect temporal infiltration rates in a
 672 water repellent sand. *Soil Science Soc. Amer.* 65, 315–320.

673 Fox, D.M., Darboux, F., Carrega, P., 2007. Effects of fire-induced water repellency on soil
 674 aggregate stability, splash erosion, and saturated hydraulic conductivity for different size
 675 fractions. *Hydrol. Processes* 21, 2377–2384.

676 Gee, G.W., Bauder, J.W., 1986. Particle-size analysis. In: Klute, A. (ed.), *Methods of Soil*
 677 *Analysis: Part 1*, American Society of Agronomy, Madison, Wisconsin, USA, pp. 383–411.

678 Huang, C., Gascuel-Oudoux, C., Cros-Cayot, S., 2001. Hillslope topographic and hydrologic
 679 effects on overland flow and erosion. *Catena* 46, 177–188.

680 Huffman, E.L., MacDonald, L.H., Stednick, J.D., 2001. Strength and persistence of fire-induced
 681 soil hydrophobicity under ponderosa and lodgepole pine, Colorado Front Range. *Hydrol.*
 682 *Processes* 15, 2877–2892.

683 Imeson, A.C., Verstraten, J.M., Van Mulligen, E.J., Sevink, J., 1992. The effects of fire and water
 684 repellency on infiltration and runoff under Mediterranean type forests. *Catena* 19, 345–361.

685 Inbar, A., Lado, M., Sternberg, M., Tenau, H., Ben-Hur, M., 2014. Forest fire effects on soil
 686 chemical and physicochemical properties, infiltration, runoff, and erosion in a semiarid
 687 Mediterranean region. *Geoderma* 221–222, 131–138.

688 Jiménez, C.C., Tejedor, M., Morillas, G., Neris, J., 2006. Infiltration rates in andisols: effect of
 689 changes in vegetation cover (Tenerife, Spain). *J. Soil and Water Conservation* 61, 153–158.
 690 Johansen, M.P., Hakonson, T.E., Breshears, D.D., 2001. Post-fire runoff and erosion from rainfall
 691 simulation: contrasting forests with shrublands and grasslands. *Hydrol. Processes* 15, 2953–
 692 2965.
 693 Jordán, A., Zavala, L.M., Nava, A.L., Alanís, N., 2009. Occurrence and hydrological effects of
 694 water repellency in different soil and land use types in Mexican volcanic highlands. *Catena*
 695 79, 60–71.
 696 Jordán, A., Zavala, L.M., Mataix-Solera, J., Doerr, S.H. 2013. Soil water repellency: Origin,
 697 assessment and geomorphological consequences. *Catena* 108, 1-5.
 698 Kawamoto, K., Moldrup, P., Komatsu, T., de Jonge, L.W., Oda, M., 2007. Water repellency of
 699 aggregate size fractions of volcanic ash soil. *Soil Science Soc. Amer. J.* 71(6), 1658–1666.
 700 Larsen, I.J., MacDonald, L.H., Brown, E., Rough, D., Welsh, M.J., Pietraszek, J.H., Libohova,
 701 Z., Benavides-Solorio, J.D., Schaffrath, K., 2009. Causes of post-fire runoff and erosion:
 702 water repellency, surface cover, or soil sealing? *Soil Science Soc. Amer. J.* 73 (4), 1393–
 703 1407.
 704 Leighton-Boyce, G., Doerr, S.H., Shakesby, R.A., Walsh, R.P.D., 2007. Quantifying the impact
 705 of soil water repellency on overland flow generation and erosion: a new approach using
 706 rainfall simulation and wetting agent on *in situ* soil. *Hydrol. Processes* 21, 2337–2345.
 707 Letey, J., 2001. Causes and consequences of fire-induced soil water repellency. *Hydrol.*
 708 *Processes* 15, 2867–2875.
 709 Littell, R.C., Milliken, G.A., Stroup, W.W., Wolfinger, R.D., Schabenberger, O., 2006. SAS® for
 710 Mixed Models, Second Edition. SAS Institute Inc., Cary, North Carolina, USA.

711 Liu, H., Lei, T.W., Zhao, J., Yuan, C.P., Fan, Y.T., Qu, L.Q., 2011. Effects of rainfall intensity and
 712 antecedent soil water content on soil infiltrability under rainfall conditions using the run off-
 713 on-out method. *J. Hydrology* 396, 24–32.

714 Lowdermilk, W.C., 1930. Influence of forest litter on run-off, percolation, and erosion. *J.*
 715 *Forestry* 28, 474–491.

716 Lozano, E., Jiménez-Pinilla, P., Mataix-Solera, J., Arcenegui, V., Bárcenas, G.M., González-
 717 Pérez, J.A., García-Orenes, F., Torres, M.P., Mataix-Beneyto, J. 2013. Biological and
 718 chemical factors controlling the patchy distribution of soil water repellency among plant
 719 species in a Mediterranean semiarid forest. *Geoderma* 207–208, 212–220.

720 MacDonald, L.H., Huffman, E.L., 2004. Post-fire soil water repellency: persistence and soil
 721 moisture thresholds. *Soil Science Soc. Amer. J.* 68, 1729–1734.

722 Martínez-Zavala, L., Jordán-López, A., 2009. Influence of different plant species on water
 723 repellency in Mediterranean heathland soils. *Catena* 76, 215–223.

724 Mataix-Solera, J., Arcenegui, V., Guerrero, C., Mayoral, A.M., Morales, J., González, J., García-
 725 Orenes, F., Gómez, I., 2007. Water repellency under different plant species in a calcareous
 726 forest soil in a semiarid Mediterranean environment. *Hydrol. Processes* 21, 2300–2309.

727 Mataix-Solera, J., Cerdà, A., Arcenegui, V., Jordán, A., Zavala, L.M., 2011. Fire effects on soil
 728 aggregation: A review. *Earth-Science Reviews* 109, 44–60.

729 Mataix-Solera, J., Arcenegui, V., Tessler, N., Zornoza, R., Wittenberg, L., Martínez, C., Caselles,
 730 P., Pérez-Bejarano, A., Malkinson, D., Jordán, M.M., 2013. Soil properties as key factors
 731 controlling water repellency in fire-affected areas: evidences from burned sites in Spain and
 732 Israel. *Catena* 108, 6–13.

733 **McBride, K., 2000. Soil description of the Bitterroot National Forest. Unpublished report.**
734 **Available at US Department of Agriculture, Forest Service, Bitterroot National Forest,**
735 **Hamilton, Montana, USA.**

736 **Meeuwig, R.O., 1971. Infiltration and water repellency in granitic soils. Research Paper**
737 **INT-111. U.S. Department of Agriculture, Forest Service, Intermountain Research**
738 **Station, Ogden, Utah, USA.**

739 **Meyer, L.D., Harmon, W.C. 1979. Multiple-intensity rainfall simulator for erosion research**
740 **on row sideslopes. Trans. Amer. Soc. Agric. Eng. 22,100-103.**

741 **Moral García, F.J., Dekker, L.W., Oostindie, K., Ritsema, C.J., 2005. Water repellency**
742 **under natural conditions in sandy soils of southern Spain. Australian J. Soil Research**
743 **43, 291–296.**

744 **Moody, J.A., Shakesby, R.A., Robichaud, P.R., Cannon, S.H., Martin, D.A., 2013. Current**
745 **research issues related to post-wildfire runoff and erosion processes. Earth-Science Reviews**
746 **122, 10–37.**

747 **(NRCS), U.S. Department of Agriculture, Natural Resources Conservation Service, 2007.**
748 **Historical accumulated precipitation (daily) for Site 433 in the state of Montana.**
749 **<[http://www.wcc.nrcs.usda.gov/snotel/snotelday2.pl?](http://www.wcc.nrcs.usda.gov/snotel/snotelday2.pl?site=433&station=13c39s&state=mt&report=precip_accum_hist)**
750 **site=433&station=13c39s&state=mt&report=precip_accum_hist> (date accessed: June**
751 **2015).**

752 **Neris, J., Tejedor, M., Rodríguez, M., Fuentes, J., Jiménez, C., 2013. Effect of forest floor**
753 **characteristics on water repellency, infiltration, runoff and soil loss in Andisols of Tenerife**
754 **(Canary Islands, Spain). Catena 108, 50–57.**

755 Nyman, P., Sheridan, G., Lane, N.J., 2010. Synergistic effects of water repellency and macropore
 756 flow on the hydraulic conductivity of a burned forest soil, south-east Australia. *Hydrol.*
 757 *Processes* 24, 2871–2887.

758 Ott, R.L., Longnecker, M., 2001. *An Introduction to Statistical Methods and Data Analysis*, fifth
 759 edition. Duxbury, Pacific Grove, California, USA.

760 Parsons, A., Robichaud, P.R., Lewis, S.A., Napper, C., Clark, J.T., 2010. Field guide for mapping
 761 post-fire soil burn severity. General Technical Report, RMRS-GTR-243. **U.S. Department of**
 762 **Agriculture, Forest Service, Rocky Mountain Research Station, Fort Collins, Colorado,**
 763 **USA, 49 pp.**

764 Peterson, A.E., Bubenzer, G.D., 1986. Intake rate: sprinkler infiltrometer. In: Klute, A., (ed.),
 765 *Methods of Soil Analysis, Part I. Physical and Mineralogical Methods—Agronomy*
 766 *Monograph no.9 (2nd Edition)*. American Society of Agronomy—Soil Science Society of
 767 America, Madison, Wisconsin, USA. pp. 845–870.

768 Pierson, F.B., Robichaud, P.R., Spaeth, K.E., 2001. Spatial and temporal effects of wildfire on
 769 the hydrology of a steep rangeland watershed. *Hydrol. Processes* 15, 2905–2916.

770 Prosser, I.P., Williams, L., 1998. The effect of wildfire on runoff and erosion in native Eucalyptus
 771 forest. *Hydrol. Processes* 12, 251–265.

772 Regalado, C.M., Ritter, A., 2005. Characterizing water dependent soil repellency with minimal
 773 parameter requirement. *Soil Science Soc. Amer. J.* 69, 1955–1966.

774 Ritsema, C.J., Dekker, L.W., 1994. How water moves in a water repellent sandy soil. Part 2
 775 Dynamics of fingered flow. *Water Resources Res.* 30, 2519–2531.

776 Ritsema, C.J., Dekker, L.W., 2000. Preferential flow in water repellent sandy soils: principles
 777 and modeling implications. *J. Hydrology* 231–232, 308–319.

778 Robichaud, P.R. 1996. Spatially-varied erosion potential from harvested hillslopes after
779 prescribed fire in the Interior Northwest. PhD Diss. University of Idaho, Moscow ID, 219 pp.

780 Robichaud, P.R., 2000. Fire effects on infiltration rates after prescribed fire in Northern Rocky
781 Mountain forests, USA. *J. Hydrology* 231–232, 220–229.

782 Robichaud, P.R., Hungerford, R.D., 2000. Water repellency by laboratory burning of four
783 northern Rocky Mountain forest soils. *J. Hydrology* 231–232, 207–219.

784 Robichaud, P.R., Lewis, S.A., Ashmun, L.E., 2008. New procedure for sampling infiltration to
785 assess post-fire soil water repellency. **Research Note, RMRS-RN-33. U.S. Department of**
786 **Agriculture, Forest Service, Rocky Mountain Research Station, Fort Collins, Colorado,**
787 **USA.**

788 Robichaud, P.R., Jordan, P., Lewis, S.A., Ashmun, L.E., Covert, S.A., Brown, R.E., 2013a.
789 Evaluating the effectiveness of wood shred and agricultural straw mulches as a treatment to
790 reduce post-wildfire hillslope erosion in southern British Columbia, Canada. *Geomorphology*
791 197, 21–33.

792 Robichaud, P.R., Lewis, S.A., Wagenbrenner, J.W., Ashmun, L.E., Brown, R.E., 2013b. Post-fire
793 mulching for runoff and erosion mitigation Part I: effectiveness at reducing hillslope erosion
794 rates. *Catena* 105, 75–82.

795 Rodriguez-Alleres, M., Benito, E., deBlas, E., 2007. Extent and persistence of water repellency
796 in north-western Spanish soils. *Hydrol. Processes* 21, 2291–2299.

797 Rulli, C.M., Bozzi, S., Spada, M., Bocchiola, D., Rosso, R., 2006. Rainfall simulations on a fire
798 disturbed Mediterranean area. *J. Hydrology* 327, 323–338.

799 SAS Institute, 2012. SAS 9.4 for Windows. SAS Institute, Cary, North Carolina, USA.

800 Shakesby, R.A., Doerr, S.H., Walsh, R.P.D., 2000. The erosional impact of soil hydrophobicity:
801 current problems and future research directions. *J. Hydrology* 231–232, 178–191.

802 Shakesby, R.A., Doerr, S.H., 2006. Wildfire as a hydrological and geomorphological agent.
803 *Earth-Science Reviews* 74, 269–307.

804 Shoji, S., Nanzyo, M., Dahlgren, R.A., 1993. *Volcanic Ash Soils: genesis, properties, and*
805 *utilization*. Elsevier Publishing, Amsterdam.

806 Stoof, C.R., Vervoort, R.W., Iwema, J., van den Elsen, E., Ferreira, A.J.D., Ritsema, C.J., 2012.
807 Hydrological response of a small catchment burned by experimental fire. *Hydrology and*
808 *Earth System Sciences* 16, 267–285.

809 Tessler, N., Wittenberg, L., Greenbaum, N., 2013. Soil water repellency persistence after
810 recurrent forest fires on Mount Carmel, Israel. *Int. J. Wildland Fire* 22, 515–526.

811 USDA Forest Service, 2000. Burned Area Emergency Rehabilitation (BAER) Report; 2500-8
812 Valley Complex Fires-Phase I. Unpublished report. Available from U.S. Department of
813 Agriculture, Forest Service, Bitterroot National Forest, Hamilton, Montana, USA.

814 Vierira, D.C.S, Fernández, C., Vega, J.A., Keizer, J.J. 2015. Does soil burn severity affect the
815 post-fire runoff and interrill erosion response? A review based on meta-analysis of field
816 rainfall simulation data. *J. Hydrology* 523, 452–464.

817 Vogelmann, E.S., Reichert, J.M., Prevedello, J., Consensa, C.O.B., Oliveira, A.É., Awe, G.O.,
818 Mataix-Solera, J., 2013. Threshold water content beyond which hydrophobic soils become
819 hydrophilic: The role of soil texture and organic matter content. *Geoderma* 209–210, 177–
820 187.

821 Wang, Z., Wu, Q.J., Wu, L., Ritsema, C.J., Dekker, L.W., Feyen, J., 2000. Effects of soil water
822 repellency on infiltration rate and flow instability. *J. Hydrology* 231–232, 265–276.

823 Wilcox, B.P., Wood, M.K., Tromble, J.M., 1988. Factors influencing infiltrability of semiarid
824 mountain slopes. *J. Range Manage.* 41, 197–206.

825 Woods, S.W., Balfour, V.N., 2008. The effect of ash on runoff and erosion after a severe forest
826 wildfire, Montana, USA. *Int. J. Wildland Fire* 17, 535-548.

827 Woods, S.W., Balfour, V.N., 2010. The effects of soil texture and ash thickness on the post-fire
828 hydrological response from ash-covered soils. *J. Hydrology* 393, 274–286.

829 Zehe, E., Elsenbeer, H., Lindenmaier, F., Schulz, K., Blöschl, G., 2007. Patterns of predictability
830 in hydrological threshold systems. *Water Resources Res.* 43(7), W07434.

831

832

Table 1

Location, simulated rainfall rate, rainfall amount, runoff ratios and sediment yields in unburned and burned plots, and reference for rainfall simulator studies in severely burned coniferous forests. Plot areas were between 0.24 and 33 m². If multiple events were conducted on the same plot, only the first simulation is shown here to represent dry antecedent conditions. All data are averages from the year of the fire.

Location	Rainfall rate (mm h ⁻¹)	Rainfall amount (mm)	Unburned runoff ratio (%)	Unburned sediment yield (g m ⁻²)	Burned runoff ratio (%)	Burned sediment yield (g m ⁻²)	Reference
Western Montana	100	100	55	14	69	1757	This study
Western Montana	76	76	Not reported	Not reported	44	1040	Woods and Balfour, 2008
Western Montana	94	47	8.5	4	26	262	Robichaud, 1996, 2000
Central Idaho	94	47	32	85	55	628	Robichaud, 1996, 2000
Southern British Columbia	80	27	Not reported	Not reported	46	600	Robichaud et al., 2013a
Central Colorado	78 (86 in burned areas)	78 (86)	55	34	66	428	Benavides-Solorio and MacDonald, 2001
Northern New Mexico ^a	60	60	20	21	42	414	Johansen et al., 2001
Eastern Spain	55	55	Not reported	Not reported	43	76 g	Cerdà and Doerr, 2008
NW Italy ^b	74	74	Not reported	Not reported	29	17	Rulli et al., 2006
Central Portugal	51	38-51 ^c	5.5	Not reported	65	Not reported	Ferreira et al., 2005

^aRotating boom simulator, 32.5 m² plots.

^bSimulation area 13 m².

^cEstimated from intensity and range of durations

Table 2

Number of plots, soil moisture, understory canopy cover, ground cover, mean soil water repellency occurrence at 0–3 cm depth, total infiltration, runoff, and collected sediment by year and treatment. The standard error of the means are shown in parentheses. Different letters within a column indicate significant differences at $\alpha=0.05$.

Year	Treat- ment	n	Soil moisture (%)	Canopy cover* (%)	Ground cover* (%)	Water repellency occurrence (%)	Infiltration (mm)	Runoff (mm)	Sediment yield (g m ⁻²)
PF0	Control	21	18 (2.0) de	25 (3.7) cd	87 (2.1) a	93 (3.9) a	44 (3.5) bc	58 (3.5) bcd	50 (7.1) c
	Bare	21	18 (2.4) de	0 (0)	0 (0)	99 (0.6) abcd	19 (2.6) e	86 (3.0) a	849 (77) a
	Burned	60	17 (2.0) cd	0.1 (0.04) f	10 (1.0) b	88 (2.3) ab	31 (1.0) de	70 (1.1) b	1757 (114) a
PF1	Control	21	33 (2.5) abc	28 (4.1) cd	90 (1.8) a	39 (8.6) d	45 (4.0) bc	56 (3.9) cd	15 (3.0) d
	Bare	21	36 (4.2) ab	0 (0)	0 (0)	38 (7.1) d	36 (2.7) bcd	64 (2.7) bcd	677 (60) a
	Burned	59	15 (1.1) d	7 (1.2) e	6 (1.4) c	79 (3.5) abc	38 (1.4) bc	61 (1.4) cd	1099 (60) a
PF2	Control	21	44 (4.8) a	42 (5.6) abc	91 (2.3) a	51 (8.8) cd	48 (3.6) b	53 (3.6) d	7 (1.4) e
	Bare	20	44 (5.7) a	0 (0)	0 (0)	62 (9.0) bcd	34 (3.2) cd	67 (3.2) bc	624 (81) a
	Burned	59	17 (1.4) cd	33 (3.1) bd	17 (3.9) b	48 (4.4) d	37 (1.3) bc	62 (1.3) cd	391 (47) b
PF5	Control	20	24 (4.2) bcd	59 (8.9) ab	91 (1.3) a	94 (4.1) a	47 (3.4) b	53 (3.4) d	54 (22) cd
	Bare	17	15 (2.3) cde	0 (0)	0 (0)	99 (1.0) ab	41 (1.7) bcd	59 (1.7) bcd	1277 (158) a
	Burned	46	3 (0.4) e	45 (2.5) ac	42 (5.2) a	45 (5.2) d	84 (1.5) a	14 (1.5) e	15 (3.6) de

*Bare plots were not included in the statistical analyses of these variables as all canopy and ground cover was removed before simulations began.

Table 3

Mean soil moisture, water repellency occurrence at 0–3 cm depth, infiltration, runoff, and sediment yield for a subset of 14 plots sampled in spring PF1. Standard errors of the means are shown in parentheses. Data for the same 14 plots are included for PF0 and PF1 for comparison.

Year	Treatment	n	Soil moisture (%)	Water repellency occurrence (%)	Infiltration (mm)	Runoff (mm)	Sediment yield (g m ⁻²)
PF0	Control	3	26 (12)	100 (0)	47 (13)	56 (14)	60 (24)
	Bare	3	29 (13)	100 (0)	22 (12)	83 (12)	626 (132)
	Burned	8	12 (2.1)	92 (4.7)	29 (1.8)	70 (1.6)	2117 (308)
Spring PF1	Control	3	74 (14)	4.2 (4.2)	67 (12)	31 (12)	9.2 (3.9)
	Bare	3	52 (8.1)	21 (21)	45 (8.2)	53 (8.3)	738 (293)
	Burned	8	21 (3.7)	36 (14)	46 (2.7)	52 (2.8)	1278 (128)
PF1	Control	3	26 (3.5)	13 (13)	40 (11)	62 (9.6)	5.1 (0.8)
	Bare	3	49 (22)	33 (8.3)	35 (0.2)	66 (0.8)	811 (371)
	Burned	8	16 (2.4)	69 (14)	36 (1.5)	63 (1.8)	1195 (68)

Figure Captions for Robichaud et al.

- Fig. 1. Location of study sites, Daly Creek snow telemetry site, and the burned area along the Montana-Idaho border. Site map on right is depicted by rectangle in locator map.
- Fig. 2. PF5 rainfall simulation on a bare plot in an unburned site. The surface vegetation, litter, and duff were removed from the plot and the area immediately adjacent to the plot. (Photo credit: USDA-Forest Service J. Yost)
- Fig. 3. Particle size distribution of burned and unburned surface soils.
- Fig. 4. Mean occurrence (%) of soil water repellency by year, treatment, and depth. Mean soil moisture (%) by year and treatment is listed.
- Fig. 5. Mean infiltration rate (mm h^{-1}) plotted over the 60 min rainfall simulation for each treatment and year.
- Fig. 6. Results of the excavation showing mean percentage of the trench cut face (50 cm wide and 20 cm deep in 2 cm depth increments) wetted by the simulated rainfall. Data shown by year and by treatment. Dark and light shading indicate depth segments, and both represent wet soil. T Inf = Total Infiltration (mm). T WA = Total Wetted Area (%).
- Fig. 7. Mean sediment concentration (g L^{-1}) over the 60 min rainfall simulation for each treatment and year.
- Fig. 8. Mean soil water repellency occurrence plotted against soil moisture by treatment (colors) and year (symbols) including Spring PF1.

Figure 1

Figure 2

Figure 3

Figure 4

Figure 5

Figure 6

Figure 7

Figure 8