Analysis of Environmental and Economic Tradeoffs in Switchgrass Supply Chains for Biofuel Production

Jia Zhongⁱ¹, T. Edward Yu[†], James A. Larsonⁱ, Burton C. Englishⁱ,

Joshua S. Fuⁱⁱ and James Calcagnoⁱⁱ

ⁱDepartment of Agricultural and Resource Economics
University of Tennessee
Knoxville, TN 37996-4518

ⁱⁱDepartment of Civil and Environmental Engineering
University of Tennessee
Knoxville, TN 37996-2313

[†] T. E. Yu is the corresponding author. Yu's contact info: 302 Morgan Hall, 2621 Morgan Circle,
Knoxville, TN 37996-4518. Tel: +1-865-974-7411. Fax: +1-865-974-9492.
E-mail: tyul@utk.edu

¹ Zhong's present address is 416 Mumford Hall, 1301 Gregory Drive, Urbana, 61801. She is currently a Ph.D. student in the University of Illinois, Urbana Champaign.

Abstract: This study considered the environmental advantages of switchgrass, along with the economic challenges in its logistics, in the design of a sustainable switchgrass supply chain in Tennessee. Applying a multi-objective optimization model to high resolution spatial data, potential tradeoffs among the objectives of minimizing feedstock costs, greenhouse gas (GHG) emissions, and soil erosion were identified for a set of conversion facilities on an efficient frontier. The tradeoff relationship was primarily driven by the type of agricultural land converted to switchgrass. Hay and pasture lands were more cost effective but resulted in higher soil carbon losses and soil erosion after being converted to switchgrass. Converting crop lands reduced GHG emissions and soil erosion but caused higher feedstock cost primarily due to the higher opportunity cost of land use. The respective average costs of abating GHG emissions and soil erosion on the efficient frontier were \$2,378 Mg⁻¹ and \$10 Mg⁻¹. The compromise-solution conversion-facility site generated 63% higher feedstock cost compared to the cost minimizing location, while reducing soil erosion by 70 fold and diminishing GHG emissions by 27%. Reducing soil erosion may be a more cost effective environmental criterion than reducing GHG emissions in developing a sustainable switchgrass supply chain in Tennessee.

Keywords: Switchgrass, multi-objective optimization, Supply chains, Greenhouse gas, Soil erosion, Tradeoffs

1 **1 Introduction¹**

Higher energy prices and the mandate set forth in the Renewable Fuel Standard of the Energy Independence and Security Act of 2007 [1] have driven growth in ethanol produced using corn (*Zea mays* L.). Changes in land use with expanded corn production have raised concerns about increased soil erosion, fertilizer and pesticide pollution, and greenhouse gas emissions [2]. Corn uses more fertilizer than other major crops and accounted for 46% of all fertilizer use in the United States in 2010 [3]. Tillage intensity is also higher for corn production than for other crop production, exacerbating water-induced soil erosion [2]. Therefore, the expansion of corn production on existing croplands, set aside agricultural lands, and grasslands [4-7] has aggravated soil erosion [8, 9] and losses of nutrients to the environment [10].

The US Environmental Protection Agency (EPA) has advocated the production of biofuels from lignocellulosic biomass (LCB) to overcome the aforementioned problems from using grain crops to produce biofuels. In addition, the US EPA's 2014 Clean Power Plan promotes the production of biofuels using LCB as a strategy to reduce GHG emissions [11]. The agency requires that any advanced biofuel generate 60% fewer lifecycle GHG emissions than gasoline or diesel fuel when measured at 2005 levels [12]. Biofuels produced from LCB, including short-

¹ Abbreviations:

LCB – lignocellulosic biomass

GHG – greenhouse gas

USDA – US Department of Agriculture

EPA – Environmental Protection Agency

RUSLE – Revised Universal Soil Loss Equation

MRS – marginal rate of substitution

rotation woody crops, agricultural residues, and herbaceous grasses, have great potential for reducing GHG emissions relative to biofuels produced from grain crops (Farrell et al. 2006). Growing perennial grasses to produce biofuels also could reduce soil erosion on agricultural lands [13, 14], an important objective of US agricultural policy [15].

Switchgrass (*Panicum virgatum*), a herbaceous prairie grass native to North America, requires less fertilizer and chemicals, has better water use efficiency, and has greater tolerance to a wide range of environmental conditions when compared to field crops and other herbaceous species [16, 17]. Because switchgrass is a perennial crop with a life span of 10 or more years, it provides year-round coverage of soils and enhances soils through its extensive root system that reduces water runoff and soil losses and by improving soil organic matter, soil structure, soil water holding capacity, and nutrient holding capacity [18]. Previous studies have suggested that biofuels produced using switchgrass could reduce GHG emissions by 60% to 90% when compared with fossil fuels [19] and up to 50% when compared with biofuels produced using corn grain [20, 21].

Despite the potential environmental and ecological advantages, the high cost of using switchgrass for biofuels production has impeded development of a switchgrass-based biofuels industry [22, 23]. Biofuels produced using switchgrass costs 17.8% more than corn and 34.4% more than gasoline when measured on an energy equivalent basis in 2005 dollars [23, 24]. Procurement costs in a switchgrass supply chain may constitute 30%–50% of the total cost of

producing biofuels [22, 25, 26]. Important factors contributing to higher supply chain costs include low bulk density of switchgrass; increasing harvest, storage, and transportation costs; and losses of feedstock stored outdoors due to weathering if switchgrass is harvested only once a year [27].

Operations research methods have been widely used to evaluate the design of LCB supply chains using cost minimization or profit maximization as the objective of the decision maker (e.g. 25–26, 28). However, an increasing number of studies have examined economic and environmental tradeoffs in the design of a sustainable LCB supply chain [28–32]. Notwithstanding the growing literature evaluating tradeoffs in biofuels production, the imputed costs of mitigating environmental degradation or improving environmental quality with biofuels produced using LCB have only been examined on a limited basis [32]. The imputed cost is the proxy value of ecosystem services provided by LCB production such as reduced GHG emissions and soil erosion in the design of a sustainable supply chain [32–33].

An assessment of the sustainability of an LCB supply chain depends on the use of high-resolution spatial data to accurately model the characteristics of the supply chain [34]. Spatially oriented factors such as LCB availability, changes in fertilizer and chemical use with LCB production, and feedstock transportation costs and emissions influence the optimal configuration of a sustainable supply chain. Models that use high spatial resolution data generate more detailed predictions of the footprint of the LCB supply chain and are more useful for policy analysis and

for private and public decision making [35]. Most multi-objective studies have not taken into account spatial characteristics, with only a few studies highlighting the value of geographic data in the economic and/or environmental optimization of the LCB supply chain [29, 32, 35, 36].

A systematic assessment of the imputed costs of environmental services in a LCB supply chain will contribute to a better understanding by potential stakeholders of the cost-benefit tradeoffs of biofuels production. However, the existing literature lacks an integrated mathematical model valuation that incorporates high-resolution geospatial data on various environmental outputs from LCB supply chains. Acknowledging that gap in the literature, the present study combines the use of detailed spatial data and a multi-criteria optimization model to examine economic and environmental tradeoffs in a LCB supply chain. This study extends the typical tradeoff analysis in bioenergy literature to assess the value of various environmental outputs from LCB supply chains. The fine spatial details included in the LCB supply chains analysis enhances the determination of feedstock draw area and conversion facility location. The detailed data also improves the precision of soil erosion and greenhouse gas emissions estimation from the land use changes required to supply the biomass.

The analysis focuses on the optimal location and design of a switchgrass supply chain in Tennessee. The state of Tennessee has several characteristics that lend itself to an evaluation of economic and environmental tradeoffs in biofuels production: a humid subtropical climate that is well suited to the production of high yielding switchgrass, agricultural soils that are highly

erodible, and a geographically diverse set of agricultural production activities and landscapes. Thus, the objectives of this study are: (1) to determine the potential tradeoffs required to minimize feedstock costs, GHG emissions, and soil erosion for a switchgrass supply chain in Tennessee, and (2) to evaluate the imputed costs of abating GHG emissions and soil erosion in the switchgrass supply chain. The valuation of GHG emissions and soil erosion can assist in the development of an economically and ecologically viable advanced biofuel production effort.

2 Methods and Data

2.1 Supply chain assumptions

Minimization of total switchgrass cost was assumed to be the primary objective of conversion facility decision makers. High feedstock cost has been identified as an important impediment to the development of a switchgrass-based biofuel industry for private investors interested in maximizing profits [22, 23]. The two environmental criteria, minimization of GHG emissions and minimization of soil erosion are driven by US EPA and US Department of Agriculture (USDA) policies aimed at reducing their levels [12],[15]. The system boundary for calculating switchgrass costs, GHG emissions, and soil erosion produced in the supply chain was from the farm field to the conversion facility plant gate (Figure 1).

[Place Figure 1 here]

The switchgrass conversion facility was assumed to produce 189.3 million liters (L) of ethanol year⁻¹. The five main feedstock cost components considered in the design of the supply

chain were: (1) land resource allocation, (2) production, (3) harvest, (4) storage, and (5) transportation. Supply chain activities were modeled on a monthly time step. Switchgrass was harvested between November and February after senescence, delivered to the facility or placed in storage during harvest, and delivered from storage to the facility for processing in the off-harvest period from March through October. Assuming a conversion rate of 287.7 L of ethanol dry Mg⁻¹ of switchgrass [37], feedstock required for the facility was 600,892 dry Mg year⁻¹.

The potential switchgrass supply area in this study included all agricultural land in Tennessee and a buffer area of 80 km contiguous to the state border (Figure 2). Locations for the conversion facility were limited to 150 industrial parks in the Tennessee Valley Authority database [38]. Candidate industrial parks had the required space and access to roads and water resources for the facility. The study area was downscaled to a 13 km² hexagon resolution, defined as the land resource unit, to capture variations in land resources, the transportation network, and other geographic features of the study area. The ratio of crop land to hay and pasture land by land resource unit in Figure 2 indicates that west Tennessee is the major crop production area, while pasture and hay land is primarily located in the eastern region of the state.

[Place Figure 2 here]

The payoff-table method was used to determine the most preferred solution [39] of the multi-objective feedstock cost, GHG emission, and soil erosion minimization model. The supply chain model considering the aforementioned feedstock cost components was solved for each individual

objective for each of the 150 industrial park sites in the study area. Optima and nadir values and the ranges obtained from solving for each individual objective were used in an improved augmented ε -constraint method [40] to solve the multi-objective function for each potential conversion facility site. Feasible and efficient solutions for all 150 sites in the study area form the efficient-frontier (also called the Pareto-optimal) set of conversion facilities for the study area. The compromise solution method [41] was used to identify the most preferred conversion facility site and the switchgrass draw area for the supply chain on the frontier. Costs of abating GHG emissions and soil erosion in the supply chain were imputed using the frontier solution.

2.2 Model structure

2.2.1 Cost minimization

Following Larson et al. [42], minimization of feedstock cost at the conversion facility plant gate (TC , \$) for the switchgrass supply chain was modeled using Equations (1) to (6):

$$\text{Min } TC = C_{\text{opportunity}} + C_{\text{production}} + C_{\text{harvest}} + C_{\text{storage}} + C_{\text{transportation}}, \quad (1)$$

$$C_{\text{opportunity}} = \begin{cases} \sum_{ip} [(Price_{ip} \times Yield_{ip} - PC_{ip}) \times AH_{ip}], & \text{if } (Price_{ip} \times Yield_{ip} - PC_{ip} - LR_{ip}) \geq 0 \\ \sum_{ip} (LR_{ip} \times AH_{ip}) & , \text{ if } (Price_{ip} \times Yield_{ip} - PC_{ip} - LR_{ip}) < 0 \end{cases}, \quad (2)$$

$$C_{\text{production}} = \sum_{ip} ((Est + AM) \times AH_{ip}), \quad (3)$$

$$C_{\text{harvest}} = \sum_{ip} (\sigma_i \times AH_{ip}), \quad (4)$$

$$C_{\text{storage}} = \sum_{mi} (\gamma_i \times NXE_{mi}), \text{ and} \quad (5)$$

$$C_{transportation} = \sum_i (\theta_i \times (\sum_m XTN_{mi} + \sum_m XTO_{mi})) / (1 - DML^{trans}). \quad (6)$$

Costs for production ($C_{production}$), harvest ($C_{harvest}$), storage ($C_{storage}$), and transportation ($C_{transportation}$) activities in Equation (1) included equipment ownership, maintenance, labor, fuel, and materials used for farm field to plant gate activities in the switchgrass supply chain. Definitions of the cost parameters and decision variables are listed in Table 1. The key parameters in the equations in this section and subsequent sections (2.2.2 and 2.2.3) are summarized in Appendix Table A.

[Placed Table 1 here]

Opportunity cost ($C_{opportunity}$) in Equation 2 was defined as the forgone profit from crop, hay, and pasture production activities from the prior land use or the market rental rate for the land [42]. Cost of switchgrass production ($C_{production}$) in Equation 3 included the annualized establishment cost and annual maintenance cost. Harvest cost ($C_{harvest}$) in Equation 4 assumes switchgrass was processed into large rectangular bales. Storage cost for switchgrass (γ_i) in Equation 5 included materials, equipment, and labor for rectangular bale staging and storage operations. Transportation costs (θ_i) in Equation 6 assumed the use of semi-trailer trucks and trailers to transport switchgrass from storage to the conversion facility. Costs for transportation were determined by the time required to perform each activity. Loading and unloading times for bales were taken from a study by Duffy [43]. Distance and truck speed based on highway speed

limits were used to determine transportation time. Maximum travel distance to transport switchgrass to the conversion facility was assumed to be 121 km.

The cost minimization was subject to constraints based on practical operation requirements and rules of mass balance:

$$\text{Available area for production: } \sum_m AH_{mip} \leq Aa_{ip}, \forall i, p \text{ Nov} \leq m \leq \text{Feb.} \quad (7)$$

$$\text{Available harvest working hours: } NM_m^k \times Avehour_m - \sum_i (MTB_i^k \times AH_{mip}) \geq 0, \forall k, m. \quad (8)$$

Harvest to shipment and storage balance:

$$\sum_p AH_{mip} \times Yield_i^{swg} = XTN_{mi} / (1 - DML^{trans}) + NXE_{mi}, \forall m, i. \quad (9)$$

Cumulative storage balance during harvest season:

$$XE_{(m+1)i} = (1 - DML_m^{stor}) \times XE_{mi} + NXE_{(m+1)i}, \forall m, i \text{ Nov} \leq m \leq \text{Feb.} \quad (10)$$

Cumulative storage balance during off-harvest season:

$$XE_{(m+1)i} = (1 - DML_m^{stor}) \times XE_{mi} - XTO_{(m+1)ip} / (1 - DML^{trans}), \forall m, i \text{ March} \leq m \leq \text{Oct.} \quad (11)$$

$$\text{Ethanol production requirement: } \lambda (\sum_i XTN_{mip} + \sum_i XTO_{mi}) - Q_m = 0, \forall m. \quad (12)$$

$$AH, NXE, XE, XTN, XTO, \text{ and } NM \geq 0. \quad (13)$$

Equation (7) restricts available land area based on switchgrass yields in each land resource unit. Machine hours month⁻¹ are constrained in Equation (8) to available harvest days based on weather during harvest. Equation (9) requires switchgrass harvested to equal the summation of switchgrass delivered directly to the conversion facility (XTN) after adjusting for transportation dry matter losses and quantity of feedstock sent to storage (NXE). Equations (10) and (11)

maintain the balance of the cumulative storage of switchgrass after accounting for storage dry matter losses. Feedstock deliveries to the conversion facility in each month need to meet the demand for biofuel production in Equation (12). All parameters and variables in the model are nonnegative as required in Equation (13).

2.2.2 GHG emissions minimization

The framework presented by Yu et al. [32] was used to calculate GHG emissions generated in the switchgrass supply chain. Equations (14) through (18) model the minimization of total GHG emissions (TE , kg yr^{-1}) from supply chain activities:

$$\text{Min } TE = E_{luc} + E_{energy} + E_{transportation} + E_{ind}. \quad (14)$$

$$E_{luc} = \sum_p \left(\sum_{mi} AH_{mip} \times (\Delta LUCO_{2,P} + \Delta LUCH_{4,P} + \Delta LUN_{2O,P}) \right), \quad (15)$$

$$E_{energy} = \sum_{mip} AH_{mip} \times (ProE + HarE) + \sum_{mip} AH_{mip} \times Yield_i^{swg} \times StorE, \quad (16)$$

$$E_{transportation} = \sum_{mi} TransE_{mip} \times (XTN_{mi} + XTO_{mi}) / (Loadwt \times (1 - DML^{trans})), \text{ and} \quad (17)$$

$$E_{ind} = \sum_{mip} (FertE + ChemE + SeedE) \times AH_{mip} + \sum_{mb} NM_{mb}^k \times machE^k. \quad (18)$$

The definitions for the emission parameters are listed in Table 1. The major sources of changes in emissions were from adjustments in land use (E_{luc}), energy consumption from switchgrass production, storage, and harvest (E_{energy}), transportation ($E_{transportation}$), and from the energy used to manufacture seed, fertilizer, chemicals, and machinery (E_{ind}) used in the supply chain. Emissions caused by changes in land use were calculated by multiplying the emission

factors for CO₂, CH₄, and N₂O by the area of crop, hay, and pasture lands converted to switchgrass production [Equation (15)]. Energy consumption for switchgrass production and storage activities were calculated through the summation of land area times the farm operations' emission factors and storage weight times the storage emission factor [Equation (16)]. Transportation emissions were calculated through the multiplication of the emission factor per truck per route times the truck loads for all transported biomass [Equation (17)]. Indirect emissions are from the manufacture of fertilizer, chemicals, seed, and machinery used in the production of switchgrass [Equation (18)].

2.2.3 Soil erosion minimization

For the soil erosion minimization objective, changes in water-induced soil erosion from converting crop, hay, and pasture lands to switchgrass production were estimated using the Revised Universal Soil Loss Equation (RUSLE) [44-46]. Water-induced soil erosion is influenced by land use activity (crop, hay, and pasture production), tillage method, landscape, and precipitation factors in the RUSLE model. Equation (19) models the annual soil loss (*TSoilE*, Mg ha⁻¹ yr⁻¹) minimization objective:

$$\text{Min } T\text{SoilE} = \sum_i \{ (R_i \times K_i \times LS_i \times P_i) \times \sum_p [(\Delta Cf) \times \sum_b AH_{ipb}] \}, \quad (19)$$

where *R* was rainfall and runoff factor, *K* was soil erodibility factor, *LS* was length and steepness of slope factor, *P* was support practice factor, and ΔCf was crop vegetation and management

factor. The R , K , LS , and P factors in each land resource unit were obtained using the ArcGIS intersect geoprocessing method and pivot table in Excel to estimate weighted average values for each factor for each land resource unit.

To evaluate the impact on soil erosion of land conversion to switchgrass, the estimates of $TSoilE$ before and after the conversion of land to switchgrass production were compared with USDA NRCS estimates of soil loss tolerance (T , $Mg\ ha^{-1}\ yr^{-1}$) by land resource unit [47]. Soil loss tolerance, T , is defined in the RULSE2 database as “the maximum amount of soil loss [$Mg\ ha^{-1}\ yr^{-1}$], that can be tolerated and still permit a high level of crop productivity to be sustained economically and indefinitely.” [48]. The frequency of land resources where $TSoilE > T$ before and after the conversion of crop, hay, and pasture lands into switchgrass production were evaluated to ascertain the effects of switchgrass production on soil erosion within the switchgrass supply chain area.

2.3 Multiple objective optimization

2.3.1 Improved augmented ϵ -constraint method in multi-objective program

The improved augmented ϵ -constraint method, AUGMECON2 [40], was applied to derive the tradeoff relationship among the three competing objectives for each potential conversion facility location. The tradeoff relationship among objectives indicates that the performance of one objective could not be improved without degrading the performance of the other objectives. The procedure was applied to all 150 potential industrial park locations for conversion facilities

in the study area to generate the efficient frontier. The details of the AUGMECON2 method are available in Mavrotas and Florios [40].

The AUGMECON2 method for the three objectives takes the form:

$$\text{Min. } (TC - \varepsilon \times (s_2 / r_2 + 10^{-1} \times s_3 / r_3)), \quad (20)$$

Subject to:

$$TE + s_2 = e_2, \text{ and} \quad (21)$$

$$TSoilE + s_3 = e_3, \quad (22)$$

where TC , TE , and $TSoilE$ are the three competing objectives defined in Equations (1), (14), and (19), ε is a small number (in this study ε was set to be 10^{-3}), s is the non-negative slack variable, r_2 and r_3 are the ranges of the objective functions for TE and $TSoilE$, e is the constraint applied to the TE and $TSoilE$ through interpolating four grid points to create five equal intervals in the value range (r). The slack variable s was added to the objective function in Equations (20) – (22) to produce only efficient solutions. Minimization of cost was the primary objective with the two environmental criteria as the secondary objectives in the optimization [40].

To determine the nadir values and generate the ranges of the TE and $TSoilE$ objective functions, a 3×3 payoff table was generated by considering each of the objectives as a single objective problem. The diagonal of the payoff table provides the optima values for each of the three objectives. For the TE and $TSoilE$ objectives, the optima were the lower bound values (l_2) and (l_3), respectively. The nadir value of TE and $TSoilE$, u_2 and u_3 , respectively, were the

maximum values of TE and $TSoilE$. The ranges of the objective value for TE and $TSoilE$ were obtained from the differences between upper and lower bound values: $r_2 = u_2 - l_2$; $r_3 = u_3 - l_3$.

The AUGMECON2 method identifies weakly efficient points and bypasses the surplus grid points, reducing computation time [40]. The combination of two sets of grid points for other objectives started from looping through the inner most objective (TE) first from the nadir value grid to the optima value grid, followed by the exterior grid point ($TSoilE$) after each iteration of the inner objective loop. The feasible solution can be obtained with the first round of relaxed exterior constraints. The rolling computation for the exterior grid point could be saved to reduce computation time if no alternative optima were generated from the prior settings of lexicographic optimization objective in Equation (20). In this study, the algorithm was further improved by eliminating the iteration of the grid points for $TSoilE$, given that the solutions did not vary from those obtained from iterating the grid points of the TE objective. Thus, the iteration in constrained objectives for a conversion facility site was reduced from 36 (6×6) to 6 in the solving process, which consequently improved the computation efficiency and reduced computation time by more than 80%.

2.3.2 Compromise solution method

The set of conversion facilities on the efficient frontier for the study region was developed to evaluate the potential tradeoffs among the three competing objectives. The most preferred

solution point on the frontier was identified using the compromise solution method [41]. The compromise solution optimal point was determined by the minimum distance ($D(S)$), measured by Tchebycheff norms [49], to the ideal point (z^*) on the frontier:

$$D(S) = \max_{j=1, \dots, 3} \left\{ \lambda_j |z_j(S) - z_j^*| \right\} \quad (23)$$

where j indexed the objective functions, λ_j was the normalized weight for each objective function, and S was the set of points on the frontier. The normalized weight, λ_j , was defined as:

$$\lambda_j = 1/r_j \times \left[\sum_{j=1}^3 (1/r_j) \right]^{-1}, \quad (24)$$

where r was the previously defined objective value range. The ideal point (z^*) was defined according to the individual minima of each objective ($z^* = [l_1, l_2, l_3]$) from the payoff tables. To further illustrate the relative relationship between each point on the frontier and the compromise solution point, a D score was calculated as the relative value of the $D(S)$ of each point to the $D(S)$ of the compromise optimal solution (i.e. the min. $D(S)$):

$$D \text{ score} = [D(S) / \min. D(S)]. \quad (25)$$

The solution for the efficient frontier was used to impute the costs of mitigating GHG emissions and soil erosion in the supply chain [31]. Two measures of the tradeoffs among higher feedstock costs, lower GHG emissions, and lower soil erosion were calculated using the model solution for the feasible and efficient set of conversion facilities on the efficient frontier. The first approach was to calculate the marginal rate of substitution (MRS) between feedstock cost and GHG emissions. MRS was determined using the ratio of the normalized weights for feedstock

costs and GHG emissions and the ratio of the range of cost to the range of GHG emissions on the efficient frontier [50]. The MRS between feedstock cost and soil erosion was also derived. The respective MRS of cost-GHG emissions and cost-soil erosion provide the average costs Mg^{-1} of reducing GHG emissions and soil erosion on the frontier. The second approach was to calculate the costs Mg^{-1} of reducing GHG emissions and soil erosion for the compromise solution conversion facility locations versus the cost minimization solution conversion facility locations. Cost comparisons were also made for the GHG emission and soil erosion minimization conversion facility locations versus the cost minimization solution conversion facility locations.

2.4 Data

The data sources and models used in the lexicographic model to estimate feedstock cost, GHG emissions, and soil erosion are summarized in Table 2. The data and derived parameters were all associated with geospatial characteristics of the land resource units. DAYCENT, a daily time-step biogeochemical plant-soil system model, was adopted to simulate soil carbon uptake and CH_4 and N_2O emission factors [51]. The change in soil carbon stock was calculated using IPCC guidelines [52]. Differences in geography and soils between east, middle and west Tennessee were considered in the estimation of soil carbon. Emission factors for energy combustion from farm equipment operations and the indirect emission factors for the manufacturer of agricultural machinery, fertilizer, chemicals, and seed were estimated using the

Greenhouse Gases, Regulated Emissions, and Energy Use in Transportation (GREET) Model [53]. Emissions from feedstock transportation were estimated using the Motor Vehicle Emissions Simulator (MOVES) version 2010b [54], considering travel distance, local weather, travel speed and slopes of roads.

[Place Table 2 here]

3 Results and Discussion

3.1 Efficient frontier

Figure 3 presents the relationships among the three competing objectives for a single conversion facility site (Figure 3-i), all 150 potential sites (Figure 3-ii), and the efficient frontier (Figure 3-iii). The following describes the key components in the frontier that are illustrated in each panel of the chart and the resulting economic implications. First, GHG emissions and soil losses were mitigated in the supply chain when switchgrass procurement costs increased; whereas, GHG emissions and soil erosion were positively correlated with each other (Figure 3-i). The model converted more crop land to accommodate the tradeoffs in lower levels of GHG emissions and soil erosion for higher feedstock costs. Crop lands have higher opportunity costs, larger fertilizer and chemical expenditures, greater soil erosion, and were more geographically dispersed relative to hay and pasture lands.

[Place Figure 3 here]

Second, GHG emissions and soil erosion in the supply chain were less dispersed with low feedstock costs (Figure 3-ii). The ranges of GHG emissions and soil erosion expanded as feedstock costs increased in the model to facilitate tradeoffs in the cost and environmental objectives. Low feedstock costs were associated with the conversion of hay and pasture lands. Abatement of GHG emissions and soil erosion were achieved through the conversion of crop land, leading to a wider dispersion in feedstock costs.

Third, a total of 881 feasible solution points were found in the optimization (Figure 3-iii) for the 150 potential conversion facility sites. Black dots on the efficient frontier are the final conversion facility site solution points given that the value of one objective could not be improved without degrading the values of the other two objectives. Among those 881 feasible solution points from 150 sites, there were a total of 40 *efficient* potential conversion facility sites on the frontier. The individual-optimum solution points for feedstock costs (A), GHG emissions (B), and soil erosion (C) are identified as blue dots on the efficient frontier. The compromise solution point (O) is identified as a red dot.

Finally, the tradeoffs between higher feedstock costs and lower GHG emissions or lower soil erosion on the efficient frontier (Figure 3-iii) were imputed using the MRS. For the 40 conversion facilities on the frontier, the average cost of abating one Mg of GHG emissions was \$2,378. The average abatement cost for GHG emission was considerably higher than the \$10 average cost to reduce soil erosion by one Mg. Results indicated that soil erosion may be a more

cost effective environmental criterion than GHG emissions in the design of a sustainable switchgrass supply chain in Tennessee.

Figure 4 further illustrates the tradeoffs among the three competing objectives. D scores for the 40 conversion facilities on the efficient frontier and the geographic locations of the efficient facilities are shown in the figure. The color of each circle is related to the D score and the size of the circle represents the level of feedstock cost (panel i), GHG emissions (panel ii), and soil erosion (panel iii). For example, the compromise solution point (O) had larger feedstock costs and GHG emissions but lower soil erosion relative to many of the other sites on the efficient frontier.

[Place Figure 4 here]

3.2 Individual-optima and compromise solution

The feedstock draw areas for each individual-optimum conversion facility site and for the compromise solution conversion facility site are displayed in Figure 5. The feedstock draw area for the cost minimization solution (A) was the most geographically compact, while the draw areas for the GHG emission, soil erosion, and compromise solutions (B, C, and O) were more geographically dispersed. Feedstock cost is related to the density of switchgrass production in the conversion facility draw area, which impacts feedstock transportation costs [42]. Crop production is more concentrated in West Tennessee while hay and pasture production is more

prevalent in Middle and East Tennessee. With the two environmental objectives, the model traded off feedstock costs to convert highly erodible crop land to switchgrass in Middle and East Tennessee for the compromise solution (O). Thus, the choice of conversion facility location and feedstock draw area was primarily related to the availability of land resources and existing agricultural production.

[Place Figure 5 here]

Figure 6 shows the land coverage change for switchgrass production. Hay and pasture lands were primarily selected in the cost minimization solution (A), whereas crop lands were mostly utilized for switchgrass production in the GHG minimization (B) and soil erosion minimization (C) solutions. Converting crop lands to switchgrass resulted in higher opportunity cost from land use selection, increased soil carbon storage, and reduced soil erosion. The opportunity costs for converting hay and pasture lands to switchgrass were lower but resulted in higher soil carbon and soil erosion losses [19, 55]. Thus, a combination of crop, hay, and pasture lands were utilized in the compromise solution (O) to achieve the integrated multi-objective goal embodied in the compromise solution.

[Place Figure 6 here]

The percentage of land area with soil erosion exceeding USDA NRCS tolerance levels *ex ante* and *ex post* land converted to switchgrass for the individual-optima and compromise

solutions are shown in Figure 7. Prior to converting land to switchgrass production, nearly 50% of the switchgrass feedstock draw area for the cost minimization solution (A) exceeded tolerance levels. Whereas, all of the land area for the GHG emission (B) and soil erosion (C) minimization solutions had soil erosion exceeding the tolerance level. For the compromise solution (O), almost all (97%) of the switchgrass draw area prior to land conversion had soil erosion exceeding the tolerance rate. In contrast, less than 1% of all land area *ex post* switchgrass production exceeded the soil erosion tolerance levels for all four solutions. The reduction in soil losses mostly resulted from the year-round ground cover and deep root system provided by perennial switchgrass.

[Place Figure 7 here]

Itemized costs for each of the individual-optima and compromise solutions are summarized in Table 3. The cost minimization solution (A) had a total plant-gate feedstock cost of \$43.4 million. Harvest cost accounted for 51.6% of total feedstock cost, followed by production cost at 19.8% of total costs. Opportunity cost of \$1.3 million for the cost minimization solution was the lowest among the three objectives because low-cost hay and pasture lands were primarily converted to switchgrass production. For the environmental objectives, the two primary factors influencing cost differences were increased opportunity costs, caused by conversion of crop lands that had higher GHG emissions and soil erosion, and increased feedstock transportation costs caused by a more widely dispersed switchgrass production area. Total feedstock cost increased to \$60.5 million for the GHG minimization solution (B). Opportunity cost for the GHG

solution was 11.8 times greater and transportation cost was 27.7% larger than for the cost minimization solution (A). Soil erosion minimization (C) had the highest total cost among all individual optima cases of \$85.4 million with considerably higher opportunity (\$35.6 million) and feedstock transportation (\$16.1 million) costs. Total feedstock cost for the compromise solution (O) was \$70.7 million, 62.9% higher than the cost minimization solution, but 20.7% lower than the soil erosion minimization solution (C).

[Place Table 3 here]

The cost effectiveness of switchgrass production in reducing GHG emissions and soil erosion was further evaluated through an examination of differences in cost and abatement amounts among the four solutions (Table 3). The GHG emission minimization (B) solution reduced total net GHG emissions by 59%, from 44.9 thousand Mg to 18.6 thousand Mg, but at an increased feedstock cost of \$17 million when compared to feedstock cost minimization (A) solution (Table 3). The imputed cost of abating GHG emissions was \$648 Mg⁻¹ (\$17 million /26.3 thousand Mg) between the two solutions. Reduction in total emissions resulted from converting crop lands to switchgrass that sequestered more soil carbon and used fewer inputs than the crops it replaced [19, 55]. For the feedstock cost minimization (A) and soil erosion minimization (C) comparisons, the imputed cost of GHG emission sequestration was \$2,765 Mg⁻¹ given that feedstock cost nearly doubled and GHG emissions declined by only 33%. Similarly, the imputed cost of GHG

emissions abatement was \$2,270 Mg⁻¹ when comparing the feedstock cost minimization solution (A) to the compromise solution (O).

With respect to the soil erosion minimization (C) solution, 7.5 million Mg of soil erosion was averted at an additional feedstock cost of \$15.2 million when compared with the feedstock cost minimization (A) solution. The imputed cost of reduced soil erosion was \$5.60 Mg⁻¹ for the soil erosion minimization (C) solution. Contrasting the GHG emission minimization (B) solution with the cost minimization (A) solution resulted in 3.4 million Mg less soil erosion with an imputed cost of abatement of \$5.00 Mg⁻¹. Finally, about 7.4 million Mg soil erosion was averted with an increase in total feedstock cost of \$12 million with the compromise solution (O). The imputed cost for conserving soil in the feedstock draw area was the lowest among the four optimal solutions at \$3.70 Mg⁻¹. The efficient frontier and compromise solution results indicate that targeting soil erosion as an objective in the development of a sustainable switchgrass supply chain in Tennessee may be more cost effective than targeting GHG emissions.

4 Conclusions

This study identified an efficient set of switchgrass conversion facilities and draw areas to minimize feedstock costs, GHG emissions, and water-induced soil erosion for a switchgrass supply chain in Tennessee. Results show that the type of agricultural land converted to switchgrass production is crucial in determining feedstock costs and environmental impacts of

the supply chain. For instance, converting only crop lands to switchgrass in the GHG emissions minimization case incurred 10 times higher opportunity cost from land use change but stored 13 times more soil carbon and decreased soil erosion by almost 70 folds when compared with the cost minimization case that only converted hay and pasture lands. A mix of crop, hay, and pasture lands (48% corn, 31% soybean, 12% of hay/pasture, 7% cotton, and 1% wheat) achieved the goal of integrating the three objectives into the switchgrass supply chain in Tennessee.

Given the tradeoffs among minimization of feedstock costs, GHG emissions and soil erosion on the efficient frontier, the imputed cost of abating GHG emissions and soil erosion were evaluated by comparing marginal rates of substitution between feedstock cost and GHG emissions and feedstock cost and soil erosion. The average imputed cost of abating GHG emissions and soil erosion on the frontier was \$2,378 Mg⁻¹ and \$10 Mg⁻¹, respectively. This finding suggests that soil erosion could be a more cost effective environmental criterion than GHG emissions in the design of a sustainable switchgrass supply chain in Tennessee. However, the compromise solution conversion facility site generated 63% higher feedstock cost compared to the cost minimization location, but reduced soil erosion 70 fold and GHG emissions by 27%. The imputed costs of abating GHG emissions and soil erosion in the efficient set of supply chain sites in Tennessee could provide policy makers important information for the development of a sustainable switchgrass biofuels industry.

453 **Acknowledgements:** This project was partially funded by USDA Agriculture and Food
454 Research Initiative Competitive Grant no. 2011-68005-30410; USDA National Institute of Food
455 and Agriculture, Sustainable Bioenergy Challenge Area grant award #11025775; and US DOT
456 Grant no. DT0S5907G00050. The authors would also acknowledge Brad Wilson for data
457 preparation and management. The usual disclaimer applies.

References

- [1] U.S. Congress, Energy Independence and Security Act of 2007, (2007) Available at: http://frwebgate.access.gpo.gov/cgi-bin/getdoc.cgi?dbname=110_cong_bills&docid=f:h6enr.txt.pdf.
- [2] Larson JA, English BC, De La Torre Ugarte DG, Menard RJ, Hellwinckel CM, West TO, Economic and environmental impacts of the corn grain ethanol industry on the United States agricultural sector, *Journal of Soil and Water Conservation*, 65 (2010) 267-279.
- [3] USDA Economic Research Service, Fuel ethanol, corn and gasoline prices, in: T. Capehart (Ed.) *U.S. Bioenergy Statistics*, 2015.
- [4] Searchinger T, Heimlich R, Houghton RA, Dong F, Elobeid A, Fabiosa J, Tokgoz S, Hayes D, Yu TH, Use of U.S. croplands for biofuels increases greenhouse gases through emissions from land-use change, *Science*, 319 (2008) 1238-1240.
- [5] Hill J, Nelson E, Tilman D, Polasky S, Tiffany D, Environmental, economic, and energetic costs and benefits of biodiesel and ethanol biofuels, *Proceedings of the National Academy of Sciences of the United States of America*, 103 (2006) 11206-11210.
- [6] Gelfand I, Zenone T, Jasrotia P, Chen J, Hamilton SK, Robertson GP, Carbon debt of Conservation Reserve Program (CRP) grasslands converted to bioenergy production, *Proc Natl Acad Sci U S A*, 108 (2011) 13864-13869.
- [7] Tilman D, Socolow R, Foley JA, Hill J, Larson E, Lynd L, Pacala S, Reilly J, Searchinger T, Somerville C, Williams R, Energy. Beneficial biofuels--the food, energy, and environment trilemma, *Science*, 325 (2009) 270-271.
- [8] Evers BJ, Blanco-Canqui H, Staggenborg SA, Tatarko J, Dedicated Bioenergy Crop Impacts on Soil Wind Erodibility and Organic Carbon in Kansas, *Agronomy Journal*, 105 (2013) 1271.
- [9] Vadas PA, Barnett KH, Undersander DJ, Economics and Energy of Ethanol Production from Alfalfa, Corn, and Switchgrass in the Upper Midwest, USA, *BioEnergy Research*, 1 (2008) 44-55.
- [10] Pimentel D, Harvey C, Resosudarmo P, Sinclair K, Kurz D, McNair M, Crist S, Shpritz L, Fitton L, Saffouri R, Blair R, Environmental and economic costs of soil erosion and conservation benefits, *Science*, 267 (1995) 1117-1123.
- [11] U.S. EPA, Carbon Pollution Emission Guidelines for Existing Stationary Sources: Electric Utility Generating Units, (2014) Available at: <http://yosemite.epa.gov/oepi/rulegate.nsf/byRIN/2060-AR33>.
- [12] U.S. EPA, EPA Finalizes Regulations for the National Renewable Fuel Standard Program for 2010 and Beyond, (2010) Available at: <http://www.epa.gov/otaq/renewablefuels/420f10007.pdf>.
- [13] Khanal S, Anex RP, Anderson CJ, Herzmann DE, Jha MK, Implications of biofuel policy-driven land cover change for rainfall erosivity and soil erosion in the United States, *Global Change Biology Bioenergy*, 5 (2013) 713-722.

- [14] Zhang G, Tang K, Ren Z, Zhang X, Impact of Grass Root Mass Density on Soil Detachment Capacity by Concentrated Flow on Steep Slopes, *Transactions of the ASABE*, (2013) 927-934.
- [15] McGranahan DA, Brown PW, Schulte LA, Tyndall JC, A historical primer on the US farm bill: Supply management and conservation policy, *Journal of Soil and Water Conservation*, 68 (2013) 67A-73A.
- [16] Lewandowski I, Scurlock JMO, Lindvall E, Christou M, The development and current status of perennial rhizomatous grasses as energy crops in the US and Europe, *Biomass and Bioenergy*, 25 (2003) 335-361.
- [17] Mitchell R, Vogel KP, Sarath G, Managing and enhancing switchgrass as a bioenergy feedstock, *Biofuels, Bioproducts and Biorefining*, 2 (2008) 530-539.
- [18] Kort J, Collins M, Ditsch D, A review of soil erosion potential associated with biomass crops, *Biomass and Bioenergy*, 14 (1998) 351-359.
- [19] Monti A, Barbanti L, Zatta A, Zegada-Lizarazu W, The contribution of switchgrass in reducing GHG emissions, *GCB Bioenergy*, 4 (2012) 420-434.
- [20] Monti A, Fazio S, Venturi G, Cradle-to-farm gate life cycle assessment in perennial energy crops, *European Journal of Agronomy*, 31 (2009) 77-84.
- [21] Ziolkowska JR, Evaluating sustainability of biofuels feedstocks: A multi-objective framework for supporting decision making, *Biomass and Bioenergy*, 59 (2013) 425-440.
- [22] Khanna M, Dhungana B, Clifton-Brown J, Costs of producing miscanthus and switchgrass for bioenergy in Illinois, *Biomass and Bioenergy*, 32 (2008) 482-493.
- [23] Wesseler J, Opportunities ('costs) matter: A comment on Pimentel and Patzek "Ethanol production using corn, switchgrass, and wood; biodiesel production using soybean and sunflower", *Energy Policy*, 35 (2007) 1414-1416.
- [24] Pimentel D, Patzek TW, Ethanol Production Using Corn, Switchgrass, and Wood; Biodiesel Production Using Soybean and Sunflower, *Natural Resources Research*, 14 (2005) 65-76.
- [25] Yu TE, He L, English BC, Larson JA, GIS-based optimization for advanced biofuels supply chains: a case study in Tennessee, *Lecture Notes in Management Science*, 6 (2014) 217-227.
- [26] Zhang J, Osmani A, Awudu I, Gonela V, An integrated optimization model for switchgrass-based bioethanol supply chain, *Applied Energy*, 102 (2013) 1205-1217.
- [27] Sokhansanj S, Kumar A, Turhollow A, Development and implementation of integrated biomass supply analysis and logistics model (IBSAL), *Biomass and Bioenergy*, 30 (2006) 838-847.
- [28] Bernardi A, Giarola S, Bezzo F, Optimizing the economics and the carbon and water footprints of bioethanol supply chains, *Biofuel Bioprod Bior*, 6 (2012) 656-672.
- [29] Parish ES, Hilliard MR, Baskaran LM, Dale VH, Griffiths NA, Mulholland PJ, Sorokine A, Thomas NA, Downing ME, Middleton RS, Multimetric spatial optimization of switchgrass plantings across a watershed, *Biofuel Bioprod Bior*, 6 (2012) 58-72.

533 [30] Nixon, J.D., P.K. Dey, P.A. Davies, S. Sagi, and R.F. Berry. Supply chain optimisation of
534 pyrolysis plant deployment using goal programming, *Energy*, 68 (2014) 262-271.

535 [31] You F, Tao L, Graziano DJ, Snyder SW, Optimal design of sustainable cellulosic biofuel
536 supply chains: Multiobjective optimization coupled with life cycle assessment and input-output
537 analysis, *AIChE Journal*, 58 (2012) 1157-1180.

538 [32] Yu TE, Wang Z, English BC, Larson JA, Designing a dedicated energy crop supply system
539 in Tennessee: a multiobjective optimization analysis, *Journal of Agricultural and Applied
540 Economics*, 46 (2014) 357-373.

541 [33] Chan Y, *Economic Methods of Analysis*, in: *Location Theory and Decision Analysis*,
542 Springer Berlin Heidelberg, 2011, pp. 17-82.

543 [34] Jäppinen E, Korpinen OJ, Ranta T, Effects of Local Biomass Availability and Road
544 Network Properties on the Greenhouse Gas Emissions of Biomass Supply Chain, *ISRN
545 Renewable Energy*, 2011 (2011) 1-6.

546 [35] Egbendewe-Mondzozo A, Swinton SM, Izaurrealde CR, Manowitz DH, Zhang X, Biomass
547 supply from alternative cellulosic crops and crop residues: A spatially explicit bioeconomic
548 modeling approach, *Biomass and Bioenergy*, 35 (2011) 4636-4647.

549 [36] Jager HI, Baskaran LM, Brandt CC, Davis EB, Gunderson CA, Wulschleger SD, Empirical
550 geographic modeling of switchgrass yields in the United States, *GCB Bioenergy*, 2 (2010) 248-
551 257.

552 [37] Wang M, Saricks C, Santini D, Effects of fuel ethanol use on fuel-cycle energy and
553 greenhouse gas emissions, (1999) Available at:
554 <http://www.transportation.anl.gov/pdfs/TA/58.pdf>.

555 [38] Tennessee Valley Authority Economic Development, *Economic Development Sites and
556 Buildings*, (2011) Available at:
557 <http://www.tvasites.com/InSite.aspx?searchArea=FeaturedProperties>.

558 [39] Reeves GR, Reid RC, Minimum values over the efficient set in multiple objective decision
559 making, *European Journal of Operational Research*, 36 (1988) 334-338.

560 [40] Mavrotas G, Florios K, An improved version of the augmented ϵ -constraint method
561 (AUGMECON2) for finding the exact pareto set in multi-objective integer programming
562 problems, *Applied Mathematics and Computation*, 219 (2013) 9652-9669.

563 [41] Ramos TRP, Gomes MI, Barbosa-Póvoa AP, Planning a sustainable reverse logistics
564 system: Balancing costs with environmental and social concerns, *Omega*, 48 (2014) 60-74.

565 [42] Larson JA, Yu TE, English BC, Jensen KL, Gao Y, Wang C, Effect of outdoor storage
566 losses on feedstock inventory management and plant-gate cost for a switchgrass conversion
567 facility in East Tennessee, *Renewable Energy*, 74 (2015) 803-814.

568 [43] Duffy M, *Estimated Costs for Production, Storage and Transportation of Switchgrass*,
569 (2007) Available at: http://www2.econ.iastate.edu/research/webpapers/paper_12917.pdf.

- [44] Wischmeier WH, Smith DD, Predicting rainfall erosion losses--a guide to conservation planning, Supersedes Agriculture Handbook No. 282, (1978) Available at: http://www.ars.usda.gov/SP2UserFiles/ad_hoc/36021500USLEDatabase/AH_537.pdf.
- [45] Renard KG, Foster GR, Weesies GA, McCool DK, Yoder DC, Predicting soil erosion by water: a guide to conservation planning with the revised universal soil loss equation, (1997) Available at: http://www.ars.usda.gov/SP2UserFiles/Place/64080530/RUSLE/AH_703.pdf.
- [46] Kokkinidis I, Ecosystem Services Provided by Agricultural Land as Modeled by Broad Scale Geospatial Analysis, in, Virginia Polytechnic Institute and State University, 2014.
- [47] United States Department of Agriculture, Web Soil Survey, (2013) Available at: <http://websoilsurvey.nrcs.usda.gov/>.
- [48] U.S. Department of Agriculture Natural Resources Conservation Service, National Soil Survey Handbook, (2014) Available at: http://www.nrcs.usda.gov/wps/portal/nrcs/detail/soils/survey/?cid=nrcs142p2_054242.
- [49] Olson DL, Tchebycheff norms in multi-objective linear programming, Mathematical and Computer Modelling, 17 (1993) 113-124.
- [50] Clemen RT, Reilly T, Making hard decisions with DecisionTools Suite, (1999).
- [51] Schimel DS, Carbon and nitrogen turnover in adjacent grassland and cropland ecosystems, Biogeochemistry, 2 (1986) 345-357.
- [52] Aalde H, Gonzalez P, Gytarsky M, Krug T, Kurz WA, Lasco RD, Martino DL, G. B, McConkey, Ogle S, Paustian K, Raison J, Ravindranath NH, Schoene D, Smith P, Somogyi Z, van A, Amstel, Verchot L, Generic methodologies applicable to multiple landuse categories, in: S. Eggleston, L. Buendia, K. Miwa, T. Ngara, K. Tanabe (Eds.) IPCC Guidelines for National Greenhouse Gas Inventories, IGES, Japan, 2006.
- [53] Argonne National Laboratory, The Greenhouse Gases, Regulated Emissions, and Energy Use in Transportation Model (GREET), (2013) Available at: <http://www.transportation.anl.gov/publications/index.html>.
- [54] U.S. EPA, Motor Vehicle Emission Simulator (MOVES) model, (2013).
- [55] Cherubini F, Jungmeier G, LCA of a biorefinery concept producing bioethanol, bioenergy, and chemicals from switchgrass, The International Journal of Life Cycle Assessment, 15 (2009) 53-66.
- [56] U.S. Department of Agriculture Nature Resources Conservation Service, Soil Survey Geographical Database (SSURGO), (2012) Available at: <http://soils.usda.gov/survey/geography/ssurgo/>.
- [57] U.S. Department of Agriculture NASS, CropScape – Cropland Data Layer Database, (2011) Available at: <http://nassgeodata.gmu.edu/CropScape>.
- [58] U.S. Department of Agriculture NASS, Crop Values Annual Summary, (2014) Available at: <http://usda.mannlib.cornell.edu/MannUsda/viewDocumentInfo.do?documentID=1050>

- [59] De La Torre Ugarte DG, Ray DE, Biomass and bioenergy applications of the POLYSYS modeling framework Paper prepared for presentation at the Modeling Tools for Biomass and Bioenergy Conference, 8–10 April 1997 Knoxville, TN, Biomass and Bioenergy, 18 (2000) 291-308.
- [60] Larson JA, Yu TE, English BC, Mooney DF, Wang C, Cost evaluation of alternative switchgrass producing, harvesting, storing, and transporting systems and their logistics in the Southeastern USA, Agricultural Finance Review, 70 (2010) 184-200.
- [61] University of Tennessee, Field crop budgets, (2015) Available at: <http://economics.ag.utk.edu/budgets.html>.
- [62] Schimel DS, Ojima DS, Hartman MD, Parton WJ, Brenner J, Mosier AR, Grosso SJD, Simulated Interaction of Carbon Dynamics and Nitrogen Trace Gas Fluxes Using the DAYCENT Model, in: S. Hansen, M.J. Shaffer, L. Ma (Eds.) Modeling Carbon and Nitrogen Dynamics for Soil Management, CRC Press, 2001.
- [63] Fribourg HA, Loveland RW, Seasonal Production, Perline Content, and Quality of Fescue After N Fertilization1, Agronomy Journal, 70 (1978) 741.
- [64] Bowling RG, McKinley TL, Rawls EL, Tennessee Forage Budgets, UT extension, (2006) 23 Available at: <http://economics.ag.utk.edu/budgets/PB1658ForageBudgets07.pdf>.
- [65] Muir JP, Sanderson MA, Ocumpaugh WR, Jones RM, Reed RL, Biomass Production of ‘Alamo’ Switchgrass in Response to Nitrogen, Phosphorus, and Row Spacing, Agronomy Journal, 93 (2001) 896.
- [66] Mitsova H, Hofierka J, Zlocha M, Iverson LR, Modelling topographic potential for erosion and deposition using GIS, International Journal of Geographical Information Systems, 10 (1996) 629-641.
- [67] Mitsova H, Brown WM, Hohmann M, Warren S, Using Soil Erosion Modeling for Improved Conservation Planning: A GIS-based Tutorial, (2001) Available at: <http://www4.ncsu.edu/~hmitaso/gmslab/reports/Cer1ErosionTutorial/denix/denixstart.html>.
- [68] American Agricultural Economics Association, Commodity Cost and Returns Handbook, in, Ames, IA, 2000.
- [69] American Society of Agricultural and Biological Engineers, Agricultural Machinery Standards, in, St. Joseph, MI, 2006.

Table 1 Definitions of Subscripts, Parameters and Variables

	Unit	Definition
Subscripts		
<i>i</i>		Land resource units
<i>j</i>		Industrial park sites for conversion facility
<i>m</i>		Month
<i>p</i>		Type of crop land (hay and pasture, corn, soybean, wheat, sorghum, cotton)
<i>k</i>		Type of machinery (tractor, mower, loader, rake, baler)
Parameters		
<i>Price</i>	\$ Mg ⁻¹	Crop prices
<i>Yield</i>	Mg ha ⁻¹	Crop yields
<i>PC</i>	\$ ha ⁻¹	Crop production costs
<i>Yield</i>	Mg ha ⁻¹	Switchgrass yields
<i>LR</i>	\$ Mg ha ⁻¹	Land rent
<i>Est</i>	\$ ha ⁻¹	Switchgrass establishment cost
<i>AM</i>	\$ ha ⁻¹	Annual maintenance cost
σ	\$ ha ⁻¹	Cost of harvesting switchgrass
γ	\$ ha ⁻¹	Cost per unit of storing switchgrass
θ	\$ ha ⁻¹	Cost per unit of transporting switchgrass
<i>DML</i>	%	Dry matter loss during transportation
<i>Aa</i>	ha	Crop land available in each land resource unit
<i>Avehour</i>	Hour	Average working hours of machinery in each month
<i>DML</i>	%	Dry matter loss during storage
<i>MTB</i>	hours ha ⁻¹	Machine time ha ⁻¹ for each machinery
Λ	L Mg ⁻¹	Switchgrass-ethanol conversional rate
<i>Q</i>	L month ⁻¹	Monthly demand for ethanol
$\Delta LUCO_2$	CO ₂ e kg ha ⁻¹	CO ₂ emission from land conversion
$\Delta LUCH_4$	CO ₂ e kg ha ⁻¹	CH ₄ emission from land conversion
ΔLUN_2O	CO ₂ e kg ha ⁻¹	N ₂ O emission from land conversion
<i>ProE</i>	CO ₂ e kg ha ⁻¹	GHG emissions factor from energy use during Switchgrass production
<i>HarE</i>	CO ₂ e kg ha ⁻¹	GHG emissions factor from energy usage during harvest
<i>StorE</i>	CO ₂ e kg ha ⁻¹	GHG emissions factor from energy usage during storage
<i>MachE</i>	CO ₂ e kg unit ⁻¹	GHG emissions factor from machinery production
<i>TransE</i>	CO ₂ e kg route ⁻¹	GHG emissions from energy usage during transportation
<i>Loadwt</i>	Mg truck ⁻¹	Switchgrass delivered per truck
<i>FertE</i>	CO ₂ e kg Mg ⁻¹	GHG emissions factor from fertilizer production
<i>ChemE</i>	CO ₂ e kg Mg ⁻¹	GHG emissions factor from chemical production
<i>SeedE</i>	CO ₂ e kg Mg ⁻¹	GHG emissions factor from seed production
<i>U</i>		Upper bound values for certain objective
<i>L</i>		Lower bound values for certain objective
<i>R</i>		Range of certain objective
Variables		
<i>AH</i>	ha	Area of switchgrass harvested
<i>XTN</i>	Mg	Switchgrass transported directly to the biorefinery
<i>NXE</i>	Mg	Switchgrass stored during harvest season
<i>XE</i>	Mg	Cumulative switchgrass storage
<i>XTO</i>	Mg	Switchgrass transported from storage to the biorefinery
<i>NM</i>	Unit	Number of equipment used for harvest

Table 2 Data sources

	Economic Cost	GHG Emissions	Soil Erosion
Land conversion from crop land to switchgrass	<p>Opportunity cost: Crop yields: USDA SSURGO [56]; Crop price and hectares: USDA NASS [57, 58]; Crop production cost: USDA ERS [58], POLYSIS [59] Switchgrass plantation: Yield: Jager et al. [36]; Production and harvest Cost: Larson, et al. [60], University of Tennessee [61]</p>	<p>Land use change (Daycent [62]): Weather data: DayMET¹; Soil texture: USDA SSURGO³ [56] Management practice for crops: University of Tennessee [61] Hay/pasture management: [63, 64] Switchgrass management: [65]</p>	<p>R factor: USDA RUSLE2² K factor: USDA SSURGO [56] C factor: USDA RUSLE2, [64,65] P factor: [64] LS factor: Drained area method [66, 67].</p>
Production	<p>Establishment: American Agricultural Economics Association [68] Annual maintenance: American Society of Agricultural and Biological Engineers [69]</p>	<p>Fuel usage: GREET [53] Fertilizer, herbicide, seed: GREET [53] Machine production: GREET [53]</p>	
Harvest	<p>Fuels and labors: University of Tennessee [61]</p>	<p>Fuel: GREET [53] Machine production: GREET [53]</p>	
Storage	<p>Covers and pallets: University of Tennessee [61]</p>		
Transportation	<p>Trailer, fuel and labor: University of Tennessee [61]</p>	<p>MOVES modeling [54]; Indirect emission from truck production: GREET [53]</p>	

¹ <http://daymet.ornl.gov/>

² RUSLE2 model website: http://fargo.nserl.purdue.edu/rusle2_dataweb/RUSLE2_Index.htm

³ SSURGO database: http://www.nrcs.usda.gov/wps/portal/nrcs/detail/soils/survey/geo/?cid=nrcs142p2_053627

Table 3 Output summary for the single objective solutions and the compromise solution

	Feedstock cost minimization (A)	GHG emissions minimization (B)	Soil erosion minimization (C)	Compromise solution (O)
Cost item	\$ (millions)			
Opportunity cost	1.334	15.697	35.628	22.056
Production cost	8.606	8.773	8.572	8.617
Harvest cost	22.395	22.613	22.351	22.409
Storage cost	2.775	2.775	2.775	2.775
Transportation cost	8.307	10.607	16.081	14.881
Total cost	43.417	60.466	85.408	70.738
	Mg (thousand)			
Total GHG emissions	44.887	18.587	29.689	32.844
	Mg (million)			
Total soil erosion	-0.106	-3.545	-7.646	-7.495

Figure 1 System boundary of switchgrass supply chain: field to conversion facility

Figure 2 Potential switchgrass supply area and industrial park sites for conversion facilities

Note: Crop ratio is the ratio of crop land to hay and pasture lands.

3-i: Solution projection on each coordinator panel for one conversion facility site

3-ii: Solution projection on each coordinator panel

3-iii: efficient frontier embracing feasible points

Figure 3 Regional feasible solutions (A: total cost minimization, B:GHG emission minimization, C: soil erosion minimization, O: compromise solution)

4-i: Total feedstock cost minimization (A)

4-ii: GHG emission minimization (B)

4-iii: Soil erosion minimization (C)

Figure 4 Distance scores and objective values for the 40 conversion facility sites on the efficient frontier.

5-i: Individual optima for total cost minimization (A)

5-ii: Individual optima for GHG emission minimization (B)

5-iii: Individual optima for soil erosion minimization (C)

5-iv: Compromise solution (O)

Figure 5 Placement of the conversion facility and switchgrass draw area under individual-optima and compromise solution cases

Figure 6 Land area converted to switchgrass for each optimization case (A: total cost minimization, B: GHG emission minimization, C: soil erosion minimization, O: compromise solution)

Figure 7 Changes in soil erosion within the feedstock draw area before and after the land was converted to switchgrass (A: total cost minimization, B: GHG emission minimization, C: soil erosion minimization, O: compromise solution)