1 Particulate and Trace Gas Emissions from Prescribed Burns in Southeastern U.S. Fuel Types:
2 Summary of a 5-year Project¹
3

4 David R. Weise^a, Timothy J. Johnson^b, James Reardon^c
5

6 ^aUSDA Forest Service, Pacific Southwest Research Station, 4955 Canyon Crest Drive, Riverside,
7 California, USA 92507, dweise@fs.fed.us, (951) 680-1543 (corresponding author)

8 ^bPacific Northwest National Laboratory, 902 Battelle Boulevard, P.O. Box 999, MSIN K3-61,
9 Richland, Washington, USA 99352, timothy.johnson@pnnl.gov, (509) 372-6058

10 ^cUSDA Forest Service, Rocky Mountain Research Station, 5775 W US Highway 10, Missoula,
11 Montana, USA 59808, jreardon@fs.fed.us, (406) 329-4849
12
13

¹ This manuscript was prepared, in part, by U.S. Government employees on official time, is not subject to copyright and is in the public domain.

Abstract

Management of smoke from prescribed fires requires knowledge of fuel quantity and the amount and composition of the smoke produced by the fire to minimize adverse impacts on human health. A five-year study produced new emissions information for more than 100 trace gases and particulate matter in smoke for fuel types found in the southern United States of America using state-of-the-art instrumentation in both laboratory and field experiments. Emission factors for flaming, smoldering, and residual smoldering were developed. Agreement between laboratory and field-derived emission factors was generally good in most cases. Reference spectra of over 50 wildland fire gas-phase smoke components were added to a publicly-available database to support identification via infrared spectroscopy. Fuel loading for the field experiments was similar to previously measured fuels. This article summarizes the results of a five-year study to better understand the composition of smoke during all phases of burning for such forests.

1 Introduction

Prescribed burning is an accepted practice to manage biomass in the United States and throughout the world [e.g. 1]. It is a particularly important practice in pine and eucalyptus forests, many of which have evolved in the presence of fire [2,3]. A recent survey [4] reported that 2.62×10^6 ha of pine forest land in the southeastern U.S. (defined by the National Association of State Foresters) burned under prescribed conditions in 2011 for silvicultural purposes such as hazardous fuel reduction, wildlife habitat improvement, and forest regeneration. The survey reported 8.2×10^6 ha of forestry and agricultural lands burned by prescription in the conterminous U.S.; in the same year, wildfire burned 3.5×10^6 ha in the U.S. [5]. In 2004, estimated burned area worldwide was 3.2×10^8 ha of which temperate and boreal North America comprise approximately one percent [6]. The impact of emissions from prescribed burning worldwide are similarly a small percentage of total estimated biomass burning emissions [7,8]; however, these emissions are regulated in many areas because they are planned.

Smoke is thus an important consequence of prescribed burning that must be managed [9]. A great deal of research has been performed since the 1970s characterizing the composition, production, and transport of smoke from such fires [e.g. 9,10–13]. A recent review of the state of science behind estimation of the contribution of wildland fire to greenhouse gases and black carbon in the U.S. identified several areas of research that must be performed [14]. In particular, two areas of knowledge that still need improvement are i) fuel characterization and smoke emissions, and ii) the correlation(s) between the two [14 and the accompanying papers]. This conclusion is likely true for many vegetation types throughout the world even though most experiments conducted over the past 30 years have been in the tropics and boreal forests. While many fuel types in the southeastern U.S. have been described for fire behavior and fire danger prediction [e.g. 15,16–18], characterization of fuel bed components important for smoke production is more limited. Emissions characterization for both gases and particles is needed to determine potential impacts of prescribed burning on nutrient cycling, atmospheric albedo, human health, and visibility [e.g. 13,19,20]. The southern U.S. was one of the first regions of the country to examine the impact of prescribed burning on air quality in both the laboratory and in the field [9,21]; recent advances in measurement devices provided an opportunity to improve knowledge of emissions using state-of the art instrumentation capable of real-time and *in situ* emissions measurements. Coupling well-controlled laboratory experiments using complex fuel beds with field measurements to determine applicability of laboratory results to actual conditions has seldom been accomplished.

The U.S. Department of Defense (DOD) manages much of its land in the southeastern U.S. to provide a wide range of ecological and economic benefits using ecological forestry [22]. Much of this land was historically dominated by a longleaf pine (*Pinus palustris* Mill.) forest maintained by frequent, natural, growing season fires [23]. Historically longleaf pine grew on approximately 3.7×10^7 ha and now occurs on less than three percent of its former range making it an ecosystem of concern [24,25] (see light gray area in Figure 1). Other southern pines (*P. taeda* L., *P. elliotii* Engelm., *P. serotina* Michx., *P. clausa* (Chapm. ex Engelm.) Vasey ex Sarg.) grow in this same

range and rely on fire as well to maintain site dominance through light and resource competition control [2,26]. Removal of fire from these ecosystems results in encroachment by hardwood trees and shrubs that threatens endangered species and limits military training [27]. Fuel accumulates in these forests faster than in other parts of the U.S. due to favorable growing conditions. As a consequence, as few as 4 to 6 fire-free years can cause a major fuel buildup making wildfires more difficult to control, and more damaging to the pine overstory when they do occur. The long-term impacts of such a change in the use of prescribed fire are currently unknown and a complex function of many factors [14,28]. Longleaf pine grows in close proximity to many wetland areas which are also subject to wildland fire [26]. Pocosin is a dense shrub/pine ecosystem found in wetlands on deep organic soils that is extremely flammable during drought and often features intense fire behavior that can be problematic to suppress. Similar shrub-dominated ecosystems produce comparable fire behavior throughout the world [29]. Heavy smoke resulting from smoldering in the deep organic soils can be injurious to human health [e.g. 30,31]. Some areas with pocosin fuels and deep organic soils are managed by the U.S. Department of Defense, [32–34] such as the Dare County Range seen in Figure 1.

In 2008 the Strategic Environmental Research and Development Program (SERDP) initiated a program to characterize the fuels, smoke chemistry and transport associated with prescribed burning on DOD bases in the U.S. Three related projects were completed and final reports are now available [35–37]. Detailed measurements of gaseous and particulate emissions were made in laboratory and field experiments. Here we summarize the work that has accurately measured the emissions of particles and numerous gases for the wildland fuels commonly found in the coastal plain and sand hills regions of the southeastern U.S. [26]. The many detailed results of these studies have largely been published in the refereed literature and are all contained in the final report [37]; this manuscript attempts to summarize the entire project in a succinct fashion, and in particular attempts to provide some key findings for scientists and users in the southern U.S. The results are also potentially applicable to many other similar pine and shrub-dominated ecosystems throughout

the world. Emphasis is placed on the emission factors (EFs) derived for fires occurring in such ecosystems, as well as the relationships between the laboratory- and field-derived EFs.

2 Methodology

The project consisted of three components: 1) a laboratory effort to derive the infrared spectral absorption coefficients of those gases contained in smoke from wildland fires and thus expand and improve the detection capability of infrared-based gas sampling instruments, 2) detailed measurements of both gaseous and particulate emissions from burning fuel beds in a large combustion laboratory, and importantly, 3) detailed ground and aerial measurement of gaseous and particulate emissions from operational prescribed burns at Camp Lejeune in North Carolina (coastal plain) and Fort Jackson in South Carolina (sand hills) (Table 1, Table 2).

2.1 Improved Infrared Instrumentation and Spectral Database

A useful technique for the measurement of gas-phase emissions from wildland fires is Fourier transform infrared [FTIR] spectroscopy. Compared to visible light, smoke is far more transparent to infrared light due to reduced Mie scattering at the longer IR wavelengths. Other advantages of FTIR include a nonintrusive measurement of a variety of flaming and smoldering compounds over an integrated path through the same air parcel. The unique spectral absorption features of the gaseous species measured means the technique is resistant to interference and can provide (with appropriate IR reference data) unambiguous compound identification. Moreover, FTIR has high temporal resolution for monitoring of dynamic processes related to emissions of biomass fires [22]. FTIR spectroscopy also provides the possibility to simultaneously measure a wide range of chemical species in smoke with good sensitivity (parts per billion levels in some cases) and high temporal resolution (1-2 sec).

The FTIR instrument used in the laboratory burns was improved by replacing the original Midac FTIR interferometer [38] with a Bruker IRcube spectrometer. The original Infrared Analysis, Inc. open-path White cell [39] was not changed. The improved Bruker IR Cube FTIR was later coupled to a closed-path White cell for the airborne measurements in 2011; the original Midac instrument

was used for the airborne measurements in 2010 (see 2.3). Besides the FTIRs, a wide variety of instruments was used in the project to describe characteristics of the gas-phase and particulate emissions from the laboratory and field fires. These fires also provided the opportunity to compare performance of different instruments, techniques [40,41] and performance of the same type of instrument at different sampling locations [42].

The PNNL infrared spectral library [43,44] was originally developed for other purposes, and formerly contained about 400 compounds, of which perhaps 50 were associated with biomass burning. For this project, four criteria were used to select additional chemical species whose spectra should be added to the library: 1) the species had been measured in smoke by non-IR methods or was expected to occur based on known chemistry, 2) the species was expected to have reasonably strong IR absorption features in the 1,300 to 700 cm^{-1} fingerprint region thus eliminating species such as Br_2 or elemental Hg, 3) the species had a vapor pressure $> \sim 0.01$ Torr or a boiling point of < 250 to 300°C , so that it was both amenable to laboratory measurement and would not immediately condense in a cooling smoke plume and 4) the species must be sufficiently stable in an N_2 bath gas in the laboratory (for minutes to hours) so the measurement could actually be completed. Using vetted database protocols [43,44] several dozen species were added to the spectral library as discussed below (3.1).

2.2 Laboratory Measurement of Emissions

In the laboratory component, fuels representative of vegetation commonly managed by prescribed burning were collected and burned under controlled conditions at the U.S. Forest Service (USFS) Fire Sciences Laboratory (FSL) in Missoula, Montana. The fuels were burned under constant environmental conditions using techniques to promote near total consumption of the fuel under a chimney hood that captured all of the emissions produced. The emissions from these laboratory burns were analyzed with a suite of state-of-the-art instrumentation too large for collective field deployment on operational prescribed burns [37]. Seldom, if ever, has such a suite of instruments been assembled to measure biomass emissions.

At the FSL, gas-phase measurements were performed by (1) an open-path Fourier transform infrared (OP-FTIR) instrument described previously [section 2.1], (2) two proton-transfer- reaction mass spectrometers (PTR-MS) for measurement of non-methane organic compounds (NMOC), (3) proton-transfer ion trap-mass spectrometry (PIT-MS) for NMOC, (4) negative-ion proton-transfer chemical-ionization mass spectrometry (NI-PT-CIMS) for detection of organic and inorganic acids, (5) gas chromatography mass spectrometry (GC-MS) for NMOC, (6) canister sampling followed with analysis by gas chromatography flame ionization detection (GC-FID) for low molecular weight hydrocarbons, (7) a LICOR CO₂ analyzer, and (8) TECO CO analyzer. Due to platform space and load restrictions, one PTR-MS and the GC-MS were housed in a control room adjacent to the combustion chamber and connected to the stack via a long Teflon sampling line. Together these instruments provided measurements of approximately 120 gas-phase components.

To characterize the particle emissions, several instruments located on the platform measured size distributions, particle number, mass, and chemical composition. Instrumentation included (9) an High Resolution Time of Flight Aerosol Mass Spectrometer (HR-TOF-AMS), (10) an Ultrafine Condensation Particle Counter (11) a Scanning Mobility Particle Sizer (SMPS), (12) a Fast Mobility Particle Sizer, (13) an Aerodynamic Particle Sizer (14) a Micro-Orifice Uniform Deposit Impactor (MOUDI), and (15) a Mass Monitor (DMM) [40,41,45,46]. Particulate matter was collected on glass and Teflon filters and subjected to a variety of offline measurements and analyses for elemental and organic carbon, elemental composition by X-ray fluorescence, ion chromatography analysis, levoglucosan and polycyclic aromatic hydrocarbons [41].

A total of 21 fuel beds representing six southeastern fuel types and 56 fuel beds representing eight southwestern U.S. fuel types were burned and measured using this suite of instruments [41,47].

Three or four replications of fuel beds from Camp Lejeune (five fuel types) and five fuel beds of pine needles from Fort Benning were burned. Unburned residue was weighed at the end of each fire to determine consumption; however, some fires were extinguished after sampling was completed before all fuel was consumed in order to keep to the burning schedule.

2.3 Field Measurement of Emissions

The field component of the project consisted of deployments to Camp Lejeune (February/March 2010) and Fort Jackson (October/November 2011). Prescribed burns at the two locations ranged from 30 to 677 ha. Each burn contained one or more of the fuel types from the laboratory phase as well as additional types. The fuel types at Camp Lejeune represent fuels associated with frequent prescribed burning (every 1-3 years) which is the typical application in the coastal plain [1]. In response to managers' concerns, the fuel types at Fort Jackson were added to represent hazardous fuel accumulations resulting from no prescribed fire use on certain parcels.

Fort Jackson is in the Sandhills region, a band of ancient beach dunes separating the coastal plain from the Piedmont [26] (Figure 1); the longleaf pine forests are distinctly different from Camp Lejeune. Fort Jackson plots were specifically selected to include stands with significant understory growth, i.e. little or no recent prescribed burn history. One plot had not burned since 2003 and the other two plots had not been burned in at least 50 years. The older stand conditions at Fort Jackson, to some extent, serve as a living model of the fuel conditions expected if prescribed fire programs become further restricted across the southern United States. Burning during the relatively dry fall season was chosen to emulate weather conditions that might occur during higher intensity wildland fires to determine if there was an effect on emissions; however, fuel and weather conditions were such that this was not achieved. Our ability to estimate fire intensity from fuel consumption was severely limited. Anecdotal ocular estimates of flame length are the best measure of fire intensity that we have for these burns.

Airborne measurements [48,49] used a closed-cell FTIR instrument to collect and measure gases, a nephelometer measured light scattering which was correlated with particulate mass ($PM_{2.5}$) or other particulate sampling instruments. At some of the burns, whole air samples were also collected and analyzed [48]. At Camp Lejeune and Fort Jackson, a closed-cell Land based FTIR (the LaFTIR), based on the original unmodified spectrometer (MIDAC 2500) and detector (Graseby FTIR-M16) coupled with a smaller, vibration-isolated multipass Infrared Analysis, Inc. White cell, was used to

estimate the composition of smoke emissions from residual smoldering combustion (RSC) of large woody fuels such as stumps and logs. RSC occurs frequently and in general refers to the smoke that is produced after the flame front has passed. This unlofted smoke is often associated with reduced highway visibility [20]. In addition to the LaFTIR closed cell instrument, at Fort Jackson a Bruker OPAG-22 OP-FTIR was set up at a fixed location for each burn, typically along a fuel break on the perimeter. The OP-FTIR sampled a mixture of both flaming and smoldering phase smoke as described below [42].

The comparison of emissions measured by various methods has been limited. In particular there are few papers which compare laboratory versus field measurements, and few that contrast airborne versus ground-based sampling [38,48,50,51]. Ground-based emission measurements have been related to airborne measurements and modified combustion efficiency (MCE) has been used as the metric to correlate emissions from fires over several orders of size [52]. The design of the overall project allowed us to examine the relationship between emission factors derived from the laboratory phase with emission factors developed for similar fuel types in the field phase [51]. Ground-based smoke emissions and airborne emissions measured using the same type of instrument were compared. Using MCE to indicate fire phase, we compared agreement between laboratory and field-derived emission factors for similar fire phases (flaming, ixed, smoldering). The flaming phase is generally characterized by more complete oxidation and higher MCE values whereas the smoldering phase is characterized by less complete oxidation and lower MCE values. The data from the controlled laboratory burns were synthesized with the actual field measurements [51]. While we did not include organic soils specifically collected in eastern North Carolina as a fuel type, organic soils from other locations were included in the laboratory phase and the results are potentially applicable to fires arising in the pocosin type which grows on organic soils [32]. Emissions from organic soil from eastern North Carolina and duff, partially decomposed forest litter material from longleaf pine [53], were compared with our ground-based LaFTIR results by converting emission ratios to emission factors using carbon mass balance [54,55].

3 Results and Discussion

To date, results from this project have been published in a variety of journals [40–42,45–49,51,56–68] and most of the papers concentrate on either the laboratory or the field experiments. An archived database containing emission factors gleaned from five decades of literature as well as the emission factors derived from this work was also compiled and later made available [69]. A brief description and discussion related to the fuel types in the project is presented prior to presentation of the results related to all three components of the project.

The fuels from Camp Lejeune used in the laboratory experiments consisted principally of five species of hardwood shrubs and small trees that grow in the southeastern Atlantic coastal plain: red maple (*Acer rubrum* L.)², redbay (*Persea borbonia* (L.) Spreng.), loblolly bay (*Gordonia lasianthus* (L.) Ellis), inkberry (*Ilex glabra* (Pursh) Chapm.), and fetterbush (*Lyonia lucida* (Lam.) K. Koch) [47]. Calculated bulk density of the various laboratory fuel beds differed by an order of magnitude between the five fuel types (Table 3). The loading for the 1- and 2-year rough fuel types fell within the range of published loadings for 1- and 2-year roughs under longleaf pine [16]. Loading of the pocosin fuel type, seldom sampled to determine fuel mass and structure [16,32,33], also fell within the range of reported loading for high pocosin and high brush fuel as did the understory hardwood fuel type (Table 3). Loading for the chipped understory hardwood (cuh) fuel type was similar to [17] depending on which 10 hr fuel loading is used and within the range of the experimental fuel beds used by [70]. The understory hardwood (uh) fuel loading fell within the range of previously reported results; however, the bulk density of the laboratory fuel beds was much higher than the field fuel beds (Table 3) due to difference in depth between the reconstructed laboratory fuel beds and the naturally occurring fuel beds. The range of fuel loading in the litter fuel beds (lit) fell within the range of reported fuel loading for slash and loblolly pine [9].

² Source of binomial nomenclature is USDA, NRCS. 2014. The PLANTS Database (<http://plants.usda.gov>, 20 May 2014). National Plant Data Team, Greensboro, NC 27401-4901 USA

Access to the field sites prior to the prescribed burns was severely limited due to ongoing military training activities. The February 2010 burn (IA) at Lejeune occurred in a two year rough of inkberry and fetterbush. The March 2010 burn (ME) included masticated fuels, resprouted fetterbush shrubs and understory hardwoods including red maple and sweetgum (*Liquidambar styraciflua*), an untreated moderate density understory of redbay, red maple, inkberry, and fetterbush, and an area of one-two year rough of fetterbush and swamp titi (*Cyrilla racemiflora* L.) with grasses. Understory fuels at Fort Jackson included farkleberry (*Vaccinium arboreum* Marshall) and longleaf pine needles. Limited fuel sampling occurred at Fort Jackson to estimate pre-burn mass per unit area and fuel mass consumed. With the exception of the IA burn at Camp Lejuene, estimated fuel consumption of the field burns was generally the same order of magnitude as the laboratory burns (Table 3). Further comparison of fuel consumption measurements was not possible.

3.1 Instrument, Software and Spectral Database Improvements

Inclusion of new hardware components of the FTIR spectrometer and gas cell installed at the Missoula Fire Sciences Laboratory (FSL) significantly improved detection capabilities for most chemical species [37]. This same spectrometer was subsequently reconfigured and deployed in the aircraft as a closed-cell system. The initial signal-to-noise ratio (SNR) reported for the original FTIR instrument was ~100 for the spectra examined [38]. In 2004 the SNR of the FTIR instrument was roughly 500, but this was increased to over 30,000 during the course of the project via improvements to the hardware, in particular interfacing a better infrared spectrometer. The increased sensitivity permitted FTIR detection of numerous new species in real-time such as HONO, glyoxal and glycolaldehyde [59,61,66].

The improved evaluation software [71] processed the data collected by the various FTIRs using a variety of analyses to isolate the individual spectra for chemical species. As a test of the changes to the improved software, the reference spectra developed by PNNL were evaluated. For eight of the nine chemical species used, the estimated variability in derived concentration was within 1-2% of

the observed, which is less than the error associated with the IR intensity values as measured in the PNNL laboratory.

In terms of potential new vapor-phase species that could be analyzed via FTIR, the proposed chemicals identified using the four criteria described in section 2 initially numbered ~50. The spectra of 53 chemicals were added to the PNNL spectral library (Table 4). We note that these spectra can be used with any IR spectrometer so, for example, they could potentially be used by space-based instruments [e.g. 72] to measure smoke emissions in addition to the ground and aircraft-based platforms described here. All the infrared reference data derived from this project are now publicly available at nwir.pnl.gov. While many of these new gases have been detected in wildland smoke using techniques such as GS-MS and the spectra now exist, many of them fell below the detection limits of the improved FTIRs were used in both the laboratory and field measurements (Table 1).

3.2 Laboratory Measurement of Smoke Emissions

In some cases (pocosin (poc) and understory hardwood (uh) fuel types), the burn was terminated after the smoke had been sampled for a period of time (e.g. 20 minutes) to adequately characterize it. The fuel consumption that is reported does not reflect the consumption that might have occurred if the fire extinguished naturally. Note that the fuel moisture of these fuel beds fell in the range of dead fuels (unsaturated wood, < 35%); reported moisture content of live stems and foliage of these species ranged from 80 to 140 percent and from 100 to over 300 percent, respectively [73].

The range of fuel loading in the litter fuel beds (lit) fell within the range of reported fuel loading for slash and loblolly pine [9] providing further support for the use of laboratory emission factors in field application. While we burned comparable fuel loadings in the laboratory and field experiments, differences in moisture content and bulk density affected the combustion efficiency of the different burns illustrating the challenges inherent in using complex wildland fuel beds in laboratory experiments [e.g. 74,75]. These differences are one of the primary reasons that laboratory and field experiments were compared and synthesized [51].

Other than the whole air canisters, most smoke measurements occurred in real-time and did not require offline chemical analysis. The canister analysis method used gas chromatography (GC) coupled with either flame ionization detection, electron capture detection, or quadrupole mass spectrometer detection. The canister methods were important so as not to miss those chemicals liberated as the reactions occurring in the flame and smoke plume sometimes continued for hours and days after release [e.g. 76].

Combustion efficiency of most experimental burns was relatively high (as characterized [77] by MCE of 0.93 to 0.96) indicating primarily flaming combustion and the resulting associated compounds. The pine litter fuel beds tended to smolder resulting in a lower MCE of 0.89 and a greater production of compounds associated with incomplete combustion such as methanol, acetic acid and furan [49]. We note that nitrous acid (HONO), an important precursor to OH, was observed for all fuel types [45]. In the FSL burns, oxygenated volatile organic compounds (OVOCs) accounted for an average of 66% of the total non-methane hydrocarbons (NMHC) measured in the Camp Lejeune fuels. Trace gas emission factors from the laboratory experiments were generally lower than emission factors previously measured in the field [55] with an airborne FTIR instrument at Camp Lejeune; MCE of the previous prescribed burns was lower than the lab experiments [55]. The OP-FTIR used in the lab measured 10 additional trace gases in comparison with the earlier work, largely due to improved sensitivity.

The carbonaceous particulate matter produced by combustion can be separated into two categories – elemental carbon (EC) and organic carbon (OC) even though the definitions of elemental carbon, black carbon, brown carbon, etc. are not always rigid [78]. These two emissions (EC and OC) comprise total carbon. With the exception of the chipped understory hardwoods, the emission factors for OC were higher in the southeastern fuels when compared to southwestern fuels [41] even though the MCE were similar. The litter fuels produced the greatest emission factors for OC consistent with an observed inverse correlation between MCE and OC. Smoldering combustion tends to produce more products of incomplete combustion (OC) and more fine particles (PM_{2.5})

[79,80]. The laboratory results supported this observation. The correlation between EC and combustion efficiency was very weak; however, the ratio of EC to total carbon was found to increase markedly when the MCE exceeded 0.94. In total, 204 trace gases, many of which had seldom been reported in wildland fire smoke, and 30+ components of particulate matter were measured in the laboratory phase of this project (Table 1).

3.3 Field Campaigns

As the late fall and winter are the active time for prescribed burning in the southern U.S., several airborne measurements were taken from prescribed burn smoke plumes in the vicinity of each installation [42,48,49]. The prescribed burns at the installations contained a mixture of the fuel types which had been measured in the 2009 laboratory experiment as well as additional fuel types. Firing patterns at both Camp Lejeune and Fort Jackson were selected to increase the fire's energy release rate. Helicopter ignition using the Delayed Aerial Ignition Device (ping-pong ball) system [81] increased the energy release rate on the Camp Lejeune burn to compensate for the short burning window that day and the wet conditions of the understory vegetation. The burn had to be completed by midafternoon to minimize smoke impacts on an adjacent major highway. Even though the energy release rate was increased, the overall consumption in the IA burn was only 11% (0.09/0.85) (Table 3). The March burn (ME) was hand-ignited with drip torches and included several fuel types. Wide strips were used on the edge of the unit to generate sufficient flame and intensity to carry the fire through wetter and denser fuel conditions in the interior of the burn unit. The fuel consumption in the ME burn was much higher (61%). We observed no difference in the airborne emissions from the beginning of the burn (initially dominated by the masticated fuels) and the transition into the untreated heavier fuels in the interior of the unit. The fire-averaged MCE of 0.94-0.95, similar to the laboratory burns, indicated relatively efficient burning and the desired intensity were achieved.

Hand-ignition with drip torches was used to start the burns at Fort Jackson. As the intent was to generate fires with greater intensity (energy release rates) than at Camp Lejeune, spacing between

adjacent strip head fires was adjusted throughout each day as ambient conditions changed to increase intensity while minimizing damage to the overstory pines. Due to a lack of fire behavior observations, estimated burning conditions (Table 5) were based on calculated indices from the 1988 National Fire Danger Rating System [82], a version specifically modified for use in the southern U.S. [83]. The indices are general indicators and should not be assumed to represent actual fire behavior of individual fires or prescribed burns wherein firing patterns are used to control fire behavior [1,84]. Observed weather data at Fort Jackson and Camp Lejeune were used to calculate fuel moisture content of 1 hr, 10 hr, 100 hr, and 1000 hr timelag fuels and fire behavior indices were then calculated for fuel model D “Southern Rough”. We assumed that fuel model D reflected the fuel accumulation in the burn units at Fort Jackson resulting from long term fire exclusion. Because neither base had a weather station with a sufficiently long record to determine the climatology (cumulative distribution function) of the fire danger indices [85], the calculated indices were compared to the climatology of nearby locations – Carolina Sandhills National Wildlife Refuge for Fort Jackson and Sandy Run remote automated weather station for Camp Lejeune. The percentile values of the indices are contained in Table 5.

Comparison of the data from the Fort Jackson and Camp Lejeune burns showed the air temperatures were higher at the time of burning at Fort Jackson while wind speeds were comparable. The NFDRS calculations show lower fire danger indices at the time of the Fort Jackson burn but also show lower dead fuel moisture content. The apparent inconsistency between the fire danger indices and dead fuel moisture can be attributed to the time of year during which the burns were conducted. The burns at Camp Lejeune were conducted in February and March. At this time of year live woody moisture content is normally at its lowest and these fuels would be expected to actively support burning [86]. In contrast, the burns at Fort Jackson were conducted in late October and early November. At this time of year near the end of the growing season the live woody fuel moistures are normally still high and the live fuels would moderate fire behavior even though the Keetch-Byram Drought Index (KBDI) indicated some rainfall deficit. We cannot

374 conclude that the burns at Fort Jackson were “higher intensity” burns in comparison to Camp
375 Lejeune. Instead, we assumed that the fires were similar in behavior and are representative of the
376 range of prescribed fire. Anecdotal observations of flame length at Fort Jackson indicated that
377 heading flame lengths were generally less than 1 meter in the litter dominated areas and up to 3
378 meters in areas with dense shrubs [87]. Backing fire flame lengths were generally less than 0.5 m.
379 Longer flame lengths and higher heat release occurred in areas where a backing fire merged with
380 the adjacent strip head fire or where two flanking fires merged [81,88].

381 The airborne MCE for Fort Jackson burns was on average slightly lower (0.92-0.94) but still within
382 the range observed in the lab. Excluding the Pine Plantation burn, the airborne MCEs ranged from
383 0.93 to 0.96 for the other fires. Due to the location of the ground-based FTIR instruments (along the
384 fireline within close proximity to the backing fire used to secure the fireline or adjacent to
385 smoldering stumps), the ground-based MCE was appreciably lower (0.79-0.88) in the Fort Jackson
386 burns for the two ground-based FTIR systems.

387 A total of 97 trace gas species were quantified from both airborne and ground-based sampling
388 platforms at Fort Jackson using the FTIR instruments and offline analysis of whole air samples
389 (WAS). The known chemistry of the monoterpenes and their measured abundance of 0.4–27.9% of
390 non-methane organic compounds (NMOCs) and ~21% of organic aerosol (mass basis) in the
391 sampled plumes suggests that the terpenes impacted both secondary formation of ozone (O₃) and
392 aerosols, as well as small organic trace gases such as methanol and formaldehyde in the first few
393 hours after emission. The variability in the initial terpene emissions in the Fort Jackson fire plumes
394 was high and, in general, the speciation of the initially emitted gas-phase NMOCs was 13–195%
395 different from that observed during the Camp Lejeune deployment. This variability is similar to that
396 observed in other studies in conifer forests [48]. It is likely that differences in stand structure and
397 environmental conditions contributed to the high variability observed within and between these
398 studies. While isoprene and terpenes are all alkenes, hardwood trees emit isoprene almost

399 exclusively whereas pine trees naturally emit primarily terpenes (such as α - and β -pinene,
400 limonene) [e.g. 89].

401 We did not quantify the overstory species composition at Camp Lejeune and Fort Jackson, but the
402 dominant overstory species were pines with a mixture of hardwoods. As expected, the $\Delta\text{HCN}/\Delta\text{CO}$
403 emission ratio was found to be fairly consistent with previous airborne fire measurements in other
404 conifer-dominated ecosystems. It was possible to measure the downwind chemical evolution of the
405 plume from one Fort Jackson burn and three prescribed burns in South Carolina that were only
406 sampled with the aircraft. Significant O_3 formation occurred in all of these plumes within two
407 hours. Changes in plume composition are also important to consider as the smoke is transported
408 outside of the immediate vicinity of a prescribed burn and can have unintended impacts on regional
409 air quality and human populations some distance from the fire location [90,91].

410 Three different FTIR instruments were deployed at Fort Jackson (two closed cell: the airborne and
411 the roving LaFTIR, and one open-path system, the OP-FTIR along the fireline). Comparison of
412 these measurements confirmed earlier results and led to some new key findings: the FTIR data
413 show that the method (airborne, ground) used to sample smoke can strongly influence the relative
414 abundance of the emissions that are measured [50]. For these fires, the majority of fire emissions
415 were lofted sufficiently high enough in the convection column so that they could be sampled by the
416 airborne FTIR – which had a minimum distance above ground level of 500 ft. The mobile, ground-
417 based, point sampling FTIR measured the contribution of individual smoldering stumps and trees
418 scattered throughout the burn site, and whose data were characterized by significantly lower MCE
419 values (associated with RSC). The OP-FTIR, however, provided a ~30 m path-integrated sample of
420 emissions transported across the fireline and typically measured two distinct combustion regimes: i)
421 a flaming phase immediately after the adjacent line ignition (back firing to establish burnt buffer)
422 but before the adjacent plume achieved significant vertical development, and ii) a smoldering phase
423 which consisted of primarily RSC smoke wafting across the fireline. The OP-FTIR provided our
424 best estimate of fireline exposure to smoke for wildland fire personnel who are charged with

holding the control lines. Our data suggest [46] that peak exposures to smoke are more likely to challenge permissible exposure limits for wildland fire personnel than shift-average (8 h) exposures which supports earlier work wherein firefighters were equipped with monitoring devices to determine smoke exposure during prescribed and wildland fires [92]. In particular, avoidance of areas with high levels of residual smoldering combustion or airway protection by fire personnel may be possible methods to mitigate exposure to peak levels [42].

As mentioned above, the project further allowed us to compare emission factors determined in a laboratory setting with emission factors determined in the field [51]. In comparison with the laboratory, a broad variety, but a smaller number of chemicals (21 trace gas and PM_{2.5}) was measured in the field. Due to the sensitivity of the OP-FTIR instrument and software improvements, the laboratory emission factors originally reported [47] were recomputed using carbon mass balance which resulted in slight changes [51]. The revised trace gas emission factors can be found in Table 6 and the full set of recomputed emission factors are supplemental material available at <http://www.atmos-chem-phys.net/13/89/2013/acp-13-89-2013-supplement.zip>.

For the twelve chemicals NO_x to PM_{2.5} the mean lab EF/field EF ratio for the pine understory fuels was not significantly different from unity [51]. Based on the lab/field comparison, emission factors for 357 pyrogenic species (including unidentified species) for southern pine understory fuels and organic soils were developed and recommended as useful for field application. The emissions we measured using the LaFTIR instrument with focused sampling on a variety of individual fuel types prone to produce residual smoldering generally fell within the ranges previously measured for bog soils and longleaf duff (Table 7).

While the number of chemical species detected in the laboratory phase with the large suite of instruments that was deployed far exceeded the number of species measured in the field phase, the FTIR instruments used were able to non-intrusively sample an increased number of species at lower concentrations than was available only 4 years ago. The FTIR technology also provided continuous measurement in comparison to collected gas canisters which generally lack a continuous temporal

signature and may change chemically from the time of collection to the time that analysis is performed. Many new chemical species previously undetected by FTIR were observed, some with good signal-to-noise, others near the detection limits of the instruments. Not all were reported in the literature, but include such species as HONO, phenol, glyoxal, methylglyoxal, glycolaldehyde, pinenes, limonene, etc. FTIR technology has the potential to improve real-time measurement of trace gas emissions in field settings (Table 1).

3.4 Emission factors database

Perception of a lack of information on emissions from southern fuel types resulted in a search through the published and “grey” literature to locate emissions information. The oldest reports date back to the 1960s, which first reported CO and CO₂ emission factors. It was not until the early 1980s, however, that significant amounts of other emissions data for wildland fire were reported. In total, 230 references were located and evaluated. See reference [69] for a complete listing of the documents which were located and included in the database. Emissions information for 118 smoke components from 51 of the reviewed references are currently contained in Wildland Fire Emissions Factor Database which contains information published up to 2011 [69]. Future updates to the database may occur.

Pertinent information related to the fuels, the instrumentation used, and geographic location is all contained in the spreadsheet. All 230 references were electronically scanned and are available. If it was not possible to convert emission ratios and emission concentrations to emission factors using information contained in the original source, the data were not included in the database. Some of the references include sufficient information so that experimental error (standard deviation) could also be determined. This information was not included in the spreadsheet version due to space limitations. Inclusion or exclusion of data from a particular report is not a statement on the quality of the information: Users of the database will need to draw their own conclusions regarding the applicability of the information to their particular situation.

476 4 Summary

477 The SERDP-sponsored project enabled new technologies and furthered basic science, mostly in the
478 area of infrared spectroscopy, a nonintrusive broadband (remote sensing, depending on
479 configuration) measurement method well suited to characterize smoke from wildland fire.

480 Advances in hardware, software and supporting reference data realized a nearly 20x improvement
481 in sensitivity and now provide quantitative IR spectra for potential detection of 53 new species and
482 actual field quantification of several new species such as nitrous acid, glycolaldehyde, α -/ β -pinene
483 and D-limonene. The new reference data also contribute to the determination of the global warming
484 potential of the greenhouse gases by both 1) enabling detection of their ambient concentrations, and
485 2) quantifying their ability to absorb IR radiation, i.e. act as a greenhouse gas.

486 Another key deliverable resulting from our studies are the data consisting of hundreds of the best
487 possible measurements of EF for a very broad suite of both trace gases and particulate species for
488 southeastern U.S. fuels. The list of chemical species measured in this project is the most extensive
489 smoke characterization achieved to date and is presented in extensive tables of EF in the various
490 publications [25-44], including broken out by vegetation type, e.g. semiarid shrublands or pine
491 understory, since the project was one of three related efforts. Prescribed fire managers can use the
492 emission factors and fuel loading data compiled in this project when planning prescribed burns.

493 Uncertainty in the emissions information can be coupled with uncertainty in fuel loading and
494 consumption derived from other sources to estimate the uncertainty of emissions produced [93].

495 Emission ratios (ER) of various compounds to CO were derived and can be used by air quality
496 specialists to estimate downwind concentrations and photochemical changes for certain species
497 using only data from CO monitors. Multiple measurements of in-plume chemical transformations,
498 O₃ formation, and secondary organic aerosol formation can be used by modelers to refine air
499 quality models such as CMAQ to improve estimates.

500 While field studies results are the most desirable, we have also confirmed that studying laboratory
501 biomass fires can significantly increase our understanding of wildland fires, especially when

laboratory and field results are carefully combined and compared. In particular, we have found that many of the emission factors for the unlofted emissions that are produced by residual smoldering combustion are very similar between the laboratory and field measurements, thus making laboratory studies of great value at characterizing smoldering-phase emissions. These unlofted emissions are of primary concern to prescribed fire managers because of the potential for traffic corridor obscuration and effects on human health. Characterization of such emissions will enable us to improve current models predicting low visibility and super-fog formation [20,94].

In summary, this five year study provided a wealth of data and technology which can be used to improve our use of prescribed burning, better manage carbon resources, and improve prediction of both the local and global effects of fire in fuels of this or similar types.

Acknowledgements

This work was supported by the Department of Defense's Strategic Environmental Research and Development Program (SERDP) project RC-1649 and we thank Dr. John Hall and his program for their support. Suggestions made by the SERDP Technical Advisory Committee helped to focus and expand the original project. In particular, we thank Prof. Robert J. Yokelson of the University of Montana for his many enormous contributions to this project. We also thank the several students, postdoctoral fellows and research scientists who contributed to individual components. In addition to SERDP and the Department of Defense installations, several other federal, state, and university organizations contributed to the success of this project including the National Oceanographic and Atmospheric Administration, the Environmental Protection Agency, the National Center for Atmospheric Research, Colorado State University, University of California-Riverside, Georgia Institute of Technology, North Carolina Forest Service, South Carolina Forestry Commission, the U.S. Forest Service, the Department of Energy, and the Pacific Northwest National Laboratory. PNNL is operated for the U.S. Department of Energy by the Battelle Memorial Institute under contract DE-AC06-76RLO 1830.

528 References

- 529 [1] T.A. Waldrop, S.L. Goodrick, Introduction to prescribed fires in southern ecosystems, USDA
530 Forest Service, Southern Research Station, Asheville, NC, 2012.
531 <http://www.treesearch.fs.fed.us/pubs/41316>.
- 532 [2] J.K. Agee, Fire and pine ecosystems, in: D.M. Richardson (Ed.), *Ecol. Biogeogr. Pinus*,
533 Cambridge University Press, Cambridge, U.K., 2000: pp. 193–218.
- 534 [3] A.M. Gill, R.H. Groves, I.R. Noble, *Fire and the Australian Biota*, Australian Academy of
535 Science, Canberra, 1981.
- 536 [4] M.A. Melvin, 2012 National Prescribed Fire Use Survey Report, Coalition of Prescribed Fire
537 Councils, Inc., 2012. [http://www.stateforesters.org/sites/default/files/publication-](http://www.stateforesters.org/sites/default/files/publication-documents/2012_National_Prescribed_Fire_Survey.pdf)
538 [documents/2012_National_Prescribed_Fire_Survey.pdf](http://www.stateforesters.org/sites/default/files/publication-documents/2012_National_Prescribed_Fire_Survey.pdf).
- 539 [5] National Interagency Fire Center, Total wildland fires and acres (1960-2009), Total Wildland
540 Fires Acres 1960-2009. (2014). http://www.nifc.gov/fireInfo/fireInfo_stats_totalFires.html.
- 541 [6] L. Giglio, J.T. Randerson, G.R. van der Werf, Analysis of daily, monthly, and annual burned
542 area using the fourth-generation global fire emissions database (GFED4): analysis of burned
543 area, *J. Geophys. Res. Biogeosciences*. 118 (2013) 317–328. doi:10.1002/jgrg.20042.
- 544 [7] P.J. Crutzen, M.O. Andreae, Biomass Burning in the Tropics: Impact on Atmospheric
545 Chemistry and Biogeochemical Cycles, *Science*. 250 (1990) 1669–1678.
546 doi:10.1126/science.250.4988.1669.
- 547 [8] W. Seiler, P.J. Crutzen, Estimates of gross and net fluxes of carbon between the biosphere and
548 the atmosphere from biomass burning, *Clim. Change*. 2 (1980) 207–247.
549 doi:10.1007/BF00137988.
- 550 [9] H.E. Mobley, *Southern forestry smoke management guidebook*, USDA Forest Service,
551 Southeastern Forest Experiment Station, Asheville, NC, 1976.
552 <http://www.treesearch.fs.fed.us/pubs/683>.
- 553 [10] D.E. Ward, Particulate matter emissions for fires in the palmetto-gallberry fuel type, *For.*
554 *Sci.* 29 (1983) 761–770.
- 555 [11] C.K. McMahon, S.N. Tsoukalas, Polynuclear aromatic hydrocarbons in forest fire smoke,
556 *Carcinogenesis*. Vol. 3 (1978) 61–73.
- 557 [12] J.S. Levine, W.R. Cofer III, D.R. Cahoon Jr., E.L. Winstead, Biomass burning: a driver for
558 global change, *Environ. Sci. Technol.* 29 (1995) 120A–125A.
- 559 [13] M.O. Andreae, P. Merlet, Emission of trace gases and aerosols from biomass burning,
560 *Glob. Biogeochem. Cycles*. 15 (2001) 955. doi:10.1029/2000GB001382.
- 561 [14] W.T. Sommers, R.A. Loehman, C.C. Hardy, Wildland fire emissions, carbon, and climate:
562 Science overview and knowledge needs, *For. Ecol. Manag.* (2014).
563 doi:10.1016/j.foreco.2013.12.014.
- 564 [15] S.S. Sackett, Scheduling prescribed burns for hazard reduction in the Southeast, *J. For.* 73
565 (1975) 143–147.
- 566 [16] R.D. Ottmar, R.E. Vihnanek, Volume VI: Longleaf pine, pocosin, and marshgrass in the
567 Southeast United States, National Wildfire Coordinating Group, National Interagency Fire
568 Center, Boise, ID, 2000.
- 569 [17] J.S. Glitzenstein, D.R. Streng, G.L. Achtemeier, L.P. Naeher, D.D. Wade, Fuels and fire
570 behavior in chipped and unchipped plots: Implications for land management near the
571 wildland/urban interface, *For. Ecol. Manag.* 236 (2006) 18–29.
572 doi:10.1016/j.foreco.2006.06.002.
- 573 [18] W.A. Hough, F.A. Albini, Predicting fire behavior in palmetto-gallberry fuel complexes,
574 USDA Forest Service, Southeastern Forest and Range Experiment Station, Asheville, NC,
575 1978. [http://www.firemodels.org/downloads/behaveplus/publications/Hough_and_Albini_SE-](http://www.firemodels.org/downloads/behaveplus/publications/Hough_and_Albini_SE-174_1978.pdf)
576 [174_1978.pdf](http://www.firemodels.org/downloads/behaveplus/publications/Hough_and_Albini_SE-174_1978.pdf).

- [19] C. Fowler, Human health impacts of forest fires in the southern United States: a literature review, *J. Ecol. Anthropol.* 7 (2003) 39–63. doi:10.5038/2162-4593.7.1.3.
- [20] G.L. Achtemeier, On the formation and persistence of superfog in woodland smoke, *Meteorol. Appl.* 16 (2009) 215–225. doi:10.1002/met.110.
- [21] C.T. Chi, D.A. Horn, D.L. Zanders, R.E. Opferkuch, J.M. Nyers, J.M. Pierovich, et al., Source Assessment: Prescribed Burning, State of the Art, United States Environmental Protection Agency, Research Triangle Park, NC, 1979. nepis.epa.gov.
- [22] R.S. Seymour, M.L. Hunter Jr., Principles of ecological forestry, in: M.L. Hunter Jr. (Ed.), *Maint. Biodivers. For. Ecosyst.*, Cambridge University Press, Cambridge, U.K., 1999: pp. 22–61.
- [23] B. Finch, B.M. Young, R. Johnson, J.C. Hall, Longleaf, far as the eye can see: a new vision of North America's richest forest, University of North Carolina Press, Chapel Hill, NC, 2012.
- [24] J.L. Landers, D.H. Van Lear, W.D. Boyer, The longleaf pine forests of the southeast: requiem or renaissance?, *J. For.* 93 (1995) 39–44.
- [25] R. Lopez, N. Burns, D. Gjerstad, G. Burger, T. Ivey, T. George, et al., Range-wide conservation plan for longleaf pine, (2009). http://www.sref.info/resources/publications/range-wide-conservation-plan-for-longleaf-pine-1/at_download/file.
- [26] N.L. Christensen, Vegetation of the Southeastern Coastal Plain, in: M.G. Barbour, W.D. Billings (Eds.), *North Am. Terr. Veg.*, 2nd ed., Cambridge University Press, New York, NY, 2000: pp. 397–448.
- [27] F. Heyward, The relation of fire to stand composition of longleaf pine forests, *Ecology*. 20 (1939) 287–304.
- [28] R.A. Loehman, E. Reinhardt, K.L. Riley, Wildland fire emissions, carbon, and climate: Seeing the forest and the trees – A cross-scale assessment of wildfire and carbon dynamics in fire-prone, forested ecosystems, *For. Ecol. Manag.* (2013). doi:10.1016/j.foreco.2013.04.014.
- [29] D.R. Weise, B.M. Wotton, Wildland–urban interface fire behaviour and fire modelling in live fuels, *Int. J. Wildland Fire*. 19 (2010) 149. doi:10.1071/WF09107.
- [30] A.G. Rappold, S.L. Stone, W.E. Cascio, L.M. Neas, V.J. Kilaru, M.S. Carraway, et al., Peat bog wildfire smoke exposure in rural North Carolina is associated with cardiopulmonary emergency department visits assessed through syndromic surveillance, *Environ. Health Perspect.* 119 (2011) 1415–1420. doi:10.1289/ehp.1003206.
- [31] A.L. Hinwood, C.M. Rodriguez, Potential health impacts associated with peat smoke: a review, *J. R. Soc. West. Aust.* 88 (2005) 133–138.
- [32] G.W. Wendel, T.G. Storey, G.M. Byram, Forest fuels on organic and associated soils in the Coastal Plain of North Carolina, USDA Forest Service, Southeastern Forest Experiment Station, Asheville, NC, 1962. <http://www.treesearch.fs.fed.us/pubs/42401>.
- [33] D.D. Wade, D.E. Ward, An analysis of the Air Force Bomb Range Fire, (1973). http://www.srs.fs.usda.gov/pubs/rp/uncaptured/rp_se105.pdf.
- [34] C.K. McMahon, D.D. Wade, S.N. Tsoukalas, Combustion characteristics and emissions from burning organic soils, in: Air Pollution Control Association, Montreal, Quebec, 1980.
- [35] M.T. Odman, Strategic Environmental Research and Development Program Final Report for RC-1647: Characterization of emissions and air quality modeling for predicting the impacts of prescribed burns at DoD lands, Georgia Institute of Technology, Atlanta, GA, 2012. <http://www.serdp.org/content/download/16800/188624/file/RC-1647-FR.pdf>.
- [36] W. Miller, Strategic Environmental Research and Development Program Final Report for RC-1648: New tools for estimating and managing local/regional air quality impacts of prescribed burns, University of California - Riverside, Riverside, CA, 2013. <http://www.serdp.org/content/download/27825/275816/file/RC-1648-FR.pdf>.
- [37] T.J. Johnson, R.J. Yokelson, S.K. Akagi, I.R. Burling, D.R. Weise, S.P. Urbanski, et al., Strategic Environmental Research and Development Program Final Report for RC-1649:

- Advanced chemical measurements of smoke from DoD-prescribed burns, Pacific Northwest National Laboratory, Richland, WA, 2014. <https://www.serdp-estcp.org/content/download/24314/252130/file/RC-1649-FR.pdf>.
- [38] R. Yokelson, D. Griffith, D. Ward, Open-path Fourier transform infrared studies of large-scale laboratory biomass fires, *J. Geophys. Res.-Atmospheres*. 101 (1996) 21067–21080. doi:10.1029/96JD01800.
- [39] J.U. White, Long optical paths of large aperture, *J. Opt. Soc. Am.* 32 (1942) 285–288.
- [40] C. Warneke, J.M. Roberts, P. Veres, J. Gilman, W.C. Kuster, I. Burling, et al., VOC identification and inter-comparison from laboratory biomass burning using PTR-MS and PIT-MS, *Int. J. Mass Spectrom.* 303 (2011) 6–14. doi:10.1016/j.ijms.2010.12.002.
- [41] S. Hosseini, S.P. Urbanski, P. Dixit, L. Qi, I.R. Burling, R.J. Yokelson, et al., Laboratory characterization of PM emissions from combustion of wildland biomass fuels: particle emissions from biomass burning, *J. Geophys. Res. Atmospheres*. 118 (2013) 9914–9929. doi:10.1002/jgrd.50481.
- [42] S.K. Akagi, I.R. Burling, A. Mendoza, T.J. Johnson, M. Cameron, D.W.T. Griffith, et al., Field measurements of trace gases emitted by prescribed fires in southeastern US pine forests using an open-path FTIR system, *Atmospheric Chem. Phys.* 14 (2014) 199–215. doi:10.5194/acp-14-199-2014.
- [43] T.J. Johnson, R.L. Sams, T.A. Blake, S.W. Sharpe, P.M. Chu, Removing aperture-induced artifacts from Fourier transform infrared intensity values, *Appl. Opt.* 41 (2002) 2831–2836. doi:10.1364/AO.41.002831.
- [44] S.W. Sharpe, T.J. Johnson, R.L. Sams, P.M. Chu, G.C. Rhoderick, P.A. Johnson, Gas-phase databases for quantitative infrared spectroscopy, *Appl Spectrosc.* 58 (2004) 1452–1461.
- [45] J.M. Roberts, P. Veres, C. Warneke, J.A. Neuman, R.A. Washenfelter, S.S. Brown, et al., Measurement of HONO, HNCO, and other inorganic acids by negative-ion proton-transfer chemical-ionization mass spectrometry (NI-PT-CIMS): application to biomass burning emissions, *Atmospheric Meas. Tech.* 3 (2010) 981–990. doi:10.5194/amt-3-981-2010.
- [46] P. Veres, J.M. Roberts, I.R. Burling, C. Warneke, J. de Gouw, R.J. Yokelson, Measurements of gas-phase inorganic and organic acids from biomass fires by negative-ion proton-transfer chemical-ionization mass spectrometry, *J. Geophys. Res.* 115 (2010). doi:10.1029/2010JD014033.
- [47] I.R. Burling, R.J. Yokelson, D.W.T. Griffith, T.J. Johnson, P. Veres, J.M. Roberts, et al., Laboratory measurements of trace gas emissions from biomass burning of fuel types from the southeastern and southwestern United States, *Atmospheric Chem. Phys.* 10 (2010) 11115–11130. doi:10.5194/acp-10-11115-2010.
- [48] S.K. Akagi, R.J. Yokelson, I.R. Burling, S. Meinardi, I. Simpson, D.R. Blake, et al., Measurements of reactive trace gases and variable O₃ formation rates in some South Carolina biomass burning plumes, *Atmospheric Chem. Phys.* 13 (2013) 1141–1165. doi:10.5194/acp-13-1141-2013.
- [49] I.R. Burling, R.J. Yokelson, S.K. Akagi, S.P. Urbanski, C.E. Wold, D.W.T. Griffith, et al., Airborne and ground-based measurements of the trace gases and particles emitted by prescribed fires in the United States, *Atmospheric Chem. Phys.* 11 (2011) 12197–12216. doi:10.5194/acp-11-12197-2011.
- [50] D.E. Ward, L.F. Radke, Emissions measurement from vegetation fires: a comparative evaluation of methods and results, in: P.J. Crutzen, J.G. Goldammer (Eds.), *Fire Environ. Ecol. Atmospheric Clim. Importance Veg. Fires*, John Wiley & Sons Ltd., 1993: pp. 53–76. http://www.fs.fed.us/rm/pubs_other/rmrs_1993_ward_d001.pdf.
- [51] R.J. Yokelson, I.R. Burling, J.B. Gilman, C. Warneke, C.E. Stockwell, J. de Gouw, et al., Coupling field and laboratory measurements to estimate the emission factors of identified and unidentified trace gases for prescribed fires, *Atmospheric Chem. Phys.* 13 (2013) 89–116. doi:10.5194/acp-13-89-2013.

- [52] D.E. Ward, W.M. Hao, Projections of emissions from burning of biomass for use in studies of global climate and atmospheric chemistry, in: Air and Waste Management Association, Vancouver, British Columbia, Canada, 1991: p. 19.
- [53] R. Yokelson, R. Susott, D. Ward, J. Reardon, D. Griffith, Emissions from smoldering combustion of biomass measured by open-path Fourier transform infrared spectroscopy, *J. Geophys. Res.-Atmospheres*. 102 (1997) 18865–18877. doi:10.1029/97JD00852.
- [54] D.E. Ward, H.B. Clements, R.M. Nelson Jr., Particulate matter emission factor modeling for fire in southeastern fuels, in: Sixth Conf. Fire For. Meteorol., American Meteorological Society, Seattle, WA, 1980: pp. 276–284.
- [55] Yokelson, R.J., J.G. Goode, D.E. Ward, R.A. Susott, R.E. Babbitt, D.D. Wade, et al., Emissions of formaldehyde, acetic acid, methanol, and other trace gases from biomass fires in North Carolina measured by airborne Fourier transform infrared spectroscopy, *J. Geophys. Res.* 104 (1999) 30109–30125. doi:10.1029/1999JD900817.
- [56] T.J. Johnson, R.L. Sams, S.D. Burton, T.A. Blake, Absolute integrated intensities of vapor-phase hydrogen peroxide (H_2O_2) in the mid-infrared at atmospheric pressure, *Anal. Bioanal. Chem.* 395 (2009) 377–386. doi:10.1007/s00216-009-2805-x.
- [57] T.J. Johnson, L.T.M. Profeta, R.L. Sams, D.W.T. Griffith, R.L. Yokelson, An infrared spectral database for detection of gases emitted by biomass burning, *Vib. Spectrosc.* 53 (2010) 97–102. doi:10.1016/j.vibspec.2010.02.010.
- [58] P. Veres, J.B. Gilman, J.M. Roberts, W.C. Kuster, C. Warneke, I.R. Burling, et al., Development and validation of a portable gas phase standard generation and calibration system for volatile organic compounds, *Atmospheric Meas. Tech.* 3 (2010) 683–691. doi:10.5194/amt-3-683-2010.
- [59] L.T.M. Profeta, R.L. Sams, T.J. Johnson, S.D. Williams, Quantitative infrared intensity studies of vapor-phase glyoxal, methylglyoxal, and 2,3-butanedione (diacetyl) with vibrational assignments, *J. Phys. Chem. A*. 115 (2011) 9886–9900. doi:10.1021/jp204532x.
- [60] A.L. Chang-Graham, L.T.M. Profeta, T.J. Johnson, R.J. Yokelson, A. Laskin, J. Laskin, Case Study of Water-Soluble Metal Containing Organic Constituents of Biomass Burning Aerosol, *Environ. Sci. Technol.* 45 (2011) 1257–1263. doi:10.1021/es103010j.
- [61] J.M. Roberts, P.R. Veres, A.K. Cochran, C. Warneke, I.R. Burling, R.J. Yokelson, et al., Isocyanic acid in the atmosphere and its possible link to smoke-related health effects, *Proc. Natl. Acad. Sci.* (2011). doi:10.1073/pnas.1103352108.
- [62] C. Wiedinmyer, S.K. Akagi, R.J. Yokelson, L.K. Emmons, J.A. Al-Saadi, J.J. Orlando, et al., The Fire INventory from NCAR (FINN): a high resolution global model to estimate the emissions from open burning, *Geosci. Model Dev.* 4 (2011) 625–641. doi:10.5194/gmd-4-625-2011.
- [63] S.K. Akagi, R.J. Yokelson, C. Wiedinmyer, M.J. Alvarado, J.S. Reid, T. Karl, et al., Emission factors for open and domestic biomass burning for use in atmospheric models, *Atmospheric Chem. Phys.* 11 (2011) 4039–4072. doi:10.5194/acp-11-4039-2011.
- [64] J. Aurell, B.K. Gullett, Emission factors from aerial and ground measurements of field and laboratory forest burns in the southeastern U.S.: $PM_{2.5}$, black and brown carbon, VOC, and PCDD/PCDF, *Environ. Sci. Technol.* (2013) 130729092352005. doi:10.1021/es402101k.
- [65] S.D. Williams, T.J. Johnson, S.W. Sharpe, V. Yavelak, R.P. Oates, C.S. Brauer, Quantitative vapor-phase IR intensities and DFT computations to predict absolute IR spectra based on molecular structure: I. Alkanes, *J. Quant. Spectrosc. Radiat. Transf.* 129 (2013) 298–307. doi:10.1016/j.jqsrt.2013.07.005.
- [66] T.J. Johnson, R.L. Sams, L.T.M. Profeta, S.K. Akagi, I.R. Burling, R.J. Yokelson, et al., Quantitative IR spectrum and vibrational assignments for glycolaldehyde vapor: glycolaldehyde measurements in biomass burning plumes, *J. Phys. Chem. A*. 117 (2013) 4096–4107. doi:10.1021/jp311945p.

- [67] C.S. Brauer, T.A. Blake, A.B. Guenther, R.L. Sams, T.J. Johnson, Quantitative infrared absorption cross-sections of isoprene for atmospheric measurements, *Atmospheric Meas. Tech. Discuss.* 7 (2014) 4163–4189. doi:10.5194/amtd-7-4163-2014.
- [68] A.A. May, G.R. McMeeking, T. Lee, J.W. Taylor, J.S. Craven, I. Burling, et al., Aerosol emissions from prescribed fires in the United States: A synthesis of laboratory and aircraft measurements: Aerosols from US prescribed fires, *J. Geophys. Res. Atmospheres*. 119 (2014) 11,826–11,849. doi:10.1002/2014JD021848.
- [69] E. Lincoln, W. Hao, D.R. Weise, T.J. Johnson, Wildland fire emission factors database, USDA Forest Service Research Data Archive, Fort Collins, CO, 2014. <http://dx.doi.org/10.2737/RDS-2014-0012>.
- [70] J.K. Kreye, L.N. Kobziar, W.C. Zipperer, Effects of fuel load and moisture content on fire behaviour and heating in masticated litter-dominated fuels, *Int. J. Wildland Fire*. 22 (2013) 440. doi:10.1071/WF12147.
- [71] D.W.T. Griffith, Synthetic calibration and quantitative analysis of gas-phase FT-IR spectra, *Appl. Spectrosc.* 50 (1996) 59–70.
- [72] C.P. Rinsland, P.F. Coheur, H. Herbin, C. Clerbaux, C. Boone, P. Bernath, et al., Detection of elevated tropospheric hydrogen peroxide (H₂O₂) mixing ratios in atmospheric chemistry experiment (ACE) subtropical infrared solar occultation spectra, *J. Quant. Spectrosc. Radiat. Transf.* 107 (2007) 340–348. doi:10.1016/j.jqsrt.2007.02.009.
- [73] W.H. Blackmarr, W.B. Flanner, Moisture variation in selected pocosin shrubs of eastern North Carolina, USDA Forest Service, Southeastern Forest Experiment Station, Asheville, NC, 1975.
- [74] R.M. Nelson Jr., C.W. Adkins, Flame characteristics of wind-driven surface fires, *Can. J. For. Res.* 16 (1986) 1293–1300. doi:10.1139/x86-229.
- [75] E. Marino, M. Guijarro, J. Madrigal, C. Hernando, C. Diez, Assessing fire propagation empirical models in shrub fuel complexes using wind tunnel data, in: J. de las Heras, C.A. Brebbia, D. Viegas, V. Leone (Eds.), *Model. Monit. Manag. For. Fires*, WITPress, Wessex, UK, 2008: pp. 121–130. doi:10.2495/FIVA080131.
- [76] S.K. Akagi, J.S. Craven, J.W. Taylor, G.R. McMeeking, R.J. Yokelson, I.R. Burling, et al., Evolution of trace gases and particles emitted by a chaparral fire in California, *Atmospheric Chem. Phys.* 12 (2012) 1397–1421. doi:10.5194/acp-12-1397-2012.
- [77] D.E. Ward, W.M. Hao, Air toxic emissions from burning of biomass globally- preliminary estimates, in: *Air and Waste Management Association*, Kansas City, MO, 1992: p. 13.
- [78] M.O. Andreae, A. Gelencsér, Black carbon or brown carbon? The nature of light-absorbing carbonaceous aerosols, *Atmospheric Chem. Phys.* 6 (2006) 3131–3148.
- [79] P.W. Ryan, C.K. McMahon, Some chemical and physical characteristics of emissions from forest fires; Paper 76-2.3, in: *Air Pollution Control Association*, Portland, OR, 1976: p. 21.
- [80] D. Ward, Combustion Chemistry and Smoke, in: E.A. Johnson, K. Miyanishi (Eds.), *For. Fires Behav. Ecol. Eff.*, Academic Press, San Diego, CA, 2001: pp. 55–77.
- [81] R.W. Johansen, Prescribed burning with spot fires in the Georgia coastal plain, Georgia Forestry Commission, Macon, GA, 1984. <http://www.treesearch.fs.fed.us/pubs/36481>.
- [82] R.E. Burgan, 1988 Revision to the 1978 National Fire-Danger Rating System, USDA Forest Service, Southeastern Forest Experiment Station, Asheville, NC, 1988.
- [83] J.E. Deeming, R.E. Burgan, J.D. Cohen, The National Fire-danger Rating System - 1978, USDA Forest Service, Intermountain Forest & Range Experiment Station, Ogden, UT, 1977.
- [84] P.L. Andrews, D.O. Loftsgaarden, L.S. Bradshaw, Evaluation of fire danger rating indexes using logistic regression and percentile analysis, *Int. J. Wildland Fire*. 12 (2003) 213. doi:10.1071/WF02059.
- [85] R.W. Furman, R.S. Helfman, A computer program for processing historic fire weather data for the National Fire-Danger Rating System, USDA Forest Service, Rocky Mountain

- Forest and Range Experiment Station, Fort Collins, CO, 1973.
http://books.google.com/books?id=EDHzCDtwzH8C&printsec=frontcover&source=gbs_ge_summary_r&cad=0#v=onepage&q&f=false.
- [86] W.H. Blackmarr, W.B. Flanner, Seasonal and diurnal variation in moisture content of six species of pocosin shrubs, USDA Forest Service, Southeastern Forest Experiment Station, Asheville, NC, 1968.
- [87] T.B. Maynard, Fire Interactions and Pulsation – Theoretical and Physical Modeling, Ph.D., University of California - Riverside, 2013. <http://scotty.ucr.edu/record=b4498808~S5>.
- [88] R.W. Johansen, Ignition patterns & prescribed fire behavior in southern pine stands, Georgia Forestry Commission, Macon, GA, 1987. <http://www.treesearch.fs.fed.us/pubs/36482>.
- [89] A. Guenther, P. Zimmerman, M. Wildermuth, Natural volatile organic compound emission rate estimates for U.S. woodland landscapes, *Atmos. Environ.* 28 (1994) 1197–1210. doi:10.1016/1352-2310(94)90297-6.
- [90] W.E. Heilman, Y. Liu, S. Urbanski, V. Kovalev, R. Mickler, Wildland fire emissions, carbon, and climate: Plume rise, atmospheric transport, and chemistry processes, *For. Ecol. Manag.* (2013). doi:10.1016/j.foreco.2013.02.001.
- [91] Y. Hu, M.T. Odman, M.E. Chang, W. Jackson, S. Lee, E.S. Edgerton, et al., Simulation of Air Quality Impacts from Prescribed Fires on an Urban Area, *Environ. Sci. Technol.* 42 (2008) 3676–3682. doi:10.1021/es071703k.
- [92] T.E. Reinhardt, R.D. Ottmar, Baseline measurements of smoke exposure among wildland firefighters, *J. Occup. Environ. Hyg.* 1 (2004) 593–606. doi:10.1080/15459620490490101.
- [93] R.D. Ottmar, A.I. Miranda, D.V. Sandberg, Chapter 3 Characterizing Sources of Emissions from Wildland Fires, in: *Dev. Environ. Sci.*, Elsevier, 2008: pp. 61–78. <http://linkinghub.elsevier.com/retrieve/pii/S147481770800003X> (accessed May 13, 2014).
- [94] M. Princevac, D. Weise, A. Venkatram, G. Achtemeier, S. Mahalingam, S. Goodrick, et al., Superfog formation: laboratory experiments and model development, University of California - Riverside, Riverside, CA, 2013. http://www.firescience.gov/projects/09-1-04-5/project/09-1-04-5_final_report.pdf.
- [95] E.L. Little Jr., Atlas of United States Trees: Volume 1. Conifers and Important Hardwoods, USDA Forest Service, Washington, D.C., 1971.

812 Table 1 Objectives and key findings of study to improve emissions for prescribed burns in the
 813 southern United States.

Objective	Key Accomplishments/Findings
Improved Infrared Instrumentation and Spectral Database	<ul style="list-style-type: none"> • Added 53 gases to spectral library to expand remote measurement of biomass burning emissions • More accurate estimation of emissions using FTIR due to increased sensitivity of instrument • Temporal measurement of 10 additional trace gases measured in the lab using FTIR • Field comparison of FTIR instruments indicate that measurement location (ground versus air) can strongly influence the measured relative abundance of emissions
Laboratory Measurement of Emissions	<ul style="list-style-type: none"> • Measurement of 204 trace gases and 30+ particulate matter components for southeastern and southwestern U.S. fuel types • Many of the 182 trace gases measured by GC-MS have been seldom measured in smoke previously
Field Measurement of Emissions	<ul style="list-style-type: none"> • Field measurements were well-correlated with laboratory measurements for EPA Criteria pollutants and many other trace gases supporting value of laboratory data • Potential firefighter fireline exposure exceeded peak levels but not per shift levels on control lines • FTIR technology can nonintrusively provide temporal

814

	measurement of trace gases at detection limits exceeding current standards
--	---

Table 2 Summary of airborne and ground-based sampling performed in the southeastern U.S. in February/March 2010 and November 2011. See [48,49] for a more detailed description of the fires and the flight tracks associated with airborne measurements. Area in ha.

Fire Name	Lat/Long (°)	Fuel type ^a	Area (ha)	Measures ^b
Camp Lejeune IA	34.5798 N, 77.3167 W	2yr	36	A, G
Camp Lejeune ME	34.6422 N, 77.4617 W	1yr, 2yr, cuh, uh	677	A, G
Little Florida 1	34.0708 N, 78.2780 W	wire grass, gallberry	16	A
Little Florida 2	34.0687 N, 78.2817 W	gallberry	24	A
Bear Pen	34.1287 N, 78.3388 W	grass		A
Holly Shelter	34.5467 N, 77.8367 W	lit	23	A
Fort Jackson 6	34.0247 N, 80.8711 W	longleaf	62	A, G
Fort Jackson 9b	34.0042 N, 80.8769 W	longleaf, sparkleberry	36	A, G
Fort Jackson 22b	34.0844 N, 80.7731 W	longleaf, loblolly, oak	29	A, G
Pine Plantation	33.5803 N, 81.1653 W	loblolly	16	A
Georgetown	33.2025 N, 79.4017 W	grass, uh	61	A
Francis Marion	33.2153 N, 79.4761 W	longleaf, wire grass	147	A
Bamberg	33.2347 N, 80.9447 W	longleaf, loblolly, uh	36	A

a. Refer to [47] for explanation of fuel codes. Wire grass - *Aristida stricta*, gallberry - *Ilex coriacea*, longleaf – *Pinus palustris* litter, sparkleberry – *Vaccinium arboretum*, loblolly – *P. taeda* litter, oak – *Quercus* spp. leaves

b. A – airborne, G – ground.

840 Table 3. Characteristics of fuel beds burned in the laboratory (L) and in prescribed burns (F) to
841 measure smoke emissions.

Fuel Type ^a	Moisture Content (%)		Preburn Dry Mass (kg m ⁻²)		Bulk Density (kg m ⁻³)		Fuel Consumption (kg m ⁻²)	
	L	F	L	F	L	F	L	F
1yr	21.7	nm ^b	0.67		0.67		0.62	
2yr	27.4	nm	0.72		0.72		0.54	
cuh	5.6	nm	2.67		2.67		2.54	
uh	12.5	nm	2.02		2.02		1.19	
poc	12.1	nm	4.63		4.63		2.50	
lit	5.0	nm	1.18		8.47		0.89	
IA				nm		0.85		0.09
ME				nm		1.68		1.02
Block 6				nm		nm		0.86
Block 9b				nm		0.85		0.57
Block 22b				nm		1.12		0.47

842
843 a. 1yr = 1 year rough (57% dead material), 2yr = 2 year rough (73%), cuh=chipped understory
844 hardwood (96%), uh = understory hardwood (50%), poc = pocosin (27%), lit = pine litter
845 (100%). Field plots were a mixture of fuel types. Plot IA = 2yr, ME = 1yr, 2yr, cuh, uh, Block 6
846 = 54 year old longleaf pine fuels, Block 9b = 55 year old longleaf fuels, Block 22b = 8 year old
847 mixed longleaf, loblolly pine, and oak litter. See [47,48] for a detailed description of the
848 species composition of fuel type.

849 b. nm = not measured

850 c. Pre-burn loading not measured, value presented is actual estimated fuel consumption.

851

852 Table 4. Chemical species found in wildland fire smoke added to the PNNL spectral library [57].

1-Pentanal	3-Methylfuran	Hexadecane	Methyl-2-methylbutyrate
1-Penten-3-ol	3-Pentanol	Hexyl acetate	Myrcene
2,3-Butanedione	4-Penten-1-ol	Hydrogen peroxide	Naphthalene
2,3-Dimethylfuran	5-Nonanol	Isobutyric acid	Octanoic acid
2,5-Dimethylfuran	Acetol	Isocaproic acid	Pentadecane
2-Carene	Acrylamide	Isopentanal	Phenol
2-Methoxyphenol	Acrylic acid	Isopentyl acetate	α -Pinene
2-Methylfuran	Diacetone alcohol	Limonene	β -Pinene
2-Nonanone	Ethyl benzoate	Malonic acid	Propylene carbonate
2-Pentanone	Eucalyptol	Menthol	Syringaldehyde
2-Pentyl furan	Geraniol	Methyl acetoacetate	Valeric acid
2-Vinyl pyridine	Glycolaldehyde	Methyl glyoxal	Vinyl phenol
3-Carene	Glyoxal	Methyl vinyl ether	Vinyl toluene
3-Methoxyphenol			

853

854
855 Table 5. Estimated fuel moisture content and fire behavior indices for prescribed burns.

Variable ^a	Location ^b					
	FJ	FJ	CS	CL	CL	SR
Date	10/27/11	11/1/11	Percentile	2/10/10	2/11/10	Percentile
Air Temp. (°C)	26	18	61, 34	8	13	7, 16
Wind (kph)	14.8	9.8	86, 55	14.8	8.2	90, 51
1 hr (%)	5.4	4.8	53, 41	5.9	4.9	15, 6
10 hr	7.0	6.4	35, 16	8.1	6.8	21, 3
100 hr	13.4	12.9	20, 12	16.9	14.1	23, 5
1000 hr	20.1	19.5	65, 55	24.7	20	73, 30
IC	18	19	66, 68	30	28	93, 92
SC	7	7	50	30	18	95, 79
BI	31	31	49	85	69	95, 85
KBDI	184	208	44, 48	2	14	2, 6
ERC	21	24	48, 54	48	51	91, 96

856
857 a. Moisture content (in percent for 1, 10, 100 , 1000 hr timelag classes) and NFDRS indices
858 estimated using 1988 National Fire Danger Rating System [82]. IC = ignition component, SC =
859 spread component, BI = burning index ($\div 32.8$ = flame length (m)), KBDI = Keetch-Byram
860 Drought Index, ERC = energy release component.

861 b. FJ = Fort Jackson, CL = Camp Lejeune, CS = Carolina Sandhills National Wildlife Refuge,
862 SR = Sandy Run remote automated weather station. Percentile is 100(value of cumulative
863 distribution function of variable) [85].

864

Table 6. Relationship between laboratory and field derived emission factors for southern pine forest understories. The lab average was calculated from all of the southeastern fuel beds as described in [47] with carbon mass balance calculations resulting in slight changes [51] since more carbon was accounted for; field average was based on the fires in Table 2. Predicted lab EFs used mean field MCE of 0.936. See [51] for a complete description of the analysis approach used to derive the lab/field EF ratios.

Species	Lab _{meas}	Field _{meas}	Lab _{pred}	$\frac{\text{Lab}_{meas}}{\text{Field}_{meas}}$	$\frac{\text{Lab}_{pred}}{\text{Field}_{meas}}$
	(g kg ⁻¹)	(g kg ⁻¹)	(g kg ⁻¹)		
CO ₂	1738	1668		1.08	
CO	83.08	72.1		1.15	
MCE	0.932	0.936		1.00	
NO	1.78	0.88		2.02	
NO ₂	1.01	2.68		0.38	
NO _x as NO	2.44	2.55	2.42	0.96	0.95
CH ₄	2.79	3.02	2.61	0.93	0.86
C ₂ H ₂	0.18	0.30	0.18	0.61	0.59
C ₂ H ₄	0.90	1.16	0.85	0.77	0.73
C ₃ H ₆	0.35	0.40	0.32	0.86	0.80
HCHO	1.11	1.51	1.02	0.74	0.67
CH ₃ OH	1.02	1.05	0.93	0.97	0.88
HCOOH	0.25	0.09	0.23	2.65	2.40
CH ₃ COOH	2.20	1.32	2.03	1.67	1.54
C ₆ H ₅ OH		0.33			
C ₄ H ₄ O	0.20	0.20	0.17	0.99	0.87
C ₂ H ₄ O ₂		0.25			
HCN	0.29	0.59	0.26	0.49	0.43
NH ₃	0.75	0.50	0.72	1.50	1.43

892	HONO	0.38	0.52	0.38	0.73	0.73
893	PM _{2.5}	6.63	13.55	6.88	0.49	0.51
894						

895 Table 7 Emission ratios (C_i/C_T) converted to emission factors (EF, g kg^{-1}) for southeastern fuels not
 896 measured during the laboratory phase of this study. See [53] for a complete description. LaFTIR
 897 samples included burning stumps, dead/down debris, fatwood, and duff [48].

898		NC Bog soil		Longleaf duff		LaFTIR
899	<u>Species</u>	<u>C_i/C_T</u>	<u>EF</u>	<u>C_i/C_T</u>	<u>EF</u>	<u>EF Range</u>
900	CO ₂	72.2	1693	65.1	1207	1305-1554
901	CO	23.9	356.6	26.4	311.4	140-222
902	CH ₄	1.5	12.79	1.85	12.471	5.20-11.50
903	C ₂ H ₄	0.179	2.67	0.192	2.265	0.89-1.53
904	C ₂ H ₂	0.012	0.17	0.026	0.285	0.22-0.25
905	C ₃ H ₆	0.155	3.47	0.17	3.008	
906	HCHO	0.073	1.17	0.784	9.910	1.79-2.51
907	Glycolaldehyde	0.014	0.45	0.183	4.626	
908	Formic acid	0.063	1.54	0.316	6.125	
909	Acetic acid	0.231	7.39	0.855	21.614	1.03-3.84
910	CH ₃ OH	0.226	3.85	1.095	14.764	2.35-6.42
911	C ₆ H ₆ O	0.068	3.41	0.219	8.674	

912

913

914

915

916 Figure 1. Military installations (dark gray) containing fuel types measured as part of project. Light

917 gray area denotes the estimated historical range of longleaf pine [95]. Dashed line indicates

918 boundary of coastal plain physiographic province ("fall line"). X denotes fires with airborne and

919 ground samples, ● indicates airborne sample only. Longleaf range map available at

920 http://www.auburn.edu/academic/forestry_wildlife/lpsdl/mappingfiles/LLP_Range_Little1971_Sha

921 [pefile.zip](#)