An Industrial Ecology Approach to Municipal Solid Waste Management: I. Methodology

Raymond L. Smith^{a*}, Debalina Sengupta^b, Sudhakar Takkellapati^a, C.C. Lee^a

^aSustainable Technology Division, National Risk Management Research Laboratory, U.S. Environmental Protection Agency, 26 W. Martin Luther King Dr., Cincinnati, Ohio, USA

^bOak Ridge Institute for Science and Education (ORISE) Post-doctoral Fellow, 26 W. Martin Luther King Dr., Cincinnati, Ohio, USA

*Corresponding author: smith.raymond@epa.gov, 513-569-7161

Abstract

Municipal solid waste (MSW) can be viewed as a feedstock for industrial ecology inspired conversions of wastes to valuable products and energy. The industrial ecology principle of symbiotic processes using waste streams for creating value-added products is applied to MSW, with examples suggested for various residual streams. A methodology is presented to consider individual waste-to-energy or waste-to-product system synergies, evaluating the economic and environmental issues associated with each system. Steps included in the methodology include identifying waste streams, specific waste components of interest, and conversion technologies, plus steps for determining the economic and environmental effects of using wastes and changes due to transport, administrative handling, and processing. In addition to presenting the methodology, technologies for various MSW input streams are categorized as commercialized or demonstrated to provide organizations that are considering processes for MSW with summarized information. The organization can also follow the methodology to analyze interesting processes.

Keywords: Industrial ecology, Municipal solid waste, MSW, Energy, Sustainability

1. Introduction and Background

Frosch and Gallopoulos (1989) introduced the term industrial ecology. They called it “an industrial ecosystem. In such a system the consumption of energy and materials is optimized, waste generation is minimized and the effluents of one process... serve as the raw material for another process.” At about the same time Aryes (1989) wrote of an industrial metabolism that needed to have increased efficiency in the use of by-products. In this work the waste or by-products of interest are the streams of municipal solid waste generated by communities. A method is presented to analyze processes that perform industrial ecology, i.e., to view wastes as potential feedstocks and turn them into valuable products and/or energy with the intent of preserving valuable resources and producing less pollution.

The term waste is out of favor because it implies something to be discarded. A different way of thinking occurs by using the term sustainable materials management to capture the ideas of productivity and sustainability (U.S. EPA, 2014a). “Waste” does not recognize the potential uses of materials in different

contexts. The adage that “one man’s waste is another man’s treasure” clearly indicates that this is not a new idea. In this contribution a method is suggested for identifying and realizing the use of otherwise discarded materials.

To begin a study on using discards as valuable materials it makes sense to first identify the materials under consideration (Table 1) and the operations used to manage them. In this work the materials of interest fall under the category of municipal solid waste (MSW), a term which rose out of local communities caring for sanitation, avoiding epidemics, advancing public health, and maintaining refuse infrastructure, as well as a result of the circumstances of the times (Louis, 2004). MSW definitions are found in the Resource Conservation and Recovery Act (RCRA) as a subset of nonhazardous solid waste regulated under Subtitle D (U.S. EPA, 2011, 2014b). Implementation of MSW management is often administered by municipalities and operated by regional-based privately-owned facilities (Louis, 2004). MSW is only a portion of total solid waste. MSW refers to everyday items discarded from residences, businesses, and institutions, but is separate from construction debris, wastewater treatment waste, or other nonhazardous industrial process waste (U.S. EPA, 2013). Items that are part of MSW include corrugated boxes, food waste, plastic film, bottles, cans, newspaper and office paper, wood pallets, and yard waste, with a more complete list available from U.S. EPA (2013). These definitions also indicate that not everything sent to a non-hazardous landfill is defined as MSW.

Table 1. MSW average percentage waste types for U.S., and average amounts of each type for 100,000 people (U.S. EPA, 2014c).

Waste Type	Average U.S. Percentage	Tonnes per Year for 100,000 People	Millions of Pounds per Year for 100,000 People
Paper and paperboard	27.4%	19,834	43.73
Glass	4.6%	3,344	7.37
Metals	8.9%	6,469	14.26
Plastics	12.7%	9,177	20.23
Rubber and leather	3.0%	2,176	4.80
Textiles	5.7%	4,142	9.13
Wood	6.3%	4,573	10.08
Food, other	14.5%	10,530	23.21
Yard trimmings	13.5%	9,816	21.64
Other materials	1.8%	1,329	2.93
Misc. inorganic wastes	1.6%	1,127	2.49
Total	100.0%	72,517	159.87

Management of MSW in the past has focused on one specific solution, fit to community needs. There are benefits to simple and historically successful operations, but the systems are likely not optimal or flexible. More recently, integrated waste management is the standard (U.S. EPA, 1989). Communities consider how various strategies can fit into an overall plan to reduce waste generation and control costs and pollution. In addition, the decision process has changed. Gone are the days of deciding, announcing, and defending a (MSW) community facility. Today the process is open, with discussions on planning, site selection, facility design, construction, and operation. Besides obtaining necessary permits, one must communicate about risks and the sharing of benefits and impacts (U.S. EPA, 1995).

A plan for integrated solid waste management should include objectives; demographics regarding population and geography; recent waste data, including characteristics and amounts; projected waste assumptions; MSW options and monitoring of collection, transport, treatment, and disposal for various types of waste flows; and the evaluation of options which considers performance and the environmental, economic, and social aspects of sustainability (World Bank, 2012). Average data on MSW in the U.S. is collected and summarized regularly by the EPA (U.S. EPA 2014c), and an example waste analysis for a community of 100,000 people is presented in Table 1. Individual communities will have specific actual flows that can vary from the averages presented in Table 1. The actual flows are more important when specific processing of each is considered, where both amount and quality can be relevant criteria.

Processes for recycling, transforming, and treating (constituents of) MSW are available for those developing an integrated solid waste management plan. Figure 1 shows how MSW can move through various processes and achieve valuable outputs. The outputs include “Conserved Resources” that are a positive result of reducing and reusing, and other products listed down the right side of Figure 1. The circled numbers in the figure correspond to the waste management hierarchy (U.S. EPA, 2013). In part two of this work (Smith et al. 2015) the Waste-to-Energy process box in Figure 1 will be expanded and various transformations (not only incineration) will be evaluated.

The processes of Figure 1 (reporting statistics from U.S. EPA, 2014c) include MSW Generation, with the U.S. generating 251 million tons (228 million tonnes) of MSW per year. Composting, the aerobic biodegradation of part of the organic fraction of MSW (OFMSW), is performed on 8% of the total MSW. Recycling processes, which employ a waste as a feedstock for making products, are responsible for using 26% of the MSW generated. Waste-to-Energy incineration, the burning of wastes with energy recovery,

accounts for 12%. That leaves 54% of MSW going to Landfills. Also represented in Figure 1 are Recycling Centers / Transfer Stations / Material Recovery Facilities (MRF), which are needed depending on process and location specifics. Recycling Centers are normally drop off locations where recyclable materials are collected, grouped, and baled, although some processing like glass crushing can be done at Recycle Centers. Transfer Stations provide a flexible staging location where waste is consolidated into larger vehicles to reduce shipping costs. MRFs separate recyclables into uniform pools (Pinellas County, 2009). A further distinction can be made between Clean MRFs and Dirty MRFs, with a Clean MRF accepting single or dual stream recyclables, while a Dirty MRF separates the recyclables from the rest of the MSW.

For sustainable solutions to waste management, those interested in considering the socially acceptable processes and products represented in Figure 1 can perform analyses of the environmental and economic aspects. These analyses should be done with information relevant to the specific location and circumstances. Here, a method is presented which allows an industrial ecology perspective to be followed.

Figure 1. An outline of waste management options, showing products along the right side. The dashed line represents “Reduce / Reuse” as the products will not be seen unless accounted for in appropriate measures. Circles with numbers in them refer to the waste management hierarchy.

2. Industrial Ecology

The term industrial ecology considers a whole system of interested parties who create desired products and exchange their wastes to generate a positive system result. Industrial ecology appeals because it suggests that an industrial system can follow the principles of ecology in using wastes and doing so in an economic way. Both industrial and ecological systems have flows of mass and energy, and both can benefit from mutualism, where associations form to benefit both parties involved. Chertow (2007) suggests that industrial ecology systems most often emerge through self-organized symbiosis to reduce costs, enhance revenues, or expand a business, while Burstrom and Korhonen (2001) put forth a

concept of municipalities acting as both physical anchors that drive regional material and energy flows and institutional anchors that provide infrastructure, education, and support for industrial ecology.

A review of aspects of industrial ecology has been presented by Smith (2004), the most important of which in an MSW context is exchanging waste. Other researchers have explored waste management from an input-output perspective (Nakamura and Kondo, 2009), life cycle assessment (LCA) for a management district (Buttol et al. 2007), LCA for management scenarios (De Feo and Malvano, 2009), and LCA for MSW management in a large growing city (Hadi et al. 2012). Geng et al. (2010) studied the potential for MSW use (urban symbiosis) in the city of Kawasaki to avoid greenhouse gases and use of landfill space.

Exchanging waste suggests that all of the processors of Figure 1 produce desirable products and one or more streams of lesser value. In Figure 1, one can think of MSW Generation as producing desired compostable material and recyclable material, with a lesser value stream being the material sent to landfill. Composting produces compost and a lesser value stream of contaminants. The key idea here is to find the value in the material sent to landfill and in the compost contaminants. In these examples the landfill material might have heat value, and the compost contaminants might include glass or plastics of value. Table 2 shows processes of Figure 1, their product and residual streams, and potential uses for the residuals. Note that this raises an important aspect of terminology and one's point of view. One can speak about treating waste: that is changing its characteristics to minimize its threat to the environment. Or residuals can be perceived as potential process feedstocks. Changing one's point of view regarding this dichotomy of treating wastes or processing feedstocks is an important aspect of implementing industrial ecology. Without a perspective that sees value in residual streams they will be treated as waste. Seeing a stream as a potential feedstock provides an opportunity to exchange or process it for value.

Table 2. MSW processes, their products and residual streams, and potential uses for the residuals. Waste-to-Energy (WTE) processes listed are expanded in Smith et al. (2015). Listing as a use does not indicate regulatory acceptance.

MSW Process	Product(s)	Residuals	Use for Residual Stream
MSW Generation	Compostable and recyclable materials	Non-compostable, non-recyclable materials	Heat value, recycling research opportunity
Composting	Compost	Contaminants (glass, plastics)	Glass and plastic recycling, heat value
Recycling Center / Transfer Station / MRF	Separated recyclable materials	Non-compostable, non-recyclable materials	Heat value, recycling research opportunity
WTE – Lignocellulosic Fermentation	Ethanol	Lignin; CO ₂	Heat value, products; beverages, algal process
WTE – Gasification (with Conversion to Ethanol)	Syngas, then ethanol	Ash/slag	Construction materials
WTE – Anaerobic Digestion	Biogas, then power	Digestate slurry	Composting, fertilizer
WTE – Incineration	Power	Ash	Construction materials

The idea in listing processes, products, residuals, and uses for residuals in Table 2 is that each process leads to products and residuals, and the residuals may be useful in another context. While Table 2 presents examples, future possibilities are open. For instance, if CO₂ is used in algal fuel processes, where oil is removed from the algae for biodiesel production, then what opportunities exist for using the remaining parts of the algae? Is it only valuable as biomass, or could there be specific components or properties that make it more valuable?

One consideration to be aware of in considering new industrial ecology uses for MSW streams is the legitimacy of recycling. That is, to be certain that processes are done to be beneficial, not to treat waste. While it is acceptable to deal with MSW under RCRA Subtitle D, the residual flows may no longer be MSW. There are many EPA documents on the topic of legitimate recycling. The ideas behind determining whether processing is legitimate or “sham recycling” include the value of the new material and the relative amount of processing it takes to make it, whether there is a market for the material, and whether it is handled as other raw materials and products are (U.S. EPA, 2014d). The material has to be effective in its proposed use, and it should not be used in excess. If it is not clear whether a residual is still treated as MSW or if a specific process is not documented as legitimate recycling, it is likely a good idea to check with the appropriate regulator.

3. Similarities to Chemical Processes

When considering any of the potential uses of waste-generated feedstocks (i.e., residuals), a number of important issues must be addressed. Technology, feedstock supply, and product-offtake reliability are all crucial to developing a new process (Smith et al. 2013). This is so for chemical processes and waste-generated feedstock ones. Because of this similarity this discussion will parallel some aspects of chemical process design, with the understanding that the reader can apply them to waste-generated processes.

A common idea in chemical processes is to convert a low-cost feedstock into a higher-value product. This difference in price for the product minus the feedstock is known as a margin or spread. In the case of petroleum refining the spread is known as the crack spread (the price of defined products minus that of crude oil). For corn to ethanol conversions it is known as the grind margin (value of products minus feedstock and energy costs). Smith et al. (2013) proposed that the MSW field develop similar terms for the corresponding product-feedstock combinations. For instance, a pelletized material made of the organic fraction of MSW (OFMSW) could be made into Refuse-Derived Fuel (RDF). The term would then be a RDF-OFMSW spread. Another example would consider a more-fully processed product, e.g., biogas or ethanol, so one could have biogas-OFMSW and ethanol-OFMSW spreads. The benefit of a product-feedstock spread is that people familiar with the processes involved develop an understanding for when specific conversion processes will be profitable, because they also know the other costs for the process. A margin or spread can be combined with the other costs to quickly determine profitability. For example, the grind margin lets people in the biorefinery industry know when their processes will make money, and sometimes news articles report that a biorefinery has temporarily shut down, almost always during a time of low profitability.

The reliability of feedstock supply and product offtake is another critical aspect to consider. A chemical process or product-MSW process may have a profitable product-feedstock margin or spread, but that is of little value if the feedstock supply or ability to sell the product are unreliable. Companies developing new processes spend time and effort establishing reliable agreements to buy and sell what they need. An example where this was not established for MSW is the city of Harrisburg, PA, where reports indicate that expected MSW was not available for the constructed incinerator, leading to very large costs for the city (Luciew, 2011).

The technology for converting the feedstock to product also needs to be reliable. This need for reliable processes is addressed in the methodology below.

In many ways MSW processes are similar to chemical processes, however, they differ because there is a social benefit of dealing with MSW. Communities want MSW solutions, which can lead to processes being built. It can also mean community involvement in what is being done. Stakeholders might be interested in the number of truck trips, dust, odors, emissions, water-based releases, litter, nuisances, etc. As an example of how important these issues could potentially be, Mannies and LaCapra (2014) report that a landfill will pay \$4.6 million for odors due to an underground fire.

4. Methodology for Attaining Industrial Ecology

A systematic procedure is proposed here for considering industrial ecology uses of various MSW-related streams. The procedure starts with identifying waste streams for consideration. These may be obvious in a community that has specific existing processes and streams. Others may be less obvious as shown in Table 2, where potential uses for residuals were listed. Identifying a waste stream is a first step (Table 3). The economic value and environmental impacts need to be considered in future steps.

Within a stream it may be that only certain components are valuable. The evaluator of a new process for waste conversion to valuable products needs to identify these components, the amount, and the concentration. For instance, a valuable component in a waste stream may be at such a low concentration that its separation and processing prove to be uneconomical and/or negative for the environment. At this point it is important to know the amount and concentration. Evaluations will be done in future steps (Table 3).

Table 3. Steps in evaluating alternative waste processes

(1)	Identify waste streams
(2)	Identify waste components
(3)	Identify current baseline technologies, and identify alternative technologies for converting waste streams and components
(4)	Determine avoided economic costs and environmental impacts of using wastes (include avoided transport and administrative handling here)
(5)	Determine the value of the alternative products
(6)	Determine economic costs and environmental impacts of new transport steps
(7)	Determine economic costs and environmental impacts of new administrative handling
(8)	Determine economic costs and environmental impacts of sorting and pretreating wastes
(9)	Determine economic costs and environmental impacts of converting wastes
(10)	Determine economic costs and environmental impacts of purifying product streams
(11)	Adjust the economic costs and environmental impacts for residual wastes

The third step is knowing the new technology (i.e., the alternative) used to obtain the waste-generated product. There may be a number of potential technologies that can convert an identified waste stream into valuable products. Figure 2 shows current facilities / technologies that have been commercialized or demonstrated for converting waste streams into more valuable products, as well as technologies that can handle a waste component without using it productively. Knowing that a MSW component can be handled can be important so that overly cumbersome sorting and pretreatment steps are avoided. However, the reality may be that a process works better for uniform feedstocks, so it is important to understand the details.

The facilities / technologies shown in Figure 2 are described here, and footnotes have been provided for some of them in the figure. Specific Recycling Processes are tuned directly to recover a specific MSW component, e.g., aluminum. As described earlier, MRFs separate mixed streams into desirable lots for further processing. Anaerobic Digestion uses microorganisms to break down biodegradable material in the absence of oxygen into methane and other reaction products. Gasification reacts carbon-based waste at high temperatures by partial oxidation to produce a syngas of mostly carbon monoxide and hydrogen. The syngas can be further processed into ethanol by reaction chemistry or by biochemical routes. Fermentation as used here refers to the growth and reaction of microorganisms to convert sugars to ethanol and carbon dioxide. Agricultural plant-wall cellulosic material is currently being demonstrated / commercialized as the sugar-based feedstock for making ethanol, and this work assumes that yard waste is a reasonable approximation for this agricultural feedstock. Incineration is

the final technology represented, and it burns materials at very high temperature in oxygen (air), producing steam and/or electricity as final products.

Before finishing step three, it is important that the baseline technologies for comparison have been identified. This may be relatively simple, as it would be common to use the current facilities / technologies as a baseline. In the next step the costs and environmental releases of baseline activities will be used to create incentive values (i.e., the potential economic and environmental gains) for adopting new technologies.

Facility / Technology Type	Metals	Glass	Paper and Paperboard	Plastics "1" and "2"	Plastics "3" - "7"	Organics			Other Trash
						Food	Fats, Oils and Grease	Yard Waste	
Specific Recycling Process ^a	●	●	●	●	●				
Dirty MRF ^b	●	●	●	●	●	●	●	●	○
Clean MRF ^b	●	●	●	●					
WTE - Anaerobic Digestion ^c			○			●	●	●	
WTE - Gasification ^d			●	●	●			●	
WTE - Fermentation ^e								●	
WTE - Incineration ^f	○	○	●	●	●	●	●	●	●

a - Recycling processes have been developed for Plastics "3"- "7", but their use is uncommon. b - Depending on the MRF, various streams are separable or exit as residues, as depicted here for a Dirty MRF handling Other Trash, and one could have for example a Clean MRF that does separate out a stream of Plastics "3"- "7". c - Paper and Paperboard sent to Anaerobic Digestion can be processed, but the time for biodegradation may be too long to be considered useful. d - The use of Gasification for MSW is not common. e - Full scale fermentation processes have not attempted to use Yard Waste. f - Metals and Glass go through Incineration but are not used productively.

Figure 2. Technologies that can process / handle various portions of MSW. Black dots indicate commercialized processes; black open circles indicate technologies that can handle a feedstock without using it productively; grey dots indicate demonstrated processes (see footnotes). Plastics #1 and #2 refer to polyethylene terephthalate (used often in bottles) and high-density polyethylene (used in milk jugs, bottles, tubs, and some bags), respectively. Plastics #3 - #7 represent polyvinyl chloride, low-density polyethylene, polypropylene, polystyrene, and other.

The fourth step is to determine the avoided economic costs and potential environmental impacts by using the identified waste stream with its baseline costs and environmental releases. Also, the waste stream may have had baseline costs associated with it, for example, due to disposal, which is now

avoided. Any baseline transport or administrative costs associated with the waste may now be saved as well. The total potential value of processing the identified waste is the sum of the product value and the baseline savings. Note that these avoided costs may be short-lived, as the steps that follow from Table 3 may add them back in, although perhaps in different amounts (i.e., transport costs and environmental releases may have been saved based on the baseline case, but new transport costs and releases will be added in for the new process being considered).

The identified waste should be made into a new valuable product, so the fifth step involves calculating the amount of product and its value to estimate a total product value. The sum of avoided costs from step four and the product value from step five provide an overall economic incentive for considering an alternative process. If the total value is not large enough then the analysis can be stopped at this point, and different alternatives or variations can be considered. As alternative costs are added in the following steps the analysis can be stopped at any point where the value is insufficient.

Potential environmental impacts may also be avoided due to not processing waste in the baseline method. There are a number of ways to account for these impacts. The simplest is to keep track of the inventory of emissions of various types: e.g., VOC, NO_x, SO_x, CO, CO₂, etc. One can also keep track of potential environmental impacts using impact assessment methods, such as the Tool for the Reduction and Assessment of Chemical and other Impacts (TRACI) (Bare et al. 2003) or the Waste Reduction Algorithm (Young and Cabezas, 1999). There may be many ways in which impacts could be reduced. For instance, various parts of the common production chain of the generated product may be avoided, because the waste-generated product is displacing the need to make the product by the common method. Also, various transportation processes may be avoided, leading to less pollution. Also, the original waste will no longer be causing potential environmental impacts. All of these should be considered in developing the total avoided potential impacts for an alternative. At this point the values determined for potential environmental impact reduction are as large as possible, as future steps will add impacts. If the potential impact reduction of the alternative is not large enough to incentivize processing the waste at this point, then the process is not worthwhile, and other alternatives or variations should be considered.

Among the benefits of processing waste into useable forms could be the reduction in landfill space used. If this is important, then the cost of new space in a landfill could be added to the savings for not sending materials to a landfill. Another benefit of not landfilling and thus not creating landfill gas is the reduction in emissions of these greenhouse gases (although they can be captured). This highlights the

idea that people need to recognize all of the costs of MSW. For example, if people do not experience the costs of landfill operation, closure, cleanup, and pollution, they may not understand the need to reduce, reuse, recycle, or find other uses for materials. The complexity of the analysis is also highlighted with this example because landfilling with gas recovery presents a different baseline for analysis as compared to landfilling without recovery.

Step six of the procedure adds costs and potential environmental impacts due to new transport done because of the processing of the waste-generated product. These transport distances could be shorter or longer than the original, and they may involve multiple collections in the community.

If there are new administrative handling procedures involved, then step seven is used to add additional costs and/or environmental impacts.

The processing of waste is accounted for in steps 8-10, where sorting and pretreating waste, converting, and purifying product steps occur. These are technical processes which require an understanding of the costs, reliability, form of final product, etc. The importance of these steps should not be underestimated. Smith et al. (2015) provide examples for WTE technologies.

Finally, if a residual waste is generated at the end of processing, the costs and environmental impacts of this residual need to be included. This could require knowledge of the components in the residual stream and their concentrations. One would likely approximate how these will be dealt with and approximate costs and environmental impacts for them. The total costs and impacts accounted for in steps 6-11 should be summed and compared to the potential avoided costs and impacts developed through step 5. Higher economic values and reductions in environmental releases indicate an alternative for further detailed study.

5. Discussion

In addition to providing a method for analyzing processes, it could be valuable to discuss the technologies and MSW components presented in Figure 2. For details people will have to study each of these more closely, but some generalizations can be pointed out. For instance, a Dirty MRF and Incineration can handle all types of MSW. This does not mean that they are issue free, but they do not require (many) pre-treatment steps and MSW can be delivered directly to these facilities. The Specific Recycling Processes are specific to a material, and so separations need to be very selective.

Fermentation to ethanol is also selective, in that the current systems are using corn stover as a feedstock, so using yard waste is an extrapolation. However, biofuels like ethanol might have a higher value depending on subsidies / incentives. Anaerobic Digestion and Gasification use a small variety of feedstocks, so some separation is required. Also, these technologies and Fermentation benefit from shredding their feedstocks into a form of Refuse Derived Fuel (RDF) which eases processing.

Another way of considering Figure 2 is through a consideration of the MSW components in the columns. For instance, Metals and Glass can only be fed to certain facilities. Food scraps and Fats, Oils, and Grease are likewise limited in terms of technologies. Plastics and Yard Waste find more acceptable facilities, and Paper and Paperboard the most. However, without understanding the technologies, it may not be clear that the products of these different “acceptable technologies” are so varied. While a Dirty MRF might separate some (inadvertently discarded) Yard Waste into an organic stream, Anaerobic Digestion will process Yard Waste into useful methane. Similarly, a Clean MRF might separate Plastics “1” and “2”, a Gasification process might turn them into syngas and other products, while a Specific Recycling Process could convert them into other useful solid products. Thus, Figure 2 should be used as a starting point for considering technologies and various MSW streams.

As for Plastics “3” – “7”, they can be recycled, but the markets are not largely developed (Association of Postconsumer Plastic Recyclers, 2014). For instance, polyvinyl chloride (PVC) (“3”) is made into some lumber-like materials. Low-density polyethylene (LDPE) (“4”) can be made into trash can liners, etc. Polypropylene (PP) (“5”) has recycled products like brooms, brushes, casings, etc. Polystyrene (PS) (“6”) can be recycled for egg cartons, foam packing, etc. While recycling processes exist, it could be useful to look at how small businesses consider undertaking such an endeavor (Association of Small Business Development Centers, 1998). This may be useful in general, rather than only for plastics.

6. Conclusions

This work has presented a methodology through the approach of industrial ecology to view residual streams as having potential to be converted into useable products and energy. The residual streams include MSW, compost residuals, recycling residuals, etc. The idea being that each process generates a residual stream that can have a further use. The methodology presented describes an approach to account for costs and potential environmental impacts for alternatives that convert residuals into useful products and energy. The method of accounting first identifies the benefits of conversion and then adds

process costs and potential environmental impacts from the various steps of processing. Should this sequence of steps lead to higher costs or higher environmental impacts for the alternative as compared to the baseline the analysis can be stopped, as the alternative process is not beneficial. When a process is eliminated, other alternatives or variations can be considered.

Acknowledgement

This project is supported in part by an appointment to the Research Participation Program for the U.S. Environmental Protection Agency, Office of Research and Development administered by the Oak Ridge Institute for Science and Education through an interagency agreement between the U.S. Department of Energy and U.S. Environmental Protection Agency.

Disclaimer

The views expressed in this article are those of the authors and do not necessarily reflect the views or policies of the U.S. Environmental Protection Agency.

References

- Aryes, R.U. (1989). "Industrial Metabolism," in *Technology and Environment*. Ausubel, J.H., Sladovich, H.E., eds. National Academies Press.
- Association of Postconsumer Plastic Recyclers (2014). Websites on various resins. <http://www.plasticsrecycling.org/> accessed on 8/20/14.
- Association of Small Business Development Centers (1998). *Writing Business Plans for Recycling Enterprises: Plastics, Glass, or Rubber*. Arlington, VA. <http://www.epa.gov/wastes/conserve/tools/rmd/docs/nevada.pdf> accessed on 8/20/14.
- Bare, J.C., Norris, G.A., Pennington, D.W., and McKone, T. (2003). "The Tool for the Reduction and Assessment of Chemical and Other Environmental Impacts," *J. Ind. Ecol.*, 6(3-4), 49-78.
- Burstrom, F., Korhonen, J. (2001). "Municipalities and Industrial Ecology: Reconsidering Municipal Environmental Management," *Sustainable Development*, 9, 36-46.
- Buttol, P., Masoni, P., Bonoli, A., Goldoni, S., Belladonna, V., Cavazzuti, C. (2007). "LCA of Integrated MSW Management Systems: Case Study of the Bologna District," *Waste Management*, 27(8), 1059-1070.
- Chertow, M.R. (2007). "'Uncovering' Industrial Symbiosis," *J. Ind. Ecol.*, 11(1), 11-30.

- De Feo, G., Malvano, C. (2009). "The Use of LCA in Selecting the Best MSW Management System," *Waste Management*, 29(6), 1901-1915.
- Frosch, R.A., Gallopoulos, N.E. (1989). "Strategies for Manufacturing," *Scientific American*, 261(3), 144-152.
- Geng, Y., Tsuyoshi, F., Chen, X. (2010). "Evaluation of Innovative Municipal Solid Waste Management through Urban Symbiosis: A Case Study of Kawasaki," *J. Clean. Prod.*, 993-1000.
- Hadi, P.A., Onoda, H., Nagata, K. (2012). "Integrated LCA for Municipal Solid Waste Management in Developing Country," in *Design for Innovative Value Towards a Sustainable Society*, Proceedings of EcoDesign 2011: 7th International Symposium on Environmentally Conscious Design and Inverse Manufacturing, Matsumoto, M., Umeda, Y., Masui, K., Fukushige, S., eds. Springer.
- Louis, G.E. (2004), "A Historical Context of Municipal Solid Waste Management in the United States," *Waste Manag. Res.*, 22, 306-322.
- Luciew, J. (2011). "Harrisburg incinerator: History of the project and how taxpayers got saddled with the debt," *Patriot-News*, http://www.pennlive.com/midstate/index.ssf/2011/07/harrisburg_incinerator_history.html, accessed on 8/18/14.
- Mannies, J. and LaCapra, V. (2014). "Bridgeton Landfill Owner to Pay More than \$4.6 Million to Neighboring Homeowners," *St. Louis Public Radio*, <http://news.stlpublicradio.org/post/bridgeton-landfill-owner-pay-more-46-million-neighboring-homeowners>, accessed on 8/18/14.
- Nakamura, S. and Kondo, Y. (2009). *Waste Input-Output Analysis: Concepts and Application to Industrial Ecology*. Springer.
- Pinellas County (2009). *Materials Recovery Facility Technology Review*. St. Petersburg, FL.
- Smith, R.L. (2004). "Hierarchical Design and Evaluation of Processes to Generate Waste-Recycled Feeds," *Ind. Eng. Chem. Res.*, 43, 2508-2515.
- Smith, R.L., Sengupta, D., Takkellapati, S., and Lee, C.C. (2013). "The Future for Municipal Solid Waste: Research and Potential Technologies," presentation at MSW Technologies Workshop, Columbus, OH, March 27, 2013.
- Smith, R.L., Sengupta, D., Takkellapati, S., and Lee, C.C. (2015). "An Industrial Ecology Approach to Municipal Solid Waste Management: II. Case Studies for Recovering Energy from the Organic Fraction of MSW," *Resources, Conservation and Recycling*, submitted.
- U.S. EPA (1989). *Decision-Makers Guide to Solid Waste Management, Volume I*, EPA-530-SW-89-072, Office of Solid Waste and Emergency Response, Washington, DC.
- U.S. EPA (1995). *Decision-Makers' Guide to Solid Waste Management, Volume II*, EPA-530-R-95-023, Office of Solid Waste and Emergency Response, Washington, DC.
- U.S. EPA (2011). *RCRA Orientation Manual 2011*. EPA530-F-11-003. Office of Solid Waste and Emergency Response, Washington, DC.

U.S. EPA (2013). *Municipal Solid Waste in the United States: 2011 Facts and Figures*. EPA-530-R-13-001, Office of Solid Waste, Washington, DC.

U.S. EPA (2014a). Sustainable Materials Management, <http://www.epa.gov/smm/>, accessed on 5/27/14.

U.S. EPA (2014b). Non-hazardous Waste Regulations, <http://www.epa.gov/osw/laws-regs/regs-non-haz.htm> , accessed on 6/12/14.

U.S. EPA (2014c), *Municipal Solid Waste Generation, Recycling, and Disposal in the United States: Facts and Figures for 2012*, EPA-530-F-14-001, Office of Solid Waste and Emergency Response, Washington, DC.

U.S. EPA (2014d). Industrial Hazardous Waste Recycling, <http://www.epa.gov/osw/hazard/recycling/industrial.htm> accessed on 8/18/14.

World Bank (2012). *What a Waste: A Global Review of Solid Waste Management*. Urban Development and Local Government Unit of the Sustainable Development Network, Washington, DC; p. 25.

Young, D.M. and Cabezas, H. (1999) "Designing Sustainable Processes with Simulation: The Waste Reduction (WAR) Algorithm," *Comput. Chem. Eng.*, 23, 1477.