Brain-computer interfaces for dissecting cognitive processes underlying sensorimotor control

Matthew D. Golub^{a,c}, Steven M. Chase^{b,c}, Aaron P. Batista^{c,d,e}, Byron M. Yu^{a,b,c,*}

^a*Department of Electrical and Computer Engineering, Carnegie Mellon University*

^b*Department of Biomedical Engineering, Carnegie Mellon University*

^c*Center for the Neural Basis of Cognition, Carnegie Mellon University & University of Pittsburgh*

^d*Department of Bioengineering, University of Pittsburgh*

^e*Systems Neuroscience Institute, University of Pittsburgh*

Abstract

Sensorimotor control engages cognitive processes such as prediction, learning, and multisensory integration. Understanding the neural mechanisms underlying these cognitive processes with arm reaching is challenging because we currently record only a fraction of the relevant neurons, the arm has nonlinear dynamics, and multiple modalities of sensory feedback contribute to control. A brain-computer interface (BCI) is a well-defined sensorimotor loop with key simplifying advantages that address each of these challenges, while engaging similar cognitive processes. As a result, BCI is becoming recognized as a powerful tool for basic scientific studies of sensorimotor control. Here, we describe the benefits of BCI for basic scientific inquiries and review recent BCI studies that have uncovered new insights into the neural mechanisms underlying sensorimotor control.

Keywords: brain-computer interfaces, sensorimotor control

Introduction

Successful sensorimotor control requires the coordination of multiple cognitive processes. On a moment-by-moment basis, the brain integrates various sources of sensory information [1–3], selects and plans upcoming movements [4–6], internally predicts the consequences of motor commands [7], and adapts to compensate for changes

*Corresponding author

Email address: byronyu@cmu.edu (Byron M. Yu)

in the body and environment [8, 9]. Addressing the complexity of these interconnected processes poses a formidable challenge for neuroscientists seeking a more complete understanding of the neural mechanisms underlying sensorimotor control.

A common paradigm for studying sensorimotor control is arm reaching (Fig. 1, *left*). Even the simplest of arm movements emerge from a complex set of neural, muscular and skeletal systems. Movement generation involves multiple distinct cortical areas that project to the spinal cord, numerous striatal and cerebellar loops, and several brainstem and thalamic nuclei [10]. However, in typical experiments, we can monitor only a tiny fraction of the hundreds of thousands of neurons that project to motoneuron pools, and it is often unknown whether the recorded neurons project to the spinal cord or affect behavior only indirectly. As a result, it is difficult to causally attribute behavioral changes to specific changes in the recorded neural activity. **Furthermore, the arm is a multi-jointed structure actuated by dozens of muscles [11], and because of these complexities, the arm’s nonlinear dynamics are not typically measured in studies of arm reaching.** In addition, sensory feedback about the arm movement is carried through multiple sensory modalities, including vision and proprioception, that have different latencies and need to be combined [12]. **Although visual feedback about the arm can be readily manipulated [8, 12–14], proprioceptive feedback cannot be decoupled from movement as easily [15].**

How can we obtain a more complete understanding of the cognitive processes underlying sensorimotor control in light of this daunting complexity? Perhaps we could gain traction if we could simultaneously record neural activity from multiple brain areas in the motor system, including all neurons that directly drive movement; if we could identify and reversibly reprogram the precise mathematical relationship between neural activity and movement; and if we could independently alter different modalities of sensory feedback.

In this review, we describe how brain-computer interfaces (BCIs) provide a simplified, well-defined, and easily-manipulated experimental paradigm that facilitates the basic scientific investigation of the cognitive processes engaged during sensorimotor control (Fig. 1, *right*). A BCI creates a direct mapping between recorded neural activity and the movement of a device, such as a computer cursor (or robotic limb)

[16][17**][18–22][23**] and substantially simplifies the complexities described above (Table 1). Although neurons throughout the brain can indirectly influence movement, only the activities of experimenter-chosen *output* neurons directly drive BCI cursor
40 movements. Thus, all aspects of behavior must be expressed in the activity of these recorded output neurons, and it is possible to causally interpret the role of each neuron in behavior since the mapping between neural activity and cursor movement is completely known to **and specified by** the experimenter. Cursor dynamics can be defined by the experimenter to be linear, and they can be altered as desired. Furthermore, we
45 can flexibly manipulate the sensory feedback because proprioceptive feedback is not hard-wired to cursor movement. As a result of these simplifications, we and others have begun to leverage BCI as a powerful experimental paradigm for addressing basic scientific questions about sensorimotor control. Although similar concepts apply to EEG- (e.g., [24]) and ECoG-based (e.g., [25]) BCI, we focus on intracortical BCI in
50 this review. Previous reviews have described use of BCI for addressing scientific questions [26–28]. Here, we focus on the key simplifications offered by BCI and describe the scientific insights that have emerged by leveraging each simplification.

Monitoring all neurons that directly drive movement

In arm reaching studies, it is typically not possible to attribute every aspect of be-
55 havior to specific features of the recorded neural activity because there are unrecorded neurons that can directly drive behavior. In contrast, for BCI, all neurons that directly drive behavior are recorded, by construction. Thus, it is possible to *causally* attribute changes in behavior to the activity of specific neurons.

This property of BCI is particularly well exemplified by single-unit operant con-
60 ditioning studies. In operant conditioning, the subject’s task is to learn to volitionally modulate neural activity to specified levels using real-time visual [29, 30] or auditory [31**] feedback. The visual or auditory feedback represents the BCI ‘behavior’. Operant conditioning is particularly valuable for studying (internal) cognitive processes because it allows the experimenter to manipulate neural activity that has, under ordi-
65 nary circumstances, only an indirect relationship to externally-measurable variables.

This approach was pioneered by Fetz [30] in the motor cortex, and later adopted by a large body of studies [32–37]. More recently, studies have demonstrated the importance of operant conditioning for studying the neural substrates of cognitive processes, including spatial [31**] and object-based [38] attention, that are involved in sensorimotor control. In particular, Schafer and Moore [31**] found that volitional changes in frontal eye field (FEF) activity are associated with selective visual attention.

Distinguishing between output and non-output neurons

Beyond monitoring all neurons that directly drive behavior in a BCI (output neurons), it is also possible to simultaneously monitor additional neurons that are not explicitly mapped to behavior (termed *non-output* neurons). This is advantageous for investigating whether and how the activity of output neurons of sensorimotor control differ from that of non-output neurons. For example, it may be that the non-output neurons support internal cognitive processes that enable output neurons to produce activity that is suitable for driving behavior. In arm reaching studies, it can be a daunting task to identify which motor cortical (M1) neurons project directly to motoneurons that innervate muscles [39–41]. In contrast, in BCI, the experimenter simply designates which recorded neurons are output versus non-output and examines neural activity as the subject learns to use the BCI over time.

This property of BCI has been exploited by comparing the activity of output and non-output neurons in M1. Output neurons have been observed to show stronger task-related modulation than non-output neurons [42*][43, 44][45*]. This finding does not imply that the non-output neurons stay silent or at baseline activity levels. Rather, the non-output neurons typically change their activity together with the output neurons [46], albeit with weaker task-related modulation. It is also possible to record non-output neurons outside of M1. Carmena and colleagues recorded non-output neurons in the striatum and found that corticostriatal plasticity is necessary for BCI learning [47] and is specific to the output neurons in M1 [48**].

Defining a simple mapping

In arm reaching studies, we typically do not know the exact mapping between neu-
95 ral activity recorded in the brain and arm movement. Even if we could identify the
mapping, it would likely involve non-linear dynamics due to spinal [49] and muscle
[11] properties, making it difficult to analyze. With BCI, the experimenter specifies
exactly how the activity of the output neurons maps to cursor movement. The mapping
can be chosen to define linear dynamics, for example:

$$\mathbf{x}_t = \mathbf{A}\mathbf{x}_{t-1} + \mathbf{B}\mathbf{u}_t \quad (1)$$

100 where $\mathbf{x}$ is the cursor movement (e.g., velocity), $\mathbf{u}$ is the activity of the output neurons,
and $\mathbf{A}$ and $\mathbf{B}$ are the mapping parameters. Commonly-used BCI mappings, including
the Kalman filter, optimal linear estimator and population vector algorithm, can be
expressed in this form.

Studies have exploited the linearity of the BCI mapping to elucidate the neural
105 mechanisms of cognitive processes underlying sensorimotor control. It is widely be-
lieved that we form internal models of our effectors, which enable internal prediction
to compensate for sensory feedback delays and selection of appropriate neural activity
patterns[8]. We found that cursor movement errors can be explained by a mismatch be-
tween the internal model and the BCI mapping [50**]. By using a linear BCI mapping,
110 we could focus on the family of linear internal models, which facilitated the identifi-
cation of internal models from neural activity. Another convenient property of a linear
BCI mapping is that one can exactly identify its *null space*—the space of neural activity
changes that do not affect movement [51]. Analyses of neural variability in this null
space have led to insights into sensorimotor learning [45*] and error correction [52].

115 Changing the BCI mapping

A key feature of sensorimotor control is the ability to learn, adapt, and refine motor
skills over time. This ability is mediated by a suite of learning processes that operate
in parallel to maintain proficient control [14]. Our understanding of these learning

processes has relied largely on studies of arm movements [8], hand movements [53],
120 and muscle activity [54–56]. Disentangling the neural basis of these processes has
proven challenging [57–59], primarily because it is difficult to interpret the behavioral
relevance of adaptive changes in neural activity if the causal role of those neurons in
generating behavior is not known [60].

BCI can help to overcome this difficulty. Just as the experimenter can define the
125 BCI mapping from neural activity to behavior, he or she can also redefine the mapping
as desired throughout an experiment and observe whether the subject is able to learn
to use the new mapping. Importantly, learning-related changes in behavior can then
be causally attributed to specific changes in the recorded neural activity. The mapping
can be redefined by shuffling its weights [16] or by altering the weights in a structured
130 fashion [46, 61, 62][23**]. These studies have found that the brain is able to attribute
behavioral errors to individual neurons responsible for the errors [61, 62], and that the
underlying network structure shapes learning [23**]. The latter study [23**] suggests
that cognitive tasks which require novel population activity patterns (i.e., additional
dimensions of the population activity [63]) can be hard to learn.

135 **Flexibly manipulating sensory feedback**

Executing a reaching movement requires estimating the current state of the arm
by combining visual, proprioceptive, and other sensory information. Understanding
multisensory integration is challenging because each sensory modality has a different
coordinate frame and processing delay, and the subject weights the different modalities
140 based on their reliability [2]. To understand how different sensory modalities contribute
to sensorimotor control, one would like to be able to manipulate or turn off each sensory
modality independently. Visual feedback is relatively easy to manipulate [8, 12–14].
Proprioception, however, is tied to the arm, making it difficult to manipulate or turn off
in a way that still allows the subject to perform the task [15].

145 With BCI, the experimenter can independently manipulate visual and propriocep-
tive feedback, thereby facilitating the study of multisensory integration during sensori-
motor control. Because BCI movements are not tied to arm movements, it is possible

to perform BCI control with the arm stationary, moving in concert with the cursor, or moving independently of it [64, 65]. This property of BCI was leveraged to study the influence of proprioceptive feedback in M1 [17**]. The study found that BCI control was more accurate when the arm was moving in concert with the cursor, thereby demonstrating the importance of informative proprioceptive feedback for M1. In a related study, Dadarlat et al. [66*] recently showed that microstimulation of primary somatosensory cortex can induce artificial proprioception, and that the sensorimotor system can optimally integrate this information with noisy visual feedback.

Conclusions

Science proceeds through the use of model systems: to understand an important but complex aspect of the natural world, we carefully select reduced systems that are experimentally tractable and that bear an important relation to the full system. Insights can emerge from the study of the simpler system that apply directly in the complex system, or at least help to crack open new avenues to understanding the more daunting problem [67]. An important question is whether BCI is an appropriate reduced system for studying sensorimotor control. BCI cursor control performance is approaching arm reaching performance [20], thereby enabling well-controlled scientific studies. In addition, well-established cognitive processes present during arm reaching, such as internal forward prediction [50**], learning [16][23**], and multisensory integration [17**], are also engaged during BCI control. Nevertheless, it remains an open question whether the neural mechanisms underlying these cognitive processes are conserved between arm reaching and BCI control. Current findings suggest that there is at least some overlap in the brain areas involved in native motor control and BCI control. Coordination between the cortex and the basal ganglia appears to be required for motor learning in both native motor [68, 69] and BCI [47][48**] control. Although the role of cerebellar circuits in BCI control has not yet been explicitly demonstrated, BCI subjects adapt to visuomotor rotations [62] and form internal models [50**], both of which are believed to be primarily cerebellar-dependent processes [8]. Due to the similarity of the cognitive processes and brain areas involved in native motor and BCI control, we view BCI

as a stepping stone toward understanding the full native sensorimotor control system. The BCI paradigm, being a reduced system, offers vastly improved accessibility and manipulability, without simplifying away the complexities of brain processing that we
180 wish to study.

As with any reduced system, BCI does have certain limitations for studying the full system. There are aspects of sensorimotor control that are difficult to study with a cortical BCI because they occur “downstream” of the particular set of neurons used for BCI control (e.g., spinal cord mechanisms). Also, it is an open question how the ab-
185 sence of some natural sensory feedback mechanisms (e.g., touch) shapes the cognitive processes being studied during BCI control. Despite its limitations, BCI studies have made important headway toward elucidating the neural mechanisms of attention, prediction, learning, and multisensory integration in the context of sensorimotor control. Sensorimotor processing is just one manifestation of cognition, and the BCI approach
190 may eventually be harnessed to yield insight into the many forms of cognition of which we human beings are capable.

ACKNOWLEDGEMENTS

This work was supported by NSF IGERT Fellowship (M.D.G.), NIH NICHD CR-CNS R01-HD071686 (B.M.Y. and A.P.B.), NIH NINDS R01-NS065065 (A.P.B.), the
195 Craig H. Neilsen Foundation (B.M.Y., A.P.B., and S.M.C.), Burroughs Wellcome Fund (A.P.B.), the Curci Foundation (S.M.C.), PA Department of Health Research Formula Grant SAP#4100057653 under the Commonwealth Universal Research Enhancement program (S.M.C.), and NIH P30-NS076405 (Systems Neuroscience Institute).

References

- [1] B. E. Stein, T. R. Stanford, Multisensory integration: current issues from the perspective of the single neuron, *Nature Reviews Neuroscience* 9 (4) (2008) 255–266.

- 205 [2] P. N. Sabes, Sensory integration for reaching: models of optimality in the context of behavior and the underlying neural circuits, *Progress in brain research* 191 (2011) 195.
- [3] C. R. Fetsch, G. C. DeAngelis, D. E. Angelaki, Bridging the gap between theories of sensory cue integration and the physiology of multisensory neurons, *Nature Reviews Neuroscience* 14 (6) (2013) 429–442.
- 210 [4] S. P. Wise, The primate premotor cortex: past, present, and preparatory, *Annual review of neuroscience* 8 (1) (1985) 1–19.
- [5] P. Cisek, J. F. Kalaska, Neural mechanisms for interacting with a world full of action choices, *Annual review of neuroscience* 33 (2010) 269–298.
- 215 [6] K. V. Shenoy, M. Sahani, M. M. Churchland, Cortical control of arm movements: a dynamical systems perspective, *Annual review of neuroscience* 36 (2013) 337–359.
- [7] D. W. Franklin, D. M. Wolpert, Computational mechanisms of sensorimotor control, *Neuron* 72 (3) (2011) 425–442.
- 220 [8] R. Shadmehr, M. A. Smith, J. W. Krakauer, Error correction, sensory prediction, and adaptation in motor control, *Annual review of neuroscience* 33 (2010) 89–108.
- [9] D. M. Wolpert, J. Diedrichsen, J. R. Flanagan, Principles of sensorimotor learning, *Nature Reviews Neuroscience* 12 (12) (2011) 739–751.
- 225 [10] G. E. Alexander, M. R. DeLong, P. L. Strick, Parallel organization of functionally segregated circuits linking basal ganglia and cortex, *Annual review of neuroscience* 9 (1) (1986) 357–381.
- [11] S. S. Chan, D. W. Moran, Computational model of a primate arm: from hand position to joint angles, joint torques and muscle forces, *Journal of neural engineering* 3 (4) (2006) 327.

- 230 [12] S. J. Sober, P. N. Sabes, Flexible strategies for sensory integration during motor planning, *Nature neuroscience* 8 (4) (2005) 490–497.
- [13] K. P. Körding, D. M. Wolpert, Bayesian integration in sensorimotor learning, *Nature* 427 (6971) (2004) 244–247.
- [14] J. W. Krakauer, P. Mazzoni, Human sensorimotor learning: adaptation, skill, and
235 beyond, *Current opinion in neurobiology* 21 (4) (2011) 636–644.
- [15] J. Gordon, M. F. Ghilardi, C. Ghez, Impairments of reaching movements in patients without proprioception. I. Spatial errors, *Journal of Neurophysiology* 73 (1) (1995) 347–360.
- [16] K. Ganguly, J. M. Carmena, Emergence of a stable cortical map for neuroprosthetic control, *PLoS biology* 7 (7) (2009) e1000153.
240
- [17] A. J. Suminski, D. C. Tkach, A. H. Fagg, N. G. Hatsopoulos, Incorporating feedback from multiple sensory modalities enhances brain–machine interface control, *The Journal of neuroscience* 30 (50) (2010) 16777–16787.
- [18] M. Hauschild, G. H. Mulliken, I. Fineman, G. E. Loeb, R. A. Andersen, Cognitive
245 signals for brain–machine interfaces in posterior parietal cortex include continuous 3D trajectory commands, *Proceedings of the National Academy of Sciences* 109 (42) (2012) 17075–17080.
- [19] L. R. Hochberg, D. Bacher, B. Jarosiewicz, N. Y. Masse, J. D. Simeral, J. Vogel, S. Haddadin, J. Liu, S. S. Cash, P. van der Smagt, et al., Reach and grasp by people
250 with tetraplegia using a neurally controlled robotic arm, *Nature* 485 (7398) (2012) 372–375.
- [20] V. Gilja, P. Nuyujukian, C. A. Chestek, J. P. Cunningham, B. M. Yu, J. M. Fan, M. M. Churchland, M. T. Kaufman, J. C. Kao, S. I. Ryu, et al., A high-performance neural prosthesis enabled by control algorithm design, *Nature neuroscience* 15 (12) (2012) 1752–1757.
255

- [21] J. L. Collinger, B. Wodlinger, J. E. Downey, W. Wang, E. C. Tyler-Kabara, D. J. Weber, A. J. McMorland, M. Velliste, M. L. Boninger, A. B. Schwartz, High-performance neuroprosthetic control by an individual with tetraplegia, *The Lancet* 381 (9866) (2013) 557–564.
- 260 [22] P. J. Ifft, S. Shokur, Z. Li, M. A. Lebedev, M. A. Nicolelis, A brain-machine interface enables bimanual arm movements in monkeys, *Science translational medicine* 5 (210) (2013) 210ra154–210ra154.
- [23] P. T. Sadtler, K. M. Quick, M. D. Golub, S. M. Chase, S. I. Ryu, E. C. Tyler-Kabara, B. M. Yu, A. P. Batista, Neural constraints on learning, *Nature* 512 (2014) 423–426.
- 265 [24] J. R. Wolpaw, D. J. McFarland, Control of a two-dimensional movement signal by a noninvasive brain-computer interface in humans, *Proceedings of the National Academy of Sciences of the United States of America* 101 (51) (2004) 17849–17854.
- 270 [25] A. G. Rouse, J. J. Williams, J. J. Wheeler, D. W. Moran, Cortical adaptation to a chronic micro-electrocorticographic brain computer interface, *The Journal of Neuroscience* 33 (4) (2013) 1326–1330.
- [26] A. L. Orsborn, J. M. Carmena, Creating new functional circuits for action via brain-machine interfaces, *Frontiers in computational neuroscience* 7 (157) (2013) 1–10.
- 275 [27] J. D. Wander, R. P. Rao, Brain–computer interfaces: a powerful tool for scientific inquiry, *Current opinion in neurobiology* 25 (2014) 70–75.
- [28] K. A. Moxon, G. Foffani, Brain-Machine Interfaces beyond Neuroprosthetics, *Neuron* 86 (1) (2015) 55–67.
- 280 [29] J. Olds, Operant conditioning of single unit responses (Operant conditioning of single unit responses, considering hippocampus and midbrain tegmentum), in: *International Congress of Physiological Sciences, 23rd, Tokyo, Japan, 87*, 372–380, 1965.

- 285 [30] E. E. Fetz, Operant conditioning of cortical unit activity, *Science* 163 (3870) (1969) 955–958.
- [31] R. J. Schafer, T. Moore, Selective attention from voluntary control of neurons in prefrontal cortex, *Science* 332 (6037) (2011) 1568–1571.
- [32] A. R. Wyler, M. M. Prim, Operant conditioning of tonic neuronal firing rates from single units in monkey motor cortex, *Brain research* 117 (3) (1976) 498–502.
- 290 [33] E. Schmidt, M. Bak, J. McIntosh, J. Thomas, Operant conditioning of firing patterns in monkey cortical neurons, *Experimental neurology* 54 (3) (1977) 467–477.
- [34] S. Kobayashi, W. Schultz, M. Sakagami, Operant conditioning of primate prefrontal neurons, *Journal of neurophysiology* 103 (4) (2010) 1843–1855.
- 295 [35] C. T. Moritz, E. E. Fetz, Volitional control of single cortical neurons in a brain-machine interface, *Journal of neural engineering* 8 (2) (2011) 025017.
- [36] B. Engelhard, N. Ozeri, Z. Israel, H. Bergman, E. Vaadia, Inducing gamma oscillations and precise spike synchrony by operant conditioning via brain-machine interface, *Neuron* 77 (2) (2013) 361–375.
- 300 [37] D. Ishikawa, N. Matsumoto, T. Sakaguchi, N. Matsuki, Y. Ikegaya, Operant conditioning of synaptic and spiking activity patterns in single hippocampal neurons, *The Journal of Neuroscience* 34 (14) (2014) 5044–5053.
- [38] M. Cerf, N. Thiruvengadam, F. Mormann, A. Kraskov, R. Q. Quiroga, C. Koch, I. Fried, On-line, voluntary control of human temporal lobe neurons, *Nature* 467 (7319) (2010) 1104–1108.
- 305 [39] R. Muir, R. Lemon, Corticospinal neurons with a special role in precision grip, *Brain research* 261 (2) (1983) 312–316.
- [40] R. P. Dum, P. L. Strick, The origin of corticospinal projections from the premotor areas in the frontal lobe, *J Neurosci* 11 (3) (1991) 667–689.

- [41] S. Perel, A. B. Schwartz, V. Ventura, Automatic scan test for detection of functional connectivity between cortex and muscles, *Journal of neurophysiology* 112 (2) (2014) 490–499.
- [42] K. Ganguly, D. F. Dimitrov, J. D. Wallis, J. M. Carmena, Reversible large-scale modification of cortical networks during neuroprosthetic control, *Nature neuroscience* 14 (5) (2011) 662–667.
- [43] P.-J. Arduin, Y. Frégnaç, D. E. Shulz, V. Ego-Stengel, “Master” neurons induced by operant conditioning in rat motor cortex during a brain-machine interface task, *The Journal of Neuroscience* 33 (19) (2013) 8308–8320.
- [44] K. B. Clancy, A. C. Koralek, R. M. Costa, D. E. Feldman, J. M. Carmena, Volitional modulation of optically recorded calcium signals during neuroprosthetic learning, *Nature neuroscience* 17 (6) (2014) 807–809.
- [45] A. J. Law, G. Rivlis, M. H. Schieber, Rapid acquisition of novel interface control by small ensembles of arbitrarily selected primary motor cortex neurons, *Journal of neurophysiology* 112 (6) (2014) 1528–1548.
- [46] E. J. Hwang, P. M. Bailey, R. A. Andersen, Volitional control of neural activity relies on the natural motor repertoire, *Current Biology* 23 (5) (2013) 353–361.
- [47] A. C. Koralek, X. Jin, J. D. Long II, R. M. Costa, J. M. Carmena, Corticostriatal plasticity is necessary for learning intentional neuroprosthetic skills, *Nature* 483 (7389) (2012) 331–335.
- [48] A. C. Koralek, R. M. Costa, J. M. Carmena, Temporally precise cell-specific coherence develops in corticostriatal networks during learning, *Neuron* 79 (5) (2013) 865–872.
- [49] G. E. Loeb, Hard lessons in motor control from the mammalian spinal cord, *Trends in Neurosciences* 10 (3) (1987) 108–113.
- [50] M. D. Golub, B. M. Yu, S. M. Chase, Internal models for interpreting neural population activity during sensorimotor control, *eLife* (2015) 10.7554/eLife.10015.

- [51] M. T. Kaufman, M. M. Churchland, S. I. Ryu, K. V. Shenoy, Cortical activity in the null space: permitting preparation without movement, *Nature neuroscience* 17 (3) (2014) 440–448.
- [52] S. D. Stavisky, J. C. Kao, J. M. Sorokin, S. I. Ryu, K. V. Shenoy, System identification of brain-machine interface control using a cursor jump perturbation, in: *Neural Engineering (NER), 2015 7th International IEEE/EMBS Conference on, IEEE*, 643–647, 2015.
- [53] R. Ranganathan, J. Wieser, K. M. Mosier, F. A. Mussa-Ivaldi, R. A. Scheidt, Learning redundant motor tasks with and without overlapping dimensions: facilitation and interference effects, *The Journal of Neuroscience* 34 (24) (2014) 8289–8299.
- [54] A. De Rugy, G. E. Loeb, T. J. Carroll, Muscle coordination is habitual rather than optimal, *The Journal of Neuroscience* 32 (21) (2012) 7384–7391.
- [55] K. Nazarpour, A. Barnard, A. Jackson, Flexible cortical control of task-specific muscle synergies, *The Journal of Neuroscience* 32 (36) (2012) 12349–12360.
- [56] D. J. Berger, R. Gentner, T. Edmunds, D. K. Pai, A. d’Avella, Differences in adaptation rates after virtual surgeries provide direct evidence for modularity, *The Journal of Neuroscience* 33 (30) (2013) 12384–12394.
- [57] C.-S. R. Li, C. Padoa-Schioppa, E. Bizzi, Neuronal correlates of motor performance and motor learning in the primary motor cortex of monkeys adapting to an external force field, *Neuron* 30 (2) (2001) 593–607.
- [58] R. Paz, C. Natan, T. Boraud, H. Bergman, E. Vaadia, Emerging patterns of neuronal responses in supplementary and primary motor areas during sensorimotor adaptation, *The Journal of neuroscience* 25 (47) (2005) 10941–10951.
- [59] T. Komiyama, T. R. Sato, D. H. OConnor, Y.-X. Zhang, D. Huber, B. M. Hooks, M. Gabitto, K. Svoboda, Learning-related fine-scale specificity imaged in motor cortex circuits of behaving mice, *Nature* 464 (7292) (2010) 1182–1186.

- [60] S. M. Chase, A. B. Schwartz, R. E. Kass, Latent inputs improve estimates of neural encoding in motor cortex, *The Journal of Neuroscience* 30 (41) (2010) 13873–13882.
- [61] B. Jarosiewicz, S. M. Chase, G. W. Fraser, M. Velliste, R. E. Kass, A. B. Schwartz, Functional network reorganization during learning in a brain-computer interface paradigm, *Proceedings of the National Academy of Sciences* 105 (49) (2008) 19486–19491.
- [62] S. M. Chase, R. E. Kass, A. B. Schwartz, Behavioral and neural correlates of visuomotor adaptation observed through a brain-computer interface in primary motor cortex, *Journal of neurophysiology* 108 (2) (2012) 624.
- [63] J. P. Cunningham, M. Y. Byron, Dimensionality reduction for large-scale neural recordings, *Nature neuroscience* .
- [64] P. Nuyujukian, J. M. Fan, V. Gilja, P. S. Kalanithi, C. Chestek, K. V. Shenoy, et al., Monkey models for brain-machine interfaces: the need for maintaining diversity, in: *Engineering in Medicine and Biology Society, EMBC, 2011 Annual International Conference of the IEEE*, 1301–1305, 2011.
- [65] A. L. Orsborn, H. G. Moorman, S. A. Overduin, M. M. Shanechi, D. F. Dimitrov, J. M. Carmena, Closed-loop decoder adaptation shapes neural plasticity for skillful neuroprosthetic control, *Neuron* 82 (6) (2014) 1380–1393.
- [66] M. C. Dadarlat, J. E. O’Doherty, P. N. Sabes, A learning-based approach to artificial sensory feedback leads to optimal integration, *Nature neuroscience* 18 (1) (2015) 138–144.
- [67] N. C. Rust, J. A. Movshon, In praise of artifice, *Nature neuroscience* 8 (12) (2005) 1647–1650.
- [68] J. D. Charlesworth, T. L. Warren, M. S. Brainard, Covert skill learning in a cortical-basal ganglia circuit, *Nature* 486 (7402) (2012) 251–255.

- [69] B. Shabbott, R. Ravindran, J. W. Schumacher, P. B. Wasserman, K. S. Marder,
390 P. Mazzoni, Learning fast accurate movements requires intact frontostriatal cir-
cuits, *Frontiers in human neuroscience* 7 (752) (2013) 1–17.

Suminski et al. [17]:** The authors independently manipulated visual and proprioceptive feedback provided to monkeys during BCI control. Subjects' performance was highest with a congruent combination of visual feedback of the BCI cursor position and proprioceptive feedback in the form of passive arm movements driven by a robot. Performance was lower when passive arm movements were driven incongruently with cursor movements, suggesting that the brain might not be able to ignore proprioceptive inputs even when they do not contribute useful information.

Sadtler et al. [23]:** The authors sought a network principle to explain why learning some tasks is easier than others. In a BCI experiment, monkeys could more easily learn BCI mappings that were consistent with the underlying network structure, relative to those that were inconsistent with the network structure.

Schafer and Moore [31]:** Monkeys were trained to volitionally modulate firing rates of individual neurons in the frontal eye field (FEF) that were tied to the pitch of auditory tones. By introducing a visual search task as probe trials, the authors found that visual attention was impaired following volitional decreases in firing rate. This study demonstrates that volitional changes in FEF activity are associated with visual attention.

Ganguly et al. [42*]: M1 neurons recorded during a monkey BCI experiment showed learning-related changes regardless of whether they were directly driving behavior (output neurons) or not (non-output neurons). The authors found that the relationship between firing rate and movement direction changed for both types of neurons, and the firing rates of non-output neurons became less coupled to movement direction relative to the firing rates of output neurons.

Law et al. [45*]: This study showed that monkeys could learn to drive 1-D BCI cursor movements using populations of up to 4 arbitrarily selected M1 neurons and that control performance tended to increase with population size. By defining a simple BCI mapping—averaging the activity of all output neurons—the authors could readily parti-

tion neural variability into cursor variability and null-space variability, and study how each changes with learning and population size.

425

Koralek et al. [48]:** In a rat BCI experiment, coherence developed selectively between neurons in dorsal striatum and output neurons in M1, suggesting a flexible coupling among distant neurons to increase behavioral performance. This finding was enabled by the authors' ability to distinguish between output and non-output neurons in M1.

430

Golub et al. [50]:** The authors used novel statistical analyses to extract internal models used by monkeys during BCI control. A mismatch between subjects' internal models and the BCI explained a majority of movement errors and limited subjects' dynamic range of movement speed. Following abrupt changes to the BCI mapping, internal models adapted in a manner consistent with the particular perturbations.

435

Dadarlat et al. [66*]: Monkeys learned to guide arm reaches based on initially unfamiliar patterns of intracortical microstimulation (ICMS), and could successfully guide goal-directed reaching by optimally combining ICMS and noisy visual stimuli.

440

Figure 1: Conceptual illustration of the sensorimotor control loop for arm reaching (left) and BCI (right) movements.

Table 1: **Comparison of BCI control to arm reaching.** Bold items indicate entries that make BCI a simplified, well-defined and easily-manipulated system for studying sensorimotor control.

Table 1

	Arm reaching	BCI
Effector	arm	cursor or robotic limb
# of non-output neurons	millions	millions
# of output neurons	thousands (only a subset are recorded)	tens-to-hundreds (all are recorded)
Neuron-to-movement mapping	unknown	known
Effector dynamics	difficult to measure, nonlinear	known, can be linear
Sensory feedback	tied to arm	flexibly manipulable

Figure 1