Towards efficient bioethanol production from agricultural and forestry residues: exploration of unique natural microorganisms in combination with advanced strain engineering

Xinqing Zhao^{*1}, Liang Xiong², Mingming Zhang², Fengwu Bai^{1, 2}

Abstract

Production of fuel ethanol from lignocellulosic feedstocks such as agricultural and forestry residues is receiving increasing attention due to the unsustainable supply of fossil fuels. Three key challenges include high cellulase production cost, toxicity of the cellulosic hydrolysate to microbial strains, and poor ability of fermenting microorganisms to utilize certain fermentable sugars in the hydrolysate. In this article, studies on searching of natural microbial strains for production of unique cellulase for biorefinery of agricultural and forestry wastes, as well as development of strains for improved cellulase production were reviewed. In addition, progress in the construction of yeast strains with improved stress tolerance and the capability to fully utilize xylose and glucose in the cellulosic hydrolysate was also summarized. With the superior microbial strains for high titer cellulase production and efficient utilization of all fermentable sugars in the hydrolysate, economic biofuels production from agricultural residues and forestry wastes can be realized.

1. Introduction

The worldwide growing demand for crude oil and continuous carbon dioxide emission concern have fostered the research on production of biofuels from renewable cellulosic biomass. Agricultural and forestry residues are rich sources of lignocellulosic feedstocks for biofuels production (reviewed by [Ho et al., 2014](#)), which include wheat straw, rice straw, corn stove, and wood biomass, such as spruce and oil palm trunks. Bioconversion of these biomass materials into bioethanol is of great potential to replace the existing liquid transportation fuels. As the most comprehensively studied renewable energy, bioethanol has been widely used as a transportation fuel. In the past decade, extensive efforts have been made in the bioconversion of various plant biomasses into fuel ethanol. The general fuel ethanol production processes include multiple units: pretreatment of biomass, enzymatic degradation of biomass to release fermentable sugars, and ethanol fermentation. Based on the consolidated degree to four biologically mediated events, namely, cellulase production, enzymatic hydrolysis, glucose conversion to ethanol, and fermentation of hemicellulose hydrolysis products (mainly xylose), alternative processing configurations can be categorized as depicted in [Figure 1](#). Separate hydrolysis and fermentation (SHF) involves the four discrete process steps, whereas simultaneous saccharification and fermentation (SSF) consolidates hydrolysis and fermentation of glucose into a single step, and further consolidation of xylose fermentation resulted in simultaneous saccharification and cofermentation (SSCF). Moreover, consolidated bioprocessing (CBP) combines cellulase production, hydrolysis, and fermentation of both cellulose and hemicellulose hydrolysis products in a single microorganism. The characteristics of these four processes were described in more detail elsewhere ([Zhao et al., 2012](#)).

Fig.1 should be here.

Despite significant progress in process optimization and strain engineering for efficient bioconversion of lignocellulosic biomass to bioethanol, three great challenges still exist for commercially favorable bioethanol from lignocellulosic biomasses. Firstly, the rigid structure of lignocellulose mainly consisting of cellulose, hemicellulose and lignin makes the substrate recalcitrant to enzymatic degradation (Zhao et al., 2012). Biological degradation of the lignocellulose by cellulolytic enzymes is efficient and also environmentally friendly. However, economic bioconversion of lignocellulosic biomass is restricted by the high production cost of cellulase. Secondly, to deconstruct the lignocellulosic materials for further enzymatic degradation, various pretreatment approaches (including diluted sulfuric acid, sodium hydroxide, aqueous ammonia, liquid hot water, ionic liquid, organic solvent, steam explosion, ammonia fibre expansion) were developed (Jönsson and Martín 2016). Most of the pretreatment methods adopted extreme conditions, resulting in the generation of various inhibitors including weak acids, furans (5-hydroxymethyl furfural (HMF) and furfural), as well as phenols during the pretreatment of lignocellulose (Jönsson and Martín 2016). In addition, other stress factors (i.e. high temperature, low pH and fermentation product ethanol, etc.) would also emerge during the fermentation process. Decreased cell viability and fermentation capability of the microbial strains under these environmental stress conditions necessitate strategies to improve fermentation efficiency in the presence of inhibitors, or removal of these inhibitory compounds. Thirdly, xylose released from hemicellulose in lignocellulosic feedstocks cannot be efficiently utilized by native *Saccharomyces*

cerevisiae strains, which are widely used for bioethanol production due to high ethanol fermentation efficiency. Therefore, it is necessary to develop efficient xylose-fermenting microorganisms that can convert xylose to ethanol using the sugar mixtures.

In the past decade, vibrant and persistent researches has not only resulted in the development of engineered strains ready for industrial fermentation of cellulosic hydrolysates, but also deepened our understanding of operational principles underlying microbial stress response and global metabolism. This review mainly focuses on the development of superior cellulase producing microbial strains, as well as robust *S. cerevisiae* strains for the conversion of lignocellulosic residues into bioethanol. We believe that employment of superior microbial strains is essential to achieve an economic process for biorefinery of agricultural and forestry residues.

2. Screening and development of cellulase producers

2.1 Exploration of natural resources for novel cellulase producers

Among the diverse cellulolytic enzyme producers, fungal strains are regarded as preferred groups that are superior to bacteria. *Trichoderma reesei* is a fungal species that has been widely used as a cellulase producer, which is utilized for industrial cellulase production. The three major categories of these cellulolytic enzymes produced by *T. reesei* include cellobiohydrolases, CBH (EC 3.2.1.91), endoglucanases (EC 3.2.1.4) and β -glucosidases (EC 3.2.1.21), which act synergistically to convert cellulose to glucose. The major drawback of *T. reesei* is its low β -glucosidase activity (Zhang et al., 2010). It is therefore of interest to explore new cellulase producer strains. Comparing with emerging interest in bacterial cellulase producers (Assareh et al., 2012), studies on fungal cellulase producers received greater attention. Novel natural fungal strains have been discovered as useful bioresources for efficient

bioconversion of lignocellulosic materials. For example, *Chrysosporthe cubensis*, a plant pathogenic fungus, was studied as a novel source of cellulases. The crude enzymes from this fungus showed good stability at 40 and 50 °C, and high efficiency in sugar release (Falkoski et al., 2013). *Acremonium strictum* isolated from Brazilian and thermophilic fungus *Malbranchea cinnamomea* were also explored as a potential cellulase producer (Goldbeck et al., 2013; Mahajan et al., 2016). A novel β -glucosidase was purified from *Penicillium piceum*, which showed high transglycosylation activity to produce cellulase inducers (Gao et al., 2013). Such novel cellulase producers have the potential to be further explored for efficient degradation of cellulosic biomass.

2.2 Synergistic proteins and implication in strain development

Lytic polysaccharide monooxygenases (LPMOs) from aerobic organisms have received great attention in the recent years due to their boosting effects on the activities of cellulases. LPMOs are classified as auxiliary activities (AA) in the Carbohydrate Active Enzyme (CAZy) database, and the fungal AA9 (formerly named GH61) and the bacterial AA10 (formerly CBM33) are known to exhibit synergistic effects with cellulases (Corrêa, et al., 2016). For example, supplementation of AA9s with cellulase greatly improved hydrolytic efficiency (reviewed by Kim, et al., 2014), which contributes to reduce enzyme loading for bioconversion of cellulosic materials. Other synergistic proteins to enhance hydrolysis efficiency of cellulases include carbohydrate-binding modules, plant or bacterial expansins or expansin-like proteins (e.g. swollenins), which were reviewed elsewhere (Kim, et al., 2014; Georgelis, et al., 2014). Encoding genes of such synergistic proteins can be identified in the genomic sequences of various organisms, presenting a promising research field to search for novel producing microbial strains or engineering novel enzyme complexes. Recently,

LPMOs genes from *Thermobifida fusca* were integrated into designer cellulosomes, resulting in 2.6-fold enhancement in the release of soluble sugars compared with free cellulases without LPMO enhancement (Arfi et al., 2014). It is desired that future cellulase producer can produce enzyme mixtures with optimized ratio of cellulases and synergistic proteins. However, dependence of the synergistic activity on biomass characteristics and pretreatment methods demands customized design for fixed process flow (Kim, et al., 2014).

2.3 Improvement of cellulase producers by genetic/metabolic engineering

Due to the low cellulase production level of the natural isolates, strain development is necessary. Traditional methods using chemical and/or physical mutagenesis are labor consuming, and it is therefore highly desired to improve cellulase production using strategies that are more rational.

There are two general strategies to improve cellulase production performance, one is to overexpress cellulosic enzyme components, and the other is manipulation of transcription factors or other regulatory proteins. Many successful examples have been reported to increase cellulase production and biomass saccharification efficiency through increasing the activities of the cellulase component. In a previous study, the *cbh2* gene was overexpressed in *T. reesei* ZU-02, and the highest production level of filter paper activity of one mutant C10 was 4.3-fold higher than that of the parental strain (Fang and Xia 2013). In another study, β -glucosidase gene encoding gene *bglI* was cloned under an artificial four copies of *cbhI* promoter. The filter paper activity of the mutant was improved by 130% in the best mutant B12 (Zhang et al., 2010).

Although several regulators have been known to exert control on cellulase induction in *T. reesei*, new regulators remain to be discovered. In a recent study,

transcriptional profiling data related to induction by various cellulose-derived substrates were analyzed, and 28 putative regulatory genes were selected to be overexpressed in *T. reesei*, among which seven genes were found to increase cellulase production (Häkkinen et al., 2014). Interestingly, improved cellulolytic enzyme activities was also achieved using a T-DNA-tagged mutant library (Zhong et al., 2012), due to random insertion of T-DNA in the chromosome of the fungal strain. With the development of systems biology tools, abundant data are emerging from genomic, transcriptomic and proteomic analysis, it will be not surprised that novel enzymes, synergistic proteins, and novel regulatory proteins that either assist efficient hydrolysis of the cellulosic feedstocks or improved cellulose production will be discovered. Indeed, novel regulatory proteins and pathways to affect cellulase production in *T. reesei* still remain to be revealed (Wang et al., 2013; Zhang et al., 2013). Strategies for development of efficient cellulase-producing fungal strain and enzyme systems, especially construction of cellulase producers based on systematic analysis of various conditions using systems biological methods were summarized in an excellent review elsewhere (Liu et al., 2013).

3. Overcoming inhibitors in the cellulosic hydrolysates

3.1 Inhibitors produced by pretreatment and general methods to combat inhibition

Production of ethanol from agricultural and forestry residues contains two steps: first is the degradation of lignocellulose substrates to sugars, and the second step is fermentation of released sugars with suitable microbial strains. Depending on the types of agricultural/forestry residues and pretreatment methods, various inhibitors are released during the process of pretreatment. The influence of pretreatment strategies on formation of inhibitors was recently reviewed recently (Jönsson and Martín 2016).

Among these inhibitory compounds, furan derivatives (e.g., furfural and 5-HMF) and organic acids (e.g., acetic, formic acid) received more attention due to higher concentration than that of phenolic compounds. [Table 1](#) listed the concentrations of acetic acid, furfural and 5-HMF from different feedstocks and pretreatment modes. Due to the ability of many microorganisms in detoxifying furfural, transforming it to less toxic furfuryl alcohol (reviewed by [Parawira and Tekere 2011](#)), the toxicity of acetic acid has aroused the most attention. Significant efforts have been focused on studying the molecular mechanisms underlying yeast response and tolerance to acetic acid, which will be briefly summarized below ([An et al., 2015](#); [Kim et al., 2015](#); [Lee et al., 2015](#); [Ma et al., 2015](#); [Meijnen et al., 2016](#); [Zhang et al., 2015](#)). It is worth mentioning that phenolic compounds, including aromatic carboxylic acids and aromatic aldehydes derived from lignin, exhibit high toxicity to fermenting microorganisms, although these compounds are normally present in low concentration ([Jönsson and Martín 2016](#)). The soluble phenolics also inhibit cellulolytic enzymes, and is also a great challenge for efficient biorefinery of cellulosic feedstocks.

[Table 1 should be here.](#)

The strategies to overcome inhibition on lignocellulosic ethanol fermentation were reviewed previously with the emphasis on various aspects, including techno-economic evaluation, conditions required by high gravity fermentation, or detoxification and strain development ([Jönsson and Martín 2016](#); [Koppram et al., 2014](#); [Parawira and Tekere 2011](#)). Based on these excellent reviews and the recent

progress in technological development, here we present an update of combination of process optimization and strain optimization strategies, and illustrate more comprehensively all the methods to conquer inhibition of cellulosic ethanol production. The scheme with the overview of these strategies is illustrated in Fig. 2.

[Fig. 2 should be here.](#)

The main purpose of process optimization is to reduce the production of inhibitors or remove these inhibitors from the hydrolysates. Detoxification and/or conditioning can be performed by adding chemicals, alternatively, biotransformation can be performed using various microorganisms to remove inhibitors, and inhibition can also be relieved by adding laccases. The above-mentioned processes are reviewed previously in detail ([Parawira and Tekere 2011](#)). The problem of these processes is that separate step and additional time required, and the cost of the solvents or enzymes also needs to be considered for large scale application. In addition, consumption of sugar by the microbes used for biotransformation is another challenge, which can be solved by using high concentration solid culture, proper aeration and well mixing ([He et al., 2016](#)). Other options in process operation include selection of fed-batch mode to alleviate the inhibition to microorganisms, adding nutrients in the culture medium, and increase the inoculum size, and these process optimization strategies have been summarized previously ([Jönsson and Martín 2016](#); [Koppram et al., 2014](#)). Although all these processes benefit subsequent ethanol fermentation, it is of great importance to obtain high ethanol productivity and ethanol

yield using proper fermentation microorganisms. Below three important strategies to obtain good fermenting strains are highlighted.

3.2 Strategies to improve ethanol fermentation performance in the presence of inhibitors by strain selection and engineering

Three general strategies in strain optimization were summarized in [Fig.2](#). Firstly, selection of a good starting strain is very important. It has been demonstrated that different microbial strains differ greatly in their ability to tolerate toxic inhibitors ([Pereira et al., 2014](#)), therefore, a lot of efforts have been made to screen wild type strains with superior growth in the presence of inhibitors. For example, cell growth and ethanol yield of 15 yeast strains were compared in resistance levels to various stress conditions, including high temperature, low pH, acetic acid, and so on, and up to 7.5 fold difference was observed in the least and the most tolerant strains ([Zheng et al., 2011](#)). The strain with the highest tolerance level can serve as the good starting strain for efficient bioconversion of sugars in cellulosic hydrolysate.

The second strategy to improve ethanol fermentation and cell growth of fermenting strain is adaption, which is also termed as evolutionary engineering. Adaptive evolution has been extensively used for the engineering of microbial system for improvement of inhibitor tolerance ([Parawira and Tekere 2011](#); [Koppram et al., 2014](#)). It is worth noting that adaptation cannot only improves inhibitor tolerance and high temperature tolerance ([Wallace-Salinas et al., 2015](#)), but can also improve xylose fermentation of the recombinant strains, which will be further discussed in the following text (section 4.2). For example, a short-term adaptation was achieved by

fed-batch cultivation in the presence of increasing ratio of cellulosic hydrolysate in less than 20 h. The adapted culture was then subjected to SSCF using wheat straw slurry. It was revealed that adaptation improved both sugar utilization and removal of furaldehydes from the slurry during SSCF (Nielsen et al., 2015).

The third strategy is systems and synthetic metabolic engineering of the fermenting microorganisms that is described recently (Becker and Wittmann 2015). The systems metabolic engineering utilizes information from multi-omics analysis to search for important targets for metabolic engineering manipulations, whereas synthetic biological tools can be implemented in metabolic engineering of microorganisms to improve biorefinery efficiency. With the rapid advances in systems wide omics technologies, more comprehensive analysis of intracellular components and their interactions can be achieved using data from genomic, transcriptomic, proteomic, metabolomic, and fluxomic analysis. Important genes involved in inhibitor tolerance can now be identified using combinations of multiple omics data. For example, according to comparative genomic analysis of two industrial yeast strains YJS329 and ZK2 with different tolerance levels to various stress conditions, overexpression of a putative zinc cluster protein encoding gene *YFL052W* that has copy number variation between the two strains improved acetic acid tolerance of ZK2 and ethanol production titer under high gravity condition (Zheng et al., 2013). Novel genes involved in acetic acid tolerance was revealed using Quantitative trait locus (QTL) mapping via pooled-segregant whole-genome sequence analysis, and it was also proved that a *HAA1* allele containing a unique single point mutation remarkably

improved acetic acid tolerance ([Meijnen et al., 2016](#)).

Transcriptome analysis has been actively used to breed stress tolerant mutants. For example, transcriptomic data revealed that *SFP1* and *ACE2* regulated genes are clearly changed in the strain YC1 with superior resistance to inhibitors (furfural and acetic acid). Hence, *SFP1* and *ACE2* overexpression was performed to explore its effect on inhibitor tolerance. The results indicated that specific ethanol productivity was improved by nearly four and three times independently in the presence of 2 g/L acetic acid and 1.5 g/L furfural ([Chen et al., 2016](#)). Similarly, *SET5* and *PPR1* were captured in our transcriptomic research by comparing zinc addition with the non-addition control, and it was demonstrated that with these two genes overexpression approximately 10% increased ethanol production was obtained in the fermentation from corn stover hydrolysate ([Zhang et al., 2015](#)).

Metabolome analysis has also been successful in improvement of strain performance. In an earlier study, metabolome analysis revealed that levels of metabolites involved in the non-oxidative pentose phosphate pathway (PPP) were significantly increased by the addition of acetate, which promoted the attempt to overexpress the genes encoding transaldolase or transketolase in PPP in the xylose-fermenting yeast strain. Enhanced ethanol productivity from xylose in the presence of acetic and formic acid were observed in the mutants ([Hasunuma et al., 2011](#)). Metabolomic analysis has been performed using yeast cell samples in different adaptation stages in the presence of the mixture of furfural, acetic acid, and phenol (FAP). It was found that proline and myo-inositol are among the most significantly

affected metabolites. Exogenous addition of proline and myo-inositol improved FAP stress tolerance, and overexpression of two related key genes *PRO1* and *INO1* both improved growth and shortened fermentation time in the presence of FAP stressors (Wang et al., 2015). It should be emphasized that it is important to improve tolerance of fermenting microorganisms to multiple stressors, including furfural, HMF, acetic acid and ethanol, therefore, it is desired that key metabolites and/or key genes that affect multiple stress tolerance are identified. In a recent report, increased intracellular spermidine content was identified to be critical for stress tolerance, and subsequent transcriptomic analysis revealed novel gene targets to improve tolerance to furfural and ethanol (Kim et al., 2015).

It is well known that response and tolerance of inhibitors involved the functions of multiple genes, which was emphasized by a recent report (Wallace-Salinas et al., 2015). Therefore, it is important to find key genes that can control multiple genes, in this case, manipulation of transcription factor is preferred choice. Indeed, it was found that mutations of the TATA-binding protein (TBP) encoded by *SPT15* led to improved acetic acid tolerance (An et al., 2015). Recent work in our group also demonstrated that artificial zinc finger protein can be used to achieve improved acetic acid tolerance and discovery of novel key genes involved in acetic acid tolerance (Ma et al., 2015).

Synthetic biology is an emerging technology for development of robust strains for industrial applications (Becker and Wittmann 2015). However, without clear understanding of the underlying molecular mechanisms of stress tolerance, it is still difficult to achieve rational design using synthetic biology. Right now, a lot of efforts

are being made to search for useful genetic elements responsible for stress tolerance. For example, heat shock protein encoding genes from a thermophile *Thermoanaerobacter tengcongensis* were overexpressed in *S. cerevisiae* cell factory with the heterologous β -amyrin pathway, and these thermotolerant devices (heterologous heat shock protein directed by yeast promoter) were proved to be functional to improve cell viability and β -amyrin production (Liu et al., 2014). Similarly, stress tolerant fermenting strains can be designed using the inhibitor tolerant devices either mining from diverse natural sources or tailor-made devices and circuit based on the understanding of response and coping mechanisms of microbial cells to stressful conditions. The combination of systems biology, synthetic biology and metabolic engineering manipulations described above is also helpful for breeding recombinant strains with improved sugar utilization capability, which will be further discussed in the following text (Section 4.2).

4. Ethanol production from sugar mixtures

4.1 Development of efficient xylose-fermenting S. cerevisiae

Efficient and rapid fermentation of all sugars present in cellulosic hydrolysates is essential for economic conversion of renewable biomass into fuels and chemicals. Xylose is the second abundant sugar in the lignocellulosic biomass derived hydrolysates next to glucose. Utilization of xylose is of great importance for efficiently conversion of majority fermentable sugars released from the plant biomass. However, the native strain of the most widely used industrial *S. cerevisiae* cannot ferment xylose into ethanol. Besides the introduction of the xylose-assimilating

pathway into *S. cerevisiae*, numerous efforts have been made on the development of engineered *S. cerevisiae* strain to ferment xylose rapidly and efficiently. Plenty of researches focus on the optimization of xylose-assimilating pathways and perturbation of gene targets that hamper xylose metabolism (reviewed by [Kim et al., 2013](#)).

The heterologous expression of the xylose isomerase (XI) gene is considered as a direct and effective strategy for establishing the xylose metabolic pathway in *S. cerevisiae*. Numerous xylose isomerase genes were identified from bacteria or fungi, however, only limited sources of *xylA* are efficiently expressed in *S. cerevisiae* and are capable of driving effective xylose consumption. Codon optimization and further mutagenesis are often needed for functional expression of the heterogenous gene with improved activities. For example, a new xylose isomerase gene *Ru-xylA* screened from the bovine rumen metagenomic library was functionally expressed in *S. cerevisiae*, exhibiting high activity level comparable to those of the *Piromyces* sp. XI. Similarly the enzyme activity was further improved by mutagenesis, the variant containing two mutations (K11T/D220V) exhibited a 68% increased enzymatic activity ([Hou et al., 2015](#)). In a recent report, the recombinant yeast strain SXA-R2P-E carrying a mutated form of XI encoding gene showed high ethanol yield using dilute acid-pretreated hydrolysates of rice straw as substrate (up to 0.46 g ethanol/g sugars), indicating its potential of cellulosic ethanol production ([Ko et al., 2016](#)). More XI remains to be discovered for breeding of improved strains in the future.

XR/XDH pathway has intrinsic defect of cofactor imbalance, which is the main reason for xylitol accumulation in *S. cerevisiae* expressing XR-XDH pathway. To

conquer this problem, protein engineering was attempted to modify the cofactor specificity of either XR or XDH (reviewed by [Kim et al., 2013](#)). In addition, further gene modifications can be performed, for example, deletion of *FPS1* and *GPD2* together with overexpressing *GLN1* encoding a NADH-dependent glutamate synthetase, as well as overexpression of *TAL1*, *TKL1*, *RPE1* and *RK11* encoding the non-oxidative pentose phosphate pathway (PPP) enzymes. These combined manipulations resulted in significant improvement of conversion of xylose to ethanol ([Xiong et al., 2011](#)).

The expression levels of the *XR/XDH/XK* genes played an important role in xylose metabolism, while the genetic and physiological background of host strains may influence the selection of optimal pathway for efficient xylose-fermenting *S. cerevisiae*. Ideally, the host strain can both utilize xylose efficiently and tolerate inhibitors in the hydrolysate ([Li et al., 2016](#)). In addition, tolerance to high temperature is also preferred in selection of host strain, which benefits ethanol production by SSF or SSCF ([Jin et al., 2013](#)). In SSCF of 9% (w/w) glucan loading ACS at 35 °C, the engineered strain Y35 harboring two copies of *XYL1*, *XYL2* and *XYL3*, which was derived from a wild-type *S. cerevisiae* strain GLBRCY0 with high growth tolerance to simultaneous elevated temperature and AFEX™ pretreated corn stover, showed higher cell viabilities and produced a similar amount of ethanol (51.3 g/L) comparable to the benchmark strain 424A(LNH-ST) ([Jin et al., 2013](#)).

Considering the impact of genetic background in strain construction, the optimal pathway for one strain may not be the best for one another, therefore pathway should

be optimized according to individual strain with specific genetic background, demanding rapid strain engineering methods. To solve this problem, high through-put combinatorial methods was developed either by employing libraries of promoters or varying combination of pathway genes followed by high-throughput screening/selection (Latimer et al., 2014). A xylose utilizing pathway with near-highest efficiency ever reported was generated via a single round of COMPACTER (customized optimization of metabolic pathways by combinatorial transcriptional engineering), in which a library of mutant pathways was created by de novo assembly of promoter mutants with varying strengths for each pathway gene in a target organism (Du et al., 2012). Similarly, the expression levels of eight genes (*XR*, *XDH*, *XK*, *RPE1*, *PK11*, *TKL1*, *TAL1* and *PYK1*) involved in the conversion of xylose to ethanol were fine-tuned by applying a library of promoters with different strengths (Latimer et al., 2014), indicating importance of strain optimization by promoter selection.

A novel strain design using synthetic biology concept enabled simultaneous utilization of cellobiose, xylose and acetic acid. In this design, cellodextrin transporter (*cdt-1*) as well as intracellular β -glucosidase (*gh1-1*) encoding genes were amplified from the cellulolytic fungus *Neurospora crassa* and expressed in *S. cerevisiae* to enable the utilization of cellobiose. In addition, the xylose assimilation pathway genes including *XR* and *XDH* encoding genes from *Scheffersomyces stipites* were also expressed in the same *S. cerevisiae* strain for xylose assimilation. At the same time, *adhE* from *Escherichia coli* was also expressed to enable the reduction of acetate to

ethanol. The resultant strain thus harbors three pathways for ethanol production using cellobiose, xylose and acetic acid, and significant improvement of ethanol yield and productivity comparing with those of the control strain was achieved (Wei et al., 2015). This successful example encourages further verifications using authentic hydrolysate for cellulosic ethanol production.

The emergence of CRISPR-Cas9 (Clustered Regularly Interspaced Short Palindromic Repeats (CRISPR) associated Cas9) system has enabled construction of new strains with complex pathways by genomic engineering with improved efficiency. This booming technology has been well developed and applied in the engineering of *S. cerevisiae* strains, including multiple gene knockout, integration and replacement of promoters (Tsai et al., 2015; Shi et al., 2016; Xu et al., 2016). Since using this method, the genome can be precisely cut with heterologously expressed endonuclease Cas9 and the customized guide RNA (gRNA) was used to generate the double stranded breaks (DSBs), the target cassettes can be integrated into the genome more precisely and efficiently. Multiple gRNAs can be introduced into the host for multiple integration or knockout. It is also advantageous to obtain scar-less constructs with no resistant marker gene via this method. For example, two copies of xylose pathway genes (*XYL1*, *XYL2*, and *XYL3*) were integrated in *PHO13* and *ALD6* loci to realize the overexpression of heterologous genes and deletion of endogenous genes simultaneously without the need of antibiotic resistant marker (Tsai et al., 2015). In a recent report, Cas9-guided promoter substitution resulted in the construction of four strains with different levels of *TAL1* expression (4, 3, 9, and 20-fold higher,

respectively than the native level). Improved xylose utilization and ethanol production was observed with the improved *TALI* expression levels, indicating that *TALI* expression is a key bottleneck for xylose utilization in the recombinant *S. cerevisiae* (Xu et al., 2016). Further development of novel technologies including CRISPR-Cas9 for genome engineering of *S. cerevisiae* will advance the construction of robust xylose utilizing yeast for fuel ethanol production.

4.2 Evolution engineering of *S. cerevisiae* for improved xylose

Along with the rational engineering of *S. cerevisiae* for xylose metabolism, adaptive laboratory evolution was also employed in the development of xylose assimilating strains. Most of the evolved strains showed improved fermentation properties after long term adaptations in the presence of xylose. For example, by multiple rounds of evolutionary engineering in complex medium containing xylose, the best-performing strain GS1.11-26 exhibited a maximum specific D-xylose consumption rate of 1.1 g/gDW/h in synthetic medium, and produced 32% more ethanol than the parent strain Ethanol Red in simultaneous saccharification and fermentation of Arundo hydrolysate (Demeke et al., 2013). A rapid 24-day batch adaptation resulted in an evolved strain SXA-R2P-E efficiently convert xylose to ethanol with a yield of 0.45 g ethanol/g xylose (Lee et al., 2014). Sometimes, adaptive evolution is not only alternative but also essential strategy to improve the ability of engineered xylose assimilating strains. It was reported that only after adaptive laboratory engineering, could the respiratory deficient strain with either XR-XDH or XI pathway efficiently consume xylose (Shen et al., 2012). While mutation is the basic impetus for adaptive laboratory evolution,

mutations in the copy number of the genes in the xylose assimilating pathway influences the xylose consumption capacities of the engineered strains. GS1.11-26 displayed 17-fold higher XI activity compared to the parent strain (Demeke et al., 2013). Besides, other genes also have important impacts of xylose assimilation. For instance, a missense mutation in *GRE3* acquired during the anaerobic evolution of GLBRCY128 harboring XI pathway contributed to the improved xylose conversion by reducing intracellular production of xylitol, an inhibitor of xylose isomerase (Parreiras et al., 2014).

4.3 Ethanol fermentation by xylose assimilating strains from pretreated biomasses

High ethanol titer and productivity is crucial to reduce the cost of bioethanol production, thus it is necessary to optimize the process of bioethanol production with high solid loading. Bioethanol production from pretreated biomass with high ethanol titer was depicted in Table 2, and several key factors to achieve high titer and efficient fuel ethanol production were found to be important, which including pre-hydrolysis (Jin et al., 2012), addition of Tween 20 to reduce cellulase loading (Zhu et al., 2014), as well as yeast feeding, combined with substrate and enzyme feeding (Zhu et al., 2014). Dry dilute acid pretreatment (DDAP) is a promising method for lignocellulose bioconversion since it remarkably reduced waste water, although inhibitors generated during the pretreatment still impede the fermentation severely. High ethanol titer of 71.40 g/L with the yield of 80.34% was achieved by SSF of DDAP corn stover at 30% solids content with an evolutionary adapted *S. cerevisiae* DQ1. No wastewater was generated from pretreatment to fermentation steps (Qureshi et al., 2015). In a

follow-up study, when performed fed-batch SSCF with undetoxified DDAP pretreated corn stover at 25% dry matter loading by xylose fermenting *S. cerevisiae* SyBE005, the final ethanol concentration reached 47.2 g/L with high yeast inoculum (Zhu et al., 2015).

Despite the successful production of high titer bioethanol using agricultural and forestry residues, strain selection and/or adaptation, and strain engineering are still required to combat the severe inhibition of ethanol production by inhibitors, including inhibition of cell growth, ethanol fermentation, as well as xylose utilization, and improvement of stress tolerance is especially important when high gravity production is performed (Koppram et al., 2014). Therefore, it is of great importance to further develop superior microbial strains to achieve economic production of fuel ethanol from cellulosic feedstocks.

Conclusion

Significant progress has been achieved in development of optimized processes and microbial strains for cellulosic ethanol production using diverse agricultural and forestry residues. It is optimistic that the production efficiency of bioethanol from cellulosic wastes can be further improved by implementation of novel technologies including synthetic biology and genome editing to develop superior microorganisms. It is necessary to consider that pretreatment (inhibitor and sugar release), cellulase production and mixed-sugar fermentation are units in a whole process during consideration of process optimization and strain development, and more efforts should be made for strain development to adapt to authentic industrial production

conditions.

Acknowledgement

The authors are grateful to financial support of National Science Foundation of China (Nos. 21376043, 31461143029 and 51561145014).

References

1. An, J., Kwon, H., Kim, E., Lee, Y.M., Ko, H.J., Park, H. Choi, I.G., Kim, S., Kim, K.H., Kim, W., Choi, W., 2015. Tolerance to acetic acid is improved by mutations of the TATA-binding protein gene. *Environ Microbiol*, **17**, 656-669.
2. Arfi Y, Shamsoum M, Rogachev I, Peleg Y, Bayer EA. 2014. Integration of bacterial lytic polysaccharide monooxygenases into designer cellulosomes promotes enhanced cellulose degradation. *Proc Natl Acad Sci USA*, **111**, 9109-14.
3. Assareh, R., Shahbani Zahiri, H., Akbari Noghabi. K., Aminzadeh, S., Bakhshi Khaniki, G., 2012. Characterization of the newly isolated *Geobacillus* sp. T1, the efficient cellulase-producer on untreated barley and wheat straws. *Bioresour Technol*, **120**, 99-105.
4. Becker, J., Wittmann, C., 2015. Advanced biotechnology: metabolically engineered cells for the bio-based production of chemicals and fuels, materials, and health-care products. *Angew Chem Int Ed Engl*, **54**, 3328-3350.
5. Chen, Y., Sheng, J., Jiang, T., Stevens, J., Feng, X., Wei, N., 2016. Transcriptional profiling reveals molecular basis and novel genetic targets for

- improved resistance to multiple fermentation inhibitors in *Saccharomyces cerevisiae*. *Biotechnol Biofuels*, **9**, 9.
6. Corrêa, T.L., Dos Santos, L.V., Pereira, G.A., 2016. AA9 and AA10: from enigmatic to essential enzymes. *Appl Microbiol Biotechnol*. **100**, 9-16.
 7. Demeke, M.M., Dietz, H., Li, Y., Foulquie-Moreno, M.R., Mutturi, S., Deprez, S., Den Abt, T., Bonini, B.M., Liden, G., Dumortier, F., Verplaetse, A., Boles, E., Thevelein, J.M. 2013. Development of a D-xylose fermenting and inhibitor tolerant industrial *Saccharomyces cerevisiae* strain with high performance in lignocellulose hydrolysates using metabolic and evolutionary engineering. *Biotechnol Biofuels*, **6**, 89.
 8. Du, B., Sharma, L.N., Becker, C., Chen, S.F., Mowery, R.A., van Walsum, G.P., Chambliss, C.K., 2010. Effect of varying feedstock-pretreatment chemistry combinations on the formation and accumulation of potentially inhibitory degradation products in biomass hydrolysates. *Biotechnol Bioeng*, **107**, 430-40.
 9. Du, J., Yuan, Y., Si, T., Lian, J., Zhao, H. 2012. Customized optimization of metabolic pathways by combinatorial transcriptional engineering. *Nucleic Acids Res*, **40**, e142.
 10. Erdei, B., Franko, B., Galbe, M., Zacchi, G. 2013. Glucose and xylose co-fermentation of pretreated wheat straw using mutants of *S. cerevisiae* TMB3400. *J Biotechnol*, **164**, 50-58.
 11. Falkoski, D. L., Guimarães, V. M., de Almeida, M. N., Alfenas, A. C., Colodette, J. L., de Rezende, S. T., 2013. *Chrysosporthe cubensis*: a new source of cellulases

- and hemicellulases to application in biomass saccharification processes. *Bioresour Technol*, 130, 296-305.
12. Fang, H., Xia, L., 2013. High activity cellulase production by recombinant *Trichoderma reesei* ZU-02 with the enhanced cellobiohydrolase production. *Bioresour Technol*, **144**, 693-7.
 13. Fujitomi, K., Sanda, T., Hasunuma, T., Kondo, A. 2012. Deletion of the *PHO13* gene in *Saccharomyces cerevisiae* improves ethanol production from lignocellulosic hydrolysate in the presence of acetic and formic acids, and furfural. *Bioresour Technol*, **111**, 161-166.
 14. Gao, L., Gao, F., Zhang, D., Zhang, C., Wu, G., Chen, S., 2013. Purification and characterization of a new β -glucosidase from *Penicillium piceum* and its application in enzymatic degradation of delignified corn stover. *Bioresour Technol*, **147**, 658-661.
 15. Georgelis, N., Nikolaidis, N., Cosgrove, D.J., 2015. Bacterial expansins and related proteins from the world of microbes. *Appl Microbiol Biotechnol*, **99**, 3807-3823.
 16. Goldbeck, R., Ramos, M. M., Pereira, G. A., Maugeri-Filho, F., 2013. Cellulase production from a new strain *Acremonium strictum* isolated from the Brazilian Biome using different substrates. *Bioresour Technol*, 128, 797-803.
 17. Häkkinen, M., Valkonen, M.J., Westerholm-Parvinen, A., Aro, N., Arvas, M., Vitikainen, M., Penttilä, M., Saloheimo, M., Pakula, T.M., 2014. Screening of candidate regulators for cellulase and hemicellulase production in *Trichoderma*

- reesei* and identification of a factor essential for cellulase production. *Biotechnol Biofuels*, **7**, 14.
18. Hasunuma, T., Ishii, J., Kondo, A., 2015. Rational design and evolutionary fine tuning of *Saccharomyces cerevisiae* for biomass breakdown. *Curr Opin Chem Biol*, **29**, 1-9.
 19. Hasunuma, T., Sanda, T., Yamada, R., Yoshimura, K., Ishii, J., and Kondo, A., 2011. Metabolic pathway engineering based on metabolomics confers acetic and formic acid tolerance to a recombinant xylose-fermenting strain of *Saccharomyces cerevisiae*. *Microb Cell Fac*, **10**, 2.
 20. He, Y., Zhang, J., Bao, J., 2016. Acceleration of biodegradation on dilute acid pretreated lignocellulose feedstock by aeration and the consequent ethanol fermentation evaluation. *Biotechnol Biofuels*, **9**, 19.
 21. Ho, D. P., Ngo, H.H., Guo, W., 2014. A mini review on renewable sources for biofuel. *Bioresour Technol*, **169**, 742-749.
 22. Hou, J., Shen, Y., Jiao, C., Ge, R., Zhang, X., Bao, X., 2015. Characterization and evolution of xylose isomerase screened from the bovine rumen metagenome in *Saccharomyces cerevisiae*. *J Biosci Bioeng*, **121**, 160-165.
 23. Jin, M., Gunawan, C., Balan, V., Lau, M.W., Dale, B.E., 2012. Simultaneous saccharification and co-fermentation (SSCF) of AFEX(TM) pretreated corn stover for ethanol production using commercial enzymes and *Saccharomyces cerevisiae* 424A(LNH-ST). *Bioresour Technol*, **110**, 587-594.
 24. Jin, M., Sarks, C., Gunawan, C., Bice, B.D., Simonett, S.P., Avanas Narasimhan,

- R., Willis, L.B., Dale, B.E., Balan, V., Sato, T.K. 2013. Phenotypic selection of a wild *Saccharomyces cerevisiae* strain for simultaneous saccharification and co-fermentation of AFEX pretreated corn stover. *Biotechnol Biofuels*, **6**, 108.
25. Jönsson, L.J., Martín, C., 2016. Pretreatment of lignocellulose: Formation of inhibitory by-products and strategies for minimizing their effects. *Bioresour Technol*, **199**, 103-112.
26. Kim, I.J., Lee, H.J., Chop, I.G., Kim K.H., 2014. Synergistic proteins for the enhanced enzymatic hydrolysis of cellulose by cellulase. *Appl Microbiol Biotechnol*, **98**, 8469-8480.
27. Kim, S.K., Jin, Y.S., Choi, I.G., Park, Y.C., Seo, J.H. 2015. Enhanced tolerance of *Saccharomyces cerevisiae* to multiple lignocellulose-derived inhibitors through modulation of spermidine contents. *Metab Eng*, **29**, 46-55.
28. Kim, S.R., Park, Y.C., Jin, Y.S., Seo, J.H. 2013. Strain engineering of *Saccharomyces cerevisiae* for enhanced xylose metabolism. *Biotechnol Adv*, **31**, 851-861.
29. Ko, J.K., Um, Y., Woo, H.M., Kim, K.H., Lee, S.M. 2016. Ethanol production from lignocellulosic hydrolysates using engineered *Saccharomyces cerevisiae* harboring xylose isomerase-based pathway. *Bioresour Technol*, **209**, 290-296.
30. Koppam, R., Albers, E., Olsson, L., 2012. Evolutionary engineering strategies to enhance tolerance of xylose utilizing recombinant yeast to inhibitors derived from spruce biomass. *Biotechnol Biofuels*, **5**, 32.

31. Koppram, R., Tomás-Pejó, E., Xiros, C., Olsson, L., 2014. Lignocellulosic ethanol production at high-gravity: challenges and perspectives. *Trends Biotechnol*, **32**, 46-53.
32. Latimer, L.N., Lee, M.E., Medina-Cleghorn, D., Kohnz, R.A., Nomura, D.K., Dueber, J.E. 2014. Employing a combinatorial expression approach to characterize xylose utilization in *Saccharomyces cerevisiae*. *Metab Eng*, **25**, 20-29.
33. Lee, S.H., Kodaki, T., Park, Y.C., Seo, J.H., 2012. Effects of NADH-preferring xylose reductase expression on ethanol production from xylose in xylose-metabolizing recombinant *Saccharomyces cerevisiae*. *J Biotechnol*, **158**, 184-191.
34. Lee, S.M., Jellison, T., Alper, H.S., 2014. Systematic and evolutionary engineering of a xylose isomerase-based pathway in *Saccharomyces cerevisiae* for efficient conversion yields. *Biotechnol Biofuels*, **7**, 122.
35. Lee, Y., Nasution, O., Choi, E., Choi, I.G., Kim, W., Choi, W., 2015. Transcriptome analysis of acetic-acid-treated yeast cells identifies a large set of genes whose overexpression or deletion enhances acetic acid tolerance. *Appl Microbiol Biotechnol*, **99**, 6391-403.
36. Li, Y.C., Mitsumasu, K., Gou, Z.X., Gou, M., Tang, Y.Q., Li, G.Y., Wu, X.L., Akamatsu, T., Taguchi, H., Kida, K., 2016. Xylose fermentation efficiency and inhibitor tolerance of the recombinant industrial *Saccharomyces cerevisiae* strain NAPX37. *Appl Microbiol Biotechnol*, **100**, 1531-1542.

37. Liu, G., Qin, Y., Li, Z., Qu, Y., 2013. Development of highly efficient, low-cost lignocellulolytic enzyme systems in the post-genomic era. *Biotechnol Adv*, **31**, 962-75.
38. Liu, Y., Zhang, G., Sun, H., Sun, X., Jiang, N., and Rasool, A. Lin, Z., Li, C., 2014. Enhanced pathway efficiency of *Saccharomyces cerevisiae* by introducing thermo-tolerant devices. *Bioresour Technol*, **170**, 38-44.
39. Liu, Z.H., Qin, L., Zhu, J.Q., Li, B.Z., Yuan, Y.J., 2014. Simultaneous saccharification and fermentation of steam-exploded corn stover at high glucan loading and high temperature. *Biotechnol Biofuels*, **7**, 67.
40. Lu, Y., Wang, Y., Xu, G., Chu, J., Zhuang, Y., Zhang, S., 2010. Influence of high solid concentration on enzymatic hydrolysis and fermentation of steam-exploded corn stover biomass. *Appl Biochem Biotechnol*, **160**, 360-369.
41. Ma, C., Wei, X.W., Sun, C.H., Zhang, F., Xu, J.R., Zhao, X.Q., Bai, F.W., 2015. Improvement of acetic acid tolerance of *Saccharomyces cerevisiae* using a zinc-finger-based artificial transcription factor and identification of novel genes involved in acetic acid tolerance. *Appl Microbiol Biotechnol*, **99**, 2441-2449.
42. Mahajan, C., Basotra, N., Singh, S., Di Falco, M., Tsang, A., Chadha, B.S., 2016. *Malbranchea cinnamomea*: A thermophilic fungal source of catalytically efficient lignocellulolytic glycosyl hydrolases and metal dependent enzymes. *Bioresour Technol*, **200**, 55-63.
43. Meijnen, J.P., Randazzo, P., Foulquié-Moreno, M.R., van den Brink, J., Vandecruys, P., Stojiljkovic, M., Dumortier, F., Zalar, P., Boekhout, T.,

- Gunde-Cimerman, N., Kokošar, J., Štajdohar, M., Curk, T., Petrovič, U., Thevelein, J.M., 2016. Polygenic analysis and targeted improvement of the complex trait of high acetic acid tolerance in the yeast *Saccharomyces cerevisiae*. *Biotechnol Biofuels*, **9**, 5.
44. Nielsen, F., Tomás-Pejó, E., Olsson, L., Wallberg, O., 2015. Short-term adaptation during propagation improves the performance of xylose-fermenting *Saccharomyces cerevisiae* in simultaneous saccharification and co-fermentation. *Biotechnol Biofuels*, **8**, 219.
45. Parawira, W., Tekere, M., Biotechnological strategies to overcome inhibitors in lignocellulose hydrolysates for ethanol production: review. *Crit Rev Biotechnol*, **31**, 20-31.
46. Parreiras, L.S., Breuer, R.J., Avanasí Narasimhan, R., Higbee, A.J., La Reau, A., Tremaine, M., Qin, L., Willis, L.B., Bice, B.D., Bonfert, B.L., Pinhancos, R.C., Balloon, A.J., Uppugundla, N., Liu, T., Li, C., Tanjore, D., Ong, I.M., Li, H., Pohlmann, E.L., Serate, J., Withers, S.T., Simmons, B.A., Hodge, D.B., Westphall, M.S., Coon, J.J., Dale, B.E., Balan, V., Keating, D.H., Zhang, Y., Landick, R., Gasch, A.P., Sato, T.K. 2014. Engineering and two-stage evolution of a lignocellulosic hydrolysate-tolerant *Saccharomyces cerevisiae* strain for anaerobic fermentation of xylose from AFEX pretreated corn stover. *PLoS One*, **9**, e107499.
47. Peng, B., Shen, Y., Li, X., Chen, X., Hou, J., Bao, X. 2012. Improvement of xylose fermentation in respiratory-deficient xylose-fermenting *Saccharomyces*

- cerevisiae*. *Metab Eng*, **14**(1), 9-18.
48. Pereira, F.B., Romaní, A., Ruiz, H.A., Teixeira, J.A., Domingues, L., 2014. Industrial robust yeast isolates with great potential for fermentation of lignocellulosic biomass. *Bioresour Technol*, **161**, 192-199.
49. Pereira, S.R., Sánchez, I., Nogué, V., Frazão, C.J., Serafim, L.S., Gorwa-Grauslund, M.F., Xavier, A.M., 2015. Adaptation of *Scheffersomyces stipitis* to hardwood spent sulfite liquor by evolutionary engineering. *Biotechnol Biofuels*, **8**, 50.
50. Qin, L., Liu, Z.H., Li, B.Z., Dale, B.E., Yuan, Y.J., 2012. Mass balance and transformation of corn stover by pretreatment with different dilute organic acids. *Bioresour Technol*, **112**, 319-326.
51. Qureshi, A.S., Zhang, J., Bao, J. 2015. High ethanol fermentation performance of the dry dilute acid pretreated corn stover by an evolutionarily adapted *Saccharomyces cerevisiae* strain. *Bioresour Technol*, **189**, 399-404.
52. Shen, Y., Chen, X., Peng, B., Chen, L., Hou, J., Bao, X., 2012. An efficient xylose-fermenting recombinant *Saccharomyces cerevisiae* strain obtained through adaptive evolution and its global transcription profile. *Appl Microbiol Biotechnol*, **96**, 1079-1091.
53. Shi, S., Liang, Y., Zhang, M.M., Ang, E.L., Zhao, H., 2016. A highly efficient single-step, markerless strategy for multi-copy chromosomal integration of large biochemical pathways in *Saccharomyces cerevisiae*. *Metab Eng*, **33**, 19-27.
54. Silva, J. P. A., Mussatto, S.I., Roberto, I.C., 2010. The Influence of initial xylose

- concentration, agitation, and aeration on ethanol production by *Pichia stipitis* from rice straw hemicellulosic hydrolysate. *Appl Biochem Biotechnol*, **162**, 1306-1315.
55. Tiwari, R., Singh, S., Nain, P. K., Rana, S., Sharma, A., Pranaw, K., Nain, L., 2013. Harnessing the hydrolytic potential of phytopathogenic fungus *Phoma exigua* ITCC 2049 for saccharification of lignocellulosic biomass. *Bioresour Technol*, 150, 228-34.
 56. Toquero, C., Bolado, S., 2014. Effect of four pretreatments on enzymatic hydrolysis and ethanol fermentation of wheat straw. Influence of inhibitors and washing. *Bioresour Technol*, **157**, 68-76.
 57. Trivedi, N., Gupta, V., Reddy, C.R., Jha, B., 2013. Detection of ionic liquid stable cellulase produced by the marine bacterium *Pseudoalteromonas* sp. isolated from brown alga *Sargassum polycystum* C. Agardh. *Bioresour Technol*, **132**, 313-319.
 58. Tsai, C.S., Kong, II, Lesmana, A., Million, G., Zhang, G.C., Kim, S.R., Jin, Y.S., 2015. Rapid and marker-free refactoring of xylose-fermenting yeast strains with Cas9/CRISPR. *Biotechnol Bioeng*, **112**, 2406-2411.
 59. Wallace-Salinas, V., Brink, D.P., Ahrén, D., Gorwa-Grauslund, M.F., 2015. Cell periphery-related proteins as major genomic targets behind the adaptive evolution of an industrial *Saccharomyces cerevisiae* strain to combined heat and hydrolysate stress. *BMC Genomics*, **16**, 514.
 60. Wang, M., Zhao, Q., Yang, J., Jiang, B., Wang, F., Liu, K., Fang, X., 2013. A

- mitogen-activated protein kinase Tmk3 participates in high osmolarity resistance, cell wall integrity maintenance and cellulase production regulation in *Trichoderma reesei*. *PLoS One*, **8**, e72189.
61. Wang, X., Bai, X., Chen, D.F., Chen, F.Z., Li, B.Z., Yuan, Y.J., 2015. Increasing proline and myo-inositol improves tolerance of *Saccharomyces cerevisiae* to the mixture of multiple lignocellulose-derived inhibitors. *Biotechnol Biofuels*, **8**, 142.
 62. Wei, N., Oh, E.J., Million, G., Cate, J.H., Jin, Y.S. 2015. Simultaneous utilization of cellobiose, xylose, and acetic acid from lignocellulosic biomass for biofuel production by an engineered yeast platform. *ACS Synth Biol*, **4**, 707-13.
 63. Xiong, M., Chen, G., Barford, J., 2011. Alteration of xylose reductase coenzyme preference to improve ethanol production by *Saccharomyces cerevisiae* from high xylose concentrations. *Bioresour Technol*, **102**, 9206-9215.
 64. Xu, H., Kim, S., Sorek, H., Lee, Y., Jeong, D., Kim, J., Oh, E.J., Yun, E.J., Wemmer, D.E., Kim, K.H., Kim, S.R., Jin, Y.S., 2016. *PHO13* deletion-induced transcriptional activation prevents sedoheptulose accumulation during xylose metabolism in engineered *Saccharomyces cerevisiae*. *Metab Eng*, **34**: 88-96.
 65. Zakaria, M. R., Hirata, S., Fujimoto, S., Ibrahim, I., Hassan, M.A., 2016. Soluble inhibitors generated during hydrothermal pretreatment of oil palm mesocarp fiber suppressed the catalytic activity of *Acremonium* cellulase. *Bioresour Technol*, **200**, 541-547.
 66. Zhang, J., Zhong, Y., Zhao, X., Wang, T., 2010. Development of the cellulolytic fungus *Trichoderma reesei* strain with enhanced beta-glucosidase and filter paper

- activity using strong artificial cellobiohydrolase 1 promoter. *Bioresour Technol*, **101**, 9815-9818.
67. Zhang, M.M., Zhao, X.Q., Cheng, C., Bai, F.W., 2015. Improved growth and ethanol fermentation of *Saccharomyces cerevisiae* in the presence of acetic acid by overexpression of *SET5* and *PPR1*. *Biotechnol J*, **10**, 1903-1911.
 68. Zhang, W., Kou, Y., Xu, J., Cao, Y., Zhao, G., Shao, J., Wang, H., Wang Z, Bao X, Chen G, Liu W., 2013. Two major facilitator superfamily sugar transporters from *Trichoderma reesei* and their roles in induction of cellulase biosynthesis. *J Biol Chem*, **288**, 32861-72.
 69. Zhao, X.Q., Zi, L.H., Bai, F.W., Lin, H. L., Hao, X.M., Yue, G.J., Ho, N.W.Y., 2012. Bioethanol from lignocellulosic biomass. In: Bai, F.W., Liu, C.G., Huang H., Tsao G.T. (Eds), *Biotechnology in China III: Biofuels and Bioenergy, Advances in Biochemical Engineering/ Biotechnology*, Springer, Berlin Heidelberg, **128**, 25-51.
 70. Zheng, D., Wu, X.C., Tao, X.L., Wang, P.M., Li, P., Chi, X.Q., Li, Y.D., Yan, Q.F., Zhao, Y.H., 2011. Screening and construction of *Saccharomyces cerevisiae* strains with improved multi-tolerance and bioethanol fermentation performance. *Bioresour Technol*, **102**, 3020-3027.
 71. Zheng, D., Liu, T.Z., Chen, J., Zhang, K., Li, O., Zhu, L., Zhao, Y.H., Wu, X.C., Wang, P.M., 2013. Comparative functional genomics to reveal the molecular basis of phenotypic diversities and guide the genetic breeding of industrial yeast strains. *Appl Microbiol Biotechnol*, **97**, 2067-2076.

72. Zhong, Y., Wang, X., Yu, H., Liang, S., Wang, T., 2012. Application of T-DNA insertional mutagenesis for improving cellulase production in the filamentous fungus *Trichoderma reesei*. *Bioresour Technol*, **110**, 572-577.
73. Zhu, J. Y., Pan, X.J., Wang, G.S., Gleisner, R., 2009. Sulfite pretreatment (SPORL) for robust enzymatic saccharification of spruce and red pine. *Bioresour Technol*, **100**, 2411-2418.
74. Zhu, J.Q., Qin, L., Li, B.Z., Yuan, Y.J., 2014. Simultaneous saccharification and co-fermentation of aqueous ammonia pretreated corn stover with an engineered *Saccharomyces cerevisiae* SyBE005. *Bioresour Technol*, **169**, 9-18.
75. Zhu, J.Q., Qin, L., Li, W.C., Zhang, J., Bao, J., Huang, Y.D., Li, B.Z., Yuan, Y.J., 2015. Simultaneous saccharification and co-fermentation of dry diluted acid pretreated corn stover at high dry matter loading: Overcoming the inhibitors by non-tolerant yeast. *Bioresour Technol*, **198**, 39-46.

Table 1. Inhibitor concentrations from various agricultural and forestry residues in selected literature*.

Lignocellulosic substrate	Pretreatment method	Main inhibitors			Reference
		acetic	Furfural	5-HM	
		acid		F	
Corn stover	Dilute sulfuric acid	4.30	6.70	1.20	Qin et al., 2012
Corn stover	Steam-explosion	3.30	0.15	n.d	Lu et al., 2010
Corn straw	Steam explosion	1.70	2.20	0.44	Du et al., 2010
Rice straw	Dilute sulfate	1.50	0.13	0.05	Silva et al., 2010
Wheat straw	Dilute NaOH	3.59	n.d	n.d	Toquero and Bolado, 2014
Spruce	Sulfite pretreatment	n.d	0.30	0.15	Zhu et al., 2009
Oil palm	Hydrothermal pretreatments	6.40	3.30	0.30	Zakaria et al., 2016
Spruce	Dilute sulfuric acid	6.30	1.10	3.40	Koppram et al., 2012

*n.d: not detected.

Table 2 A brief summary of bioethanol production from different pretreated biomass with high ethanol titer.

Biomass types	Biomass loading (%)	Operating temperature (°C)	Pre-hydrolysis time (h)	Ethanol titer (g/L)	Y_{Ethanol} (%)	P_{Ethanol} (g/L/h)*	C_{Xylose} (%)	References
DDAP CS	30% DML	34	6	71.4	80.3	0.99	NA	Qureshi et al., 2015
DDAP CS	25% DML	37	12	47.2	65.5	0.49	NA	Zhu et al., 2015
AAPCS	12% GL	38	12	68.8	79.8	0.72	89	Zhu et al., 2014
ACS	9% GL	30	6	54.4	NA	0.78	NA	Jin et al., 2013
SPWM and SPWS	7.5% WIS	32	0	60.0	76.0	0.63	31	Erdei et al., 2013

*The ethanol volumetric productivity was calculated based on the highest ethanol titer and the duration of whole process including pre-hydrolysis and fermentation.

Abbreviations: SPS, steam pretreated spruce; CS, corn stover; DDAP, dry diluted acid pretreatment; ACS, ammonia fibre expansion (AFEX) pretreated corn stover; AAPCS, aqueous ammonia pretreated corn stover; SPWS, steam pretreated wheat straw; SPWM, steam pretreated wheat meal; WIS, water insoluble solids; GL, glucan loading; DML, dry matter loading.

Figure legends

Fig.1 Schematic representations of key processes involved in lignocellulosic ethanol production.

Fig.2 Strategies for improved cellulosic ethanol production using inhibitor-containing cellulosic hydrolysates.

Fig.1

Fig. 2