Biohydrogen production from waste bread in a continuous stirred tank reactor: a techno-economic analysis

Wei Han, Yun Yi Hu, Shi Yi Li, Fei Fei Li, Jun Hong Tang*

College of Materials and Environmental Engineering, Hangzhou Dianzi University,
Hangzhou, 310018, China

Abstract: Biohydrogen production from waste bread in a continuous stirred tank reactor (CSTR) was techno-economically assessed. The treating capacity of the H₂-producing plant was assumed to be 2 ton waste bread per day with lifetime of 10 years. Aspen Plus was used to simulate the mass and energy balance of the plant. The total capital investment (TCI), total annual production cost (TAPC) and annual revenue of the plant were USD931020, USD299746/year and USD639920/year, respectively. The unit hydrogen production cost was USD1.34/m³ H₂ (or USD14.89/kg H₂). The payback period and net present value (NPV) of the plant were 4.8 years and USD1266654, respectively. Hydrogen price and operators cost were the most important variables on the NPV. It was concluded that biohydrogen production from waste bread in the CSTR was feasible for practical application.

Abstract: biohydrogen production; continuous stirred tank reactor; economic analysis;

* Corresponding authors: Jun-Hong Tang, Tel.: +86 13738020870; E-mail address: dr_tjh@163.com

waste bread

1. Introduction

Due to the environmental pollution and depletion of the fossil fuel, it is urgent to look for the alternative energy in the near future (Turner, 2004). Hydrogen is widely regarded as one of the most important energy carriers because it is clean and renewable (Show et al., 2012). At present, hydrogen is mainly produced from fossil raw materials (such as natural gas), and therefore could not solve the problem of environmental deterioration and energy crisis (Acar and Dincer, 2015). [Biological hydrogen production, which could use organic raw material as substrate, seems to be an attractive solution \(Wake, 2012; Han et al., 2016a\).](#) There are mainly two ways for biological hydrogen production: dark fermentation and photo fermentation (Kim et al., 2010). Photo fermentation seems less attractive than dark fermentation because it would encounter the problem of light limitation (Logan et al., 2002). However, dark fermentative hydrogen production is difficult to realize for practical application due to the high unit hydrogen production cost. Using organic waste (such as waste bread) as feedstock for dark fermentative hydrogen production is considered to be a promising way (Van-Ginkel et al., 2005; Chu and Majumdar, 2012).

[Waste bread is a major food waste in the world. It is reported that around 1.5 million](#)

tons of waste bread could be produced annually in the China alone (Han et al., 2016b). Waste bread is regarded as an attractive substrate for biohydrogen production because it contains a large amount of starch and protein (De Gioannis et al., 2013). However, the nutrients need to be hydrolyzed into glucose and free amino nitrogen (FAN) prior to be used by H₂-producing microorganisms, and which is regarded as the limited step for biohydrogen production (Kim et al., 2011). In the previous study, a novel bioprocess combining solid state fermentation (SSF) and dark fermentation for hydrogen production from waste bread has been successfully developed (Han et al., 2016b). *Aspergillus awamori* and *Aspergillus oryzae* were utilized to generate complex enzymes (glucoamylase and protease) from waste bread via SSF. The complex enzymes were then used to hydrolyze the waste bread to generate the liquid waste bread hydrolysate which was utilized as substrate for subsequent biohydrogen production. The proposed combined bioprocess has been proved to effectively accelerate the hydrolysis speed, improve the nutrients conversion rate and increase the biohydrogen yield (Han et al., 2015b). In light of the above technological analysis, the purpose of the present work was to assess the techno-economic feasibility of biohydrogen production from waste bread in the CSTR.

2. Methods and materials

2.1 Description of biohydrogen production from waste bread in the CSTR

Fig. 1 showed the description of biohydrogen production from waste bread in the CSTR.

The government was responsible for the collection and transportation of waste bread

(Lam et al., 2014). The composition of the waste bread was summarized in the previous

study (Han et al., 2016b). The collected waste bread was stored in the E1 and milled

into smaller size with water in the E2. The pretreated waste bread was then transferred

in the E3 where glucoamylase and protease could be produced via SSF by *A. awamori*

and *A. oryzae* with temperature of 30 °C. The produced enzymes were utilized to

hydrolyze waste bread in the E4. The temperature and agitation speed for enzymatic

hydrolysis of waste bread were 55 °C and 500 rpm, respectively. The mixture was then

centrifuged in the E5 with 10000 rpm at 4 °C and filtered to obtain the liquid waste

bread hydrolysate and undigested waste bread. The above conditions have been

approved to be optimal for SSF and waste bread hydrolysis (Han et al., 2015a). The

hydrolysis efficiency from starch to glucose was 61.4%. The produced waste bread

hydrolysate, which was rich in glucose and free amino acid, was diluted with tap water

in the E6 to get the optimal chemical oxygen demand (COD) concentration for

biohydrogen production (Han et al., 2016). The anaerobic sludge used for biohydrogen

production was collected and stored in the E10 and heat pretreated in the E8 at 100 °C

to inhibit the activity of CH₄-producing microorganism. In order to save the energy loss,

the heat exchangers (E9) were arranged in the H₂-producing plant. The pretreated sludge was inoculated into the E7 with waste bread hydrolysate to produce the biogas which was purified in the E11 to get H₂ and CO₂.

The treating capacity of the H₂-producing plant was assumed to be 2 ton waste bread per day with lifetime of 10 years. As the glucose yield obtained from the waste bread hydrolysate was 0.277 g glucose/g waste bread (Han et al., 2016b), it could be calculated that the glucose production was 554 kg/day. The glucose utilization derived from waste bread hydrolysate was 84.5%. The H₂ and CO₂ contents in the produced biogas were 37.6% and 59.8%, respectively. The highest hydrogen production rate in the CSTR was achieved at COD of 6000 mg/L and HRT of 6 h. So, the capacity of the H₂-producing plant (CSTR) could not be smaller than 58.8 m³. Aspen Plus was used in this study to simulate the mass and energy balance of the H₂-producing plant.

2.2 Total capital investment

The total capital investment (TCI) of the H₂-producing plant was dependent on fixed capital cost (FCC) and working capital cost (WCC). As a new plant, the FCC included the land cost, equipments cost and installation cost. The land cost could not be considered since the H₂-producing plant was built for waste-recycle and the local government would provide the space for free (Lam et al., 2014). The main equipments

used for biohydrogen production were indicated in the Fig. 1. The quantities of the equipments were simulated by mass and energy balance using Aspen Plus and the quotations of the equipments were supplied by the local machine factory. In addition to the equipments cost, the installation cost for building up the H₂-producing plant was taken into account. The WCC was considered to be 6.5% of the FCC (Urbaniec and Grabarczyk, 2014). So, according to the Eq. (1), the TCI of the H₂-producing plant could be calculated.

$$TCI = FCC (\text{Equipments cost} + \text{Installation cost}) + WCC \quad (1)$$

2.3 Total annual production cost

The total annual production cost (TAPC) included the raw materials cost, operators cost, utilities cost, waste treatment cost, maintenance and insurance. As the H₂-producing plant was a waste-recycle project, the government was responsible for the collection and transportation of waste bread (Lam et al., 2014). In this case, the raw materials used for biohydrogen production were only fungi and chemicals. The quantity of the fungi (*A. awamori* and *A. oryzae*) and chemicals were simulated by Aspen Plus and their unit prices were provided by the local chemical company. Operators cost was the charge for hiring the operators with the average salary of USD3000/year. It was required 6 staffs to operate the H₂-producing plant. The waste treatment cost could not be considered

because the liquid waste produced from the H₂-producing plant (mainly ethanol, acetate and butyrate) could be used for further biomethane production and the solid waste (mainly undigested waste bread) could be utilized to feed animal. The maintenance and insurance of the plant were assumed to be 1% and 2% of the FCC, respectively (Ljunggren and Zacchi, 2010). So, the TAPC for the H₂-producing plant could be calculated (Eq. (2)).

$$\text{TAPC} = \text{Raw material cost} + \text{Utilities cost} + \text{Labour cost} + \text{Maintenance} + \text{Insurance} \quad (2)$$

The unit hydrogen production cost (per cubic meter or kilogram) was estimated based on Eq. (3).

$$\text{Unit hydrogen production cost} = (\text{TCI}/L_T + \text{TAPC} - R_{EH})/P_H \quad (3)$$

where L_T was the lifetime of the H₂-producing plant, R_{EH} was the revenue excluding hydrogen and P_H was the cubic meter or kilogram of produced hydrogen.

2.4 Total annual profit

The total annual profit (TAP) was the annual revenue minus total annual production cost.

The annual revenue of the H₂-producing plant was originated from the sales of H₂ (S_H), CO₂ (S_{CD}) and undigested waste bread (S_{UFW}) and the charge for waste bread treatment (C_{FWT}). The prices of H₂ and CO₂ were USD2.7/m³ and USD0.3/m³, respectively (Li et al., 2012). Undigested waste bread could be utilized to feed animal (fish feed) with price

of USD0.15/kg (Lam et al., 2014). The waste bread producers need to pay the charge of waste bread treatment (USD16.11/ton waste bread). So, the annual revenue and total annual profit of the H₂-producing plant could be calculated according to Eq. (4) and Eq. (5).

$$\text{Annual revenue} = S_H + S_{CD} + S_{UFW} + C_{FWT} \quad (4)$$

$$\text{Total annual profit} = \text{Annual revenue} - \text{Total annual production cost} \quad (5)$$

3. Results and discussion

3.1 Analysis of total capital investment (TCI) of the H₂-producing plant

The TCI of the H₂-producing plant included the FCC (equipment cost and installation cost) and WCC (Eq. (1)). The equipment cost was dependent on the quantity of the major equipments used for biohydrogen production. Table 1 presented the equipments cost which was USD408200 in total. Table 2 summarized the installation cost for building up the H₂-producing plant. According to the equipments cost (Table 1) and installation cost (Table 2), the FCC of USD874200 could be estimated. WCC, which was considered to be 6.5% of the FCC (Urbaniec and Grabarczyk, 2014), was USD56820. Therefore, the TCI for the H₂-producing plant was USD931020. As shown in Fig. 2, the largest part of the TCI was installation cost (50%) which indicated that installation cost was the main constraint for set-up of H₂-producing plant.

3.2 Analysis of total annual production cost (TAPC) of the H₂-producing plant

The total annual production cost (TAPC), which included the raw material cost, utilities cost, labour cost, maintenance and insurance, were shown in Table 3. The quantity of the raw material (fungi, NaHCO₃ and H₂SO₄) and utilities (electricity and process water) used for the operation of H₂-producing plant was simulated by Aspen Plus. According to the local unit price of chemicals, electricity and process water, the raw material cost (USD19120/year) and utilities cost (USD74400/year) could be calculated, respectively. The total employees for operating the H₂-producing plant were 6 with average annual salary of USD30000/employee. So, the operators cost of H₂-producing plant was USD180000/year. The maintenance and insurance, which were 2% and 1% of the FCC (Ljunggren and Zacchi, 2010), were USD17484/year and USD8742/year, respectively. Therefore, the TAPC of USD299746/year could be calculated according to Eq. (2). Fig. 3 showed the percentage of TAPC of the H₂-producing plant. The largest part of the TAPC was the operators cost (60%). So, it could be concluded that reducing the quantity of employee (or improve the automatic technology for operating the plant) was the most important parameter for realize biohydrogen production from waste bread in industrial application.

3.3 Analysis of total annual profit and unit hydrogen production cost of the H₂-producing plant

The annual revenue of the H₂-producing plant was originated from the sales of H₂ (S_H), CO₂ (S_{CD}) and undigested waste bread (S_{UFW}) and the charges for waste bread treatment (C_{FWT}) (Table 4). The highest hydrogen production rate and carbon dioxide production rate of CSTR were 353.9 ml/h/l H₂ and 530.8 ml/h/l CO₂, respectively (Han et al., 2016b). So, the annual yield of H₂ and CO₂ were 182060 m³ H₂ and 273080 m³ CO₂, respectively. It could be calculated that the annual revenue from sales of H₂ and CO₂ were USD491560/year and USD81920/year, respectively. The S_{UFW} could be utilized to feed animal with revenue of USD54760/year. According to the annual quantity of treated waste bread (730 ton) and unit price for waste bread treatment (USD16/ton), the C_{FWT} of USD11680/year could be calculated. Therefore, the annual revenue of the H₂-producing plant was USD639920/year. As the total annual production cost was USD299746/year, the total annual profit of USD244186/year could be calculated. Fig. 4 showed the percentage of annual revenue of the H₂-producing plant. It was observed that the revenue from sale of H₂ (76.8%) occupied the most important part of the annual revenue. So, the hydrogen yield and hydrogen market price played a crucial role for realizing biohydrogen production in industrial scale.

According to Eq. (3), the unit hydrogen production cost of the plant was USD1.34/m³

H₂ (or USD14.89/kg H₂). The current unit hydrogen production costs from other technologies were shown in Table 5. It was observed that the steam methane reforming was the most competitive way in term of the unit hydrogen production cost since it had been developed and industrialized for a long period. Water electrolysis seemed to be more attractive than other technologies, but it needed to consume electricity power to release hydrogen from water. Although the obtained unit hydrogen production cost could not compete with other reported ways at the present time, it was still much cheaper than the hydrogen market unit price (USD2.7/m³). Furthermore, biohydrogen production from waste bread could be a promising and sustainable technology in the future because it could use renewable substrate (waste bread) for hydrogen production. The potential benefits obtained by biohydrogen production from waste bread are much more meaningful than other technologies.

3.4 Profitability criteria of the H₂-producing plant

Fig. 5 (a) showed the net present value (NPV) and payback period (PP) of the H₂-producing plant with different discount rate. Obviously, the NPV increased and PP decreased with the discount rate decreased from 30% to 0 which indicated that the H₂-producing plant was more attractive with lower discount rate. The optimal NPV of USD1266654 and PP of 4.8 years were obtained at discount rate of 0. Fig. 5 (b)

described the internal rate of return (IRR) of the H₂-producing plant from waste bread. It was observed that IRR was 21.77% with the NPV was equal to 0. The positive IRR indicated the attractiveness of the hydrogen-producing plant. Therefore, it was found that the H₂-producing plant was feasible for industrial application.

In order to examine the effects of the economic variables on the performance of the H₂-producing plant, the sensitivity analysis was carried out in this study. Fig. 6 (a) indicated the sensitivity analysis of the H₂-producing plant from waste bread. It was observed that the most important variables on the NPV were hydrogen price and operating labor cost with sensitivity slopes of $y = 4E + 06x + 1E + 06$ and $y = -2E + 06x + 1E + 06$, respectively (Table 6). Obviously, the hydrogen price and operating labor cost were the largest parts of the annual revenue and total annual production cost, respectively. So, reducing the quantity of operators and improving the automatic technology were the best way to avoid the risk while increasing the hydrogen yield was the most efficient method for realizing hydrogen production for industrial application.

Fig. 6 (b) described the annual cost or revenue of the H₂-producing plant with the required quantity of the waste bread per day. The fixed costs were assumed to keep unchanged for treating 2 ton waste bread/day. The variable cost, total cost and revenue of the H₂-producing plant were direct proportion to the quantity of treated waste bread. It was observed from Fig. 6 (b) that the revenue was bigger than the total cost when the

quantity of treated waste bread was 0.58 ton/day. Therefore, the least required quantity of treated waste bread per day was 0.58 ton and the H₂-producing plant began to profit when the quantity of the treated waste bread was higher than that point.

4. Conclusions

The feasibility of the biohydrogen production in a continuous stirred tank reactor (CSTR) from waste bread was assessed. The obtained unit hydrogen production cost was USD1.34/m³ H₂ (or USD14.89/kg H₂) which was much cheaper than the hydrogen market unit price (USD2.7/m³). The H₂-producing plant was more attractive with lower discount rate and began to profit when the quantity of the treated waste bread was higher than 0.58 ton/day. Reducing the quantity of operating labor and improving the automatic technology were the best way to avoid the risk of industrial biohydrogen production.

Acknowledgements

This research was supported by National Science Foundation of China (No. 41373121), Zhejiang Education Department (Y201533249) and Research Foundation from Hangzhou Dianzi University (KYS205613034).

References

1. Acar, C., Dincer, I., 2015. Impact assessment and efficiency evaluation of hydrogen production methods. *Int. J. Energ. Res.* 13, 1757-1768.
2. Chu, S., Majumdar, A., 2012. Opportunities and challenges for a sustainable energy future. *Nature* 488, 294-303.
3. De Gioannis, G., Muntoni, A., Poletti, A., Pomi, R., 2013. A review of dark fermentative hydrogen production from biodegradable municipal waste fractions. *Waste Manage.* 33, 1345-1361.
4. Dufo-Lopez, R., Bernal-Agustin, L.Z., Mendoza, F., 2009. Design and economical analysis of hybrid PV-wind systems connected to the grid for the intermittent production of hydrogen. *Energy Policy* 37, 3082-3095.
5. Galera, S., Gutierrez-Ortiz, F.J., 2015. Techno-economic assessment of hydrogen and power production from supercritical water reforming of glycerol. *Fuel* 144, 307-316.
6. Guerra-Lemus, R., Martinez-Duart, J.M., 2010. Updated hydrogen production costs and parties for conventional and renewable technologies. *Int. J. Hydrogen Energy* 35, 3929-3936.
7. Han, W., Hu, Y.Y., Li, S.Y., Li, F.F., Tang, J.H., 2016a. Biohydrogen production in the suspended and attached microbial growth systems from waste pastry hydrolysate.

Bioresour. Technol. 218, 589-594.

8. Han, W., Huang, J.G., Zhao, H.T., Li, Y.F., 2016b. Continuous biohydrogen production from waste bread by anaerobic sludge. Bioresour. Technol. 212, 1-5.

9. Han, W., Lam, W.C., Melikoglu, M., Wong, M.T., Leung, H.T., Ng, C.L., Yan, P., Yeung, S.Y., Lin, C.S.K., 2015a. Kinetic analysis of a crude enzyme extract produced via solid state fermentation of bakery waste. ACS Sustain. Chem. Eng. 3, 2043-2048.

10. Han, W., Ye, M., Zhu, A.J., Zhao, H.T., Li, Y.F., 2015b. Batch dark fermentation from enzymatic hydrolyzed food waste for hydrogen production. Bioresour. Technol. 191, 24-29.

11. Hatech, C., Center, A., Feitelberg, A.S., Fisher, E.M., Mutolo, P.F., 2013. Economic analysis of hydrogen production from wastewater and wood for municipal bus system. Int. J. Hydrogen Energy 38, 16002-16010.

12. Kalinci, Y., Hepbasli, A., Dincer, I., 2015. Techno-economic analysis of a stand-alone hybrid renewable energy system with hydrogen production and storage options. Int. J. Hydrogen Energy 40, 7652-7664.

13. Kim, D.H., Kim, S.H., Kim, H.W., Kim, M.S., Shin, H.S., 2011. Sewage sludge addition to food waste synergistically enhances hydrogen fermentation performance. Bioresour. Technol. 102, 8501-8506.

14. Kim, D.H., Kim, S.H., Kim, K.Y., Shin, H.S., 2010. Experience of a pilot-scale hydrogen producing anaerobic sequencing batch reactor (ASBR) treating food waste. *Int. J. Hydrogen Energy* 35, 1590-1594.
15. Lam, K.F., Leung, C.C.J., Lei, H.M., Lin, C.S.K., 2014. Economic feasibility of a pilot-scale fermentative succinic acid production from bakery wastes. *Food Bioprod. Process.* 92, 282-290.
16. Li, Y.C., Liu, Y.F., Chu, C.Y., Chang, P.L., Hsu, C.W., Lin, P.J., Wu, S.Y., 2012. Techno-economic evaluation of biohydrogen production from wastewater and agricultural waste. *Int. J. Hydrogen Energy* 37, 15704-15710.
17. Ljunggren, M., Zacchi, G., 2010. Techno-economic evaluation of a two-step biological process for hydrogen production. *Biotechnol. Prog.* 26, 496-504.
18. Logan, B.E., Oh, S., Kim, I.S., Van-Ginkel, S., 2002. Biological H₂ production measured in batch anaerobic respirometers. *Environ. Sci. Technol.* 36, 2530-2535.
19. Show, K.Y., Lee, D.J., Tay, J.H., Lin, C.Y., Chang, J.S., 2012. Biohydrogen production: current perspectives and the way forward. *Int. J. Hydrogen Energy* 34, 15616-15631.
20. Turner, J. A., 2004. Sustainable Hydrogen Production. *Science* 305, 972-974.
21. Urbaniec, K., Grabarczyk, R., 2014. Hydrogen production from sugar beet molasses - a techno-economic study. *J. Clean. Prod.* 65, 324-329.

22. Van-Ginkel, S.W., Oh, S.E., Logan, B.E., 2005. Biohydrogen gas production from food processing and domestic wastewaters. *Int. J. Hydrogen Energy* 30, 1535-1542.
23. Wake, B., 2012. Energy economics: Biofuel economic potential. *Nat. Clim. Chang.* 2, 394-395.
24. Yasin, N.H.M., Mumtaz, T., Hassan, M.A., Rahman, N.A.A., 2013. Food waste and food processing waste for biohydrogen production: A review. *J. Environ. Manage.* 130, 375-385.

Figure legends

Table 1 Equipment cost of the H₂-producing plant from waste bread.

Table 2 Installation cost of the H₂-producing plant from waste bread.

Table 3 Total annual production cost of the H₂-producing plant from waste bread.

Table 4 Annual revenue of the H₂-producing plant from waste bread.

Table 5 Unit hydrogen production costs with different processes.

Table 6 Results of sensitivity analysis of the H₂-producing plant from waste bread.

Fig. 1. The flow of biohydrogen production from waste bread in the CSTR.

Fig. 2. The percentage of total capital investment of the H₂-producing plant.

Fig. 3. The percentage of total annual production cost of the H₂-producing plant.

Fig. 4. The percentage of annual revenue of the H₂-producing plant.

Fig. 5. Cumulative cash flow diagram at different discount rates (a) and internal rate of return (b).

Fig. 6. Sensitivity analysis (a) and breakeven chart (b) of the H₂-producing plant from waste bread.

1 **Table 1** Equipment cost of the H₂-producing plant from waste bread.

Code	Equipment	Specification	Quantity	Cost (USD)
E1	Waste bread storage	Working capacity: 20 ton	1	15000
E2	Waste bread grinding	Working capacity: 2 ton/h	1	72000
E3	Solid state fermentation	Oil jacket	2	24000
E4	Waste bread hydrolysis	Oil jacket with stirrer	1	46000
E5	Centrifuge of mixture	Working capacity: 670 L/h	1	28200
E6	Waste bread hydrolysate tank		1	15000
E7	CSTR	Working volume: 29.4 m ³	2	55000
E8	Sludge heat pretreated equipment	100°C thermostatic control	1	30000
E9	Heat exchanger	Heat exchanger	3	45000
E10	Sludge storage	100°C	1	15000
E11	Biogas purified system	Separation of produced biogas	1	63000
Total	-	-	-	408200

2

3

4

1 **Table 2** Installation cost of the H₂-producing plant from waste bread.

Item	Cost (USD)	Item	Cost (USD)
Installation	68000	Instrumentation	17200
Piping	40800	Supervision	40800
Electrical systems	27200	Construction	54400
		expenses	
Buildings	68000	Legal expenses	13600
Service facilities	34000	Contractor's fee	20400
Yard improvements	13600	Contingency	68000
Total	-	-	466000

2

3

4

5

6

7

8

9

10

1 **Table 3** Total annual production cost of the H₂-producing plant from waste bread.

	Component	Unit price (USD)	Quantity	Cost
Raw materials cost	<i>A. awamori</i>	6.3/kg	200	1260
(Chemicals)				
	<i>A. oryzae</i>	37.6/kg	200	7520
	NaHCO ₃	10/ton	950	9500
	H ₂ SO ₄	4/ton	210	840
Utilities cost	Electricity	0.084/kWh	600000	50400
	Process water	0.1/m ³	240000	24000
Labor cost	-	30000/employee	6	180000
Maintenance	-	2% of FCC	-	17484
Insurance	-	1% of FCC	-	8742
Total	-	-	-	299746

2

3

4

5

6

1 **Table 4** Annual revenue of the H₂-producing plant from waste bread.

Product	Quantity	Unit price (USD)	Revenue (USD/year)
H ₂	182060 m ³	2.7	491560
CO ₂	273080 m ³	0.3	81920
Solid biomass (fish feed)	365 ton	150	54760
Waste bread treatment	730 ton	16	11680
Annual revenue (after tax)	-	-	639920 (543932)
Total annual production cost	-	-	299746
Total annual profit	-	-	244186

2

3

4

5

6

1 **Table 5** Unit hydrogen production costs with different processes.

Processes	Unit H ₂ production price (USD/kg H ₂)	References
Steam methane reforming	4-5	Hatech et al., 2013
Water electrolysis	8.4-12.2	Yasin et al., 2013
Hydropower electrolysis	5.4-7.9	Guerrro-Lemus and Martinez-Duart, 2010
Supercritical water reforming of glycerol	5.36	Galera and Gutierrez-Ortiz, 2015
Solar thermochemical cycle	6.7-11.6	Guerrro-Lemus and Martinez-Duart, 2010
Hybrid PV-wind (photovoltaic-wind)	12-13	Dufo-Lopez et al., 2009
Biohydrogen production from waste bread	14.9	This study

2

3

4

5

1 **Table 6** Results of sensitivity analysis of the H₂-producing plant from waste bread.

Item	Sensitivity slopes
H ₂ price	4E + 06x + 1E + 06
CO ₂ price	737280x + 1E + 06
Solid biomass	492840x + 1E + 06
Operators cost	-2E + 06x + 1E + 06
Utilities cost	-669600x + 1E + 06
Raw materials cost	-172080x + 1E + 06

2

3

4

5

Fig. 1. The flow of biohydrogen production from waste bread in the CSTR. (E1: waste bread storage; E2: waste bread grinding; E3: solid state fermentation; E4: waste bread hydrolysis; E5: centrifuge of the mixture; E6: waste bread hydrolysate tank; E7: CSTR; E8: sludge heat pretreated equipment; E9: heat exchanger; E10: sludge storage)

Fig. 2. The percentage of total capital investment of the H₂-producing plant.

Fig. 3. The percentage of total annual production cost of the H₂-producing plant.

Fig. 4. The percentage of annual revenue of the H₂-producing plant.

a

b

Fig. 5. Cumulative cash flow diagram at different discount rates (a) and internal rate of return (b).

Fig. 6. Sensitivity analysis (a) and breakeven chart (b) of the H₂-producing plant from waste bread.