1 **Novel approach to evaluate the dynamic variation of wind drift and**
2 **evaporation losses under moving irrigation systems**

3 S-H. Sadeghi^{a,*}, T. Peters^a, M.Z. Amini^a, S. L. Malone^b and H.W. Loescher^c,

4 ^a Dept. of Biological Systems Engineering, Washington State University, Prosser, WA

5 ^b US Forest Service, Rocky Mountain Research Station, Fort Collins, CO

6 ^c The National Ecological Observatory Network (NEON), Boulder, CO, and the Institute of
7 Alpine and Arctic Research (INSTAAR), University of Colorado, Boulder, CO

8
9
10 * *Corresponding author.a*

11 E-mail address: s.hossein.sadeghi@wsu.edu
12
13

1.0 Abstract

The increased need for water and food security requires the development of new approaches to save water through irrigation management strategies, particularly for center pivot irrigation. To do so entails monitoring of the dynamic variation in wind drift and evaporation losses (WDELs) of irrigation systems under different weather conditions and for relatively long time periods. The historical catch can method has limited our ability to address this goal. Here, a new and easy-to-implement methodology, called the strip test, was developed and validated against the catch can technique. Our results showed strong agreement between the catch can method and the strip test for determining the average water application efficiency ($WAE \approx 1 - WDEL$). Because the strip test method was measured for shorter intervals compared to the catch can method, the variables influencing WAE were able to be compared during each test. WAE had a large variance over time, which was controlled, in part, by wind speed ($> 4 \text{ m s}^{-1}$). Site-specific characterisation of WDEL is needed to apply this technique. Once applied, it can provide a better understanding of WAE behaviour over the time, and enhance the capability of predicting results for the optimising water use in sprinkler irrigation.

Keywords: wind drift; evaporation loss; center pivot; catch can test; water application efficiency; weather condition; strip test

Nomenclature		T	Temperature ($^{\circ}\text{C}$)
j	an index representing the tip number within each 5-min interval	WAE	water application efficiency
L	total distance between the first and the last row of cans (m)	WDEL	wind drift and evaporation loss
m	the total number of tips over 5-min for strips B	WAE_{can}	WAE from the catch can method
n	the total number of tips over 5-min for strips A	WAE_{Strip}	WAE from the strip method
p	the total number of tips over 5-min for strips C	z_i	the catch can irrigation depth after taking evaporation into account (m)

q_{av}	average sprinkler discharge ($m^3 \text{ min}^{-1}$)	α	Tipping bucket calibration coefficient
$q_{A,j}$	the flow rate for strips A after the j th tip ($m^3 \text{ min}^{-1}$)	β	strip width (m)
$q_{B,j}$	the flow rate for strips B after the j th tip ($m^3 \text{ min}^{-1}$)	Δt	time difference between two consecutive tips
$q_{C,j}$	the flow rate for strips C after the j th tip ($m^3 \text{ min}^{-1}$)	λ	sprinkler head spacing (m)
RH	relative humidity		

2.0 Introduction

In many areas of the world, 70 to 80 % of available fresh water is currently used in agriculture (Hoekstra & Chapagain, 2007). However, it is expected that as population and economy grow, a larger fraction of available water will be required for non-agricultural purposes, *e.g.*, urban and industrial applications (Boserup, 2005). Also, climate change has already limited water resources for many regions of the world (Li et al. 2007; McVicar *et al.*, 2007; Bandyopadhyay *et al.*, 2009), which has a negative feedback to future agricultural sustainability and food security (Rockström *et al.*, 2009; Gheysari *et al.*, 2015). Optimising agronomic water use efficiency through new irrigation management approaches is one way to mitigate this negative feedback, while at the same time, maximizing economic returns (Evans, 2008; Montazar & Behbahani, 2007; Delirhasannia *et al.*, 2010).

Center pivot irrigation systems currently irrigate more than 12.5 million ha around the globe (Spears, 2003; Sadeghi & Peters, 2013), and they are steadily replacing traditional flood irrigation and other types of sprinkler irrigation. The key advantage of center pivots is their ability to apply water on a regular and consistent basis (Peters & Evett, 2007). In addition, pivots can easily irrigate large fields with relatively low labour and energy costs, and they are also adaptable to different and changing management objectives (Keller & Bliesner, 1990; Kincaid *et al.*, 1996). Despite these advantages, center pivot systems are unable to irrigate the whole circle in a perfectly uniform manner. The ‘global’ water

application uniformity is dependent on the water application efficiency (WAE), *i.e.*, the amount of water that reaches the soil surface for storage divided by the amount of water that leaves the sprinkler nozzles for any given area (Harrison, 1993, ANSI 1995). It is generally recognised that typical center pivots will have an average WAE of 80 - 85% (Musick *et al.*, 1988; Neibling, 2009). The temporal WAE is, however, not necessarily within this range and mostly depends on wind drift and evaporation losses (WDELs, where $WAE \approx 1 - WDELs$), *i.e.*, spray losses (Schneider, 2000; Ortiz *et al.*, 2009) that occur during the irrigation event. The most rapid center pivots complete a full rotation in $\sim 1\frac{1}{2}$ days, but 2-to-4 days per rotation is typical. Over this time period a wide range in weather (synoptic), diurnal, and microclimate conditions occurs. On a large scale, this contributes to poor application uniformity under center pivots, as well as inaccurate estimates of actual water application depths. A grower using an irrigation system with inconsistent uniformity must then apply additional water in order to adequately irrigate the entire field, often applying water when and where it is not needed. Overwatering some areas increases the risk of potential runoff, nutrient leaching and soil loss (Santos *et al.*, 2003; Bauder *et al.*, 2008). Non-uniform watering will also result in non-uniform plant growth reducing overall yield and producing a loss of quality (Ortiz *et al.*, 2010).

Finding practical solutions to reduce the temporal variation in center pivot water application efficiency is clearly needed. Catch-can based studies have been conducted in the past to measure the WAE of pressurised irrigation systems (Christiansen, 1942; Frost & Schwalen, 1955; George, 1955; Kraus, 1966; Sternburg, 1967; Yazar *et al.*, 1984; Robinson, 1973; Kohl *et al.*, 1987; Musick *et al.*, 1988; Seginer *et al.*, 1991; Abo-Ghobar, 1992; Tarjuelo *et al.*, 1999; McLean *et al.*, 2000; Faci *et al.*, 2001; Ocampo *et al.*, 2003; Playán *et al.*, 2005; Silva, 2006; Bavi *et al.*, 2009; Ortiz *et al.*, 2009; King *et al.*, 2012). The testing usually involved the placement of multiple catch cans in a networked pattern and estimating

the amount of water being delivered to the cans (assuming spatial independence of the measurements, Loescher *et al.*, 2002). Although the catch-can test is a standardised international test (ISO 11545) that is quick and suitable for discretely evaluating system performance during the growing season, it cannot be used to measure the continuous variation of the WAE due to (i) its lack of spatial representation, *i.e.*, n-size sampling theory (Loescher *et al.*, 2014), (ii) its inability to reflect the dynamic variation of WAE, *i.e.*, more than 30-min is needed and only a single data point is provided at the end of the experiment, (iii) low catch efficiency occurring under windy conditions (Kohl, 1972; Marek *et al.*, 1985; Livingston *et al.*, 1985; Hindawi *et al.*, 2005) and; (iv) it is a cumbersome and time-consuming technique (Sadeghi & Peters, 2012; Uddin *et al.*, 2010). For example, recent catch can based studies carried out by Playán *et al.* (2005) and Ortiz *et al.* (2009) used only 52 and 47 irrigation tests to evaluate WDELs under a center pivot irrigation.

Optimising irrigation WAE requires a new approach to advance our understanding of the abiotic controls on the continuous variation of WDELs under different weather conditions. As such, estimates of WAE (and subsequently WDELs) must be determined over both short- and long-sampling periods that span the microclimate (5 to 60-min) diurnal (24-h), and synoptic (several days) controls. Using a larger catchment area can also be measured more frequently and be a possible solution to achieve this goal, *i.e.*, collector strips. This method has been previously used to evaluate the uniformity of spray distribution from nozzles in laboratory conditions (rf. Sayinci and Bastaban, 2010) as well as estimating surface runoff and/or sediment on different soil textures (rf. Sharpley, 1995; Ghadiri *et al.*, 2001). However, to date, no effort has been made to use this technique for measuring the WAE under irrigation systems. Here, we propose, develop and validate the strip method as a cost effective technique to monitor WAE under different weather conditions for center pivot and linear move irrigation systems.

3.0 Materials and Method

We used a two-span stationary linear move irrigation system located at the Irrigated Agricultural Research and Extension Center (IAREC), Washington State University, Prosser, WA, USA (46° 15' 6.40" N, 119° 44' 21.64" W, 351 m a.s.l). Each span was 60 m long and consisted of twenty sprinklers installed at a 3 m spacing and 1.5 m a.g.l. Sprinklers were six-groove spinner yellow plate spray (model S3000, Nelson Irrigation Corp., Walla Walla, WA, USA), and were equipped with 103.42 KPa pressure regulators and 4.37 mm diameter nozzles (#22, Nelson Irrigation Corp). The nozzle flow rate was characterised before this study as 13 l min⁻¹ from measures of discharged volume and irrigation time.

To capture the amount of water being delivered to the soil surface, three small surface runoff catchments (*i.e.*, referred to as strips, 21 m × 1 m × 0.1 m) were made from a wooden berm, impervious tarp on the soil, and a sub-surface mounted tipping bucket rain gauge (TB1L; Hydrological Services Pty Ltd, Australia) (Fig. 1). These strips were placed underneath- and perpendicular- to the lateral movement of the linear irrigation system (see A, B and C in Fig. 2). Preliminary characterisation of the sprinklers determined a maximum wetted radius of 10 m under very windy conditions (~ 6 m s⁻¹). Because the linear system was stationary and positioned at the center of the collection strips, the 21 m span length was therefore assumed to be a representative area. PVC pipes (25 mm diameter) were attached to the top of each berm so that catchment surface area was well defined (*i.e.*, 21 m²). The soil was bare with a slope of 0.1% (Nakawuka *et al.* 2014).

Because the prevailing wind direction for the area under study was SW to NE, we positioned the strips to capture the full (not partial) effect of the prevailing winds. Hence, the strips were placed in the middle of the left span and close to the middle tower (Fig. 2), which also minimised the effect of edge sprinklers underestimating WDELs. It should be noted that the 20 sprinklers on the right span were not used during this study to avoid additional runoff

not contributed by our experimental design. We also objectively chose the placement of the strips to assure spatial representation (*i.e.*, effect of the catchment location) of the WDELs in relation to the distance from the sprinklers, *i.e.*, the right berm of strip C was located exactly beneath the 6th sprinkler whereas those of strips B, and A were 1 m and 2 m away from the 7th, and the 8th sprinkler, respectively (Fig. 2). The strips were installed by gently levelling the soils to remove any depressions from the surface.

The berms were made of wood and were funnelled downstream such that the runoff was oriented toward the outlet (Fig. 1). Irrigation water was collected within the strip using a large waterproof tarpaulin that was placed over the strips creating impermeable surface to prevent any infiltration during the experiment. The tarpaulin was green in colour to simulate the presence of a very short and uniform plant canopy. Attention was paid not to produce significant wrinkles when installing the tarpaulin. The edges of the tarpaulins at each side of the strips were attached to the ground by being buried in adjacent soil and held down with heavy objects. For additional precaution, 6 rectangular asphalt shingles (1020 mm × 340 mm × 30 mm) were placed inside each strip every 3 m to fix the inside tarpaulin to the ground and prevent the wind from blowing underneath.

Local meteorology was measured 2 m upwind of strip B (Fig. 2) in the prevailing wind direction using a cup anemometer (014A-L; Campbell Scientific Inc., Logan, UT, USA), a wind direction sensor (024A-L; Campbell Scientific Inc.) and a temperature-relative humidity probe (T and RH, PC72V; Michell Instruments Ltd., UK), and data were acquired at 1 s execution interval by a datalogger (CR-3000, Campbell Scientific Inc.). All sensors were mounted at 0.75 m a.g.l. height.

At the outlet of each strip (runoff catchment), a pit was dug (0.9 m × 0.7 m × 0.4 m) to install the tipping bucket rain gauges below grade. The tipping buckets were covered by triangular shaped wooden shields to prevent bias due to wind, dust, evaporative demand

and/or falling soil (Fig. 1). Their data were acquired at a 0.01 s execution interval by the datalogger. A trench was dug to drain the wastewater produced by these tipping buckets.

A total of 8 controlled irrigation tests were carried out in 2014 as part of this study, (Table 1). Among these, 2 tests were made under windy conditions, and the remaining tests were conducted during calmer winds with high (and sometimes extreme) temperatures (Table 1). An instantaneous flow rate (q) for each of the three strips was estimated by:

$$q = \frac{0.5 \times \alpha}{\Delta t} \quad (1)$$

where 0.5 is the bucket volumetric capacity (0.5 l); α is the calibration coefficient determined for each of the three tipping buckets; and Δt is time difference between two consecutive tips (min). 5-min average values of the WAE (WAE_{5min}) were then calculated by dividing the average flow rate from all 3 strips by the average sprinkler nozzle flow rate ($q_{av} = 13 \text{ l min}^{-1}$), and correcting by the ratio of strip width (β) to sprinkler head spacing (λ) as follows:

$$WAE_{5min} = \frac{\left(\sum_{j=2}^n q_{A,j} + \sum_{j=2}^m q_{B,j} + \sum_{j=2}^p q_{C,j} \right) \times \lambda}{q_{av}(n+m+p-3)\beta} \quad (2)$$

where, n , m and p are the total number of tips over 5-min for strips A, B and C, respectively; j is an index representing the tip number within each 5-min interval (*i.e.*, $1 \leq j \leq n$ for strip A, $1 \leq j \leq m$ for strip B and $1 \leq j \leq p$ for strip C); $q_{A,j}$, $q_{B,j}$ and $q_{C,j}$ are the flow rates for strips A, B and C, respectively, after the j th tip, which were evaluated using Eq. 1. For example, $q_{B,4}$ refers to the flow rate for strip B after the occurrence of the 4th tip. For each sigma, j starts from 2 since the first flow rate could not be calculated unless the second tip occurred. The value of 3 inserted in the denominator was due to the fact that for each strip and for each timing interval (*i.e.*, 5-min), the total number of calculated flow rates was always equal to the total number of tips for that strip minus 1.

To validate this study, catch cans were also concurrently installed and collected during these events. For this purpose, 108 plastic commercial cans (110 mm diameter, 130 mm height) were installed inside – and outside strips A and B. The spatial design consisted of 6 rows of 18 catch cans each with 1 m spacing. Two rows (out of the 6) were placed in the centreline of the strips. The duration of each test was at least 45-min (Table 1). After the sprinklers were shut off, the catch can collection was estimated in < 20-min. Water depth was calculated by dividing the volume collected by the surface area of the aperture of the catch can. Water evaporation from the cans during the experiment was taken into account empirically, by filling a single can with a known volume of water, placing it outside the influence of the irrigation, and measuring it before and after the test (Playan et al., 2005, Ortiz et al., 2009). To decrease the collector evaporation losses, the cans were pre-wetted before a test.

WAE from the catch can method was estimated by:

$$WAE_{can} = \frac{\lambda \times 1 \sum_{i=1}^{108} z_i}{L q_{av} t} \quad (3)$$

where λ is sprinkler head spacing (3 m); L is total distance between the first and the last row of cans (6 m); q_{av} is sprinkler discharge ($0.013 \text{ m}^3 \text{ min}^{-1}$); t is irrigation time (min) (Table 1); 1 m^2 is the surface area represented by each catch can; z_i is the catch can irrigation depth after taking evaporation into account (m) and; n-size = 108 total number of catch cans, *i.e.*, $i = 1, 2, \dots, 108$.

Estimates of WAE from the strip and catch can methods had different sampling intervals, *i.e.*, 5-min verses the total period of the test, respectively. Because the aim was to validate the strip results against the catch can method, a global WAE was derived (here called WAE_{Strip}) for the strip test by inserting n , m and p (for strips A, B and C respectively) in Eq. (2) as the total number of tips for each complete test.

3.1 Data Analysis (Statistics)

Mixed modelling methods with variance–covariance matrices explicitly formulated to appropriately account for the random effects of the experimental design, were used to evaluate drivers of WAE and the differences in WAE_{Strip} and WAE_{Can} (catch can method). Variance–covariance parameters were estimated via restricted maximum likelihood using the SAS procedure PROC MIXED (v.9.4, SAS Institute Inc. Cary, NC, USA). The model included fixed effects for the method (catch can and strip), average wind direction (θ), and average and maximum air temperature ($^{\circ}\text{C}$), relative humidity, and wind speed (m s^{-1}). Random effects were included for the test number (1 to 8) and test duration (min).

Mixed modeling methods were used to explore the effects of environmental conditions on the WAE_{5min} with fixed (temperature, wind speed and relative humidity) and random effects (test and time). Explanatory variables were explored strategically due to high correlation among parameters (Table 2) to prevent multi-collinearity. Parameter selection was based on the Wald chi-square statistics, and parameters were removed from the model if they were not influential ($P > 0.05$). Goodness-of-fit statistics, Akaike’s information criteria (AIC) and Bayesian information criteria (BIC), were used to compare models. AIC and BIC are model selection statistics appropriate for non-nested models, which measure how close fitted values are to true values, with a penalty for the number of parameters in the model (Littell *et al.*, 2006). At each step in model selection, the significance of each model parameter was evaluated to ensure that the final model had the lowest AIC and BIC values. To test for differences among levels of categorical variables, least square means were produced, which are the marginal predicted mean values for the model-dependent variable given all other variables in the model are at their average values. Differences among means were tested with the Tukey–Kramer multiple comparisons test. Assumptions of normality and homoscedasticity were evaluated visually by plotting residuals.

4.0 Results and Discussion:

4.1 Validation with catch can data

Good agreement was observed between the catch can (WAE_{Can}) and the strip (WAE_{Strip}) methods for all tests, with a maximum difference being only 2.3% (Fig. 3). Tests 1 and 2 showed the largest difference between methods, which occurred under high wind speeds (Figs. 3). The mixed effects model supports these observations showing that there was no significant difference between methods ($p = 0.4135$), and that the WAE_{Strip} and WAE_{Can} had both a significant negative relationship with average wind speed ($p = 0.0829$) (Table 3; Fig. 4). The interaction between methods and wind speed, suggests that as wind speeds increased, the WAE_{Can} was lower than WAE_{Strip} ($p = 0.0587$; Table 3; Figs. 4 and 5c). However, high correlation between explanatory factors (Table 2) restricted the inclusion of more than one explanatory factor in the final mixed effects model.

Wind speed was highly correlated with mean and maximum air temperature ($p < 0.001$; Table 2). High covariance between wind speed, air temperature, and relative humidity suggests that interacting effects may be important though difficult to quantify due to the sample size, and high spatial and temporal covariance. Linear relationships between the difference between methods, air temperature (Fig. 5a), relative humidity (Fig. 5b), and wind speed (Fig. 5c) were also observed and this suggested that WAE_{Strip} was enhanced by lower temperatures ($< 24^{\circ}\text{C}$) and appeared to be less sensitive to higher wind speeds ($> 1.69\text{ m s}^{-1}$; Fig. 5). The WAE_{Can} was higher when temperatures were $\sim 24^{\circ}\text{C}$ and at lower wind speeds ($< 1.69\text{ m s}^{-1}$; Fig. 5).

4.2 Sources of errors

It was assumed that random effects were the same for both approaches. It was also assumed that systematic sources were the same for both measurement systems, but the effects of these sources differed. For example, i) **collection efficiency**: there is a variance in the sprinkler's

249 ability to distribute water spatially, which was assumed to be better captured by the larger
 250 strips compared to the smaller surface area. Hendawi *et al.* (2005) reported that catch can
 251 collection efficiency is generally reduced under high wind conditions and becomes further
 252 reduced when droplet sizes are very small (*i.e.*, < 0.5 mm). In our study, however, most of
 253 the droplet sizes were between 1 to 2 mm (King, private communication) thus the catch can
 254 efficiency should be $> 95\%$ (Hendawi *et al.*, 2005). Here, the collection efficiency of both
 255 systems was assumed to be 100%, because the sources of error differ in part, *i.e.*, water
 256 collected by strips is continuous verses discrete collection by the catch cans. However, under
 257 high wind conditions, the WAE_{Can} was lower than WAE_{Strip} (Figs. 3 and 4). Thus, if the
 258 collection efficiency of cans is fully accounted for, our estimate of 2.3% error reported may
 259 be reduced, ii) ***evaporative losses and surface capacitance***: the amount of surface area and
 260 surface capacitance differ between the two methods. This exposes the strip method to
 261 potentially large evaporative losses. To account for this potential bias, wind speed and
 262 temperatures (*i.e.*, water temperature under the irrigation source which is close to the wet
 263 bulb temperature Sadeghi *et al.* (2013), and tarpaulin temperatures that change with incident
 264 solar radiation, air and water temperatures) should be measured directly. The WAE results
 265 were re-evaluated by neglecting the water evaporation from the cans during the experiments.
 266 It was concluded that there was a relative difference of only 0.1% in the final (total) WAE
 267 output by the catch can method. Therefore, this affect was discounted in the interpretation as
 268 other researchers have done (e.g. Playan *et al.*, 2005; Ortiz *et al.*, 2009; King *et al.*, 2012).
 269 Empirically assessing this source of bias was not within the scope of this study, and it was
 270 assumed to be lower in magnitude than the bias due to the (in)ability to assess the changing
 271 environmental conditions that control WAE, and *i.e.*, temporal averaging—which is within
 272 the scope of this study, and iii) ***Hysteresis effect***: It is acknowledged that evaporative losses
 273 change exponentially throughout the day due to changing environmental conditions, e.g.,

increases in air temperature (Campbell and Norman, 1998). Although the strips exposed more surface area than the cans, both were subject to the same diurnal hysteresis in evaporative demand. It can be assumed that the overall evaporative quantities are orders of magnitude smaller than the gross collection amounts that we wish to compare, and to discount this effect. In addition, the water captured water by the strips was in the form of droplets which quickly reached the main stream that was flowing towards the outlet. Therefore, the effect of hysteresis on the measured WAE was likely to be minimal.

4.3 Comparison with other methods

As an alternative method for measuring WAE over short timing intervals a network of tipping bucket rain gauges (TBRG) could be used. The TBRG method has several shortcomings, such as; i) the need to have numerous (and costly) collectors with the same collection area as the strip method, and to account for a spatial representative mean and variance (Loescher et al. 2002), ii) higher maintenance efforts/cost, iii) additional source of error in breakthrough volume and over spill in the tipping mechanism (a the common problem of the tipping mechanism is not operating sufficiently rapidly to cope with quantity of water delivered to the collector), and iv) the spatial averages would be compromised if one (or perhaps several) tipping buckets were damaged during the experiment. Interpolation would be a good solution to fill the gap in spatial coverage, but it would also introduce another source of uncertainty. This source of uncertainty would be further compounded if wind speed and direction changed during the test (rf. Dechmi *et al.*, 2003). The strip method on the other hand, does not embody any of these operational shortcomings or uncertainties.

4.4 Measuring WAE_{5min}

WAE_{5min} was variable and changed even over a 45-min test (e.g test 6 in Fig. 6). In tests with very high wind speeds, WAE_{5min} varied from 80 % to 92 % and from 77 % to 95 % (Fig. 6). The WAE_{Can} for the two tests returned average values of 87 % and 82 %, respectively.

Variations in WAE_{5min} persisted at lower values under low wind conditions (tests 3 to 8). This can be attributed to the abrupt changes of wind direction during the experiments, (see Fig. 4). All these observations confirm again that the catch can method failed to capture the dynamic variation of the WAE with time.

4.5 Drivers of the WAE.

In a similar manner to the effects of environment on WAE_{Can} and WAE_{Strip} , WAE_{5min} decreased with both temperature and wind speed and increased with relative humidity. However, only the correlations with temperature ($p = 0.002$) and wind speed ($p < 0.001$) were significant, not for relative humidity (Table 4). When considering the WAE_{Strip} and WAE_{can} , only wind speed showed a significant relationship (Table 2). This indicates that evaluating the WAE over short time intervals (e.g. 5 min) may be a better way to study its drivers even though the instantaneous effects of the weather variables on WAE_{5min} cannot be established due to the inherent time lag in the measurements.

Although the relationship between relative humidity and WAE was not significant, neither for WAE_{5min} nor for WAE_{Strip} , it is likely that this parameter is also important driver of WAE, as has been shown for WDELs using center pivots (Harrison 1993; McLean et al., 2000; Playán et al., 2005; Ortiz et al., 2009). This further suggests that all the drivers of evapotranspiration (ET) also control WAE, i.e., Penman Montieth, or Priestly & Taylor equations (Priestly & Taylor 1972, Steiner *et al.* 1983, Penman & Unsworth, 1990, Keller & Bliesner, 1990; Allen *et al.*, 1998). The question is, under what conditions do specific parameters exert the most control. For example, Clark and Finley (1975) found winds $> 4.5 \text{ m s}^{-1}$ controlled evaporative losses (i.e. aerodynamic conductance terms became important, Steiner *et al.* 1983), and at lower windspeeds, vapour pressure deficit exerted a greater control. A similar conclusion can be drawn from Playán *et al.* (2005) who found that wind speed best explained WAE when data from both day and night measurements were grouped

together, but not when night time data was used alone, suggesting that aerodynamic conductance with a lack of (night time) evaporative demand does not control ET. While biophysical models can provide insight on the abiotic drivers of WAE, irrigation is inherently applied to the agronomic system, thus imposing interactive effects of the abiotic drivers and the physical structure of the irrigation system. For example, Playán *et al.* (2005) suggested that sprinkler height above the surface roughness should be taken into account given the vertical wind profiles, and Steiner *et al.* (1983) found that orientation of the irrigation system to mean wind direction can also affect WAE. Not only are the designs of sprinklers becoming important, but also how they are situated in the agronomic system, i.e. height within the surface layer distance from roughness elements (Monteith & Unsworth 1990). Taken in concert, our study also suggests that the integration of biophysical approaches (e.g. Penman-Monteith controls on ET), hydrological approaches to the estimate of WAE, runoff, and capacitance (e.g. a Rutter-type model, Calder *et al.* 1986, Loescher *et al.* 2002, 2005) along with design attributes of the irrigation system and where it is located above the plant canopy, will advance our understanding of WAE and help better optimise irrigation efficiencies as a whole.

5.0 Conclusions

A strip method of water distribution measurement was proposed for the measurement of wind drift and evaporation losses under linear moving or center pivot sprinkler irrigation systems and this was validated against the standard catch can technique. Compared to the catch can method, this new approach has the advantage of measuring WDELs continuously and provides more information on how changing weather and environmental conditions affect WAE. Our results indicated that the instantaneous WAE (here measured every 5 min) is dynamic in time and space, and can make site- and system-specific characterisation more pertinent. In general, it was concluded that the difference between the maximum and the

minimum WAE_{5min} is high when wind speeds are high. The strip technique should assist in developing a predictive capacity (for the WAE) and meet the increasing need for enhancing the efficiency of delivering irrigation water. The technique could provide the context for future investigations to more accurately estimate the continuous variation of wind drift and evaporation losses over short time intervals, for long time periods, and when canopy is present or not.

6.0 Acknowledgements:

S-HS acknowledges the four societies that have provided support and have bestowed awards as part of this study: American Society of Civil Engineers Freeman Fellowship (2013), Soil Science Society of America graduate student award from the soil and water management and conservation section (2013), the American Society of Agronomy outstanding graduate student award from the environmental quality section (2013), and the American Water Resource Association graduate student award from the - Washington section (2013). HWL acknowledges the National Science Foundation (NSF) for ongoing support. The NEON is a project sponsored by the NSF and managed under cooperative support agreement (1029808) by NEON, Inc. Any opinions, findings, and conclusions or recommendations expressed in this material are those of the authors and do not necessarily reflect the views of our sponsoring agencies. This commentary would not have taken shape if it were not for meaningful engagement with community members.

References:

Abo-Ghobar, H. M. (1992). Losses from low-pressure center-pivot irrigation systems in a desert climate as affected by nozzle height. *Agricultural Water Management* 21(1), 23–32.

373 Allen, R. G., Pereira, L. S., Raes, D., & Smith, M. (1998). *FAO Irrigation and drainage*
374 *paper* No. 56. Rome: Food and Agriculture Organization of the United Nations, pp. 300.

375 ANSI/ASAE Standards S436, 1995. Test procedure for determining the uniformity of water
376 distribution of center-pivot, corner pivot, and moving lateral irrigation machines
377 equipped with spray or sprinkler nozzles. In: *ASAE Standards*. ASAE, St. Joseph, MI.

378 Bauder, T. A., Andales, A. A., & Waskom, R. M. (2008). *Nitrogen and Irrigation*
379 *Management*. Colorado State University Extension. pp 2.

380 Bavi, A., Kashkuli, H. A., Boroomand, S., Naseri, A., & Albaji, M. (2009). Evaporation
381 losses from sprinkler irrigation systems under various operating conditions. *Journal of*
382 *Applied Science*, 9(3), 597–600.

383 Bandyopadhyay, A., Bhadra, A., Raghuwanshi, N. S., & Singh, R. (2009). Temporal trends
384 in estimates of reference evapotranspiration over India. *Journal of Hydrologic*
385 *Engineering*. 14(5), 508–518.

386 Boserup, E. (2005). *The conditions of agricultural growth: The economics of agrarian*
387 *change under population pressure*. Transaction Publishers. pp 137.

388 Calder, I.R., Wright, I.R., & Murdiyaso, D., (1986). A study of evaporation from a tropical
389 rain forest-west Java. *Journal of Hydrology*, 89, 13–31.

390 Campbell, G. S., & Norman, J. M. (1998). *An introduction to environmental biophysics*.
391 Springer-Verlag New York, 286 pp..

392 Christiansen, J. E. (1942). *Irrigation by sprinkling*. University of California, Agricultural
393 Experiment Station B-670, Berkeley, CA. pp.110–116.

394 Clark, R. N., & Finley, W. W. (1975). Sprinkler evaporation losses in the Southern Plains.

395 Dechmi, F., Playán, E., Caverro, J., Faci, J. M., & Martínez-Cob, A. (2003). Wind effects on
396 solid set sprinkler irrigation depth and yield of maize (*Zea mays*). *Irrigation*
397 *Science*, 22(2), 67–77.

398 Dechmi, F., Playán, E., Cavero, J., Martí'nez-Cob, A., & Faci, J. M. (2004). Couple crop and
399 solid set sprinkler simulation model. I: model development. *Journal of Irrigation and*
400 *Drainage Engineering, ASCE*, 130(6), 499–510.

401 Delirhasannia, R., Sadraddini, A. A., Nazemi, A. H., Farsadizadeh, D., & Playán, E. (2010).
402 Dynamic model for water application using center pivot irrigation. *Biosystems*
403 *Engineering*, 105(4), 476–485.

404 Evans, R. G., & Sadler, E. J. (2008). Methods and technologies to improve efficiency of
405 water use. *Water Resources Research*, 44(7), doi: 10.1029/2007WR006200

406 Faci, J.M., Salvador, R., Playán, E., & Sourell, H. (2001). A comparison of fixed and rotating
407 spray plate sprinklers. *Journal of Irrigation and Drainage Engineering, ASCE*, 127
408 (4), 224–233.

409 Frost, K. R. & Schwalen, H. C. (1955). Sprinkler evaporation losses. *Agricultural*
410 *Engineering*, 36(8), 526–528.

411 Geary, B., Johnson, D. A., Hamm, P. B., H. C. & Cummings, T. F. (1999). Fungicide
412 application for late blight management: a boom attached to a center pivot irrigation
413 system. *Plant Disease*, 83(6), 512–515.

414 George, T. J. (1955). *Evaporation from irrigation sprinkler sprays as determined by an*
415 *electrical conductivity method*. Unpublished M.S. Thesis. University of California,
416 Davis, CA.

417 Ghadiri, H., Rose, C. W., & Hogarth, W. L. (2001). The influence of grass and porous barrier
418 strips on runoff hydrology and sediment transport. *Transactions of the ASAE*, 44(2),
419 259–268.

420 Gheysari, M., Loescher, H. W., Sadeghi, S. H., Mirlatifi, S. M., Zareian, M. J., &
421 Hoogenboom, G. (2015). Water-yield relations and water use Efficiency of maize

- under Nitrogen fertigation for semiarid environments: experiment and synthesis. *Advances in Agronomy*, 130, 175–229.
- Harrison, K. A. (1993). *Water application efficiency measurements for three sprinkler packages in Georgia*. San Diego, California, Irrigation Association Technical Conference Proceedings. United States of America. pp. 8.
- Hendawi, M., Molle, B., Folton, C., & Granier, J. (2005). Measurement accuracy analysis of sprinkler irrigation rainfall in relation to collector shape. *Journal of irrigation and drainage engineering*, 131(5), 477-483.
- Hoekstra, A. Y., & Chapagain, A. K. (2007). Water footprints of nations: water use by people as a function of their consumption pattern. *Water Resources Management*, 21(1), 35–48.
- ISO-11545. (1994). Agricultural irrigation equipment. Center pivot and moving lateral irrigation machines with sprayer or sprinkler nozzles. Determination of uniformity of water distribution.
- Keller, J., & Bliesner, R. D. (1990). *Sprinkler and trickle irrigation*. Van Nostrand Reinhold, New York. pp 652.
- Kincaid, D., Salomon, K., & Oliphant, J. (1996). Drop size distributions for irrigation sprinklers. *Transactions of the ASAE*, 39(3), 839–845.
- King, B. A., Dungan, R. S., & Bjorneberg, D. L. (2012). Evaluation of center pivot sprinkler wind drift and evaporation measurement technique. In *ASABE Annual International Meeting* (Vol. 2012 July, pp. 1–11), Dallas TX.
- Kohl, R. A. (1972). Sprinkler precipitation gage errors. *Transaction of the ASAE*, 15(2), 264–265.
- Kohl, K. D., Kohl, R. A., & DeBoer, D. W. (1987). Measurement of low pressure sprinkler loss. *Transactions of the ASAE*, 30(4), 1071–1074.

447 Kraus, J. H. (1966). Application efficiency of sprinkler irrigation and its effects on
 448 microclimate. *Transactions of the ASAE*, 9(5), 642–645.

449 Li L. J., Zhang, L., Wang, H., Wang, J., Yang, J. W., Jiang, D. J., Li, J. Y., & Qin, D. Y.
 450 (2007). Assessing the impact of climate variability and human activities on
 451 Streamflow from the Wuding River basin in China. *Hydrological Processes*, 21(5),
 452 3485–3491.

453 Littell, R. C., Milliken, G. A., Stroup, W. W., Wolfinger, R. D., & Schabenberger, O., (2006).
 454 *SAS for mixed models*, 2nd Edition. SAS Institute Inc., Cary NC, 813 pp.

455 Livingston, P., Loftis, J. C., & Duke, H. R. (1985). A wind tunnel study of sprinkler catch-
 456 can performance. *Transactions of the ASAE*, 28(6), 1961–1965.

457 Loescher, H. W., Ayres, E., Duffy, P., Luo, H., & Brunke, M., (2014). Spatial variation in
 458 soil properties among North American ecosystems and guidelines for sampling
 459 designs. *Plos One*, 9(1), e83216.

460 Loescher, H.W., Gholz, H. L., Jacobs, J. M., & Oberbauer, S. F. (2005). Energy dynamics
 461 and modeled evapotranspiration from a wet tropical forest in Costa Rica. *Journal of*
 462 *Hydrology*, 315, 274–294.

463 Loescher, H.W., Powers, J. S., & S.F. Oberbauer, S. F., (2002). Spatial variation of
 464 throughfall volume in an old growth tropical rain forest. *Journal of Tropical Ecology*,
 465 18, 397–407.

466 Marek, T. H., Schneider, A. D., Baker, S. M., & Popham, T. W. (1985). Accuracy of three
 467 sprinkler collectors. *Transactions of the ASAE*, 28(4), 1191–1195.

468 McLean, R. K., Ranjan, S., & Klassen, G. (2000). Spray evaporation losses from sprinkler
 469 irrigation systems. *Canadian Agricultural Engineering*, 42(1), 1–8.

470 McVicar, T. R., Niel, T. G. V., Li, L.T., Hutchinson, M. F., Mu, X. M., & Liu, Z. H. (2007)
 471 Spatially distributing monthly reference evapotranspiration and pan evaporation
 472 considering topographic influences. *Journal of Hydrology*, 338 (3-4), 196–220.

473 Montazar, A., & Behbahani, S. M. (2007). Development of an optimized irrigation system
 474 selection model using analytical hierarchy process. *Biosystems engineering*, 98(2),
 475 155–165.

476 Monteith, J. L., & Unsworth, M. H. (1990). *Principles of Environmental Physics*. Edward
 477 Arnold, London. pp. 291.

478 Musick, J. T., Pringle, F. B., & Walker, J. D. (1988). Sprinkler and furrow irrigation trends-
 479 Texas High Plains. *Applied engineering in agriculture*, 4(1), 46–52.

480 Neibling, H., Shewmaker, G. & Falen, G. (2009). Center Pivot Management for Forage
 481 Production. In: Proceedings, 2009 Western Alfalfa and Forage Conference, December
 482 2-4, 2009, Reno, Nevada. UCCE, University of California, Davis 95616.

483 Nakawuka, P., Okwany, R. O., Peters, T. R., Desta, K., & Sadeghi, S. H. (2014). Efficacy of
 484 boom systems in controlling runoff under center pivots and linear move irrigation
 485 systems. *Applied Engineering in Agriculture*, ASAE, 30(5), 797–801.

486 Ocampo, L. R., Thomas, D. L., Hook, J.E., & Harrison, K. A. (2003). Comparative loss
 487 study of four different sprinkler packages on center pivot systems under South
 488 Georgia conditions. *ASBE Paper No. 032013*, St. Joseph, MI.

489 Ortiz, J. N., Tarjuelo, J. M., & De Juan, J. A. (2009). Characterization of evaporation and
 490 drift losses with center pivots. *Agricultural Water Management*, 96(11), 1541–1546.

491 Ortiz, J. N., De Juan, J. A., & Tarjuelo, J. M. (2010). Analysis of water application
 492 uniformity from a center pivot irrigator and its effect on sugar beet (<i>Beta
 493 vulgaris</i> L.) yield. *Biosystems engineering*, 105(3), 367–379.

494 Peters, R. T., & Evett, S. R. (2007). Spatial and temporal analysis of crop conditions using
 495 multiple canopy temperature maps created with center-pivot-mounted infrared
 496 thermometers. *Transactions of the ASAE*, 50(3), 919–927.

497 Playán, E., Salvador, R., Faci, J. M., Zapata, N., Martínez-Cob, A., & Sánchez, I. (2005). Day
 498 and night wind drift and evaporation losses in sprinkler solid-sets and moving laterals.
 499 *Agricultural Water Management*, 76(3), 139–159.

500 Priestly, C.H.B., & Taylor, R.J., (1972). On the assessment of the surface heat flux and
 501 evaporation using large scale parameters. *Monthly Weather Review*, 100, 81–92.

502 Robinson, F. E. (1973). Increase in conductivity of irrigation water during irrigation.
 503 *Agronomy Journal*, 65(1), 130.

504 Rockström, J., Falkenmark, M., Karlberg, L., Hoff, H., Rost, S., & Gerten, D. (2009). Future
 505 water availability for global food production: the potential of green water for
 506 increasing resilience to global change. *Water Resources Research*, 45(7).

507 Sadeghi, S. H., & Peters, T. (2012). Analytical determination of distribution uniformity for
 508 microirrigation tapered laterals laid on uphill and horizontal slopes. *Journal of*
 509 *Irrigation and Drainage Engineering, ASCE*, 139(6), 483–489.

510 Sadeghi, S. H., & Peters, T. (2013). Adjusted friction correction factors for center-pivots with
 511 an end-gun. *Irrigation Science*, 31(3), 351–358.

512 Sadeghi, S. H., Peters, T. R., Cobos, D. R., Loescher, H. W., & Campbell, C. S. (2013).
 513 Direct Calculation of Thermodynamic Wet-Bulb Temperature as a Function of
 514 Pressure and Elevation. *Journal of Atmospheric and Oceanic Technology*, 30(8),
 515 1757–1765.

516 Santos, F. L., Reis, J. L., Martins, O. C., Castanheira, N. L., & Serralheiro, R. P. (2003).
 517 Comparative assessment of infiltration, runoff and erosion of sprinkler irrigated
 518 soils. *Biosystems Engineering*, 86(3), 355–364.

519 Sayinci, B., & Bastaban, S. (2011). Spray distribution uniformity of different types of nozzles
520 and its spray deposition in potato plant. *African Journal of Agricultural*
521 *Research*, 6(2), 352–362.

522 Schneider, A. D. (2000). Efficiency and uniformity of the LEPA and spray sprinkler
523 methods: A review. *Transactions of the ASAE*, 43(4), 937–944.

524 Seginer, I., Kantz, D., & Nir, D. (1991). The distortion by wind of the distribution patterns of
525 single sprinklers. *Agricultural Water Management*, 19(4), 341–359.

526 Sharpley, A. N. (1995). Dependence of runoff phosphorus on extractable soil
527 phosphorus. *Journal of Environmental Quality*, 24(5), 920–926.

528 Silva, L. L. (2006). The effect of spray head sprinklers with different deflector plates on
529 irrigation uniformity, runoff and sediment yield in a Mediterranean soil. *Agricultural*
530 *Water Management* 85(3), 243–252.

531 Spears, T. D. (2003). Irrigating efficiently to feed the world in 2050. In *Proceedings of the*
532 *2003 irrigation association international exposition and technical conference, The*
533 *Irrigation Association, Falls Church, VA* (pp. 411–422).

534 Steiner, J. L., Kanemasu, E. T., & Clark, R. N. (1983). Spray Losses and partitioning of water
535 under a center pivot sprinkler systems. *Transactions of the ASAE*, 26 (4), 1128–1134.

536 Sternburg, Y. A. (1967). Analysis of sprinkler irrigation losses. *Journal of Irrigation and*
537 *Drainage Engineering, ASCE*, 93(4), 11–124.

538 Tarjuelo, J. M., Montero, J., Carrion, P. A., Honrubia, F. T., & Calvo, M. A. (1999).
539 Irrigation uniformity with medium size sprinklers. Part II: Influence of wind and other
540 factors on water distribution. *Transactions of the ASAE*, 42(3), 677–689.

541 Uddin, J., Smith, R., Hancock, N., & Foley, J. P. (2010). Droplet evaporation losses during
542 sprinkler irrigation: an overview. In *Australian Irrigation Conference and Exhibition*
543 *2010: Proceedings* (pp. 1–10). Irrigation Australia Ltd.

544 Yazar, A. (1984). Evaporation and drift losses from sprinkler irrigation systems under
545 various operating conditions. *Agricultural Water Management*, 8, 439–449.
546

547 **Figure Captions**

548 **Fig. 1.** Conceptual representation of a strip and its tipping bucket.

549 **Fig. 2.** Experimental design of the field sampling.

550 **Fig. 3.** WAE_{Strip} , WAE_{Can} and average wind speed.

551 **Fig. 4.** Linear relationships between wind speed ($m\ s^{-1}$) and WAE_{Strip} and WAE_{Can} ($P < 0.001$).

552 **Fig. 5.** Linear relationship between the residuals from $WAE_{Strip} - WAE_{Can}$ and (a) air
553 temperature, (b) relative humidity, and (c) wind speed.

554 **Fig. 6.** Time series of (a) wind speed, (b) air temperature, (c) relative humidity, and (d) the
555 WAE_{5min} for each test.

556

Tables

Table 1. Time, duration of each test, and weather conditions.

Test	Date	Test Duration (min)	Average Temperature (°C)	Average RH (%)	Average Wind Speed (m/s)	Maximum Wind Speed (m/s)
1	8 May	90	15.5	71.9	3.9	5.7
2	9 May	90	16.2	43.8	4.8	5.9
3	25 Aug.	60	23.8	54.8	1.1	1.7
4	25 Aug.	90	27.4	42.9	0.9	1.5
5	26 Aug.	90	19.9	63.5	0.6	1.2
6	26 Aug.	45	25.6	44.7	0.9	1.2
7	26 Aug.	90	32.6	24.7	0.9	1.7
8	28 Aug.	90	25.2	46.6	1.5	1.9

Table 2. Pearson's correlation coefficients for explanatory variables and WAE_{Strip} and WAE_{Can}.

<i>r</i> <i>p-value</i>	Wind Direction	Air Temperature (Average)	Air Temperature (Max)	Relative Humidity (Average)	Relative Humidity (Max)	Wind Speed (Average)	Wind Speed (Max)
Wind Direction							
Air Temperature (Average)	-0.7178 0.0017						
Air Temperature (Max)	-0.6945 0.0028	0.9936 <.0001					
Relative Humidity (Average)	0.6989 0.0026	-0.7797 0.0004	-0.7217 <.0001				
Relative Humidity (Max)	0.7054 0.0023	-0.7996 <.0001	-0.7338 <.0001	0.9850 <.0001			
Wind Speed (Average)	0.3611 0.1695	-0.7473 0.0009	-0.7665 <.0001	0.2609 0.3291	0.3562 0.1757		
Wind Speed (Max)	0.3500 0.1839	-0.7517 <.0001	-0.7573 0.0007	0.3232 0.2220	0.4274 0.0987	0.9886 <.0001	
WAE _{Strip/Can}	0.1232 0.6494	0.3147 0.2352	0.3569 0.1748	0.2323 0.3865	0.1382 0.6098	-0.7778 <.0001	-0.7680 <.0001

Table 3. Mixed modeling effects for WAE_{Strip} and WAE_{Can}.

Effect		Estimate	Standard Error	Pr > t
Intercept		0.9317	0.04176	<.0001
Method				
WAE _{Can} vs. WAE _{Strip}		0.004248	0.004843	0.4135
Average Wind speed		-0.01373	0.006702	0.0829
Wind speed * Method				
Wind Speed	WAE _{Can} vs. WAE _{Strip}	-0.00592	0.003248	0.0587

Table 4. Mixed modeling effects for WAE_{5min}

Effect	Estimate	Standard Error	DF	t Value	Pr > t
Intercept	1.0518	0.02733	9.17	38.48	<.0001
Temperature	-0.00462	0.00097	7.87	-4.77	0.0015
Wind Speed	-0.0264	0.00331	13.3	-7.97	<.0001

Figure 3. WAE_{Strip} , WAE_{can} and average wind speed.

Figure 4. Linear relationships between wind speed (m s⁻¹) and WAE_{Strip} and WAE_{Can} ($P < 0.001$).

Figure 5. The linear relationship between the residuals from $WAE_{Strip} - WAE_{can}$ and (a) air temperature, (b) relative humidity, and (c) wind speed.

Fig 6. Time series of (a) wind speed, (b) air temperature, (c) relative humidity, and (d) the $\text{WAE}_{5\text{min}}$ for each test.