Quantitative interpretation of CO₂ plume from Sleipner (North Sea), using post-stack inversion and rock physics modeling

Ranjana Ghosh^{a*}, Mrinal K. Sen^{a, b}, and Nimisha Vedanti^a

^aCSIR-National Geophysical Research Institute, Hyderabad, India

^bUniversity of Texas at Austin, Austin, Texas, USA

*Corresponding authors: ranjana159@gmail.com

ABSTRACT

Sleipner gas field in the North Sea is the world's first industrial scale CO₂ injection project designed specifically to reduce the emission of greenhouse gas. Here CO₂ separated from natural gas produced at Sleipner gas field is injected into the Utsira sand, which is a major saline aquifer in the North Sea basin. From time-lapse (4D) seismic data, CO₂ plume is observed as a number of bright sub-horizontal reflections within the reservoir. Correlation of log data with the seismic data indicates that CO₂ accumulates within a series of interbedded sandstones and mudstones beneath a thick cap rock of mudstone. Nine reflective horizons have been mapped within the reservoir on the six seismic surveys from 1999 to 2008. Comparison with the baseline seismic survey of 1994 (pre-injection) provides clear impression of the migration of CO₂ plume. In this paper, we attempt to model CO₂ distribution quantitatively within the reservoir by applying a pressure-dependent differential effective medium (PDEM) theory using 4D seismic data. Pre- and post-injection acoustic impedances are calculated by inverting post-stack seismic data of 1994 and 2001 using a model-based inversion technique. A 3D CO₂ saturation volume is estimated using PDEM theory from inverted acoustic impedance of the year 2001 taking the reference of that from the results of pre-injection data of the year 1994. Since the gas distribution type is seldom known, we estimate the saturation distribution using both a homogeneous and a patchy distribution pattern in our rock physics model. We estimate saturation for homogeneous

distribution of CO₂ to be 0-20% and for CO₂ as patches of gas as 0-80% of the total porosity within ~200 m thick reservoir unit. 5-7% uncertainty in the predicted CO₂ saturation is estimated using a Monte-Carlo simulation technique. Our results indicate that a large amount of CO₂ is accumulated as patches of gas within sand layers capped by mud layers, though some amount of gas may have mixed uniformly with water.

Keywords: Post-stack inversion, CO₂ sequestration, PDEM theory, Uncertainty, time lapse seismic, 4D

1. Introduction

The Sleipner field in the North Sea (Fig. 1) is considered to be the longest running carbon capture and storage (CCS) site (Arts et al., 2004, 2008; Chadwick and Noy, 2010). The CO₂ removed from the natural gas field of Sleipner is injected near the base of the Utsira sand, a porous saline reservoir occupying about 26000 km² area (Chadwick et al., 2005). The Utsira sand deposited during Pliocene times in the eastern part of the North Sea basin is 200-300 m thick (Chadwick et al., 2004). The sediment buried at a depth of about 800-1100 meter below sea level (mbsl) consists of fairly uniform unconsolidated sand with porosity 35-40% and permeability 1-3 Darcy (Arts et al., 2004; Chadwick et al., 2005, 2006). The structure of the reservoir (Chadwick et al., 2004; Zweigel et al., 2000; Boait et al., 2012) is delineated using the baseline survey data of 1994 (Fig. 2a), which shows that the Utsira sand is underlain by Nordland shale and overlain by Hordland shale forming an ideal reservoir of CCS. Injected CO₂ as super critical fluid is accumulated in the sandstone layers of the reservoir, which is composed of interbedded stack of sandstone, and mudstone layers having thicknesses between 10-40 m and 1-6 m respectively (Isaken and Tonstad, 1989; Zweigel et al., 2000). These laterally discontinuous mudstone layers within the sediment column act as semi-permeable barriers and the thick overlying Nordland shale acts as the main caprock to fluid flow.

Injection was started in 1996 with a plan to continue for the next twenty years at a rate of approximately 1 million tons (Mt) per year. The CO₂ was injected into the lower half of the reservoir at ~1012 mbsl via a 2 km long deviated well (Baklid et al., 1996), which eventually migrated upward until it reached flow barriers such as thin discontinuous mud layers and the top thick shale at a depth of ~800 mbsl. The CO₂ as a supercritical fluid accumulated as a few meters thick layers following the structural relief beneath each intra-reservoir shale layer (Arts et al., 2008). These CO₂ layers are observed as bright sub horizontal reflections in the seismic section as the compressibility of CO₂ is much higher than that of brine; constructive tuning effects take place between upper and lower parts of the reflectors. A multi-institutional research project SACS (Saline Aquifer CO₂ Storage) and its successor CO2STORE were run in parallel (Arts et al., 2003; Chadwick et al., 2005) with the ongoing injection project to monitor and model the injected CO₂ in order to ensure that sequestration is safe and environmentally acceptable in long term.

The time-lapse seismic surveys aim to monitor the migration and distribution of the CO₂ plume, warn leakage problem if any and can be used as a quantification and verification tool. The reservoir at Sleipner has been imaged by seven time-lapse marine seismic surveys including one pre-injection (1994) and six post-injection (1999-2008) surveys. These seven time-lapse seismic surveys demonstrate that CO₂ spread up to the top of the Utsira sand through nine horizons. The probable driving mechanism for which CO₂ rises buoyantly until it reaches a shale layer is gravity (Lindeberg et al., 2001; Meer et al., 2001; Lyle et al., 2005).

CO₂ storage at the Utsira sand provides an excellent example of the application of surface seismic methods to CO₂ plume monitoring under favorable circumstances. Several authors (Arts et al., 2004; Clochard et al., 2009; Chadwick et al., 2010; Delépine et al., 2010; Rubino and Velis, 2011; Fornel and Estublier, 2012; Labat et al., 2012) have interpreted pre-stack or post-stack seismic volumes of Sleipner field in terms of CO₂ saturation. The analysis and applications of the proposed methods to the real data from Sleipner field are still being carried out to address the non-uniqueness of the modeling technique as well as uncertainties associated with the modeling parameters.

On time-lapse seismic data, a growing CO₂ plume is imaged as a series of bright reflections, generated due to acoustic impedance contrast at the boundaries between CO₂-saturated sandstone and water saturated mudstone layers. However, qualitative interpretation from seismic data may not be sufficient to understand the subsurface mechanism. Rock physics modeling helps to establish a link between geology (reservoir properties like porosity, permeability, saturation *etc*) and seismic data (attributes like velocity, amplitude, reflectivity *etc*). A suitable rock physics model may reduce interpretation risk significantly. However, many rock physics models exist each with its own advantages and shortcomings. It is important that the rock physics model to be used in interpretation is consistent with the local geology and local conditions. The Gassmann's poro-elastic theory (Gassmann, 1951) is the most widely used rock physics model in academic and industrial research because of its simplicity. The theory is valid at low frequency if the rock is isotropic and minerals forming the rock have homogeneous elastic properties. The geometry of different constituents of rock is not considered in this theory either. Presence of high fraction of clay and pores of more than one type of geometry can be the reason of intrinsic anisotropy and local pressure gradient (at the scale of microstructure). Global pressure gradient (at the scale of seismic wavelength) may also exist due to the presence of large heterogeneity (comparable to seismic wavelength) in the sediment. In such cases, the basic assumptions of Gassmann's theory are violated. Intrinsic fluid flow due to local or global pressure gradient causes the effective medium to be visco-elastic and dispersive. If ultrasonic (>1 MHz) measurements combined with a rock physics model are to be used to interpret low frequency (<1 KHz) seismic data, then Gassmann's theory is not applicable as the theory is valid only for low frequency. Several visco-elastic models (White, 1975; White et al., 1975; Mukerji and Mavko, 1994; Dvorkin et al., 1995; Chapman et al., 2003; Pride et al., 2004; Carcione and Picotti, 2006; Jakobsen and Chapman, 2009; Ghosh and Sen, 2012) exist in literature, which explain the cause of seismic attenuation in reservoir rocks at seismic frequencies due to wave-induced fluid flow owing to heterogeneities at the scale comparable or larger to pore scale but much smaller than the seismic wave length. Seismic attenuation becomes prominent if the

reservoir rock is partially saturated with gas and water because of strong contrast in the seismic properties of the pore fluids.

In this paper, we assume a dual porosity model and make quantitative estimate of CO₂ saturation in Sleipner reservoir using the rock physics model based on pressure-dependent differential effective medium theory (PDEM) described in Ghosh and Sen (2012). Previously, Ghosh and Sen (2012) have shown the effects of both pore scale and mesoscale (intermediate scale between pore scale and seismic scale) heterogeneity on fluid flow. As the presence of cracks or fractures in the unconsolidated Utsira sediment is not observed in the conventional seismic data, we assume the sediment to be isotropic. The PDEM has been used to relate acoustic impedance (AI, velocity multiplied by density), a secondary seismic parameter, with the CO₂ and water saturation of the reservoir at *in situ* pressure and temperature conditions. We used a model-based inversion technique to obtain 3D AI volume from the post-stack 3D seismic data. First, we calibrate our rock physics model with the observed AI calculated from pre-injection sonic log. Next, 3D CO₂-saturation volume is predicted using PDEM by comparing AI of CO₂ saturated sediment obtained by inverting 3D post-injection seismic data (of the year 2001) with the background (water-saturated sediment) AI.

2. Data

Seismic data: one pre-injection and one post-injection post stack 3D seismic volume collected in the year 1994 and 2001 respectively are used in our study (Fig. 2).

Well log data: in this area, data from two wells, one deviated injection well and one vertical production well, are available. Delépine et al. (2010) reported caving effects due to unconsolidated sandstone in case of well data of the vertical well, and therefore, we replaced unrealistic density and sonic data with those available from the horizontal well. The clay volume and porosity as a function of depth are calculated from the gamma ray and the density logs respectively.

3. Modeling

The PDEM theory is based on Eshelby's volumetric average (Eshelby, 1957) approach of elastic properties of a composite material, which is composed of a preferred matrix or host material and inclusions of other components (into the host material). The conventional DEM theory has been extended to formulate PDEM theory (Appendix A) to include the effect of fluid pressure and overburden stress on the predicted elastic properties of porous and permeable media (Ghosh and Sen, 2012). The PDEM theory is capable of explaining velocity dispersion through squirt flow mechanism. When seismic waves propagate through a heterogeneous (pores of different shape and size) porous and permeable media, local pressure gradient is created between different kinds of pores and the fluid flows in the direction of local pressure gradient, known as squirt flow. Stress and strain tensors associated with the propagation of wave is described in Appendix B. Fluid pressure in different kinds of pores when wave propagates through a medium is given in Appendix C. Different parameters needed to evaluate CO₂ saturation using PDEM are described in the following sub-sections.

3.1. Porosity

The Utsira sand has medium to high porosity and is a good permeable zone (average porosity 35-40% and average permeability 1-3 Darcy). Presence of cracks or fractures in this unconsolidated sediment cannot be guaranteed by conventional seismic survey. We have simulated this well-connected porous and permeable reservoir by a dual porosity model. The reservoir is assumed to be composed of spherical pores, which are connected with randomly oriented ellipsoidal pores, forming a well-connected porous network. The ellipsoidal pores assumed here do not resemble thin cracks (very low aspect ratio). Note that opening and closing of thin cracks (very soft pores), that is, density of thin cracks as well as crack porosity depend on the effective stress (Murphy, 1985; Crampin, 1994; Peacock et al., 1994), whereas, ellipsoidal porosity (less soft pore), like spherical porosity (stiff pores), is independent on allowable change in effective stress.

3.2. Mineralogy

We assume that quartz and clay are the dominant minerals in this sediment and presence of other minerals is negligible. The geometry of quartz and clay is assumed to be spherical and plate like (ellipsoidal). Gamma ray log is available in this region, which has been used to calculate concentration of clay with depth using the following relation

$$v_c = (gr - gr_{min}) / (gr_{max} - gr_{min}) \quad (1)$$

where, gr , gr_{max} , gr_{min} are respectively value of gamma log at a depth, maximum and minimum values of gamma log through out the depth section.

Concentration of quartz is calculated from the following relations

$$v_{clay} = (1 - \phi_t) * v_c \quad (2a)$$

$$v_{quartz} = 1 - \phi_t - v_{clay} \quad (2b)$$

where, ϕ_t , v_{quartz} , v_{clay} are respectively the total porosity (computed from density log), quartz and clay content in terms of fraction of sediment.

3.3. Inclusion of minerals and pores

The Utsira sand is composed of a stack of thick sand (mainly quartz) and thin mud (mainly clay) layers. For simplicity we assume these mud and sand layers are flat as bedding geometry cannot be interpreted fully from the seismic data. Since, the reservoir is mainly composed of quartz, we assume quartz (aspect ratio 1) to be the host mineral and clay minerals (aspect ratio 0.05) as inclusions. The combined self-consistent approximation and differential effective medium (SCA-DEM, Jakobsen et al., 2000; Ghosh et al., 2010) theory are used to calculate effective elastic moduli of the minerals. Since the sediment is isotropic, we assume clay minerals are randomly oriented and the average elastic properties of randomly oriented clay platelets are computed by combining SCA-DEM with Voigt's average technique (Sayers, 1994). Effective elastic properties of two-phase minerals can also be calculated using Mori-Tanaka approximation (Mori and Tanaka, 1973), but the theory should be used with caution in multiphase applications (Norris, 1989).

We assume a dual porosity model that causes local pressure gradient. The medium now behaves like a visco-elastic medium (Chapman et al., 2002; Chapman, 2003) and its elastic properties are frequency dependent. We use PDEM (Ghosh and Sen, 2012) to calculate effective elastic properties of the sediment containing spherical and ellipsoidal pores. First, the spherical pores are included into the quartz-clay background and ellipsoidal pores are included into the medium containing quartz, clay and spherical pores. Voigt's average technique is combined with PDEM to compute average elastic properties of randomly oriented ellipsoidal pores.

3.4. Background (pre-injection) impedance

Fig. 3 shows a schematic diagram of the microstructure of a sandstone reservoir, which is heterogeneous in terms of elastic property and geometry of each constituent. We predict the effective elastic properties of such a medium using PDEM theory. The rock physics model is calibrated with the observed background (before injection of CO₂) sonic impedance (sonic velocity multiplied with density). The porosity, permeability, mineralogy and density are known from the well log data. Given these, the concentration of ellipsoidal pores that connect the spherical pores and their aspect ratios are only two unknown parameters. Based on some initial guess of the concentration of the ellipsoidal pores and their aspect ratios, we divide the total porosity with depth into two parts, namely, spherical and ellipsoidal porosity. We apply directed Monte Carlo method (Sen and Stoffa 1996; Sen and Stoffa, 2013) to find the best fit between the observed background sonic impedance and the estimated background (water-saturated sediment) impedance (Fig.4). Very fast simulated annealing (VFSA, Sen and Stoffa, 2013) has been used for global optimization and the PDEM theory has been used for forward modeling (Fig. 5). Note that according to our assumption, local pressure gradient exists in the medium as the pressure in the spherical pores and the ellipsoidal pores are different (Appendix C) and velocity dispersion occurs as a result of squirt flow. Based on the published literature (Sothcott et al., 2000; Chapman, 2001, 2003), we use squirt flow relaxation time for water saturated sandstone to be $\tau_m = 2 \times 10^{-5}$ s.

After calibrating our model with well log data at sonic frequencies we predict CO₂ saturation from seismic data using the same model at seismic frequency.

3.5. Estimation of CO₂ saturation

Six post-injection time-lapse (1999-2008) seismic data were acquired to investigate the upward and lateral movement of CO₂ plume within the reservoir. Initially we received post injection seismic data of the year 2001 only, which we used to quantify CO₂ saturation. This work describes a method for quantitative interpretation of CO₂ movement. With the availability of other time-lapse seismic data, movement of CO₂ plume can be described with time. Model based inversion technique is used here to invert both pre- and post-injection 3D seismic data to obtain seismic impedance volumes. Velocity and density measured from the well log were used to build an initial model. The amplitude spectrum of the wavelet used for the inversion has been calculated using the autocorrelation of the seismic trace at a constant phase determined from the log data.

Here, a uniform (gas is mixed with water uniformly) and patchy (gas and water remain separately as patches) distribution has been superimposed on the squirt flow model (Appendix D). We expect the proposed method is consistent with the existing uniform model (Gassmann-Wood bound in the low frequency limit) provided elastic moduli of each constituent (required in the effective medium theory) and dry moduli of the rock frame (required in the Gassmann's theory) are consistent. To estimate CO₂ saturation, CO₂ gas is included from 0 to 100% in the water-saturated sediment by replacing water. We have used the mean values of concentration of ellipsoidal pores and their aspect ratios calculated for the background sediment. Predicted impedance at each depth point for 0 to 100% CO₂ saturation is compared with the observed impedance volume (obtained by inverting seismic data) to estimate the saturation volume.

3.6. Uncertainty estimation

Uncertainty estimation of any kind of prediction is important to guess the degree of reliability of the prediction. Here, uncertainty in predicted CO₂ saturation is estimated by a

Monte-Carlo simulation technique, following similar steps described in section 3.4 and Fig. 5. Mean model parameters (total porosity, clay volume, quartz volume, density, ellipsoidal porosity and aspect ratio of ellipsoidal pore) with depth obtained from the Monte-Carlo simulation method for the background sediment, and CO₂ saturation with depth calculated at the well location (separately for uniform and patchy distribution) are the required model parameters for uncertainty estimation. A search window with depth is generated taking $\pm 10\%$ of the initial values of these model parameters. Our results produce similar final models within one standard error when we increase the limits of the search window of the model parameters. Also, significant variation in the model parameters is not realistic and consumes more computation time. Uncertainty is calculated taking percentage of standard deviation of the mean model parameters obtained from the inversion.

4. Results

Mean model parameters determined by the Monte-Carlo simulation technique (described in section 3.4) are shown in Fig. 6. Presence of CO₂ as a critical fluid in the reservoir reduces seismic impedance, as both velocity and density of CO₂ are less than those of water. A number of bright reflectors are observed in the time-lapse seismic data, which mark high impedance contrast between water saturated and CO₂ gas saturated layers (Fig. 2b). Impedance volume obtained by inverting post-injection 3D-seismic volume has been used to estimate CO₂ saturation with depth in the reservoir. Fig. 7 shows the initial model, original log, wavelet used for inversion, inverted result and synthetic seismogram at the well location. Derived synthetic volume and error volume (difference between real seismic and synthetic data) are shown in Fig. 8. All the reflectors observed in the real seismic data (Fig. 2b) are reproduced in the synthetic seismogram (Fig. 8a), and error volume (Fig. 8b) shows very low amplitude. Fig. 9 displays seismic impedance corresponding to the anomaly (bright reflectors) observed in the seismic section of 2001 (Fig. 2b), mimicking the CO₂ plume moving upwards.

Using the result of seismic inversion (e.g., Sen 2006), we estimated CO₂ saturation for both patchy and uniform type of distributions. We present our results in depth domain instead of time domain (following 3D conversion law). Elastic properties of different constituents of the sediment are given in Table 1. Fig. 10 shows CO₂ saturation within the reservoir from 875 to 1041 meter depth (equivalent to 880 to 1080 ms time) corresponding to the impedance anomaly shown in Fig. 9. Horizontal distributions of CO₂ at different depth points for both types of distribution are shown in Fig. 11.

Type of distribution of gas is not easy to know and this is the largest ambiguity in prediction of saturation of gas. We found calculated impedance of sediment with CO₂ saturation of 0-20% for uniform and 0-80% for patchy types of distribution match well with the observed impedance of CO₂-sequestered sediment. We attempt to overcome this ambiguity by comparing the injected CO₂ mass with the estimated CO₂ mass from both type of distributions. Fig. 11 shows horizontal slice of CO₂ gas plume is approximately elliptical and Fig. 10 depicts seven such ellipsoidal zones of average thickness (2a) of approximately 20 m. As each inline and cross-line is separated by 6.25 m, the volume of each ellipsoidal zone ($\frac{4}{3}\pi abc$) is calculated as $2.36 \times 10^6 \text{ m}^3$ by taking average major (2b) and minor (2c) axes as 600 and 375 m respectively. Taking average porosity of the reservoir as 38% and density of CO₂ as 693 kg/m³, total mass of CO₂ within these seven ellipsoidal zones is calculated as 3.48 million tons for patchy (average 80% saturation) and 0.87 million tons for uniform (average saturation 20%) distributions. Since, *in situ* mass of injected CO₂ in the year 2001 is 4.26 million tones and no leakage from the reservoir has been detected (Chadwick et al., 2005; Arts et al., 2008), we can predict from our results that CO₂ is mainly distributed as patches of gas within ellipsoidal zones and some amount of gas may have distributed homogeneously in both sides of the gas plume (Figs 10,11). We have calculated uncertainty of saturation for each kind of distribution. Uncertainty in predicted saturation is within 5% at most of the observation points; at other places it is less than 7% (Fig. 12).

5. Discussion and Conclusions

In section 3.1, we have explained the reason for adapting a new dual porosity model to describe a homogeneous and isotropic reservoir. Generally, stiff pores (spherical primary pores) and soft pores (cracks/fractures) are two types of pores considered in most published work. The density of cracks/fractures depends on the effective pressure. Cracks/fractures tend to close with increasing effective pressure – these are termed soft pores. However, spherical primary pores do not change significantly – these are so-called stiff pores. In our modeling, we have considered spherical pores that are connected by ‘pore throat’ - a passage between any two spherical pores, which resembles with ellipsoidal pores (Fig. 3). These ellipsoidal pores are not as soft as cracks or fractures and very high effective pressure is required to close them. In other words, we presume porosity is unchanged with pressure. Also, after CO₂ injection no overpressure is observed in the open saline aquifer.

Fig. 13 shows that the calculated impedance from the PDEM theory increases as we move from seismic frequency to ultrasonic frequency by 9 and 11% for water saturated and 80% CO₂ saturated sediment respectively. We observe that the predicted impedances at seismic (10 Hz) and sonic frequencies (10 KHz) for 80% CO₂ saturation, and for 0% and 100% CO₂ saturation at seismic frequency (Fig. 14) vary almost in similar way. Thus, if low frequency seismic data are required to interpret through sonic/ultrasonic measurements, then any low frequency rock physics model will not be appropriate to explain the log (sonic) or laboratory measured (ultra-sonic) elastic properties of sediments, if dispersion phenomenon occurs due to fluid flow between different kind of pores.

In this paper, we consider free CO₂ gas in the pore space, but with time the gas will dissolve into brine and become chemically reactive, which may change physical properties like porosity, permeability and mineralogy of the sediment. Numerical modeling shows that such reactions may have considerable effect on a twenty-year time scale (Johnson and Nitao, 2003). Also, fluid flow simulation study suggests upto 10% of free CO₂ gas has been dissolved into the

brine (Chadwick and Noy, 2010). Since, we are dealing with the data of the year 2001, assumption of only free CO₂ phase can be justified from the previous studies.

We observe calculated acoustic velocity from the PDEM theory is insensitive above 25% of CO₂ saturation for uniform gas model. Our model predicts that maximum CO₂ concentration for two end members (uniform to patchy) of distribution varies from 20% to 80% in the region of lowest acoustic impedance. Figs 10 and 11 demonstrate that CO₂ gas is migrating upwards due to buoyancy as a CO₂ gas plume, while, some amount of gas spread laterally. In our modeling, uncertainty in prediction of saturation of any kind of distribution is much less than 10%. Though, distribution of gas in the pore space is seldom known, existence of bright reflections in all the post injection seismic data with reference to the base line pre-injection survey indicates very high saturation of CO₂ within the sand layers.

Velocity pushdown below the reservoir can be a useful proxy to estimate the cumulative mass and distribution of CO₂ within a reservoir (Boait et al., 2012). Observed pushdown and cumulative amplitude of reflective horizons suggest huge accumulation of CO₂ within the sand layers. Previous studies in this region (Chadwick et al., 2005; Golding et al., 2011; Queißer and Singh, 2013) established that saturation of CO₂ is probably more than 30%. Boait et al. (2012) suggests that distribution of CO₂, as a whole, is not uniform as time-varying reflectivity is observed. Comparing our predictions for both types of distribution with the injected CO₂ mass, we conclude CO₂ is mainly distributed as patches of gas; though some amount of gas may mix with water homogeneously. The S-wave impedance distribution that can be estimated from pre-stack inversion can perhaps result in better constraints on the characterization of fluid in the pore space as well as our prediction.

Appendix A

Existing static DEM theory (Hornby et al., 1994) can be expressed as follows:

$$\frac{dC}{dv_i} = \frac{1}{1-v_i}(C_i - C)K_i C \quad (A1)$$

where, dC is the change in effective stiffness C due to an increment dv_i in volume concentration v_i of the i th component, C_i is stiffness of the i th inclusion. K_i is a fourth rank tensor that relates the applied stress σ to the average inclusion strain e_i as (Hudson and Knopoff, 1989),

$$e_i = K_i \sigma, \quad (A2)$$

For fluid-filled pores/cracks, the inclusion stress (σ_i) can be replaced with the pore fluid pressure tensor $p_i \delta$, δ being the Dirac delta function. The relation between inclusion strain (e_i) and inclusion stress (σ_i) is given below (Zatsepin and Crampin, 1997; Chapman et al., 2002),

$$e_i = (I - PC)^{-1} C^{-1} (\sigma - CP p_i \delta) \quad (A3)$$

where, I is the identity matrix of rank four. P is also a fourth rank tensor (Mura, 1982, Page 119).

The PDEM theory is derived by substituting Eqs (A2) and (A3) in Eq. (A1) that finally takes the form as

$$\frac{dC}{dv_i} = \frac{1}{1-v_i} (C_i - C) (I - PC)^{-1} C^{-1} (\sigma - CP p_i) \sigma^{-1} C. \quad (A4)$$

Appendix B

The complete stress tensor for an isotropic body looks like

$$\sigma = \begin{bmatrix} (\lambda + 2\mu)\varepsilon_{xx} + \lambda(\varepsilon_{yy} + \varepsilon_{zz}) & 2\mu\varepsilon_{xy} & 2\mu\varepsilon_{xz} \\ 2\mu\varepsilon_{yx} & (\lambda + 2\mu)\varepsilon_{yy} + \lambda(\varepsilon_{xx} + \varepsilon_{zz}) & 2\mu\varepsilon_{yz} \\ 2\mu\varepsilon_{zx} & 2\mu\varepsilon_{zy} & (\lambda + 2\mu)\varepsilon_{zz} + \lambda(\varepsilon_{xx} + \varepsilon_{yy}) \end{bmatrix} \quad (\text{B1})$$

In classical elasticity, the strain and stress tensors associated with the propagation of a P-wave are given by

$$\varepsilon^P = \begin{bmatrix} 1 & 0 & 0 \\ 0 & 0 & 0 \\ 0 & 0 & 0 \end{bmatrix} s(t) \quad (\text{B2})$$

$$\sigma^P = \begin{bmatrix} \lambda + 2\mu & 0 & 0 \\ 0 & \lambda & 0 \\ 0 & 0 & \lambda \end{bmatrix} s(t) \quad (\text{B3})$$

Similarly, the strain and stress tensors associated with the propagation of a S-wave are given by

$$\varepsilon^S = \begin{bmatrix} 0 & 0 & 1 \\ 0 & 0 & 0 \\ 1 & 0 & 0 \end{bmatrix} s(t) \quad (\text{B4})$$

$$\sigma^S = \begin{bmatrix} 0 & 0 & 2\mu \\ 0 & 0 & 0 \\ 2\mu & 0 & 0 \end{bmatrix} s(t) \quad (\text{B5})$$

where, $s(t)$ is a harmonic function (Chapman et al., 2002; Chapman, 2003). Lamé' parameters λ and μ are the elastic properties of the matrix.

419 **Appendix C**

420

421 The expected pressure in a spherical pore (p_p) is given by (Chapman, 2003),

$$422 \quad p_p = D_p \sigma_{ii} \quad (C1)$$

423 where,

$$424 \quad D_p = \gamma_1 / \gamma \quad (C2)$$

$$\gamma = (3/8) * (\pi / ((1 - \nu) * (1 + k_c))) * (1 + k_p)$$

$$425 \quad \gamma_1 = \gamma * ((1 - \nu) / (1 + \nu)) * (1 / (1 + k_p))$$

$$k_p = ((4/3) * \mu) / k_f$$

$$k_c = (\pi * \mu * r) / (2 * (1 - \nu) * k_f)$$

426 The pressure in an ellipsoidal pore (p_c) is given by (Chapman, 2003),

$$427 \quad p_c = G_1 \sigma_i + G_2 \sigma_{ii} \quad (C3)$$

428

429 where,

$$430 \quad G_1 = \frac{i\omega\tau_m}{(1 + k_c)(1 + i\omega\tau_m)}, \quad (C4)$$

$$431 \quad G_2 = \frac{1 + i\omega\gamma\tau_m}{1 + i\omega\tau_m} D_c - \frac{i\omega\tau_m\gamma'}{1 + i\omega\tau_m}$$

$$432 \quad D_c = ((1 - \iota) * \gamma_1) + (\iota * ((1 + i\omega\tau_m\gamma_1) / (1 + i\omega\tau_m)))$$

$$433 \quad \iota = (\phi_c / r) / ((\phi_c / r) + \phi_p)$$

434

435 Here, σ_i, σ_{ii} are respectively normal stress acting on a crack face and sum of all normal stresses,

436 τ_m is the characteristic time of squirt flow for pore-scale heterogeneity, ω is the angular

437 frequency, p_v, c_v are respectively volumes of individual pore and crack, ϕ_c is crack porosity, k_f is

438 fluid bulk modulus, κ is fluid permeability, η is fluid viscosity, ζ is grain size, μ and ν are

respectively shear modulus and Poisson's ratio of the matrix, r is the aspect ratio of ellipsoidal pore.

Appendix D

The distribution dependant effects of CO₂ gas on the elastic properties of sediment have been accounted by modifying the calculation of the fluid's bulk modulus. A uniform or homogeneous gas distribution assumes that proportions of water and gas are same in each pore space. In this case, effective elastic stiffness of the saturated sediment is calculated from our modeling with fluid bulk modulus as K_f recalculated from the Reuss average of the water (K_w) and gas (K_g) bulk moduli (Mavko et al., 1998; Helgerud et al., 1999):

$$K_f = \frac{S_w}{\frac{1}{K_w} + \frac{1-S_w}{K_g}} \quad (D1)$$

where, S_w is the water saturation.

Patchy distribution occurs when patches of gas is much larger than the average pore size and fully surrounded by water-saturated sediment. In this case, effective elastic stiffness of the sediment is calculated as (Mavko et al., 1998; Helgerud et al., 1999):

$$C_{eff}^{ij} = \frac{S_w}{\frac{1}{C_{wsat}^{ij}} + \frac{1-S_w}{C_{gsat}^{ij}}}, \quad i = 1, 6; j = 1, 6 \quad (D2)$$

where, C_{wsat}^{ij} and C_{gsat}^{ij} are the effective stiffness calculated for fully water saturated and fully gas saturated sediments.

Acknowledgements

We are thankful to Statoil and SINTEF Petroleum Research Institute, Trondheim, Norway for providing us seismic and well log data. We are also thankful to the Director, CSIR-NGRI, Hyderabad, India and The Royal Norwegian Embassy, New Delhi for financial support and permission to publish this work. We are thankful to the two anonymous reviewers for useful suggestions. MKS was partially supported at the Center for Frontiers of Subsurface Energy Security, an Energy Frontier Research Center funded by the U.S. Department of Energy, Office of Science, Office of Basic Energy Sciences under Award Number DE-SC0001114.

References

- Arts, R., Eiken, O., Chadwick, R. A., Zweigel, P., van der Meer, L., Zinsaner, B., 2004. Monitoring of CO₂ injected at Sleipner using timelapse seismic data. *Energy* 29, 1383–1392.
- Arts, R., Chadwick, R. A., Eiken, O., Thibeau, S., Nooner, S., 2008. Ten years' experience of monitoring CO₂ injection in the Utsira Sand at Sleipner, offshore Norway. *First Break* 26, 65–72.
- Arts, R., Eiken, O., Chadwick, R. A., Zweigel, P., Van der Meer, L., Zinszner, B., 2003. Monitoring of CO₂ injected at Sleipner using time lapse seismic data, In: Gale, J. & Kaya, Y. (eds) *Greenhouse Gas Control Technologies*. Elsevier, Oxford, 347–352.
- Baklid, A., Korbøl, R., Owren G., 1996. Sleipner Vest CO₂ disposal, CO₂ injection into a shallow underground aquifer, paper presented at SPE Annual Technical Conference and Exhibition, Society of Petroleum Engineering, Denver.
- Boait, F. C., White, N. J., Bickle, M. J., Chadwick, R. A., Neufeld, J. A., Huppert, H. E., 2012. Spatial and temporal evolution of injected CO₂ at the Sleipner Field, North Sea. *Journal of Geophysical Research* 117, B03309.

- Carcione, J. M., Picotti S., 2006. P-wave seismic attenuation by slow wave diffusion: Effects of inhomogeneous rock properties. *Geophysics* 71 (3), O1–O8, doi:10.1190/1.2194512.
- Chadwick, R. A., Arts, R., Eiken, O., 2005. 4D seismic quantification of a growing CO₂ plume at Sleipner, North Sea, in *Petroleum Geology: North-West Europe and Global Perspectives: Proceedings of the 6th Petroleum Geology Conference Held at the Queen Elizabeth II Conference Centre, London 6–9 October 2003*, edited by A. G. Dore and B. A. Vining, pp. 1385–1399, Geol. Soc., London.
- Chadwick, R. A., Noy D. J., 2010. History: Matching flow simulations and time-lapse seismic data from the Sleipner CO₂ plume, in *From Mature Basins to New Frontiers: Proceedings of the 7th Petroleum Geology Conference Held at the Queen Elizabeth II Conference Centre, London 30 March-2 April 2009*, edited by B. A. Vining and S. C. Pickering, pp. 1171–1182, Geol. Soc., London.
- Chadwick, R. A., et al., 2010. Quantitative analysis of time-lapse seismic monitoring data at the Sleipner CO₂ storage operation. *Leading Edge* 29, 170–177.
- Chadwick, R. A., Zweigel, P., Gregerson, U., Kirby, G., Holloway, S., Johannessen, P., 2004. Geological reservoir characterization of a CO₂ storage site: The Utsira Sand, Sleipner, northern North Sea. *Energy* 29, 1371–1381.
- Chadwick, R. A., Arts, R., Eiken, O., Williamson, P., Williams G., 2006. Geophysical monitoring of the CO₂ plume at sleipner, north sea: an outline review, *In: Lombardi, S., Altunia, L.K., and Beaubien, S.E. (Eds.) Advances in the Geological Storage of Carbon Dioxide*. Springer, Dordrecht, NATO Science, IV Earth and Environmental Sciences Vol. 65, 303-314.
- Chapman, M., 2001. Modelling the wide-band laboratory response of rock samples to fluid and pressure changes. PhD thesis, University of Edinburgh.
- Chapman, M., 2003. Frequency-dependent anisotropy due to meso-scale fractures in the presence of equant porosity. *Geophysical Prospecting* 51, 369–379.
- Chapman, M., Zatsepin, S. V., Crampin, S., 2002. Derivation of a microstructural poroelastic model. *Geophysical Journal International* 151, 427–451.

520 Clochard, V., Delépine, N., Labat, K., Ricarte P., 2009. Post-stack versus pre-stack stratigraphic
521 inversion for CO₂ monitoring purposes: A case study for the saline aquifer of the
522 Sleipner field, SEG International Exposition and 79th Annual Meeting, Expanded
523 Abstracts, 2417–2421.

524 Crampin, S., 1994. The fracture criticality of crustal rocks. *Geophysical Journal International*
525 118, 428–438.

526 Delépine, N., Clochard, V., Labat, K., Ricarte, P., 2011. Post-stack stratigraphic inversion
527 workflow applied to carbon dioxide storage: application to the saline aquifer of Sleipner
528 field. *Geophysical Prospecting* 59, 132-144 .

529 Dvorkin, J., Mavko, G., Nur A., 1995. Squirt flow in fully saturated rocks, *Geophysics* 60, 97–
530 107.

531 Eshelby, J. D., 1957. The determination of the elastic field of an ellipsoidal inclusion, and related
532 problems. *Proceedings of the Royal Society London*, A241, 376–396.

533 Fornel, A., Estublier, A. 2012. To a dynamic update of the Sleipner CO₂ storage geological
534 model. GHGT-11 Conference, Kyoto, 19-22 Nov 2012.

535 Gassmann F., 1951. Ueber die Elastizität poröser Medien. *Vierteljahresschrift der*
536 *Naturforschenden Gesellschaft in Zürich*, 96, 1–23.

537 Ghosh, R., Sen M. K., 2012. Predicting subsurface CO₂ movement: From laboratory to field
538 scale. *Geophysics* 77, 1–11.

539 Ghosh, R., Sain, K., Ojha M., 2010, Effective medium modeling of gas hydrate-filled fractures
540 using the sonic log in the Krishna-Godavari basin, offshore eastern India. *Journal of*
541 *Geophysical Research* 115, B06101 (a).

542 Golding, M. J., Huppert H., 2011. The effect of confining impermeable boundaries on gravity
543 currents in a porous medium. *Journal of Fluid Mechanics* 649, 1–17.

544 Helgerud, M. B., Dvorkin, J., Nur, A., Sakai, A., Collet, T., 1999. Elasticwave velocity in marine
545 sediments with gas hydrates: Effective medium modeling: *Geophysical Research Letters*
546 26, 2021–2024, doi: 10.1029/ 1999GL900421.

547 Hornby, B. E., Schwartz, L. M., Hudson J. A., 1994. Anisotropic effective-medium modeling of
548 elastic properties of shales. *Geophysics* 59, 1570–1583.

549 Hudson, J. A., Knopoff L., 1989. Predicting the overall properties of composite materials with
550 small-scale inclusions of cracks. *Pure and Applied Geophysics* 131, 551-576.

551 Isaksen, D., Tonstad, K., 1989. A revised Cretaceous and Tertiary lithostratigraphic
552 nomenclature for the Norwegian North Sea, Bulletin 5, Norwegian Petroleum
553 Directorate, Stavanger, Norway.

554 Jakobsen, M., J. A. Hudson, T. A. Minshull, and S. C. Singh (2000), Elastic properties of
555 hydrate-bearing sediments using effective medium theory, *J. Geophys. Res.*, 105 561–
556 577.

557 Jakobsen, M., Chapman, M., 2009. Unified theory of global flow and squirt flow in cracked
558 porous media. *Geophysics* 74, P.WA65–WA76.

559 Johnson, J. W., Nitao J. J., 2003. Reactive transport modelling of geologic CO₂ sequestration at
560 Sleipner. In: Gale J, Kaya Y, editors. *Greenhouse Gas Control Technologies*. Elsevier
561 Science Ltd, Oxford, p. 327 – 332.

562 Labat, K., Del’epine N., Clochard, V., Ricarte, P., 2012. 4D Joint Stratigraphic Inversion of
563 Prestack Seismic Data: Application to the CO₂ Storage Reservoir (Utsira Sand
564 Formation) at Sleipner Site. *Oil & Gas Science and Technology – Rev. IFP Energies*
565 *nouvelles* 67 (2), 329-340

566 Lindeberg, E., Vuillaume, J., Ghaderi A., 2009. Determination of the CO₂ storage capacity of the
567 Utsira formation, *Energy Procedia* 1, 2777–2784.

568 Lyle, S., Huppert, H., Hallworth, M., Bickle, M., Chadwick A., 2005. Axisymmetric gravity
569 currents in a porous medium. *Journal of Fluid Mechanics* 543, 293–302.

570 Mavko, G., Mukerji, T., Dvorkin, J., 1998. *The rock physics handbook: tools for seismic analysis*
571 *of porous media*, Cambridge University Press.

572 Meer LGHvander, Arts, R. J., Peterson, L., 2001. Prediction of migration of CO₂ injected into a
573 saline aquifer: reservoir history matching to a 4D seismic image with a compositional
574 gas/water model. In: Williams DJ, et al., editors. *Greenhouse gas control technologies*.

Collingwood, Australia: CSIRO Publishing, 378–84.

Mori, T., Tanaka, K., 1973. Average Stress in the Matrix and Average Elastic Energy of Materials with Misfitting Inclusions. *Acta metallurgica* 21, 571–574. [doi:10.1016/0001-6160\(73\)90064-3](https://doi.org/10.1016/0001-6160(73)90064-3).

Mukerji, T., Mavko, G., 1994. Pore fluid effects on seismic velocity in anisotropic rocks, *Geophysics*, 59, 233–244.

Mura, T., 1982. *Micromechanics of defects in solids* (Martinus Nijhoff).

Murphy, W.F., 1985. Sonic and ultrasonic velocities: theory versus experiment. *Geophysical Research Letter* 12, 85–88.

Norirs, A. N., 1989. An Examination of the Mori-Tanaka Effective Medium Approximation for Multiphase Composites. *Journal of Applied Mechanics* 56 (1), 83-88.

Peacock, S., McCann, C., Sothcott, J., Astin T.R., 1994. Seismic velocities in fractured rocks; an experimental verification of Hudson’s theory. *Geophysical Prospecting* 42, 27–80.

Pride, S. R., Berryman, J. G., Harris J. M., 2004. Seismic attenuation due to wave induced flow. *Journal of Geophysical Research* 109, B01201, doi: 10.1029/2003JB002639.

Queiße, M., Singh, S. C., 2013. Full waveform inversion in the time lapse mode applied to CO₂ storage at Sleipner. *Geophysical Prospecting* 61, 537-555.

Rubino, J. G., Velis D. R., 2011. Seismic characterization of thin beds containing patchy carbon dioxide-brine distributions: A study based on numerical simulations. *Geophysics* 76 (3), R57–R67, doi: 10.1190/1.3556120.

Sayers, C. M., 1994, The elastic anisotropy of shales, *Journal of Geophysical Research* 99, 767–774, doi:10.1029/93JB02579.

Sen, M. K., and P. L. Stoffa, 1996, Bayesian inference, Gibbs’ sampler and uncertainty estimation in geophysical inversion, *Geophysical Prospecting* 44 (2), 313-350.

Sen, M. K., 2006, *Seismic Inversion*, Society of Petroleum Engineers.

Sen, M.K., Stoffa, P.L., 2013. *Global optimization methods in Geophysical inversion* (Elsevier).

Sothcott, J., McCann, C., O’Hara S.G., 2000. The influence of two different pore fluids on the acoustic properties of reservoir sandstones at sonic and ultrasonic frequencies, 70th SEG

- Meeting, Calgary, Canada, Expanded Abstracts, 1883–1886.
- White, J. E., 1975. Computed seismic speeds and attenuation in rocks with partial gas saturation. *Geophysics* 40, 224–232, doi:10.1190/ 1.1440520.
- White, J. E., Mikhaylova, N. G., Lyakhovitskiy, F. M., 1975, Low-frequency seismic waves in fluid saturated layered rocks, *Izvestija, Academy of Sciences, USSR: Physics of the Solid Earth* 11, 654–659.
- Zatsepin S. V., Crampin, S., 1997. Modelling the compliance of crustal rock, I. Response of shear-wave splitting to differential stress. *Geophysical Journal International* 129, 477–494.
- Zweigel, P., Lothe, A., Arts, R., Hamburg, M., 2000. Reservoir geology of the storage units in the Sleipner CO₂-injection case: A contribution to the saline aquifer CO₂ storage project (SACS), Rep. 23.4285.00/02/00, Stiftelsen for Indust. og Tek. Forsk., Trondheim, Norway.

Fig. Captions

Fig. 1. Location of Sleipner Field (after Arts et al., 2008).

Fig. 2. Representative 2D seismic sections from the pre-injection and the post-injection post stack 3D seismic volume of the year 1994 (top panel) and 2001 (bottom panel) respectively.

Fig. 3. A schematic diagram of heterogeneous microstructure of a sandstone reservoir describing approximate geometry of different constituents.

Fig. 4. Observed acoustic impedance from well log and the calculated impedance using PDEM theory.

Fig. 5. Flowchart describing the directed Monte-Carlo method for background calibration.

Fig. 6. Mean model parameters with depth estimated by the Monte-Carlo method based on fitting the observed background impedance at the well.

Fig. 7. Correlation between original log (blue), initial model (black) and inverted model (red), and synthetic (red) and seismic (black) data at the well location. A wavelet shown in the window is used for inversion.

Fig. 8. Derived (a) synthetic seismic and (b) residual section (difference between real seismic and synthetic seismic) of the year 2001.

Fig. 9. One representative 2D Seismic impedance section (time window 700-1300 ms with 2 ms sampling interval) derived by inverting seismic data of 2001.

Fig. 10. Predicted CO₂ saturation section corresponding to the impedance section shown in Fig. 9 for uniform (upper) and patchy (lower) distribution.

Fig. 11. Horizontal distribution of CO₂ saturation at different depth points (depth slice). Left panel is for patchy and right panel is for uniform distributions.

Fig. 12. Estimated uncertainty (in percentage) for uniform (upper) and patchy (lower) type CO₂ saturation.

Fig. 13. Predicted impedances for various CO₂ saturation with frequency.

Fig. 14. (a) Predicted impedances for 80% CO₂ saturation at 10 Hz (seismic) and 10 KHz (sonic) frequencies, (b) Predicted impedances for 0% and 80% CO₂ saturation at 10 Hz frequency.

Table Caption

Table 1. Elastic properties of different constituents of sediment used for modeling.

Fig. 1

Fig. 2

679
680

681
682
683
684

Fig. 3

Fig. 4

Fig. 5

Fig. 6

Fig. 7

Fig. 8

Fig. 9

717
718
719
720
721
722
723
724
725
726
727
728
729
730
731

Fig. 10

Fig. 11

Fig. 12

Fig. 13

Fig. 14

Components	Bulk-modulus (GPa)	Rigidity- modulus (GPa)	Density (kg/m ³)
Quartz	38	44	2700
Clay	21	6.7	2600
CO ₂	0.0229	-	693
Brine	2.3	-	1090

Table 1