1 Probabilistic cost estimation methods for treatment of water extracted during CO₂ storage and EOR.

2 Enid J. Sullivan Graham^{a*}, Shaoping Chu^b, and Rajesh J. Pawar^b

3 ^aChemical Diagnostics and Engineering Group, MS J964, Los Alamos National Laboratory, Los Alamos,
4 New Mexico, 87545, ejg@lanl.gov, ph 505-667-2889, f 505-665-2342

5 ^bComputational Earth Science Group, MS T003, Los Alamos National Laboratory, Los Alamos, New
6 Mexico, 87545

7 *corresponding author

8

9 ABSTRACT

10 Extraction and treatment of in-situ water can minimize risk for large-scale CO₂ injection in saline aquifers
11 during carbon capture, utilization, and storage (CCUS), and for enhanced oil recovery (EOR).
12 Additionally, treatment and reuse of oil and gas produced waters for hydraulic fracturing will conserve
13 scarce fresh-water resources. Each treatment step, including transportation and waste disposal, generates
14 economic and engineering challenges and risks; these steps should be factored into a comprehensive
15 assessment. We expand the Water Treatment Model (WTM) coupled within the sequestration system
16 model CO₂-PENS and use chemistry data from seawater and proposed injection sites in Wyoming, to
17 demonstrate the relative importance of different water types on costs, including little-studied effects of
18 organic pretreatment and transportation. We compare the WTM with an engineering water treatment
19 model, utilizing energy costs and transportation costs. Specific energy costs for treatment of Madison
20 Formation brackish and saline base cases and for seawater compared closely between the two models,
21 with moderate differences for scenarios incorporating energy recovery. Transportation costs corresponded
22 for all but low flow scenarios (<5000 m³/d). Some processes that have high costs (e.g., truck
23 transportation) do not contribute the most variance to overall costs. Other factors, including feed-water
24 temperature and water storage costs, are more significant contributors to variance. These results imply
25 that the WTM can provide good estimates of treatment and related process costs (AACEI equivalent level
26 5, concept screening, or level 4, study or feasibility), and the complex relationships between processes
27 when extracted waters are evaluated for use during CCUS and EOR site development.

28
29 Keywords: organic pretreatment, reverse osmosis, multiple-effect distillation, importance analysis, Monte
30 Carlo simulation.

31 32 INTRODUCTION

33 Extraction of in-situ water (referred to here as “extracted water”) is a critical option for minimizing the
34 impacts and enhancing large-scale CO₂ injection in saline aquifers during carbon capture, utilization, and
35 storage (CCUS). The potential reuse of extracted (“produced”) waters derived from oil and gas
36 production processes is also a key issue during enhanced oil recovery (EOR) and hydraulic fracturing for
37 shale gas and oil. For sequestration, water may be extracted from storage reservoirs during CO₂ injection
38 in order to control the movement of CO₂ in the subsurface, to control system pressures, and to increase
39 available pore space. Commercial-scale CCUS may require large volumes of water to be extracted, on the
40 order of cubic kilometers over 30 years[1]. For the oil and gas industry, reuse of produced water creates a

constant, drought-proof source of water for drilling and completions. Treatment and use of these extracted waters could provide alternative resources to replace fresh-water demands for carbon capture processes, thermoelectric cooling, hydraulic fracturing, and other water uses for carbon-capture power plants and industrial use. However, extracted waters typically have complex chemistries, including a wide range of total dissolved solids (TDS) (up to 200,000 mg/L or greater); high organic carbon contents ($\mu\text{g/L}$ to percent range); and high concentrations of scale-forming minerals (e.g., carbonates, sulfates)[2]. The waters at times may also contain naturally-occurring radioactive materials (NORM, as Ra-226 and Ra-228) [3, 4]. Disposal of the waste products from desalination can be costly, particularly when deep well injection is required for the concentrated effluent (“concentrate”) [5]. While site-specific engineering analysis clearly can define the costs to treat a specific water source [6], little analysis has been conducted to understand the broader significance and impacts of cumulative process choices, or varying source properties, on the overall cost trends of treatment for CO_2 storage-extracted waters (hereafter, “extracted waters”). Each step of treatment, including treated product transportation and waste concentrate disposal, generates additional economic and engineering challenges and risks; these need to be factored into a comprehensive assessment in order to fully understand and evaluate water treatment options. When viewed as a whole system, nearly every process choice is linked to one or more process outcomes. Knowledge of these costs with respect to other system costs for carbon capture, utilization, and storage (CCUS) can help evaluate the economic impacts associated with CCUS system design and implementation. Evaluating treatment process selections, the costs of these processes, and the tradeoffs of the costs and processes are an important portion of overall system understanding, risk assessment, and total cost of the CCUS system.

Variations in temperature, pressure, and salinity are primary factors that affect water treatment choices [7]. State-of-the-art reverse osmosis (RO) treatment for marine-type water chemistries (TDS $\sim 35,000$ - $40,000$ mg/L) is well understood and readily assessed for costs and process choices [8, 9]. However, marine-type chemistry conditions are not common among extracted waters [2, 7, 10, 11]. Higher salinities ($>45,000$ mg/L TDS) in extracted waters will require thermal methods (e.g., multi-stage flash [MSF] or multiple-effect distillation [MED]); we have shown these methods to be more cost effective than membrane treatments in some circumstances[7]. The International Energy Agency Greenhouse Gas (IEAGHG) program presented treatment cost analyses for four specific locations worldwide; variance in costs was related to water extraction rate but not to transportation; variable salinity was considered, but not other aspects of geochemistry [2]. Others have examined treatment of extracted water within the inorganic geochemical constraints of carbon storage on aquifer geochemistry [11-13]. Beneficial use of coal-bed methane waters, including geochemistry and treatment, was examined by Dahm and others [14].

Among these studies, there is a need for better analysis of treatment scenarios as a part of a total system approach to understanding the effects of process choices on overall costs and risks to CCUS scenarios [1].

The cost of electricity, pretreatments (organic and inorganic), and transportation strongly impact the total cost of treatment [9]. While total energy (thermal and electric combined) use for thermal desalination processes is higher than other processes (40-120 kWh/m³), electricity is typically the sole power source for membrane treatments such as RO (3.5-4.5 kWh/m³) or nanofiltration (NF) [9]. Electricity use is strongly correlated with total RO costs, because electricity is used to drive the pumps that create pressure on the separation membranes [15-17]. The higher the system salinity, the more electrical energy consumed, up to the point where membranes are no longer effective (>~45,000 mg/L TDS) because of membrane osmotic potential limitations [8, 17]. Energy recovery from the pressurized system on the concentrate side of the membrane is now routinely performed by using devices such as Pelton turbines or turbochargers, and has been very effective at driving down the overall costs of membrane treatments [18].

Inorganic pretreatments to remove divalent constituents (Ca²⁺, Mg²⁺, SO₄²⁻, Ba²⁺) and other constituents (Fe, silica) are used to prevent scaling and fouling in both membrane systems and thermal treatment systems, although thermal treatments by design use pretreatments less frequently [19]. Pretreatment includes acid and/or antiscalant chemical additions to prevent mineral scale formation, aeration, and micro- or ultrafiltration to remove particulates. Water types requiring pretreatment based on their affinity for fouling are discussed by El-Manharawy [20]; many of the waters extracted for carbon storage purposes are expected to have not only high chloride concentrations (> 100 mMol/kg Cl⁻ or >10,000 mg/L TDS by EPA regulation)[21], but will also have high sulfate fouling potential based upon SO₄/Alkalinity ratios (>10; seawater ~10) and high carbonate fouling potentials (typically found in waters between 4,000 mg/L to ~45,000 mg/L TDS) [2, 11, 22, 23]. A similar situation exists for oil and gas produced waters [24, 25]. Even though guidelines are available to develop pretreatment methods and costs for seawater RO (e.g., Dow [26]), little information is available regarding costs, and therefore sensitivity, for pretreatment of extracted or produced waters.

There are currently no models for treatment of extracted water that adequately address organic pretreatment [2, 15]. The use of EOR reservoirs for carbon storage means a likelihood that extracted water will contain organic constituents from oil residues. These constituents may cause fouling of membrane or thermal systems, may be toxic, and liable for regulation [27]. Membrane manufacturers suggest that the organic content in feed waters be reduced to <0.5 mg/L to prevent fouling [26]. Consequently, organic pretreatment is necessary prior to RO and NF membrane treatment, and often is advisable for thermal treatments to prevent air emissions of toxic, volatile chemicals. Engineering design

models for membrane desalination plants usually rely on seawater composition which includes moderate, known ranges of polar organic compounds such as organic acids [10, 26, 28, 29]; for waste-water treatment, known composition and concentration data is preferred. For extracted waters, information is scarce; in particular, the National Carbon Sequestration Database and Geographic Information System (“NATCARB”) does not yet contain significant dissolved or total organic content information for sequestration formations [30]. To fill this data gap, we can use characterization information in the literature for oil and gas produced waters and EOR waters, that contain from $<1 \mu\text{g/L}$ to $>11,000 \text{ mg/L}$ concentrations of total organic carbon (TOC) [31]. TOC in EOR reservoir waters includes not only organic acids, but nonpolar, volatile and semivolatile, aliphatic, and aromatic organic compounds. Different types of organic compounds require different types of pretreatment. There are many different options for treatment of organic constituents in water, with widely varying capabilities and costs [32-34]. Free-phase oils or colloids are often removed by oil-water separation or dissolved air flotation (DAF). Dissolved non-polar organic compounds can be removed by sorption, oxidation, air stripping or vapor extraction, and biological degradation methods. Dissolved polar compounds are removed via oxidation, membrane separation (e.g., nanofiltration), biological degradation, ion exchange, or precipitation. A lack of specific composition and concentration information, and, thus, poorly defined pretreatment choices, may lead to poor estimations of costs for organic pretreatment of extracted waters. The variance in these costs should be considered as a part of the total cost profile of the system.

Transportation costs are more easily quantifiable than pretreatments, can contribute to costs at multiple steps in the treatment process, and have interdependencies with other treatment aspects including concentrate disposal and delivery of treated water to the end user. For example, Class II well disposal is a common method for disposal of saline oil and gas produced water, and may be an important option for disposal of EOR concentrate from extracted waters. However, if this option is not available locally (e.g., as in the Marcellus region of Pennsylvania), then transportation to the disposal point becomes increasingly significant as a cost contributor to the disposal portion of the treatment train.

System models that include both primary (treatment train) and secondary or peripheral processes (transport to and from treatment; regulatory constraints) can expand our knowledge of the costs, risks, and impacts on the feasibility of large-scale treatment of extracted waters. The WTM uses more complexity than informal calculations, and incorporates up-to-date cost and process information, but is not intended to be a rigorous engineering design model. The cost estimation is equivalent to DOE/AACEI cost estimation level 5 (concept screening) or level 4 (study or feasibility) [35]. Stochastic data sets, such as water quality, feed water temperature, and volumes, are incorporated easily into the model. User input

such as site location, and distance to a disposal or treated water point-of-use are included. This type of model captures the major contributors to costs, without needing detailed site data, and while allowing sensitivity analysis and importance analysis for multiple variables to improve decision making. Here we describe use of the CO₂-PENS water treatment module (WTM) to assess potential CO₂ storage-extracted waters for costs of some primary and secondary processes that are significant to risk analysis and decision making. We examine the importance of transportation by truck and pipeline, the importance of pretreatment methods (for inorganic and organic foulants), the relationships of these costs with disposal choices, and show a relative performance comparison of the WTM with an engineering-based treatment design model [2, 15].

METHODS

CO₂-PENS Water Treatment Module

The WTM was developed using the GoldSim[®] platform [7, 36]. GoldSim[®] is used to develop analysis models that perform multi-realization, probabilistic simulations. A FORTRAN code captures the logic of treatment process selection and is linked within GoldSim[®]. GoldSim uses custom data elements for input of user-specified parameters including stochastic distributions. The WTM captures all decision points; both stochastic range and constant data input values. Figure 1 shows a model schematic diagram including user-specified and model-calculated factors. For this study, we have expanded WTM capability to address pretreatments for organic foulants, TDS composition effects on inorganic pretreatment choices (acid, antiscalent, or both), and a bimodal transportation model (truck and pipeline) (Figure 2). The WTM includes the effects of regulation on multiple disposal choices and the effects of location (regional climate) and water type (produced or not produced) on disposal choices (e.g., Class I, Class II, or Class V wells) [7]. Treatment choices are selected based on influent water volume, temperature, and composition. The WTM includes two modes for pretreatment costing: a generic pretreatment cost mode based on literature-reported treatment costs [7], that is activated based upon the user-reported pH of the water and adds a generic quantity of acid and/or antiscalent; and a specific scaling- potential calculation mode that accounts for scale-forming ion concentrations in the influent, that adds a calculated amount of acid and antiscalent based on specific user-reported mineral element concentrations in the water [26]. We refer to these modes as either “generic” or “specific” throughout the text. For CO₂ storage applications, costs are calculated in terms of US dollars/ton of CO₂ stored; for water treatment applications costs are calculated in terms of US dollars/m³ of water treated. Table 1 lists ranges of input parameters (design basis) for potential extracted and produced water types, including saline and brackish waters.

Figure 1. Schematic of Water Treatment Module. Top: Pretreatment phases. Bottom: Treatment and post-treatment phases. Transportation segments are designated as X1, X2, and X3. Pretreatments are defined as generic (source water chemistry unknown, generic cost applied), or specific (chemistry known and input by user, specific costs applied).

Figure 2. Simple transportation model.

The module accounts for influent flow volumes (Q_{in}), applies a calculated percent recovery ratio based on the water chemistry and treatment process used, and calculates the final volumes for both treated water (permeate, Q_{perm}) and wastewater (concentrate, Q_{conc}). Concentrate waste is always a byproduct of treatment, except when zero-liquid-discharge (ZLD) is a disposal option (creates a solid waste product).

We used data from three proposed CO₂ storage sites in Wyoming: the Madison Fm. and the Tensleep/Weber Fms. in the Rock Springs uplift region, and data for the Teapot Dome region, following our previous studies on pretreatment and thermal treatment methods [2, 7, 37].

Module Comparisons

Verification of a model indicates correct implementation of the conceptual model by observing consistency of response compared to real world applications and other models. We compared WTM results with the Desalination Energy Evaluation Program (DEEP) v.4.0 [15]. DEEP is a spreadsheet-based model that includes membrane and thermal treatment processes similar to the WTM, and has been used for treatment method and cost determinations for carbon sequestration site analysis [2]. DEEP includes engineering-based calculations, such as capital and O&M costs, infrastructure depreciation over a project lifetime, and economies of scale for treatment. The model uses seawater treatment technologies and processes as the design basis, and optimizes desalination based on specific energy consumption [15]. DEEP includes different types of power plant sources (nuclear, oil and gas, coal-fired) used to supply electricity and heat for desalination, while the WTM makes no assumptions for electricity

196 **Table 1.** Water quality scenarios, input and output data, and model criteria used for model simulations.

Location	Seawater [26]	Rock Springs Uplift, Madison Fm., Wyoming [37] “Madison Brackish”	Rock Springs Uplift, Tensleep/Weber Fms., Wyoming [37]	Teapot Dome, Wyoming [2]
Plant Type³	Saline Water RO	Brackish Water RO Saline Water MED and MSF	Saline and Hot Water >45°C MED and MSF	Saline Water RO, MED, and MSF
Formation Type	<i>Average Surface Seawater</i>	<i>Brackish to Saline Fm.; Gas Reservoir</i>	<i>Brackish to Saline Fm.; Oil and Gas Reservoir</i>	<i>Brackish to Saline Fm.; Oil and Gas Reservoir</i>
Feed Volume¹ (m³/d)-user input	37,854 (10 mgd)	37,854 (2000-10,000 [#]) (10 mgd)	37,854 (10 mgd)	6,700 m ³ /d
Supply TDS (mg/L) User input	35,000	<1,000-76,777[37] <i>Mean Brackish=14,114 Brine 2=52,852 mg/L TDS</i>	<1,000-101,685[37] <i>Brine 1=95,670 mg/L TDS</i>	10,000
Pretreatment Type	Model Selected	Model Selected	Model Selected	Model Selected
Permeate % of feed volume (model calculated)	50	50 [#]	50, 75, 90	50
Desired Permeate TDS (mg/L) User input	<500	<500-1500	<500-1500	<500
Concentrate as % of feed volume (model calculated)	50	50 [#]	50, 25, 10	50
Concentrate TDS (mg/L)	Model Output	Model Output	Model Output	Model Output
Cost to Treat (US\$/m³)	Model Output	Model Output	Model Output	Model Output
Temperature range (°C)-user input	25	49-117 (ref [38]); 25 (base case)	49-117 (ref [38]); Median=71	15-65 ² (selected range from [2])
Estimated cost of energy (US\$/kWh)-user input or model selected	0.07	0.04-0.20	0.04-0.20	0.07
Feed pH (ref [37])-user input	7	6.0-8.6	6.8-8.6	8.0
Feed Turbidity (NTU)-user input	5	0.5-10	0.5-10	5.0
Feed Silt Density Index-user input	5	0.5-10	0.5-10	5.0

Italics indicate a simulation criterion.

MSF= multi-stage flash distillation (thermal process); RO=reverse osmosis; mgd=million gallons per day

¹feed volume normalized to 37,854 m³/d or 10 mgd; ²lower temperature range used to illustrate effect of cooling during water storage and colder site temperatures; ³plant type is selected by model based on user inputs (TDS, Temperature); [#]base case parameters for verification of model.

or heat sources; electricity costs and influent water temperature are selected by the WTM user from reasonable or known values. Table 2 compares the features of each model. A base case of saline extracted water from the Madison Formation, in the Rock Springs uplift region of Wyoming (Table 1) was chosen for the DEEP and WTM comparison. We also use standard seawater chemistry (Table 1) [26] as a baseline for chemistry comparisons. Table 3 compares different parameters used for the models for the comparisons. A key difference between the models is that the WTM extracts literature cost data from many sources, and does not distinguish between capital and O&M costs, although these combined costs are sometimes used as input to the stochastic cost ranges used in model calculations. Results from the WTM are usually shown as probabilistic cost ranges per volume CO₂ stored, or per volume (m³) influent flow (Q) basis.

We use importance analysis to show the effects of different choices for treatment on overall costs, and the tradeoffs between what might otherwise be considered unrelated segments of treatment. This applies to choices that are stochastic in nature, where a range of values is possible. The importance analysis of the input variables to the results are statistical measures computed by analyzing multiple realizations of the model in which all of the stochastic variables are simultaneously sampled for each realization of a Monte Carlo simulation. The importance measure is a metric that varies between 0 and 1 representing the fraction of the result's variance that is explained by the variable. This measure is useful in identifying nonlinear, non-monotonic relationships between an input variable and the result (which conventional correlation coefficients may not reveal). The importance measures in this study are normalized for each case so that they can be compared among different cases of interest.

Estimation of inorganic pretreatment costs

Candidate deep saline reservoirs and oil and gas reservoirs for sequestration can have very high concentrations of scaling minerals, including divalent metals (calcium, magnesium, barium, strontium), iron, bicarbonate and sulfate [2, 11, 13, 22]. Most literature values for antiscalent treatment are based upon either inland brackish water conditions [39] or marine desalination conditions [16, 40] and may not reflect the full range of values that will occur in extracted waters. We used several examples ranging from brackish (Madison Fm.) to high salinity (Tensleep) waters to illustrate the effects of chemistry on inorganic pretreatment costs in the WTM [37]. The DEEP model does not estimate pretreatment costs,

227 **Table 2.** Comparison of model features.

Key Features	CO ₂ -PENS WTM	DEEP v. 4.0
Cost of Electric Power	User-selected variable, no plant source assumptions	Calculated from different plant sources
Pre- and post-treatments	User-selected variable or model assists	Included-user variable or default
RO Energy Recovery	User-selected variable methods	Included-fixed
Economies of Scale	Stochastic ranges from literature values with scaling algorithm	Engineering calculations
Disposal	Multiple methods, stochastic ranges. User-selected, model assists	Infall/outfall cost included as % of total cost (user can modify)
Transportation	Pipeline and Trucking, user-selected variable type and distances, stochastic ranges (literature)	Included as user off-on selection
Storage	Model Selected, Tank or Pond	Not included as separate cost

228

229 **Table 3.** DEEP and WTM parameters chosen for verification scenarios.

Parameter	CO ₂ -PENS WTM	DEEP v. 4.0
Energy cost (US\$/kWh)	0.04-0.20 (if fixed, 0.10)	Steam-cycle Coal cost rate 1800 MWt thermal power
Desalination Plant Type /recovery %	Reverse Osmosis/50 Multiple Effect Distillation/90	Reverse Osmosis/calculated Multiple Effect Distillation/calculated
Plant Capacity (m ³ /d)	1,700-10,000	1,700-10,000
Pretreatment	User selects method Model calculates costs	\$0.05/m ³
Transportation (km)	¹ X1= 1.6-32 (variable) ² X2=X3=0.8	Model selected
Maximum Membrane pressure (bar)	NA	69
Discount Rate %	NA	5
Interest Rate %	NA	5
Fuel Escalation Rate %	NA	3

230 ¹Truck and pipeline scenarios; ² pipeline only; NA=not applicable

231

but uses an adjustable rate for pretreatment, with a default setting of \$0.05/m³ (O&M chemical costs only). This rate is higher than some outside compiled estimates [16], and higher than generic pretreatment cost rates evaluated from literature values in the WTM, and thus is a conservative estimate. Using a conservative value is appropriate for the types of waters that might be extracted during carbon storage.

Estimation of organic pretreatment costs

The WTM uses literature-based cost ranges for various organic pretreatment technologies, including adsorption, oxidation, filtration, zeolite treatments, activated carbon, and chemical treatments (e.g., lime). Costs may vary widely on a site-to-site basis, and so a truncated probability cost curve with an appropriate median value is used to provide a probabilistic range for organic pretreatment, without the need for site-specific organic concentration data. This analysis is particularly useful for preliminary site evaluations, because little organic speciation or concentration information is known in most cases. Figure 3 shows ranges and medians for organic pretreatment costs gathered from the literature, along with an example of the truncated probability curve used by the WTM to estimate the most likely range of pretreatment costs for unknown concentrations of organic constituents. Low median values for some of the methods indicate that more sources were found with the lower costs, partially because of cost reductions over time as treatments have become more efficient. The use of the probability curve allows the user to best estimate the cost ranges of organic pretreatment without knowing the exact composition of the extracted water; the curve also can be used to estimate probabilities of costs changing when composition changes. This may occur, for example, when an extraction well is pumped for a long time. The DEEP model does not specifically address organic pretreatment, although these costs could be considered part of the generic cost of pretreatment along with inorganic pretreatments.

Figure 3. Literature cost ranges of various organic pretreatment methods (◇ are medians) (left), and an

example truncated probability curve as a solution to wide variations and site specificity in organic pretreatment costs (right).

RESULTS

Module verification -Energy Costs

Energy costs comprise approximately 50% of most seawater membrane (RO) treatment plant costs [8, 11, 16]. Figures 4a and 4b shows a comparison between specific energy costs in US\$ for a range of volumes treated per day (m^3/d) using the DEEP model and the WTM module for two CCUS scenarios, the Madison Fm. (brackish range, mean TDS~14,000 mg/L), Madison Fm. Brine 1 (high range TDS~75,000 mg/L) (Figure 4a), and for typical seawater (Figure 4b). Assumptions for these WTM model runs for simplified scenarios included a 50% recovery goal with no organic pretreatment, transportation, or storage. The WTM data includes various options for pressure energy recovery, such as Pelton turbines, and a no-recovery option; energy recovery is implicit in the DEEP calculations. The WTM returns both RO and thermal results in Figure 4a; the brackish water is treated by RO, while the brine is treated by thermal methods. The term “generic” refers to pretreatment scenario used; salinities for each case are shown in the Fig. 4a legend. Specific electricity costs (DEEP) are US\$0.24/ m^3 for seawater (42% recovery ratio), and US\$0.16/ m^3 for the Madison Fm. (14,000 mg/L TDS and 77% recovery ratio). Specific costs for seawater calculated by the WTM are US\$0.19/ m^3 ; and \$0.076/ m^3 for the Madison Fm. (14,000 mg/L case). Computations were run for the Tensleep Fm. Brine 2 (TDS=108,740 mg/L); however, the results were the same as for the Madison Fm. brine (Tensleep results not shown). This occurs because the WTM defaults to thermal treatment methods when the salinity exceeds 35,000 mg/L TDS (in common for both waters), and thermal treatment electrical costs are predominantly related to pumping, not salinity.

278

279 Figure 4a. WTM vs. DEEP model results for RO and thermal (MED and MSF) treatment cost analysis of
 280 Madison Fm. water. Costs from the WTM are: 1) total costs excluding transport and storage cost; 2)
 281 energy costs alone without additional energy recovery, and 3) energy costs with recovery methods (Pelton
 282 Turbine and Piston Isobaric). “Generic” refers to pretreatment type; salinities are listed for each scenario.

283

Figure 4b. WTM vs. DEEP for seawater, cost comparisons for RO treatment. Costs from the WTM are: 1) total costs excluding transport and storage cost; 2) energy costs alone without additional energy recovery, and 3) energy costs with energy recovery methods (Pelton Turbine and Piston Isobaric). Generic refers to pretreatment type.

Electricity costs presented here are model-calculated for membrane (RO) methods only; WTM does not calculate separate electricity costs for thermal methods. Borsani and Rebagliati [41] discuss methods for estimating costs for thermal plants (MSF, MED) as well as RO plants. They calculated that specific costs for electric power in treatment plants (seawater; 2005 US\$), based on a US\$0.03/kWh electricity cost, would be between \$0.10-0.15/m³ (\$0.12-0.18; 2013 US\$) (Table 4); this implies electricity cost percentages of 23% of total plant costs for MSF, 19% for MED, and 33% for RO. When these ratios are applied to total treatment costs from the WTM, MED and MSF electricity costs are very close to those calculated by DEEP for a steam-cycle coal-fired power plant (Table 4). DEEP arrives at power costs based upon user-selected characteristics of the power source to be used for desalination (e.g., coal, nuclear, steam cycle, gas cycle, etc.). A steam-cycle, coal-fired plant creates electricity at a modeled cost of US\$0.076/kWh, more than double the electricity cost used by Borsani and Rebagliati [41]. For Madison Fm. brackish (TDS~14,000 mg/L) water, this leads to a specific electricity cost of US\$0.155/m³ (15% of

Table 4. Comparison of electricity costs per volume of water treated.

	WTM			Borsani and Rebagliati			DEEP (coal, steam cycle)		
	RO	MED Calculated	MSF Calculated	RO	MED	MSF	RO	MED	MSF
Power cost (\$/kWh)	0.07	0.07	0.07	0.03	0.03	0.03	0.076	0.076	0.076
Seawater Case (\$/m³)	0.19	0.12	0.15	0.15	0.10 (0.12)*	0.12 (0.15)*	0.24	0.12	0.16
Madison Fm. Case TDS~14,000 mg/L (\$/m³)	0.076	0.084-0.22	0.10-0.26	N/A	N/A	N/A	0.16	0.12	0.16

N/A-not applicable. *values in parentheses are corrected to 2013 US\$ via inflation index. Plant size for calculations-10,000 m³/d, except: Borsani and Rebagliati: MSF and MED-58,000 m³/hr.

plant operating costs at 1000 m³/d, up to 30% at 8000 m³/d); for seawater, the specific electricity cost is US\$0.20/m³ (20% of operating costs at 1000 m³/d, up to 35% at 8000 m³/d).

Transportation Costs

We show a sensitivity analysis for both models in Figure 5. The DEEP model estimates transportation costs using a percentage of total treatment costs, while the WTM model takes user input information. The WTM model produces cost variations shown as median values derived from the full stochastic output distributions (not shown in Figure 5). For simplicity, the base WTM scenario was evaluated using either all trucking or all pipelines for transportation segments X1, X2, and X3 (Figure 2). Distances were varied from 0.8-32 km for the X1 transportation segment (Figure 2). The constant value of 0.8 km was used for X2 and X3 segments. Transportation adds considerably to costs for the DEEP results below 4000 m³/d capacity, with maximum costs near \$10/m³ at Q=1000 m³/d, compared to \$2/m³ for treatment with no transportation.

Figure 5. Sensitivity of DEEP (left) and WTM (right) to transportation choices for the Madison Fm., generic pretreatment case. Conditions include TDS= 14,000 mg/L; T= 15-45°C for RO, 45-65°C for thermal treatments. Note differences in y-axes.

Inorganic Pretreatment

A cross-check of seawater chemistry between the two WTM inorganic pretreatment modes (generic literature costs vs specific scaling potential calculations) yielded near-identical mean results (not shown). This supports the WTM generic scenario costs which are based on seawater desalination references. Figure 6a shows the sensitivity of the DEEP model to pretreatment cost variations. DEEP is dependent upon user cost input, while the WTM depends upon specific chemistry input values. Figure 6b shows mean pretreatment costs calculated with the WTM using various input chemistry values, including the Madison Fm. (~14,000 mg/L), seawater, and Brine 1 and Brine 2 (Table 1). The WTM is not designed to provide cost reductions for increased pretreatment volumes. The seawater example has the lowest pretreatment costs, converging with the DEEP model at higher capacities. The Madison Fm. and the two brine samples are more costly to treat based on input geochemistry values.

Figure 6a. Sensitivity of DEEP model to pretreatment cost variations. DEEP is dependent upon user cost input, WTM depends upon specific chemistry input values. Generic pretreatment Madison Fm. scenario, no transportation, storage or disposal included.

Figure 6b. Mean pretreatment costs effects in WTM for various input chemistries, including Madison Fm., seawater, and two brine examples.

Organic Pretreatment

Organic pretreatment costs can be significant with respect to overall treatment costs. Figure 7 shows a comparison between a Teapot Dome base case (Table 1) without organic pretreatment (left chart), and with organic pretreatment (right chart). Without pretreatment, costs for membrane desalination range from $\$0.45/\text{m}^3$ to $\$13/\text{m}^3$, and is primarily dependent upon the concentrate disposal method chosen by the model. The addition of organic pretreatments increases the range of potential costs for both membrane treatments (shown below the 45°C source water temperature cutoff) and thermal methods ($>45^\circ\text{C}$). Costs increase up to $\$17/\text{m}^3$ for membrane methods, and up to $\$12/\text{m}^3$ for thermal methods in the most extreme

scenarios. Median costs for treatment including organic pretreatments were found to be \$2.33/m³ (S.D. ±1.138, n=297) for membrane methods, and \$3.10/m³ (S.D. ±1.08, n=203) for thermal methods, without additional disposal costs.

Figure 7. Effect of no organic pretreatment (left) versus adding organic pretreatment (right) to overall costs for a Teapot Dome case, shown versus source water temperature (°C) and plotted for four concentrate disposal methods.

DISCUSSION

Energy use and recovery

For thermal treatment methods, the cost of energy is included as electricity for pumping, and as thermal heat for evaporative effects. Specific electricity costs are lower for thermal methods than for RO, because only low-pressure pumping is needed. The WTM thermal electrical using estimations of the fraction of total electricity costs compare well with costs calculated by the DEEP model (Table 4).

Energy recovery is now a standard for all newer RO systems. The WTM calculates a greater energy savings (cost reduction) for each of the energy recovery methods than does the DEEP model. The wide variation in specific costs indicates that the WTM methodology may estimate larger savings via energy recovery; this is device-dependent and based upon manufacturers reported savings.

Transportation-model comparisons and importance analysis

Within WTM, truck transportation costs are based on a fixed cost/volume; the only variation is in transportation distance. No economy of scale occurs with truck transportation. Here, stochastic variation from distances describes the deviation from the mean. Pipelines enjoy steep cost reductions through economics of scale; broadly, pipeline construction costs are linearly related to pipe diameter whereas flow in the pipeline increases exponentially [42].

The DEEP transportation costs compare well with the WTM costs when no transportation is included, and at higher Q values ($>4,000 \text{ m}^3/\text{d}$) (Figure 5). However, deviation from the WTM results reached 5 times the costs at lower flow rates. This cost effect far exceeds the economy of scale evident in the no-transportation case calculated by DEEP. This is likely because dividing overall treatment costs by smaller flow volumes in the DEEP spreadsheet increases the relative effect of the transport percentage. A similar effect has been observed in some WTM simulations. The DEEP results compare well with the WTM cost calculation methods for no-transport and higher-volume transport scenarios. DEEP may overestimate transportation costs per volume at low volumes.

We used WTM to evaluate the relative importance of the two types of transportation versus other stochastic inputs for the fixed-salinity base case (Madison Fm., TDS~14,000 mg/L, Figure 8). Four disposal scenarios were selected by the model. Base-case inputs considered were pretreatment costs including acid and antiscalent, feed temperature, feed pH, and concentrate disposal costs arrayed by concentrate disposal method. Disposal method is an important consideration related to transportation, because concentrate disposal is almost always needed, and because appropriate concentrate disposal may not exist at the treatment site, implying a dependence upon distance to a disposal location. Note that for all importance analyses the y-axis refers to cost importance.

Figure 8. Importance analysis comparison of pipeline (left) and truck (right) transportation versus other WTM stochastic parameters. Conditions include TDS= 14,000 mg/L; T= 15-45°C for RO, 45-65°C for thermal methods. Disposal conditions do not include Class II well option for simplicity.

For pipeline transportation, feed temperature was the most important factor related to costs, followed by transportation distance. Feed temperature controls the selection of treatment method in WTM. Thermal methods are selected at high temperatures $>45^{\circ}\text{C}$ because of potential damage to RO or NF membranes. Higher temperature feed also implies cost savings for thermal methods. The combination of these factors indicates that it is worth locating thermal treatment facilities closer to hot water sources, where heat can be better conserved and used in treatment, regardless of the distance to permeate use and concentrate disposal locations. For truck transportation, a greater importance is placed on distance than on feed temperature. If truck transportation is used, reducing distances between source, treatment, and use is critical to cost management, with a lower priority on thermal treatment methods.

In a second analysis, we include only one disposal method (Class I well) for simplicity, but include both tank and pond storage options (Figure 9). When truck transportation is used, distance remains the most important contributor to costs; pond storage is second followed by feed temperature. Pond storage is most important when pipeline transport is used. At high volumes, and for more permanent installations, pond storage is usually necessary. If combined with truck transportation, we see that treatment location, volume, and storage may combine to dominate a cost profile regardless of treatment method or even economies of scale. Interestingly, we found that pond storage tended to be more expensive on a per volume basis than transport costs ($\$3.00/\text{m}^3$ to store vs $\$1.24/\text{m}^3$ to transport); however, the cost of transportation by truck has a higher standard deviation per volume and thus exerts more influence on overall cost variation.

Figure 9. Importance analysis comparing WTM stochastic inputs for three different water chemistry

cases. Class I well disposal was selected for simplicity of comparison. Pipeline transportation is shown on left, truck transportation on right. Generic and scaling calculations refer to pretreatment scenarios.

Inorganic Pretreatment Effects on Costs

Brines (waters with salinities greater than seawater) can be expected to have complex geochemistry [11], and, thus, more complex or expensive pretreatment processes will be needed to prevent formation of mineral scale. This is particularly true for membrane processes; but also is possible for thermal treatments of inland (non-marine) waters. The WTM is designed to consider the basic inorganic geochemistry of a water sample when calculating pretreatment costs. Figure 6b illustrates the effects of complex geochemistry on the cost model. The least-cost geochemistry (seawater) converges with the DEEP model, validating the treatment assumptions at higher volumes. At lower volumes, DEEP estimates higher costs/volume. This is driven partially by the cost calculations in DEEP but also by division by smaller volumes.

Figure 10 shows an importance analysis for four cases (Madison Fm. brackish water, seawater, and two brines, Table 1). We included Class I well disposal, pipeline transportation, and storage options, but not produced water or class II well disposal. Figure 10 (left) compares all of the stochastic process results. Pond storage is clearly the most significant contributor to cost variance, followed by feed temperature. Given this result, we conclude that volume management is a critical feature of these systems. Figure 10 (right) shows the comparison without storage included. Among the remaining variables, feed temperature contributes the most to variance for the lower salinity samples. Temperature figures into the cost calculations in the WTM in two places: scaling factor calculations that determine additive (antiscalent and acid) costs, and as the determining factor separating membrane treatments from thermal treatments. Thermal treatments tend to cost more in terms of energy used, but have less cost from pretreatment. We note that Brine 2 costs are more dependent upon distance, acid cost rates, and disposal rates, factors related to the higher scaling potential of that brine fluid chemistry [2].

Class I Well importance analysis for 4 chemistry cases

Class I Well importance analysis for 4 chemistry cases

Figure 10. Importance analysis for several different water chemistries, including two brine samples. For simplicity, produced water options were not included, and Class I well disposal was chosen. Waters are from Table 1.

Effects of organic pretreatment on overall costs

While specific concentration and chemistry data and subsequent rigorous engineering design specifications are the most desirable scenario for understanding organic pretreatment costs, our interpretation of the literature ranges for an unconstrained system indicates that these costs can be estimated for a generalized case, and can create a significant influence on overall costs. This analysis is particularly important for source waters that originate from EOR or from “uneconomic” brackish and saline reservoirs (where residual organics, but not economically recoverable hydrocarbons, exist). An importance analysis of organic pretreatment costs versus other stochastic variables is shown in Figure 11. We used produced water as the water type for this analysis because EOR waters are regulated and handled as produced water. When organic pretreatment is added to a base case scenario, these costs became more important to the total cost profile than feed temperature and concentrate disposal costs, except for Class II well concentrate disposal cases. Because of regulation, produced water concentrate disposal in the WTM is limited to evaporation pond, zero-liquid discharge, or a Class II well. Because Class II well disposal has a very wide range of potential costs in the literature (from $< \$0.01$ to $> \$10.00/\text{m}^3$), this disposal method remains a large contributor to costs and to cost variance regardless of other contributors to treatment costs [43, 44]. Otherwise, feed temperature is the secondary cost variance driver. Modeling waters that are not defined as “produced” for the purposes of the model will result in much lower variance in the concentrate disposal parameter.

Figure 11. Importance analysis of stochastic parameters used to calculate a Teapot Dome base case (left, no organic pretreatment) and a case with organic pretreatment (right).

We also considered the importance of organic pretreatment in relation to transportation and storage in an EOR scenario (Produced water type, Class II well disposal, organic pretreatment included). There is a large potential for cost divergence from the base case (non-EOR). This is illustrated in Figure 12, where organic pretreatment and concentrate disposal change importance relative to feed temperature and pond storage costs. In figure 9 (left side), we show the truck transportation variant of this scenario. We note that storage, transportation to disposal sites, and concentrate disposal cost estimation is complex and volume dependent. The comparisons illustrate the tradeoffs that may need to be considered when analyzing cost scenarios that include transportation, disposal, and storage for EOR or produced waters.

Figure 12. Comparison of importance cases from Figure 9 (Madison Fm. pipeline transport case) with the same case treated as an EOR (produced) water type. Generic and scaling calculation refers to pretreatment scenario.

Conclusions

Water treatment is becoming a significant contributor to costs for energy production and extraction. There is significant potential for extracted water treatment processes and costs to be poorly understood and underestimated utilizing current models. Comprehensive system analysis models can reduce the potential risk of ignoring significant costs related to treatment and transportation. The WTM includes both primary and secondary processes in a treatment train that can be used to show the interconnections between process choices and costs, specifically for underestimated parameters like organic pretreatments, transportation, and storage. Monte Carlo capabilities and sensitivity analysis allow the user to better understand tradeoffs when planning for treatment of waters that are not similar to seawater, and in cases where specific site chemistry data are not available.

Acknowledgement

This work was funded by the US DOE's Office of Fossil Energy through the National Energy Technology Laboratory's Carbon Sequestration Program. We acknowledge the review by Richard S. Middleton and two anonymous reviewers.

List of Tables

Table 1. Water quality scenarios, input and output data, and criteria used for model simulations.

Table 2. Comparison of DEEP and WTM model features.

488 Table 3. DEEP and WTM parameters chosen for verification scenarios.

489 Table 4. Comparison of electricity costs per volume of water treated.

490

491 List of Figures

492 Figure 1. Schematic of Water Treatment Module. Top: Pretreatment phases. Bottom: Treatment and post-
493 treatment phases. Transportation segments are designated as X1, X2, and X3. Pretreatments are defined as
494 generic (source water chemistry unknown, generic cost applied), or specific (chemistry known and input
495 by user, specific costs applied).

496 Figure 2. Simple transportation model.

497 Figure 3. Literature cost ranges of various organic pretreatment methods ($\diamond$ are medians) (left), and an
498 example truncated probability curve as a solution to wide variations and site specificity in organic
499 pretreatment costs (right).

500 Figure 4a. WTM vs. DEEP model results for RO and thermal (MED and MSF) treatment cost analysis of
501 Madison Fm. chemistry. Costs from the WTM are: 1) total costs excluding transport and storage cost; 2)
502 energy costs alone without additional energy recovery, and 3) energy costs with recovery methods (Pelton
503 Turbine and Piston Isobaric). “Generic” refers to pretreatment type; salinities are listed for each scenario.

504 Figure 4b. WTM vs. DEEP for seawater, cost comparisons for RO treatment. Costs from the WTM are:
505 1) total costs excluding transport and storage cost; 2) energy costs alone without additional energy
506 recovery, and 3) energy costs with energy recovery methods (Pelton Turbine and Piston Isobaric).
507 Generic refers to pretreatment type.

508 Figure 5. Sensitivity of DEEP (left) and WTM (right) to transportation choices for the Madison Fm.,
509 generic pretreatment case. Conditions include TDS= 14,000 mg/L; T= 15-45°C for RO, 45-65°C for
510 thermal treatments.

511 Figure 6a. Sensitivity of DEEP model to pretreatment cost variations. DEEP is dependent upon user cost
512 input, WTM depends upon specific chemistry input values. Generic pretreatment Madison Fm. scenario,
513 no transportation, storage or disposal included.

514 Figure 6b. Mean pretreatment costs effects in WTM for various input chemistries, including Madison
515 Fm., seawater, and two brine examples.

516 Figure 7. Effect of no organic pretreatment (left) versus adding organic pretreatment (right) to overall
517 costs for a Teapot Dome case, shown versus source water temperature (°C) and plotted for four
518 concentrate disposal methods.

519 Figure 8. Importance analysis comparison of pipeline (left) and truck (right) transportation versus other
520 WTM stochastic parameters. Conditions include TDS= 14,000 mg/L; T= 15-45°C for RO, 45-65°C for
521 thermal methods. Disposal conditions do not include Class II well option for simplicity.

Figure 9. Importance analysis comparing WTM stochastic inputs for three different water chemistry cases. Class I well disposal was selected for simplicity of comparison. Pipeline transportation is shown on left, truck transportation on right. Generic and scaling calculations refer to pretreatment scenarios.

Figure 10. Importance analysis for several different water chemistries, including two brine samples. For simplicity, produced water options were not included, and Class I well disposal was chosen. Waters are from Table 1.

Figure 11. Importance analysis of stochastic parameters used to calculate a Teapot Dome base case (left, no organic pretreatment) and a case with organic pretreatment (right). Note, median cost for activated carbon is the median chosen for modeling scenarios in this paper. Low values reflect changes in costs over time as systems become more efficient.

Figure 12. Comparison of importance cases from Figure 9 (Madison Fm. pipeline transport case) with the same case treated as an EOR (produced) water type. Generic and scaling calculation refers to pretreatment scenario.

REFERENCES

1. Middleton, R.S., et al., *The cross-scale science of CO₂ capture and storage: from pore scale to regional scale*. Energy & Environmental Science, 2012.
2. Klapperich, R.J., et al., *IEAGHG, "Extraction of Formation Water from CO₂ Storage"*. 2012, IEAGHG: Cheltenham, GLOS, United Kingdom.
3. Attallah, M.F., et al., *Comparative study on the radioactivity of TE-NORM in different components of oil separator tanks*. Radiochimica Acta, 2013. **101**: p. 57-65.
4. Fakhru'l-Razi, A., et al., *Review of technologies for oil and gas produced water treatment*. Journal of Hazardous Materials, 2009. **170**(2-3): p. 530-551.
5. Mickley, M.C., *Membrane Concentrate and Disposal: Practices and Regulation*, 2nd Ed. 2006, U.S. Bureau of Reclamation: Denver, CO. p. 312.
6. Kobos, P.H., et al., *Combining power plant water needs and carbon dioxide storage using saline formations: Implications for carbon dioxide and water management policies*. International Journal of Greenhouse Gas Control, 2011. **5**(4): p. 899-910.
7. Sullivan, E.J., et al., *A method and cost model for treatment of water extracted during geologic CO₂ storage*. International Journal of Greenhouse Gas Control, 2013. **12**: p. 372-381.
8. Fritzmann, C., et al., *State-of-the-art of reverse osmosis desalination*. Desalination, 2007. **216**(1-3): p. 1-76.
9. Campos, C., *The Economics of Desalination for Various Uses*, C. Campos, Editor. 2013, "CETaqua Water Technology Center".
10. Greenlee, L.F., et al., *Reverse osmosis desalination: Water sources, technology, and today's challenges*. Water Research, 2009. **43**(9): p. 2317-2348.
11. Bourcier, W.L., et al., *A preliminary cost and engineering estimate for desalinating produced formation water associated with carbon dioxide capture and storage*. International Journal of Greenhouse Gas Control, 2011. **5**(5): p. 1319-1328.
12. Wolery, T.J., et al., *Fresh Water Generation from Aquifer-Pressured Carbon Storage: Annual Report FY09*. 2009, Lawrence Livermore National Laboratory: Livermore, Ca. p. 1-46.

13. Buscheck, T.A., et al., *Combining brine extraction, desalination, and residual-brine reinjection with CO₂ storage in saline formations: Implications for pressure management, capacity, and risk mitigation*. Energy Procedia, 2011. **4**: p. 4283-4290.
14. Dahm, K.G., et al., *Composite Geochemical Database for Coalbed Methane Produced Water Quality in the Rocky Mountain Region*. Environmental Science & Technology, 2011. **45**(18): p. 7655-7663.
15. IAEA, *Desalination Economic Evaluation Program (DEEP)*. 2011, International Atomic Energy Agency.
16. *Desalination: A National Perspective*. 2008, The National Academies Press: Washington, DC.
17. Georgopoulou, E., et al., *A methodology to investigate brackish groundwater desalination coupled with aquifer recharge by treated wastewater as an alternative strategy for water supply in Mediterranean areas*. Desalination, 2001. **136**(1-3): p. 307-315.
18. Pankratz, T.M., *Advances in Desalination Technology*. Int. J. Nuclear Desalination, 2005. **1**(4): p. 450-455.
19. Ebrahim, S.H., M.M. Abdel-Jawad, and M. Safar, *Conventional pretreatment system for the Doha Reverse Osmosis Plant: Technical and economic assessment*. Desalination, 1995. **102**(1-3): p. 179-187.
20. El-Manharawy, S. and A. Hafez, *A new chemical classification system of natural waters for desalination and other industrial uses*. Desalination, 2003. **156**: p. 163-180.
21. EPA, U.S. *Federal Underground Injection Control (UIC) Class VI Program for Carbon Dioxide (CO₂) Geologic Sequestration (GS) Wells* 2011 07/29/2014]; Available from: <https://www.federalregister.gov/articles/2011/09/15/2011-23662/announcement-of-federal-underground-injection-control-uic-class-vi-program-for-carbon-dioxide-co2>.
22. Aines, R.D., et al., *Fresh water generation from aquifer-pressured carbon storage: Feasibility of treating saline formation waters*. Energy Procedia, 2011. **4**: p. 2269-2276.
23. Millero, F.J., K. Lee, and M. Roche, *Distribution of alkalinity in the surface waters of the major oceans*. Marine Chemistry, 1998. **60**(1-2): p. 111-130.
24. Collins, A.G., *Geochemistry of Oilfield Waters*. Developments in Petroleum Science, 1. 1975, New York: Elsevier. 496.
25. Tibbetts, P.J.C., et al., *A comprehensive determination of produced water composition*, in *Produced Water*, J.P. Ray and F.R. Engelhardt, Editors. 1992, Plenum Press: New York.
26. Dow_Chemical. [cited 2013 01/07/2013]; Feed Water Quality Guidelines for Dow Filmtec Membranes]. Available from: https://dow-answer.custhelp.com/app/answers/detail/a_id/3170/~/_filmtec-membranes---feed-water-quality-guidelines.
27. Shaffer, D.L., et al., *Desalination and Reuse of High-Salinity Shale Gas Produced Water: Drivers, Technologies, and Future Directions*. Environmental Science & Technology, 2013. **47**(17): p. 9569-9583.
28. Das, N., R. Vimala, and P. Karthika, *Biosorption of heavy metals - An overview*. Indian Journal of Biotechnology, 2008. **7**(2): p. 159-169.
29. Coşkun, T., E. Debik, and N.M. Demir, *Operational Cost Comparison of Several Pre-Treatment Techniques for OMW Treatment*. CLEAN – Soil, Air, Water, 2012. **40**(1): p. 95-99.
30. NETL. *National Carbon Sequestration Database and Geographic Information System (NATCARB)*. accessed 02/28/2012; Available from: http://www.netl.doe.gov/technologies/carbon_seq/natcarb/index.html.
31. Neff, J.M. and S. Stout, *Predictors of Water-soluble Organics (WSOs) in Produced Water-A Literature Review*, in *Regulatory and Scientific Affairs*. 2002, American Petroleum Institute: Washington, DC. p. 23.

32. Kruithof, J.C., P.C. Kamp, and B.J. Martijn, *UV/H₂O₂ treatment: A practical solution for organic contaminant control and primary disinfection*. Ozone: Science and Engineering, 2007. **29**(4): p. 273-280.
33. Hickey, R., T. Hayes, and G. Mazewski, *Innovative bioreactor offers cleanup option for petroleum-contaminated wastes*. Environmental Solutions. **7**(6): p. 73-74.
34. Ranck, J.M., et al., *BTEX Removal from Produced Water Using Surfactant-Modified Zeolite*. Journal of Environmental Engineering, 2005. **131**(3): p. 434-442.
35. AACEI, *AACE RP 18R-97 Cost Estimate Classification System-as applied in Engineering Procurement and Construction for the Process Industry*. 2011, AACEI_American Association for Cost Estimating International.
36. GoldSim_Technology_Group, *GoldSim Probabilistic Simulation Environment User's Guide, Version 11.1. Volumes 1 and 2*. 2014, GoldSim Technology Group LLC: Issaquah, Washington.
37. Smith, M.S., et al., *Baseline geochemical characterization of potential receiving reservoirs for carbon dioxide in the Greater Green River Basin, Wyoming*. Rocky Mountain Geology, 2010. **45**(2): p. 93-111.
38. Burtner, R.L., *Origin and evolution of Weber and Tensleep Formation waters in the greater Green River and Uinta-Piceance basins, northern Rocky Mountain Area, U.S.A.* Chemical Geology (Isotope Geoscience Section), 1987. **65**: p. 255-282.
39. Gorder, P.J., *Development of Brackish Groundwater as a Sustainable Supply to Support Growth and Military Base Expansion in El Paso-The Kay Bailey Hutchison Desalination Facilities Project- El Paso Water Utilities*, in 2009 9th Annual National Salinity Summit, Las Vegas, Nevada. 2009.
40. Wetterau, G., *Cost Trends in Desalination*, in *Border Governor's Binational Desalination Conference*. 2010: El Paso, TX.
41. Borsani, R. and S. Rebagliati, *Fundamentals and costing of MSF desalination plants and comparison with other technologies*. Desalination, 2005. **182**(1-3): p. 29-37.
42. Middleton, R.S., *A new optimization approach to energy network modeling: anthropogenic CO₂ capture coupled with enhanced oil recovery*. International Journal of Energy Research, 2013. **37**(14): p. 1794-1810.
43. Acharya, H.R., et al., *Cost Effective Recovery of Low-TDS Frac Flowback Water for Re-use*. 2011, United States Department of Energy, National Energy Technology Laboratory: Morgantown, West Virginia. p. 100.
44. Boysen, D., et al., *Produced Water Management Handbook*. 2003, Gas Technology Institute. p. 1-74.