Numerical Analysis of Cyclic CH₄ Injection in Liquid-rich Shale Reservoirs Based on the Experiments Using Different-diameter Shale Cores and Crude Oil

Lei Li and James J. Sheng

Texas Tech University, Lubbock, Texas, USA

*Corresponding author: james.sheng@ttu.edu, [Tel:806 834 8477](tel:8068348477)

ABSTRACT

In this paper, the potential to enhance oil recovery (EOR) by CH₄ gas injection in shale reservoirs is investigated through numerical analysis based on the experiments using different-diameter shale cores and crude oil. The cores used in these experiments had the same length of 2 inches and six different diameters of 1, 1.5, 2, 3, 3.5 and 4 inches. The crude oil from Wolfcamp was used to saturate the shale core plugs. A Gas Chromatography/Mass Spectrometer (GC/MS) instrument and Xcalibur software were used to analyze the crude oil components.

The experiments were history-matched using numerical simulation models. The calibrated numerical models were then employed to perform a series of sensitivity studies to investigate the effects of operation parameters on oil recovery in shale oil cores, such as the number of injection cycles, molecular diffusion, soaking time, and operation schedule. The experimental results show that oil recovery factor is smaller from a larger core than that from a smaller core due to the decline of surface area per volume and the drop of pressure gradient along the diameter. The simulation results show that incremental oil recovery in each of the subsequent cycle decreases as the number of injection cycles increases. In terms of EOR mechanisms, viscous displacement and relative permeability hysteresis may be important, while molecular diffusion does not seem to play an important role after the first five cycles. For the soaking time, a larger core needs a longer soaking time to achieve the maximized oil recovery than a smaller core within a single cycle. Within a fixed elapse time, a shorter soaking time results in higher oil recovery. This work provides a fundamental understanding of the key parameters that control cyclic CH₄ injection to enhance oil recovery in shale rocks.

1. Introduction

Shale oil production has been gaining worldwide attention over the past several years. The combination of horizontal well and hydraulic fracturing technologies made it possible to produce shale gas economically (Yuan and Wood, 2015). In recent years, cyclic gas injection, which avoids fingering between connected wells, has been proven to be an effective recovery method to enhance oil recovery in laboratory experiments (Wan et al., 2015; Meng et al., 2016; Meng and Sheng, 2016) and simulation for shale oil production (Sheng, 2015, 2015b; Wan and Sheng, 2015a, 2015b, 2015c; Wan et al., 2016). The production increase is achieved by the sufficient energy provided from injection gas and the oil viscosity decrease. Cyclic gas injection (huff-n-puff is also one kind of cyclic gas injection) to enhance oil recovery has been used in conventional reservoirs in a number of experimental and field studies. Monger and Coma (1988) discussed cyclic CO₂ injection for light oil recovery and found cyclic CO₂ injection would be an economical method to recover additional incremental oil. Then Haines and Monger (1990) examined the feasibility of cyclic natural gas injection for enhanced recovery of light oil from waterflooded fields, and their results showed that approximately 40% of waterflood residual oil was

recovered in core flooding using two injection cycles. Wang et al. (2013) used 6 cyclic coreflood tests, 20 cycles in a 973 mm-long composite core to optimize cyclic CO₂ injection in low-pressure and low-permeability oil reservoirs. Their results show that the optimal operation should have three cycles, and the ultimate recovery factor for these three cycles could reach above 30%. Gamadi et al. (2013) claimed that cyclic gas (N₂ or CO₂) injection could increase the oil recovery from 10% to 50% in the laboratory study of shale cores depending on the injection pressure. In terms of cyclic gas injection simulation, Hsu and Brugman (1986) used a compositional reservoir simulator to simulate CO₂ huff-n-puff process in a light oil reservoir. They validated their model by history-matching the first two cycles' production data and making a prediction of the third cycle. Then they used this model to analyze the effects of the number of cycles, injection and soak time, injection solvent quantity and composition on oil recovery. They declared that soak time has little effect on oil recovery, while the quantity of injection solvents is the most important parameter. Liu et al. (2005) developed an EOS simulation to examine various oil recovery mechanisms for the CO₂ huff-n-puff process in conventional oil reservoirs, including swelling effect, viscosity reduction, relative permeability effect, miscibility effect, and gas solubility. They claimed that EOS simulation is a useful tool for evaluating gas huff-n-puff processes both in the design stage and in production optimization. Wan et al. (2013) were the first to conduct simulation modeling of cyclic gas injection in shale oil reservoir. They showed that total oil recovery can be increased up to 29% by cyclic gas (77% C1, 20% C2, 3% C6) injection in a hydraulically fractured shale reservoir, compared with the initial 6.5% recovery from the primary depletion in the simulation results. Yu et al. (2014) built a numerical fracture model to simulate CO₂ huff-n-puff in Bakken tight oil reservoirs. They compared the CO₂ flooding in two horizontal wells and CO₂ huff-n-puff in a horizontal well and did a sensitivity study. They claimed that the most important parameter is CO₂ injection rate, followed by CO₂ injection time, the number of cycles, and CO₂ diffusivity.

The gas can be used in cyclic injection including N₂, CO₂, CH₄ and other light hydrocarbon mixture. Gamadi et al. (2014a) conducted experiments to evaluate the potential of cyclic CO₂ injection and proved it could enhance oil recovery significantly in the Eagle Ford cores. While in oil field production, sometimes it is difficult to employ CO₂ in certain circumstances due to transport, economic or corrosion problems. Other gasses, such as N₂ and CH₄, come to the mind of scholars. Compared with CO₂, CH₄ is a more easily available gas in the oil field after separating gas from the produced oil. Shayegi et al. (1996) presented the results of laboratory investigations of cyclic gas injection process using CH₄, N₂ and mixtures of these gases with CO₂ in immiscible condition in consolidated sandstone cores with waterflood residual oil. He declared that pure CH₄ recovered approximately the same amount of waterflood residual oil as CO₂, whereas pure N₂ recovered about half that amount. Zhang et al. (2006) did a laboratory investigation of enhanced light-oil recovery by CO₂ / flue gas huff-n-puff process and proved that enriched flue gas performed as well as or better than pure carbon dioxide. Ivory et al. (2010) studied cyclic solvent injection using a solvent mixture (e.g., CH₄/propane) injected to heavy-oil reservoirs and the oil recovery after primary production and six solvent cycles was 50%, which was much higher than 5-10% from the cold production.

This study targets cyclic CH₄ injection in shale rock cores. Cyclic N₂ and CO₂ injection have been studied by several authors, but there were fewer experiments on cyclic CH₄ injection. The effects of operation parameters on oil recovery during cyclic CH₄ injection are also not discussed in previous literature. In our experiments, we used CH₄ as the gas resource and crude oil from Wolfcamp for core saturation. The composition of crude oil was analyzed using GC/MS. In the numerical study, the compositional

simulation model is validated with oil recovery data from our laboratory experiments. After that, a series of sensitivity study were performed to explore the efficiency of operation parameters on shale oil EOR such as the number of injection cycles, core sizes, soaking time, molecular diffusion, injection pressure, soaking pressure and operation schedules. The main purpose of this paper is to analyze cyclic CH_4 injection and provide a fundamental understanding of the key parameters that control cyclic CH_4 injection EOR in shale rocks.

2. Experimental methods

2.1. Experimental materials

The materials included crude oil and cores from the Wolfcamp formation in Apache's Lin field, six shale oil cores of the same length of 2 inches but different dimensions in diameters with 1, 1.5, 2, 3, 3.5 and 4 inches, respectively. The measured average helium porosity was 6% - 8% and the nitrogen permeability ranges 300 nD to 500 nD. The original pressure of the CH_4 gas (purity of > 99%) is 2500 psi.

2.2. Experimental equipment

The main experimental flows for core saturation and cyclic CH_4 injection are shown in **Fig. 1** and **Fig. 2**.

Fig. 1. Schematic diagram of the experimental equipment for oil saturation.

Fig. 2. Schematic diagram of the experimental equipment for cyclic gas injection.

Quizix QX pump is a syringe pump with two cylinders and it can pump fluids continuously. Cores were placed vertically in the high-pressure stainless steel core container, which were connected with two-way valves. The pressure gauge is placed directly on the top of the stainless core container to record the pressure around the core throughout the injection stage, soaking period and pressure depletion time in each experiment. A pressure regulator is connected to the CH_4 cylinder to control the gas injection pressure. The syringe pump is used as a pressure boost to maintain the designed pressure inside the core container. All the experiments were conducted at the temperature of 95°F in the temperature controllable oven.

2.3. Experimental procedure - core saturation and cyclic CH_4 injection

Due to the extremely low permeability of shale cores, the traditional saturation method for conventional reservoir cores is not suitable in these experiments. In this study, the same saturation method as applied in our previous experiments were used (Li et al., 2015, 2016, Li and Sheng, 2016). The procedures are shown as following:

Core saturation experimental procedure:

1. Core samples were named and dry weighted (W_d) after putting in the oven for one day.
2. As shown in Fig. 1, a core sample was placed in the core container, then vacuumed for three days.
3. Turn off the vacuum pump and close valve V1. Open valves V2 to V4, then water can be displaced to the bottom of the accumulator using the Quizix QX pump. Then crude oil in the top of the accumulator was pumped into the vessel by the force transient from the bottom water.
4. After the core was completely soaked with crude oil, a certain pressure of 2,000 psi was maintained in the vessel for 5 days.

Saturated oil weight in each core was calculated using the difference between the core dry weight (W_d) and saturated weight (W_s). After saturation, the core sample was put into a core container in the oven and the cyclic CH_4 injection process started.

Cyclic CH_4 injection procedure:

1. Put the saturated core into the core container in the oven (with a constant temperature of 95 °F) as shown in Fig. 2. CH₄ was injected into the core container. Shut in the well when the pressure gauge showed 2,000 psi.
2. A certain period of soaking time was maintained to allow CH₄ to dissolve into the oil.
3. After soak period finished, release the internal pressure to the atmosphere pressure of 14.7psi.
4. Wait for 6 hours until the core weight will not change, weigh and record the core sample again as W_i .
5. The second cycle of gas injection was carried immediately after the first cycle and a third cycle conducted after the second one, and so on.

The same procedures repeated in subsequent cycles use the similar manner to the first one. Each sample was weighed and recorded after each cycle to calculate the oil recovery with its weight differences using the following equation.

$$\text{Accumulative Oil Recovery in cycle } i = \frac{W_s - W_i}{W_s - W_d} \times 100\% \quad (1)$$

The choice of the temperature (95 °F) is based upon the consideration of the feasibility and accuracy of the experiments. As shown in equation (1), the oil recovery is calculated by measuring the weight differences in a room temperature after each injection cycles. The minimum temperature the oven can maintain is 95 °F. We also need to avoid the damage of the core caused by a rapid change of temperature. The experiment injection pressure is chosen after considering the safety factor and experiment equipment capability. After analyzing other researchers' work in shale cores (Gamadi et al., 2013, 2014a, 2014b; Meng and Sheng, 2016; Yu et al., 2016), the choice of pressure 2000 psi is a feasible pressure and can be used to test the effectiveness of gas cyclic injection EOR in shale oil cores.

2.4. Experimental results and discussion

Table 1 includes the recovery factors of cyclic CH₄ injection for shale cores at different core sizes with the same length of 2 inches and different diameters of 1, 1.5, 2, 3, 3.5 and 4 inches. **Fig. 3** displays the experiment results that under the same operating situation (injection pressure 2000psi), the core with a bigger diameter had a lower oil recovery in the same injection cycle. The most important factor is the surface area per unit volume, as calculated by

$$\text{Surface area per unit volume} = \frac{\text{Outer surface area of the core}}{\text{Volume of the core}}$$

With more surface area connected with gas and higher pressure gradient, more oil recovery will be achieved in the smaller diameter core. Focused on one core, we can see the incremental oil in one cycle will decrease as the increases of the number of injection cycles. The oil near the surface of the core is easily and firstly produced owing to the high pressure gradient and oil saturation gradient. More details will be discussed in the simulation study in the later part of this paper. This experiment result that higher oil recovery in smaller diameter cores is in line with the expectations. In reservoir development, more fracture stages lead to smaller matrix volume, then more oil will be produced.

Table 1.

Oil recovery data in gas injection cycles with different core diameters.

Core No.	Diameters, inches	Surface area per unit volume, ft ² /ft ³	Cycle 1	Cycle 2	Cycle 3	Cycle 4	Cycle 5
1	1	24	12.63%	20.84%	29.11%	35.41%	40.07%
2	1.5	16	11.26%	19.73%	27.34%	33.58%	39.17%
3	2	12	10.53%	18.58%	25.90%	32.86%	38.34%
9	3	8	9.77%	16.31%	24.23%	30.92%	36.08%

10	3.5	6.9	9.34%	15.52%	23.14%	28.97%	33.79%
11	4	6	8.62%	14.46%	21.15%	27.69%	32.31%

Fig. 3. R.F. data of different diameter cores for 5 injection cycles under the conditions of 2000psi with crude oil and CH₄ injection.

3. Numerical simulation section

In order to further investigate the effect of operation parameters during cyclic CH₄ injection process in different size shale oil cores, numerical simulation is applied to match the oil recovery data in the experiments. Compositional model of a clean crude dead oil sample is built by using CMG Winprop module according to oil compositions analyzed by GC, as described below. The simulation model is built and optimized by using the CMG-GEM simulator. Relative permeability in numerical model is turned to match the experimental oil recovery factors.

3.1. Model build up

3.1.1. Crude oil composition analysis with GC/MS

A light crude oil from the Wolfcamp formation in Apache's Lin field was used in saturating the cores for the cyclic CH₄ injection experiments. At the laboratory temperature 20°C and pressure 14.7 psi, oil density is 0.81 g/cm³ and viscosity is 3.7 cp. In order to build the compositional simulation model, oil composition should be tested. GC/MS is an accurate method to measure and analyze the chemical characterization of different materials such as botany, medicine, essential oils, and crude oil. (Al-Thamir, 1985, Halket et al., 2005, Rubiolo et al., 2008, Hiller et al., 2009, Eshiet et al., 2014). In this study, Thermo Scientific Trace Ultra Gas Chromatograph equipped with FID measurements and Weight/Quadruple ISQ Mass Spectrometer were used to analyze the oil components. In this paper, Xcalibur software from Thermo Scientific was used to analyze this crude oil chromatogram. The crude oil mixture covered the components with boiling range from *n*-C3 to *n*-C42. In order to get the percent of each component, the mass spectrum needed to be separated and compared with all the hydrocarbons. The GC result for Wolfcamp crude oil show in **Fig. 4**. The mole fraction of different components in the crude oil is presented in **Table 2**.

Fig. 4. GC result for Wolfcamp crude oil.

Table 2.

Mole percent data of Wolfcamp dead oil.

Component	Percent	Component	Percent	Component	Percent
C3H8	0.009%	FC9	8.339%	FC21-22	2.268%
IC4	0.004%	FC10	8.336%	FC23-24	1.040%
NC4	0.005%	FC11-12	11.786%	FC25-26	1.727%
IC5	1.349%	FC13-14	9.413%	FC27-28	1.050%
NC5	1.349%	FC15-16	6.787%	FC29-30	0.501%
FC6	4.588%	FC17-18	4.940%	FC31-36	0.952%
FC7	10.684%	FC19	2.148%	FC37-40	0.937%
FC8	12.295%	FC20	1.284%	FC41+	8.210%

In GEM-CMG simulation, hydrocarbon component material balance equations need to be solved in every time step. The full compositional simulation with 24 components in the crude oil will definitely cause exhausting simulation run time. Hong (1982) did the simulation using 5 pseudo components and showed that it matched the laboratory-measured phase behavior data almost as accurately as the more complex 14 to 17 component models originally used in reservoir simulation. In our simulation, we lumped the original 24 components into 5 pseudo components, shown in **Table 3**, using WinProp-CMG. **Table 4** present the Peng-Robinson EOS fluid description of the Wolfcamp dead crude oil. Correlation coefficients should be fit to experimental data to validate that the lumping is reasonable. The Jossi-Stiel-Thodos (JST) viscosity correlations equation is used in this model (CMG Manual, 2014).

$$\left[(\mu - \mu^*)_{\xi} + 10^{-4} \right]^{0.25} = a_0 + a_1 \rho_r + a_2 \rho_r^2 + a_3 \rho_r^3 + a_4 \rho_r^4 \quad (2)$$

$$\rho_r = v_c \times v; \quad v_c = \left(\sum_{i=1}^{n_c} x_i v_{ci}^\alpha \right)^{1/\alpha} \quad (3)$$

$$\xi = T_c^{1/6} MW^{1/2} P_c^{2/3} \quad (4)$$

where, μ is phase viscosity, cp; μ^* is low-pressure fluid viscosity, cp, calculated internally from the Herning- Zipperer and Yoon-Thodos formulas; T_c is fluid pseudo-critical temperature, deg K; MW is fluid molecular weight, gm/gmol; P_c is fluid pseudo-critical pressure, atm; ρ_r is fluid reduce-molar density; v is fluid molar density, kmol/m³; x_i is the mole fraction of component i; v_c is critical volume, l/mol.

Table 3.

Wolfcamp crude oil components after lumping.

Component	C ₃₋₄	C ₅₋₈	C ₉₋₁₉	C ₂₀₋₄₀	C ₄₁₊
Percentage	0.018%	30.265%	51.748%	9.759%	8.21%

Table 4.

Peng-Robinson EOS fluid description of Wolfcamp crude oil after lumping.

Components	HC	Pc(atm)	Tc(K)	Accentric Fac.	MW	Vc(l/mol)	Vol.Shift
C ₁	1	45.4	190.6	0.008	16.043	0.099	-0.1595
C ₃₋₄	1	39.269	394.7228	0.1687	51.1105	0.230214	-0.07924
C ₅₋₈	1	29.8467	556.4605	0.3331	101.7772	0.402268	0.027859
C ₉₋₁₉	1	19.9401	692.5801	0.5833	185.1622	0.698281	0.128336
C ₂₀₋₄₀	1	11.4471	844.253	0.9918	352.9444	1.269132	0.225044
C ₄₁₊	1	7.8659	950.8726	1.2629	513.5156	1.797165	0.276248

3.1.2. Logarithmic refinement composition model

A radial coordinate model with two-dimensional radial cross section (r-z) and compositional reservoir simulator (CMG-GEM) are used to simulate the cyclic CH₄ injection experiment. The core container has a diameter of 2.4-inch and height of 5.6-inch. The surrounding annular volume between the container and core represents the fracture volume. Three faces of the core sample are open during the gas injection, soaking, and production stages. **Fig. 5** shows the process of the model build up. Firstly, the field-scale hydraulic fracturing model was simplified to the experiment model. The experiment study focused on only one branch of the hydraulic fracture (the matrix between two hydraulic fractures) shown in **Fig. 5 a**. The horizontal well and fractures are saturated with gas during the injection period. In the experiment study, the core was located in the center of the core container, and the volume between the core and the core container was fully saturated with methane when we conducted the experiments. Thus in **Fig. 5c** the core represents the matrix and the volume between the core and core container represents the fracture space according to the field-scale model. Based upon this simplification, the radial model in **Fig. 5 d** was built to simulate the process of our experiment. The radial model has 22 grid blocks in the r direction and 46 grid blocks in the z direction. In order to separate the output of shale matrix and the surrounding fracture, we divided the simulation domain into two sectors. The shale matrix is set as sector 1 covering grid blocks from 1 to 12 in the r direction and grid blocks from 31 to 46 in the z direction. The matrix permeability is assumed as 0.0005 milli-Darcy (mD). Fracture space with the permeability of 1000 mD is set as sector S2 includes the other grid blocks except sector S1. The changes of pressure, gas and oil

saturation are more sensitive at the matrix and fracture contact surface (the core surface in the laboratory experiment). Logarithmic refinement was used in the matrix-fracture contact surface to get more accurate results shown in **Fig. 5 e and f**. 2 wells (1 producer, and 1 injector) were used to simulate the cyclic gas injection process in the shale cores. The injection well is located at grid blocks (1, 1, 1) and (1, 1, 2) which means it perforated at layers 1 and 2 in the z direction. The injection well is constrained to the maximum injection pressure of 2000 psi and the maximum surface gas rate of 10 MSCF/day. The constraint will be automatically changed to the other one if either of the two is violated. The production well is located at grid blocks (1, 1, 3) and (1, 1, 4) meaning perforated at layers 3 and 4 and restrained to the minimum bottom-hole pressure of 14.7 psi. This setting makes it convenient to simulate the physical displacement process of the cyclic gas injection. The reservoir rock and fluid properties of the simulation model are shown in **Table 5**.

Fig. 5. Model build up process and radial simulation model with logarithmic refinement (legend is initial oil saturation).

Table 5.

Reservoir and fluid properties used in the simulation model.

Parameter	Value	Unit
Matrix permeability	0.0005	mD

Fracture permeability	1000	mD
Porosity	6	%
Total compressibility	1×10^{-6}	psi ⁻¹
Initial core pressure	14.7	psi
CH ₄ injection pressure	2000	psi
Injection time	0.01	day
Soaking time	1	day
Production time	0.01	day
Temperature	95	F

3.1.3. Model validation

The comparison of cases with totally 24 components and the lumped 5 components was shown in **Fig. 6**. The result validated that the fluid system with lumped 5 pseudo components can represent the original Wolfcamp oil fluid system when discussing the oil recovery in the simulation model.

Fig. 7 shows the result of grid refinement influence on oil recovery factor. A series of models with grids of 15, 22, 31, 41 and 50 respectively in the r direction and refined grids with 46 and 92 respectively in the z direction were tested to get the stable radial model. 22*1*46 model is producing similar results with more refined 50*1*92 grid blocks model, so the 22*1*46 model is stable to properly simulate the gas injection process. In this paper, the optimized 22*1*46 model was used in our further study.

Fig. 6. Effect of the lumped components on calculated oil recovery factor.

Fig. 7. Effect of the grid sensitivity on calculated oil recovery factor.

3.2. History Matching Experiments

After setting up the model, it is really important to validate the model with experiment data in order to make sure the simulation model is correct. The history match method used in this study is to tune the model input parameters including the shale matrix permeability, matrix porosity, fracture permeability within an acceptable range and adjust the relative permeability curves based upon the relative permeability curves generated in the previous shale oil reservoir simulation studies (Wan et al., 2013, 2015, 2016; Yu et al., 2014a, 2014b; Yu et al., 2016). The results for the oil recovery factor are shown in **Fig. 8**. A good agreement between the numerical simulation results and the actual experiment data is obtained for oil recovery, while a slight mismatch is found in the cycle 4 and cycle 5. This may be caused by the non-uniform distribution in different cores and the unavoidable experimental errors. The simulation model is used to further study other parameters during cyclic CH_4 injection in the following discussion. As mentioned previously, the oil-gas relative permeability curves were tuned for history match as presented in **Fig. 9**.

Table 6 shows the operation schedules in a CH_4 injection cycle. **Fig. 10** displays the oil saturation and pressure distribution changes in every grid block (from matrix center block to peripheral block covering the distance from 0 to 0.0625ft which represents the core radius) along the radial direction.

Fig. 8. History matching curves with experiment results.

Fig. 9. Oil-gas relative permeability curves for a reasonable history match.

Table 6.

Operational schedule in a cycle.

Time (days)	0-0.01	0.01-1	1-1.01	1.01-2
Operations	Injection time	Soak period	Production time	Further depletion

Fig. 10. Oil saturation and pressure distribution curve in different radial blocks (Take layer 40 in the axial direction and the fifth CH_4 injection cycle as an example, core diameter = 0.125 ft).

In this model, the fifth CH_4 injection cycle in the No. 40 layer along the axial direction in a core diameter of 1.5 inches was taken as an example. In **Fig. 10**, the solid lines represent oil saturation and dash lines stand for pressure, using the same color for oil saturation and pressure at the identical operation time. The red line with the round marker shows oil saturation distribution from the center block to the peripheral block after the fourth cycle. The pressure remains the minimum allowable bottom-hole pressure (BHP) (14.7 psi, the same as our experiment). The blue line with the square marker illustrates that as the CH_4 injection period started, injected CH_4 pushed oil from the peripheral block to the center of the core, the incremental oil saturation in the center block increased more rapidly than the peripheral blocks, which was occupied by the CH_4 gas. The pressure in the blocks increased to the injection gas pressure 2000 psi. The magenta line with the cross marker presents the oil saturation distribution after 0.01 days' (14.4 minutes) production time, which decreased a lot compared with the one after soak period. The pressure at this moment is denoted by the magenta dash line. The pressure in the fracture space dropped to the minimum BHP (14.7 psi), however, the pressure in the center shale core remained at 400 psi after depletion for 14.4 minutes which indicated that the pressure drawdown in the fracture space decreased at a higher rate than the tight shale cores. The pressure dropped to 14.4 psi for all the blocks after one day's further depletion, and the oil saturation in the blocks redistributed, as the brown dash line with the diamond marker shows. The oil saturation in the center block decreased, while the oil saturation in the peripheral block increased, which indicates that oil migrated from the center block to the fracture due to the pressure gradient and oil concentration difference. Overall, the oil saturation after the further depletion period (as the brown line with the diamond marker shows) decreased than the one at the end of production

time (as the magenta line with the cross marker indicated). It illustrates that there was considerable oil produced during the further depletion time. Compared with the red line and the brown line, the difference in the oil saturation represents the oil produced within cycle 5.

3.3. Sensitivity Analysis

3.3.1. Effect of injection cycles number

Table 7 illustrates the effect of the number of injection cycles on oil recovery factor with injection pressure of 2000 psi (1.5-inch diameter). The peak oil production in one cycle was 11.7% in the first cycle and then decreased with the increase of injection cycle number. The first 5 cycles' oil recovery were higher compared with the following cycles. After 8 cycles, the production rate increased only about 2% at each cycle until it equilibrated at an average of 57%. The results of oil saturation distribution in the radial direction in layer 40 are presented in **Fig. 11**. The change of oil saturation in the blocks shows that with the increase of the number of injection cycles, the oil saturation in the core declines. Oil saturation in the peripheral blocks reduced faster than that in the center blocks due to the high permeability difference and the high oil saturation gradient. The oil in the center blocks would transport to the peripheral blocks owing to convection and dispersion. The oil in the center blocks needs to overcome larger force than the oil in the peripheral blocks, also the pressure gradient is lower due to the long distance of central core to the fracture, which leads to lower incremental oil recovered in the latter cycle than that in the former cycle. The oil saturation gradient between the matrix and fracture decreases as the oil saturation inside the matrix reduces during the production process. Thus, the driving forces of convection and dispersion become lower than before. These contribute to the decline in incremental oil recovery.

Table 7.

Simulation results of cyclic CH₄ injection (injection pressure 2000 psi).

Core No.	1	2	3	9	10	11
Diameter, inches	1	1.5	2	3	3.5	4
Cycle 1	14.50%	11.70%	10.34%	8.79%	8.51%	7.97%
Cycle 2	23.11%	19.10%	17.37%	15.82%	15.40%	14.84%
Cycle 3	31.08%	26.90%	25.04%	23.74%	23.03%	22.14%
Cycle 4	37.85%	34.33%	32.58%	31.33%	30.48%	29.02%
Cycle 5	43.24%	40.35%	38.95%	37.81%	36.65%	35.43%
Cycle 6	47.41%	44.95%	43.80%	42.67%	41.48%	40.42%
Cycle 7	50.75%	48.57%	47.56%	47.15%	45.25%	44.14%
Cycle 8	53.45%	51.48%	50.55%	49.25%	48.23%	47.23%
Cycle 9	55.73%	53.90%	53.01%	51.67%	50.71%	49.73%
Cycle 10	57.66%	55.94%	55.08%	53.70%	52.77%	51.84%
Cycle 11	59.30%	57.71%	56.86%	55.44%	54.57%	53.66%

Fig. 11. Oil saturation distribution in the radial direction in layer 40 after saturation for No.2 core in different injection cycles (injection pressure 2000 psi and core diameter 1.5 inches).

3.3.2. Effect of diffusion

In order to investigate the role of molecular diffusion of CH₄ in EOR improvement in cyclic gas injection, we compared the simulation results of cyclic CH₄ injection with / without diffusion shows in **Fig. 12**. The molecular diffusion coefficients in the gas phase are calculated using the Sigmund (1976) correlation. Without taking diffusion into consideration, the principal driving mechanisms are pressure gradient (viscous displacement) and probably relative permeability hysteresis. In each cycle, the pressure difference is identical but the hysteresis could be different. Denoyelle and Lemonnier (1987) studied the gas relative permeability hysteresis in drainage-expansion cycles. They found when gas invades a porous medium (drainage, which is equivalent to injection period in our model), it forms a continuous phase and is immediately mobile, but when gas is formed within the oil phase during depletion, it exists as independent bubbles and moves only after a given critical saturation has been reached. The relative permeability hysteresis acts as a positive force when the oil saturation is relatively high. Because at this period gas is independent bubbles struggling to come out to the fracture region, which gives the oil an

additional driving force. Once the oil saturation declines to a certain saturation, the gas saturation in the matrix becomes higher. Then the gas will form a continuous phase and move out of matrix easily. Because we do not have such hysteresis, this effect is not included in this paper.

Fig. 12. Influence of diffusion on oil recovery factor.

Considering diffusion, part of the injected gas will diffuse into oil. Diffusion is caused by gas concentration differences. At the first stage of gas injection, the differences in gas saturation between matrix and fracture are large, causing a large amount of gas diffusing into the oil, extracting some hydrocarbon components, and resulting in mass transfer between two phases, thus producing more oil. **Fig. 12** shows that the oil recovery with diffusion is about 10% higher than that without diffusion in the first five cycles. With more cycles of gas injection, a further increase in oil recovery caused by diffusion was not observed. Therefore, from these simulated cases, it seems that diffusion did not play an important role as the pressure gradient in enhancing oil recovery.

3.3.3. Effect of soaking time

Gamadi et al. (2014b) conducted a series of experiments to test the effect of soaking time on oil recovery in cyclic CO₂ injection using Mancos and Eagle Ford core plugs. Yu et al. (2016) did a series of tests on investigating the effect of N₂ soaking time on huff-n-puff process in Eagle Ford core samples. In our study, we tested the soaking time effect on oil recovery with cyclic CH₄ injection in shale cores with two different core diameters, 1.5 and 4 inches under the same injection pressure, 2000 psi as shown in **Fig. 13** and **Fig.14**.

Fig. 13 shows the influence of soaking time on oil recovery for a core sample with diameter of 1.5 inches. It revealed that the incremental oil recovery was 6% when the soaking time was increased from 1 to 4 hrs and then only added about 2% when soaking time rose from 4 to 12 hrs. There was little difference when soaking time larger than 12 hrs. However, for the 4-inch diameter core sample in **Fig. 14**, when the soaking time was increased from 1 to 4 hrs, 4 to 12 hrs, and 12 to 24 hrs, the oil recovery was enhanced about 10%, 5%, and 2% respectively. There was hardly oil increase with extended soaking time, which means the pressure inside the matrix achieved equilibrium in the first 24 hrs' soaking time. This illustrates that there exists an optimum value of soaking time, and a further increase of it will hardly contribute to the improvement of oil recovery, but some time is lost for injection and production. Also, it reveals that the larger core sample needs a longer soaking time to allow pressure equilibrium inside the core to

achieve the maximized oil recovery in a single cycle. The results are in consistence with the conclusion of Gamadi et al. (2014b) or Yu et al. (2016) that in a single cycle without time limitation, the longer soaking time will result in a higher oil recovery. However, in the field scale production, people pursue the maximum oil recovery in a fixed operation time. Thus the effect of soaking time in the same operation period was discussed in the following part.

Fig. 13. Effect of soaking time on oil recovery factor (Core diameter = 1.5 inches).

Fig. 14. Effect of soaking time on oil recovery factor (Core diameter = 4 inches).

3.3.4. Effect of operation schedule

There always exists a balance of soaking time and injection cycles in a given operation time. In order to get the maximum economic benefit (the maximum oil recovery) in a fixed operation period, we choose three operation schedules in an operation time of 8 days (excluding the saturation time of 3 days) shown in **Table 8**. The results of different operation schedules are displayed in **Fig. 15**. The CH₄ injection pressure was kept at 2000 psi, injection time and production time were fixed at 0.01 days (0.24 hrs). The soak period and further depletion time were also kept at the same value. There are 22, 8 and 4 cycles in the operation period for No. 3, No. 2 and No. 1 operation schedules, respectively. **Fig. 15** illustrates that the maximum oil recovery for these three schedules are 58.62%, 45.05%, and 29.52%, respectively. **Fig.**

16, Fig. 17 and Fig. 18 display the pressure changes of the three operation schedules in different injection cycles. So in a fixed period, a shorter soaking period leads to more injection/production cycles. Then the core sample can get re-pressurized in a short time and the system keeps at a higher pressure gradient driving oil from the center blocks to the fracture region, thus achieving a higher oil recovery. The result confirms that a shorter soaking time with more injection cycles led to a higher oil recovery comparing of using a longer soaking time with less injection cycles in a fixed operation period. This result is in good agreement with our previous study (Wan et al., 2013; Gamadi et al., 2014b; Sheng, 2015a; Yu et al., 2016) and proves that no matter which kind of injection gases, a shorter soaking period is preferable in a fixed operation time.

Table 8.

Operation schedule (Total 11 days including 3 days' saturation time and 8 days' operation period).

Operation Schedule	Saturation time (days)	Injection time (hrs)	Soaking period (hrs)	Production time (days)	Further depletion (hrs)	Total Injection Cycles	Oil Recovery Factor (%)
1	3	0.24	24	0.24	24	4	29.52
2	3	0.24	12	0.24	12	8	45.05
3	3	0.24	4	0.24	4	22	58.62

Fig. 15. Effect of operation schedule on oil recovery factor (Core diameter = 1.5 inches).

Fig. 16. Pressure change in every injection cycle for operation schedule 1 (Core diameter = 1.5 inches).

Fig. 17. Pressure change in every injection cycle for operation schedule 2 (Core diameter = 1.5 inches).

Fig. 18. Pressure change in every injection cycle for operation schedule 3 (Core diameter = 1.5 inches).

This paper provides an insight on the fundamentals of CH_4 cyclic injection in shale reservoirs. In this study, the lab scale experiments were conducted to check the feasibility of cyclic gas injection and a multiple component model is built to test the effects of different parameters on oil recovery in the lab scale. Through this study, the CH_4 huff-n-puff is proved to be an effective EOR method in shale oil cores. From the experiment results on 6 cores with different diameters, it is found that under the same operation condition or schedule, a larger scale will result in a lower oil recovery. In a subsequent study, the application of cyclic gas injection from the lab scale to the field model becomes our focus. After examining the literature information to upscale spontaneous imbibition, we will derive dimensionless variable groups which govern the displacement of oil in reservoirs by gas and generate an upscale equation or a single curve which can describe the relationship of oil recovery versus dimensionless time for cyclic gas injection in different scales. Thus, the result of a lab study can be converted to the result of a field scale. The operation parameters for the field scale such as injection time and production time will be investigated.

4. Conclusion

Cyclic CH_4 injection in different-diameter cores was investigated using experimental and numerical methods in this paper. Crude oil and shale core samples from the Wolfcamp formation were used. Different operation parameters were analyzed in detail to investigate their effects on shale oil EOR using cyclic CH_4 injection. From the analysis, the following conclusions may be drawn.

1. Oil in the peripheral area (blocks) was first produced owing to the convection and dispersion. As the oil in the center grid blocks (which was produced in the latter cycles) has relatively lower pressure gradient and lower oil saturation gradient than that in peripheral grid blocks, the incremental oil recovery from a single cycle decreased as the cycle number increased.

2. The core with a smaller diameter has a relatively bigger surface area per unit volume and a higher pressure gradient during production when the injection pressure is the same for the cores of different diameters. A larger core had a lower oil recovery than a smaller core corresponding to the same sequence of the cycle.
3. In a fixed operation period, a shorter soaking period will re-pressurize core more frequently and maintain higher pressure gradients to achieve a higher oil recovery. However, when considering the recovery in a single huff-n-puff cycle with no time limitation, there exists an optimum soaking time. Further increasing soaking time may not significantly contribute to the improvement of oil recovery. A larger core sample needs a longer soaking time to maximize oil recovery in a single cycle.
4. By comparing the oil recovery factors from the simulated cases with and without diffusion, the molecular diffusion only affects the first five injection cycles and does not play an important role as that of pressure gradient in enhancing oil recovery.

Acknowledgments

Crude oil and cores were provided by Apache Corporation. The work presented in this paper is supported by the Department of Energy under Award Number DE-FE0024311. The authors are grateful to Dr. Kaz Surowiec in the Department of Chemistry, Texas Tech University to let us use their GC/MS instrument.

References

- Al-Thamir, W. K. 1985. Determination of Composition of Reservoir Crude Oils By GC-PVT Combination Techniques. SPE 15337.
- CMG Manual. 2014. Parameters for Computing Viscosity of Hydrocarbon Fluids. GEM, Compositional & Unconventional Reservoir Simulator Version, PP. 429-432.
- Denoyelle, L.C., Lemonnier, P., 1987. Simulation of CO₂ Huff 'n' Puff Using Relative Permeability Hysteresis. Paper SPE 16710 presented at the SPE Annual Technical Conference and Exhibition, Dallas, Texas, USA, 27-30 September.
- Eshiet E. R., Zhu, J., Anderson, T. A. and Smith, E.E. 2014. Chemical Characterization of *Brickellia Cavanillesii* (Asteraceae) Using Gas Chromatographic Methods. *Food Science & Nutrition* **2** (2): 105-113.
- Gamadi, T.D., Sheng, J.J. and Soliman, M.Y., 2013. An Experimental Study of Cyclic Gas Injection to Improve Shale Oil Recovery. Paper SPE 166334 presented at the SPE Annual Technical Conference and Exhibition, New Orleans, Louisiana, USA, 30 September - 2 October.
- Gamadi, T.D., Sheng, J.J., Soliman, M.Y., Menouar, H., Watson, M.C. and Emadibaladehi, H. 2014a. An Experimental Study of Cyclic CO₂ Injection to Improve Shale Oil Recovery. Paper SPE 169142 presented at the SPE Improved Oil Recovery Symposium, Tulsa, Oklahoma, USA, 12-16 April.
- Gamadi, T.D., Elldakli, F., Sheng, J.J., 2014b. Compositional Simulation Evaluation of EOR Potential in Shale Oil Recovery by Cyclic Natural Gas Injection. Paper SPE 1922690 (URTeC 1922690) presented at the Unconventional Resources Technology Conference, Denver, Colorado, USA, 25-27 August.

- Haines, H.K., Monger, T.G., 1990. A Laboratory Study of Natural Gas Huff-n-Puff. Paper SPE 21576 presented at the CIM/SPE International Technical Meeting, Calgary, Alberta, Canada, 10-13 June.
- Halket, J.M., Waterman, D., Przyborowska, A.M., Patel, R.K.P., Fraser, P.D., and Bramley, P.M. 2005. Chemical Derivatization and Mass Spectral Libraries in Metabolic Profiling by GC/MS and LC/MS/MS. *Journal of Experimental Botany* **56** (410): 219-243.
- Hiller, K., Hangebrauk, J., Jäger, C., Spura, J., Schreiber, K. and Schomburg, D. 2009. Metabolite Detector: Comprehensive Analysis Tool for Targeted and Nontargeted GC/MS Based Metabolome Analysis. *Analytical Chemistry* **81** (9): 3429-3439.
- Hong, K.C. 1982. Lumped-Component Characterization of Crude Oils for Compositional Simulation. Paper SPE 10691 presented at SPE Enhanced Oil Recovery Symposium, Tulsa, Oklahoma, USA, 4-7 April.
- Hsu, H. H. and Brugman, R. J. 1986. CO₂ Huff-n-Puff Simulation Using a Compositional Reservoir Simulator. Paper SPE 15503 presented at the 61st Annual Technical Conference and Exhibition, New Orleans, Louisiana, USA, 5-8 October.
- Ivory, J., Chang, J., Coates, R. and Forshner, K. 2010. Investigation of Cyclic Solvent Injection Process for Heavy Oil Recovery. *Journal of Canadian Petroleum Technology* **49** (9): 22-33.
- Li, L., Sheng, J. J. 2016. Experimental study of core size effect on CH₄ huff-n-puff enhanced oil recovery in liquid-rich shale reservoirs. *Journal of Natural Gas Science and Engineering*, 34, 1392-1402.
- Li, L., Sheng, J. J., Sheng, J. 2016. Optimization of Huff-n-Puff Gas Injection to Enhance Oil Recovery in Shale Reservoirs. SPE 180219 presented at SPE Low Perm Symposium held in Denver, Colorado, USA, 5-6 May.
- Li, L., Sheng, J.J., Watson, M., Mody, F. 2015. Experimental and Numerical Upscale Study of Cyclic Methane Injection to Enhance Shale Oil Recovery. AICHE 425710 in AICHE Annual Conference, Salt Lake City, Utah, 8-13 November.
- Liu, H., Wang, M. C., Zhou, X. and Zhang, Y.P. 2005. EOS Simulation for CO₂ Huff-n-Puff Process. Paper PETSOC2005-120 presented at Petroleum Society's 6th Canadian International Petroleum Conference, Calgary, Alberta, 7-9 June.
- Meng, X. and Sheng, J.J. 2016. Experimental and Numerical Study of Huff-n-Puff Gas Injection to Revaporize Liquid Dropout in Shale Gas Condensate Reservoirs, *J. of Natural Gas Science and Engineering*, 35, 444-454.
- Meng, X., Sheng, J.J., and Yu, Y. 2016. Experimental and Numerical Study on Enhanced Condensate Recovery by Huff-n-Puff Gas Injection in Shale Gas Condensate Reservoirs, *SPE Reservoir Evaluation & Engineering*, in press.
- Monger, T. G., and Coma, J. M. 1988. A Laboratory and Field Evaluation of the CO₂ Huff 'n' Puff Process for Light-Oil Recovery. *SPERE* **3**(04): 1168-1176.

- Rubiolo, P., Liberto, E., Sgorbini, B., Russo, R., Veuthey, J.L., and Bicchi, C. 2008. Fast-GC-conventional Quadrupole Mass Spectrometry in Essential Oil Analysis. *Journal of Separation Science* **31** (6-7): 1074-1084.
- Shayegi, S., Jin, Z., Schenewerk, P., and Wolcott, J. 1996. Improved Cyclic Stimulation Using Gas Mixtures. Paper SPE 36687 presented at the SPE Annual Technical Conference and Exhibition, Denver, Colorado, USA, 6-9 October.
- Sheng, J. J. 2015a. Enhanced oil recovery in shale reservoirs by gas injection. *Journal of Natural Gas Science and Engineering*, 22, 252-259.
- Sheng, J.J. 2015b. Increase liquid oil production by huff-n-puff of produced gas in shale gas condensate reservoirs, *Journal of Unconventional Oil and Gas Resources*, 11, 19-26.
- Wan, T., Sheng, J.J., Soliman, M.Y. 2013. Evaluation of the EOR Potential in Shale Oil Reservoirs by Cyclic Gas Injection. Paper SPWLA-d-12-00119 presented at the SPWLA 54th Annual Logging Symposium Held in New Orleans, Louisiana, USA, 22-26 June.
- Wan, T., Sheng, J., Soliman, M. Y., and Zhang, Y. 2016. Effect of Fracture Characteristics on Behavior of Fractured Shale-Oil Reservoirs by Cyclic Gas Injection, *SPEREE*, May, 350-355, doi:10.2118/168880-PA
- Wan, T. and Sheng, J.J. 2015a. Enhanced Recovery of Crude Oil from Shale Formations by Gas Injection in Zipper-Fractured Horizontal Wells, *Petroleum Science and Technology*, 33(17-18), 1605-1610.
- Wan, T. and Sheng, J.J. 2015b. Evaluation of the EOR Potential in Hydraulically Fractured Shale Oil Reservoirs by Cyclic Gas Injection, *Petroleum Science and Technology*, 33(7), 812–818.
- Wan, T. and Sheng, J.J. 2015c. Compositional Modelling of the Diffusion Effect on EOR Process in Fractured Shale-Oil Reservoirs by Gas flooding, *JCPT*, 54(2), 107-115.
- Wan, T., Yu, Y., and Sheng, J.J. 2015. Experimental and numerical study of the EOR potential in liquid-rich shales by cyclic gas injection, *Journal of Unconventional Oil and Gas Resources*, 12, 56-67.
- Wang, Z., Ma, J., Gao, R., Zeng, F., Huang, C., Tontiwachwuthikul, P. and Liang, Z. 2013. Optimizing Cyclic CO₂ Injection for Low - permeability Oil Reservoirs through Experimental Study. Paper SPE 167193 at the SPE Unconventional Resources Conference, Calgary, Alberta, Canada, 5–7 November 2013.
- Yu, W., Al-Shalabi, E.W., Sepehrnoori, K. 2014b. A Sensitivity Study of Potential CO₂ Injection for Enhanced Gas Recovery in Barnett Shale Reservoirs. Paper SPE 169012 presented at the SPE Unconventional Resources Conference, Woodlands, Texas, USA, 1-3 April.
- Yu, W., Lashgari, H., Sepehrnoori, K. 2014a. Simulation Study of CO₂ Huff-n-Puff Process in Bakken Tight Oil Reservoirs. Paper SPE 169575 presented at the SPE Western North American and Rocky Mountain Joint Meeting, Denver, Colorado, USA, 17-18 April.

- Yu, Y., Li, L., and Sheng, J.J. 2016. Further Discuss the Roles of Soaking Time and Pressure Depletion Rate in Gas Huff-n-Puff Process in Fractured Liquid-rich Shale Reservoirs. Prepared for the SPE Annual Technical Conference and Exhibition, Dubai, UAE, 26-28 September. SPE-181471-MS.
- Yuan, B., Wood, D.A. 2015. Production Analysis and Performance Forecasting for Natural Gas Reservoirs: Theory and Practice (2011-2015), Journal of Natural Gas Science and Engineering, Volume 26, September 2015, Pages 1433-1438.
- Zhang, Y. P., Sayegh, S. G., Huang, S. and Dong, M. 2006. Laboratory Investigation of Enhanced Light-Oil Recovery By CO₂/Flue Gas Huff-n-Puff Process. Journal of Canadian Petroleum Technology **45** (2): 24-32.